

103. Binary Tree Zigzag Level Order Traversal

[Description \(?tab=Description\)](#)[Submission \(?tab=Submission\)](#)[Solutions \(?tab=Solutions\)](#)[Add to List \(?tab=List\)](#)Total Accepted: **88118** Total Submissions: **269738** Difficulty: **Medium** Contributors: **Admin**

Notes

Given a binary tree, return the *zigzag level order* traversal of its nodes' values. (ie, from left to right, then right to left for the next level and alternate between).

For example:

Given binary tree [3,9,20,null,null,15,7] ,

```
  3
 / \
9   20
 / \
15  7
```

return its zigzag level order traversal as:

```
[
  [3],
  [20,9],
  [15,7]
]
```

Subscribe (/subscribe/) to see which companies asked this question.

[Show Tags](#)[Show Similar Problems](#)

Have you met this question in a real interview?

[Discuss \(https://discuss.leetcode.com/category/111\)](https://discuss.leetcode.com/category/111)[Pick One \(/problems/random-one-question/\)](/problems/random-one-question/)[Editorial Solution](#)

Python



```
1 # Definition for a binary tree node.
2 # class TreeNode(object):
3 #     def __init__(self, x):
4 #         self.val = x
5 #         self.left = None
6 #         self.right = None
7
8 class Solution(object):
9     def zigzagLevelOrder(self, root):
10         """
11         :type root: TreeNode
12         :rtype: List[List[int]]
13         """
14         def bfs(root):
15             d=[]#d is a list
16             i=0
17             thislevel=[root]
18             while thislevel:
19                 d.append([]) #add a new list to d for a new level
20                 for node in thislevel:
21                     d[i].append(node.val)
22                 if i%2==1:
23                     d[i]=d[i][::-1]
24                 nextlevel=[]
25                 for node in thislevel:
26                     if node.left:
27                         nextlevel.append(node.left)
28                     if node.right:
29                         nextlevel.append(node.right)
30                 i=i+1
31                 thislevel=nextlevel
32             return d
33         if root:
34             d=bfs(root)
35             return d
36         return []
```

[✉ Send Feedback \(mailto:admin@leetcode.com?subject=Feedback\)](mailto:admin@leetcode.com?subject=Feedback)

[Custom Testcase](#) [Contribute Testcase](#) [Run Code](#)[Submit Solution](#)

Run Code Status: Finished

Run Code Result:

 Notes

Your input

`[3,9,20,null,null,15,7]`

Your answer

`[[3],[20,9],[15,7]]`

Expected answer

`[[3],[20,9],[15,7]]`[Show Diff](#)

Runtime: 42 ms

Note: is Run Code inconsistent with Submit Solution? If you are using global variables or C/C++, check this ([/faq/#different-output](#)) out.[Frequently Asked Questions \(/faq/\)](#) | [Terms of Service \(/tos/\)](#)[Privacy](#)

Copyright © 2017 LeetCode

 [Send Feedback \(mailto:admin@leetcode.com?subject=Feedback\)](mailto:admin@leetcode.com?subject=Feedback)