



01.01.2024

Quality Specification of release waste paper for Cycle4green recycling

Release waste paper is collected for use in recycled paper products. In recycling process release waste paper needs to conform to the specification outlined in this document.

Pallets prepared for transport need to be exceed the minimum weight and be packed in secure way according to the specification outlined in this document.

1. Material Quality

Release waste paper (label backing papier) needs to be sorted to meet the material quality specification as shown in APP 1.

2. Packaging Quality

Minimum weight for one (1) pallet: 480 Kg.

Pallets may consist of material packed into (carton) containers, big bags or pressed bales.

Pallets prepared for transport need to be secured by stretch-wrapping and/or pallet strapping as shown in APP 2.

Secured full pallets can be stacked in warehouse conditions. Pallets need to be **stored indoors** in dry conditions. Loading in trucks must be done **in single-layer** only unless specifically otherwise agreed.

Inspection

All shipments will be inspected at point of unloading at recycling plant. When deviation from Delivery Specification and/or rejection of material occurs will be the customer/waste supplier informed within 5 working days.

Damage

In case where rejection of material leads to manual re-sorting holds Cycle4green Ltd. the right to charge 60 euro/ton of waste in order to cover the additional waste management costs generated by re-sorting.

In case complete delivery is rejected due to non-specified material(s) costs of transport and disposal will be charged.



Specification of release waste paper for C4G recycling - Material

APP. 1 (1/2)

Sorted material – **accepted quality**



Contamination – **NOT accepted quality**

Labels



Labels



Fully black printed paper



Label rolls



Labelrolls



PET / films / plastics



Carton cores



Cartons / Card board



**Specification of release waste paper for C4G recycling- Material****APP. 1 (2/2)**

Release waste paper needs to be sorted and the contaminants listed below removed.

Contaminants and their tolerance limits

Type of contamination	Description	Rejection limit
1. Labels, label stock materials	Laminates with adhesives -long strips of labels -rest rolls with labels -laminate trims -tape materials	Labels not accepted; <i>Tapes/labels are accepted when used e.g. joining label web (1-2 pc/roll)</i>
2. Plastics, filmic label materials	All plastic materials	Any quantity of plastic materials
3. Black printed backing paper	fully printed paper with black ink printing	Labels not accepted; only single pieces of black material accepted
4. Extrusion coated papers	Papers coated with PE-coating or similar	Any quantity of plastic materials
5. Wet strength papers	Paper with high water resistance by using wet-strength resins	not accepted
6. Waxy papers	Papers impregnated with waxy materials, e.g. baking papers	not accepted
7. Thermal papers	Papers with thermal coatings, e.g. fax papers	not accepted
8. Wood containing papers	e.g. printed magazine papers	not accepted
9. Carton board	Brown carton board	Any quantity of carton materials
10. Metallized papers		Any quantity of metal materials



Specification of release waste paper for C4G recycling – Packaging

APP. 2 (1/1)

- 1) Loose liner material (paper strips, sheet etc.) cannot be packed into containers due to low weight. Loose waste needs compacting by shredding or pressing into industrial bales.
- 2) Pallets need to be secured by stretch-wrapping and/or pallet strapping.
- 3) Pallets with carton containers need to be stored indoors in dry conditions.
- 4) Only wood pallets in good condition can be used. One-way and/or EUR/EPAL-pallets are accepted.

