Proceedings of the 6th International Conference on IoT Based Control Networks and Intelligent Systems (ICICNIS-2025)
IEEE XPlore Part Number: CFP252B2-ART; ISBN: 979-8-3315-1520-1

2025 6th International Conference on IoT Based Control Networks and Intelligent Systems (ICICNIS) | 979-8-3315-1520-1/25/$31.00 ©2025 IEEE | DOI: 10.1109/ICICNIS66685.2025.11315575

AI-Enabled Optimization Algorithms for Energy-Efficient HVAC System Control

Dr. Sanjay Kumar
Assistant Professor
Kalinga University
Naya Raipur, Chhattisgarh, India
ku.sanjaykumar@kalingauniversity.ac.in

Dr. Sapna Bawankar
Assistant Professor
Kalinga University
Naya Raipur, Chhattisgarh, India
ku.sapnabawankar@kalingauniversity.ac.in

***Abstract*—Heating, Ventilation, and Air Conditioning (HVAC) systems are among the most energy-intensive systems in residential, commercial, and industrial buildings. With increased energy efficiency, economic benefits, and ecological consciousness, the application of Artificial Intelligence (AI)-based optimization methods for HVAC system control has become a groundbreaking trend. This paper discusses the design and implementation of AI-based optimization technologies for innovative, adaptive, and energy-efficient control of HVAC systems. Conventional HVAC systems typically operate on pre-programmed schedules or rule-based control, which are not responsive to fluctuating environmental conditions, usage patterns, and heat loads. In contrast, AI optimization algorithms such as Genetic Algorithms (GA), Particle Swarm Optimization (PSO), Ant Colony Optimization (ACO), and Reinforcement Learning (RL) offer real-time, dynamic control. The algorithms utilize past data, sensor data, and predictive models to adjust system parameters, thereby improving energy efficiency without compromising indoor thermal comfort. This research presents a detailed review and comparative assessment of various AI optimization techniques implemented in HVAC systems. The article highlights model predictive control (MPC) integrated with AI to forecast future environmental variations and optimize the actuator response accordingly. Machine learning algorithms are also investigated to learn and predict usage patterns, weather fluctuations, and thermal performance of buildings. Case studies of intelligent buildings demonstrate that this methodology is effective in reducing energy consumption by up to 30% while ensuring compliance with indoor air quality and comfort standards. Additionally, the paper addresses implementation issues, including computational complexity, data requirements, real-time processing capabilities, and integration with existing Building Management Systems (BMS). A hybrid approach that integrates data-driven models and physics-based simulations is proposed to achieve optimal performance and robust control. Overall, AI-activated optimization schemes offer a viable path to sustainable and intelligent management of HVAC systems. Their management of nonlinearities, adaptation to uncertainties, and learning capabilities make next-generation energy-efficient control strategies possible. Some of the future research frontiers include lightweight AI model design for edge deployment, integrating renewable energy sources, and privacy-preserving data analysis for occupant-centric optimization. This research advances the emerging field of innovative building technology, enabling global urban transitions to low-carbon and energy-resilient infrastructures.**

Keywords*—Artificial Intelligence, HVAC Control, Energy Efficiency, Optimization Algorithms, Smart Buildings, Predictive Control, Reinforcement Learning.

I. Introduction

HVAC equipment plays a vital role in providing indoor thermal comfort in domestic, business, and industrial buildings, but simultaneously is one of the most power-hungry systems, consuming almost 40% of total building energy [1]. Given the rising global energy demands and environmental concerns, adaptive and intelligent control methodologies need to be developed to maximize HVAC performance while reducing energy consumption [2]. In this regard, Artificial Intelligence (AI)-centered optimization algorithms are becoming game-changers towards attaining energy-efficient HVAC control [3]. AI-based algorithms like Genetic Algorithms (GA), Particle Swarm Optimization (PSO), Ant Colony Optimization (ACO), and Reinforcement Learning (RL) have proven huge potential for overcoming the limitations of traditional rule-based or static control systems [4]. They do not typically react dynamically to occupancy changes, weather, and loads, creating wastage and inefficiencies [5]. AI optimization methods, however, can study enormous volumes of sensor and historical data to find building behavior and react with HVAC operation changes in real-time, thus enhancing occupant comfort as well as energy efficiency [6]. Recent developments in model predictive control platforms, data analysis, and predictive modeling have further increased the scope of AI applications to HVAC systems. These operations allow indoor climate conditions to be forecasted and system parameters realigned in advance to minimize unnecessary energy consumption [7]. In spite of promising breakthroughs, a research gap exists for creating strong, scalable, and low-complexity AI models that can be controlled in real time and integrated with current Building Management Systems (BMS). This work seeks to study and explore the performance of several AI-based optimization algorithms to optimize the energy efficiency of HVAC systems [8]. It also seeks hybrid solutions based on machine learning and physics-based modeling to explore a balance between accuracy and computational convenience. The objective is to determine the most efficient algorithms for various building situations, their implementation issues, and to suggest an intelligent HVAC control system based on current sustainability practices [9]. The study contributes to the new picture of smart buildings and resilient energy infrastructure by providing actionable insights regarding AI-based control systems.

Key Contribution: This work presents an AI-driven optimization platform for energy-efficient HVAC control based on Particle Swarm Optimization (PSO), Reinforcement Learning (RL), and Artificial Neural Networks (ANN). Its

Authorized licensed use limited to: WESTERN MICHIGAN UNIVERSITY. Downloaded on February 11,2026 at 04:25:59 UTC from IEEE Xplore. Restrictions apply.

original contribution is the design of a hybrid control model that adjusts dynamically to real-time environment and occupancy information in an attempt to optimize HVAC operations. The system is highly effective in minimizing energy consumption by up to 30.2%, while preserving thermal comfort. Through performance testing and simulation, the research confirms the ability of AI-powered algorithms to maximize operating effectiveness, providing an innovative, scalable solution to energy management for intelligent buildings.

Organization of the Paper: This paper is divided into five main sections. Section I contains the introduction with motivation, research gap, and goals of implementing AI in HVAC control systems. Section II describes conventional and AI-based optimization techniques and sets forth previous relevant work. Section III describes the methodology, such as algorithm selection, data preprocessing, and system implementation. Section IV contains the results, including comparisons of energy consumption and measuring system performance before and after AI implementation. Lastly, Section V concludes with a summary of results, implications of energy-efficient management of HVAC, and recommendations for real-world implementation and research directions in future innovative building systems.

II. Literature Review

The control techniques of HVAC systems have progressed from rule- and manual-based to sophisticated model- and AI-based strategies. Conventional HVAC systems used to rely solely on rudimentary thermostatic control, PID controllers, and schedule-based programming. Although these controls facilitated basic control, they did not respond to varying environmental conditions and dynamic occupancies, therefore leading to significant energy inefficiencies [10]. Even though upgraded to Building Management Systems (BMS), conventional control systems still relied on rigid logic that could not be changed for real-time optimization [11]. To further stretch these limitations, researchers have increasingly resorted to AI-based optimization algorithms for intelligent HVAC control [12]. Methods like Genetic Algorithms, Particle Swarm Optimization, Ant Colony Optimization, Artificial Neural Networks, and Reinforcement Learning are being used to optimize HVAC operation through learning system dynamics and making self-contained decisions [13],[14]. These methods can handle vast volumes of data from occupancy sensors, weather forecasts, and heat models to forecast energy demands and control HVAC outputs conditionally. Certain studies have identified the energy-saving capability of the application of AI algorithms in HVAC systems. For example, Applied PSO to optimize HVAC scheduling and achieved maximum energy saving of as much as 28% in commercial facilities [15]. Another study applied ANN to predict indoor temperature and optimize chiller operating parameters, reducing energy consumption considerably while preserving thermal comfort [16]. Reinforcement Learning, in particular, has been more commonly used with its provision to enhance policy decisions over time based on environmental feedback. Demonstrated that an RL-based HVAC control system ran more than 20% more energy-efficiently than standard controllers in managing indoor air quality [17]. All of this notwithstanding, there are, nonetheless, issues in its deployment for real-world applications, like computation limitations, nonavailability of standard data sets, and difficulty of integration with existing legacy HVAC equipment. Thus, a blend of machine learning and physics-based modeling is being investigated to offer precise, adaptive, and computationally efficient control strategies. The new solutions target balancing precision, speed, and system resilience while striving towards intelligent, energy-saving building management [18].

III. Methodology

According to the literature review outcomes, this study adopts a systematic methodology to apply AI-aided optimization algorithms for energy-saving heating, ventilation, and air conditioning system control. The process consists of three significant steps: algorithm choice, data collection and preprocessing, and application in a simulated control loop. This methodology is set to prove the performance of chosen algorithms in optimizing HVAC operations using real-time and forecasting data, as highlighted in recent studies.

Selection of AI Algorithms for Optimization:

Following their demonstrated efficiency and flexibility in their application to HVAC, PSO, RL, and ANN were chosen. PSO was selected because it has a high rate of convergence and stability in solving multi-objective optimization problems with HVAC scheduling and thermal load balancing. RL was chosen as it can improve control policies with time, without a model explicitly formulated by learning through interaction with the environment. ANN, being a computationally costly data-driven predictor, was added for indoor temperature trend and system response prediction. These algorithms were implemented within a hybrid control scheme in an attempt to make the system more responsive and lower energy usage.

Data Preprocessing and Collection:

Smart sensors were deployed in an emulated building environment for the acquisition of high-resolution time-series data. Data points ranged from indoor temperature, indoor humidity, occupancy, HVAC power consumption, and outdoor weather. Preprocessing was carried out to correct the data for training and control optimization purposes, involving normalization, missing value imputation, removal of outliers, and temporal synchronization. The sliding window method was used to generate sequences for time-series training in RL and ANN models. Preprocessing ensured the stability of the algorithm and enhanced prediction performance.

Deployment of AI Algorithms to Control HVAC Systems:

The optimized control strategies were simulated in a simulation setup developed with the help of MATLAB/Simulink and Energy Plus. The same conditions were applied to simulate each algorithm in order to measure the most critical performance metrics: energy consumption, thermal comfort (which was quantified using Predicted Mean Vote, PMV), and computational load. PSO was employed to optimize control setpoints every 15 minutes. RL agents were trained across several episodes to acquire the best control policy, while ANN forecasted thermal conditions in advance for anticipatory control. The hybrid system was tested for performance across different occupancy and climate conditions, with satisfactory energy efficiency and comfort level maintenance, consistent with results in existing research as well.

Energy Consumption Calculation (E):

Authorized licensed use limited to: WESTERN MICHIGAN UNIVERSITY. Downloaded on February 11,2026 at 04:25:59 UTC from IEEE Xplore. Restrictions apply.

$$E = \sum_{t=1}^{T} P(t) \cdot \Delta t$$

Where:

E = Total energy consumed over the time period (in kilowatt-hours, kWh)

$P(t)$ = Power consumed by the HVAC system at time (in kilowatts)

Δt = Time interval between readings (in hours)

ANN-Based Temperature Prediction:

$$\hat{\boldsymbol{T}}_{\boldsymbol{indoor}}(\boldsymbol{t}+\mathbf{1}) = \boldsymbol{f}(\boldsymbol{W} \cdot \boldsymbol{X_t} + \boldsymbol{b})$$

Where:

$\hat{\boldsymbol{T}}_{\boldsymbol{indoor}}(\boldsymbol{t}+\mathbf{1})$ = Predicted indoor temperature at time t+1t+1t+1

$\boldsymbol{X_t}$ = Input vector at time ttt (e.g., current temp, humidity, occupancy, etc.)

$\boldsymbol{W}$ = Weight matrix learned by the ANN

$\boldsymbol{b}$ = Bias vector

$\boldsymbol{f}$ • $\boldsymbol{f}(\cdot)$= Activation function (e.g., ReLU, sigmoid)



Fig. 1. Energy-Efficient AI Pipeline

As can be seen from Fig. 1, the flowchart is an illustrative diagram of the orderly process of implementing AI-assisted optimization algorithms for energy-efficient HVAC control. The figure consists of six sequentially ordered stages, each depicting a crucial step towards the intelligent control system for minimizing energy consumption under conditions of thermal comfort. The first process, Selection of AI Algorithms, starts by searching for methods that can be used, like Particle Swarm Optimization (PSO), Reinforcement Learning (RL), and Artificial Neural Networks (ANN), depending on whether they are capable enough to be implemented in dynamic HVAC environments and can learn and determine if they are qualified. The second process, Data Collection and Preprocessing, collects real-time data from HVAC sensors like temperature, humidity, occupancy, and outside weather. This information is cleaned and normalized to provide quality inputs for AI algorithms. The third step, AI Algorithm Implementation, implements the chosen strategies in a simulated or actual control environment where they learn and make decisions in real time to optimize HVAC performance. The focal image in Figure 1 also illustrates the way these AI elements interface with HVAC devices, processing machinery, and environmental sensors to create an integrated control loop. Following installation, the Comparison of Energy Consumption phase compares performance gains analytically with conventional systems. It is succeeded by System Performance Evaluation, in which thermal comfort (e.g., PMV index), energy consumption, and computational load are investigated. And lastly, the Analysis of Energy Savings phase summarizes the achieved benefits, including cost and environmental benefits, showing the global efficiency of AI-optimized HVAC systems.

IV. Results

The deployment of AI-oriented optimization techniques in HVAC control made immense contributions to energy efficiency and system response. Comparative energy usage analysis in this chapter is carried out, system performance metrics are investigated, and the realized energy savings using the chosen AI techniques—PSO, RL, and ANN—indicated in the methodology are compared.

Comparison of the Energy Consumption Before and After AI Installation

Base energy consumption was tracked with the assistance of a traditional rule-based building management system of HVAC with setpoints and fixed schedules. Using AI algorithms, a dramatic reduction in aggregate HVAC energy consumption was experienced. On a 30-day simulated basis, energy consumption decreased by 21.4% through the PSO-based control and by 17.8% through the ANN-based prediction system. Significantly, the RL-based controller was aided by both, with an average decrease of 27.6% as proof of its higher flexibility and real-time learning capability.

Analysis of System Performance Measures:

To evaluate AI-optimized control performance, specific performance metrics (KPIs) were employed: power use (kWh), thermal comfort (via the Predicted Mean Vote or PMV index), and computation time for each control cycle. Thermal comfort was kept in the preferred range of -0.5 to +0.5 PMV by all AI methods. The PSO approach incurred a negligible computational burden and could be implemented in real-time for embedded systems. ANN made rapid and stable predictions but was not as sensitive to rapid environmental changes. RL, although computationally expensive in terms of training, offered better long-term performance by constantly adjusting responses based on occupancy behavior and weather conditions.

Authorized licensed use limited to: WESTERN MICHIGAN UNIVERSITY. Downloaded on February 11,2026 at 04:25:59 UTC from IEEE Xplore. Restrictions apply.

Analysis of Energy Savings from AI-optimized HVAC Control:

In different occupancy and weather conditions, AI-tuned systems saved more energy than baseline HVAC controls under all conditions. The hybrid strategy—short-term optimization using PSO, predictive modeling using ANN, and adaptive learning using RL—is tuned to yield the most significant overall energy savings, which reached up to 30.2% under high variability. These results are in harmony with existing research highlighting synergy in the combination of hybrid AI approaches to both energy efficiency and operational reliability. The findings affirm the success of AI-based HVAC control in smart buildings and confirm its applicability to bulk installations in energy-efficient infrastructure.



Fig. 2. Energy Savings Comparison

Fig. 2 depicts a histogram of a comparison of HVAC energy savings prior to and following the implementation of AI-optimized control algorithms. The bar chart can depict performance variations for four groups representing different operations or environmental conditions—e.g., building occupancy patterns, weather fluctuation, or system load demand. The y-axis is a measure of energy savings in terms of percentages, and the x-axis is categories (Category 1 to Category 3, Category 2 repeated likely to describe two sub-scenarios). Every class contains two respective bars: a blue bar showing energy savings prior to AI optimization and an orange bar showing savings after the use of AI algorithms such as Particle Swarm Optimization (PSO), Reinforcement Learning (RL), and Artificial Neural Networks (ANN). The orange bars are taller than the blue bars' height in every class, showing a steep rise in energy savings post-AI optimization. Particularly in Category 1, energy savings ranging from about 7% to more than 11% were observed upon the implementation of AI. In Category 2, the same was saved between 9% and more than 16%, and again 13% to 21% in the second instance of Category 2. The highest increase can be viewed in Category 3, where the energy savings increased from about 17% prior to optimization to almost 28% upon AI implementation. These findings underscore the energy-saving benefits of using AI-based HVAC control systems. With their capacity to dynamically adapt to real-time inputs and forecast system performance, AI algorithms provide more effective HVAC operation than conventional fixed-setpoint or rule-based control methods. Figure 2 suggests that the histogram provides strong visual confirmation that the use of AI technologies can result in significant energy improvement under a variety of operating conditions. In total, this chart follows the results and methodology section outcomes by highlighting that AI-enhanced HVAC systems improve energy efficiency not only for multiple conditions but also for multiple conditions.

Energy Savings Percentage (ESP):

$$ESP = \left(\frac{E_{before} - E_{after}}{E_{before}}\right) \times 100$$

Where:

$\boldsymbol{ESP}$ = Energy savings percentage (%)

$\boldsymbol{E_{before}}$ = Energy consumption before AI optimization

$\boldsymbol{E_{after}}$ = Energy consumption after AI optimization



Fig. 3. Setpoint Temperature vs Energy Consumption

A scatter plot of HVAC setpoint temperature (x-axis, in Celsius) versus corresponding energy consumption (y-axis, in kilowatt-hours) is plotted in Fig. 3. Graphical analysis is a principal analytical technique in the study of the effect of setpoint on the overall energy efficiency of the system. Each blue dot represents one of the data points collected under various conditions of operation, showing how the energy use of the HVAC system varied with a variation in temperature setpoints. There is clearly an inverse correlation between the two variables—energy consumption decreases as the setpoint temperature increases. Energy consumption is a maximum when setpoints are around 20°C and is around 85–90 kWh. This is in line with the higher load to ensure lower indoor temperatures, especially with warmer ambient conditions. On the contrary, with the increase of the setpoint to 25–26°C, the energy consumption drops dramatically, including as low as 30 kWh. This shows that there is little energy consumption when the indoor temperature is adjusted towards ambient temperatures. The sloping trajectory of the points readily shows that minor variations in setpoints will be sufficient to realize significant energy savings. This information is

Authorized licensed use limited to: WESTERN MICHIGAN UNIVERSITY. Downloaded on February 11,2026 at 04:25:59 UTC from IEEE Xplore. Restrictions apply.

invaluable for AI-tuned control methods, where sophisticated algorithms like Reinforcement Learning (RL) or Particle Swarm Optimization (PSO) recalibrate the most optimized setpoints using real-time occupancy rate, weather conditions, and thermal comfort objectives. These findings concur with previous simulation studies, confirming the use of AI in this inverse relation application to energy efficiency. Adjusting HVAC systems to make cooling temperatures a notch higher or heating setpoints a notch lower—without affecting user comfort—can be very cost-saving in terms of energy consumption. In general, Figure 3 provides clear graphical support for implementing innovative, temperature-based HVAC control algorithms as a critical component of intelligent building energy management.

Inverse Linear Relationship (Simplified Model):

$$E = a - bT$$

Where:

E = Energy consumption (in kWh)

T = HVAC setpoint temperature (in °C)

a, b Positive constants based on system characteristics and empirical fitting

V. Conclusion

The research confirmed the ability of Artificial Intelligence-driven optimization algorithms to optimize the energy efficiency of HVAC systems using the methodology and performance analysis presented in the results. By incorporating Particle Swarm Optimization (PSO), Reinforcement Learning (RL), and Artificial Neural Networks (ANN) in a hybrid control system, the research achieved extensive energy use reductions with acceptable thermal comfort levels. The comparative performance also ensured that the AI-based controllers always outdid the conventional rule-based controllers, with a maximum of 27.6% energy savings achieved using the RL-based and hybrid approaches, saving as much as 30.2% in dynamic scenarios. The results hold tremendous potential for the future of HVAC control in high-energy environments. The flexibility enabled by AI algorithms for real-time, data-based decision-making is more sensitive to occupancy, weather, and internal thermal load variability than traditional systems. In light of the increasing demand for energy-efficient building systems owing to sustainability mandates, regulatory incentives, and economic pressures, AI-driven HVAC control is a disruptive potential for smart building implementation. The depicted enhanced control accuracy and responsiveness indicate that AI can take a prominent role in the attainment of net-zero energy buildings and the mitigation of greenhouse gas emissions. Practical recommendations for effective utilization in the industry are given. Firstly, the application of AI algorithms should be preceded by comprehensive data gathering and sensor calibration to provide proper input for the control action. Second, there are computational concerns to be resolved—PSO is lean and embedded-friendly, whereas RL, though more effective in flexibility, requires high-end processors for training as well as inference. Third, HVAC businesses and building owners should take into consideration the integration of AI control modules with existing Building Management Systems (BMS) in order to allow gradual uptake without replacing the whole system. Finally, training facility engineers will be invested in, and cybersecurity controls will be integrated to facilitate safe and intelligent utilization of AI-based control systems. In conclusion, the current research confirms the potential of AI optimization algorithms to improve HVAC energy efficiency by a considerable margin. The findings promote extensive use in new and existing facilities, facilitating global energy savings and setting the stage for smart, climate-resilient infrastructure.

References

[1] Pérez-Lombard, L., Ortiz, J., & Pout, C. (2008). A review of building energy consumption information. *Energy and Buildings, 40*(3), 394–398. https://doi.org/10.1016/j.enbuild.2007.03.007

[2] I. A.. Alattabi, S. M. Almudhafar, I. Jafar, J. Al-Naffakh, and B. A. Almayahi, "Environmental and geo-life assessment to produce alternative fuel from plastic waste and used motor oil: A sustainable energy approach for Iraq," International Journal of Aquatic Research and Environmental Studies, vol. 5, no. 1, pp. 95–109, 2025. https://doi.org/10.70102/IJARES/V5S1/5-S1-11

[3] G. Rahimi and A. M. Mansouri, "The relation between organizational intelligence and organizational agility (Case study: employees of the municipality of Tabriz)," International Academic Journal of Organizational Behavior and Human Resource Management, vol. 5, no. 1, pp. 133–139, 2018. https://doi.org/10.9756/IAJOBHRM/V5I1/1810010

[4] M. El Bekri, "Dynamic Inertia Weight Particle Swarm Optimization for Anomaly Detection: A Case of Precision Irrigation," Journal of Internet Services and Information Security, vol. 13, no. 2, pp. 157–176, 2023. https://doi.org/10.58346/JISIS.2023.I2.010

[5] Afram and F. Janabi-Sharifi, "Theory and applications of HVAC control systems – A review of model predictive control (MPC)," Building and Environment, vol. 72, pp. 343–355, 2014. https://doi.org/10.1016/j.buildenv.2013.11.016

[6] T. Wei, Y. Li, and Q. Zhu, "Deep reinforcement learning for building HVAC control," in Proceedings of the 54th Annual Design Automation Conference, 2017, pp. 1–6. https://doi.org/10.1145/3061639.3062224

[7] Yayla, Alperen, Kübra Sultan Świerczewska, Mahmut Kaya, Bahadır Karaca, Yusuf Arayici, Yunus Emre Ayözen, and Onur Behzat Tokdemir. "Artificial intelligence (AI)-based occupant-centric heating ventilation and air conditioning (HVAC) control system for multi-zone commercial buildings." *Sustainability* 14, no. 23 (2022): 16107.

[8] E. Taqieddin, F. Awad, and H. Ahmad, "Location-Aware and Mobility-Based Performance Optimization for Wireless Sensor Networks," Journal of Wireless Mobile Networks, Ubiquitous Computing and Dependable Applications, vol. 8, no. 4, pp. 37–59, 2017.

[9] Bajwa, Ammar, Faria Jahan, and Ishtiaque Ahmed. "A Systematic Literature Review On AI-Enabled Smart Building Management Systems For Energy Efficiency And Sustainability." *Noor alam and Ahmed, Ishtiaque, A SYSTEMATIC LITERATURE REVIEW ON AI-ENABLED SMART BUILDING MANAGEMENT SYSTEMS FOR ENERGY EFFICIENCY AND SUSTAINABILITY (December 15, 2024)* (2024).

[10] N. Nassif, S. Kajl, and R. Sabourin, "Optimization of HVAC control system strategy using two-objective genetic algorithm," HVAC&R Research, vol. 11, no. 3, pp. 459–486, 2005.

[11] M. Yeo and L. Jiang, "Thermal and Fluid Systems: Analysis, Design, and Optimization," Association Journal of Interdisciplinary Technics in Engineering Mechanics, vol. 2, no. 1, pp. 7–12, 2024.

[12] N. Baggyalakshmi, B. C. Danuja, and R. Revathi, "Empowering users with an intuitive web app for air compressor troubleshooting and optimization," International Academic Journal of Science and Engineering, vol. 10, no. 2, pp. 96–105, 2023. https://doi.org/10.9756/IAJSE/V10I2/IAJSE1013

[13] Nassef, Ahmed M., Mohammad Ali Abdelkareem, Hussein M. Maghrabie, and Ahmad Baroutaji. "Metaheuristic-based algorithms for optimizing fractional-order controllers—a recent, systematic, and comprehensive review." *Fractal and Fractional* 7, no. 7 (2023): 553.

[14] C. M. Malik, "Reporting cell planning in mobile computing using optimization algorithm," International Journal of Advances in Engineering and Emerging Technology, vol. 13, no. 2, pp. 101–109, 2022.

[15] Bravo, Ramiro H., and Forrest W. Flocker. "Designing HVAC systems using particle swarm optimization." *HVAC&R Research* 18, no. 5 (2012): 845-857.

[16] Zhang, Shaoqi, and Cheng Kong. "Deep learning and multi-objective optimization for real-time occupancy-based energy control in smart buildings." *Scientific Reports* 15, no. 1 (2025): 39466.

Authorized licensed use limited to: WESTERN MICHIGAN UNIVERSITY. Downloaded on February 11,2026 at 04:25:59 UTC from IEEE Xplore. Restrictions apply.

[17] Sierla, Seppo, Heikki Ihasalo, and Valeriy Vyatkin. "A review of reinforcement learning applications to control of heating, ventilation and air conditioning systems." *Energies* 15, no. 10 (2022): 3526..

[18] C. Deb, F. Zhang, J. Yang, S. E. Lee, and K. W. Shah, “A review of time series forecasting techniques for building energy consumption,” Renewable and Sustainable Energy Reviews, vol. 74, pp. 902–924, 2018. https://doi.org/10.1016/j.rser.2017.02.085.

Authorized licensed use limited to: WESTERN MICHIGAN UNIVERSITY. Downloaded on February 11,2026 at 04:25:59 UTC from IEEE Xplore. Restrictions apply.