Name: Santhiya.S

Class: 24CS4C

Reg No: 732924CSR142

Assignment No: 3

Sub: DBMS

Input

Run SQL

```
create table student_santhiya(ID INT,NAME
VARCHAR(20),MARK INT,GENDER
VARCHAR(1),BRANCH VARCHAR(3));
```

Output

Available Tables

SQL query successfully executed.
However, the result set is empty.

Input

Run SQL

```
INSERT INTO student_santhiya
VALUES('1','A','90','M','CSE');
INSERT INTO student_santhiya
VALUES('2','B','80','M','ECE');
INSERT INTO  student_santhiya
VALUES('3','C','60','M','CSE');
INSERT INTO  student_santhiya
VALUES('4','D','85','F','EEE');
INSERT INTO  student_santhiya
VALUES('5','E','70','F','CSE');
```

Output | Available Tables

SQL query successfully executed.
However, the result set is empty.

Input

Run SQL

```
update student_santhiya
 set mark=75 where id=5;
select * from student_santhiya
```

Output

Available Tables

ID	NAME	MARK	GENDER	BRANCH
1	A	90	M	CSE
2	B	80	M	ECE
3	C	60	M	CSE
4	D	85	F	EEE
5	E	75	F	CSE

Input

Run SQL

```
delete from student_santhiya where id=5;
select*from student_santhiya;
```

Output

Available Tables

ID	NAME	MARK	GENDER	BRANC
1	A	90	M	CSE
2	B	80	M	ECE
3	C	60	M	CSE
4	D	85	F	EEE

Input

Run SQL

```
select distinct branch from
student_santhiya;
```

Output

Available Tables

BRANCH
CSE
ECE
EEE

Input

Run SQL

```
select NAME,MARK from student_santhiya
order by MARK DESC;
```

Output

Available Tables

NAME	MARK
A	90
D	85
B	80
C	60

Input

Run SQL

```
select branch from student_santhiya group
by branch having avg(mark)>75;
```

Output

Available Tables

BRANCH
ECE
EEE

Input

Run SQL

```
select name from student_santhiya where
mark>(select mark from student_santhiya
where name='C');
```

Output

Available Tables

NAME
A
B
D
E

Input

Run SQL

```
select avg(mark) from student_santhiya
where branch='CSE';
select avg(mark) from student_santhiya
where branch='ECE';
select avg(mark) from student_santhiya
where branch='EEE';
```

Output | Available Tables

avg(mark)
73.33333333333333

avg(mark)
80

avg(mark)
85

Input

Run SQL

```
CREATE TABLE santhiya (id int,name
varchar(20),marks int,city
varchar(20),department varchar(20));
```

Output

Available Tables

SQL query successfully executed.
However, the result set is empty.

Input

Run SQL

```
INSERT INTO santhiya
VALUES('201','A','90','Chennai','cse');
INSERT INTO santhiya
VALUES('202','B','85','Madurai','ece');
INSERT INTO santhiya
VALUES('203','C','70','Erode','eee');
INSERT INTO santhiya
VALUES('204','D','75','Salem','it');
INSERT INTO santhiya
VALUES('205','E','90','chennai','cse');
```

Output | Available Tables

SQL query successfully executed.
However, the result set is empty.