

Rajalakshmi Engineering College

Name: SANTHOSH S
Email: 241801251@rajalakshmi.edu.in
Roll no: 241801251
Phone: 9790911586
Branch: REC
Department: I AI & DS FD
Batch: 2028
Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ravi is developing a student registration system for a college. To efficiently store and manage the student IDs, he decides to implement a doubly linked list where each node represents a student's ID.

In this system, each student's ID is stored sequentially, and the system needs to display all registered student IDs in the order they were entered.

Implement a program that creates a doubly linked list, inserts student IDs, and displays them in the same order.

Input Format

The first line contains an integer N the number of student IDs.

The second line contains N space-separated integers representing the student IDs.

Output Format

The output should display the single line containing N space-separated integers representing the student IDs stored in the doubly linked list.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

10 20 30 40 50

Output: 10 20 30 40 50

Answer

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
// Node structure for doubly linked list
```

```
typedef struct Node {  
    int data;  
    struct Node* prev;  
    struct Node* next;  
} Node;
```

```
// Function to create a new node
```

```
Node* createNode(int data) {  
    Node* newNode = (Node*)malloc(sizeof(Node));  
    newNode->data = data;  
    newNode->prev = newNode->next = NULL;  
    return newNode;  
}
```

```
// Function to insert at the end of the list
```

```
void insertAtEnd(Node** head, int data) {  
    Node* newNode = createNode(data);  
    if (*head == NULL) {  
        *head = newNode; // If list is empty, new node becomes the head
```

```

    return;
}

Node* temp = *head;
// Traverse to the end of the list
while (temp->next) {
    temp = temp->next;
}
// Insert the new node at the end
temp->next = newNode;
newNode->prev = temp;
}

```

```

// Function to print the list from head to tail
void printList(Node* head) {
    Node* temp = head;
    while (temp != NULL) {
        printf("%d ", temp->data);
        temp = temp->next;
    }
    printf("\n");
}

```

```

int main() {
    int N;
    scanf("%d", &N); // Read the number of elements

    Node* head = NULL;

    // Insert all employee IDs into the doubly linked list
    for (int i = 0; i < N; i++) {
        int empID;
        scanf("%d", &empID);
        insertAtEnd(&head, empID);
    }

    // Print the final linked list
    printList(head);

    return 0;
}

```

Status : Correct

Marks : 10/10