

Show one page at a time

Finish review

Completed Tuesday, 5 November 2024, 12:16 PM
Duration 48 days 5 hours

Question 1
Correct
Marked out of 1.00
Flag question

The code given below contains instructions to print the text **"I love Apples"** to the console.

The `\n` in the text **"I love Apples\n"** ensures that the line breaks after printing the text **"I love Apples"** (which means that nothing else is printed on the same line).

Follow the steps given below to change the text, execute **compile** command and finally **execute** the file :

1. In the code given below, change the text to print **"I love Mangoes"** instead of **"I love Apples"**.

Answer: (penalty regime: 0 %)

Reset answer

```
1 #include <stdio.h>
2 int main()
3 {
4     printf("I love Mangoes");
5     return 0;
6 }
```

Question **2**

Correct

Marked out of
1.00

🚩 Flag question

	Expected	Got	
✓	I love Mangoes	I love Mangoes	✓

Passed all tests! ✓


Given below is a simple program written in **C** language.

Change the text in the code given below to make the program print "**Hello C**" instead of "**Hello B**".

Answer: (penalty regime: 0 %)

Reset answer

```
1 #include <stdio.h>
2
3 int main()
4 {
5     printf("Hello C");
6     return 0;
7 }
```



	Expected	Got	
✓	Hello C	Hello C	✓

Passed all tests! ✓

Finish review

Question

Correct

Marked out of
3.00

[Flag question](#)

Objective

This is a simple challenge to help you practice printing to stdout.

We're starting out by printing the most famous computing phrase of all time! In the editor below, use either `printf` or `cout` to print the string ***Hello, World!*** to stdout.

Input Format

You do not need to read any input in this challenge.

Output Format

Print ***Hello, World!*** to stdout.

Sample Output

Hello, World!

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     printf("Hello, World!");
```

	Expected	Got	
✓	Hello, World!	Hello, World!	✓

Passed all tests! ✓

Marked out of
5.00

🚩 Flag question

This challenge will help you to learn how to take a character, a string and a sentence as input in C.

To take a single character **ch** as input, you can use `scanf("%c", &ch);` and `printf("%c", ch)` writes a character specified by the argument `ch` to `stdout`:

```
char ch;  
scanf("%c", &ch);  
printf("%c", ch);
```

This piece of code prints the character **ch**.

Task

You have to print the character, **ch**.

Input Format

Take a character, **ch** as input.

Output Format

Print the character, **ch**.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     char ch;
5     scanf("%c",&ch);
6     printf("%c",ch);
7 }
```

	Input	Expected	Got	
✓	c	c	c	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of
7.00

🚩 [Flag question](#)

Objective

The fundamental data types in c are int, float and char. Today, we're discussing int and float data types.

The printf() function prints the given statement to the console. The syntax is printf("format string",argument_list);. In the function, if we are using an integer, character, string or float as argument, then in the format string we have to write %d (integer), %c (character), %s (string), %f (float) respectively.

The scanf() function reads the input data from the console. The syntax is scanf("format string",argument_list);. For ex:
The scanf("%d",&number) statement reads integer number from the console and stores the given value in variable **number**.

To input two integers separated by a space on a single line, the command is scanf("%d %d", &n, &m), where **n** and **m** are the two integers.

Task

Your task is to take two numbers of [int data type](#), two numbers of float data type as input and output their sum:

1. Declare **4** variables: two of type int and two of type float.
2. Read **2** lines of input from stdin (according to the sequence given in the 'Input Format' section below) and initialize your **4** variables.
3. Use the + and - operator to perform the following operations:
 - o Print the sum and difference of two int variable on a new line.
 - o Print the sum and difference of two float variable rounded to one decimal place on a new line.

Input Format

The first line contains two integers.

The second line contains two floating point numbers.

Constraints

- $1 \leq \text{integer variables} \leq 10^4$
- $1 \leq \text{float variables} \leq 10^4$

Output Format

Print the sum and difference of both integers separated by a space on the first line, and the sum and difference of both float (scaled to **1** decimal place) separated by a space on the second line.

Sample Input

```
10 4
4.0 2.0
```

Sample Output

```
14 6
6.0 2.0
```

Explanation

When we sum the integers **10** and **4**, we get the integer **14**. When we subtract the second number **4** from the first number **10**, we get **6** as their difference.

When we sum the floating-point numbers **4.0** and **2.0**, we get **6.0**. When we subtract the second number **2.0** from the first number **4.0**, we get **2.0** as their difference.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,g,f;
5     float c,d,i,l;
6     scanf("%d%d",&a,&b);
7     scanf("%f%f",&c,&d);
8     g=a+b;
9     f=c+d;
10    i=a-b;
11    l=c-d;
12    printf("%d %d\n",g,f);
13    printf("%.1f %.1f\n",i,l);
14 }
```

	Input	Expected	Got	
✓	10 4 4.0 2.0	14 6 6.0 2.0	14 6 6.0 2.0	✓
✓	20 8 8.0 4.0	28 12 12.0 4.0	28 12 12.0 4.0	✓

Passed all tests! ✓

Finish review

Question **1**

Correct

Marked out of
3.00

 Flag question

Write a program to input a name (as a single character) and marks of three tests as m1, m2, and m3 of a student considering all the three marks have been given in integer format.

Now, you need to calculate the average of the given marks and print it along with the name as mentioned in the output format section.

All the test marks are in integers and hence calculate the average in integer as well. That is, you need to print the integer part of the average only and neglect the decimal part.

Input format :

Line 1 : Name(Single character)

Line 2 : Marks scored in the 3 tests separated by single space.

Output format :

First line of output prints the name of the student.

Second line of the output prints the average mark.

Constraints

Marks for each student lie in the range 0 to 100 (both inclusive)

Sample Input 1 :

A
3 4 6

Sample Output 1 :

A
4

Sample Input 2 :

T
7 3 8

Sample Output 2 :

T
6

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     char a;
5     int b,c,d,e;
6     scanf("%c\n",&a);
7     scanf("%d%d%d",&b,&c,&d);
8     printf("%c\n",a);
9     e=(b+c+d)/3;
10    printf("%d",e);
11
12 }
```

	Input	Expected	Got	
✓	A 3 4 6	A 4	A 4	✓
✓	T 7 3 8	T 6	T 6	✓
✓	R 0 100 99	R 66	R 66	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of
5.00

🚩 Flag question

Some C data types, their format specifiers, and their most common bit widths are as follows:

- *Int* ("%d"): 32 Bit integer
- *Long* ("%ld"): 64 bit integer
- *Char* ("%c"): Character type
- *Float* ("%f"): 32 bit real value
- *Double* ("%lf"): 64 bit real value

Reading

To read a data type, use the following syntax:

```
scanf("`format_specifier`", &val)
```

For example, to read a *character* followed by a *double*:

```
char ch;
```

```
double d;
```

```
scanf("`%c %lf`", &ch, &d);
```

For the moment, we can ignore the spacing between format specifiers.

Printing

To print a data type, use the following syntax:

```
printf("`format_specifier`", val)
```

For example, to print a *character* followed by a *double*:

```
char ch = 'd';
```

```
double d = 234.432;  
printf("%c %lf", ch, d);
```

Note: You can also use *cin* and *cout* instead of *scanf* and *printf*; however, if you are taking a million numbers as input and printing a million lines, it is faster to use *scanf* and *printf*.

Input Format

Input consists of the following space-separated values: *int*, *long*, *char*, *float*, and *double*, respectively.

Output Format

Print each element on a new line in the same order it was received as input. Note that the floating point value should be correct up to 3 decimal places and the double to 9 decimal places.

Sample Input

```
3 12345678912345 a 334.23 14049.30493
```

Sample Output

```
3  
12345678912345  
a  
334.230  
14049.304930000
```

Explanation

Print *int* **3**,
followed by *long* **12345678912345**,
followed by *char* **a**,
followed by *float* **334.23**,
followed by *double* **14049.30493**.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     long b;
6     char c;
7     float d;
8     double e;
9     scanf("%d %ld %c %f %lf",&a,&b,&c,&d,&e);
10    printf("%d\n%ld\n%c\n%.3f\n%.9lf",a,b,c,d,e);
11 }
```

	Input	Expected	Got	
✓	3 12345678912345 a 334.23 14049.30493	3 12345678912345 a 334.230 14049.304930000	3 12345678912345 a 334.230 14049.304930000	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of
7.00

🚩 Flag question

Write a program to print the [ASCII value](#) and the two adjacent characters of the given character.

Input

E


Output

69

D F

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     char a,b,c;
5     scanf("%c",&a);
6     printf("%d\n",a);
7     b=a-1;
8     c=a+1;
9     printf("%c %c",b,c);
10 }
```



	Input	Expected	Got	
✓	E	69 D F	69 D F	✓

Passed all tests! ✓

Finish review

Question **1**

Correct

Marked out of
1.00

 [Flag question](#)

The program must accept a positive integer N and print the digit in the tenth position.

Input Format:

The first line denotes the value of N.

Output Format:

The first line contains the value of N.

Boundary Conditions:

$10 \leq N \leq 9999999$

Example Input/Output 1:

Input:

20

Output:

2

Example Input/Output 2:

Input:

37843

Output:

4

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int N,a;
5     scanf("%d",&a);
6     N=(a/10)%10;
7     printf("%d",N);
8     return 0;
9 }
```

	Input	Expected	Got	
✓	20	2	2	✓
✓	37843	4	4	✓

Passed all tests! ✓

Question **1**

Correct

Marked out of
1.00

 Flag question

Write a C Program to calculates the area (floating point number with two decimal places) of a Circle given it's radius (integer value). The value of Pi is 3.14.

Sample Test Cases

Test Case 1

Input

7

Output

Area of a circle = 153.86

Test Case 2

Input

50

Output

Area of a circle = 7850.00

Test Case 3

Input

42

Output

Area of a circle = 5538.96

For example:

Input	Result
7	Area of a circle = 153.86
50	Area of a circle = 7850.00

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int r ;
5     float a ;
6     scanf("%d",&r);
7     a=3.14*r*r;
8     printf("Area of a circle = %.2f",a);
9     return 0 ;
10 }
```

	Input	Expected	Got	
✓	7	Area of a circle = 153.86	Area of a circle = 153.86	✓
✓	50	Area of a circle = 7850.00	Area of a circle = 7850.00	✓

Passed all tests! ✓

Question **1**

Correct

Marked out of
1.00

[Flag question](#)

Develop a 'C' program to **swap** two numbers (using three variables).

Input

10 20

Output

Before swapping :

a = 10 b = 20

After swapping :


a = 20 b = 10

For example:

Input	Result
10 20	Before swapping : a = 10 b = 20 After swapping : a = 20 b = 10

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main ()
3 {
4     int a,b;
5     scanf("%d%d",&a,&b);
6     printf("Before swapping : \na = %d b = %d",a,b);
7     printf("\nAfter swapping : \na = %d b = %d",b,a);
8     return 0;
9 }
```

	Input	Expected	Got	
✓	10 20	Before swapping : a = 10 b = 20 After swapping : a = 20 b = 10	Before swapping : a = 10 b = 20 After swapping : a = 20 b = 10	✓

Passed all tests! ✓

Finish review

Question **1**

Correct

Marked out of
1.00

Flag question

Write a program to print the **ASCII value** of the given character.

Input

A

Output


The **ASCII value** of the given character A is : 65

For example:

Input	Result
A	The ASCII value of the given character A is : 65

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     char a;
5     scanf("%c",&a);
6     printf("The ASCII value of the given character A is : %d",a);
7     return 0 ;
8 }
```



	Input	Expected	Got	
✓	A	The ASCII value of the given character A is : 65	The ASCII value of the given character A is : 65	✓

Passed all tests! ✓

Finish review