

```

PS C:\Users\santh\OneDrive\Documents\MINI PROJECT\mini hackathon\ML-DATA-ANALYSIS-EPCET\shopping-sql> npm run setup
> shopping-sql@1.0.0 setup
> node setup.js

cart: 12
categories: 6
customers: 12
inventory: 12
order_items: 48
orders: 24
payments: 24
products: 12
reviews: 30
shipping: 24
suppliers: 6
PS C:\Users\santh\OneDrive\Documents\MINI PROJECT\mini hackathon\ML-DATA-ANALYSIS-EPCET\shopping-sql> npm start

```

```

order_items: 48
orders: 24
payments: 24
products: 12
reviews: 30
shipping: 24
suppliers: 6
PS C:\Users\santh\OneDrive\Documents\MINI PROJECT\mini hackathon\ML-DATA-ANALYSIS-EPCET\shopping-sql> npm start
> shopping-sql@1.0.0 start
> node index.js

```

(index)	product_name	category_name	price	quantity
0	'Basmati Rice 5kg'	'Groceries'	'620.00'	40
1	'Filter Coffee 500g'	'Groceries'	'280.00'	48
2	'Bluetooth Speaker'	'Electronics'	'1899.00'	56
3	'USB-C Charger'	'Electronics'	'799.00'	64
4	'Cotton Bedsheet'	'Home'	'1199.00'	72
5	'Steel Water Bottle'	'Home'	'449.00'	80
6	'Men Cotton Shirt'	'Fashion'	'899.00'	88
7	'Women Kurta'	'Fashion'	'1299.00'	96
8	'SQL Handbook'	'Books'	'550.00'	104
9	'Data Structures Guide'	'Books'	'690.00'	112

```

PS C:\Users\santh\OneDrive\Documents\MINI PROJECT\mini hackathon\ML-DATA-ANALYSIS-EPCET\shopping-sql>

```

```

MySQL 8.0 Command Line Cli
mysql> USE shopping2;
Database changed
mysql> SHOW TABLES;
+-----+
| Tables_in_shopping2 |
+-----+
| cart                 |
| categories            |
| customers            |
| inventory            |
| order_items          |
| orders              |
| payments            |
| products            |
| reviews            |
| shipping            |
| suppliers            |
+-----+
11 rows in set (0.00 sec)

mysql> SELECT COUNT(*) AS categories FROM categories;
+-----+
| categories |
+-----+
|           6 |
+-----+
1 row in set (0.01 sec)

mysql> SELECT COUNT(*) AS suppliers FROM suppliers;

```

```
MySQL 8.0 Command Line Cli x + v
mysql> SELECT COUNT(*) AS suppliers FROM suppliers;
+-----+
| suppliers |
+-----+
|          6 |
+-----+
1 row in set (0.00 sec)

mysql> SELECT COUNT(*) AS customers FROM customers;
+-----+
| customers |
+-----+
|          12 |
+-----+
1 row in set (0.00 sec)

mysql> SELECT COUNT(*) AS products FROM products;
+-----+
| products |
+-----+
|          12 |
+-----+
1 row in set (0.00 sec)

mysql> SELECT COUNT(*) AS inventory FROM inventory;
+-----+
| inventory |
+-----+
|          12 |
+-----+
```