

REC-CIS

```
1 #include<stdio.h>
2 int main()
3 {
4     int X,Y;
5     scanf("%d",&X);
6     scanf(" %d",&Y);
7     if(X>=100&&Y>=100)
8     {
9         printf("YES");
10    }
11    else{
12        printf("NO");
13    }
14
15
16 }
```

	Input	Expected	Got	
✓	100 110	YES	YES	✓
✓	100 90	NO	NO	✓

Passed all tests! ✓

SAMPLE OUTPUT 2

1

Explanation Case 1: The lonely board member shakes no hands, hence 0. Case 2: There are 2 board members, 1 handshake takes place.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<math.h>
3 int main()
4 {
5     int n,x;
6     scanf("%d",&n);
7     x=(n*(n-1))/2;
8     printf("%d",x);
9 }
```

	Input	Expected	Got	
✓	1	0	0	✓
✓	2	1	1	✓

REC-CIS

Explanation Out of given numbers, 8 is maximum.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d %d",&a,&b,&c);
6     if(a>b && a>c)
7     {
8         printf("%d",a);
9     }
10    else if(b>a && b>c)
11    {
12        printf("%d",b);
13    }
14    else{
15        printf("%d",c);
16    }
17
18 }
```

	Input	Expected	Got	
✓	81 26 15	81	81	✓
Passed all tests! ✓				

REC-CIS

167.64

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<math.h>
3 int main()
4 {
5     int feet,inches;
6     float centimeters;
7     scanf("%d\t",&feet);
8     scanf("%d",&inches);
9     centimeters=(feet*30.48)+(inches*2.54);
10    printf("%.2f",centimeters);
11
12 }
```

	Input	Expected	Got	
✓	5 6	167.64	167.64	✓
Passed all tests! ✓				

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,sum,diff,product,division,remainder;
5     scanf("%d",&a);
6     scanf("%d",&b);
7     sum=a+b;
8     diff=a-b;
9     product=a*b;
10    division=a/b;
11    remainder=a%b;
12    printf("%d\n%d\n%d\n%d\n%d",sum,diff,product,division,remainder);
13
14 }
```

	Input	Expected	Got	
✓	100	106	106	✓
	6	94	94	
		600	600	
		16	16	
		4	4	

Passed all tests! ✓

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int loaves;
5     float price,discount,total;
6     scanf("%d",&loaves);
7     price=3.49*loaves;
8     printf("Regular price: %.2f\n",price);
9     discount=price*0.60;
10    printf("Discount: %.2f\n",discount);
11    total=(price-discount);
12    printf("Total: %.2f",total);
13
14
15
16
17 }
```

	Input	Expected	Got	
✓	10	Regular price: 34.90 Discount: 20.94 Total: 13.96	Regular price: 34.90 Discount: 20.94 Total: 13.96	✓

Passed all tests! ✓