

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int t,m,n,c=0;
5     scanf("%d",&t);
6     for(int i=0;i<t;i++){
7         c=0;
8         scanf("%d\n%d",&m,&n);
9         int arr[n];
10        for(int j=0;j<n;j++)
11        {
12            scanf("%d",&arr[j]);
13        }
14        for(int a=0;a<n-1;a++){
15            for(int b=a+1;b<n;b++){
16                if(arr[a]+arr[b]==m){
17                    printf("%d %d\n",a+1,b+1);
18                    c=1;break;
19                }
20            }if(c==1)break;
21        }
22    }
23    return 0;}
```

	Input	Expected	Got	
✓	2	1 4	1 4	✓
	4	1 2	1 2	
	5			
	1 4 5 3 2			
	4			
	4			
	2 2 4 3			

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,m,c,c1=0,co;
5     scanf("%d",&n);
6     int arr[n];
7     for(int a=0;a<n;a++){
8         scanf("%d",&arr[a]);
9     }
10    scanf("%d",&m);
11    int brr[m],ans[m];
12    for(int b=0;b<m;b++)
13    {
14        scanf("%d",&brr[b]);
15    }
16    for(int j=0;j<m;j++)
17    {
18        c=0;
19        for(int i=0;i<n;i++){
20            if(arr[i]==brr[j]){
21                c=1;
22                arr[i]=-1;
23                break;
24            }
25        }
26        if(c==0){
27            ans[c1]=brr[j];
28            c1++;
29        }
30    }
31    for(int a=0;a<c1;a++){
32        co=0;
33        for(int b=0;b<c1;b++){
34            if(ans[b]<ans[a])
35                co++;
36        }
37    }
```

REC-CIS

```
27     }
28     if(c==0){
29         ans[c1]=brr[j];
30         c1++;
31     }
32 }
33 for(int a=0;a<c1;a++){
34     co=0;
35     for(int b=0;b<c1;b++){
36         if(ans[b]<ans[a])
37             co++;
38     }
39     int temp=ans[a];
40     ans[a]=ans[co];
41     ans[co]=temp;
42 }
43 for(int i=0;i<c1;i++)
44     printf("%d ",ans[i]);
45 return 0;
46 }
```

	Input	Expected	Got	
✓	10 203 204 205 206 207 208 203 204 205 206 13 203 204 204 205 206 207 205 208 203 206 205 206 204	204 205 206	204 205 206	✓

Passed all tests! ✓

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int t,n,Is,rs,m;
5     scanf("%d",&t);
6     for(int i=0;i<t;i++)
7     {
8         Is=0;
9         rs=0;
10        scanf("%d",&n);
11        int arr[n];
12        for(int j=0;j<n;j++)
13            scanf("%d",&arr[j]);
14        m=n/2;
15        if(arr[m]==0){
16            for(m=0;arr[m]==0 && m<n;m++);
17        }
18        for(int j=0;j<=m;j++)
19            Is=Is+arr[j];
20        for(int j=m;j<n;j++)
21            rs=rs+arr[j];
22        printf("%s\n",(Is==rs)?"YES":"NO");
23    }
24    return 0;
25 }
26 }
```

	Input	Expected	Got	
✓	3	YES	YES	✓
	5	YES	YES	
	1 1 4 1 1	YES	YES	
	4			

REC-CIS

```
19 Is=Is+arr[j];
20 for(int j=m;j<n;j++)
21 rs=rs+arr[j];
22 printf("%s\n",(Is==rs)?"YES":"NO");
23
24 }
25 return 0;
26 }
```

	Input	Expected	Got	
✓	3 5 1 1 4 1 1 4 2 0 0 0 4 0 0 2 0	YES YES YES	YES YES YES	✓
✓	2 3 1 2 3 4 1 2 3 3	NO YES	NO YES	✓

Passed all tests! ✓