

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int arr[3][3];
5     for(int i=0;i<3;i++)
6     {
7         for(int j=0;j<3;j++)
8         {
9             scanf("%d",&arr[i][j]);
10        }
11    }
12    int odd=0,even=0;
13    for(int i=0;i<3;i++)
14    {
15        for(int j=0;j<3;j++)
16        {
17            if((i+j)%2!=0)
18                odd+=arr[i][j];
19            else
20                even+=arr[i][j];
21        }
22    }
23    printf("%d\n%d",even,odd);
24 }
25
```

	Input	Expected	Got	
✓	1 2 3 4 5 6 7 8 9	25 20	25 20	✓
✓	21 422 423 443 586 645 657 846 904	2591 2356	2591 2356	✓

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 struct data
3 {
4     int gen;int tal;
5
6 };
7 int main()
8 {
9     int n;
10    scanf("%d",&n);
11    struct data a[n];
12    for(int i=0;i<n;i++)
13        scanf("%d %d",&a[i].gen,&a[i].tal);
14    for(int i=0;i<n-1;i++)
15    {
16        for(int j=0;j<n-i-1;++j)
17        {
18            if(a[j].tal<a[j+1].tal)
19            {
20                struct data temp=a[j];
21                a[j]=a[j+1];
22                a[j+1]=temp;
23            }
24        }
25    }
26    for(int i=0;i<n;i++)
27    {
28        if(a[i].gen==0)
29            printf("%d ",a[i].tal);
30    }
31    for(int i=0;i<n;i++)
32    {
33        if(a[i].gen==1)
```

REC-CIS

```
25
26 }
27 for(int i=0;i<n;i++)
28 {
29     if(a[i].gen==0)
30         printf("%d ",a[i].tal);
31 }
32
33 for(int i=0;i<n;i++)
34 {
35     if(a[i].gen==1)
36         printf("%d ",a[i].tal);
37 }
38 }
```

	Input	Expected	Got	
✓	5 0 3 1 6 0 2 0 7 1 15	7 3 2 15 6	7 3 2 15 6	✓
✓	6 0 1 0 26 0 39 0 37 0 7 0 13	39 37 26 13 7 1	39 37 26 13 7 1	✓
✓	12	31 29 18 14 12 10 9 8 5 3 2 1	31 29 18 14 12 10 9 8 5 3 2 1	✓

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int i,j,n,x1,x2,y1,y2,t=0;
5     long long total=0;
6     int arr[1001][1001]={0};
7     scanf("%d",&n);
8     while(n--)
9     {
10         scanf("%d %d %d %d %d",&x1,&y1,&x2,&y2,&t);
11         for(i=x1;i<=x2;i++)
12         {
13             for(j=y1;j<=y2;j++)
14             {
15                 if(arr[i][j]==0)
16                     arr[i][j]+=t;
17                 else if(arr[i][j]>0)
18                     arr[i][j]=(-1)*(arr[i][j]+t);
19                 else if(arr[i][j]<0)
20                     arr[i][j]-=t;
21             }
22         }
23     }
24     for(i=1;i<1001;i++)
25     {
26         for(j=1;j<1001;j++)
27         {
28             if(arr[i][j]<0)
29                 total+=arr[i][j];
30         }
31     }
32     printf("%lld\n",(-1)*total);
33     return 0;
34 }
```

REC-CIS

```
26         for(j=1;j<1001;j++)
27     {
28         if(arr[i][j]<0)
29             total+=arr[i][j];
30     }
31 }
32 printf("%lld\n",(-1)*total);
33 return 0;
34 }
```

	Input	Expected	Got	
✓	3 1 4 4 6 1 4 3 6 6 2 2 2 5 4 3	35	35	✓
✓	1 48 12 49 27 8	0	0	✓
✓	3 88 34 99 76 44 82 65 94 100 81 58 16 65 66 7	10500	10500	✓

Passed all tests! ✓