

UNIT-3

LEETCODEEXERCISE

1.Delete Duplicate Emails

Problem Summary

Table: Person

Column Name	Type
id	int
email	varchar

Id is the primary key (column with unique values) for this table.

Each row of this table contains an email.

The emails will not contain uppercase letters.

Task

Write a solution to delete all duplicate emails, keeping only one unique email with the smallest id.

Solution

MySQL   Auto

```
1 # Write your MySQL query statement below
2 delete p1
3 from Person p1, Person p2
4 where p1.Email = p2.Email and p1.Id > p2.Id
-
```

Output

id	email
--	-----
1	john@example.com
2	bob@example.com

Expected

id	email
--	-----
1	john@example.com
2	bob@example.com

2. Customers Who Never Order

Problem Summary

Table: Customers.

Id	Name
1	Joe
2	Henry
3	Sam
4	Max

Table: Orders.

Id	CustomerId
1	3
2	1

Task

Write a SQL query to find all customers who never order anything.

Solution

MySQL   Auto

```
1 # Write your MySQL query statement below
2 select c.Name as Customers
3 from Customers c
4 where c.Id not in (select CustomerId from Orders);
```

Output

```
| Customers |
| ----- |
| Henry    |
| Max      |
```

Expected

```
| Customers |
| ----- |
| Henry    |
| Max      |
```

3. Biggest Single Number

Problem Summary

Table: Activity

Column Name	Type
player_id	int
device_id	int
event_date	date
games_played	int

Task

Write an SQL query that reports the first login date for each player.

Solution

MySQL   Auto

```
1 # Write your MySQL query statement below
2 select a.player_id, min(a.event_date) as first_login
3 from Activity a
4 group by a.player_id
5
```

Output

player_id	first_login
1	2016-03-01
2	2017-06-25
3	2016-03-02

Expected

player_id	first_login
1	2016-03-01
2	2017-06-25
3	2016-03-02

4. Exchange Seats

Problem Summary

Table: Seat

Column Name	Type
id	int
student	varchar

Task

Write a solution to swap the seat id of every two consecutive students. If the number of students is odd, the id of the last student is not swapped.

Solution

MySQL  Auto

```
1 # Write your MySQL query statement below
2 SELECT
3     a.id id,
4     COALESCE(b.student, a.student) student
5 FROM
6     seat a LEFT JOIN seat b
7     ON b.id = (CASE
8         WHEN a.id%2=1 THEN a.id+1
9         ELSE a.id-1
10        END)
11 ORDER BY a.id
```

Output

```
| id | student |
| -- | -|
| 1 | Doris |
| 2 | Abbot |
| 3 | Green |
| 4 | Emerson |
| 5 | Jeames |
```

Expected

```
| id | student |
| -- | -|
| 1 | Doris |
| 2 | Abbot |
| 3 | Green |
| 4 | Emerson |
| 5 | Jeames |
```

5. Triangle Judgement

Problem Summary

A pupil Tim gets homework to identify whether three line segments could possibly form a triangle.

However, this assignment is very heavy because there are hundreds of records to calculate.

x	y	z
13	15	30
10	20	15

Task

writing a query to judge whether these three sides can form a triangle, assuming table triangle holds the length of the three sides x, y and z.

Solution

MySQL   Auto

```
1 # Write your MySQL query statement below
2 select *,
3     if(x+y>z and x+z>y and y+z>x, 'Yes', 'No') as triangle
4 from triangle
```

Output

x	y	z	triangle
13	15	30	No
10	20	15	Yes

Expected

x	y	z	triangle
13	15	30	No
10	20	15	Yes