

Name: Santhosh M  
Reg no: 240701475

## Week 8: Sorting Algorithms - Bubble and Selection

### 1. Easy going

#### Problem statement:

Coders here is a simple task for you, you have given an array of size  $N$  and an integer  $M$ .

Your task is to calculate the *difference between maximum sum and minimum sum of  $N-M$  elements* of the given array.

#### Constraints:

$$1 \leq t \leq 10$$

$$1 \leq n \leq 1000$$

$$1 \leq a[i] \leq 1000$$

#### Input:

First line contains an integer  $T$  denoting the number of testcases.

First line of every testcase contains two integer  $N$  and  $M$ .

Next line contains  $N$  space separated integers denoting the elements of array

#### Output:

For every test case print your answer in new line

## Program:

```
1 #include<stdio.h>
2 int diff(int arr[],int n,int m)
3 {
4     int e=n-m;
5     int max=0,min=0;
6     for(int i=0;i<e;i++)
7     {
8         min+=arr[i];
9     }
10    for(int j=n-1;j>m-1;j--)
11    {
12        max+=arr[j];
13    }
14    int dif=max-min;
15    return dif;
16 }
17 int main()
18 {
19     int t,d,num,temp;
20     scanf("%d",&t);
21     while(t-->0)
22     {
23         int n,m;
24         scanf("%d %d",&n,&m);
25         int arr[n];
26         for(int i=0;i<n;i++)
27         {
28             scanf("%d",&arr[i]);
29         }
30
31         for(int i=0;i<n;i++)
32         {
33             num=i;
34             for(int j=i+1;j<n;j++)
35             {
36                 if(arr[j]<arr[num])
37                 {
38                     num=j;
39                 }
40             }
41             temp=arr[num];
42             arr[num]=arr[i];
43             arr[i]=temp;
44         }
45         d=diff(arr,n,m);
46         printf("%d\n",d);
47     }
48     return 0;
49 }
```

## Test cases:

	Input	Expected	Got	
✓	1 5 1 1 2 3 4 5	4	4	✓

Passed all tests! ✓

## 2. sort it out

### Problem statement:

You are given an array **A** of non-negative integers of size **m**. Your task is to sort the array in non-decreasing order and print out the original indices of the new sorted array.

#### Example:

A={4,5,3,7,1}

After sorting the new array becomes A={1,3,4,5,7}.

The required output should be "4 2 0 1 3"

#### INPUT :

The first line of input consists of the size of the array

The next line consists of the array of size m

#### OUTPUT :

Output consists of a single line of integers

### Program:

```
1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     int arr1[n];
7     for(int i=0;i<n;i++)
8     {
9         scanf("%d",&arr1[i]);
10    }
11    int arr2[n];
12    for(int i=0;i<n;i++)
13    {
14        arr2[i]=arr1[i];
15    }
16    for(int i=0;i<n;i++)
17    {
18        int temp=0;
19        for(int j=i+1;j<n;j++)
20        {
21            if(arr2[i]>arr2[j])
22            {
23                temp=arr2[j];
24                arr2[j]=arr2[i];
25                arr2[i]=temp;
26            }
27        }
28    }
29    for(int i=0;i<n;i++)
30    {
31        for(int j=0;j<n;j++)
32        {
33            if(arr2[i]==arr1[j])
34            {
35                printf("%d ",j);
36            }
37        }
38    }
39    return 0;
```

Test cases:

	Input	Expected	Got	
✓	5 4 5 3 7 1	4 2 0 1 3	4 2 0 1 3	✓

Passed all tests! ✓

### 3. Save patient

Problem statement:

A new deadly virus has infected large population of a planet. A brilliant scientist has discovered a new strain of virus which can cure this disease. Vaccine produced from this virus has various strength depending on midichlorians count. A person is cured only if midichlorians count in vaccine batch is more than midichlorians count of person. A doctor receives a new set of report which contains midichlorians count of each infected patient, Practo stores all vaccine doctor has and their midichlorians count. You need to determine if doctor can save all patients with the vaccines he has. The number of vaccines and patients are equal.

#### Input Format

First line contains the number of vaccines - N. Second line contains N integers, which are strength of vaccines. Third line contains N integers, which are midichlorians count of patients.

#### Output Format

Print a single line containing 'Yes' or 'No'.

Program:

```
1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     int vac[n],pat[n];
7     for(int i=0;i<n;i++)
8     {
9         scanf("%d",&vac[i]);
10    }
11    for(int i=0;i<n;i++)
12    {
13        scanf("%d",&pat[i]);
14    }
15    for(int i=0;i<n;i++)
16    {
17        int flag=0;
18        for(int j=0;j<n;j++)
19        {
20            if(vac[i]<pat[j])
21                flag=1;
22            //break;
23        }
24        if(flag==1)
25        {
26            printf("No");
27            }break;
28    }
29    return 0;
30 }
```

Test cases:

	Input	Expected	Got	
✓	5 123 146 454 542 456 100 328 248 689 200	No	No	✓

Passed all tests! ✓

## 4. Shubham and xor

Problem statement:

You are given an array of  $n$  integer numbers  $a_1, a_2, \dots, a_n$ . Calculate the number of pair of indices  $(i, j)$  such that  $1 \leq i < j \leq n$  and  $a_i \text{ xor } a_j = 0$ .

### Input format

- First line:  $n$  denoting the number of array elements
- Second line:  $n$  space separated integers  $a_1, a_2, \dots, a_n$ .

### Output format

Output the required number of pairs.

Program:

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,count=0;
5     scanf("%d",&n);
6     int arr[n];
7     for(int i=0;i<n;i++)
8     {
9         scanf("%d",&arr[i]);
10    }
11    for(int i=0;i<n-1;i++)
12    {
13        for(int j=i+1;j<n;j++)
14        {
15            if((arr[i]^arr[j])==0)
16            {
17                count++;
18            }
19        }
20    }
21    printf("%d",count);
22    return 0;
23 }
```

	Input	Expected	Got	
✓	5 1 3 1 4 3	2	2	✓

Passed all tests! ✓

