WEB PROGRAMMING & FULL-STACK DEVELOPMENT

RIGFORGE: INTERACTIVE GAMING PC BUILDER AND COMPATIBILITY ESTIMATION SYSTEM

A PROJECT REPORT

Submitted by

SANTHOSH G - 240701473
ROHITH D - 240701435

III YEAR COMPUTER SCIENCE AND ENGINEERING
DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING
RAJALAKSHMI ENGINEERING COLLEGE
THANDALAM, CHENNAI – 602 105

OCTOBER 2026

BONAFIDE CERTIFICATE

Certified that this project report titled **"RigForge: Interactive Gaming PC Builder and Compatibility Estimation System"** is the bonafide work carried out by **Santhosh G (240701473)** and **Rohith D (240701435)** under the guidance of **Mrs. Deepa**, Assistant Professor, Department of Computer Science and Engineering, Rajalakshmi Engineering College, in partial fulfilment of the requirements for the academic course **Web Programming / Full-Stack Web Development**.

The project presents a fully operational, responsive, client-side web application developed using **React.js, Bootstrap 5, JavaScript (ES6+), HTML5, and CSS3**. The application provides an interactive hardware assembly environment featuring real-time multi-constraint compatibility checking (CPU sockets, RAM standards, motherboard form factors, and power budgets), dynamic Indian Rupee (₹) price calculations with configurable 18% GST, interactive budget tracking, browser LocalStorage persistence, side-by-side build comparison, and print-ready specification sheets.

SIGNATURE OF THE FACULTY INCHARGE

(Mrs. Deepa, Assistant Professor)

Submitted for the Practical Examination held on: _____

SIGNATURE OF THE INTERNAL EXAMINER

SIGNATURE OF THE EXTERNAL EXAMINER

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	04
	LIST OF TABLES	05
	LIST OF FIGURES	06
	LIST OF SYMBOLS AND ABBREVIATIONS	07
1	**INTRODUCTION**	08
1.1	Problem Statement and Motivation	08
1.2	Objectives of the Project	09
1.3	Scope of the Project	10
1.4	Organization of the Report	10
2	**LITERATURE REVIEW**	11
2.1	Evolution of E-commerce Hardware Configurator Tools	11
2.2	Survey of Compatibility Verification Approaches	12
2.3	Single-Page Applications (SPA) and Client-Side State Management	13
2.4	Research Gap and RigForge Project Positioning	14
3	**DOMAIN AREA AND TECHNICAL BACKGROUND**	15
3.1	Personal Computer (PC) Hardware Architecture	15
3.2	Processor Sockets, Generations, and Motherboard Chipsets	16
3.3	Memory Standards (DDR4 vs DDR5 Architectural Differences)	17
3.4	Motherboard and Cabinet Form Factor Standards (ATX, mATX, ITX)	17
3.5	Thermal Design Power (TDP) and Power Supply Sizing Economics	18
3.6	Web Technologies Stack: React.js, Bootstrap 5, Vite, LocalStorage	19
4	**PROBLEM FORMULATION AND REQUIREMENTS SPECIFICATION**	20
4.1	Mathematical Problem Formulation	20
4.2	Formal Compatibility Constraint Rules	21

CHAPTER NO.	TITLE	PAGE NO.
4.3	Functional Requirements (FR-01 to FR-10)	22
4.4	Non-Functional Requirements (NFR-01 to NFR-06)	24
4.5	System Assumptions and Operational Boundaries	25
5	**PROPOSED SYSTEM DESIGN AND WORKFLOW**	26
5.1	System Overview and Design Philosophy	26
5.2	Modular Structure of RigForge	27
5.3	End-to-End User Operational Workflow	28
5.4	Expected System Deliverables and Outputs	29
5.5	Error Prevention, UI Feedback, and Fallback Strategy	30
6	**SYSTEM ARCHITECTURE AND DESIGN**	31
6.1	High-Level Multi-Tier Client Architecture	31
6.2	Presentation Layer Component Hierarchy	32
6.3	Centralized State Management Pipeline (`BuilderContext`)	33
6.4	LocalStorage Persistence and Hydration Layer	34
6.5	System Data Flow and Sequence Logic	35
7	**CORE ALGORITHMS AND COMPUTATIONAL LOGIC**	36
7.1	Real-Time Compatibility Validation Algorithm	36
7.2	Dynamic Price Calculation and Configurable Tax (GST) Engine	38
7.3	Adaptive Budget Utilization and Visual Progress Heuristic	39
7.4	Multi-Attribute Search, Filter, and Sorting Algorithms	40
7.5	Build Comparison and Differencing Logic	41
8	**IMPLEMENTATION DETAILS**	42
8.1	Development Environment and Directory Organization	42
8.2	Data Schema and Hardware Catalog Design (`componentsData.js`)	43
8.3	Detailed Component Implementation Walkthrough	44
8.4	Custom CSS and Neon Cyberpunk Gaming Aesthetic	47

CHAPTER NO.	TITLE	PAGE NO.
8.5	User Interface Screenshot Register	48
9	**TESTING AND VALIDATION**	50
9.1	Testing Strategy and Quality Assurance Methodology	50
9.2	Unit Testing of Hardware Constraints	50
9.3	State Management and Storage Integration Testing	51
9.4	Comprehensive Test Case Matrix (TC-01 to TC-20)	52
9.5	User Acceptance Testing (UAT) and Edge Cases	55
10	**EXPERIMENTAL EVALUATION AND BENCHMARKING**	56
10.1	Evaluation Setup and Benchmarking Metrics	56
10.2	Performance, Bundle Size, and Load Time Analysis	56
10.3	Compatibility Checker Execution Latency	57
10.4	LocalStorage Reliability and Storage Quota Usage	58
10.5	Cross-Browser and Responsive Device Matrix	58
11	**RESULTS AND DISCUSSION**	59
11.1	Functional Verification of System Modules	59
11.2	In-Depth Analysis of Hardware Compatibility Scenarios	60
11.3	Budget Optimization and User Experience Feedback	61
11.4	Comparative Advantage Over Static Price Lists	62
12	**LIMITATIONS AND RISK ANALYSIS**	63
12.1	Market Price Volatility and Static Dataset Bounds	63
12.2	Advanced Physical Clearance Exclusions (RAM vs Cooler)	63
12.3	Browser Storage Quota and Cache Clearing Vulnerabilities	64
12.4	Risk Analysis and Mitigation Register	64
12.5	Consumer Guidance and Advisory Protocols	65
13	**FUTURE WORK**	66
13.1	Real-Time E-Commerce Web Scraping and Multi-Vendor Price Tracking	66

CHAPTER NO.	TITLE	PAGE NO.
13.2	AI-Powered Gaming FPS Prediction and Bottleneck Analyzer	66
13.3	Cloud User Authentication and Community Rig Sharing	67
13.4	Augmented Reality (AR) 3D Component Assembly Visualization	67
14	**LEARNING OUTCOMES**	68
14.1	Mastery of Modern React & Hook-Based State Management	68
14.2	Constraint-Satisfaction Engine Design in JavaScript	68
14.3	Responsive UI/UX Design with Bootstrap 5 and Custom CSS	69
14.4	Software Engineering, Testing, and Academic Documentation	69
15	**CONCLUSION**	70
16	**ACKNOWLEDGEMENT**	71
17	**REFERENCES**	72

ABSTRACT

Custom personal computer (PC) building has emerged as an essential skill for students, gamers, software engineers, and digital content creators. However, selecting compatible hardware components remains an error-prone task for beginners. Incompatible processor sockets (e.g., LGA1700 vs. AM4), conflicting memory generations (DDR4 vs. DDR5), mismatched chassis form factors (ATX motherboards in Micro-ATX cases), and undersized Power Supply Units (PSUs) frequently result in hardware failures, financial losses, and assembly delays. Furthermore, buyers struggle with financial tracking, such as managing dynamic budgets, factoring in government taxes (18% Goods and Services Tax in India), and comparing conflicting component alternatives.

To resolve these challenges, this project presents **RigForge**, a modern, responsive, client-side **Gaming PC Builder** web application developed for the academic course **Web Programming**. The application is engineered using **React.js, Bootstrap 5, JavaScript (ES6+), HTML5, and CSS3**, powered by the **Vite** frontend tooling ecosystem. RigForge models PC configuration as an interactive Constraint Satisfaction Problem (CSP). The system provides:

1. **Eight Core Hardware Categories:** Processors (CPUs), Graphics Cards (GPUs), Motherboards, Memory (RAM), Storage (NVMe M.2 SSDs), Power Supplies (PSUs), Cabinets, and CPU Coolers.

2. **Deterministic Real-Time Compatibility Engine:** Evaluates CPU-motherboard socket alignments, DDR4/DDR5 pin standards, chassis form factor support, cooler thermal brackets, and total system wattage against power supply headroom in sub-millisecond execution times.
3. **Live Price and Tax Calculator:** Automatically calculates subtotal, configurable 18% GST, and grand total in Indian Rupees (₹) using the standard Indian numbering system without page reloads.
4. **Adaptive Budget Planner:** Allows users to set target budgets via quick presets (₹50k, ₹75k, ₹1L, ₹1.5L) or custom entries, providing visual feedback through color-coded progress indicators and variance meters.
5. **Prebuilt Gaming Rig Profiles:** Offers one-click presets tuned for Budget Esports, 1080p Ultra, 1440p Powerhouse, and 4K Enthusiast configurations.
6. **Local Persistence and Comparison Matrix:** Persists builds across browser sessions using HTML5 LocalStorage, supports complete CRUD operations (save, view, rename, delete), and generates side-by-side comparison tables highlighting component specifications and cost variances.
7. **Print-Ready Specification Sheet:** Generates formatted hardware quotations that can be printed or exported directly to PDF via clean CSS print media queries.

RigForge operates entirely in the browser with zero paid API dependencies or mandatory server-side databases, making it an ideal, lightweight, robust project for academic evaluation and real-world consumer guidance.

Keywords: Gaming PC Builder, React.js, Bootstrap 5, Compatibility Checker, Hardware Configuration, Constraint Validation, LocalStorage, Vite, Indian Rupee (₹) Pricing, Budget Planner.

LIST OF TABLES

Table No.	Title	Page No.
Table 1	Component Categories and Compatibility Parameters in RigForge	16
Table 2	Hardware Form Factor Compatibility Matrix	18
Table 3	Functional Requirements Specification (FR-01 to FR-10)	22
Table 4	Non-Functional Requirements Specification (NFR-01 to NFR-06)	24
Table 5	RigForge System Technology Stack and Role Matrix	28
Table 6	Curated Prebuilt Gaming PC Preset Configurations	30
Table 7	Compatibility Verification Engine Rules and Severity Levels	37
Table 8	Hardware Catalog Sample Data Schema and Specification	44
Table 9	Comprehensive Unit and Integration Test Case Matrix	52
Table 10	Lighthouse Web Performance and Bundle Size Benchmark	56
Table 11	Compatibility Engine Execution Latency across Build Configurations	57
Table 12	Risk Analysis and Mitigation Register	64

LIST OF FIGURES

Figure No.	Title	Page No.
Figure 1	Conceptual Hardware Interaction and Compatibility Dependency Graph	15
Figure 2	High-Level Multi-Tier Client Architecture of RigForge	31
Figure 3	React Component Hierarchy and Data Flow Diagram	32
Figure 4	Centralized State Management Pipeline (`BuilderContext`)	33
Figure 5	End-to-End User Operational Flowchart	35
Figure 6	Compatibility Validation Logic and Power Consumption Decision Flow	38
Figure 7	Screenshot: Application Landing Page and Hero Section	48
Figure 8	Screenshot: Interactive PC Builder Workstation with Live Price Summary	48
Figure 9	Screenshot: Budget Planner Progress Bar and Compatibility Alert Panel	49
Figure 10	Screenshot: Side-by-Side Configuration Comparison Matrix	49
Figure 11	Screenshot: Printable Build Specification Sheet and Quotation Invoice	50

LIST OF SYMBOLS AND ABBREVIATIONS

Term / Symbol	Full Form / Description
AI	Artificial Intelligence
AIO	All-In-One Liquid Cooler
API	Application Programming Interface
ARGB	Addressable Red Green Blue (Lighting standard)
ATX	Advanced Technology eXtended (Motherboard / PSU Form Factor)
CPU	Central Processing Unit (Processor)
CRUD	Create, Read, Update, Delete
CSP	Constraint Satisfaction Problem
CSS	Cascading Style Sheets
DDR4 / DDR5	Double Data Rate Synchronous Dynamic RAM (4th / 5th Generation)
DIMM	Dual In-line Memory Module
DOM	Document Object Model
FPS	Frames Per Second
GPU	Graphics Processing Unit (Video Card)
GST	Goods and Services Tax (18% Statutory Tax in India)
HTML	HyperText Markup Language
INR (₹)	Indian Rupee (Official Currency of India)
JSON	JavaScript Object Notation
LGA	Land Grid Array (Intel CPU Socket Architecture)
mATX	Micro-ATX Form Factor
NVMe	Non-Volatile Memory Express (High-Speed Solid State Storage)
PCIe	Peripheral Component Interconnect Express
PSU	Power Supply Unit
RAM	Random Access Memory

Term / Symbol	Full Form / Description
SPA	Single-Page Application
TDP	Thermal Design Power (Measured in Watts)
UI / UX	User Interface / User Experience
VRAM	Video Random Access Memory
VRM	Voltage Regulator Module

CHAPTER 1: INTRODUCTION

1.1 Problem Statement and Motivation

In modern computing, personal desktop computers are indispensable tools for computer science education, software development, data science, artificial intelligence model training, 3D animation, and competitive gaming. While pre-assembled original equipment manufacturer (OEM) desktops exist, assembling a custom desktop PC provides substantial advantages:

- Higher computing performance per rupee spent.
- Complete freedom to select premium hardware parts.
- Modular upgradeability and simplified component replacement.
- Optimized thermal dissipation and superior acoustic characteristics.

However, designing a custom PC is a daunting task for beginners and undergraduate students. A personal computer is not a single monolith, but a tightly coupled ecosystem of eight interconnected subsystems:

1. Central Processing Unit (CPU)
2. Graphics Processing Unit (GPU)
3. Motherboard
4. Random Access Memory (RAM)
5. Storage (Solid State Drive / Hard Disk Drive)
6. Power Supply Unit (PSU)
7. Cabinet (Computer Chassis)
8. Central Processing Unit Cooler

Each of these subsystems operates under strict physical, electrical, and architectural constraints:

- **Processor Socket Incompatibility:** An Intel 13th/14th Generation Core processor requires an LGA1700 motherboard socket, whereas an AMD Ryzen 5000 processor requires an AM4 socket, and an AMD Ryzen 7000 processor requires an AM5 socket. Forcing an incompatible processor into a mismatched socket results in bent motherboard pins and permanent component destruction.
- **Memory Generation Conflict:** Motherboards exclusively support either DDR4 or DDR5 memory architectures. DDR4 and DDR5 memory modules have distinct physical notches, operational voltages (1.2V vs 1.1V), and pin counts (288 pins with differing key notches), making them physically and electrically incompatible.
- **Form Factor and Spatial Restrictions:** Standard Full ATX motherboards cannot be installed inside compact Micro-ATX (mATX) or Mini-ITX chassis due to missing standoff mounting points and insufficient physical volume.
- **Power Envelope Deficits:** High-performance GPUs and CPUs produce severe transient power spikes. Selecting an inadequate 450W PSU for a system demanding 550W under peak gaming load results in system instability, kernel panics, emergency shutdowns, and potential component damage.
- **Financial Uncertainty:** Consumers must calculate component prices manually, factor in an 18% Goods and Services Tax (GST) in the Indian context, track a rigid budget ceiling, and manually compare competing configurations across multiple retail browser tabs.

Manual validation using spreadsheets or paper notes is inefficient, prone to oversight, and inaccessible to non-technical users. There is a clear need for an automated, visual, beginner-friendly **Gaming PC Builder** web application that provides real-time compatibility validation, live price calculations in Indian Rupees (₹), interactive budget tracking, and local configuration persistence.

1.2 Objectives of the Project

The primary objective of this project is to develop and deploy **RigForge**, a responsive, modern single-page web application using **React.js, Bootstrap 5, JavaScript (ES6+), HTML5, and CSS3**.

The specific technical objectives are:

1. **Develop an Interactive Component Selection Workstation:** Implement an intuitive catalog spanning eight hardware categories, allowing users to browse, search, filter, select, replace, and remove components seamlessly.
2. **Implement a Deterministic Compatibility Checking Engine:** Construct an automated verification algorithm that inspects processor sockets, memory standards, motherboard chassis dimensions, and total system power consumption, flagging incompatibilities with explanatory warning alerts.

3. **Build a Real-Time Price and Tax Calculation System:** Engineer an automated price calculator that computes component subtotals, an optional configurable 18% GST addition, and a grand total in Indian Rupees (₹) formatted according to the Indian numbering system.
4. **Design an Adaptive Budget Planner:** Create an interactive budget monitor with preset milestones (₹50k, ₹75k, ₹1L, ₹1.5L) and custom input capabilities, featuring a dynamic, color-coded progress bar to visualize budget utilization and alert users to over-budget amounts.
5. **Provide Curated Prebuilt Rig Configurations:** Deliver four pre-configured, tested gaming builds (Budget Esports, 1080p Ultra, 1440p Powerhouse, and 4K Enthusiast) that can be loaded into the builder with a single click.
6. **Enable Local Storage Persistence:** Implement full CRUD (Create, Read, Update, Delete) operations using browser LocalStorage, allowing users to name, save, reload, rename, and delete configurations without requiring an external backend database.
7. **Construct a Side-by-Side Build Comparison Matrix:** Build a tabular comparison interface that highlights hardware specifications, pricing differences, power draw, and compatibility statuses across multiple configurations.
8. **Generate a Print-Friendly Quotation Sheet:** Develop a clean summary view that presents a complete component manifest and quotation invoice, ready for printing or exporting to PDF via CSS `@media print` stylesheets.

1.3 Scope of the Project

The scope of this project encompasses:

- A fully client-side single-page application built on the Vite + React.js framework.
- Modern, responsive UI design utilizing Bootstrap 5 grid systems and custom cyber-gaming styling.
- A comprehensive hardware dataset representing modern Intel, AMD, NVIDIA, MSI, ASUS, Corsair, Crucial, DeepCool, and Lian Li components with realistic market prices.
- Client-side persistence using the HTML5 Web Storage API (`localStorage`), guaranteeing privacy, instant response times, and zero server hosting expenses.

The project explicitly excludes:

- Mandatory server-side backends or paid cloud databases during initial evaluation.
- Live automated web scrapers connecting to e-commerce retailer APIs (due to API paywalls and rate limiting).
- Direct e-commerce payment gateway integrations or automated inventory fulfillment.

1.4 Organization of the Report

This project report is organized as follows:

- **Chapter 2 (Literature Review):** Reviews existing hardware configurators, compatibility engines, and client-side web application architectures.
- **Chapter 3 (Domain Area and Technical Background):** Examines PC hardware engineering, socket standards, power delivery, and the chosen software technologies.
- **Chapter 4 (Problem Formulation and Requirements):** Formulates the configuration challenge mathematically and details all functional and non-functional requirements.
- **Chapter 5 (Proposed System Design):** Details the system's operational design, core modules, user workflow, and error prevention strategies.
- **Chapter 6 (System Architecture and Design):** Explains the multi-tier client architecture, component hierarchy, and centralized state pipeline.
- **Chapter 7 (Core Algorithms and Computational Logic):** Details the mathematical and logical algorithms for compatibility verification, price calculation, budget tracking, and comparison.
- **Chapter 8 (Implementation Details):** Describes the directory structure, data schemas, code implementations, custom CSS, and UI screenshots.
- **Chapter 9 (Testing and Validation):** Details the testing strategy, unit test suite, integration verification, and a 20-point test case matrix.
- **Chapter 10 (Experimental Evaluation and Benchmarking):** Evaluates performance, bundle size, validation latency, and cross-browser reliability.
- **Chapter 11 (Results and Discussion):** Discusses functional verification, compatibility scenario demonstrations, and user feedback.
- **Chapter 12 (Limitations and Risk Analysis):** Analyzes technical constraints, price volatility risks, and consumer disclaimers.
- **Chapter 13 (Future Work):** Outlines future enhancements including live web scraping, AI FPS estimation, and cloud synchronization.
- **Chapter 14 (Learning Outcomes):** Summarizes technical competencies gained throughout the project.
- **Chapter 15 (Conclusion):** Concludes the project report.
- **Chapters 16 & 17:** Acknowledgement and academic references.

CHAPTER 2: LITERATURE REVIEW

2.1 Evolution of E-commerce Hardware Configurator Tools

Early computer retail websites in the late 1990s and early 2000s functioned primarily as static digital product catalogs. Consumers had to navigate through disjointed categories, write down hardware specifications on paper, and consult printed manuals or hardware enthusiast forums to confirm compatibility.

The introduction of dynamic web interfaces led to early configurators such as PCPartPicker. These platforms proved that client-side rule validation significantly decreases customer return rates and assembly failures. However, commercial platforms are often cluttered with external advertising, affiliate tracking scripts, complex user interfaces, and pricing schemes geared toward North American or European markets. For undergraduate students and emerging developers in India, these systems lack integration with local currency formats (Indian Rupees ₹), standard domestic taxation structures (18% GST), and compact, responsive interfaces suitable for mobile screens.

2.2 Survey of Compatibility Verification Approaches

Hardware compatibility checking in software systems generally falls into two paradigms:

1. **Heuristic Keyword Parsing:** Systems attempt to parse component names using regular expressions (e.g., searching for "AM4" or "DDR4" inside an arbitrary product title string). While simple to implement, keyword parsing is fragile. Brand names or descriptions with overlapping strings (such as a cooler labeled "AM4 and AM5 compatible" or a motherboard described as "Upgraded from DDR4") often produce false-positive errors.
2. **Deterministic Relational Attribute Matching:** Systems store hardware components as structured records with explicit compatibility fields (`socket` , `ramType` , `formFactor` , `tdp` , `wattage`). Compatibility is then computed through relational set theory and conditional logic.

RigForge adopts the deterministic relational attribute matching approach. By decoupling component titles from their engineering specifications, the validation engine operates deterministically, eliminating false-positive warnings and enabling reliable client-side execution.

2.3 Single-Page Applications (SPA) and Client-Side State Management

Early web configurators relied on multi-page architectures built with PHP or ASP.NET, where selecting a single component triggered a full HTTP POST request, server-side processing, and a complete browser page reload. This traditional approach introduces latency, disrupts user focus, and strains server resources.

Modern web engineering relies on Single-Page Applications (SPAs) powered by component-based declarative libraries like React.js. SPAs maintain an in-memory Virtual Document Object Model (Virtual DOM). When a user selects or removes a component, React computes the minimal necessary DOM diff and updates only the affected UI elements (such as the total price badge and compatibility alert) without reloading the page. Centralized state management—using tools like the React Context API—ensures that multiple disparate views (Builder Workstation, Live Cart Navbar, Summary Sheet, Comparison Table) remain synchronized from a single source of truth.

2.4 Research Gap and RigForge Project Positioning

While commercial platforms and academic toy models exist, there is a clear gap for an educational, open-source, modern web configurator that combines:

- A clean, modern gaming aesthetic (dark backgrounds with neon-blue accents) without visual clutter.
- Dedicated support for Indian pricing structures (₹ INR format, standard domestic tax calculations).
- A unified multi-constraint compatibility engine that checks sockets, memory standards, chassis sizes, and power budgets simultaneously.
- Zero mandatory server dependencies or paid APIs, running seamlessly via modern frontend tooling (Vite + React 18) and browser LocalStorage.

RigForge fills this gap by delivering an educational, robust, beginner-friendly web application suitable for academic demonstration and practical consumer planning.

CHAPTER 3: DOMAIN AREA AND TECHNICAL BACKGROUND

3.1 Personal Computer (PC) Hardware Architecture

A custom personal computer consists of distinct interconnected subsystems, each performing a specialized computational, structural, or electrical role:




Figure 1: Conceptual Hardware Interaction and Compatibility Dependency Graph

Table 1: Component Categories and Compatibility Parameters in RigForge

Category ID	Category Name	Primary Role	Critical Compatibility Attribute
`cpu`	Processor	Executes system logic and game physics	Socket type (`LGA1700` , `AM4` , `AM5`), TDP (Watts)
`gpu`	Graphics Card	Renders high-frame-rate 3D graphics	TDP (Watts), Recommended PSU (Watts)
`motherboard`	Motherboard	Central electrical backplane	Socket type, RAM standard (`DDR4` , `DDR5`), Form factor
`ram`	Memory	High-speed cache for running games	Generation standard (`DDR4` , `DDR5`), Speed (MHz)
`storage`	Solid State Storage	High-speed OS boot and game storage	Interface (`M.2 NVMe PCIe 4.0`), Capacity
`psu`	Power Supply	Converts AC mains to regulated DC	Continuous wattage rating (Watts), 80+ Efficiency
`case`	Cabinet Chassis	Structural housing and airflow duct	Supported motherboard form factors (`ATX` , `mATX`)
`cooler`	CPU Cooler	Dissipates processor thermal energy	Supported sockets, Thermal capacity rating (Watts)

3.2 Processor Sockets, Generations, and Motherboard Chipsets

The CPU socket is the physical interface between the processor and the motherboard. Sockets vary in pin count, physical pitch, retention mechanisms, and bus routing:

- **Intel LGA1700:** Land Grid Array with 1,700 contact pins. Compatible with Intel 12th, 13th, and 14th Generation Core processors (e.g., Core i5-13400F, Core i7-14700K). Used in B760 and Z790 chipsets.
- **AMD Socket AM4:** Pin Grid Array with 1,331 pins. Utilized by AMD Ryzen 1000 through 5000 series processors (e.g., Ryzen 5 5600). Paired with B550 and X570 motherboards.
- **AMD Socket AM5:** Land Grid Array with 1,718 contact pads. Introduced for AMD Ryzen 7000, 8000, and 9000 series processors (e.g., Ryzen 5 7600X, Ryzen 7 7800X3D). Requires B650 or X670 chipsets.

A processor cannot be installed on a motherboard with a differing socket standard.

3.3 Memory Standards (DDR4 vs DDR5 Architectural Differences)

- **DDR4 (Double Data Rate 4th Gen):** Operates at an industry standard of 1.2V with transfer speeds commonly ranging from 2400MHz to 3600MHz.
- **DDR5 (Double Data Rate 5th Gen):** Introduces on-die Error Correction Code (ODECC), dual independent 32-bit sub-channels per module, and an on-module Power Management Integrated Circuit (PMIC) operating at 1.1V. Speeds range from 4800MHz to over 6000MHz.

The physical key notch on DDR5 modules is placed closer to the center than on DDR4 modules. Motherboards are manufactured with dedicated DDR4 or DDR5 slots; they cannot accept both simultaneously.

3.4 Motherboard and Cabinet Form Factor Standards (ATX, mATX, ITX)

Table 2: Hardware Form Factor Compatibility Matrix

Motherboard Form Factor	Dimensions (Width x Height)	Expansion Slots	Fits Full ATX Case?	Fits Micro-ATX Case?
Full ATX	$305\text{ mm} \times 244\text{ mm}$305 mm × 244 mm (12.0" × 9.6"12.0" × 9.6")	Up to 7 PCIe slots	Yes	**No (Too tall)**
Micro-ATX (mATX)	$244\text{ mm} \times 244\text{ mm}$244 mm × 244 mm (9.6" × 9.6"9.6" × 9.6")	Up to 4 PCIe slots	Yes	Yes
Mini-ITX (MITX)	$170\text{ mm} \times 170\text{ mm}$170 mm × 170 mm (6.7" × 6.7"6.7" × 6.7")	1 PCIe slot	Yes	Yes

A compact Micro-ATX chassis cannot physically accommodate a standard Full ATX motherboard because the chassis lacks the required internal vertical height and motherboard tray standoff screw positions.

3.5 Thermal Design Power (TDP) and Power Supply Sizing Economics

Thermal Design Power (TDP) represents the maximum amount of heat generated by a computer chip that the cooling system is designed to dissipate under typical workloads. It also serves as a baseline indicator of electrical consumption:

- Modern high-performance CPUs consume between 65W and 125W (with boost spikes exceeding 200W).
- Mid-range to flagship GPUs consume between 75W and 320W.
- Peripheral motherboard circuitry, RAM modules, NVMe drives, RGB lighting, and cooling fans consume an estimated base load of 100W.

$$\text{Estimated Total Power Draw} = \text{TDP}_{\text{CPU}} + \text{TDP}_{\text{GPU}} + 100\text{W}$$
Estimated Total Power Draw = TDPCPU + TDPGPU + 100W

To prevent power supply overcurrent protection (OCP) shutdowns during transient spikes, the recommended PSU capacity includes a 30% safety headroom:

$$\text{Recommended PSU Capacity} = \text{Estimated Total Power Draw} \times 1.30$$
Recommended PSU Capacity = Estimated Total Power Draw × 1.30

3.6 Web Technologies Stack: React.js, Bootstrap 5, Vite, LocalStorage

- **React.js 18:** A declarative, component-based JavaScript library for building user interfaces. It uses hooks (`useState` , `useEffect` , `useMemo` , `useContext`) to build reactive, modular, state-driven interfaces.
- **Bootstrap 5.3:** A responsive CSS framework providing a 12-column grid system, utility classes, and accessible UI controls, styled here using dark-mode variables.
- **Bootstrap Icons 1.11:** High-quality vector iconography used to improve visual hierarchy and readability across hardware categories.
- **Vite 5.2:** A next-generation frontend development tool and build system featuring native ES module imports and instant Hot Module Replacement (HMR).
- **HTML5 Web Storage API (`localStorage`):** Provides synchronous key-value storage within the browser sandbox, allowing configurations to persist across reloads without requiring a remote database.

CHAPTER 4: PROBLEM FORMULATION AND REQUIREMENTS SPECIFICATION

4.1 Mathematical Problem Formulation

The custom PC configuration challenge can be modeled as a **Constraint Satisfaction Problem (CSP)** defined by the tuple:

$$P = \langle X, D, C, f_{\text{cost}}, f_{\text{budget}} \rangle$$
P = ⟨X, D, C, fcost, fbudget⟩

Where:

- $X = \{x_{\text{cpu}}, x_{\text{gpu}}, x_{\text{mb}}, x_{\text{ram}}, x_{\text{ssd}}, x_{\text{psu}}, x_{\text{case}}, x_{\text{cooler}}\}$X = {xcpu, xgpu, xmb, xram, xssd, xpsu, xcase, xcooler} is the set of 8 component category variables.
- $D = \{D_{\text{cpu}}, D_{\text{gpu}}, \ \ldots, D_{\text{cooler}}\}$D = {Dcpu, Dgpu, ... , Dcooler} represents the domains of available hardware items for each variable.

- Each item $i \in D_k$ i ∈ Dk is an object with attributes:
  $i = \langle \text{id, name, brand, price, socket, ramType, formFactor, tdp, wattage, specs} \rangle$
  i = ⟨id, name, brand, price, socket, ramType, formFactor, tdp, wattage, specs⟩
- $C = \{C_{\text{socket}}, C_{\text{memory}}, C_{\text{formfactor}}, C_{\text{cooler_socket}}, C_{\text{power}}\}$C = {Csocket, Cmemory, Cformfactor , Ccooler_socket, Cpower} is the set of hard physical and electrical compatibility constraints.
- A candidate configuration is an assignment vector: $S = (x_{\text{cpu}} \leftarrow a, x_{\text{gpu}} \leftarrow b, \ \ldots, x_{\text{cooler}} \leftarrow h)$S = (xcpu ← a, xgpu ← b, … , xcooler ← h)
- A configuration SS is **feasible** if and only if all constraints in CC evaluate to true:

$$\text{Feasible}(S) \iff \bigwedge_{c \in C} c(S) = \text{True}$$

Feasible(S) ⟺ c∈C⋀ c(S) = True

4.2 Formal Compatibility Constraint Rules

1. Processor and Motherboard Socket Alignment (C_{socket} Csocket)

If both a CPU and a Motherboard are assigned, their socket interfaces must match:
$C_{\text{socket}}(S) = (\text{socket}(x_{\text{cpu}}) = \text{socket}(x_{\text{mb}}))$Csocket(S) = (socket(xcpu) = socket(xmb))

2. Motherboard and Memory Standard Alignment (C_{memory} Cmemory)

If both a Motherboard and RAM are selected, the RAM generation must be supported by the motherboard's memory interface: $C_{\text{memory}}(S) = (\text{ramType}(x_{\text{ram}}) \subseteq \text{ramType}(x_{\text{mb}}))$Cmemory(S) = (ramType(xram) ⊆ ramType(xmb))

3. Motherboard and Cabinet Form Factor Compatibility ($C_{\text{formfactor}}$ Cformfactor)

The physical dimensions of the motherboard must be supported by the cabinet's internal mounting brackets: $C_{\text{formfactor}}(S) = (\text{formFactor}(x_{\text{mb}}) \in \text{supportedFormFactors}(x_{\text{case}}))$Cformfactor(S) = (formFactor(xmb) ∈ supportedFormFactors(xcase))

4. CPU Cooler Socket Mounting Bracket Support ($C_{\text{cooler_socket}}$ Ccooler_socket)

The cooler's included mounting brackets must support the processor's socket architecture:
$C_{\text{cooler_socket}}(S) = (\text{socket}(x_{\text{cpu}}) \in \text{supportedSockets}(x_{\text{cooler}}))$Ccooler_socket(S) = (socket(xcpu) ∈ supportedSockets(xcooler))

5. Power Supply Electrical Envelope (C_{power} Cpower)

The continuous output capacity of the PSU must meet or exceed the total estimated electrical load of the system: $P_{\text{est}}(S) = \text{tdp}(x_{\text{cpu}}) + \text{tdp}(x_{\text{gpu}}) + 100$Pest(S) = tdp(xcpu) + tdp(xgpu) + 100
$C_{\text{power}}(S) = (\text{wattage}(x_{\text{psu}}) \geq P_{\text{est}}(S))$Cpower(S) = (wattage(xpsu) ≥ Pest(S))

4.3 Functional Requirements (FR-01 to FR-10)

Table 3: Functional Requirements Specification

Requirement ID	Requirement Name	Description and Acceptance Criteria
FR-01	Categorized Hardware Catalog	The system shall display eight distinct hardware categories with specifications, images, brand badges, and prices in Indian Rupees (₹).
FR-02	Interactive Component Selection	Users shall be able to select, replace, or remove components in any category with immediate updates to state.
FR-03	Real-Time Compatibility Engine	The system shall validate socket, memory, form factor, and power rules immediately upon any selection change, displaying clear alerts.
FR-04	Live Price and Tax Engine	The system shall automatically calculate subtotal, optional 18% GST, and grand total in INR without page reloads.
FR-05	Interactive Budget Planner	Users shall be able to set a target budget via presets (₹50k, ₹75k, ₹1L, ₹1.5L) or custom entries, tracking utilization via a dynamic progress bar.
FR-06	Prebuilt Rig Loading	The system shall provide four curated gaming PC configurations that can be loaded into the builder with a single click.
FR-07	Search, Filter, and Sort	Users shall be able to search components by keyword, filter by brand, and sort listings by price in ascending or descending order.
FR-08	LocalStorage Persistence	Users shall be able to name, save, reload, rename, and delete custom configurations using browser LocalStorage.
FR-09	Build Comparison Matrix	The system shall render a side-by-side comparison table contrasting components, prices, power draw, and compatibility across builds.
FR-10	Print-Ready Quotation Sheet	The system shall provide a dedicated summary view optimized for printing or PDF export via CSS print media queries.

4.4 Non-Functional Requirements (NFR-01 to NFR-06)

Table 4: Non-Functional Requirements Specification

Requirement ID	Requirement Name	Metric / Benchmark Standard
NFR-01	Real-Time Performance	Compatibility checks and price recalculations must execute in under 16 milliseconds ($< 16\ \text{ms}$ < 16 ms) to maintain a smooth 60 FPS UI.
NFR-02	Responsive Layout	The application must render cleanly across mobile ($< 768\text{px}$ < 768px), tablet ($768\text{px} - 991\text{px}$768px – 991px), and desktop ($\geq 992\text{px}$≥ 992px) viewports.
NFR-03	Aesthetic Polish	The interface must follow a cohesive dark cyber-gaming visual theme using charcoal backgrounds (`#0a0d14`), clean cards, and neon-blue accents.
NFR-04	Client-Side Independence	The initial release must function fully in modern web browsers without requiring external paid APIs or backend databases.
NFR-05	Image Fallback Gracefulness	The UI must display an SVG placeholder containing the brand and category name if an external product image fails to load.
NFR-06	Accessibility and Semantic HTML	Interactive controls must feature descriptive ARIA labels, semantic buttons, and keyboard accessibility.

4.5 System Assumptions and Operational Boundaries

1. **Academic Dataset Scope:** Component prices and specifications are curated sample values for academic simulation and consumer demonstration.
2. **Single Component Per Category:** The baseline system supports one component per category (e.g., one CPU, one motherboard, one primary RAM kit).
3. **Browser Sandbox Environment:** LocalStorage persistence is scoped to the user's local browser profile and domain origin. Clearing browser caches will reset saved data.

CHAPTER 5: PROPOSED SYSTEM DESIGN AND WORKFLOW

5.1 System Overview and Design Philosophy

RigForge is designed as a modular, responsive single-page application built on three foundational principles:

1. **Transparency:** Every compatibility alert, wattage estimation, and price calculation is derived from clear, visible rules rather than opaque heuristics.

2. **Immediacy:** State changes trigger instant visual updates via React's reactive data-binding architecture, avoiding page reloads or jarring layout shifts.
3. **Simplicity and Accessibility:** The interface avoids visual clutter, providing clear typography, intuitive icons, and streamlined navigation accessible to beginners and technical evaluators alike.

5.2 Modular Structure of RigForge

The application is organized into six core functional modules:

```
+-------------------------------------------------------------------------+
|                            RIGFORGE CORE                                |
+-------------------------------------------------------------------------+
|  [Catalog & Filtering Module]     --> Browsing, searching, brand filters |
|  [Hardware Selection Module]      --> Selecting, replacing, clearing     |
|  [Compatibility Engine Module]    --> Sockets, RAM, case, PSU wattage    |
|  [Price & Tax Calculator Module]  --> Subtotal, 18% GST toggle, totals   |
|  [Budget Planner Module]          --> Preset milestones, progress bar    |
|  [Persistence & Export Module]    --> LocalStorage CRUD, print summaries |
+-------------------------------------------------------------------------+
```

Table 5: RigForge System Technology Stack and Role Matrix

Technology	Version	Purpose in RigForge
React.js	18.3.1	Core UI library for declarative, component-based rendering
Bootstrap	5.3.3	Responsive 12-column grid system, cards, forms, and modals
Bootstrap Icons	1.11.3	Scalable vector icons for categories and status badges
Vite	5.2.11	High-speed frontend build tool and local development server
React Router	6.23.1	Client-side routing between Home, Builder, Saved, Compare, Summary
HTML5 LocalStorage	Standard	Persistent key-value client storage across browser sessions

5.3 End-to-End User Operational Workflow

The operational workflow guides users from initial concept to a final, verified specification sheet:




Figure 5: End-to-End User Operational Flowchart

5.4 Expected System Deliverables and Outputs

1. **Interactive PC Builder:** A 2-column responsive workspace featuring a component selection panel alongside a sticky financial and compatibility sidebar.
2. **Prebuilt Gaming Rigs:** Four ready-to-load configurations: *Table 6: Curated Prebuilt Gaming PC Preset Configurations* | Preset ID | Rig Title | Target Resolution & FPS | Key Hardware Highlights | Estimated Cost | | :--- | :--- | :--- | :--- | :--- | | `preset-budget` | **Budget Esports Rig** | 1080p Esports (100+ FPS) | Ryzen 5 5600, RX 6600 8GB, 16GB DDR4, 550W PSU | ₹51,893 | | `preset-1080p` | **1080p Ultra Gaming PC** | 1080p AAA (80+ FPS) | Core i5-13400F, RTX 4060 8GB, 16GB DDR4, 650W PSU | ₹81,893 | | `preset-midrange` | **1440p Powerhouse** | 1440p Ultra (100+ FPS) | Ryzen 5 7600X, RTX 4070 Super 12GB, 32GB DDR5, 750W PSU | ₹1,35,792 | | `preset-highend` | **4K Enthusiast PC** | 4K Ultra (90+ FPS) | Core i7-14700K, RTX 4080 Super 16GB, 32GB DDR5, 850W PSU | ₹2,30,492 |
3. **Saved Builds Manager:** A dedicated interface for managing saved configurations with load, rename, and delete actions.
4. **Comparison Matrix:** A side-by-side tabular view contrasting two configurations.

5. **Printable Build Specification Sheet:** A clean, print-formatted quotation ready for physical output or PDF saving.

5.5 Error Prevention, UI Feedback, and Fallback Strategy

- **Image Fallback Handling:** If an external hardware image fails to load (e.g., due to an ad-blocker or network timeout), an `onError` event handler swaps the source with an inline SVG placeholder displaying the product brand and category.
- **Defensive State Deserialization:** The `storage.js` utility wraps all `localStorage.getItem()` calls inside `try-catch` blocks, falling back gracefully to empty arrays if stored data is corrupted.
- **Non-Negative Value Enforcers:** All financial calculations use `Math.max(0, ...)` to ensure prices and budget counters never display negative values.

CHAPTER 6: SYSTEM ARCHITECTURE AND DESIGN

6.1 High-Level Multi-Tier Client Architecture

RigForge employs a multi-tier client architecture that cleanly separates data, state management, UI components, and presentation views:



Figure 2: High-Level Multi-Tier Client Architecture of RigForge

6.2 Presentation Layer Component Hierarchy

The UI component tree is organized into reusable components and routed pages:

```
App.jsx (Root Routing & Toast Wrapper)
 ├── Navbar.jsx (Global Navigation & Active Cart Counter)
 ├── ScrollToTop.jsx (Scroll Reset on Navigation)
 ├── ToastBanner.jsx (Global Toast Feedback Alerts)
 ├── Routes:
 │    ├── Route "/": Home.jsx
 │    │    ├── HeroSection.jsx (Hero Banner & Call-to-Actions)
 │    │    ├── WorkflowSteps (4-Step Explanatory Guide)
 │    │    ├── PresetRigsShowcase (Prebuilt PC Cards)
 │    │    └── PopularComponents (Trending Hardware Grid)
 │    ├── Route "/builder": PCBuilder.jsx
 │    │    ├── ComponentSelector.jsx (Category Pills & Hardware Grid)
 │    │    │    ├── SearchFilters.jsx (Search Bar, Brand Filter, Sort)
 │    │    │    └── ComponentCard.jsx (Hardware Item Display & Badges)
 │    │    └── Sticky Sidebar:
 │    │         ├── PriceSummary.jsx (Live Subtotal, GST Switch, Actions)
 │    │         ├── BudgetPlanner.jsx (Presets, Custom Input, Progress Bar)
 │    │         └── CompatibilityChecker.jsx (Power Metrics & Alerts)
 │    ├── Route "/saved": SavedConfigurations.jsx
 │    │    └── SavedBuilds.jsx (Saved Cards, Rename, Delete, Load)
 │    ├── Route "/compare": CompareBuilds.jsx
 │    │    └── BuildComparison.jsx (Dropdown Selectors & Diff Matrix)
 │    └── Route "/summary": BuildSummary.jsx
 │         └── PrintableSpecificationSheet (Printable Quotation Sheet)
 └── Footer.jsx (Course Details, Disclaimers, Tech Stack Badges)
```

Figure 3: React Component Hierarchy and Data Flow Diagram

6.3 Centralized State Management Pipeline (`BuilderContext`)

To prevent prop drilling across nested components, RigForge centralizes application state inside `BuilderContext.jsx`. The context exposes:

- **State Variables:** `selectedComponents`, `buildName`, `budget`, `includeGst`, `savedBuilds`, and `toastMessage`.
- **Action Functions:** `selectComponent()`, `removeComponent()`, `clearBuild()`, `loadPreset()`, `loadSavedBuild()`, `saveCurrentBuild()`, `removeSavedBuild()`, and `updateSavedBuildName()`.
- **Derived Computations (`useMemo`):** Automatically recomputes `totals`, `compatibility`, and `budgetAnalysis` whenever relevant state variables change.




Figure 4: Centralized State Management Pipeline (`BuilderContext`)

6.4 LocalStorage Persistence and Hydration Layer

State persistence is managed through the `storage.js` utility module, which interfaces directly with the browser's `window.localStorage` API:

- `current_active_build`: Automatically serialized via a `useEffect` hook on every state change, restoring the user's active session upon page refresh.
- `gaming_pc_builder_saved_builds`: An array of user-saved configurations containing unique IDs, names, component manifests, prices, and timestamps.
- `gaming_pc_builder_preferences`: Stores user preferences such as target budgets and GST toggle settings.

CHAPTER 7: CORE ALGORITHMS AND COMPUTATIONAL LOGIC

7.1 Real-Time Compatibility Validation Algorithm

The compatibility engine inspects the active hardware selection and returns a structured diagnostic report:

```
ALGORITHM: CheckHardwareCompatibility(components)
INPUT: components object { cpu, gpu, motherboard, ram, psu, case, cooler }
OUTPUT: result { isCompatible: boolean, issues: array, estimatedPower: number,
recommendedPsu: number }

BEGIN
    issues = []

    // Step 1: Calculate power consumption
    cpuTdp = (components.cpu != null) ? components.cpu.tdp : 65
    gpuTdp = (components.gpu != null) ? components.gpu.tdp : 0
    baseDraw = (components.cpu != null || components.gpu != null) ? 100 : 0
    estimatedPower = cpuTdp + gpuTdp + baseDraw
    recommendedPsu = ROUND(estimatedPower * 1.30)

    // Step 2: Validate CPU and Motherboard socket match
    IF components.cpu != null AND components.motherboard != null THEN
        IF components.cpu.socket != components.motherboard.socket THEN
            issues.APPEND({
                type: 'error',
                severity: 'danger',
                category: 'Processor & Motherboard',
                message: 'Socket Incompatibility: ' + components.cpu.name +
                         ' (' + components.cpu.socket + ') does not match ' +
                         components.motherboard.name + ' (' + components.motherboard.socket
+ ').'
            })
        END IF
    END IF

    // Step 3: Validate Motherboard and RAM generation match
    IF components.motherboard != null AND components.ram != null THEN
        IF NOT components.motherboard.ramType.INCLUDES(components.ram.ramType) THEN
            issues.APPEND({
                type: 'error',
                severity: 'danger',
                category: 'Motherboard & RAM',
                message: 'Memory Standard Conflict: ' + components.motherboard.name +
                         ' requires ' + components.motherboard.ramType + ', but ' +
                         components.ram.name + ' is ' + components.ram.ramType + '.'
            })
        END IF
    END IF

    // Step 4: Validate Motherboard form factor and Case fit
    IF components.motherboard != null AND components.case != null THEN
```

```
        IF components.motherboard.formFactor NOT IN components.case.supportedFormFactors
THEN
            issues.APPEND({
                type: 'error',
                severity: 'danger',
                category: 'Cabinet & Motherboard Size',
                message: 'Form Factor Mismatch: ' + components.case.name +
                         ' does not fit a ' + components.motherboard.formFactor + '
motherboard.'
            })
        END IF
    END IF

    // Step 5: Validate Cooler socket bracket and thermal capacity
    IF components.cpu != null AND components.cooler != null THEN
        IF components.cpu.socket NOT IN components.cooler.supportedSockets THEN
            issues.APPEND({
                type: 'error',
                severity: 'danger',
                category: 'CPU Cooler Mounting',
                message: 'Mounting Bracket Mismatch: ' + components.cooler.name +
                         ' does not support socket ' + components.cpu.socket + '.'
            })
        END IF
        IF components.cooler.tdpRating < components.cpu.tdp THEN
            issues.APPEND({
                type: 'warning',
                severity: 'warning',
                category: 'Thermal Throttling Advisory',
                message: 'High Thermal Load: Cooler rated for ' +
components.cooler.tdpRating +
                         'W may run hot under ' + components.cpu.tdp + 'W CPU loads.'
            })
        END IF
    END IF

    // Step 6: Validate Power Supply capacity
    IF components.psu != null THEN
        IF components.psu.wattage < estimatedPower THEN
            issues.APPEND({
                type: 'error',
                severity: 'danger',
                category: 'Power Supply Deficit',
                message: 'Critical Power Deficit: Estimated load of ~' + estimatedPower +
                         'W exceeds ' + components.psu.name + ' (' + components.psu.wattage
+ 'W).'
```

```
            })
        ELSE IF components.psu.wattage < recommendedPsu THEN
            issues.APPEND({
                type: 'warning',
                severity: 'warning',
                category: 'PSU Headroom Advisory',
                message: 'Low Power Headroom: System draw is ~' + estimatedPower +
                         'W. Recommended capacity is ' + recommendedPsu + 'W+ for peak
safety.'
            })
        END IF
    END IF

    hasErrors = issues.EXISTS(item => item.type == 'error')
    hasWarnings = issues.EXISTS(item => item.type == 'warning')

    RETURN {
        isCompatible: NOT hasErrors,
        hasWarnings: hasWarnings,
        estimatedPower: estimatedPower,
        recommendedPsuWattage: recommendedPsu,
        issues: issues
    }
END
```

Table 7: Compatibility Verification Engine Rules and Severity Levels

Rule ID	Checked Components	Evaluated Condition	Severity Level	Resulting User Notification
CR-01	CPU + Motherboard	`cpu.socket == mb.socket`	`DANGER (Error)`	Physical socket mismatch; system cannot be assembled.
CR-02	Motherboard + RAM	`mb.ramType.includes(ram.ramType)`	`DANGER (Error)`	Memory generation conflict (DDR4 vs DDR5); pins will not fit.
CR-03	Motherboard + Case	`case.supported.includes(mb.formFactor)`	`DANGER (Error)`	Motherboard dimensions exceed internal cabinet clearance.
CR-04	CPU + Cooler	`cooler.supportedSockets.includes(cpu.socket)`	`DANGER (Error)`	Cooler mounting bracket incompatible with CPU socket.
CR-05	CPU + Cooler	`cooler.tdpRating >= cpu.tdp`	`WARNING (Advisory)`	Thermal capacity warning; CPU may throttle under heavy loads.
CR-06	System + PSU	`psu.wattage >= estimatedPower`	`DANGER (Error)`	Inadequate power supply; risk of system crashes under load.
CR-07	System + PSU	`psu.wattage >= recommendedPsu`	`WARNING (Advisory)`	Minimal power headroom; recommend 30% headroom for transient spikes.

7.2 Dynamic Price Calculation and Configurable Tax (GST) Engine

Price calculations use functional array reducers and non-negative boundaries:

$$\text{Subtotal} = \sum_{k \in X} \max(0, \text{Price}(x_k))$$

Subtotal = k∈X∑ max(0, Price(xk))

$$\text{GST Amount} = \begin{cases} \text{Round}(\frac{\text{Subtotal} \times 18}{100}) & \text{if includeGst=True} \\ 0 & \text{if includeGst=False} \end{cases}$$

```
GST Amount = {Round (100Subtotal×18)0if includeGst = Trueif includeGst = False
```

$$\text{Grand Total} = \text{Subtotal} + \text{GST Amount}$$

Grand Total = Subtotal + GST Amount

Prices are formatted into the Indian numbering system using `toLocaleString('en-IN')`:

$$\text{Formatted String} = \text{"₹"} + \text{GrandTotal.toLocaleString}(\text{'en-IN'})$$

Formatted String = "₹" + GrandTotal.toLocaleString('en-IN')

For example, a raw integer total of `135792` is automatically formatted as `₹1,35,792`.

7.3 Adaptive Budget Utilization and Visual Progress Heuristic

The budget planner calculates financial utilization and determines visual feedback states:

$$\text{Variance} = \text{Budget} - \text{Grand Total}$$

Variance = Budget − Grand Total

$$\text{Actual Percentage} = \begin{cases} \left(\frac{\text{Grand Total}}{\text{Budget}}\right) \times 100 & \text{if Budget} > 0 \\ 0 & \text{otherwise} \end{cases}$$

```
Actual Percentage = {(BudgetGrand Total) × 1000if Budget > 0otherwise
```

$$\text{Clamped Percentage} = \min(100, \text{Actual Percentage})$$

Clamped Percentage = min(100, Actual Percentage)

The progress bar styling is determined as follows:

- **Safe Zone ($\leq 85\%$≤ 85%):** Green gradient (`progress-bar-glow-green`), badge displays "Within Budget".
- **Caution Zone ($85\% - 100\%$85% – 100%):** Amber gradient (`progress-bar-glow-yellow`), badge displays "Near Limit".
- **Deficit Zone ($> 100\%$> 100%):** Red pulsing gradient (`progress-bar-glow-red`), badge displays "Over Budget!", showing the exact deficit: $\text{Over Amount} = \text{Grand Total} - \text{Budget}$
  Over Amount = Grand Total − Budget

7.4 Multi-Attribute Search, Filter, and Sorting Algorithms

The catalog filtering engine processes search queries, brand selections, and sorting orders in a single pipeline:

```
javascript
const filteredComponents = useMemo(() => {
  let result = [...categoryData];

  // 1. Text Search Filter (Matches name, brand, or specifications)
  if (searchTerm.trim()) {
    const query = searchTerm.toLowerCase();
    result = result.filter(item =>
      item.name.toLowerCase().includes(query) ||
      (item.brand && item.brand.toLowerCase().includes(query)) ||
      (item.specs && item.specs.toLowerCase().includes(query))
    );
  }

  // 2. Brand Category Filter
  if (selectedBrand !== 'all') {
    result = result.filter(item => item.brand === selectedBrand);
  }

  // 3. Price Sorting Heuristic
  if (sortBy === 'price-asc') {
    result.sort((a, b) => a.price - b.price);
  } else if (sortBy === 'price-desc') {
    result.sort((a, b) => b.price - a.price);
  }

  return result;
}, [categoryData, searchTerm, selectedBrand, sortBy]);
```

7.5 Build Comparison and Differencing Logic

The comparison engine takes two builds (B_1 B1 and B_2 B2), extracts their component manifests, and highlights differences:

- For each category $k \in \text{CATEGORIES}$k ∈ CATEGORIES, compare IDs: $\text{IsDifferent}(k) = (B_1.\text{components}[k].\text{id} \neq B_2.\text{components}[k].\text{id})$IsDifferent(k) = (B1 .components[k].id □= B2.components[k].id)
- When `IsDifferent` evaluates to true, the table row renders with a highlighted cyan accent border (`border-start border-3 border-info`), helping users spot hardware variations across configurations.

CHAPTER 8: IMPLEMENTATION DETAILS

8.1 Development Environment and Directory Organization

RigForge is organized into a clean, modular directory structure:

```
d:\Downloads\web program\
├── package.json              # Project dependencies and run scripts
├── vite.config.js            # Vite build configuration with React plugin
├── index.html                # Main entry HTML file with Google Gaming Fonts
├── preview.html              # Standalone interactive zero-install preview
├── README.md                 # Setup and run instructions
├── PROJECT_REPORT.md         # Academic project report documentation
├── public/
│   └── favicon.svg           # Neon gaming rig SVG brand icon
└── src/
    ├── main.jsx              # React DOM mounting
    ├── App.jsx               # Application routes and layout
    ├── index.css             # Dark gaming cyber theme styling
    ├── context/
    │   └── BuilderContext.jsx# React Context for cross-page state
    ├── data/
    │   ├── componentsData.js # 8 component categories with specs & prices
    │   └── presetBuilds.js   # 4 curated gaming PC configurations
    ├── utils/
    │   ├── priceCalculator.js# INR currency formatting & tax logic
    │   ├── compatibilityChecker.js # Sockets, RAM, case & PSU checks
    │   └── storage.js        # LocalStorage persistence utility
    ├── components/
    │   ├── Navbar.jsx        # Navigation bar with active build counter
    │   ├── Footer.jsx        # Academic footer with tech badges
    │   ├── HeroSection.jsx   # Landing banner with CTA buttons
    │   ├── ComponentCard.jsx # Hardware product card with image & badges
    │   ├── ComponentSelector.jsx # Category pills, search & hardware grid
    │   ├── PriceSummary.jsx  # Real-time subtotal, GST & grand total
    │   ├── BudgetPlanner.jsx # Budget presets, custom input & progress bar
    │   ├── CompatibilityChecker.jsx # Real-time hardware validation
    │   ├── SavedBuilds.jsx   # Saved builds list with load/delete
    │   ├── BuildComparison.jsx # Side-by-side comparison table
    │   └── SearchFilters.jsx # Search by name/brand & price sort
    └── pages/
        ├── Home.jsx          # Landing page
        ├── PCBuilder.jsx     # Main builder workstation
        ├── SavedConfigurations.jsx # Saved builds manager
        ├── CompareBuilds.jsx # Side-by-side comparison page
        └── BuildSummary.jsx  # Printable specification sheet
```

8.2 Data Schema and Hardware Catalog Design (`componentsData.js`)

Table 8: Hardware Catalog Sample Data Schema and Specification

Unique ID	Category	Component Name	Brand	Price (₹)	Key Specifications	Compatibility Attributes
cpu-1	Processor	AMD Ryzen 5 5600	AMD	₹11,499	6 Cores, 12 Threads, 4.4 GHz, 35MB Cache	Socket: AM4, RAM: DDR4, TDP: 65W
cpu-2	Processor	Intel Core i5-13400F	Intel	₹17,999	10 Cores (6P+4E), 16 Threads, 4.6 GHz	Socket: LGA1700, RAM: DDR4/DDR5, TDP: 65W
cpu-3	Processor	AMD Ryzen 5 7600X	AMD	₹19,899	6 Cores, 12 Threads, 5.3 GHz, PCIe 5.0	Socket: AM5, RAM: DDR5, TDP: 105W
cpu-4	Processor	Intel Core i7-14700K	Intel	₹36,499	20 Cores (8P+12E), 28 Threads, 5.6 GHz	Socket: LGA1700, RAM: DDR4/DDR5, TDP: 125W
gpu-2	Graphics Card	Sapphire Radeon RX 6600	Sapphire	₹19,999	8GB GDDR6, 128-bit, 1792 Stream Processors	TDP: 132W, Rec. PSU: 500W
gpu-3	Graphics Card	MSI GeForce RTX 4060	MSI	₹28,999	8GB GDDR6, DLSS 3.5, Ray Tracing, 3072 Cores	TDP: 115W, Rec. PSU: 550W
gpu-4	Graphics Card	Gigabyte RTX 4070 Super	Gigabyte	₹58,999	12GB GDDR6X, 192-bit, 7168 CUDA Cores	TDP: 220W, Rec. PSU: 650W
mb-1	Motherboard	MSI B550M PRO-VDH WiFi	MSI	₹9,499	Micro-ATX, 4x DDR4 DIMM, PCIe 4.0, WiFi	Socket: AM4, RAM: DDR4, Size: Micro-ATX
mb-2	Motherboard	ASUS Prime B760M-A WiFi	ASUS	₹13,999	Micro-ATX, 4x DDR4 slots, Dual M.2 Gen4	Socket: LGA1700, RAM: DDR4, Size: Micro-ATX
mb-3	Motherboard	Gigabyte B650 Gaming X AX	Gigabyte	₹17,499	Full ATX, 4x DDR5 slots, Triple M.2, WiFi 6E	Socket: AM5, RAM: DDR5, Size: Full ATX
ram-1	Memory	Corsair Vengeance 16GB (2x8)	Corsair	₹3,499	DDR4, 3200MHz, CL16, Aluminum spreader	Standard: DDR4, Capacity: 16GB

Unique ID	Category	Component Name	Brand	Price (₹)	Key Specifications	Compatibility Attributes
`ram-4`	Memory	Corsair Vengeance 32GB (2x16)	Corsair	₹10,499	DDR5, 6000MHz, CL30 AMD EXPO & XMP	Standard: DDR5, Capacity: 32GB
`psu-1`	Power Supply	Deepcool PK550D 550W Bronze	DeepCool	₹3,499	550W, 80 Plus Bronze, Flat Black Cables	Wattage: 550W, Efficiency: 80+ Bronze
`psu-3`	Power Supply	Corsair RM750e 750W Gold	Corsair	₹8,999	750W, 80+ Gold, ATX 3.0, Fully Modular	Wattage: 750W, Efficiency: 80+ Gold
`case-1`	Cabinet	Ant Esports ICE-100 Mini	Ant Esports	₹2,999	Micro-ATX Mini Tower, 3x ARGB Fans	Supported: ['Micro-ATX', 'Mini-ITX']
`case-2`	Cabinet	MSI MAG Forge 120R ATX	MSI	₹4,399	Mid-Tower ATX, 4x 120mm Fans, Mesh Front	Supported: ['ATX', 'Micro-ATX', 'Mini-ITX']
`cooler-2`	CPU Cooler	Deepcool AG400 ARGB Tower	DeepCool	₹1,899	4 Heatpipes, 120mm PWM Fan, 220W TDP	Sockets: ['LGA1700', 'AM4', 'AM5']

8.3 Detailed Component Implementation Walkthrough

1. Global Context State Management (`src/context/BuilderContext.jsx`)

`BuilderContext.jsx` provides application-wide state management. It initializes state by hydrating saved data from LocalStorage, computes derived metrics using `useMemo`, and exports action handlers:

```javascript
export const BuilderProvider = ({ children }) => {
  const initialPrefs = getUserPreferences();

  // Primary active selection state
  const [selectedComponents, setSelectedComponents] = useState(() => {
    const saved = localStorage.getItem('current_active_build');
    if (saved) {
      try { return JSON.parse(saved); } catch { return {}; }
    }
    return {};
  });

  const [buildName, setBuildName] = useState('My Custom Gaming Rig');
  const [budget, setBudget] = useState(initialPrefs.budget || 100000);
  const [includeGst, setIncludeGst] = useState(initialPrefs.includeGst || false);
  const [savedBuilds, setSavedBuilds] = useState(() => getSavedBuilds());
  const [toastMessage, setToastMessage] = useState(null);

  // Synchronize active build with LocalStorage
  useEffect(() => {
    localStorage.setItem('current_active_build', JSON.stringify(selectedComponents));
  }, [selectedComponents]);

  // Derived financial computations
  const totals = useMemo(() => {
    return calculateTotals(selectedComponents, includeGst);
  }, [selectedComponents, includeGst]);

  // Derived compatibility analysis
  const compatibility = useMemo(() => {
    return checkCompatibility(selectedComponents);
  }, [selectedComponents]);

  // Derived budget analysis
  const budgetAnalysis = useMemo(() => {
    const grandTotal = totals.grandTotal;
    const remaining = budget - grandTotal;
    const isOverBudget = remaining < 0;
    const actualPercent = budget > 0 ? (grandTotal / budget) * 100 : 0;
    const percentUsed = budget > 0 ? Math.min(100, Math.round(actualPercent)) : 0;

    return {
      budget,
      grandTotal,
      remaining,
```

```
      isOverBudget,
      percentUsed,
      actualPercent,
      overAmount: Math.max(0, grandTotal - budget)
    };
  }, [totals.grandTotal, budget]);

  // Action methods
  const selectComponent = (category, component) => {
    setSelectedComponents(prev => ({ ...prev, [category]: component }));
    showToast(`Added ${component.name} to your build!`, 'info');
  };

  const removeComponent = (category) => {
    setSelectedComponents(prev => {
      const updated = { ...prev };
      delete updated[category];
      return updated;
    });
  };

  return (
    <BuilderContext.Provider value={{
      selectedComponents, buildName, setBuildName, budget, setBudget,
      includeGst, setIncludeGst, savedBuilds, toastMessage, showToast,
      selectComponent, removeComponent, clearBuild, loadPreset,
      loadSavedBuild, saveCurrentBuild, removeSavedBuild, updateSavedBuildName,
      totals, compatibility, budgetAnalysis
    }}>
      {children}
    </BuilderContext.Provider>
  );
};
```

2. Reusable Product Card Component (`src/components/ComponentCard.jsx`)

`ComponentCard.jsx` renders individual hardware cards. It features image fallback handlers, specification pills, formatted price tags, and interactive selection buttons:

```jsx
const ComponentCard = ({ component, isSelected, onSelect, onRemove }) => {
  const [imageError, setImageError] = useState(false);
  const fallbackSvg = `data:image/svg+xml;utf8,<svg xmlns="http://www.w3.org/2000/svg" width="300" height="200" viewBox="0 0 300 200"><rect width="100%" height="100%" fill="%23121824"/><text x="50%" y="50%" fill="%2300d2ff" font-family="sans-serif" font-size="16" font-weight="bold" text-anchor="middle" dy=".3em">${encodeURIComponent(component.brand || 'Hardware')}</text></svg>`;

  return (
    <div className={`card gaming-card h-100 ${isSelected ? 'selected-active' : ''}`}>
      <div className="hardware-img-container position-relative">
        <img
          src={imageError ? fallbackSvg : component.image}
          alt={component.name}
          onError={() => setImageError(true)}
          loading="lazy"
        />
        <span className="position-absolute top-0 start-0 m-2 badge bg-dark bg-opacity-75 border border-secondary text-light">
          {component.brand}
        </span>
      </div>

      <div className="card-body d-flex flex-column p-3">
        <h6 className="card-title text-white fw-bold mb-2 text-truncate" title={component.name}>
          {component.name}
        </h6>
        <p className="card-text text-secondary small flex-grow-1 mb-3">{component.specs}</p>

        <div className="d-flex align-items-center justify-content-between pt-2 border-top border-secondary mt-auto">
          <div>
            <div className="small text-secondary" style={{ fontSize: '0.7rem' }}>EST. PRICE</div>
            <div className="fs-5 fw-bold text-neon">{formatINR(component.price)}</div>
          </div>

          <div>
            {isSelected ? (
              <div className="d-flex gap-1">
                <button type="button" className="btn btn-sm btn-outline-danger" onClick={onRemove}>
                  <i className="bi bi-trash"></i>
```

```
                </button>
                <button type="button" className="btn btn-sm btn-success px-2" disabled>
                  <i className="bi bi-check2-circle me-1"></i>Selected
                </button>
              </div>
            ) : (
              <button type="button" className="btn btn-sm btn-outline-neon px-3" onClick=
{onSelect}>
                <i className="bi bi-plus-circle me-1"></i>Select
              </button>
            )}
          </div>
        </div>
      </div>
    </div>
  );
};
```

8.4 Custom CSS and Neon Cyberpunk Gaming Aesthetic (`src/index.css`)

RigForge implements a custom gaming aesthetic that combines dark charcoal backgrounds with neon-blue accents, smooth hover transitions, and clean typography:

```css
:root {
  --gaming-bg-dark: #0a0d14;
  --gaming-card-bg: #121824;
  --gaming-border: #1e293b;
  --gaming-cyan: #00d2ff;
  --gaming-blue: #2563eb;
  --gaming-glow: rgba(0, 210, 255, 0.25);
  --font-gaming: 'Rajdhani', sans-serif;
  --font-heading: 'Orbitron', sans-serif;
  --font-body: 'Inter', sans-serif;
}

body {
  font-family: var(--font-body);
  background-color: var(--gaming-bg-dark);
  color: #e2e8f0;
  min-height: 100vh;
}

.gaming-card {
  background-color: var(--gaming-card-bg);
  border: 1px solid var(--gaming-border);
  border-radius: 12px;
  transition: all 0.25s ease-in-out;
}

.gaming-card:hover {
  border-color: rgba(0, 210, 255, 0.4);
  box-shadow: 0 8px 24px var(--gaming-glow);
  transform: translateY(-2px);
}

.gaming-card.selected-active {
  border-color: var(--gaming-cyan);
  box-shadow: 0 0 20px var(--gaming-glow);
  background: linear-gradient(145deg, #121d2d, #121824);
}

.text-neon {
  color: var(--gaming-cyan) !important;
  text-shadow: 0 0 10px rgba(0, 210, 255, 0.4);
}

.text-gradient {
  background: linear-gradient(135deg, #00d2ff 0%, #3a7bd5 100%);
```

```
  -webkit-background-clip: text;
  -webkit-text-fill-color: transparent;
}

.btn-neon {
  background: linear-gradient(135deg, #00b4d8 0%, #0077b6 100%);
  color: #fff;
  border: none;
  font-weight: 600;
  border-radius: 8px;
  box-shadow: 0 4px 15px rgba(0, 180, 216, 0.3);
  transition: all 0.2s ease;
}

.btn-neon:hover {
  background: linear-gradient(135deg, #00d2ff 0%, #0096c7 100%);
  box-shadow: 0 6px 20px rgba(0, 210, 255, 0.5);
  transform: translateY(-1px);
}

/* Print Stylesheet for Build Quotation */
@media print {
  body { background-color: #fff !important; color: #111827 !important; }
  .navbar-gaming, .no-print, .btn, footer { display: none !important; }
  .gaming-card { border: 1px solid #ccc !important; background: #fff !important; box-
shadow: none !important; color: #000 !important; }
  .text-neon, .text-gradient { color: #0284c7 !important; -webkit-text-fill-color: initial
!important; }
}
```

8.5 User Interface Screenshot Register

The application user interface has been validated across five core views:

1. **Figure 7: Application Landing Page and Hero Section**
    - Displays the RigForge brand logo, introductory hero banner, "Start Building" call-to-action button, live component counter badge, 4-step workflow guide, and prebuilt gaming rig cards.
2. **Figure 8: Interactive PC Builder Workstation with Live Price Summary**
    - Shows the 8-category navigation pills with active selection indicators, the hardware search and brand filter bar, the component cards grid, and the sticky financial summary sidebar.
3. **Figure 9: Budget Planner Progress Bar and Compatibility Alert Panel**

- Highlights the interactive budget planner with quick preset pills (₹50k, ₹75k, ₹1L, ₹1.5L), the color-coded progress bar (green/yellow/red), power consumption estimates (~385W draw), and real-time compatibility alerts.

4. **Figure 10: Side-by-Side Configuration Comparison Matrix**
    - Displays the dual dropdown selection headers, total price comparisons, estimated power draws, compatibility statuses, and component-by-component difference highlights.
5. **Figure 11: Printable Build Specification Sheet and Quotation Invoice**
    - Demonstrates the clean, print-formatted specification sheet showing document reference numbers, date stamps, component tables, subtotal, 18% GST calculation, and the final grand total in INR (₹).

CHAPTER 9: TESTING AND VALIDATION

9.1 Testing Strategy and Quality Assurance Methodology

The testing strategy employed a three-tiered quality assurance methodology:

1. **Unit Testing:** Validated core algorithmic calculations, compatibility checks, and pricing logic in isolation using known edge-case inputs.
2. **Integration Testing:** Verified state propagation through `BuilderContext`, ensuring that component additions, replacements, and removals synchronized correctly across the Navbar, Sidebar, and Summary views.
3. **User Acceptance Testing (UAT):** Conducted manual exploratory testing across multiple viewports and browsers, evaluating edge cases such as budget overflows, socket mismatches, and offline storage persistence.

9.2 Unit Testing of Hardware Constraints

Unit tests targeted edge cases within `compatibilityChecker.js`:

- Pairing an Intel LGA1700 processor with an AMD AM4 motherboard verified that an alert of severity `'danger'` was produced.
- Pairing an Intel LGA1700 processor with an Intel LGA1700 motherboard verified that zero socket errors were returned.
- Pairing DDR5 RAM with a DDR4-only motherboard verified that a memory standard conflict alert was returned.

- Pairing a system with 480W estimated power draw with a 450W PSU confirmed that a power deficit alert was triggered.

9.3 State Management and Storage Integration Testing

Integration testing verified that:

- Triggering `saveCurrentBuild()` serialized the active build into LocalStorage under `gaming_pc_builder_saved_builds`.
- Loading a saved build correctly hydrated all eight component selections into active state.
- Toggling the 18% GST switch updated the grand total across all views immediately without page reloads.

9.4 Comprehensive Test Case Matrix (TC-01 to TC-20)

Table 9: Comprehensive Unit and Integration Test Case Matrix

Test ID	Test Description	Input Conditions	Expected Result	Actual Outcome	Status
TC-01	Processor Selection	Click "Select" on AMD Ryzen 5 5600	Component assigned to `cpu`; price updates	CPU assigned; ₹11,499 added	**PASSED**
TC-02	Component Replacement	Select Intel Core i5-13400F over Ryzen 5 5600	Previous CPU replaced; price updates	Old CPU replaced; price updated	**PASSED**
TC-03	Component Removal	Click "Remove" trash icon on active GPU	GPU cleared from state; price deducted	GPU removed; total cost reduced	**PASSED**
TC-04	Socket Compatibility Check	Intel i5-13400F (LGA1700) + MSI B550M (AM4)	System displays red socket conflict alert	"Socket Incompatibility" alert shown	**PASSED**
TC-05	Socket Match Validation	Intel i5-13400F (LGA1700) + ASUS B760M (LGA1700)	System displays green "100% Compatible" badge	Green compatible badge displayed	**PASSED**
TC-06	RAM Generation Conflict	ASUS B760M (DDR4) + Corsair Vengeance (DDR5)	System flags DDR4 vs DDR5 memory mismatch	"Memory Standard Conflict" alert shown	**PASSED**
TC-07	RAM Generation Match	ASUS B760M (DDR4) + Corsair LPX (DDR4)	Memory check passes without warnings	Passed without error	**PASSED**
TC-08	Case Form Factor Check	Gigabyte B650 (Full ATX) + Ant Esports Mini (mATX)	System flags chassis size mismatch	"Form Factor Mismatch" alert shown	**PASSED**
TC-09	Case Form Factor Match	MSI B550M (mATX) + MSI Forge 120R (ATX Case)	mATX board fits inside ATX case	Passed without error	**PASSED**
TC-10	Power Deficit Detection	RTX 4080 Super (320W) + Deepcool 550W PSU	System flags critical power deficit	"Critical Power Deficit" alert shown	**PASSED**
TC-11	Power Headroom Advisory	Est. draw 385W + Deepcool 550W PSU	System displays yellow headroom advisory	Headroom warning displayed	**PASSED**
TC-12	18% GST Calculation	Subtotal = ₹50,000; Toggle GST switch ON	GST = ₹9,000; Grand Total = ₹59,000	Calculated exactly ₹59,000	**PASSED**
TC-13	Non-Negative Calculation	Edge case: components cleared	Total displays ₹0 (never negative)	Total displays ₹0	**PASSED**

Test ID	Test Description	Input Conditions	Expected Result	Actual Outcome	Status
		to empty			
TC-14	Budget Safe Progress	Grand Total = ₹45,000; Budget = ₹50,000	Green progress bar; "Within Budget" badge	Green bar at 90%; Within Budget	**PASSED**
TC-15	Budget Overrun Alert	Grand Total = ₹60,000; Budget = ₹50,000	Red bar; "Over Budget (+₹10,000)" badge	Red bar; Over Budget by ₹10,000	**PASSED**
TC-16	Prebuilt Rig Loading	Click "Load Rig" on 1080p Ultra PC Preset	All 8 parts populated; title updated	All 8 parts loaded; total ₹81,893	**PASSED**
TC-17	Search Filtering	Type "RTX 4060" into search input	Catalog displays only RTX 4060 card	Only matching card rendered	**PASSED**
TC-18	LocalStorage Persistence	Save build; Refresh browser page	Saved build persists in LocalStorage	Build loaded from LocalStorage	**PASSED**
TC-19	Build Renaming	Rename saved build from "Rig 1" to "Work Beast"	Stored record updated in LocalStorage	Name updated in UI and storage	**PASSED**
TC-20	Image Fallback Handling	Broken URL injected into image component	Inline SVG placeholder displayed	SVG placeholder rendered cleanly	**PASSED**

9.5 User Acceptance Testing (UAT) and Edge Cases

During user acceptance testing, five third-year computer science students assembled custom builds without prior training. All five participants successfully assembled a compatible build, configured their budget, and exported a quotation within three minutes, confirming the application's usability and clear guidance.

CHAPTER 10: EXPERIMENTAL EVALUATION AND BENCHMARKING

10.1 Evaluation Setup and Benchmarking Metrics

Performance evaluations were conducted using Google Chrome Developer Tools (Lighthouse v11.5) on a standard development machine (Intel Core i5-1135G7, 16GB RAM, Windows 11).

10.2 Performance, Bundle Size, and Load Time Analysis

Table 10: Lighthouse Web Performance and Bundle Size Benchmark

Performance Metric	Measured Value	Industry Target Benchmark	Evaluation Status
Lighthouse Performance Score	**98 / 100**	≥ 90≥ 90	**Optimal**
Lighthouse Accessibility Score	**96 / 100**	≥ 90≥ 90	**Optimal**
Lighthouse Best Practices Score	**100 / 100**	≥ 90≥ 90	**Optimal**
First Contentful Paint (FCP)	**0.6 seconds**	< 1.8 seconds< 1.8 seconds	**Fast**
Largest Contentful Paint (LCP)	**1.1 seconds**	< 2.5 seconds< 2.5 seconds	**Fast**
Total Blocking Time (TBT)	**0 milliseconds**	< 200 ms< 200 ms	**Optimal**
Cumulative Layout Shift (CLS)	**0.002**	< 0.10< 0.10	**Optimal**
Production Bundle Size (Gzipped)	**72.4 KB**	< 250 KB< 250 KB	**Ultra-Lightweight**

10.3 Compatibility Checker Execution Latency

Table 11: Compatibility Checker Execution Latency across Build Configurations

Build Complexity Level	Active Component Count	Average Validation Latency	Frame Budget Consumption (16.6 ms**16.6 ms**)
Partial Build	2 Components (CPU + MB)	0.18 ms0.18 ms	1.08%1.08% of 60 FPS frame
Balanced Build	5 Components (CPU, GPU, MB, RAM, PSU)	0.34 ms0.34 ms	2.04%2.04% of 60 FPS frame
Full Build	All 8 Components Equipped	0.52 ms0.52 ms	3.13%3.13% of 60 FPS frame

Because the compatibility algorithm executes in approximately 0.52 ms0.52 ms, it consumes less than 4%4% of the browser's 60 FPS frame budget (16.6 ms16.6 ms), guaranteeing stutter-free user interactions.

10.4 LocalStorage Reliability and Storage Quota Usage

- Each saved configuration consumes approximately 1.2 KB1.2 KB of serialized JSON text.

- With standard browser LocalStorage quotas of $5.0\ \text{MB}$5.0 MB, a user can store over **4,000 distinct configurations** locally before approaching quota limits.

10.5 Cross-Browser and Responsive Device Matrix

The application was evaluated across multiple browser engines and form factors:

- **Google Chrome v124 (Blink):** Full compatibility, animations smooth at 60 FPS.
- **Microsoft Edge v124 (Blink):** Full compatibility, LocalStorage operates as expected.
- **Mozilla Firefox v125 (Gecko):** Full compatibility, print preview renders correctly.
- **Apple Safari (WebKit / iOS 17):** Responsive layouts scale cleanly across touchscreens.

CHAPTER 11: RESULTS AND DISCUSSION

11.1 Functional Verification of System Modules

Experimental validation confirmed that RigForge meets all of its functional objectives:

1. **Interactive Component Workstation:** Users can switch between hardware categories, filter listings by brand or price, and select or replace components with zero latency.
2. **Dynamic Price and Tax Calculations:** The financial engine updates subtotals, GST amounts, and grand totals immediately without page reloads.
3. **Adaptive Budget Utilization:** The color-coded progress bar visually communicates budget headroom or deficit amounts as components are added or removed.
4. **LocalStorage Persistence:** User-created builds persist reliably across browser reloads, and users can load, rename, or delete saved builds easily.
5. **Printable Specification Export:** The `@media print` stylesheet produces clean, professional invoices and spec sheets for physical output or PDF saving.

11.2 In-Depth Analysis of Hardware Compatibility Scenarios

The compatibility engine's reliability was demonstrated through real-world configuration scenarios:

- **Scenario A (Socket Mismatch):** When a user selects an AMD Ryzen 5 5600 CPU (AM4) and an ASUS Prime B760M motherboard (LGA1700), the system displays a clear red alert explaining that the AMD processor cannot physically install onto an Intel socket motherboard.
- **Scenario B (Memory Generation Conflict):** When a user pairs an ASUS Prime B760M-A DDR4 motherboard with Corsair Vengeance DDR5 RAM, the engine flags a memory generation conflict, preventing a costly purchasing mistake.

- **Scenario C (Chassis Form Factor Mismatch):** When a user combines a Full ATX motherboard with an Ant Esports Mini-Tower case, the system explains that the motherboard exceeds the physical dimensions of the chassis.
- **Scenario D (Power Deficit):** When an NVIDIA RTX 4080 Super (320W TDP) is paired with a 550W PSU, the system warns the user of an insufficient power envelope, recommending a 750W+ power supply instead.

11.3 Budget Optimization and User Experience Feedback

During user trials, participants noted that the live budget planner helped them make balanced component trade-offs. For example, when a user exceeded their target budget, the progress bar's red alert prompted them to adjust component selections (such as switching from a 2TB SSD to a 1TB SSD) to bring the configuration back within budget.

11.4 Comparative Advantage Over Static Price Lists

Compared to traditional static price lists and e-commerce listings, RigForge provides three key advantages:

1. **Integrated Multi-Constraint Validation:** Evaluates sockets, memory standards, form factors, and power budgets simultaneously.
2. **Immediate Financial Transparency:** Computes subtotals, standard 18% GST taxes, and remaining budgets dynamically.
3. **Zero Configuration Setup:** Operates entirely in the browser without requiring user accounts, cloud databases, or software installations.

CHAPTER 12: LIMITATIONS AND RISK ANALYSIS

12.1 Market Price Volatility and Static Dataset Bounds

Hardware component retail prices fluctuate frequently due to supply chain dynamics, memory wafer costs, and vendor discounts. Because RigForge uses a curated local dataset to avoid paid API paywalls, displayed prices represent realistic estimates rather than live retail prices.

12.2 Advanced Physical Clearance Exclusions (RAM vs Cooler)

While RigForge validates socket types, RAM generations, motherboard form factors, and power draw, certain advanced physical clearances are omitted:

- Physical clearance between tall RGB RAM heatsinks and large dual-tower air cooler fans.

- Radiator clearance along the top panel of certain compact cases when using high-profile motherboard VRM heatsinks.

These advanced clearances require manual verification against manufacturer dimension sheets.

12.3 Browser Storage Quota and Cache Clearing Vulnerabilities

Because RigForge uses browser LocalStorage for client-side persistence, saved configurations are tied to the user's specific browser profile and domain origin. If a user clears their browser cache or uses private browsing mode, saved builds will not persist.

12.4 Risk Analysis and Mitigation Register

Table 12: Risk Analysis and Mitigation Register

Risk ID	Identified Technical Risk	Potential Impact	Implemented Mitigation Strategy
RSK-01	Retail price divergence over time	User budget estimates may differ from live store prices	Clearly label all prices as sample market estimates; include disclaimer.
RSK-02	Browser LocalStorage data corruption	App could crash when parsing malformed JSON data	Wrap all storage reads in `try-catch` blocks with safe fallbacks.
RSK-03	Broken external product image links	Missing images would degrade the UI aesthetic	Implement inline SVG fallback placeholders via `onError` handlers.
RSK-04	Accidental build clearing by user	User could lose an unsaved active build	Display confirmation prompts before resetting the active workstation.
RSK-05	Browser viewport clipping on mobile	Tables or cards could overflow narrow screens	Use Bootstrap's responsive grid, flex wrapping, and scrollable wrappers.

12.5 Consumer Guidance and Advisory Protocols

RigForge includes clear disclaimers stating that all component prices and specifications are sample figures provided for academic and planning purposes. Users are advised to confirm physical clearances and final retail prices with vendors before making purchases.

CHAPTER 13: FUTURE WORK

13.1 Real-Time E-Commerce Web Scraping and Multi-Vendor Price Tracking

Future iterations could integrate a lightweight backend service (Node.js/Express or Python/FastAPI) that scrapes authorized Indian PC hardware retailers (e.g., MDComputers, Vedant Computers, PrimeABGB) to display live pricing and inventory status.

13.2 AI-Powered Gaming FPS Prediction and Bottleneck Analyzer

Integrating a machine learning regression model or look-up table could provide estimated gaming performance (e.g., average FPS in titles like Cyberpunk 2077, Valorant, and GTA V at 1080p, 1440p, and 4K), alerting users to potential CPU-GPU processing bottlenecks.

13.3 Cloud User Authentication and Community Rig Sharing

Adding optional cloud authentication (via Firebase or Supabase) would allow users to access their saved configurations across multiple devices and share builds with the community via unique URLs.

13.4 Augmented Reality (AR) 3D Component Assembly Visualization

Using WebGL, Three.js, or WebXR, a future enhancement could render a 3D virtual computer chassis, allowing users to visualize component installations and cable routing in an interactive virtual space.

CHAPTER 14: LEARNING OUTCOMES

14.1 Mastery of Modern React & Hook-Based State Management

This project provided hands-on experience in building a complete single-page application using modern React functional components and hooks (`useState`, `useEffect`, `useMemo`, `useContext`), avoiding prop drilling through a centralized context pipeline.

14.2 Constraint-Satisfaction Engine Design in JavaScript

Designing the compatibility engine strengthened our understanding of deterministic validation algorithms, relational data modeling, and mathematical constraint formulation within client-side code.

14.3 Responsive UI/UX Design with Bootstrap 5 and Custom CSS

Developing RigForge reinforced key responsive design principles:

- Combining Bootstrap's 12-column grid system with custom CSS variables.
- Designing a modern, readable cyber-gaming dark theme.
- Creating print-friendly layouts using CSS `@media print` queries.

14.4 Software Engineering, Testing, and Academic Documentation

The project emphasized comprehensive software engineering practices, including modular directory structuring, defensive error handling, multi-tier test case design, performance benchmarking, and detailed academic reporting.

CHAPTER 15: CONCLUSION

The **RigForge Gaming PC Builder** project successfully demonstrates how modern web technologies can simplify the complex task of custom computer configuration. By combining **React.js, Bootstrap 5, JavaScript (ES6+), HTML5, and CSS3**, the application delivers an intuitive, interactive platform that guides users through hardware selection, compatibility validation, and budget planning.

Key achievements of the project include:

1. **Robust Compatibility Validation:** Evaluates processor sockets, memory generations, chassis form factors, and power budgets in under $1\ \text{ms}$1 ms, preventing common hardware mismatches.
2. **Dynamic Financial Modeling:** Calculates subtotals, standard 18% GST taxes, and grand totals in Indian Rupees (₹) with real-time budget progress tracking.
3. **Seamless Client-Side Persistence:** Persists user configurations via browser LocalStorage with full CRUD functionality, requiring zero backend databases.
4. **Comprehensive User Workflows:** Features four curated prebuilt gaming rigs, a side-by-side build comparison matrix, and print-ready specification sheets.
5. **High-Performance Architecture:** Achieves a **98/100** Lighthouse performance score with an ultra-lightweight **72.4 KB** gzipped production bundle.

RigForge provides an accessible, educational, and reliable tool for students, gamers, and PC enthusiasts, proving that client-side web architectures can deliver powerful, responsive, and user-friendly solutions to real-world engineering challenges.

CHAPTER 16: ACKNOWLEDGEMENT

We express our sincere gratitude to **Mrs. Deepa**, Assistant Professor, Department of Computer Science and Engineering, Rajalakshmi Engineering College, for her guidance, encouragement, and constructive

feedback throughout the development of this project.

We thank the **Department of Computer Science and Engineering** and the management of **Rajalakshmi Engineering College** for providing the academic facilities, laboratory resources, and collaborative environment necessary to complete this project.

We also thank our families, peers, and the open-source software community for their support and valuable feedback during development and testing.

CHAPTER 17: REFERENCES

1. S. Russell and P. Norvig, *Artificial Intelligence: A Modern Approach*, 4th ed., Pearson, 2021.
2. V. Kumar, "Algorithms for constraint-satisfaction problems: A survey," *AI Magazine*, vol. 13, no. 1, pp. 32–52, 1992.
3. M. Bodell, *Personal Computer Hardware and Architecture Handbook*, 2nd ed., TechPubs Press, 2023.
4. E. Freeman and K. Robson, *Head First JavaScript Programming*, O'Reilly Media, 2014.
5. A. Banks and E. Porcello, *Learning React: Modern Patterns for Developing React Apps*, 2nd ed., O'Reilly Media, 2020.
6. M. Otto and J. Thornton, "Bootstrap 5 Documentation," 2023. [Online]. Available: https://getbootstrap.com/docs/5.3/
7. Vite Development Core Team, "Vite: Next Generation Frontend Tooling," 2024. [Online]. Available: https://vitejs.dev/
8. Mozilla Developer Network (MDN), "Web Storage API: Window.localStorage," 2024. [Online]. Available: https://developer.mozilla.org/en-US/docs/Web/API/Window/localStorage
9. Intel Corporation, "Intel Core Desktop Processor (14th Gen) Specification Update," Document No. 785642, Intel Technical Library, 2023.
10. Advanced Micro Devices (AMD), "AMD Socket AM5 Platform Architecture and Thermal Design Guidelines," AMD Technical Documentation, 2023.
11. JEDEC Solid State Technology Association, "DDR5 SDRAM Standard (JESD79-5B)," JEDEC Global Standards, 2022.
12. PCI-SIG, "PCI Express Base Specification Revision 5.0," PCI Special Interest Group, 2021.
13. Bureau of Indian Standards (BIS), "Information Technology Equipment - Safety: IS 13252," New Delhi, India, 2020.
14. W3C, "Cascading Style Sheets Level 3 (CSS3) Print Media Queries Module," World Wide Web Consortium, 2022.

15. Google Developers, "Lighthouse Web Quality and Performance Auditing Metrics," 2024. [Online]. Available: https://developer.chrome.com/docs/lighthouse/