EKO BLOCKS
EKO
CM/L - 6600064112
IS 2185: Part 3
www.vsecoblocks.com

# FEATURES OF EKO BLOCKS

Advantages of EKO Blocks

To Construction Community

Advantages Of EKO Blocks

To Householders Segment

Social Advantages of EKO Blocks

Easy To Work

Energy

Construction

Termite

Cost- EffectiveNon-

Resistance

Saves steel &

Noise Pollution

Earthquake Saves

Resistance Fertile

Resistance

Toxic

Reduce Recyclable

Materials

Land

Fast

Thermal

Efficiency

concrete

EKO BLOCKS is a leading manufacturer of AAC Blocks in Andhra and Telangana, distinguished by our unwavering dedication to the highest quality standards. Our manufacturing process is supervised by seasoned professionals with extensive experience in AAC technologies, and it integrates cutting-edge technologies and adheres to current industry trends.

We customize the size, production, and delivery of AAC Blocks to satisfy the unique needs of our esteemed clients. These blocks provide a distinctive combination of high compressive strength, lightweight, superior thermal insulation, easy to work, good workability, and impeccable build quality.

Our objective at EKO Blocks is to become the premium manufacturer of AAC blocks in Andhra and Telangana. We are committed to consistently establishing the trust of our clients by providing AAC Blocks of the highest quality.

LowSaves

Fire Proof

WastageLand Fills

Good Plastering

Surface

Long

Life Span

Reduces

Carbon Foot Print

# FIND YOUR PERFECT BLOCK

Size Chart

| | 2" | 3" | 4" | 5" | 6" | 8" | 9" |
|---|---|---|---|---|---|---|---|
| Length | 24" (600) | 600 | 600 | 600 | 600 | 600 | 600 |
| Height | 8" (200) | 200 | 200 | 200 | 200 | 200 | 200 |
| Width | 2" (50) | 75 | 100 | 125 | 150 | 200 | 230 |

*Customized sizes are also available

2" 3" 4" 5" 6" 8"

# TECHNICAL SPECIFICATION

| Property | Units | EKO Block (AS per IS2185 Part 3) | Clay Brick |
|---|---|---|---|
| Size | mm | 600 x 200 x (50 to 230) | 230 x 75 x 110 |
| Size Tolerance | mm | +/- 5mm in length*<br>+/- 3mm in width & height | to 15 |
| Compressive Strength | N/mm2 | Min 4.0* | |
| Normal Dry (Oven Dry) Density | Kg/m2 | 551 to 650* | 1800 - 2000 |
| Thermal Conductivity "K" | W/m-k | <0.24 | 0.81 - 1.2 |
| Drying Shrinkage | | | NA |
| Fire Resistance | Hrs. | Up to 6 Hours (Depending on thickness) | Up to 1 Hour |
| Sound Reduction Index | Db | 45 for 100 mm thick wall | 35 |
| Water Absorption | | NA | 15-20% |

# COMPARISON BETWEEN AAC BLOCK & CLAY BRICK

| Parameter | EKO Block | Clay Brick |
|---|---|---|
| Structural Cost | Savings upto 15% | No saving because of Higher Densities |

| | | |
|---|---|---|
| Mortar Consumption | Lower due to Uniform size, and less number of joints | Requires more due to uneven dimensions and surface |
| Breakage | Less than 2% | Up to 12% |
| Construction Speed | Faster construction due to its big size. | Slower |
| Quality | Uniform & Consistent | Inconsistent |
| Cost Effective | Faster Construction Lower Mortar & Plasting Needs | Higher Due to Laboure, Mortar and Plaster Costs |
| Energy Saving | Up to. 30% reduction on air-conditioned Load | No such saving |

# RECOMMENDED JOINTING

# MORTAR FOR EKO BLOCK

Introducing EKO ADHESIVE, our premium quality high performance ready-to-use block jointing mortar (Thin bed jointing mortar) revolutionizes the way you build. Our product is made in a fully automated plant using silica sand, Portland cement and elastomeric polymers, to provide hassle-free and cost-effective solutions for your construction needs.

With EKO ADHESIVE, you can say goodbye to the hassle of mixing mortar on-site. It is specially formulated to bond EKO blocks, making it the perfect choice for external and internal walls, whether you build a commercial or residential property.

# AREAS OF APPLICATION

Thin bed jointing mortar adaptability makes it a valuable material for diverse construction needs, ensuring efficiency and durability across various construction applications. Its primary areas of application include:

1. Masonry Construction
2. Internal and External Walls
3. Partition Walls
4. Renovation and Retrofitting
5. High-Rise Buildings
6. Residential, Industrial & Commercial Structures

# TECHNICAL SPECIFICATION

| Test | Methodology | Result |
|---|---|---|
| Colour | In House Method | Grey Powder |
| Pot Life 27±2 $^{0}$Celsius | In House Method | 90 Min |
| Compressive Strength voc | IS 2250:1981 (RA 2010) | >12N/mm2 |
| | IS 33:1992 (RA 2014) | Very Low |

# USAGE ADVICE

Thin bed jointing mortar adaptability makes it a valuable material for diverse construction needs, ensuring efficiency and durability across various construction applications. Its primary areas of application include:

- Add powder to water slowly and mix gradually to avoid lumps and to form uniform mixture.
- Adjust the water requirement according to the environmental conditions.
- Use notch trowel to get ideal results.

- Pre-wet and maintain AAC Blocks under SSD condition before construction.
- Use Reinforced Cement and Sand bed to maintain zero level of the surface and every 3 to 4ft as and when required.

# UPCOMING PRODUCTS

EKO FIX

EKO GROUT

EKO

Teachers colony , Kundanbagh Colony , Begumpet
, Hyderabad, Telangana - 500 016.

Contact Us : +91 6303536113
Email : santhoshbanoth80@gmail.com