

## **Playbooks :**

Playbooks are the files where Ansible code is written. Playbooks are written in YAML format. YAML stands for Yet Another Markup Language. Playbooks are one of the core features of Ansible and tell Ansible what to execute. They are like a to-do list for Ansible that contains a list of tasks.

Playbooks contain the steps which the user wants to execute on a particular machine. Playbooks are run sequentially. Playbooks are the building blocks for all the use cases of Ansible.

## **Playbook Structure :**

Each playbook is an aggregation of one or more plays in it. Playbooks are structured using Plays. There can be more than one play inside a playbook.

The function of a play is to map a set of instructions defined against a particular host.

YAML is a strict typed language; so, extra care needs to be taken while writing the YAML files. There are different YAML editors but we will prefer to use a simple editor like vim.

A YAML starts with --- (3 hyphens)

## **The Different YAML Tags :**

Let us now go through the different YAML tags. The different tags are described below -

### **name**

This tag specifies the name of the Ansible playbook. As in what this playbook will be doing. Any logical name can be given to the playbook.

### **hosts**

This tag specifies the lists of hosts or host group against which we want to run the task. The hosts field/tag is mandatory. It tells Ansible on which hosts to run the listed tasks. The tasks can be run on the same machine or on a remote machine. One can run the tasks on multiple machines and hence hosts tag can have a group of hosts' entry as well.

### **vars**

Vars tag lets you define the variables which you can use in your playbook. Usage is similar to variables in any programming language.

## tasks

All playbooks should contain tasks or a list of tasks to be executed. Tasks are a list of actions one needs to perform. A tasks field contains the name of the task. This works as the help text for the user. It is not mandatory but proves useful in debugging the playbook. Each task internally links to a piece of code called a module. A module that should be executed, and arguments that are required for the module you want to execute.

### Now Lets start writing Some Sample Plays

```
#mkdir      /Plays
```

```
#cd /Plays
```

#### 1) Writing Sample Play

```
#vim play1.yml
```

```
---
```

```
- name : Sample Play to Create User ( Play 1 )
```

```
  hosts : db
```

```
  become : true
```

```
  tasks :
```

```
    - name : This Task is to create user RAVI ( Task 1 of Play 1 )
```

```
      user :
```

```
        name : ravi
```

```
        uid : 9001
```

```
        state : present
```

```
:wq!
```

**#ansible-playbook --syntax-check play1.yml ( To Perform the Syntax Check on play1.yml)**

**#ansible-playbook play1.yml --list-hosts ( To see what hosts would be affected by a playbook before you run it )**

**#ansible-playbook -C play1.yml ( Executing a playbook with out doing any changes ..Dry RUN )**

**#ansible-playbook play1.yml ( Executing Play Book )**

## **2) Writing Play With multiple tasks**

#vim play2.yml

---

- name : Installing Few Packages & Ensuring Selected Services are UP ( Play 1 )

hosts : db

become : true

tasks :

- name : Installing chrony Package ( Task 1 of Play 1 )

yum :

name : chrony

state : latest

- name : Installing Apache Package ( Task 2 of Play 1 )

yum :

name : httpd

state : latest

- name : Starting & Enabling NTP Service ( Task 3 of Play 1 )

service :

name : chronyd

state : started

enabled : true

- name : Starting & Enabling Apache Service ( Task 4 of Play 1 )

service :

name : httpd

state : started

enabled : true

:wq!

### 3)Writing a Playbook to Setup Webserver

#vim apache.yml

---

- name : Setting Up Webserver ( Play 1 )

hosts : db

become : true

tasks :

- name : Installing Apache Package ( Task 1 of Play 1 )

yum :

name : httpd

state : latest

- name : Defining Index.html file ( Task 2 of Play 1 )

copy :

src : /apache/index.html

dest : /var/www/html/index.html

- name : Ensure Apache Service i Started & Enabled ( Task 3 of Play 1 )

service :

name : httpd

state : started

enabled : true

:wq!

#### 4)Writing Playbook with Multiple Plays :

```
#vim multiplay.yml
```

```
---
```

```
- name : Setting up Few Services ( Play 1 )
```

```
hosts : db
```

```
become : true
```

```
tasks :
```

```
- name : Installing Dovecot Service ( Task 1 of Play 1 )
```

```
  yum :
```

```
    name : dovecot
```

```
    state : latest
```

```
- name : Installing DNS Package ( Task 2 of Play 1 )
```

```
  yum :
```

```
    name : bind
```

```
    state : latest
```

```
- name : Ensuring Services are UP ( Play 2 )
```

```
hosts : db
```

become : true

tasks :

- name : Starting Dovecot Service ( Task 1 of Play 2 )

  - service :

    - name : dovecot

    - state : started

    - enabled : true

- name : Starting DNS Service ( Task 2 of Play 2 )

  - service :

    - name : named

    - state : started

    - enabled : true

- name : Manually Resolving with out DNS ( Play 3 )

hosts : db

become : true

tasks :

- name : Adding Entries to /etc/hosts ( Task 1 of Play 3 )

  - lineinfile :

    - path : /etc/hosts

    - line : '192.168.1.200 ae'

    - state : present

:wq!

### **Booleans Variations in Playbook**

True | true | YES | yes | 1

False | false | NO | no | 0 ( Zero )

### **PlayBook Syntax Variations :**

hosts :

- 192.168.1.201
- 192.168.1.205
- 192.168.1.210
- 192.168.1.215
- 192.168.1.220
- db
- mail\_servers
- middle\_ware

### **Short Form :**

hosts : [192.168.1.201, 192.168.1.205, 192.168.1.210, 192.168.1.215, 192.168.1.220, db, mail\_servers, middle\_ware]

tasks :

- name : Starting DNS Service ( Task 2 of Play 2 )

service :

name : named

state : started

enabled : true

### Short Form :

- name : Some task Description
- service : name=named, state=started, enabled=true

### 5) Writing Playbook with New Variations in Syntax

```
#vim webserver_user.yml
```

```
---
```

- name : Setting up Webserver Locally

hosts :

- 192.168.1.108
- 192.168.1.109
- 192.168.1.110

tasks :

- name : Installing the latest Packages req to setup Webserver

yum :

name :

- httpd
- firewalld
- vim
- wget
- yp-tools

state : latest

- name : Defining INDEX.html file

copy :

content : "Welcome to my Ansible Training"



dest : /var/www/html/index.html

- name : Ensure Firewall Service is Started & Enabled

service :

name : firewalld

state : started

enabled : true

- name : Adding Port to the Firewall Rule

firewalld :

port : 80/tcp

permanent : true

state : enabled

immediate : yes

- name : Ensuring Apache Service is Running & Enabled

service : name=httpd state=started enabled=true

- name : Creating Users from Selected Group Members

hosts : db

tasks :

- name : This task is to create user

user :

name : clouduser

comment : userforCLOUD

uid : 6798

groups : aws,azure,gcp

append : yes

shell : /bin/sh

generate\_ssh\_key : true

ssh\_key\_bits : 2048

ssh\_key\_file : .ssh/id\_rsa

expires : -1

state : present

:wq!