📖 DOCUMENTATION

AgentOps Pro Setup Guide

Complete installation, configuration, and deployment guide for the AI Agent Operations Dashboard — Angular 21 admin template.

Version 1.0.0 | ⚡ Angular 21 | 🟦 TypeScript 5.8 | 📅 February 2025

1 Quick Start

Get AgentOps Pro running in under 3 minutes with these steps:

BASH

```bash
# 1. Extract the zip and navigate into the folder
cd agentops-pro

# 2. Install dependencies
npm install

# 3. Start mock server (in a separate terminal)
npm run mock-server

# 4. Start the Angular dev server
npm start

# ✅ Open: http://127.0.0.1:4200
# Login: demo@agentops.ai / demo1234
```

✅ **You're in!**

The dashboard loads with live mock WebSocket data — all 21 pages work out of the box without any backend configuration needed.

2 Requirements

Make sure your development environment meets these requirements before installing.

Check your versions

BASH

```bash
node --version    # Should be v18.x or higher
npm  --version    # Should be 9.x or higher
ng   --version    # Should be 17.x or higher (optional)
```

⚠️ **Node version mismatch?**

If you have an older Node.js version, use `nvm` (Node Version Manager) to switch:

`nvm install 20 && nvm use 20`

3 Installation

Step 1 — Extract the ZIP

Unzip `agentops-pro-v1.0.0.zip` to your preferred directory.

Step 2 — Install Angular CLI OPTIONAL

If you don't have Angular CLI installed globally:

```bash
npm install -g @angular/cli
```

Step 3 — Install dependencies REQUIRED

```bash
cd agentops-pro
npm install
```

> ℹ️ **Installation time**
>
> First install takes 1–3 minutes depending on your connection. Subsequent installs are much faster due to npm cache.

Verify installation

```bash
npm run lint     # Should print: All files pass linting.
npx tsc --noEmit  # Should print nothing (no errors)
```

4 Running the App

Development Server

```bash
npm start
# Equivalent to: ng serve --host 127.0.0.1
# Available at:  http://127.0.0.1:4200
```

Demo Login Credentials

FIELD	VALUE	NOTES
`Email`	demo@agentops.ai	Pre-filled on login page
`Password`	demo1234	Pre-filled on login page
`Mode`	Mock Data	No backend required

> ℹ️ **Use 127.0.0.1 — not localhost**
> The dev server is bound to `127.0.0.1:4200`. Browsers treat `localhost` and `127.0.0.1` as different origins. Always use `http://127.0.0.1:4200` to avoid CORS issues with the mock server.

All available scripts

COMMAND	DESCRIPTION
`npm start`	Start dev server at 127.0.0.1:4200
`npm run mock-server`	Start mock WebSocket + REST server at :8081
`npm run build`	Production build → dist/
`npm run lint`	Run ESLint across all source files
`npm test`	Run unit tests (Karma + Jasmine)

5 Mock Server

The included mock server (`mock-server/`) provides a full local backend with Express REST endpoints and WebSocket events — no real backend needed during development.

Start the mock server

```bash
# In a separate terminal window
npm run mock-server

# Output you'll see:
# ✅ Mock server listening on http://127.0.0.1:8081
# ✅ WebSocket server ready on ws://127.0.0.1:8081/ws
```

What the mock server provides

ENDPOINT	METHOD	DESCRIPTION
`/api/auth/login`	POST	Returns JWT token for demo credentials
`/api/agents`	GET	List of mock AI agents with status
`/api/metrics`	GET	Token usage, latency, cost data
`/api/sessions`	GET	Session replay data
`/ws`	WebSocket	Real-time agent events, heartbeats

> ⚠️ **Run both servers simultaneously**
> You need two terminal windows open: one for `npm run mock-server` and one for `npm start`. The Angular app won't login successfully without the mock server running.

6 Environment Configuration

All environment-specific settings live in `src/environments/`. Angular CLI automatically loads the correct file based on the build configuration.

Environment files

FILE	USED WHEN	MOCK DATA
`environment.ts`	ng serve (default)	Live mode default
`environment.themeforest.ts`	ng build --configuration=themeforest	Mock mode ON
`environment.prod.ts`	ng build --configuration=production	Live mode

Key environment variables

TYPESCRIPT

```typescript
// src/environments/environment.ts
export const environment = {
  production:     false,
  apiUrl:         'http://localhost:3000',    // ← your backend
  wsUrl:          'ws://localhost:3000/ws',   // ← your WebSocket
  mockMode:       false,
  mockServerUrl:  'http://127.0.0.1:8081',    // ← local mock server
};
```

PROPERTY	TYPE	DESCRIPTION
`production`	boolean	Enables Angular production mode
`apiUrl`	string	Your real backend REST API base URL
`wsUrl`	string	Your real backend WebSocket URL
`mockMode`	boolean	If true, forces mock data mode at startup
`mockServerUrl`	string	Local mock server URL (dev only)

> ℹ️ **Runtime toggle**
>
> Users can switch between Mock and Live data at runtime using the toggle button in the header — no rebuild needed. The setting persists in `localStorage`.

7 Project Structure

AgentOps Pro follows Angular best-practice folder structure with clear separation of concerns.

```
agentops-pro/ ├── src/ │ ├── app/ │ │ ├── core/ │ │ │ ├── models/ ← 18 TypeScript interfaces │ │ │ ├── services/ ← 31 signal-based services │ │ │ └── store/ ← AgentStore (global state) │ │ ├── features/ ← 21 feature pages │ │ │ ├── dashboard-v1/ │ │ │ ├── agent-monitor/ │ │ │ ├── orchestration/ │ │ │ ├── cost-optimizer/ │ │ │ ├── hallucination-detection/ │ │ │ ├── session-replay/ │ │ │ ├── playground/ │ │ │ ├── prompt-manager/ │ │ │ └── ... 13 more pages │ │ ├── layout/ ← Header, Sidebar, Footer │ │ └── shared/ │ │ ├── components/ ← 30 reusable components │ │ └── pipes/ ← RelativeTimePipe, TokenFormatPipe │ ├── environments/ ← dev, prod, themeforest configs │ └── styles/ │ └── _tokens.scss ← All design tokens (colors, spacing) ├── mock-server/ ← Express + WebSocket mock server ├── docs/ ← Feature documentation ├── angular.json ├── package.json ├── eslint.config.js ← Marketplace-grade lint rules ├── README.md └── CHANGELOG.md
```

8 Features Overview

AgentOps Pro ships with 21 fully-built pages and 31 services. Here are the 10 showcase features:

9 Customization

Changing colors & branding

All design tokens are in `src/styles/_tokens.scss`. Edit these to rebrand the entire app instantly:

SCSS

```scss
// src/styles/_tokens.scss — Edit these to rebrand
:root {
  /* Primary accent — default: cyan */
  --accent-primary:   #00e5ff;  // ← change to your brand color
  --accent-success:   #00e676;
  --accent-warning:   #ff9100;
  --accent-error:     #ff5252;

  /* Backgrounds */
  --bg-primary:       #0a0e1a;  // ← main background
  --bg-secondary:     #0d1526;
  --bg-tertiary:      #111827;

  /* Typography */
  --font-mono:        'JetBrains Mono', monospace;
}
```

Adding / removing sidebar routes

Edit `src/app/layout/sidebar/sidebar.ts` — find the `navItems` array and add or remove entries:

TYPESCRIPT

```typescript
const navItems = [
  {
    label: 'My New Page',
    route: '/my-page',
    icon:  'rocket_launch',
    badge: { text: 'NEW', type: 'success' }   // optional
  },
];
```

Switching from mock to live data

At runtime, click the **Mock / Live** toggle in the top header. For a permanent switch, set `mockMode: false` in your environment file and point `apiUrl` to your backend.

💡 **Signal-based architecture**

All 31 services use Angular Signals (`signal()`, `computed()`). Components use `ChangeDetectionStrategy.OnPush` for maximum performance.

10 Connecting a Real Backend

When you're ready to replace mock data with a real backend, follow these steps:

Expected login response shape

JSON

```
{
  "access_token":  "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9 ... ",
  "refresh_token": "dGhpcyBpcyBhIHJlZnJlc2ggdG9rZW4 ... ",
  "user": {
    "id":       "user-001",
    "name":     "Alex Johnson",
    "email":    "alex@example.com",
    "role":     "admin",
    "avatar":   "https:// ... "
  }
}
```

🔐 **Security reminder**

Never commit real API keys or secrets to your repository. Use environment variables on your hosting platform and keep sensitive keys out of `environment.ts`.

11 Production Build

```bash
# Standard production build
npm run build
# Output → dist/agentops-pro/browser/

# Demo / marketplace build (all features + mock data enabled)
ng build --configuration=themeforest
# Output → dist/agentops-pro/browser/
```

Deploy the dist/ folder

The output is a standard static site. Deploy to any static host:

PLATFORM	COMMAND / NOTES
Netlify	Drag & drop `dist/agentops-pro/browser`
Vercel	`vercel --prod` from project root
GitHub Pages	`ng deploy` with angular-cli-ghpages
AWS S3 + CloudFront	Upload dist/ contents to S3 bucket
Apache / Nginx	Serve dist/ folder, add SPA rewrite rule

Nginx rewrite rule (for Angular routing)

```nginx
# Required for Angular HTML5 routing
location / {
  try_files $uri $uri/ /index.html;
}
```

12 Troubleshooting

Common issues and how to fix them:

Cause: The mock server is not running, or you're using `localhost` instead of `127.0.0.1`.

Fix: Open a second terminal and run `npm run mock-server`. Then navigate to `http://127.0.0.1:4200` (not localhost).

Fix: Use the `--legacy-peer-deps` flag:

BASH

```bash
npm install --legacy-peer-deps
```

Cause: `node_modules` is corrupted or missing.

Fix: Delete and reinstall:

BASH

```bash
rm -rf node_modules package-lock.json
npm install
```

Cause: Data mode is set to "Live" but no real backend is connected, or the mock server isn't running.

Fix: Click the **Mock ↔ Live** toggle in the header to switch to Mock mode. Or start the mock server.

Fix: Install Angular CLI globally:

```bash
npm install -g @angular/cli
```

Or use the local binary: `npx ng serve`

Fix: Start on a different port:

```bash
ng serve --port 4201 --host 127.0.0.1
```

13 License

LICENSE	USE CASE	PROJECTS
`Personal License`	Personal projects, learning, portfolio	1 non-commercial project
`Developer License`	Client work, commercial SaaS, internal tools	1 commercial end product
`Extended License`	SaaS products sold to multiple users	Unlimited end products

📄 **What you CAN do**

Modify the source code · Use in client projects · Build SaaS products (Developer/Extended) · Remove AgentOps branding

🚫 **What you CANNOT do**

Redistribute or resell this template · Share the source ZIP · Sub-license to third parties

14 Support

Need help? Here's how to reach us:

CHANNEL	RESPONSE TIME	BEST FOR
📧 `Email support`	24–48 hours	Bug reports, billing questions
💬 `Live chat`	Business hours	Quick setup questions
📖 `Documentation`	Instant	Self-service help
🐛 `GitHub Issues`	48–72 hours	Bug reports with repro steps

> ⭐ **Enjoying AgentOps Pro?**
>
> Please leave a review on the marketplace — it helps other developers discover the template and keeps the project funded for future updates. Thank you!

⚡

AgentOps Pro v1.0.0

Built with Angular 21 · TypeScript · SCSS · Signal-based architecture