Status	Finished
Started	Monday, 19 October 2026, 8:21 PM
Completed	Monday, 19 October 2026, 8:24 PM
Duration	2 mins 48 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

a. Error

b. {'rec', 1, ('cse', 'ece')} ✓

c. {'rec', 1, ('cse', 'ece'),True}

d. {'rec', True, ('cse', 'ece')}

Question **2**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. True ✓

b. False

Question **3**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
False

b. True ✓
True

c. False
True

d. True
False

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

my_t1 = (1, 2, 3, 4)

my_t1.append((5, 6, 7))

print(len(my_t1))

a. 2

b. Error ✓

c. 5

d. 1

Question **5**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

t = (58, 47, 36, 25, 14, 3)

x = t[2:-1]

print(x)

- a. (36, 25, 14) ✓
- b. (58,47,36,25)
- c. Error
- d. (3,14,25)

Question **6**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

- a. {2}
- b. {1,3,2}
- c. {4} ✓
- d. {1,3,4}

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

b. Name Error

c. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

d. TypeError: update() doesn't allow list as a argument.

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. {40, 10, 50, 20, 60, 30}

b. {40, 10, '10', 50, 20, 60, 30} ✓

c. {40, '10', 50, 20, 60, 30}

d. SynatxError: Different types cannot be used with sets

Question **9**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

a. {2,5,1}

b. {2,5,3,1}

c. {}

d. {3} ✓

Question **10**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

a. Error ✓

b. (12)

c. 12

d. (55,78,64,25)

Question **11**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

- a. {0,9} ✓
- b. It will throw an error as there are two 0 while creating the set.
- c. {0,0,9}
- d. {9}

Question **12**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (1,2,3,(4,5))
t2 = (3,2,1,(4,5))
print(t1>t2)
```

- a. Error
- b. Error
- c. True
- d. False ✓

Question **13**

Incorrect

Mark 0.00 out of 1.00

What will set1|set2 do?

```
If set1={"a","b",3}
set2={3,7}
```

- a. Elements of set2 will get appended to set1 ✗
- b. Elements of set1 will get appended to set2
- c. A new set will be created with the elements of both set1 and set2
- d. A new set will be created with the unique elements of set1 and set2.

Question **14**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

- a. (30, 40, 50)(40, 50, 60, 70, 80)
- b. (30, 40, 50) (10, 20, 30, 40)
- c. (10, 20, 30, 40) (40, 50, 60, 70, 80)
- d. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

Question **15**

Correct

Mark 1.00 out of 1.00

Which of the following is a Python tuple?

- a. (1,4,5,6,7) ✓
- b. {1,3,8,9,41}
- c. ("Wonder")
- d. [1,2,3,4]