

GE23131-Programming Using C-2024

Quiz navigation

[Show one page at a time](#)[Finish review](#)

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Monday, 4 November 2024, 8:49 AM
Duration	49 days 8 hours

Question 1

Correct

Marked out of 3.00

[Flag question](#)

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,d;
5     scanf("%d %d",&a,&b);
6     c=a%10;
7     d=b%10;
8     if(c == d)
9     {
10         printf("true");
11     }
```

```
12 else
13 {
14     printf("false");
15 }
16 return 0;
17 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

[Next page ➡](#)

GE23131-Programming Using C-2024

Quiz navigation



Show all questions on one page

Finish review

Question 2

Correct

Marked out of 5.00

Flag question

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, n , perform the following conditional actions:

- If n is odd, print **Weird**
- If n is even and in the inclusive range of **2** to **5**, print **Not Weird**
- If n is even and in the inclusive range of **6** to **20**, print **Weird**
- If n is even and greater than **20**, print **Not Weird**

Complete the stub code provided in your editor to print whether or not n is weird.

Input Format

A single line containing a positive integer, n .

Constraints

- $1 \leq n \leq 100$

Output Format

Print **Weird** if the number is weird; otherwise, print **Not Weird**.

Sample Input 0

3

Sample Output 0

Weird

Sample Input 1

24

Sample Output 1

Not Weird

Explanation

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print **Weird**.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     if(n%2!=0 )
7     {
8         printf("Weird");
9     }
10    else if(n>=2 && n<=5)
11    {
12        printf("Not Weird");
13    }
14    else if(n>=6 && n<=20)
15    {
16        printf("Weird");
17    }
18    else
19    {
20        printf("Not Weird");
21    }
22    return 0;
23 }
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

GE23131-Programming Using C-2024

Quiz navigation

[Show all questions on one page](#)[Finish review](#)

Question 3

Correct

Marked out of 7.00

[Flag question](#)

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,d,f,e;
5     scanf("%d %d %d",&a,&b,&c);
6     d= a*a ;
7     e= b*b;
8     f = c*c;
9     if(a>b && b>c)
10 {
11     if((f+e) == d)
12     {
13         printf("yes");
14     }
15     else
```

```
16 {
17     printf("no");
18 }
19 }
20 else if(b>c && c>a)
21 {
22     if((d+f)== e)
23     printf("yes");
24     else
25     printf("no");
26 }
27 else
28 {
29     if(d+e == f)
30     printf("yes");
31     else
32     printf("no");
33 }
34 return 0;
35 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

[Previous page](#)[Finish review](#)