



Hello, 2024101067.

Diameter of a binary tree

[Submit solution](#)[My submissions](#)
[All submissions](#)
[Best submissions](#)✓ **Points:** 100 (partial)⌚ **Time limit:** 1.0s📄 **Memory limit:** 256M▼ **Allowed languages**

C

Given an array of integers which represents the `parent` of each node of the binary tree, return the length of the `diameter` of the tree.

The `diameter` of a binary tree is the length of the longest path between any two nodes in a tree.

The length of a path between two nodes is represented by the number of edges between them.

You are given an array which describes a tree structure where each element represents the parent of a corresponding node. If $\text{parent}[i] = -1$, node i is the root of the tree and j is the parent of i if $\text{parent}[i] = j$. Moreover it is guaranteed that node 1 will always be the root node and each node will have atmost 2 children.

The tree consists of n nodes, labeled from 1 to n . It is guaranteed that the tree is connected, meaning there is a path between any two nodes, and that there are no self-loops, i.e., for every node i , the parent of i is not i .

Input Format

- The first line contains an integer `t`, the number of testcases.
- The second line contains an integer `n`, the number of nodes in the tree.
- The third line contains n space-separated integers, where the i -th integer represents the parent of the i -th node. If the integer is -1 , the i -th node is the root node.

Output Format

- For each test case, output an integer representing the diameter of the corresponding binary tree.

Constraints

Hello, **2024101067**.

Following is the helper code for taking input and building the tree:

[Copy](#)



Hello, 2024101067.

```
int data;
struct Node* left;
struct Node* right;
};

// Function to create a new Node
struct Node* newNode(int x) {
    struct Node* node = (struct Node*)malloc(sizeof(struct Node));
    node->data = x;
    node->left = NULL;
    node->right = NULL;
    return node;
}

-----

int n;
scanf("%d", &n); // Read the number of nodes

int parent[n+1];
struct Node* nodes[n+1]; // Array to store all nodes

// Read the parent array
for (int i = 1; i <= n; i++) {
    scanf("%d", &parent[i]);
    nodes[i] = newNode(i); // Create a node for each index
}

struct Node* root = NULL;

// Construct the binary tree from the parent array
for (int i = 1; i <= n; i++) {
    if (parent[i] == -1) {
        root = nodes[i]; // Root node has no parent
    } else {
        struct Node* parentNode = nodes[parent[i]];
        if (parentNode->left == NULL) {
            parentNode->left = nodes[i]; // Assign left child
        } else if (parentNode->right == NULL) {
            parentNode->right = nodes[i]; // Assign right child
        }
    }
}
```

Example

Hello, **2024101067**.

```
10
3
-1 3 1
7
-1 1 5 7 7 4 1
4
-1 3 1 3
1
-1
5
-1 3 4 5 1
1
-1
1
-1
6
-1 4 2 1 3 2
1
-1
4
-1 4 1 1
```

Copy

Output

```
2
4
2
0
4
0
0
4
0
3
```

Copy

? Clarifications

[Request clarification](#)

No clarifications have been made at this time.