



Hello, 2024101067.

Subtree Minimum Query in a Binary Tree

[Submit solution](#)[All submissions](#)[Best submissions](#)✓ **Points:** 100 (partial)⌚ **Time limit:** 1.0s📄 **Memory limit:** 256M▼ **Allowed languages**

C

Given a binary tree, for every node from 0 to $n - 1$ find the node with the least value present in the subtree rooted at that node. The tree is represented by a **parent array**, where the index represents a node and the value at that index represents its parent's index. The root node is indicated by a parent value of -1 .

Input Format

- The **first line** contains a single integer n , the number of nodes in the tree.
- The **second line** contains n space-separated integers representing the parent array. For each node i :
 - If the value is -1 , then i is the root.
 - Otherwise, the value represents the index of node i 's parent.

Output Format

Print n integers where the i 'th integer represents the node with the least value present in the subtree of i 'th node

Constraints:

- Batch 1: $1 \leq N \leq 1e3$
- Batch 2: $1 \leq N \leq 1e5$

Samples

Input





Hello, 2024101067.

```
1 3 1 -1 3
```

Output

```
0 0 2 0 4
```

Copy

Input

```
6  
-1 0 0 1 1 2
```

Copy

Output

```
0 1 2 3 4 5
```

Copy

Input

```
6  
3 4 4 5 5 -1
```


Copy

Output

```
0 1 2 0 1 0
```

Copy

Binary Tree for Sample 1



? Clarifications

[Request clarification](#)



Hello, **2024101067**.