



Hello, 2024101067.

Dynamic Minimum Difference in a BST

[Submit solution](#)[All submissions](#)[Best submissions](#)✓ **Points:** 100 (partial)⌚ **Time limit:** 1.0s📄 **Memory limit:** 256M▼ **Allowed languages**

C

You are given an **initially empty Binary Search Tree (BST)**. You need to insert nodes one by one, and after each insertion, print the minimum absolute difference between values of any two nodes in the BST. It is guranteed that all the values to be inserted will be unique and between 1 and 10^9 .

Input Format

- The **first line** contains a single integer `n`, the number of insertions to be made in the tree.
- The **second line** contains `n` space-separated integers representing the values to be inserted in the tree.

Output Format

After every insertion print the minimum absolute difference between any two values in the tree. Since there is only one value in the tree after the first insertion print `-1` instead.

Constraints:

- Batch 1: $1 \leq N \leq 1e3$
- Batch 2: $1 \leq N \leq 1e5$

Samples

Input

```
5
4 2 6 1 3
```

[Copy](#)

Hello, **2024101067**.

```
-1 2 2 1 1
```

Copy

Input

```
8
5 1 9 15 21 18 12 6
```

Copy

Output

```
-1 4 4 4 4 3 3 1
```

Copy

Input

```
5
10 4 16 22 8
```

Copy

Output

```
-1 6 6 6 2
```

Copy

? Clarifications

[Request clarification](#)

No clarifications have been made at this time.