Status	Finished
Started	Thursday, 10 September 2026, 1:10 PM
Completed	Thursday, 10 September 2026, 1:17 PM
Duration	6 mins 48 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Complete

Mark 1.00 out of 1.00

What is the output of the following code :

```
x=True
y=False
z=False
if x or y and z:
    print("YES")
elif x and y or z:
    print("yes")
else:
    print("no")
```

a. Error

b. no

c. YES

d. yes

Question **2**

Complete

Mark 1.00 out of 1.00

What is the output of the following snippet?

```
s1 = "IIT "  # Remember there is a space after T in IIT
s2 = "Punjab"
s1 = s1 * 2
s2 = "Ropar"
print(s1, s2)
```

a. IIT Ropar

b. IIT IIT Ropar

c. IIT Punjab

d. IIT IIT Punjab

Question **3**

Complete

Mark 1.00 out of 1.00

What is the output of the given below program?

```
if 1 + 3 == 7:
    print("Hello")
else:
    print("REC")
```

a. Hello

b. Compiled Successfully, No Output.

c. **REC**

Question **4**

Complete

Mark 1.00 out of 1.00

Which among the following codes have equivalent logic?

Code 1:

```
if(value3>1000 and value3<1006):
  if(value1=="ABC"):
    if(value2=="A"):
      value4=10
    else:
      value4=8
  elif(value1=="XYZ"):
    if(value2=="A"):
      value4=8
    else:
      value4=6
print(value4)
```

Code 2:

```
if(value3>=1001 and value3<=1005 and value1=="ABC"):
    if(value2=="A"):
        value4=10
    else:
        value4=8
elif(value3>1000 and value3<1006 and value1=="XYZ"):
     if(value2=="A"):
        value4=8
     else:
        value4=6
print(value4)
```

Code 3:

```
if(value3>1000 and value3<1006 or value1=="ABC"):
   if(value2=="A"):
      value4=10
   else:
      value4=8
elif(value3>1000 and value3<1006 or  value1=="XYZ"):
   if(value2=="A"):
      value4=8
   else:
      value4=6
print(value4)
```

a. Code 1, Code 3

b. Code 1, Code 2

c. Code 2, Code 3

Question **5**

Complete

Mark 1.00 out of 1.00

To write else statement in if-elif ladder is mandatory?

a. False

b. True

Question **6**

Complete

Mark 1.00 out of 1.00

What does the arithmetic operator % do?

- a. Finds the remainder on dividing two numbers
- b. Finds the quotient on dividing two numbers
- c. Finds the sum of two numbers
- d. Finds the product of two numbers

Question **7**

Complete

Mark 1.00 out of 1.00

Correct syntax of writing 'simple if' statement is _____

- a. **if condition --**
  statements
- b. **if (condition)**
  statements
- c. **if condition :**
  statements
- d. **if condition**
  statements

Question **8**

Complete

Mark 1.00 out of 1.00

What is the value of x at the end of the following sequence of instructions?

```
x = 10
x = x * 3
x = x + 5
```

a. 45

b. 15

c. 30

d. 35

Question **9**

Complete

Mark 1.00 out of 1.00

What should be the value of num1 and num2 to get the output as "1"?

```
if((num1/num2==5) and (num1+num2)>5):
    print("1")
elif((num1-num2)<=1 or (num1%num2)==0):
    print("2")
else:
    print("3")
```

a. num1=0, num2=5

b. num1=5, num2=1

c. num1=-10,num2=2

d. num1=11, num2=2

Question **10**

Complete

Mark 1.00 out of 1.00

Number of elif in a program is dependent on the _____

a. **number of conditions to be checked**

b. **number of loops in a program**

c. All the Above

d. **number of variables in a program**

Question **11**

Complete

Mark 1.00 out of 1.00

What is the output

```
a, b, c = 1, 3, 5

if a + b + c:

    print("Hello")

else:

    print("Know Program")
```

a. Compiled Successfully, No Output.

b. Error

c. Know Program

d. Hello

Question **12**

Complete

Mark 1.00 out of 1.00

What is the output of the given below program?

```
if 1 + 3 == 7:
    print("Hello")
else:
    print("Know Program")
```

a. Error

b. Hello

c. Compiled Successfully, No Output.

d. Know Program

Question **13**

Complete

Mark 1.00 out of 1.00

____ is an empty statement in Python.

a. None

b. Empty

c. pass

d. Jump

Question **14**

Complete

Mark 1.00 out of 1.00

choose a valid Python if statement :

a. if a>=2 :

b. if (a >= 2)

c. if (a => 22)

Question **15**

Complete

Mark 1.00 out of 1.00

Given the nested `if-else` below, what will be the value `x` when the code executed successfully

```
x = 0
a = 5
b = 5
if a > 0:
    if b < 0:
        x = x + 5
    elif a > 5:
        x = x + 4
    else:
        x = x + 3
else:
    x = x + 2
print(x)
```

a. 4

b. 0

c. 2

d. 3