RSA Algorithm using Encryption and Decryption

Dr.Chandrakala.H.L
Assistant professor
Dept. of Computer science and Design
BGSCET
Bangalore, India

Kiran kumar N.A
Dept. of Computer science and Design
BGSCET
Bangalore, India
1MP22CG026@bgscet.ac.in

Tharun K.L
Dept. of Computer science and Design
BGSCET
Bangalore, India
1MP22CG057@bgscet.ac.in

Santhosh S.M
Dept. of Computer science and Design
BGSCET
Bangalore, India
1MP22CG048@bgscet.ac.in

Jagadhish kumar N
Dept. of Computer science and Design
BGSCET
Bangalore, India
1MP23CG402@bgscet.ac.in

ABSTRACT

The Data Encryption and Decryption Tool employs a hybrid cryptographic approach using AES and RSA algorithms to secure sensitive data. AES (Advanced Encryption Standard) is used for fast and efficient encryption of large data sets like files and images, while RSA (Rivest-Shamir-Adleman) ensures secure keys exchange. The tool is specifically designed for applications such as file, text, and picture encryption and decryption, making it versatile for various industries. It supports multiple data formats, providing robust protection for documents, images, and text messages. With its intuitive interface, users can easily encrypt and decrypt data, ensuring high-level confidentiality. This is ideal for securing personal, corporate, or sensitive information, complying with data protection standards, and is suitable for fields such as finance, healthcare, and secure communications.

Keywords:

RSA Encryption and Decryption, HTML, CSS, JavaScript, Python and other Libraries

I.Introduction of RSA Algorithm

It introduced in 1977 by Ron Rivest, Adi Shamir, and Leonard Adleman, is a widely used asymmetric cryptographic algorithm. It employs two keys for encryption and decryption:

- **Public Key:** Used for encryption**.**
- **Private Key:** Used for decryption.

The security of RSA relies on the difficulty of factoring large composite numbers, which makes it computationally secure. The algorithm is rooted in number theory, involving prime numbers, modular arithmetic, and Euler's Totient Function.

Steps in RSA Algorithm

1. **Key Generation**

The key generation process involves creating a public-private key pair.

Step 1: Choose two large prime numbers, p and q:

- Select two random prime numbers p and q.
- These numbers should be kept secret**.**

Step 2: Compute n:

- Multiply p and q:
  $n=p\times q$
- n will be part of both the public and private keys.

Step 3: Compute Euler's Totient Function, $\phi(n)$:

- Calculate$\phi(n)$ using formula:

$\phi(n)=(p-1)\times(q-1)$

- $\phi(n)$ represents the number of integers less than n that are coprime with n.

Step 4: Choose the public exponent e:

- Select e, which satisfies the following conditions:
  - $1<e<\phi(n)$
- Common choices for e are small prime numbers like 3, 17, or 65537.

Step 5: Compute the private key d:

- Calculate d as the modular multiplicative inverse of e modulo $\phi(n)$:
  $e\times\phi(n)=1e$

- This means d satisfies:

  $d=e-1\text{mod}\ \phi(n)d = e^{-1}$

Step 6: Generate the keys:

- PublicKey:(e,n)
- Private Key: (d,n)This is kept secret.

2. **Encryption**

This step uses the public key (e,n) to encrypt a message.

Step 1: Convert the plaintext message M into an integer m:

- Ensure mmm satisfies $0\leq m<n0$.
- If M is text, encode it (e.g., using ASCII or UTF-8) to convert it into an integer m.

Step 2: Compute the ciphertext C:

- Encrypt the message using the formula:C = m^e
- C is the encrypted message.

Step 3: Send the ciphertext C to the recipient.

3. Decryption

This step uses the private key (d,n)(d, n)(d,n) to decrypt the ciphertext.

Step 1: Compute the original message m:

- Use the formula: m=C^d

Step 2: Convert m back to plaintext M:

- Decode mmm (e.g., from ASCII or UTF-8) to retrieve the original plaintext message M.

Mathematical Basis of RSA

- Prime Numbers: Factoring the product of two large primes is computationally hard.
- Modular Arithmetic: Operations are performed over a modulus n.
- Euler's Totient Function: Counts numbers coprime to n, fundamental for key generation.

II. Frontend Development

HTML , CSS and JavaScript

The frontend design of an RSA Encryption & Decryption tool. The explanation of how the frontend can be implemented using HTML, CSS, and JavaScript.

- HTML provides the structure of the page and defines elements like buttons, inputs, and layout.
- CSS is used to style the layout, buttons, inputs, and container to make the interface visually appealing.
- JavaScript adds functionality to the buttons (e.g., handling RSA key generation, encryption, and decryption processes).

Conclusion

The RSA algorithm is a robust and widely adopted cryptographic technique that ensures secure communication through asymmetric encryption. By utilizing a public key for encryption and a private key for decryption, RSA guarantees confidentiality, integrity, and authentication of data. Its security relies on the computational difficulty of factoring large composite numbers, making it an essential foundation for modern encryption systems.

Future Scope of RSA Encryption and Decryption

1.Continued Relevance in Secure Communications

- RSA remains a cornerstone in securing communications, including SSL/TLS protocols for web security.
- It will continue to be used for:
    - Secure email communication (e.g., PGP encryption).
    - Digital signatures to verify authenticity.
    - Certificate authorities for identity verification.

2. Adaptation for Emerging IoT and 5G Networks

- With the proliferation of the Internet of Things (IoT) and the global adoption of 5G, secure data transmission is crucial.
- RSA could be adapted for:
    - Authenticating IoT devices.
    - Enabling secure communication in edge and cloud computing.

3. Hybrid Encryption Models

- RSA is often combined with symmetric encryption algorithms (e.g., AES) in hybrid systems to balance security and performance.

- These hybrid models are expected to evolve, particularly for applications in large-scale secure data exchanges (e.g., healthcare, finance, and cloud storage).

4. Quantum-Resistant Cryptography

- The rise of quantum computing poses a significant threat to RSA due to algorithms like Shor's, which can factor large numbers exponentially faster than classical computers.
- Future scope includes:
    - Transitioning RSA to higher key sizes (e.g., 4096-bit or greater) to counter immediate threats.
    - Phasing out RSA in favor of quantum-resistant algorithms (e.g., lattice-based cryptography).
    - Hybrid systems integrating RSA with post-quantum cryptographic techniques.

Challenges to Its Future

- Quantum computing advancements.
- Increasing key sizes leading to higher computational overhead.
- Adoption of more efficient, quantum-resistant algorithms

References

[1] Rongrong Xi, Shuyuan Jin, Xiaochun Yun and Yongzheng Zhang,"CNSSA: A Comprehensive Network Security Situation Awareness System", in International Joint Conference of IEEE TrustCom, ISSN: 978-0-7695-4600-1/11,doi: 10.1109/TrustCom.2011.62, 2011.

[2] Wang, C. Yao, A. Singhal and S. Jajodia, “Network Security AnalysisUsingAttack Graphs :Interactive Analysis of Attack Graphs using Relational Queries”, in proceedings of IFIP WG Working Conference on Data and Application Security (DBSEC), 11.3 pages 119-132, 2006.

[3] Mr. Marc Grégoire and Mr. Luc Beaudoin, “Visualisation for Network Situational Awareness in Computer Network Defence”, in proceedings of visualisation and the common operational picture meeting RTO-MP-IST-043, Paper 20. 2008.

[4] White Paper on, “Public Safety and Homeland Security SituationalAwareness”, in ESRI, February 2008.

[5] P. Barford, M. Dacier, T. G. Dietterich, M. Fredrikson, “Cyber SA: Situational Awareness”, in Cyber Defense University of Wisconsin, 2009.

[6] Rostyslav Barabanov, Stewart Kowalski and Louise Yngström, “Information Security Metrics”, DSV Report series No 11-007, Mar 25, 2011

[7] Pallavi Vaidya and S. K. Shinde, “Application for Network Security Situation Awareness”, in International Conference in Recent Trends in Information Technology and Computer Science (ICRTITCS - 2012), IJCA, ISSN: 0975 – 8887, 2012.

[8] Xiu-Zhen Chena, Qing-Hua Zhenga, Xiao-Hong Guana,b, Chen-Guang Lina,Jie Sun, “Multiple behavior information fusion based quantitative threat evaluation”, in Elsevier Journal of Computers & Security , ISSN: 0167-4048 ,doi:10.1016/j.cose.2004.08.009,2005. pp 218-231

[9] Lingyu Wang, Tania Islam, Tao Long, Anoop Singhal, and Sushil Jajodia,“An Attack Graph-Based Probabilistic Security Metric”, in National Institute of Standards and Technology Computer Security Division; Concordia Institute forInformation Systems Engineering, Montreal, Canada.

[10] Marianne Swanson, Nadya Bartol, John Sabato, Joan Hash, and LaurieGraffo, “Security Metrics Guide for Information Technology Systems”, in NISTSpecial Publication 800-55, July 2003.

[11] William Streilein, Kendra Kratkiewicz, Michael Sikorski, Keith Piwowarski, Seth Webster, “PANEMOTO: Network Visualization of Security Situational Awareness through Passive Analysis“, inWorkshop on Information Assurance United States Military Academy, Proceedings of the IEEE, 2007.

[12] Rongzhen FAN, Mingkuai ZHOU, “Network Security Awareness andTracking Method by GT”, in Journal of Computational Information Systems, Binary Information Press, ISSN: 1043-1050, Vol. 9: Issue 3, 2013.