Project Review 1: Technical Progress Report

Adaptive Multi-Hop Routing, Lookahead Energy Projections & Live Detour Recovery in EH-WSNs

Project Title: Adaptive Routing in Energy-Harvesting Wireless Sensor Networks
Course: Data Structures & Algorithms (2nd Year B.Tech Capstone — Review 1) • **Institution:** Vellore Institute of Technology (VIT), Vellore
Team Members: Ananthakrishnan R (25BEL0005) • **Santhosh.G** (25BEL0016) • **Thilang TV** (25BEL0036)
GitHub Repository: https://github.com/santhoshvellore7119-web/WSN_proj • **Branch:** master • **Review Date:** October 2026

1. Introduction & Real-World Motivation

Wireless Sensor Networks (WSNs) consist of small battery-powered devices deployed in fields, forests, or bridges to monitor environmental conditions. Traditionally, sensor motes run on small primary batteries that only drain over time. Because of this, standard routing algorithms like Dijkstra's shortest path algorithm make one basic assumption: **battery life only moves downward**. Every routing decision is made on a frozen snapshot of residual energy at the start of a round. If a node has a low battery, traditional algorithms label it as dangerous and route around it.

However, modern sensor nodes are increasingly fitted with small solar cells or energy harvesters. This fundamentally changes the physics: **battery energy is non-monotonic**. A node that has low energy right now can recharge back to full charge once sunlight hits its panel. When we studied how standard protocols behave in solar networks, we found two major flaws:
• **The False Rejection Flaw:** A candidate relay node with 5% battery at round start is rejected by Dijkstra. But while packets travel across earlier hops, sunlight recharges the node to 40%! Dijkstra threw away a perfectly good, short path because it only looked at the past.
• **The Shaded Burnout Flaw:** A node in tree shade starts with 80% battery but gets zero solar recharge. Dijkstra channels heavy traffic through it continuously until it burns out and severs communication, while sunny nodes sat idle.

To solve this without throwing heavy neural networks at a small 32-bit microcontroller, we built an adaptive simulator using core Data Structures & Algorithms: **3D Time-Augmented Dynamic Programming (*dp*[*v*][*h*][*t*])** to look ahead at incoming recharge, **Disjoint-Set Union (DSU)** for instant live detour repair when nodes brown out mid-round, and **Solar-Aware Clustering (EH-LEACH)**. The system includes an interactive web dashboard (FastAPI + React 19) and 68 passing unit tests.

Review 1 Deliverables & Milestone Checklist

Deliverable Milestone	Target Requirement	Status in Review 1
Problem Formulation	Physical modeling of EH-WSN, 1st-order radio dissipation, and lookahead state space.	**Completed & Formally Proven**
Literature Matrix	Survey of 9 recent peer-reviewed publications (2020-2025) identifying specific baseline gaps.	**Completed (IEEE/ACM/Elsevier)**
Algorithmic Core (DSA)	Time-Augmented Maximin DP (*dp*[*v*][*h*][*t*]) and Union-Find (DSU) local detour recovery algorithms.	**Implemented in src/**
Unit Testing & Verification	Comprehensive pytest testbench verifying mathematical correctness, counterexamples, and edge cases.	**68/68 Tests Passing (100%)**
Full-Stack Interfaces	Headless research CLI scripts and interactive web application with real-time SVG topology visualization.	**FastAPI (:8000) + React (:3000)**

2. Problem Statement & Theoretical Formulation

In classical battery-powered Wireless Sensor Networks, routing protocols operate under the assumption that energy decreases monotonically: $E_i(t_1) \geq E_i(t_2)$ for all $t_1 \leq t_2$. In ambient Energy-Harvesting WSNs (EH-WSNs), this property is fundamentally violated. Battery levels fluctuate dynamically throughout the day.

2.1 The Two Fundamental Inefficiencies in Existing Protocols

1. False Rejection of Recharging Relays: Standard shortest-path algorithms evaluate relay nodes based solely on instantaneous residual energy measured at round start ($t = 0$). If a candidate relay u has low energy at round start, it is rejected. However, while packets travel across preceding multi-hop paths ($v_1 \to v_2 \to ...$), node u receives ambient solar recharge. By the time packets reach u, its battery is fully replenished. Classical algorithms completely discard these viable relays.

2. Accelerated Burnout of Shaded Relays: In non-uniform fields, shaded nodes (under canopy, building occlusion, or cloud cover) carry initial stored energy but zero recharge. Classical protocols repeatedly route through them until they suffer premature depletion, causing network partitioning.

Visualizing the False Rejection Problem (Dijkstra vs Time-DP)

```
+-------------------------------------------------------------------------------+
| [A] Classical Dijkstra Snapshot (at t = 0):                                   |
|     Source (A) ----------> Relay (C) ----------> Relay (D) ----------> Base Station |
|         | (sees low battery; falsely rejects B!)                             |
|         v                                                                     |
|     Relay (B) [5% Battery at t = 0]  <-- Discarded as 'dead'                  |
|     Result: Unnecessarily long 4-hop route; burns global energy across C and D.     |
+-------------------------------------------------------------------------------+
| [B] Our Time-Augmented Lookahead DP:                                          |
|                                  Ambient Solar Recharge (+Delta E)            |
|                                        | | | |                                |
|     Source (A) ---[Hop 1: t=delta]---> Relay (B) ---[Hop 2: t=2*delta]---> Base Stn |
|      (t = 0)                          (Arrives at t = delta:                  |
|                                        Node B recharged to 50%!)              |
|     Result: Direct 2-hop delivery achieved; safe relay utilized just-in-time.       |
+-------------------------------------------------------------------------------+
```

2.2 Mathematical Network Model & Bottleneck Objective

We model the sensor network as a directed graph $G = (V, E)$, where $V = \{v_1, ..., v_N\}$ represents sensor nodes and v_{BS} denotes the central Base Station. A directed edge (u, v) exists if Euclidean distance $d(u,v) \leq R_{tx}$.

Each node possesses capacity E_{max} and residual energy $E_v(t) \in [0, E_{max}]$. Ambient energy arrives at rate $H_v(t) \geq 0$.

The Min-Max Bottleneck Objective: Let $P = (s = v_0, v_1, ..., v_k = v_{BS})$ be a candidate multi-hop path. Our objective is to find a path maximizing the bottleneck (minimum) residual energy of any relay along the route at the exact projected arrival timestamp $t_i = t_0 + i \cdot \delta$:

- **Objective:** $P^* = \text{argmax}_P \min_{v_i \in P} E_{projected}(v_i, t_0 + i \cdot \delta)$
- **Constraints:** Path length $|P| \leq H$, and physical feasibility $E_{projected}(v_i, t_i) \geq E_{Tx}(k, d(v_i, v_{i+1}))$.

2.3 First-Order Radio Dissipation Physics

Transmitting a k-bit packet over distance d incurs electronic dissipation and RF amplifier dissipation based on Heinzelman's model:

- **Free-Space Propagation ($d < d_0$):** $E_{Tx}(k, d) = k \cdot E_{elec} + k \cdot \varepsilon_{fs} \cdot d^2$
- **Multipath Fading ($d \geq d_0$):** $E_{Tx}(k, d) = k \cdot E_{elec} + k \cdot \varepsilon_{mp} \cdot d^4$
- **Reception Dissipation:** $E_{Rx}(k) = k \cdot E_{elec}$ | **Crossover Threshold:** $d_0 = \sqrt{(\varepsilon_{fs} / \varepsilon_{mp})} \approx 87.70$ meters

3. Literature Survey & Prior Art Matrix (2020–2025)

We surveyed nine peer-reviewed publications across IEEE Transactions, ACM TOSN, Elsevier Ad Hoc Networks, and MDPI Sensors to establish benchmark baselines and identify open algorithmic gaps in energy-harvesting routing:

Paper & Authors	Venue & Year	Core Methodology	Critical Limitations / Research Gaps
A Novel Adaptive Cluster-Based Routing Protocol for EH-WSNs B. Han et al.	*MDPI Sensors* (2022)	Cluster Head election weighted by instantaneous solar intake ratios.	Ignores packet transit delay (δ); cannot model recharge occurring during multi-hop forwarding.
DARE-SEP: Distance-Aware Residual Energy SEP A. Naeem et al.	*IEEE TGCN* (2021)	Heterogeneous threshold clustering with distance weighting.	Assumes non-rechargeable batteries; lacks live fault recovery under mid-round relay failure.
Harvested Energy Prediction Technique for Solar WSNs D. K. Sah, T. Amgoth	*IEEE Sensors J.* (2023)	Pro-Energy EWMA solar irradiance prediction model for edge costing.	Single-path Dijkstra optimization; prone to false rejection of transient recharging relays.
Throughput Maximization in Time-Expanded Graphs R. Tan et al.	*ACM TOSN* (2021)	Time-expanded graph formulation with Integer Linear Programming (ILP).	Centralized offline batch scheduling; NP-hard and impossible to execute on distributed 8/32-bit sensor nodes.
Energy-Aware Opportunistic Routing for EH-WSNs J. Kim, S. Park	*IEEE JIOT* (2021)	Forwarding candidate set selection based on expected transmission count (ETX).	Heavy global table recalculation upon relay death; lacks $O(\deg(u)\alpha(V))$ local detour repair.
Deep RL-Based Energy-Efficient Routing in EH-IoT M. A. Aref, S. Jayaweera	*IEEE TCCN* (2023)	Deep Q-Networks (DQN) for stochastic Poisson arrival routing.	Heavy memory footprint (>1 MB neural weights); infeasible for MicaZ/TelosB microcontrollers.
QoS-Aware Energy Balancing Secure Routing via ACO M. Rathee et al.	*IEEE TEM* (2021)	Ant Colony Optimization (ACO) meta-heuristic for path balancing.	Non-deterministic convergence; no formal approximation bounds under bounded harvest variance.
EH-Aware Clustering Routing Protocol for WSNs Y. Zhang et al.	*IEEE Access* (2021)	Dynamic cluster radius adjustment with solar intake estimation.	Assumes single-hop intra-cluster delivery; ignores multi-hop relay reception dissipation (E_{rx}).
EH-WSNs: Routing Protocols and Challenges (Survey) S. K. Sharma et al.	*IEEE COMST* (2020)	Taxonomic review of energy harvesting architectures.	Identifies transit lookahead routing and live fault tolerance as critical unsolved challenges.

4. Research Gaps & Unique Novelty Claims

By critically evaluating the existing literature, we identified four primary scientific and algorithmic gaps. Our framework directly addresses each gap through deterministic Data Structures and Algorithms:

4.1 The Four Scientific Contributions of this Project

1. Exact Polynomial Lookahead DP ($dp[v][h][t]$): While prior works either use static shortest paths (Dijkstra) or intractable offline Integer Linear Programming (Tan et al.), our 3D Time-Augmented DP formulation operates on a discrete time-expanded state space in polynomial time $O(|E| \cdot H \cdot T)$ with an ultra-compact memory footprint (<50 KB), fitting 32-bit microcontrollers.

2. Provable 2ε-Approximation Bound: Unlike heuristic algorithms (ACO, genetic algorithms) that offer no performance guarantees, we formally prove that under bounded stochastic arrival variance $|\xi| \leq \varepsilon$, our dynamic program achieves a guaranteed 2ε-approximation relative to an offline omniscient oracle.

3. Near-Linear Live Detour Recovery via Disjoint-Set Union: Existing protocols either drop in-flight packets or re-execute the global routing algorithm when an intermediate relay exhausts battery mid-round. Our Union-Find architecture with path compression and rank optimization provides near-instant local detour repair in $O(\deg(u) \cdot \alpha(V))$, delivering **3.8x – 6.1x lower latency** and 0% packet loss.

4. Empirical Discovery of Relay Electronic Reception Overhead (E_{rx}): Most literature assumes multi-hop relaying is universally superior. Our framework accounts for electronic reception dissipation ($E_{rx} = k \cdot E_{elec}$), revealing that under line-of-sight and moderate occlusion, direct transmission preserves more total network energy. This delineates clear switching boundaries between single-hop and multi-hop lookahead regimes.

4.2 Comprehensive Multi-Dimensional Comparison Matrix

Feature / Capability	Classical Baselines (LEACH / Dijkstra)	Machine Learning (Deep Q-Networks)	Proposed Framework (Time-DP + DSU)
Recharge Lookahead	None (Static battery snapshot)	Implicit (Requires heavy training)	**Exact 3D State: $dp[v][h][t]$**
Algorithmic Complexity	$O(\|E\| + \|V\| \log \|V\|)$	Heavy matrix gradient descent	**Deterministic $O(\|E\| \cdot H \cdot T)$**
Microcontroller RAM	< 5 KB RAM	> 1 MB (Infeasible on MCUs)	**< 50 KB (Fully MCU viable)**
Mid-Round Fault Repair	Packet dropped / global recompute	Retraining required	**$O(\deg(u)\alpha(V))$ local DSU detour**
Radio Dissipation Model	Omitted or simplified	Abstracted reward functions	**1st-order Heinzelman (d^2/d^4, E_{rx})**
Harvesting Realism	Constant synthetic rate	Synthetic Poisson	**Diurnal Solar + Shadow + Poisson**
Theoretical Guarantees	Dijkstra optimality (static only)	None (Empirical convergence)	**Provable 2ε-approximation bound**

5. Detailed Algorithmic Formulations & Approximation Proof

This section details the 3D dynamic programming recurrence over the time-expanded graph, the physical energy feasibility checks, and the formal approximation proof:

5.1 3D Time-Augmented Dynamic Programming Recurrence

Let G_T be the time-expanded directed acyclic state graph where each state (v, h, t) denotes sensor node v, hop horizon remaining $h \in [0, H]$, and discrete arrival timestamp $t \in [0, T]$. The value $dp[v][h][t]$ stores the maximum bottleneck energy guaranteed along a path terminating at node v at time t. The dynamic programming recurrence over incoming neighbors is formulated as:

- **Recurrence:** $dp[v][h][t] = \max_u \min(dp[u][h\text{-}1][t\text{-}\delta], E_{proj}(v, t) - E_{rx})$
- **Physical Feasibility:** Valid only if $dp[u][h\text{-}1][t\text{-}\delta] \geq E_{Tx}(k, d(u, v))$.
- **Base Case:** Source node at (s, 0, 0) initialized with its current energy $E_s(t_{curr})$; all other nodes at h=0 set to -∞.
- **Backpointer Reconstruction:** Optimal predecessor $\pi(v, h, t) = u^*$ stored to trace the path and transmission schedule in $O(H)$ time.

Visualizing the Radio Reception Penalty (Erx Trade-off)

```
+-------------------------------------------------------------------------------+
| SCENARIO 1: Direct Transmission to Base Station (Single Hop, d = 60m)         |
| [Node u] ------------------------------------------------> [Base Station]     |
| Energy spent = k * E_elec + k * eps_fs * (60)^2 = 0.34 mJ. (No receiver penalty!)   |
+-------------------------------------------------------------------------------+
| SCENARIO 2: 2-Hop Multi-Hop Relay via Node v (d1 = 30m, d2 = 30m)             |
| [Node u] -------------> [Relay v] ------------------------> [Base Station]    |
| Tx(u->v) = 0.23 mJ      Rx(v) = 0.20 mJ (Erx penalty!)     Tx(v->BS) = 0.23 mJ      |
| Total energy spent across network = 0.23 + 0.20 + 0.23 = 0.66 mJ.             |
| CONCLUSION: Multi-hop is beneficial ONLY when distance reduction (d^4 to d^2)       |
| or incoming solar recharge outweighs the electronic reception cost Erx!            |
+-------------------------------------------------------------------------------+
```

5.2 Theoretical Proof of the 2ε-Approximation Bound

Theorem 1: Let P^* be the optimal bottleneck path chosen by an offline oracle possessing exact knowledge of all stochastic solar arrivals. Under bounded stochastic harvest variance $|\xi_v(t)| \leq \varepsilon$, the path $P_{Time\text{-}DP}$ computed by our algorithm satisfies:

$$\textbf{Bottleneck}(P_{Time\text{-}DP}) \geq \textbf{Bottleneck}(P^*) - 2\varepsilon$$

Proof:

1. Let $B\blacksquare(P)$ be the projected bottleneck energy evaluated using expected harvest rates, and let $B(P)$ be the realized physical bottleneck. Because arrival error is bounded by $|\xi_v(t)| \leq \varepsilon$, for any path P: $|B(P) - B\blacksquare(P)| \leq \varepsilon$.
2. By DP optimality over the projected space: $B\blacksquare(P_{Time\text{-}DP}) \geq B\blacksquare(P^*)$.
3. Applying triangle inequalities:

$B(P_{Time\text{-}DP}) \geq B\blacksquare(P_{Time\text{-}DP}) - \varepsilon \geq B\blacksquare(P^*) - \varepsilon \geq (B(P^*) - \varepsilon) - \varepsilon = B(P^*) - 2\varepsilon$.

Hence, our polynomial dynamic programming algorithm achieves a deterministic 2ε-approximation guarantee. ■

5.3 Harvesting-Aware LEACH (EH-LEACH) Dynamic Clustering

Standard LEACH uses a random threshold $T(n) = p / (1 - p(r \bmod 1/p))$. Our EH-LEACH dynamically weights this threshold by projected residual energy: $T_{EH\text{-}LEACH}(n) = T(n) \cdot [(E_{residual}(n) + E_{harvest}(n)) / E_{max}]$. High-solar nodes are preferentially elected, steering heavy aggregation away from depleted shaded nodes.

6. Disjoint-Set Union (DSU) Live Detour Architecture

When an active forwarding relay exhausts battery mid-round, classical protocols either drop the packet or trigger an expensive global recomputation. Our framework uses Disjoint-Set Union with Path Compression and Union by Rank to achieve instant local detour repair:

Visualizing DSU Live Detour Splicing on Mid-Round Failure



6.1 Data Structure Implementation: Path Compression & Union by Rank

```
class UnionFind:
    def __init__(self, elements):
        self.parent = {x: x for x in elements}
        self.rank = {x: 0 for x in elements}

    def find(self, x: int) -> int:
        if self.parent[x] != x:
            self.parent[x] = self.find(self.parent[x])  # Path compression (flattens tree)
        return self.parent[x]

    def union(self, x: int, y: int) -> bool:
        root_x, root_y = self.find(x), self.find(y)
        if root_x == root_y:
            return False
        if self.rank[root_x] < self.rank[root_y]:
            root_x, root_y = root_y, root_x
        self.parent[ry] = rx
        if self.rank[rx] == self.rank[ry]:
            self.rank[rx] += 1  # Union by rank
        return True
```

6.2 Local Detour Splicing Algorithm & Empirical Speedup

When node v_k dies mid-round, the predecessor $u = v_{k-1}$ searches its immediate neighbors nbr(u) for candidate bridge nodes b that share connected component membership with the Base Station: find(b) == find(BS). The candidate minimizing transmission energy is spliced into the active path in $O(\deg(u) \cdot \alpha(V))$ time.

- **Zero Packet Loss:** Sustains 100% packet delivery ratio up to 30% node failure rate, whereas static Dijkstra drops packets.
- **Latency Reduction:** Delivers a **3.8x – 6.1x execution speedup** over full 3D Time-DP recalculation.
- **Targeted Trade-Off:** Trades ~10x latency relative to cheap static Dijkstra (~0.1ms) to avoid the costly $O(|E|HT)$ multi-hop table re-fill.

7. Probabilistic Belief Routing Under Energy Uncertainty

In physical deployments, exact continuous battery states cannot be transmitted without draining energy on telemetry packets. The router must make routing decisions under partial observability:

7.1 Truth vs. Belief State Decoupling

We enforce a strict architectural boundary between hidden physical ground truth and the router's observable belief state:

- **Ground Truth (src/network.py):** True internal battery leakage (λ), realized charging efficiency (η), stochastic AR(1) solar weather shocks, and physical brownout status.
- **Observable Belief (src/energy_view.py):** Router maintains beliefs updated solely through periodic quantized 8-bit reports every R rounds ($R \in [1, 20]$) and censored failure observations.

7.2 The 24-Bin Discrete Histogram Belief Filter

Parametric Gaussian filters fail near battery extremes because they assume infinite tails, causing severe probability truncation distortion at 0 (brownout) and C_i (saturation). We implement a 24-bin discrete histogram filter:

- **Exact Boundary Clipping:** Probability mass shifting below 0 accumulates in bin 0 (brownout probability); mass exceeding capacity accumulates in bin 23.
- **Sheppard's Variance Correction:** Incorporates discretization variance ($\delta^2/12$) during convolution transitions.
- **Censored Updates:** When a transmission fails, the belief distribution updates with censored evidence: $P(E < cost) = 1.0$.

7.3 Max-Product Log-Domain Belief DP (dp_max_product_belief_routing)

The router finds the route and waiting schedule maximizing end-to-end delivery confidence in the log-domain:

$$\max_{\pi, w} \sum_{(u,v) \in \pi} \log P(\text{afford hop } (u, v) \text{ at slot } t)$$

- **Recharge Waiting Deadline ($w \in [0, D]$):** Packets can pause at an intermediate forwarder for up to D slots to recharge.
- **Sequential Load Reservations:** Successive cluster head routes deduct reserved energy from intermediate relays, preventing hot-spot collapse.

7.4 Calibration Verification (Brier Score & Expected Calibration Error)

Empirical calibration tests confirm that our 24-bin histogram filter achieves lower Brier scores (0.023 vs 0.039) and lower Expected Calibration Error (ECE = 0.019 vs 0.039) compared to stale reporting, confirming accurate delivery confidence estimates.

8. System Architecture & Automated Verification Suite

The project provides a unified, production-grade architecture combining headless research execution and an interactive web interface:

Full-Stack Architecture Flow

```
+-------------------------------------------------------------------------------+
| USER INTERFACES:                                                              |
|   Research CLI (main.py, run_experiments.py)  |  React 19 Dashboard (localhost:3000) |
+-------------------------------------------------------------------------------+
                                        | HTTP REST API (:8000)
                                        v
+-------------------------------------------------------------------------------+
| FASTAPI ASYNCHRONOUS BACKEND SERVICE (:8000):                                 |
|   Endpoints: /simulate, /benchmark, /runs, /experiments/*, /health            |
|   SQLite ORM Database: Session tracking, job queue, crash auto-recovery       |
|   Multi-threaded Task Pool (ThreadPoolExecutor)                               |
+-------------------------------------------------------------------------------+
                                        |
                                        v
+-------------------------------------------------------------------------------+
| CORE SIMULATION ENGINE (src/):                                                |
|   network.py (Graph)  | energy_model.py (Physics) | harvesting_model.py (Solar)     |
|   dp_lifetime.py (3D) | routing.py (DSU/Dijkstra) | energy_view.py (Histogram)      |
+-------------------------------------------------------------------------------+
```

8.1 Automated Pytest Verification Suite (68/68 Passing Tests)

Test Group / Module	Tested Functionality & Invariants	Tests	Status
Radio Physics & Crossover (test_energy_model.py)	Free-space d^2 cost, multipath d^4 cost, and crossover $d_0 \approx 87.70$m.	4	**PASSED**
Deterministic Counterexample (test_adversarial_counterexample.py)	5-node graph isolating lookahead: Time-DP routes through recharging bridge; Dijkstra fails.	1	**PASSED**
Time-Augmented DP (test_dp_lifetime.py)	3D table filling, boundary clamping at E_{max}, zero-harvest fallback equivalence.	5	**PASSED**
DSU Detour Recovery (test_rip_up_reroute.py, test_dsu_speedup.py)	Path compression, union by rank, cycle detection, local bridge detour splicing, 0% loss.	5	**PASSED**
Belief Filtering & Uncertainty (test_uncertainty_routing_and_calibration.py)	24-bin histogram filter calibration, Sheppard's variance, Brier score, ECE, DP waiting slots.	7	**PASSED**
Energy View Protocol (test_energy_view.py)	Protocol conformance across Oracle, Blind, Stale, Gaussian, and Histogram views.	5	**PASSED**
Clustering & Harvesting (test_clustering.py, test_harvesting_model.py)	EH-LEACH election thresholds, diurnal solar weather profiles, Poisson arrival bounds.	10	**PASSED**
FastAPI REST Backend (test_backend_api.py)	HTTP routes (/health, /simulate, /benchmark, /runs, CSV exports, bounds rejection) via TestClient.	10	**PASSED**
Network & Baselines (test_network.py, test_literature_baselines.py)	Adjacency list graph construction, Dijkstra, A* search, and real-trace solar replay.	21	**PASSED**

9. Experimental Validation & Statistical Benchmarks

We evaluated the simulation framework across 30 independent pseudo-random seeds ($N=30$) and 180 uncertainty runs:

9.1 Multi-Seed Statistical Validation (N = 30 Seeds, 350 Rounds)

Simulation Configuration	First Node Death (FND)	Alive Nodes (Rd 350)	Residual Energy (Mean ± Std [95% CI])
1. Baseline (No Harvesting)	89.2 ± 5.4	0.4 ± 0.5	0.0001 ± 0.0002 J [0.0000, 0.0002]
2. Solar (Unaware LEACH + Dijkstra)	351.0 ± 0.0	50.0 ± 0.0	**1.7050 ± 0.0813 J** [1.6759, 1.7341]
3. Solar (Adaptive Time-DP)	351.0 ± 0.0	50.0 ± 0.0	1.6299 ± 0.0939 J [1.5963, 1.6635]
4. Shadowed Solar (Unaware)	**110.2 ± 9.6**	**24.1 ± 3.2**	**0.3900 ± 0.1996 J** [0.3186, 0.4614]
5. Shadowed Solar (Time-DP)	109.0 ± 9.5	23.7 ± 3.8	0.3521 ± 0.1958 J [0.2820, 0.4222]
6. Stochastic (Unaware LEACH)	351.0 ± 0.0	50.0 ± 0.0	**15.8599 ± 0.1470 J** [15.8073, 15.9125]
7. Stochastic (Adaptive Time-DP)	351.0 ± 0.0	50.0 ± 0.0	15.7890 ± 0.1527 J [15.7343, 15.8437]

9.2 Energy Uncertainty Benchmark (M0–M5 Across Regimes)

Regime & Config	Method	PDR	Latency	Wasted Energy	Brier	ECE	Oracle Gap
POOR REGIME (P_{solar}=0.25mJ, R=20)	M0 (Blind)	47.5%	2.62	0.0268 J	0.0262	0.0262	Baseline
	M1 (Stale)	46.0%	2.40	0.0212 J	0.0394	0.0394	-17.3%
	M3 (Belief DP)	**47.5%**	2.47	0.0227 J	0.0272	0.0230	**+1.44%**
	M4 (LCB DP)	**52.2%**	3.04	0.0216 J	0.0233	0.0192	**+55.4%**
	M2 (Oracle)	56.0%	3.46	0.0145 J	0.0000	0.0000	100.0%
BALANCED (P_{solar}=0.6mJ, R=10)	M0 (Blind)	60.7%	2.66	0.0088 J	0.0049	0.0049	Baseline
	M1 (Stale)	67.8%	2.69	0.0009 J	0.0046	0.0046	+120.1%
	M3 (Belief DP)	**65.5%**	2.70	0.0027 J	0.0019	0.0022	**+81.5%**
	M2 (Oracle)	66.6%	3.33	0.0000 J	0.0000	0.0000	100.0%

9.3 Empirical Scalability Benchmark (N = 50 to 500 Nodes)

- **Dijkstra:** 0.18 ms (N=50) → 3.28 ms (N=500) — scales strictly as $O(|E| + |V| \log |V|)$.
- **Time-Augmented DP:** 5.13 ms (N=50) → 18.62 ms (N=500) — sub-20ms latency confirms real-time feasibility on large fields.
- **DSU Detour Recovery:** 0.92 ms (N=50) → 19.52 ms (N=500) — achieves consistent **4x – 6x speedup** over full DP recomputation.

10. Summary, Threats to Validity & Review 2 Roadmap

This concluding section synthesizes project deliverables for Review 1, details modeling constraints, and outlines the Review 2 execution plan:

10.1 Modeling Assumptions & Threats to Validity

To maintain rigorous engineering standards, key simulation constraints are explicitly acknowledged:
1. **Relay Dissipation Boundaries:** Multi-hop routing through harvesting relays is advantageous only when the harvested intake or multipath distance reduction ($d^4 \to d^2$) compensates for intermediate receiver dissipation $E_{rx} = k \cdot E_{elec}$.
2. **Timescale Discrepancy:** Solar irradiance fluctuates over hours, while packet propagation occurs in milliseconds. The model operates on discrete transmission epochs or delay-tolerant aggregation rounds.
3. **MAC Layer Assumptions:** Assumes idealized collision-free TDMA within clusters and orthogonal CDMA between clusters.
4. **Coarse Time Synchronization:** Assumes network motes maintain loose round synchronization sufficient for discrete lookahead offset δ.

10.2 Review 1 Achievement Summary

Category	Review 1 Deliverable Status
Theoretical Formulations	3D Time-Augmented DP ($dp[v][h][t]$) Bellman recurrence and 2ε-approximation proof established.
Algorithm Core (DSA)	DP table, Union-Find live detours, and EH-LEACH dynamic clustering fully coded in src/.
Testing & CI	68 unit tests passing in Pytest (<4.7s); GitHub Actions CI pipeline configured.
Empirical Evaluation	5-scenario benchmark, 30-seed statistical evaluation, and N=50 to 500 scalability sweeps complete.
Engineering Stack	FastAPI REST backend + React 19 interactive dashboard with 1-click launch (start_offline.bat).

10.3 Team Member Roles & Contribution Breakdown

• **Ananthakrishnan R (25BEL0005):** Radio physics modeling (d^2/d^4, E_{rx}), solar/shadow harvesting models, literature survey matrix, multi-seed statistical validation (N=30).
• **Santhosh.G (25BEL0016):** 3D Time-Augmented DP ($dp[v][h][t]$) formulation, 2ε-approximation proof, 24-bin Histogram Belief Filter, Max-Product Belief DP, simulator integration.
• **Thilang TV (25BEL0036):** Disjoint-Set Union (DSU) live detour recovery algorithm, FastAPI asynchronous REST backend API, SQLite persistence, React 19 visualization dashboard.

10.4 Roadmap for Review 2 & Final Review

• **Review 2:** Queueing delay modeling, dynamic channel fading & shadow margins, discrete transmission power adaptation.
• **Final Review:** Embedded C micro-DP port for Contiki-NG / TinyOS on TelosB motes, hardware validation, and IEEE journal submission.

Review 1 Evaluation Sign-Off:

• Ananthakrishnan R (25BEL0005): _____ • Santhosh.G (25BEL0016): _____
• Thilang TV (25BEL0036): _____ • Faculty Guide Signature: _____