

SUBS


Item	Description	Upper connection	Lower connection	Size	Туре
1	Kelly sub	Kelly	Drill pipe	All size	A or B
2	Drill pipe sub	Drill pipe	Drill pipe	All size	A or B
3	sub	Drill pipe	Drill collar	All size	A or B
4	Drill collar sub	Drill collar	Drill collar	All size	A or B
5	Drill Bit sub	Drill collar	Drill bit	All size	A or B
6	Swivel sub	Swivel lower sub	Kelly	All size	С
7	Fishing sub	Kelly	Drill pipe	All size	С
		Drill pipe	Fishing tool	All size	С

Type A: One sub has one same OD.

Type B: One sub has two sizes OD.

Type C: The connection type is left hand type.


STRAIGHT OD SUBS



BOX*BOX PIN*PIN


BOX*PIN

SUBS WITH FISHING NECK



BOX*BOX BOX*PIN PIN*PIN


KELLY SAVER SUBS



KELLY SAVER
SUB NO PROTECTOR


KELLY SAVER SUB

BIT SUBS










BIT SUB WITH FLOAT

BIT SUB NO

FLOAT


LIFT SUB





Lift Cap


Bit Box Float Bores



Bit Box Size	Baker Float Type	L	DF	d1
2 3/8REG	1R	9 1/8	3-3/64	1 11/16
2 7/8REG	1F-2R	10	3 39/64	1-15/16
3 1/2REG	2F-3R	10-1/2	4-7/64	2-7/16
4 1/2REG	4R	12-13/16	5-21/64	3-1/2
6 5/8REG	5F-6R	17	7-23/64	4-13/16
7 5/8REG	5F-6R	17-1/4	8-15/32	4-13/16
8 5/8REG	5F-6R	17-3/8	9-35/64	4-13/16
O STOTILO	6F	20-1/4	9-35/64	5-23/32


Float Valve Sub





Technical specifications and parameters					
Type	Sub O.D.	Joint	Valve O.D.	LD.(mm)	
FFITO 4.1	(mm)	connection	(mm)	+7 6	
FFJT241	241.3	7 5/8 REG	Ф121	Ф76	
FFJT228	228.6	7 5/8 REG	Ф121	Ф76	
FFJT209	209.6	6 5/8 REG	Ф121	Φ76	
FFJT203	203.2	6 5/8 REG	Ф121	Φ71	
FFJT178	177.8	4 1/2 IF	Ф88	Φ71	
FFJT165	165.2	4 1/2 REG	Ф88	Ф57	
FFJT146	146	4 1/2 REG	Ф88	Ф57	
FFJT121	121	3 1/2 REG	Ф61	Φ51	
FFJT108	108	3 1/2 REG	Ф61	Ф38	

Circulation Sub



Thread t	ype	I.D.	Length	
Drill pipe box connection	Casing thread	1.0.	Length	
	5 BTC		500	
NC38	5 LTC	57		
	5 ST & C			
	5 1/2 BTC		580	
NC38	5 1/2 LTC	57		
	5 1/2 ST & C			
	7 BTC		600	
NC50	7 LTC	71		
	7 ST & C			
	9 5/8 BTC		620	
NC50	9 5/8 LTC	71		
	9 5/8 ST & C			
	10 3/4 BTC		670	
NC50	10 3/4 LTC	71		
	10 3/4 ST & C			
	13 3/8 BTC		670	
NC50	13 3/8 LTC	71		
	13 3/8 ST & C			