

Assignment 1: Bayesian Decision Theory and Parametric Estimation

Prof. Santiago Toledo Cortés
Machine Learning

Submission:

Groups of maximum 1 students

Question 1 (1.25)

- a) Download the Hearth Disease dataset. We will take into account only numerical attributes for the input and ignore the categorical ones. The attributes to use are: `age`, `trestbps`, `chol`, `thalach`, and `oldpeak`.
- b) Load and process the dataset to obtain two numpy arrays `X` and `y`, with the input features and the class label respectively.
- c) Split the dataset in training and validation using the following `scikit-learn` command:

```
train_test_split(X, y, test_size=0.33, random_state=42)
```

where `X` and `y` are the input features and labels respectively.

- d) For each one of the 5 input features build a univariate Gaussian classifier estimating the parameters using the training dataset and evaluating the classifier in the validation dataset. For each classifier write down the parameters. Report accuracy, precision and recall. Which classifier is the best? For this classifier draw the curves for the posterior distribution for each class and show where the decision boundary is.

Question 2 (1.25)

- a) In this question, you will take all the combinations of pair of features. For each pair of features you will model the classes as bivariate Gaussian distributions with a covariance matrix $\Sigma = I\sigma$, where σ is a scalar, shared by all the classes. This is, the distribution for each class has a different mean but the same covariance matrix.
- b) For each combination estimate the parameters using the training dataset and evaluate the classifier in the validation dataset. Which combination of parameters obtained the best performance? Report the evaluation results for the best performing combination.
- c) Draw ROC curves for the best performing univariate model (from question 1) and bivariate model. Which model is better? Explain the results.

Question 3 (1.25)

- a) For the best bivariate model (from question 2) draw a plot, where the regions corresponding to the two classes are shown with different colors. A region corresponding to a class is the set of points where the particular class discriminant function is maximum (decision regions, [?] Sect. 3.4).
- b) The boundary between class regions must be a line. Calculate the equation of this line clearly explaining the deduction process. Draw the line along with the regions.

Question 4 (1.25)

- a) Using the best combination of parameters found in question 2 build a bivariate classifier, but this time the covariance matrix could be an arbitrary matrix (not diagonal) and different for each class.
- b) Draw the regions corresponding to each class. Compare with the regions obtained in question 3. Discuss.
- c) Add the possibility of rejection to your model. Draw the three regions corresponding to both classes and rejection. Discuss.

Submission instructions: The assignment must be submitted as a Jupyter notebook. The file must be named as:

`ml-assign1-username1-username2-username3.ipynb`

where **username** is the user name assigned by the university (include the usernames of all the members of the group). **Do not submit additional files, only the notebook file.**

References

- Alp14 Alpaydin, E. *Introduction to Machine Learning, 3rd Ed.* The MIT Press, 2014.
- DHS00 Duda, R. O., Hart, P. E., and Stork, D. G. *Pattern Classification (2nd Edition)*. Wiley-Interscience, 2000.