

Algorithmic Methods for Mathematical Models (AMMM)

Greedy Algorithms Examples

Luis Velasco

(luis.velasco@upc.edu)

Campus Nord D6-107

Algorithmic Methods for Mathematical Models (AMMM)

Assignments

Luis Velasco

(lvelasco @ ac.upc.edu)

Campus Nord D6-107

Assign tasks to computers (lab session 2)

- T Set of tasks, index t .
 C Set of computers, index c .
 r_t Resources requested by task t .
 r_c Available capacity of computer c .

minimize z

subject to:


$$\sum_{c \in C} x_{tc} = 1 \quad \forall t \in T$$

$$\sum_{t \in T} r_t \cdot x_{tc} \leq r_c \quad \forall c \in C$$

$$z \geq \frac{1}{r_c} \cdot \sum_{t \in T} r_t \cdot x_{tc} \quad \forall c \in C$$

$$x_{tc} \in \{0,1\} \quad \forall c \in C, t \in T$$

Assign tasks to computers



$$q(<t, c>, S) = \frac{\text{usedCapacity}(c, S) + r_t}{r_c}$$

Load if assignment

$S \leftarrow \emptyset$

$\text{sorted}T \leftarrow \text{sort}(T, r_p, \text{DESC})$

for each c in C **do** $\text{usedCapacity}_c \leftarrow 0$

for each t in $\text{sorted}T$ **do**

$C(t) \leftarrow \emptyset$

for each c in C **do**

if $\text{usedCapacity}_c + r_t \leq r_c$ **then** $C(t) \leftarrow C(t) \cup \{c\}$

if $|C(t)|=0$ **then return** INFEASIBLE

$c_{\text{best}} \leftarrow \text{argmin}\{q(<t, c>, S) \mid c \text{ in } C(t)\}$

$\text{usedCapacity}_{c_{\text{best}}} \leftarrow \text{usedCapacity}_{c_{\text{best}}} + r_t$

$S \leftarrow S \cup \{<t, c_{\text{best}}>\}$

return S

Assignment Tasks to computers: Iterative execution

Computers	c1	c2	c3	
rc	505.67	503.68	701.78	
Tasks	t1	t2	t3	t4
rt	261.27	560.89	310.51	105.8

sortedTasks	t2	t3	t1	t4
-------------	----	----	----	----

Computers	c1	c2	c3
residualCap	505.67	503.68	701.78

#1 **task: t2** 560.89

C(t2)	c3
cbest	c3

Computers	c1	c2	c3
residualCap	505.67	503.68	140.89
Load	0	0	0.799
Solution	{<t2,c3>}		

#2 **task: t3** 310.51

C(t2)	c1	c2
Load if assignment		
c1	0.6141	
c2	0.6165	
cbest	c1	

Computers	c1	c2	c3
residualCap	195.16	503.68	140.89
load	0.6141	0	0.799
Solution	{<t2,c3>,<t3,c1>}		

#3 **task: t1** 261.27

C(t1)	c2
Load if assignment	
c2	0.5187
cbest	c2

Computers	c1	c2	c3
residualCap	195.16	242.41	140.89
load	0.6141	0.5187	0.799
Solution	{<t2,c3>,<t3,c1>,<t1,c2>}		

#4 **task: t4** 105.8

C(t4)	c1	c2	c3
Load if assignment			
c1	0.8233		
c2	0.7288		
c3	0.95		
cbest	c2		

Computers	c1	c2	c3
residualCap	195.16	136.61	140.89
load	0.6141	0.7288	0.799
Solution	{<t2,c3>,<t3,c1>,<t1,c2>,<t4,c2>}		

Solution	
Solution	{<t2,c3>,<t3,c1>,<t1,c2>,<t4,c2>}
f(Solution)	0.799

Algorithmic Methods for Mathematical Models (AMMM)

Set Covering

Luis Velasco

(lvelasco @ ac.upc.edu)

Campus Nord D6-107

Set Covering

- Let $M=\{1, 2, \dots, m\}$ be the universe of elements to be covered.
- Let $P=\{p_j\}_{j \in N}$, be a family of subsets p_j , $N=\{1, 2, \dots, n\}$. Coefficient a_{ij} is 1 if element i is in subset p_j , and 0 otherwise.
- Let c_j be the cost associated with p_j , e.g. its cardinality ($|p_j|$).
- The set covering problem consists on finding the sub-family of elements $\{p_j\}_{j \in N^*}$, $N^* \leq N$, with minimum cost such that $\cup p_j = M$, i.e., covering M .

$$\text{minimize } \sum_{j=1}^n c_j x_j$$

subject to:

$$\sum_{j=1}^n a_{ij} x_j \geq 1 \quad \forall i \in M$$
$$x_j \in \{0,1\}$$

Set Covering

M/P	p1	p2	p3	p4	p5	p6	p7	p8
1						X		
2			X	X			X	
3	X	X		X	X		X	
4	X			X	X	X		X
5					X	X		
cost	2	1	1	3	3	3	2	1

Optimal solutions (cost 5)

$S = \{p6, p7\}$

$S = \{p2, p3, p6\}$

Other feasible solutions

$S = \{p1, p3, p6\}$ (cost=6)

$S = \{p4, p6\}$ (cost=6)

Greedy for set covering

Let S the solution sub-family

Let R the set of covered elements

Greedy function:

$$q(p_j, R) = |p_j \cap (M \setminus R)| = |p_j \setminus (R \cap p_j)| \rightarrow \text{Number of additional elements of } p_j$$

If every p_j has its own associated cost c_j , the greedy function would be:

$$q(p_j, R) = c_j / |p_j \cap (M \setminus R)|$$

$$S = \{\}$$

$$R = \{\}$$

compute $q(p_j) \forall p_j \in P \setminus \omega$

Select the best element: p_4

$$S = \{p_4\}$$

$$R = \{2, 3, 4\}$$

$$q(p_1) = 2 \quad q(p_5) = 3$$

$$q(p_2) = 1 \quad q(p_6) = 3$$

$$q(p_3) = 1 \quad q(p_7) = 2$$

$$q(p_4) = 3 \quad q(p_8) = 1$$

compute $q(p_j) \forall p_j \in P \setminus \omega$

Select the best element: p_6

$$S = \{p_4, p_6\}$$

$$R = M$$

$$q(p_1) = 0 \quad q(p_5) = 1$$

$$q(p_2) = 0 \quad q(p_6) = 2$$

$$q(p_3) = 0 \quad q(p_7) = 0$$

$$q(p_8) = 0$$

Cost: 6

Algorithmic Methods for Mathematical Models (AMMM)

Network planning



Luis Velasco

(lvelasco @ ac.upc.edu)

Campus Nord D6-107

Network planning

- A set of users U needs to be connected to the Internet. For that purpose, we have a set of access point locations A where we could install routers (one per access point at the most).
 - For each user u , the amount cr_u of capacity units it consumes from the router it is connected to is given.



Network planning

- We have a set M of router models.
 - Each model m with its fixed cost f_m , capacity k_m , and reach d_m .
 - A router m can only connect users that are within a distance d_m from the access point.
- We assume Euclidean distances, so for each user u and each access point a , we know its Cartesian coordinates (x, y) .
- We have to decide:
 - which model of router, if any, should be installed in each access point,
 - which access point each user should be connected to.
 - The goal is to minimize the total cost, computed as the summation of the cost of all the installed routers.

Network planning: Greedy algorithm

$$q(u, S) = \min\{q(< u, a >, S)\}$$

$$q(< u, a >, S)$$

$$= \begin{cases} \infty & \text{if } d(u, a) > \max\{d_m\} \text{ OR } cr_u > \left(\max\{k_m\} - \sum_{u' \in U(a)} cr_{u'}\right) \\ 0 & \text{if } d(u, a) \leq d_a \text{ AND } cr_u \leq \left(k_a - \sum_{u' \in U(a)} cr_{u'}\right) \\ f_m - f_a & \text{if } d(u, a) > d_a \text{ OR } cr_u > \left(k_a - \sum_{u' \in U(a)} cr_{u'}\right), d(u, a) \leq d_m \text{ AND } cr_u \leq \left(k_m - \sum_{u' \in U(a)} cr_{u'}\right) \end{cases}$$

Infeasible either because of the reach or the load

User u can be served
with the router currently
installed in location a

Router currently installed in location a needs to be upgraded because of the reach or the load to serve user u

$S \leftarrow \emptyset, C \leftarrow U$

Evaluate $q(u, \emptyset) \forall u \in C$

while $C \neq \emptyset$ **do**

$u^{min} \leftarrow \operatorname{argmin} \{q(u, S) \mid u \in C\}$



$S \leftarrow S \cup \{u^{min}\}$

$C \leftarrow C \setminus \{u^{min}\}$

Reevaluate the incremental costs $q(u, S) \forall u \in C$

return S

Network planning: Problem Instance



	R1	R2	R3
f	100	140	180
k	6	8	10
d	2	3	4

d(u,a)		u	1	2	3	4	5	6	7	8	9	10
		x	1	2	0	4	1	2	0	1	3	2
		y	1	3	1	1	2	2	1	1	4	4
1	2	3	2.2	0.0	2.8	2.8	1.4	1.0	2.8	2.2	1.4	1.0
2	1	2	1.0	1.4	1.4	3.2	0.0	1.0	1.4	1.0	2.8	2.2
3	1	1	0.0	2.2	1.0	3.0	1.0	1.4	1.0	0.0	3.6	3.2
4	0	2	1.4	2.2	1.0	4.1	1.0	2.0	1.0	1.4	3.6	2.8
5	1	3	2.0	1.0	2.2	3.6	1.0	1.4	2.2	2.0	2.2	1.4
a	x	y										

Network planning: Iterative execution (1/5)

#1

u	1	2	3	4	5	6	7	8	9	10
cr	2	3	4	1	2	2	1	2	3	4
q(u)	100	100	100	140	100	100	100	100	100	100
a	3	1	3	1	2	1	3	3	1	1
d(u,a)	0.0	0.0	1.0	2.8	0.0	1.0	1.0	0.0	1.4	1.0

a	1	2	3	4	5
m			R1		
U(a)			{1}		
km-cr			4		

#2

u	1	2	3	4	5	6	7	8	9	10
cr	2	3	4	1	2	2	1	2	3	4
q(u)		40	0	40	0	0	0	0	80	80
a	3	3	3	3	3	3	3	3	3	3
d(u,a)	0.0	2.2	1.0	3.0	1.0	1.4	1.0	0.0	3.6	3.2

a	1	2	3	4	5
m			R1		
U(a)			{1,8}		
km-cr			2		

Network planning: Iterative execution (2/5)

#3

u	1	2	3	4	5	6	7	8	9	10
cr	2	3	4	1	2	2	1	2	3	4
q(u)		40	40	0	0	0	0		80	80
a	3	3	3	3	3	3	3	3	3	3
d(u,a)	0.0	2.2	1.0	3.0	1.0	1.4	1.0	0.0	3.6	3.2

a	1	2	3	4	5
m			R1		
U(a)			{1,5,8}		
km-cr			0		

#4

u	1	2	3	4	5	6	7	8	9	10
cr	2	3	4	1	2	2	1	2	3	4
q(u)		80	80	40		40	40		80	80
a	3	3	3	3	3	3	3	3	3	3
d(u,a)	0.0	2.2	1.0	3.0	1.0	1.4	1.0	0.0	3.6	3.2

a	1	2	3	4	5
m			R2		
U(a)			{1,5,7,8}		
km-cr			1		

Network planning: Iterative execution (3/5)

#5

u	1	2	3	4	5	6	7	8	9	10
cr	2	3	4	1	2	2	1	2	3	4
q(u)		100	100	0		40			100	100
a	3	1	4	3	3	3	3	3	1	1
d(u,a)	0.0	0.0	1.0	3.0	1.0	1.4	1.0	0.0	1.4	1.0

a	1	2	3	4	5
m			R2		
U(a)			{1,4,5,7,8}		
km-cr			0		

#6

u	1	2	3	4	5	6	7	8	9	10
cr	2	3	4	1	2	2	1	2	3	4
q(u)		100	100			40			100	100
a	3	1	4	3	3	3	3	3	1	1
d(u,a)	0.0	0.0	1.0	3.0	1.0	1.4	1.0	0.0	1.4	1.0

a	1	2	3	4	5
m			R3		
U(a)			{1,4,5,6,7,8}		
km-cr			0		

Network planning: Iterative execution (4/5)

#7

u	1	2	3	4	5	6	7	8	9	10
cr	4	3	4	1	2	2	1	2	3	4
q(u)		100	100						100	100
a	3	1	4	3	3	3	3	3	1	1
d(u,a)	0.0	0.0	1.0	3.0	1.0	1.4	1.0	0.0	1.4	1.0

a	1	2	3	4	5
m	R1		R3		
U(a)	{2}		{1,4,5,6,7,8}		
km-cr	3		0		

#8

u	1	2	3	4	5	6	7	8	9	10
cr	4	3	4	1	2	2	1	2	3	4
q(u)			40						0	40
a	3	1	1	3	3	3	3	3	1	1
d(u,a)	0.0	0.0	2.8	3.0	1.0	1.0	1.0	0.0	1.4	1.0

a	1	2	3	4	5
m	R1		R3		
U(a)	{2,9}		{1,4,5,6,7,8}		
km-cr	0		0		

Network planning: Iterative execution (5/5)

#9

u	1	2	3	4	5	6	7	8	9	10
cr	4	3	4	1	2	2	1	2	3	4
q(u)			80							80
a	3	1	1	3	3	3	3	3	1	1
d(u,a)	0.0	0.0	2.8	3.0	1.0	1.0	1.0	0.0	1.4	1.0

a	1	2	3	4	5
m	R3		R3		
U(a)	{2,9,10}		{1,4,5,6,7,8}		
km-cr	0		0		

#10

u	1	2	3	4	5	6	7	8	9	10
cr	4	3	4	1	2	2	1	2	3	4
q(u)			100							
a	3	1	4	3	3	3	3	3	1	1
d(u,a)	0.0	0.0	1.0	3.0	1.0	1.0	1.0	0.0	1.4	1.0

a	1	2	3	4	5
m	R3		R3	R1	
U(a)	{2,9,10}		{1,4,5,6,7,8}	{3}	
km-cr	0		0	2	

Solution Cost=460

Algorithmic Methods for Mathematical Models (AMMM)

Greedy Algorithms

Luis Velasco

(lvelasco @ ac.upc.edu)

Campus Nord D6-107