



I- Shine



Timer



Lock



Quick Cooling
/Heating



Intelligent
Defrosting Monitor



Refrigerant
Lacking
Protection



Intelligent &
Controllable
Electric Heating



Quiet Design



Wide Operation
Climate Range



Healthy Filters



Intelligent
Defrosting
Monitor



LED Display



Closed Structure
of Connection
Pipe Outlet



Mice
Prevention
Design



Wide
Voltage Range



Fireproof Design




Crashproof
Design



Touch Button

Features: ● Standard ● Optional

Floor Standing type



► 90.Artistic columnar appearance

Based on the columnar body of i series, top appearance and integrated design are optimized, showing its unique fashionable style.



► User-friendly touch display

Concealed display integrates perfectly with touch control technology, bringing a modern sense to your life.



► Diamond-style base

Inspired from the lines of diamond, innovative diamond-style base is designed to make it more exquisite.



► Wide-angle swing mode for wider air supply range

When turning on the unit, the panel will open automatically in rotation. After setting "left&right swing", air outlet can swing left and right automatically to achieve wide-angle swing and even airflow distribution, so that you can enjoy coolness in each corner of the room.



► Ultra-long air outlet with sufficient air volume

Its ultra-long vertical air outlet, matched with flexible up&down air guide louvers, generates big circulating air volume in wide air supply angle, so as to adjust indoor temperature quickly.





Model			GVH24AK-K3DNC8A
			Cooling/Heating
Capacity	Cooling	Btu/h	7100
	Heating	Btu/h	8800
EER/C.O.P		W/W	3.2/3.2
Power Supply		Ph,V,Hz	1Ph,220~240V,50Hz
Power Input	Cooling	W	2220
	Heating	W	2750
Rated Current	Cooling	A	21
	Heating	A	22
Airflow Volume	Indoor	m ³ /h (SH/H/M/L)	1480/1200/1060/750/570
Indoor Unit			
Sound Pressure Level	Indoor	dB(A) (SH/H/M/L)	47/42/39/35/30
Outline Dimension	WxHxD	mm	458*1790*458
Package Dimension	WxHxD	mm	543*2083*525
Net Weight/Gross Weight	Indoor	kg	50/65.5
Outdoor Unit			
Sound Pressure Level	Outdoor	dB(A)	57
Piping Connection	Gas	mm	416
	Liquid	mm	46
Outline Dimension	WxHxD	mm	965*700*396
Package Dimension	WxHxD	mm	1029*750*458
Net Weight/Gross Weight	Outdoor	kg	58/62.5
Loading Quantity	40'GP	sets	61
	40'HQ	sets	62

1.The product with * is under development, and the parameters are estimated, please refer to the value on nameplates.

2.Gree reserves the right to modify the specifications without prior notice. Please confirm the final specifications with sales representatives.