

Floor Standing



> 91.Side-drawing filter design for convenient cleaning

The filter adopts user-friendly side-drawing design, which is more convenient for cleaning.



▶ Simple design brings life to its original nature



Beautiful integrated design



Side-drawing filter for convenient cleaning



Precise air guiding



Concealed display screen and touch control button



| Model | | | GVC18AL-K6NNC7A | GVC24AL-K6NNC7A | GVC24AL-M6NNC7A | GVC30AL-K6NNC7A | GVC36AL-K6NNC7A | GVC48AL-M6NNC7A |
|-------------------------|---------|--------------------|-------------------|-------------------|-------------------|-------------------|---------------------|---------------------|
| | | | Cooling | Cooling | Cooling | Cooling | Cooling | Cooling |
| Capacity | Cooling | Btu/h | 18000 | 24000 | 24000 | 30000 | 33000 | 42000 |
| | Heating | Btu/h | 1 | 1 | 1 | 1 | 1 | 1 |
| EER/C.O.P W/W | | 3.0 | 2.8 | 2.8 | 2.80 | 2.80 | 2.8 | |
| Power Supply Ph,V,Hz | | Ph,V,Hz | 1Ph,220-240V,50Hz | 1Ph,220-240V,50Hz | 3Ph,380-415V,50Hz | 1Ph,220-240V,50Hz | 1Ph,220-240V,50Hz | 3Ph,380-415V,50Hz |
| Power Input | Cooling | W | 1760 | 2500 | 2500 | 3140 | 3450 | 4390 |
| | Heating | W | 1 | 1 | 1 | 1 | 1 | 1 |
| Rated Current | Cooling | A | 10.5 | 16.5 | 9.6 | 18.63 | 21.30 | 9.55 |
| | Heating | A | 1 | 1 | 1 | 1 | 1 | 1 |
| Airflow Volume | Indoor | m³/h (SH/H/M/L) | 970/830/720/610 | 1000/850/730/650 | 930/800/710/600 | 1100/940/850/760 | 1850/1650/1450/1300 | 1900/1850/1700/1530 |
| Indoor Unit | | | | | | | | |
| Sound Pressure Level | Indoor | (SH/H/M/L) | 45/42/41/38 | 46/44/41/38 | 45/42/41/38 | 49/46/43/40 | 52/49/46/44 | 53/50/48/45 |
| Outline Dimension | WxHxD | mm | 485×1720×321 | 507×1770×320 | 485×1720×321 | 507×1770×320 | 587×1882×394 | 587×1882×394 |
| Package Dimension | WxHxD | mm | 618×1928×430 | 623×1988×440 | 618×1928×430 | 623×1988×440 | 738×2153×545 | 738×2153×545 |
| Net Weight/Gross Weight | Indoor | kg | 36/49.5 | 38.5/52 | 36/49.5 | 39/51 | 55/77.5 | 55/77.5 |
| Outdoor Unit | | | | | | | | |
| Sound Pressure Level | Outdoor | dB(A) | 56 | 55 | 56 | 56 | 56 | 59 |
| Piping Connection | Gas | mm | φ12 | φ12 | φ12 | φ16 | φ16 | φ16 |
| | Liquid | mm | φ6 | φ6 | φ6 | φ9.52 | φ9.52 | φ9.52 |
| Outline Dimension | WxHxD | mm | 965×700×396 | 965×700×396 | 965×700×396 | 1012×790×427 | 1012×790×427 | 1032×1250×412 |
| Package Dimension | WxHxD | mm | 1029×750×458 | 1029×750×458 | 1029×750×458 | 1143×880×483 | 1143×880×483 | 1113×1400×453 |
| Net Weight/Gross Weight | Outdoor | kg | 54/58.5 | 60/64.5 | 59/63.5 | 68.0/73.0 | 68.0/73.0 | 107/118 |
| | | | | 1 | | | | |
| Loading Quantity | 40'GP | sets | 65 | 66 | 65 | 53 | 42 | 32 |
| | 40'HQ | sets | 75 | 71 | 75 | 63 | 48 | 39 |

^{1.}The product with "is under development, and the parameters are estimated, please refer to the value on nameplates.
2.Gree reserves the right to modify the specifications without prior notice. Please confirm the final specifications with sales need to be a specification of the parameters.