

Web and Multimedia Technologies

Lab class 3 (optional) – Basic HTML + CSS

Instructions to use the laboratory computers (rooms B2/B4):

1. If the computer is off, start it with Windows (all computers have a Linux-Windows dual boot)
2. Your username is *cl* followed by the six digits of your student ID; your password is *inf* followed by the last two digits of your student ID (e.g., if the student ID is 123456, the username is *cl123456*, and the password is *inf56*)
3. At the end of the class, please log out

Steps:

1. Create the folder web
2. Within web, create the (text) file `index.html`
3. Using an HTML editor or an ordinary text editor, write (in `index.html`) the following HTML code:

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8">
    <title>Online Books</title>
  </head>
  <body>
    <h1>The strange case of Dr. Jekyll and Mr. Hyde</h1>
    <h2>Story of the Door</h2>
    <p>
      Mr. Utterson the lawyer was a man of a rugged countenance that
      was never lighted by a smile; cold, scanty and embarrassed in
      discourse; backward in sentiment; lean, long, dusty, dreary and
      yet somehow lovable.
    </p>
    <p>
      At friendly meetings, and when the wine was to his taste,
      something eminently human beaconed from his eye; something
      indeed which never found its way into his talk, but which spoke
      not only in these silent symbols of the after-dinner face, but
      more often and loudly in the acts of his life.
    </p>
  </body>
</html>
```

4. At the end of the page, add an image of your choice, for example saving it from a website (`<img>` tag and attribute `src` to specify the file pathname) – remember that the allowed formats are GIF, JPEG, PNG, AVIF, WebP, and SVG
5. At the end of the page, after the image, add an ordered list (`<ol>` tag) listing the titles of the first four chapters of the novel (*Story of the Door*, *Search for Mr Hyde*, *Dr Jekyll was Quite and at Ease*, and *The Carew Murder Case*)
6. Make each list item a link to a page containing the corresponding chapter (`<a>` tag with attribute `href`, inside `<li>` tags). Suppose that the pages are within the `chapters` folder (to be created), inside the `web` folder. Also, create the HTML files of the four chapters (with any content, e.g., simply the chapter's title), naming them `ch1.html`, `ch2.html`, etc.
7. At the end of each chapter's page, include a link to `index.html`
8. At the end of the page, create a table like the following (*Chapters* is an `<h1>` heading):

Chapters

Info \ Chapter	Chapter 1	Chapter 2	Chapter 3	Chapter 4
Titles	Story of the Door	Search for Mr Hyde	Dr Jekyll was Quite and at Ease	The Carew Murder Case
Pages	5 - 12	13 - 25	26 - 30	31 - 37

9. Modify the previous table so that the last four cells of the first row and the two last cells of the first column are merged into single cells (`colspan` and `rowspan` attributes):

Info \ Chapter	Chapters 1 - 4			
Titles and pages	Story of the Door	Search for Mr Hyde	Dr Jekyll was Quite and at Ease	The Carew Murder Case
	5 - 12	13 - 25	26 - 30	31 - 37

10. Create a form roughly like the following (**do not worry** about the alignment of controls and labels):

Registration Form

Name and Surname

Gender ☐ M ☐ F

I heard about this service through ☐ Internet ☐ Press ☐ Television

I wish to receive a message every

Comments

11. Modify the file created at step 3 so that the page loads the external style sheet `mystyle.css`, located within the web folder (`<link>` tag)
12. In `mystyle.css` (to be created), specify a background color for the page (`background-color` property)
13. In the CSS, specify for `<h2>` a `sans-serif` font whose size is twice the size of the default container's font, red, bold, and centered (properties `font-family`, `font-size`, `color`, `font-weight` and `text-align`, with values `sans-serif`, `2em`, `red`, `bold`, and `center`)
14. Specify for the page a global margin (all four sides) that is 2.5 times the size of the container's default font (value `2.5em` for property `margin` in the style for `<body>`)
15. Directly in the HTML file defined at step 3, specify a style for the second paragraph, so that it is bold and green (style attribute in the `<p>` tag; properties `font-weight` and `color` with values `bold` and `green`)
16. In `mystyle.css`, define the style for the class `special` of the `<span>` tag, so that the text is blue and underlined (properties `color` and `text-decoration`, values `blue` and `underline`). Then, apply the tag and the class to the words *Mr. Utterson the lawyer* in the first paragraph of the page defined at step 3
17. Specify that `<h2>` headings have a 5-pixel red solid border, with a 20-pixel padding area (`border` property with values `solid red 5px` and `padding` property with value `20px`)
18. Specify a background image for the page (property `background-image` in the style for tag `<body>`, value `url ("...")`)
19. Define some styles (as you prefer) to change the look of the form and its controls (e.g., fonts, colors, sizes, etc.)