

Web and Multimedia Technologies

Lab class 7 – jQuery

Instructions to use the laboratory computers (room B2/B4):

1. If the computer is off, start it with Windows (all computers have a Linux-Windows dual boot)
2. Your username is *cl* followed by the six digits of your student ID; your password is *inf* followed by the last two digits of your student ID (e.g., if the student ID is 123456, the username is *cl123456* and the password is *inf56*)
3. At the end of the class, please log out

Steps:

1. Create the folder `jquery` and, within it, the folder `jquery1`
2. Download from <https://jquery.com/download/> the compressed, production version of *jQuery 3.7.1* to the folder `jquery`
3. Download to the folder `jquery1` the files
<https://vision.unipv.it/wmt/lab/jquery/jq1/v.mp4>,
<https://vision.unipv.it/wmt/lab/jquery/jq1/jquery.jpg>,
<https://vision.unipv.it/wmt/lab/jquery/jq1/reload.png>,
<https://vision.unipv.it/wmt/lab/jquery/jq1/reload2.png>,
<https://vision.unipv.it/wmt/lab/jquery/jq1/p.jpg>, and
<https://vision.unipv.it/wmt/lab/jquery/jq1/mycss.css>
4. Create, in the folder `jquery1`, the file `index.html` with the following code:

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <title>jQuery example</title>
    <link rel="stylesheet" href="mycss.css">
    <script src="../jquery-3.7.1.min.js"></script>
    <script src="init.js"></script>
  </head>
  <body>
    <h1>jQuery Test</h1>
    <section id="main">
      <div id="mainvideo">
        <video muted autoplay poster="p.jpg">
          <source src="v.mp4" type="video/mp4">
        </video>
      </div>
      <div id="animtext">
        <h2 id="t1">Web and Multimedia Technologies</h2>
        <h2 id="t2">A demo about the power of</h2>
        <h2 id="t3">JavaScript and jQuery</h2>
        <h2 id="t4">Learn jQuery.</h2>
        <h2 id="t5">Now!</h2>
        <a id="replaylink" href="javascript:replay()"></a>
      </div>
    </section>
  </body>
</html>
```

5. Create, in the folder `jquery1`, the JavaScript file `init.js` with the following code:

```
function mytext() {
  $("#t1").delay(0).fadeIn(300);
  $("#t1").delay(1400).fadeOut(300);
  $("#t2").delay(2100).fadeIn(300);
```

```

    $("#t2").delay(1400).fadeOut(300);
    $("#t3").delay(5200).fadeIn(300);
    $("#t3").delay(1400).fadeOut(300);
    $("#t4").delay(7300).fadeIn(300);
    $("#t5").delay(8500).fadeIn(200);
    $("#replaylink").delay(9000).fadeIn(2000);
}

function setCookie(key, value) {
    var expires = new Date();
    var minutes = 1;
    expires.setTime(expires.getTime() + (minutes * 60 * 1000));
    document.cookie = key + '=' + value + '; expires=' +
        expires.toUTCString();
}

function getCookie(key) {
    var keyValue = document.cookie.match('(^\|;) ?' + key +
        '=[^;]*)(;|$)');
    return keyValue ? keyValue[2] : null;
}

function replay() {
    setCookie('fc', '0');
    setTimeout(function() {this.location.reload()}, 300);
}

function showStaticText() {
    $("#mainvideo").css("border", "0px");
    $("#mainvideo video").hide();
    $("#t4").show();
    $("#t5").show();
    $("#replaylink").show();
}

$(document).ready(function() {
    if (getCookie('fc') != '1') {
        $("#mainvideo video").bind('ended', function() {
            mytext();
            $("#mainvideo").fadeOut(4000, function() {
                $("#mainvideo video").remove();
            });
        });
        setCookie('fc', '1');
    } else {
        showStaticText();
    }
});

```

6. Open index.html in the browser and check the result (important: cookies may not work if the page is loaded locally – e.g., they work with Firefox but not with Chrome)
7. Create the folder jquery2 within the folder jquery
8. Create, in the folder jquery2, the file index.html with the following code:

```

<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8">
    <title>jQuery example</title>
    <script src="../../jquery-3.7.1.min.js"></script>

```

```
<script>
  $(document).ready(function() {
    $("#flip").click(function() {
      $("#panel").slideToggle(700);
    });
  });
</script>
<style>
  #panel, #flip {
    padding: 5px;
    text-align: center;
    background-color: #e5eccc;
    border: solid 1px #c3c3c3;
  }

  #flip { cursor: pointer }

  #panel {
    background-color: yellow;
    padding: 50px;
    display: none;
  }
</style>
</head>
<body>
  <div id="flip">Click to slide the panel down or up</div>
  <div id="panel">Long life to JavaScript and jQuery!</div>
</body>
</html>
```

9. Open index.html in the browser and check the result