DISTRIBUTED SYSTEMS Principles and Paradigms Second Edition ANDREW S. TANENBAUM MAARTEN VAN STEEN

Chapter 2 ARCHITECTURES

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

1

Architectural Styles (1)

Important styles of architecture for distributed systems

- Layered architectures
- Object-based architectures
- Data-centered architectures
- Event-based architectures

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

Architectural Styles (2)




Figure 2-1. The (a) layered architectural style and ...

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

3

Architectural Styles (3)




Figure 2-1. (b) The object-based architectural style.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

Architectural Styles (4)




Figure 2-2. (a) The event-based architectural style and ...

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-

0

Architectural Styles (5)




Figure 2-2. (b) The shared data-space architectural style.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

Centralized Architectures




Figure 2-3. General interaction between a client and a server.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-

7

Application Layering (1)

Recall previously mentioned layers of architectural style

- The user-interface level
- The processing level
- The data level

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

Application Layering (2)




Figure 2-4. The simplified organization of an Internet search engine into three different layers.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5


S


Multitiered Architectures (1)


The simplest organization is to have only two types of machines:


- A client machine containing only the programs implementing (part of) the userinterface level
- A server machine containing the rest,
 - the programs implementing the processing and data level

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5









Structured Peer-to-Peer Architectures (3)




Figure 2-8. (b) Splitting a region when a node joins.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

15

Unstructured Peer-to-Peer Architectures (1)

Actions by active thread (periodically repeated):

```
select a peer P from the current partial view;

if PUSH_MODE {
    mybuffer = [(MyAddress, 0)];
    permute partial view;
    move H oldest entries to the end;
    append first c/2 entries to mybuffer;
    send mybuffer to P;
} else {
    send trigger to P;
}
if PULL_MODE {
    receive P's buffer;
}
construct a new partial view from the current one and P's buffer;
increment the age of every entry in the new partial view;
```

Figure 2-9. (a) The steps taken by the active thread.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

Unstructured Peer-to-Peer Architectures (2)


Actions by passive thread:

```
receive buffer from any process Q;
if PULL_MODE {
    mybuffer = [(MyAddress, 0)];
    permute partial view;
    move H oldest entries to the end;
    append first c/2 entries to mybuffer;
    send mybuffer to P;
}
construct a new partial view from the current one and P's buffer;
increment the age of every entry in the new partial view;
```

Figure 2-9. (b) The steps take by the passive thread

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

17



Superpeers




Figure 2-12. A hierarchical organization of nodes into a superpeer network.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

20

Edge-Server Systems




Figure 2-13. Viewing the Internet as consisting of a collection of edge servers.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

Collaborative Distributed Systems (1)




Figure 2-14. The principal working of BitTorrent [adapted with permission from Pouwelse et al. (2004)].

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5


22

Collaborative Distributed Systems (2)

Components of Globule collaborative content distribution network:

- A component that can redirect client requests to other servers.
- A component for analyzing access patterns.
- A component for managing the replication of Web pages.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5



24

General Approaches to Adaptive Software

Three basic approaches to adaptive software:

- Separation of concerns
- Computational reflection
- Component-based design

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5