

Daily Vulnerability Report - 2026-09-13

Window (UTC): 2026-09-13T00:00 to 2026-09-14T00:00 | Sources: NVD, CISA KEV, FIRST EPSS | Generated 2026-09-17 05:58:45 UTC

Total	KEV (exploited)	Critical	High	Medium	Low	Unscored	Watchlist
281	4	40	130	54	47	10	171

P1 - Act now (KEV / high EPSS)

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-58704			Yes	0.001	google:pixel	Google Pixel devices contain an improper authorization vulnerability in the cellular modem. A logic error may allow an attacker to bypass permission checks and escalate privileges.
CVE-2026-76460			Yes		cisco:identity services engine	Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) contain an incorrect use of privileged APIs vulnerability that could allow an unauthenticated, remote attacker to gain unauthorized access to the affected device by bypassing the web-based management interface.
CVE-2026-76461			Yes	0.02	cisco:secure email gateway	Cisco AsyncOS software for Cisco Secure Email Gateway (SEG) contains a SQL injection vulnerability that could allow an unauthenticated, remote attacker to execute arbitrary commands with root privileges on the underlying operating system.
CVE-2026-87886			Yes		acronis:backup	Acronis Backup plugin for cPanel & WHM and extension for Plesk contains an incorrect default permissions vulnerability that could allow for privilege escalation.

P2 - High (CVSS >= 9.0 or 7.0+ with EPSS >= 0.10)

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-81648	10.0	CRIT		0.003		The CryptoPayment Gateway WordPress plugin from 1.2.1 to 1.2.2 does not apply an authorization check on one of its AJAX endpoints, allowing unauthenticated users to invoke administrative operations, including deleting arbitrary files on the server, overwriting the payment gateway configuration and recovering stored wallet credentials in cleartext.
CVE-2026-80926	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ksmbd: fix use-after-free in oplock break notification smb2_oplock_break_noti() reads opinfo->conn without any lock and dereferences it after two allocations which may sleep. When the durable handle owning the oplock is disconnected, session_fd_check() clears opinfo->conn and drops its conn reference under ci->m_lock, and the last ksmbd_conn_pu...
CVE-2026-80980	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: stop killed, freed and out_of_sync sharing a byte The three connection state flags are single-bit bitfields, so they occupy one byte of struct smc_connection and every store to one is a read-modify-write of the other two: u8 killed : 1; u8 freed : 1; u8 out_of_sync : 1; They are not written under a common lock. smc_cdc...
CVE-2026-80981	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: fix use-after-free of the LLC qentry in smc_llc_srv_add_link() smc_llc_srv_add_link() keeps add_llc pointing into the queue entry: add_llc = &qentry->msg.add_link; smc_llc.c:1482 ... smc_llc_save_add_link_info(link_new, add_llc); smc_llc.c:1494 smc_llc_flow_qentry_del(&lgr->llc_flow_lcl); smc_llc.c:1495 ... u8 *llc_msg =...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-80986	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: bound the peer rkey counts in SMC-Rv2 LLC messages On a link whose device has max_rcv_sge == 1 there is no shared v2 receive buffer, and smc_llc_save_add_link_rkeys() takes the v2 extension from 44 bytes past the start of the queue entry's inline message: ext = (struct smc_llc_msg_add_link_v2_ext *)(&llc_msg + SMC_WR_TX_SIZE); The e...
CVE-2026-89492	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ocfs2: validate directory-index entry counts when reading metadata ocfs2_validate_dx_leaf() and ocfs2_validate_dx_root() check the ECC and signature of an indexed-directory block before it reaches higher-level callers, but neither validator bounds the ocfs2_dx_entry_list counts against the capacity of the block that holds them. ocfs2_dx_dir_sea...
CVE-2026-89526	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Validate Read chunk positions before reconstruction The RPC/RDMA Read chunk position field is supplied by the remote client and stored verbatim in the parsed chunk list. xdr_count_read_segments() checks only 4-byte alignment; it never compares the position against the received inline body length. In the single-chunk path, svc_rdma_read...
CVE-2026-89530	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Reject inline replies that overflow the pull-up buffer An RPC-over-RDMA client can request a reply, such as an NFS READ payload, without providing a Write list or a Reply chunk to carry it. When such a reply needs more scatter/gather entries than the device's Send Queue supports, svc_rdma_pull_up_needed() selects pull-up and svc_rdma_pu...
CVE-2026-89546	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: close backchannel before destroying callback service A backchannel receive can complete a request while the NFS callback service is being torn down. xprt_complete_bc_request() removes the request from bc_pa_list, drops bc_alloc_count, marks the request in use, and then asks xprt_enqueue_bc_request() to hand it to the callback service. ...
CVE-2026-89558	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: md/raid10: fix still_degraded being inverted in raid10_sync_request() Commit fe6a19d40ceb ("md/md-bitmap: merge md_bitmap_start_sync() into bitmap_operations") converted still_degraded from int to bool, but inverted the assignment in the loop that checks whether the array will still be degraded after the current device is recovered: "still_degra...
CVE-2026-89610	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: verify run length exceeding volume boundary The mapping pairs decoder validates that the starting LCN is within the volume but does not check if the run extends beyond the volume boundary. A malformed NTFS image with a crafted mapping pairs array could cause the kernel to access memory beyond the volume boundary, potentially leading to me...
CVE-2026-89611	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ntfs: validate non-resident attribute offsets ntfs_attr_update_meta() shifts the attribute name when converting between non-sparse and sparse attributes. Converting to sparse also adds the compressed_size field before the name and mapping pairs, requiring eight additional bytes in the attribute record. However, the validator does not check that...
CVE-2026-89612	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: reject invalid MFT LCNs from boot sector The NTFS boot sector stores the MFT and MFTMirr locations as unsigned 64-bit LCNs, but parse_ntfs_boot_sector() decoded them into an s64. A crafted high-bit value could therefore become negative and pass the existing upper-bound check. The invalid value then propagated into the MFT zone allocator a...
CVE-2026-89613	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: reject invalid empty mapping pairs Reject an attribute with empty mapping pairs if it has inconsistent highest VCN and size.
CVE-2026-89614	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ntfs: bound the free-cluster bitmap scan to the volume vol->lc_n_empty_bits_per_page is sized from vol->nr_clusters at mount, but ntfs_cluster_alloc() bounds its scan of that array by the size of \$Bitmap. Those are independent on-disk quantities and the mount-time check only rejects a \$Bitmap that is too small, so an image whose \$Bitmap covers mo...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89633	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix OOB read/write from unvalidated DataOffset in coalesce_t2() coalesce_t2() computes data pointers directly from server-supplied DataOffset fields with no validation against buffer bounds: data_area_of_tgt = (char *)&pSMBt->hdr.Protocol + get_unaligned_le16(&pSMBt->t2_rsp.DataOffset); data_area_of_src = (...
CVE-2026-89635	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ksmbd: only rebind the reopened file's own oplock on durable reconnect ksmbd_reopen_durable_fd() walks the inode's m_op_list and rebinds every detached oplock to the reconnecting session: list_for_each_entry_rcu(op, &ci->m_op_list, op_entry, lockdep_is_held(&ci->m_lock)) { if (op->conn) continue; op->conn = ksmbd_conn_get(fp->conn);...
CVE-2026-89637	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix UAF and buffer leak in cifs_check_trans2() for malformed secondary T2 When a valid primary TRANSACT2 response has been received (mid->resp_buf set, mid->multiRsp true) and a subsequent secondary response causes cifs_check_trans2() to return false -- either because the SMB header is invalid (malformed != 0) or because check2ndT2(...
CVE-2026-89651	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ceph: bound MDSCapAuth path and fs_name decode in handle_session() handle_session() decodes the MDSCapAuth records carried by a CEPH_SESSION_OPEN message (msg_version >= 6). For each record the match.path and match.fs_name byte strings are read by first decoding a 32-bit length and then copying that many bytes with the bare ceph_decode_copy(). U...
CVE-2026-89654	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ceph: fix UAF in check_new_map() on session freed during unlock check_new_map() iterates mdsc->sessions[] and for each active session drops mdsc->mutex to perform per-session operations. The forced-close path (rank removed from map) correctly takes a reference on s via ceph_get_mds_session() before releasing mdsc->mutex, but three other paths d...
CVE-2026-89658	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during NFSv4.0 revoked-state cleanup nfs40_clean_admin_revoked() takes a stateid reference under clp->cl_lock, drops nn->client_lock, and calls nfsd4_drop_revoked_stid(), which dereferences the stateid's client through s->sc_client->cl_lock. The stateid reference does not pin the client, so a teardown racing ...
CVE-2026-89659	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during delegation revoke A delegation stateid holds only a bare pointer to its owning nfs4_client and does not keep it alive. The client survives its stateids only because __destroy_client() drains cl_delegations and cl_revoked before free_client() runs. nfs4_laundromat() breaks that invariant: it unhashes a...
CVE-2026-89660	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during admin state revocation A stateid holds only a bare pointer to its nfs4_client; a stateid reference does not pin it. The client survives only because __destroy_client() drains its stateids before free_client() runs. nfsd4_revoke_states() drops nn->client_lock across revoke_one_stid(), which dereference...
CVE-2026-89675	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix UAF in async copy cancel and shutdown An async copy could be freed or used after free while a teardown caller (OFFLOAD_CANCEL, nfsd4_shutdown_copy, nfsd4_cancel_copy_by_sb) raced the copy kthread: - find_async_copy() bumped copy->refcount but left the copy on clp->async_copies, so the reaper's cleanup_async_copy() could run ...
CVE-2026-89676	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix stale s2s_cp_stateids IDR entry for async COPY For an async COPY, nfsd4_copy() called nfs4_init_copy_state() before dup_copy_fields(), so the s2s_cp_stateids IDR was pointed at &u->copy->cp_stateid -- memory in the per-rqstp COMPOUND buffer that is reused by the next request. dup_copy_fields() copies only the value into async_copy, so ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89677	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix possible fh_compose of wrong dentry in nfsd4_create_file() dentry_create() can hypothetically provide a different dentry than the one passed in. This could happen, for example, if the exported filesystem is NFS, and the server returned to OPEN a filehandle which matched a directory that was already in the dcache. Clearly this would n...
CVE-2026-89681	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix layout fence worker double-reference race The workqueue core clears WORK_STRUCT_PENDING before the callback is invoked, so delayed_work_pending() in lm_breaker_timedout() can return false while the fence worker is already running. This lets the breaker take a duplicate sc_count reference and schedule a new worker that coalesces with th...
CVE-2026-89686	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix BUG_ON in nfsd4_alloc_layout_stateid on racing delegation revoke nfsd4_alloc_layout_stateid reads fp->fi_deleg_file without holding fi_lock when the parent stateid is a delegation. A concurrent delegation revoke via the laundromat can clear fi_deleg_file under fi_lock, causing nfsd_file_get() to return NULL and triggering the BUG_ON. ...
CVE-2026-89688	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: drop the stateid, not the stateowner, on seqid_op replay retry In nfs4_preprocess_seqid_op() the stateid is obtained from nfsd4_lookup_stateid(), which holds a reference on the nfs4_stid (sc_count) but takes no reference on the stateowner. openlockstateid() merely casts that stid and likewise takes no reference. When nfsd4_cstate_assign_r...
CVE-2026-89689	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: don't free session slots that are still in use nfsd4_sequence() can free the very slot it is currently processing. When the session shrinker has reduced se_target_maxslots below se_fchannel.maxreqs, the shrink path checks three conditions before calling free_session_slots(): 1. se_target_maxslots < maxreqs (shrink was advertised) 2. ...
CVE-2026-89702	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: size fh_verify server sockaddr slot by xpt_locallen The nfsd_fh_verify and nfsd_fh_verify_err tracepoints declare the server sockaddr slot sized by xpt_remotelen but fill it from xpt_local using xpt_locallen: TP_STRUCT__entry(... __sockaddr(server, rqstp->rq_xprt->xpt_remotelen) ...) TP_fa...
CVE-2026-89703	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: set SC_STATUS_FREED in nfsd4_drop_revoked_stid for delegations nfsd4_drop_revoked_stid() handles FREE_STATEID for admin-revoked delegations but does not set SC_STATUS_FREED before releasing cl_lock. revoke_delegation() uses this flag to detect whether FREE_STATEID has already processed the delegation -- without it, the freed delegation is ...
CVE-2026-89708	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: RCU-protect cl_cb_session to fix use-after-free on session teardown After a DESTROY_SESSION the per-session teardown path can free a session while rpciod still holds an inflight callback rpc_task that dereferences clp->cl_cb_session. nfsd4_probe_callback_sync() flushes cl_callback_wq, but once nfsd4_run_cb_work() has called rpc_call_async...
CVE-2026-90561	9.3	CRIT		0.002		Strapi versions 4.x through 4.26.2 and 5.x before 5.48.1 contain a stored cross-site scripting vulnerability in the content manager WYSIWYG preview component that fails to strip script tags from rich text. An Author-role user can store malicious script tags in rich text fields that execute in an Editor or Super Admin's session when the preview pane is expanded, enabling account takeover.
CVE-2026-90562	9.2	CRIT		0.004		LangBot before 4.10.11 generates password recovery keys with only 24 bits of entropy and applies no rate limiting to the unauthenticated reset-password endpoint. Remote attackers knowing the administrator email can exhaust the keyspace through concurrent requests to reset the admin password and gain account access.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-80945	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: crypto: iaa - unmap dst before software fallback on decompress On a hardware analytics error, decompress retries through the software fallback, which writes req->dst with the CPU while it is still mapped DMA_FROM_DEVICE. With SWIOTLB active the later dma_unmap_sg() copies the stale bounce buffer over req->dst, corrupting the result. Unmap before...
CVE-2026-89537	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: Reject short RFC 4121 MIC tokens in gss_krb5_verify_mic_v2 gss_krb5_verify_mic_v2() reads the token ID at ptr[0..1], the flags byte at ptr[2], and padding at ptr[3..7], then passes ptr + GSS_KRB5_TOK_HDR_LEN and cksum_len to gss_krb5_mic_build_sg(). None of these accesses check read_token->len first. The minimum safe token size is GSS_K...
CVE-2026-89630	9.1	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: smb: client: restore the data_offset bound in is_valid_oplock_break() Commit 83bfd0bb902 ("cifs: Remove the RFC1002 header from smb_hdr") changed the quantity this bound is measured against. It used to be srv->total_read minus the 4-byte RFC1002 preamble that total_read then included, so it was the SMB message length. The same commit stopped ...
CVE-2026-89631	9.1	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: smb: client: reject a tree connect response whose byte count is too small CIFSCon() bounds its strlen() over the byte area with the server's ByteCount minus two, which for ByteCount 0 or 1 goes negative as an int and converts to a huge size_t. The later subtraction wraps the __u16 bytes_left, and that is what bounds cifs_strndup_from_utf16():...
CVE-2026-89713	9.1	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: check truncate permission under inode lock nfsd_setattr() checks whether a size update needs NFSD_MAY_TRUNC before it takes inode_lock(). The comparison uses the file size sampled by that unlocked read, but the actual ATTR_SIZE update is applied later under inode_lock() by notify_change(). This leaves a TOCTOU window for append-only files...

Watchlist matches (other priorities)

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-80937	8.8	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: wifi: mt76: mt7915: bound the device EEPROM address before the EFUSE copy mt7915_mcu_get_eeprom() copies a fixed EFUSE block into the driver's dev->mt76.eeprom.data buffer at the offset reported by the MCU response (res->addr, a device-controlled __le32) without checking it against the buffer size. A malicious or malfunctioning device can report...
CVE-2026-89445	8.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: iommufd: Fix UAF in selftest IOPF reporting IOMMUFD selftest TRIGGER_IOPF borrows an attach handle from group->pasid_array without synchronizing against PASID detach, then a concurrent iommu_report_device_fault() can dereference that borrowed handle's domain pointer after the detach erases the handle and frees the backing struct iommufd_attach_h...
CVE-2026-89450	8.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: iommu/tegra241-cmdq: Reject a vSID wider than the SID_MATCH field tegra241_vintf_init_vsid() programs the guest-provided vSID into SID_MATCH, whose VIRT_SID field spans bits [20:1] with bit 0 as the match-enable flag. The HW therefore matches only a 20-bit Stream ID. The bound check rejects only virt_sid > UINT_MAX, which admits a value far wi...
CVE-2026-89513	8.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: RISC-V: KVM: Fix PMU event info array size overflow SBI PMU EVENT_GET_INFO stores guest-controlled num_events * sizeof(*info) in a 32-bit integer. On RV64, num_events = 0x10000001 makes 0x100000010 truncate to 16. KVM then allocates one entry but loops over the original num_events, causing out-of-bounds reads and writes. A nested guest triggers...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89534	8.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Clear sc_cm_id when ADDR_CHANGE replacement fails When svc_rdma_listen_handler() handles RDMA_CM_EVENT_ADDR_CHANGE, it creates a replacement listener cm_id and returns 1, telling the CM core to destroy the old one. If the replacement allocation fails, sc_cm_id still points at the old cm_id that the CM core is about to destroy. Any subse...
CVE-2026-89601	8.8	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: ext2: Fix lost inode updates for IS_SYNC inodes ext2_setsize() and ext2_xattr_set2() had a construct like: if (IS_SYNC(inode)) { sync_inode_metadata(inode, 1); } else { mark_inode_dirty(inode); } which leads to lost inode updates for IS_SYNC inodes because sync_inode_metadata() does anything only if the inode is already dirty and hence ...
CVE-2026-90776	8.7	HIGH		0.005		Nodemailer versions 9.1.0 through 10.0.4 contain a quadratic time complexity vulnerability in the addressparser component when parsing email addresses with RFC 5322 comments. Attackers can craft malicious email headers with comment-separated atoms to consume excessive CPU and block the Node.js event loop for several seconds, causing denial of service.
CVE-2026-90493	8.5	HIGH		0.001		A vulnerability was detected in Tonec Internet Download Manager up to 6.42 Build 63 on Windows. The impacted element is an unknown function of the file idmwfp.sys of the component Kernel Driver. The manipulation results in improper access controls. Attacking locally is a requirement. Internet Download Manager for Windows up to and including 6.42 Build 63 installs idmwfp.sys, a Windows kernel driver that exposes th...
CVE-2026-80953	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: i3c: master: adi: initialize the lock before enabling interrupts adi_i3c_master_probe() requests the IRQ and unmask REG_IRQ_PENDING_CMDR before the controller's IBI state, transfer queue list and transfer queue lock are initialized. A pending CMDR interrupt can therefore run adi_i3c_master_irq() and take master->xferqueue.lock before the dynam...
CVE-2026-81004	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ipmi:msghandler: Cancel work cleanly on an error If an error occurs during startup of an IPMI interface, it may have scheduled work to run. The work needs to be canceled before the interface can be freed.
CVE-2026-89452	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: iommu/msm: Unwind probe state on registration failure msm_iommu_probe() adds its devm-managed IOMMU object to qcom_iommu_devices before adding the IOMMU sysfs device and registering it with the IOMMU core. If iommu_device_sysfs_add() fails, probe returns with the object still on qcom_iommu_devices. The driver core then releases the devm allocat...
CVE-2026-89588	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ACPI: APEI: GHES: fix ARM section length accounting after header In ghes_handle_arm_hw_error(), after skipping the cper_sec_proc_arm header with (err + 1), the remaining length was reduced by sizeof(err) (pointer size) instead of sizeof(*err) (structure size). That overestimates the bytes left for cper_arm_err_info records and can let the parse...
CVE-2026-90772	8.3	HIGH		0.002		Amundsen frontend through 4.3.0 renders table, dashboard, and feature descriptions with dangerouslySetInnerHTML without HTML sanitization in ResourceListItem components. Attackers can inject malicious markup like img elements with onerror handlers into descriptions via the metadata service or Elasticsearch, executing JavaScript in every user's browser that views search results.
CVE-2026-80985	8.2	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: net/smc: carry oversized SMC-Rv2 LLC messages in the queue entry smc_llc_rmt_delete_rkey() and smc_llc_save_add_link_rkeys() read the part of a v2 message that does not fit into the 44-byte union smc_llc_msg, and both bound themselves by the size of the buffer it landed in, not by what arrived. On a link with a shared v2 receive buffer a 44-byte...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89632	8.2	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix use-before-check of ReparseDataLength in reparse_buf_ptr() reparse_buf_ptr() reads buf->ReparseDataLength before checking that count covers the full fixed header: buf = (struct reparse_data_buffer *)((u8 *)io + off); len = sizeof(*buf); /* 8 bytes */ rrlen = le16_to_cpu(buf->ReparseDataLengt...
CVE-2026-37008	8.1	HIGH		0.001		CrewAI before fb2323b offers a Python blocklist approach that operates at the wrong level of abstraction, a different vulnerability than CVE-2026-2275. Import-time blocking of module names does not address the availability of Python's complete object graph. For example, calling ctypes.CDLL(None) loads the C library without relying in any import statements. In other words, a within-process sandbox cannot merely acc...
CVE-2026-89535	8.1	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Reorder rpcrdma_rn_unregister before rdma_destroy_id svc_rdma_free() caches rdma->sc_cm_id->device before teardown, then calls rdma_destroy_id(sc_cm_id) which frees the cm_id. rpcrdma_rn_unregister() follows, but between those two calls the transport's sc_rn entry is still installed in the device's rd_xa. A concurrent ib_unregister_devi...
CVE-2026-89667	8.1	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: close shrinker/GC/fsnotify vs per-net shutdown race in filecache The shrinker, GC worker, and fsnotify/lease callbacks can unhash an nfsd_file from the rhashtable and then call nfsd_file_dispose_list_delayed() to move it to the per-net dispose list. If nfsd_file_cache_shutdown_net() runs concurrently, its rhashtable walk misses the already...
CVE-2026-89682	8.1	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix fcache_disposal UAF by inlining dispose state into nfsd_net nfsd_file_dispose_list_delayed() defers fput() to nfsd service threads via a per-net freeme queue, preventing the shrinker and GC worker from bearing the cost of closing files (see ffb402596147). However, the queue lives in a separately-allocated struct nfsd_fcache_disposal t...
CVE-2026-89709	8.1	HIGH		0.003		In the Linux kernel, the following vulnerability has been resolved: lockd, nfsd: RCU-protect nlmsvc_ops dispatch nlmsvc_ops is published by nfsd_lockd_init() and cleared by nfsd_lockd_shutdown() with plain stores, while lockd dereferences it unguarded from dispatch sites in fs/lockd/svcs.c. The pointer targets nfsd's .rodata and the fopen/fclose callbacks live in nfsd's .text, so a stale load after rmmod nfsd...
CVE-2026-90651	8.1	HIGH		0.002		Socket Firewall (socketdev/socket-registry-firewall) in registry mode before 2.0.0 does not verify upstream TLS certificates by default. When the api_ssl_verify and upstream_ssl_verify configuration keys are omitted from socket.yml, the generated configuration sets SOCKET_API_SSL_VERIFY='false' and UPSTREAM_SSL_VERIFY='false', and the OpenResty/Lua HTTP client used for outbound requests accepts any certificate, in...
CVE-2026-80929	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: sysctl: move the "cad_pid" entry from pid_table[] to kern_reboot_table[] cad_pid is global, and kill_cad_pid() is only used in the root namespace. However, due to pid_table_root_permissions(), a non-root user can unshare pid/user namespaces and modify it from the child namespace. This makes no sense and is simply wrong. Move it to kern_reboot_...
CVE-2026-80936	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: wifi: mt76: mt7925: cancel mlo_pm_work on stop mt7925 queues mlo_pm_work with a 5 second delay during multi-link power-save setup and never cancels it on the stop path. If the device is torn down inside that window, the work outlives the teardown and its timer fires afterwards, trying to queue onto the workqueue that is already gone: workqueue...
CVE-2026-80947	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: rtl8xxxu: fix use-after-free from rx_urb_wq on stop rtl8xxxu arms rx_urb_wq from the RX completion path: rtl8xxxu_rx_complete() hands the URB to rtl8xxxu_queue_rx_urb(), which queues it on rx_urb_pending_list and, once the list grows past RTL8XXXU_RX_URB_PENDING_WATER, schedules rx_urb_wq. The worker rtl8xxxu_rx_urb_work() drains rx_urb_p...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-80950	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: i3c: renesas: Check that the transfer is valid before accessing it The Renesas I3C driver uses an asynchronous model to transfer data. It prepares a struct renesas_i3c_xfer, enqueues it, and waits for completion. The interrupt handler dequeues the transfer, updates/uses it, and signals the waiting thread. If the completion times out, the waitin...
CVE-2026-80954	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: i3c: Fix unlocked dereference of dev->desc in i3c_device_get_supported_xfer_mode() i3c_device_get_supported_xfer_mode() uses dev->desc to obtain the master controller. However, dev->desc must not be dereferenced unless bus->lock is held, and this function does not take that lock. The function only needs access to the master controller associat...
CVE-2026-80955	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: dm-pcache: fix use-after-free and invalid seg operations in kset_replay() In kset_replay, when key->seg_gen is stale (key->seg_gen < key->cache_pos.cache_seg->gen), cache_key_put(key) is called but then key->cache_pos.cache_seg is accessed as the argument to cache_seg_get(). This is a use-after-free on the freed key memory. Although mempool recy...
CVE-2026-80959	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: dm-pcache: bound the persisted tail-position offset cache_pos_decode() takes the persisted key_tail and dirty_tail seg_off from the cache device and addresses within the segment with it. A seg_off at or past the segment data_size, controllable by whoever supplies the device (CAP_SYS_ADMIN), reads past the segment data. Reject a decoded seg_off ...
CVE-2026-80961	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: dm-pcache: validate kset key_num and intra-segment bounds Two more fields decoded from the cache device go unbounded. The kset key_num drives cache_kset_crc() and the replay loop in cache_replay(), the writeback worker and the GC worker, but only the magic and a fixed-seed CRC are checked first, so a non-last kset whose key_num exceeds the PCACH...
CVE-2026-80962	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: dm-pcache: validate geometry fields from on-disk cache_info cache_segs_init() iterates cache_info->n_segs times indexing cache->segments[], which is sized to the cache device geometry, and get_seg_id() takes each segment id from the on-media cache_info and the per-segment next_seg link. Both come from cache device metadata that is only CRC-prot...
CVE-2026-80975	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: mfd: qnap-mcu: keep the reply buffer alive past a command timeout qnap_mcu_exec() publishes an on-stack buffer to the receive path: unsigned char rx[QNAP_MCU_RX_BUFFER_SIZE]; ... reply->data = rx; reply->length = length; and qnap_mcu_receive_buf() writes into it from the serdev receive path, which runs out of flush_to_ldisc() and is not se...
CVE-2026-80991	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: net: ravb: serialize PTP clock teardown ravb_ptp_interrupt() can race with ravb_ptp_stop() and pass the clock to ptp_clock_event() while ptp_clock_unregister() is freeing it. This can lead to a use-after-free. Use READ_ONCE() and WRITE_ONCE() for lockless access to the clock pointer. Atomically detach it with xchg() before disabling PTP interr...
CVE-2026-80995	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: net: mctp: hold a reference to the route device in mctp_route_lookup() mctp_route_lookup() uses rt->dev without holding a reference on it. mctp_route_lookup_single() returns the route under RCU only, so the route's device can be torn down concurrently: mctp_dev_put() drops the last reference and synchronously kfree()s mdev->addrs. mctp_dev_sadd...
CVE-2026-81006	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ipmi: Remove all sysfs files on registration failure ipmi_add_smi() creates the nr_users and nr_msgs files before trying to create the maintenance_mode file. If that last creation fails, the error path removes only nr_users before dropping the final reference to the interface. Remove nr_msgs as well so no sysfs attribute embedded in the freed i...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-81015	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86/amd/pmc: Fix LPS0 and debugfs leaks when STB init fails amd_pmc_probe() registers the LPS0 s2idle handler with acpi_register_lps0_dev() and creates the driver's debugfs directory before calling amd_stb_s2d_init(), which is the last step in probe that can fail. When amd_stb_s2d_init() fails (for example the S2D telemetry region cann...
CVE-2026-89436	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: platform/x86: panasonic-laptop: Fix sentinel write past pcc->sinff[] acpi_pcc_retrieve_biosdata() rejects SINF packages only when pcc->num_sifr is strictly less than hkey->package.count, then unconditionally writes a trailing sentinel at pcc->sinff[hkey->package.count]. But pcc->sinff[] is allocated with exactly pcc->num_sifr elements (valid indice...
CVE-2026-89441	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: mmc: via-sdmmc: cancel card-detect work on remove Disabling the device interrupt and freeing the IRQ prevents new card-detect work from being queued, but carddet_work already queued by the handler can still run after via_sd_remove() returns. via_sdc_card_detect() recovers the host through container_of() and dereferences its MMIO base; once remov...
CVE-2026-89472	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: power: supply: charger-manager: register regulators before exposing sysfs charger_manager_remove() and the err_reg_extcon probe error path free each charger regulator with regulator_put() before tearing down the power_supply sysfs entries (power_supply_unregister()). charger_manager_remove() also calls try_charger_enable(cm, false) after the reg...
CVE-2026-89486	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ipmi: Fix use-after-free of cmd_rcvr in _ipmi_destroy_user() Commit 9e91f8a6c868 ("ipmi:msghandler: Remove srcu for the ipmi_interfaces list") dropped the synchronize_rcu() between unlinking the command receivers from intf->cmd_rcvrs and freeing them, updating only the comment that explains why the barrier is needed. The cmd_rcvrs list is still...
CVE-2026-89499	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ring-buffer: Stop remote reader update when page swap fails The remote swap_reader_page callback can return -EBUSY when the writer moves the head before the remote catches it, particularly during an event storm on a small buffer. __rb_get_reader_page_from_remote() currently warns about that failure but continues with the unchanged reader ID and ...
CVE-2026-89500	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ring-buffer: Make cpu_buffer::free_page a buffer_data_read_page Discarding a cached reader page after a concurrent ring buffer resize uses the new global subbuf_order for the free_pages() call. This mismatched order may crashes the kernel or leaks memory because the cached page was allocated under the old size. Save the actual free_page order a...
CVE-2026-89501	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ring-buffer: Hold cpu_buffer::lock when resizing a subbuf Because, ring_buffer_subbuf_order_set() can clear cpu_buffer->free_page, hold cpu_buffer->lock to prevent races with ring_buffer_alloc_read_page() and ring_buffer_free_read_page().
CVE-2026-89503	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ring-buffer: Fix subbuf resize race with ring_buffer_alloc_read_page() ring_buffer_alloc_read_page() is racy with ring_buffer_subbuf_order_set, it can allocate a reader page with an outdated order. This isn't a big issue, the user can still re-allocate a new reader page and try again. However, what is more problematic is if the value of subbuf_...
CVE-2026-89507	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: RDMA/ucma: Lock the handler in ucma_write_cm_event() ctx->file may only be changed under the handler lock and the xa_lock, which is what stops uevents being queued for a ctx while ucma_migrate_id() moves it to another file. The CM core takes that lock before invoking ucma_event_handler(), but the write() paths that queue uevents themselves do n...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89520	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: sched/core: Make core-sched flips wait for in-flight selections Core scheduling's pick_next_task() operates on all sibling rq's under one acquisition of the shared core-wide lock. A ->pick_task() that releases the rq lock leaves every sibling __lock momentarily free, letting __sched_core_flip(false) complete mid-selection and rebind rq_lockp() un...
CVE-2026-89522	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: media: staging/ipu7: fix async notifier UAF on probe error path isys_register_devices() registers the V4L2 async notifier via isys_notifier_init(). If a subsequent probe step such as isys_fw_log_init() fails, isys_probe() jumps to the out_cleanup label which only calls isys_unregister_devices(). That helper tears down the video devices, subdevic...
CVE-2026-89523	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: wifi: mt76: mt7925: cancel pending mlo_pm_work If the device is reset, suspended or unregistered within that window, the pending work can still run and access vif/bss data that may already be freed, or send MCU commands while the firmware is not available. Add cancel_delayed_work_sync(&dev->mlo_pm_work) in all relevant teardown and suspend path...
CVE-2026-89545	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: sunrpc: defer rq_argp and rq_resp free until after RCU grace period svc_rqst_free() frees rqstp->rq_argp and rqstp->rq_resp synchronously via kfree(), but defers the rqstp struct free via kfree_rcu(). After svc_exit_thread() calls list_del_rcu() and svc_rqst_free(), there is a window where RCU readers that started before list_del_rcu() can stil...
CVE-2026-89564	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ip: orphan prefetched skbs before multicast forwarding IPv4 and IPv6 input preserve an skb->sk association installed by bpf_sk_assign() so that local delivery can use the selected socket under RCU. Both address families can also prefetch a socket in UDP early demux. In both paths (BPF and UDP early demux) a reference is not guaranteed to be held...
CVE-2026-89570	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: cxl/mce: Make the MCE notifier per-region Flavien Solt reported lifetime issues with the CXL MCE notifier, which can lead to NULL dereferences and use-after-free in the MCE handler. The notifier was registered per memory device and stored in 'struct cxl_memdev_state', even though it only needs the region state (the region's SPA range and its ext...
CVE-2026-89574	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: dm array: validate array block headers on read array_block_check() validates blocknr and csum and nothing else, while node_check(), next to it, has bounded the structural fields since both were written. dm_array_cursor_next() takes its loop bound from the on-disk nr_entries and element_at() is unguarded pointer arithmetic, so a count larger than...
CVE-2026-89580	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: bpf: Disable preemption in __bpf_get_stack get_perf_callchain() returns a per-CPU perf_callchain_entry buffer and releases its recursion slot via put_callchain_entry() before returning, so nothing keeps the entry reserved while __bpf_get_stack() consumes it below. A preemptible BPF program (e.g. a non-sleepable raw tracepoint program on a PREEM...
CVE-2026-89581	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: bpf, x86: Fix per-CPU address resolution into an extended register The destination of the per-CPU address MOV is encoded in ModRM.reg, which is extended by REX.R, but the REX prefix is built with add_1mod(), which sets REX.B. REX.B extends ModRM.rm and SIB.base, and this instruction addresses memory as disp32 with no base, so the bit has no effe...
CVE-2026-89584	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: block: validate user space vectors during extraction The bio-based drivers don't necessarily check the alignment split, and stacking block drivers don't always handle a misalignment detected after submitting the bio. Validate user vectors against the device's dma_alignment as the bio is built from the iov_iter, rejecting misaligned early with -E...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89600	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: fanotify: fix use-after-free of file range info fsnotify_pre_content() builds its file_range on the triggering task's stack. fanotify_alloc_perm_event() saves a pointer to range.pos in the heap-allocated permission event so copy_range_info_to_user() can report the offset later. The event reader can set the event state to FAN_EVENT_REPORTED and ...
CVE-2026-89602	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: erofs: skip sufficiently large global buffers when resizing z_erofs_gbuf_nrpages is advanced only after every global buffer has been grown. If a resize fails after some buffers were enlarged, a retry revisits those enlarged buffers. Retrying the same size then returns -ENOMEM because alloc_pages_bulk() has no pages to add and the unchanged retu...
CVE-2026-89619	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: HID: intel-thc-hid: intel-quickspi: bound GET_REPORT response to the caller buffer quickspi_hid_raw_request() receives the caller's buffer length in len, but quickspi_get_report() never sees it and copies the whole device-supplied response into buf regardless: memcpy(buf, qsdev->report_buf, qsdev->report_len); qsdev->report_len comes from ...
CVE-2026-89620	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: HID: intel-thc-hid: intel-quickspi: validate report size before copy write_cmd_to_txdma() builds an output report in qsdev->report_buf, a heap buffer allocated in quickspi_alloc_report_buf() to the device-descriptor derived max_report_len (a few hundred bytes for a touch controller). It copies the caller-supplied report into that buffer: m...
CVE-2026-89622	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: HID: mcp2221: clear rxbuf after I2C/SMBus transfer completes mcp_i2c_smbus_read() stores the caller-supplied buffer pointer in mcp->rxbuf for the duration of a transfer but never clears it when the transfer finishes or times out. Once the caller frees or reuses the buffer, mcp->rxbuf becomes a dangling pointer. A delayed or spurious MCP2221_I2C_...
CVE-2026-89624	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: HID: universal-pidff: stop the device when force-feedback init fails universal_pidff_probe() starts the device with hid_hw_start() and then, if force-feedback initialisation fails, returns the error through a label that only does "return error". The device is left started. The HID core does not unwind on the driver's behalf. __hid_device_prob...
CVE-2026-89638	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: smb: client: clear setuid/setgid bit on write with cifsacl/modefromsid/posix extensions When a file has the setuid or setgid bit set and is written to, the VFS strips those bits and issues a setattr with ATTR_KILL_SUID/ATTR_KILL_SGID together with an ATTR_MODE carrying the already-cleared mode. Both cifs_setattr_unix() and cifs_setattr_nounix()...
CVE-2026-89641	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: cifs: clear tcon after cifsFileInfo_put() in cifs_file_set_size() When the else branch of cifs_file_set_size() finds a writable file handle via find_writable_file(), it borrows tcon and server from the handle's tlink, attempts the handle-based set_file_size() RPC, and then releases the handle with cifsFileInfo_put(). If set_file_size() fails, e...
CVE-2026-89646	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ceph: fix leaked inode reference on writeback abort at umount ceph_dirty_folio() takes a wrbuffer claim on each newly dirtied folio: it bumps i_wrbuffer_ref (taking an ihold() on the 0->1 transition) and attaches the snap_context to folio->private. That claim is released only by ceph_put_wrbuffer_cap_refs(), which for a submitted write runs fro...
CVE-2026-89668	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: move nfsd_debugfs_init() after nfsd4_init_slabs() in init_nfsd() nfsd_debugfs_init() runs before nfsd4_init_slabs() in init_nfsd(). If the slab allocation fails, the bare "return retval" bypasses nfsd_debugfs_exit(), leaving orphan debugfs files with stale fops pointers into the freed module text. Move nfsd_debugfs_init() to after the sla...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89670	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: hold rcu across localio cmpxchg retry nfsd_file objects are freed via call_rcu (filecache.c:296), and nfsd_file_slab is created without SLAB_TYPESAFE_BY_RCU (KMEM_CACHE(nfsd_file, 0) at filecache.c:789), so the slab page backing a freed nfsd_file becomes freely reclaimable once the RCU grace period elapses. The again: retry block in nfsd_...
CVE-2026-89690	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: defer vfree of compound ops to fix rpc_status UAF The rpc_status netlink dumpit walks every in-flight svc_rqst under rcu_read_lock and, for NFSv4 requests, reads opnums out of args->ops[]. But args->ops is a separate vmalloc buffer freed synchronously by vfree() in nfsd4_release_compoundargs() at the end of every compound. The dumpit's rcu...
CVE-2026-89738	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: usb: gadget: at91_udc: drain polled-VBUS timer/work before udc is freed In polled-VBUS mode (board.vbus_pin && board.vbus_polled), probe arms a self-restarting cycle: at91_vbus_timer() schedules vbus_timer_work, and at91_vbus_timer_work() calls at91_vbus_update() and re-arms the timer via mod_timer(). Both recover the same udc through container_...
CVE-2026-89747	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: tracing: Fix use-after-free in trace_pipe read on sub-buffer order change Writing to buffer_subbuf_size_kb calls ring_buffer_subbuf_order_set(), which frees every sub-buffer of the ring buffer, including the reader page, and replaces them with newly allocated ones. Readers of trace_pipe hold pointers into those pages. ring_buffer_peek() looks u...
CVE-2026-89748	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: tracing: Fix retry exhaustion in simple ring buffer reader swap simple_ring_buffer_swap_reader_page() starts with retry set to 8 and post-decrements it only after a failed link replacement. On the final attempt, a successful replacement leaves retry at zero, while a failed replacement leaves it at -1. The current !retry test reverses both outco...
CVE-2026-89754	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: mm/pagewalk: fix stale walk->action escaping walk_pmd_range() If ->pmd_entry() sets walk->action = ACTION_AGAIN, the pmd_none() check is retried. The PMD entry may be cleared at the point of retry. In this case, if walk->ops->install_pte is not specified, the code continues to the next PMD entry in the range without resetting walk->action to A...
CVE-2026-89755	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: mm/migrate_device: clear stale mapping after freeing swapcache __migrate_device_pages() reads the folio mapping before calling folio_free_swap(). When folio_free_swap() succeeds, the folio is removed from the swap cache, but the saved mapping still points to swap_space. Passing the stale mapping to folio_migrate_mapping() makes it use the mapp...
CVE-2026-89758	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: mm/mempolicy: skip non-present PMDs when queueing folios Patch series "mm: handle device-private PMDs in walk callbacks", v3. Since commit 368076f52ebe ("mm/huge_memory: add device-private THP support to PMD operations") a PMD may hold a device-private swap entry whenever an HMM-based GPU driver migrates an anonymous THP folio to device memory ...
CVE-2026-89760	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: mm, swap: don't free a hibernation slot that is in the swap cache A slot with a folio in the swap cache is freed when the folio leaves the cache, not when its count drops. swap_put_entries_cluster() follows that rule. swap_free_hibernation_slot() does not, it calls __swap_cluster_free_entries() whether or not a folio sits on the slot. Cluster...
CVE-2026-89761	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: apparmor: fix out-of-bounds write when null terminating a label vec aa_vec_unique() null terminates at vec[n - dups] when VEC_FLAG_TERMINATE is passed. If the components are all distinct no duplicates are dropped, dups is 0 and the terminator goes to vec[n], so the caller has to provide room for n + 1 entries. aa_label_strn_parse() sets up its ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89762	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: apparmor: fix cred UAF caused by begin_current_label_crit_section() AppArmor's begin_current_label_crit_section() is a scary function called from lots of LSM hooks (in particular VFS/socket-related ones) that checks if the label referenced by the current creds is marked FLAG_STALE, and if so, attempts to use aa_replace_current_label() to replace...
CVE-2026-89763	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: KEYS: trusted: Fix TPM teardown ordering trusted_tpm_exit() drops the TPM chip reference and frees the digest array before unregistering the trusted key type. key_type_lookup() holds key_types_sem for reading until the key operation finishes, while unregister_key_type() takes it for writing. It therefore provides the synchronization point that m...
CVE-2026-89764	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: rust: devres: fix race between concurrent revokers There is a potential race condition when two paths try to revoke a Devres concurrently. The driver core's devres_release_all() calls Revocable::revoke() via the release callback, while Devres::drop() calls revoke_nosync() on another CPU. The revoker that does not claim the is_available swap re...
CVE-2026-89767	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ovl: fix double end_creating() on the casefold-mismatch path ovl_create_real() releases the new dentry twice when the casefold consistency check fails. The S_IFDIR branch calls end_creating() and sets err, then falls through to the common out: label which calls end_creating() on the same dentry again: case S_IFDIR: newdentry = ovl_do_mkdir(...
CVE-2026-89771	7.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: ring-buffer: Fix subbuf resize race with ring buffer readers trace_buffer_subbuf_size is read lockless in ring_buffer_read_page() and ring_buffer_read_start(), while it can simultaneously be resized with ring_buffer_subbuf_order_set(). Instead of trace_buffer::subbuf_size, use bpage::order in ring_buffer_read_start() and ring_buffer_read_page()...
CVE-2026-29811	7.7	HIGH		0.003		CyberPanel before 2.4.4 attempts to detect an "alais" domain (i.e., a second domain that serves the same content as a primary domain; normally spelled "alias") via an ORM query filter rather than a Python "if" statement.
CVE-2026-81016	7.7	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: platform/x86/amd/pmc: Propagate SMU errors and validate S2D address amd_stb_s2d_init() discards the return value of several S2D SMU commands. When the SMU refuses a command (e.g. "SMU cmd failed. err: 0xff") the failure is only noticed indirectly - if at all - and reported as -EIO, masking the real error. More seriously, the S2D_PHYS_ADDR_LOW/H...
CVE-2026-89743	7.7	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: misc: nsm: bound the device-reported response length nsm_sendrecv_msg_locked() stores the virtqueue used-ring length reported by the NSM device into msg->resp.len without bounding it to the response buffer. A malicious or buggy backend can report a length larger than the response buffer; parse_resp_raw() then copies that many bytes out of the fi...
CVE-2026-80943	7.6	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: rtlwifi: rtl8192du: check QoS TID before indexing tids rtl92du_tx_fill_desc() uses ieee80211_get_tid() to read the QoS TID from the 802.11 header and then uses it as an index into sta_entry->tids[]. ieee80211_get_tid() returns the low 4-bit QoS TID value, so the result can be in the range 0..15. rtlwifi only allocates MAX_TID_COUNT entrie...
CVE-2026-80997	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: net: ipa: fix stalled modem TX queue after runtime resume ipa_start_xmit() unconditionally stops the TX queue before calling pm_runtime_get(), relying on the wake scheduled by runtime resume (ipa_modem_wake_queue_work()) to restart it once power is ACTIVE. But that work is queued from within the runtime resume callback, before the device's power...
CVE-2026-80998	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: net: bnxt: ring the doorbell when SW USO exits early When a burst of packets is handed down to the driver, the driver defers the doorbell to the end by setting txr->kick_pending = 1. The normal TX path handles this, but the SW USO path can miss it if it returns early. If bnxt_sw_udp_gso_xmit runs but returns early with NETDEV_TX_BUSY and txr->k...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89528	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Reject Read lists that exceed the page budget Individual Read segment lengths are validated at decode time, but nothing prevents a requester from sending multiple segments whose cumulative length exceeds the rq_pages array budget. When one segment fills the page array exactly, the runtime guard in svc_rdma_build_read_segment() is bypass...
CVE-2026-89544	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: fix gssx_dec_option_array error path bugs Four coupled defects in the gssx XDR option-array decoder make the error paths unsafe: a NULL deref in the caller, a refcount leak on the decoded group_info, and a latent use-after-free that the leak fix would otherwise expose. gssx_dec_option_array() sets oa->count = 1 before allocating oa->dat...
CVE-2026-89561	7.5	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: ipv6: rpl: fix NULL dereference of idev in ipv6_rpl_srh_rcv() ipv6_rpl_srh_rcv() dereferences idev from __in6_dev_get() without a NULL check when reading idev->cnf.rpl_seg_enabled. When the device's MTU drops below IPV6_MIN_MTU, addrconf_ifdown() clears dev->ip6_ptr through RCU_INIT_POINTER(). A packet that passed the idev check in ip6_rcv_core...
CVE-2026-89647	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: ceph: do not repeat ceph_trim_dentries() if no progress possible ceph_cap_reclaim_work() re-queues itself for as long as ceph_trim_dentries() returns -EAGAIN, which happens whenever a lease walk exhausts its `nr_to_scan` budget. This creates a busy loop that consumes CPU without making any progress when there is nothing to reclaim: with no cap ...
CVE-2026-89648	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: ceph: cap delegated inode count in ceph_parse_deleg_inos() ceph_parse_deleg_inos() decodes interval sets of delegated inode numbers from an MDS create-with-delegation reply. For each set it reads a 64-bit start and a 64-bit len with ceph_decode_64_safe(), which only validates that the eight bytes are present in the message, not the value, and th...
CVE-2026-89664	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: release OPEN-decoded posix ACLs via op_release nfsd4_decode_createhow4() calls nfsd4_decode_fattr4(), which allocates refcounted struct posix_acl objects via posix_acl_alloc() and stores them in open->op_pacl and open->op_dpac1. These pointers must be released once the OPEN compound finishes. When nfsd4_decode_open_claim4() returns a non-...
CVE-2026-89678	7.5	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix partial-write detection in nfsd_direct_write nfsd_direct_write() walks a list of write segments and, after each vfs_iocb_iter_write(), tries to detect a short write so the loop can stop before placing the next segment at a wrong file offset: host_err = vfs_iocb_iter_write(file, kiocb, &segments[i].iter); if (host_err < 0) ...
CVE-2026-89679	7.5	HIGH		0.007		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix null dereference in nfsd4_setattr for deleg timestamp attrs When a SETATTR request includes FATTR4_WORD2_TIME_DELEG_ACCESS or FATTR4_WORD2_TIME_DELEG_MODIFY in the attribute bitmap, nfsd4_setattr() sets deleg_attrs=true and calls nfs4_preprocess_stateid_op() to validate the stateid. If the client supplies the NFSv4 "one stateid" (all-...
CVE-2026-89680	7.5	HIGH		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix nfsd_file leak on inter-server COPY setup failure When nfsd4_setup_inter_ssc() fails, nfsd4_copy() returns nfserr_offload_denied directly, bypassing the out: label where release_copy_files() would drop the nf_dst reference taken by nfs4_preprocess_stateid_op(). Each failed inter-server COPY leaks one nfsd_file, pinning file/inode/dentr...
CVE-2026-89685	7.5	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix clock domain mismatch in clients_still_reclaiming() clients_still_reclaiming() computes a deadline from nn->boot_time (CLOCK_REALTIME, ~1.7 billion) but compares it against ktime_get_boottime_seconds() (CLOCK_BOOTTIME, seconds since boot). The comparison is always false — it would take ~54 years of uptime for BOOTTIME to exceed the REA...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89687	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: ensure nfsd_file_do_acquire() does not use a non-opened file ->atomic_open is permitted to return success without actually opening the file. It indicates this by calling finish_no_open(). This means dentry_create() can return a file which hasn't been opened. This is extremely unlikely as ->atomic_open handlers typically use finish_no_open...
CVE-2026-89692	7.5	HIGH		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: clear CALLBACK_RUNNING on failed delegation recall queue nfsd_break_one_deleg() sets NFSD4_CALLBACK_RUNNING via test_and_set_bit at entry to serialize recall work, then calls nfsd4_run_cb() to queue the recall. When the queue attempt fails the refcount bump is undone, but the RUNNING bit is left set. The only site that clears the bit is ...
CVE-2026-89695	7.5	HIGH		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: cap decoded POSIX ACL count to bound sort cost nfsd4_decode_posixacl() reads a u32 entry count off the wire and passes it straight to posix_acl_alloc() and sort_pacl_range(). The latter is an O(n^2) bubble sort, so a client-chosen count drives unbounded CPU in the server's compound processing path. nfsd4_decode_posixacl() xdr_st...
CVE-2026-89769	7.4	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: clocksource/drivers/nxp-pit: Fix IRQ leak on cpuhp_setup_state error path When cpuhp_setup_state fails after pit_clockevent_per_cpu_init has successfully called request_irq, the error handling jumps directly to out_pit_clocksource_unregister without freeing the registered IRQ. This leaks the IRQ line and, since kfree(pit) follows, leaves a dang...
CVE-2026-89521	7.3	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: sched/core: Handle pick_task() releasing the rq lock Core scheduling's pick_next_task() breaks when a ->pick_task() implementation can release the rq lock. The selection state derived on entry is only valid while the lock is held continuously. Once a pick can drop the lock, an interleaving selection can invalidate all of it: the single-CPU fast ...
CVE-2026-80958	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: dm-pcache: clamp the tail kset read to the segment data region The tail-kset read in cache_replay(), the writeback worker and the GC worker bounds its length by PCACHE_SEG_SIZE - seg_off, the raw segment size rather than the data region. A tail near the segment end reads past the segment data into the following control area. Clamp the read to c...
CVE-2026-89571	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: cxl/features: bound fwctl command payload to the input buffer fwctl_cmd_rpc() copies cmd->in_len bytes into inbuf = kzalloc(cmd->in_len) and passes inbuf and in_len to ->fw_rpc(). The CXL callback cxlctl_fw_rpc() ignores in_len and never checks the user-controlled op_size against it. cxlctl_set_feature() bounds op_size only from below (op_size...
CVE-2026-89639	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: cifs: use cifs_invalidate_cache() in cifs_do_truncate() for O_TRUNC cifs_do_truncate() is invoked from cifs_open() without i_rwsem, so it cannot use cifs_resize_file_locked() to perform a proper fscache cookie resize. Instead, add cifs_invalidate_cache() after cifs_setsize(). cifs_invalidate_cache() calls fscache_invalidate(), which works with...
CVE-2026-89691	7.1	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: nfsd: clear opcnt on compound arg release to prevent OOB read nfsd4_release_compoundargs() resets args->ops to the inline iops[8] array when the dynamically-allocated ops buffer is freed, but leaves args->opcnt at its original value (which can be up to 200 for NFSv4.1+ compounds). If rq_status_counter is stuck at an odd value (which can happen ...
CVE-2026-89705	7.1	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: nfsd: restore rq_status_counter to even on all nfsd_dispatch() exit paths nfsd_dispatch() sets rq_status_counter to an odd value once a request has been decoded, and back to an even value once it has been fully processed, forming a seq-lock like protocol with the lockless reader in nfsd_nl_rpc_status_get_dumpit(). Only the fully successful path...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89731	7.1	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: cxl/ras: Fix cxl_rch_get_aer_info() out-of-bounds AER register read cxl_rch_get_aer_info() copies the RCH Downstream Port AER capability from the RCRB MMIO block using a readl() loop bounded by sizeof(struct aer_capability_regs). This struct is a software layout and its embedded struct pcie_tlp_log is larger than the on-wire AER capability. As a...
CVE-2026-90775	7.1	HIGH		0.003		PostGIS address_standardizer through 3.7.0 fails to validate the Weight parameter from caller-supplied rules tables before using it as an array index. Attackers can craft malicious rule rows with out-of-range Weight values to trigger out-of-bounds reads in the load_value array, causing the PostgreSQL backend process to crash and terminate all cluster sessions.
CVE-2026-89459	7.0	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: s390/percpu: Fix MVIY_PERCPU() with older binutils Commit a737737cdb9c ("s390/percpu: Infrastructure for more efficient this_cpu operations") introduced MVIY_PERCPU(), which stringifies arguments that are already C string literals. This generates an assembler macro invocation with whitespace-separated quoted arguments: GEN_MVIY "459712" "%r3"...
CVE-2025-25252	6.5	MEDI		0.003	fortinet:fortios	An Insufficient Session Expiration vulnerability [CWE-613] in FortiOS SSL VPN 7.6.0 through 7.6.2, 7.4.0 through 7.4.6, 7.2.0 through 7.2.10, 7.0.0 through 7.0.16, 6.4 all versions may allow a remote attacker (e.g. a former admin whose account was removed and whose session was terminated) in possession of the SAML record of a user session to access or re-open that session via re-use of SAML record.
CVE-2026-90509	5.5	MEDI		0.003		A weakness has been identified in dromara orion-visor up to 2.5.7. Affected by this issue is the function ExposeApiAspect.beforeExposeApi of the file ExposeApiAspect.java. Executing a manipulation can lead to hard-coded credentials. The attack can be executed remotely. The exploit has been made available to the public and could be used for attacks. The project was informed of the problem early through an issue rep...
CVE-2026-90510	5.5	MEDI		0.003		A security vulnerability has been detected in dromara orion-visor up to 2.5.7. This affects the function HostKeyServiceImpl.encryptKey of the file orion-visor-modules/orion-visor-module-asset/orion-visor-module-as set-service/src/main/java/org/dromara/visor/module/asset/service/impl/HostKeyServiceImpl.java. The manipulation leads to use of hard-coded cryptographic key . The attack is possible to be carried out rem...
CVE-2026-90522	5.5	MEDI		0.005		A vulnerability was determined in jaychouchannel Tourism-Management-System up to d984d172dceca907f8b447efbdb06dc233f7938d. Impacted is the function resetPass of the file UsersController.java of the component Password Recovery. This manipulation causes weak password recovery. The attack can be initiated remotely. The exploit has been publicly disclosed and may be utilized. Continuous delivery with rolling releases ...
CVE-2026-90523	5.5	MEDI		0.005		A vulnerability was identified in jaychouchannel Tourism-Management-System up to 229956e20dbd4a80eef14535e44d3099502af09. The affected element is an unknown function of the file travel/src/main/java/com/controller/UsersController.java of the component User Register Endpoint. Such manipulation of the argument UsersEntity leads to improper privilege management. The attack can be launched remotely. The exploit is pu...
CVE-2026-90584	5.5	MEDI		0.004		A weakness has been identified in TooTallNate Java-WebSocket up to 1.6.1. The impacted element is the function processFrameContinuousAndNonFin of the file Draft_6455.java of the component Fragmentation Handler. Executing a manipulation can lead to allocation of resources. The attack may be performed from remote. The exploit has been made available to the public and could be used for attacks. The pull request to fi...
CVE-2026-90583	5.3	MEDI		0.003		A security flaw has been discovered in kagisearch smallweb up to 0ecb9c48edbf98dc7e934b54fbac43869e64b4cf. The affected element is the function index of the file app/sw.py of the component Query String Rendering. Performing a manipulation of the argument qs results in cross site scripting. The attack is possible to be carried out remotely. This product adopts a rolling release strategy to maintain continuous deliv...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-90563	5.1	MEDI		0.002		A vulnerability was determined in maliangnansheng bbs-springboot 3.0.0. This affects the function utils.toToc of the file ArticleController.java. This manipulation causes cross site scripting. The attack is possible to be carried out remotely.
CVE-2026-90569	4.8	MEDI		0.003		A flaw has been found in linlinjava litemall 1.5.0/1.6.0/1.7.0/1.8.0. This vulnerability affects the function AdminTopicController.validate of the file litemall-vue/src/views/items/topic/index.vue of the component Admin Topic Handler. This manipulation causes cross site scripting. The attack may be initiated remotely. The project was informed of the problem early through an issue report but has not responded yet.
CVE-2026-90570	4.8	MEDI		0.003		A vulnerability has been found in linlinjava litemall 1.4.0/1.5.0/1.6.0/1.7.0/1.8.0. This issue affects the function AdminGoodsService.validate of the file litemall-vue/src/views/items/detail/index.vue of the component Product Detail. Such manipulation of the argument detail leads to cross site scripting. The attack may be launched remotely. The project was informed of the problem early through an issue report but...
CVE-2026-90488	2.1	LOW		0.002		A vulnerability was determined in Xuxueli xxl-job up to 3.4.2. This affects the function GroovyClassLoader.parseClass of the file xxl-job-core/src/main/java/com/xxl/job/core/glue/GlueFactory.java. This manipulation causes code injection. Remote exploitation of the attack is possible. The exploit has been publicly disclosed and may be utilized. The vendor was contacted early about this disclosure but did not respon...
CVE-2026-90511	2.1	LOW		0.002		A vulnerability was detected in GongShengyue OnlineBooks up to dfc5eacc08d3b0396c266049548618f6fb9587ea. This vulnerability affects unknown code of the file src/cn/ylcto/book/servlet/BooksServlet.java of the component listSplit Interface. The manipulation of the argument column results in sql injection. The attack may be performed from remote. The exploit is now public and may be used. This product utilizes a roll...
CVE-2026-90520	2.1	LOW		0.004		A vulnerability has been found in jaychouchannel Tourism-Management-System up to 84d8ec384f669df3985293dab293bb7b477efa64. This vulnerability affects unknown code of the file AuthorizationInterceptor.java of the component Authorization Interceptor. The manipulation leads to improper authorization. It is possible to initiate the attack remotely. The exploit has been disclosed to the public and may be used. This pro...
CVE-2026-90521	2.1	LOW		0.004		A vulnerability was found in jaychouchannel Tourism-Management-System up to 8122bf020d91199eddfff3ee02d1632a70a9a132. This issue affects some unknown processing of the file MenpiaodingdanController.java of the component CRUD. The manipulation of the argument ID results in authorization bypass. It is possible to launch the attack remotely. The exploit has been made public and could be used. This product takes the a...
CVE-2026-90581	2.1	LOW		0.002		A vulnerability was determined in cym1102 nginxWebUI up to 4.4.2. This issue affects the function MainController.autoUpdate of the file /adminPage/main/autoUpdate. This manipulation of the argument url causes code injection. Remote exploitation of the attack is possible. The exploit has been publicly disclosed and may be utilized. The pull request to fix this issue awaits acceptance.
CVE-2026-90594	2.1	LOW		0.002		A vulnerability was identified in wxiaoqi Spring-Cloud-Platform 3.0.1/3.1.0. This vulnerability affects the function PermissionService.checkUserPermission of the file /rpc/service/PermissionService.java of the component Permission Service. The manipulation leads to missing authorization. Remote exploitation of the attack is possible. The exploit is publicly available and might be used. The project was informed of ...
CVE-2026-90595	2.1	LOW		0.002		A security flaw has been discovered in wxiaoqi Spring-Cloud-Platform 1.0/2.2/3.0. This issue affects the function OnlineController.getOnlineInfo of the file aceModules/ace-admin/auth/controller/OnlineController.java. The manipulation results in missing authorization. The attack can be executed remotely. The exploit has been released to the public and may be used for attacks. The project was informed of the problem...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-90598	2.1	LOW		0.002		A vulnerability was detected in jaygajera17 E-commerce-project-springBoot up to 5e74a46b4b70623d0e4a0c9c4aee3bd1777185d2. The impacted element is the function UserController.updateUser of the file UserController.java. Performing a manipulation of the argument userid results in authorization bypass. It is possible to initiate the attack remotely. The exploit is now public and may be used. This product is using a ro...
CVE-2025-64059	1.8	LOW		0.002		Grav 1.7.50.2 allows admins to enter JavaScript via the Home Page editor. NOTE: the relevance of this for stored XSS is disputed because admins are allowed to modify templates, install plugins, and upload other executable content.
CVE-2026-80948				0.002		In the Linux kernel, the following vulnerability has been resolved: wifi: iwlwifi: dvm: fix memory leak in iwl_op_mode_dvm_start() In iwl_op_mode_dvm_start(), jumping to out_free_eeprom currently bypasses the out_free_eeprom_blob label. Consequently, error paths triggered after successfully parsing the EEPROM free priv->nvm_data but leak priv->eeprom_blob. Fix this memory leak by reordering the error handling l...
CVE-2026-89556				0.002		In the Linux kernel, the following vulnerability has been resolved: module: validate string table section types In elf_validity_cache_sechdrs, section sizes and offsets are validated, unless the section type is SHT_NULL or SHT_NOBITS. Later, elf_validity_cache_secstrings and elf_validity_cache_index_str access the section name table (.shstrtab) and symbol string table (.strtab) headers without first ensuring th...
CVE-2026-89642				0.002		In the Linux kernel, the following vulnerability has been resolved: cifs: call pagecache_isize_extended() in cifs_setsize() when extending cifs_setsize() calls truncate_pagecache() but skips pagecache_isize_extended() on extension. truncate_setsize() shows the correct pattern: i_size_write(inode, newsize); if (newsize > oldsize) pagecache_isize_extended(inode, oldsize, newsize); truncate_pagecache(...
CVE-2026-89722				0.002		In the Linux kernel, the following vulnerability has been resolved: PCI/sysfs: Fix out-of-bounds read in pci_write_legacy_io() pci_write_legacy_io() loads 4 bytes from the kernfs write buffer regardless of how many bytes userspace wrote: if (count != 1 && count != 2 && count != 4) return -EINVAL; return pci_legacy_write(bus, off, *(u32 *)buf, count); kernfs_fop_write_iter() allocates the buffer ...
CVE-2026-89773				0.002		In the Linux kernel, the following vulnerability has been resolved: drm/amd/display: Skip Update HDCP Config In Transition State Transition state does not have a valid dm_stream_ctx that should skip configuring HDCP routine. The routine is valid to go through only when a valid stream is created.

P3/P4 items (237) are in the Excel report. Unscored CVEs are newly published and awaiting NVD analysis; re-check tomorrow's report.