

Daily Vulnerability Report - 2026-09-16

Window (UTC): 2026-09-16T00:00 to 2026-09-17T00:00 | Sources: NVD, CISA KEV, FIRST EPSS | Generated 2026-09-17 06:05:47 UTC

Total	KEV (exploited)	Critical	High	Medium	Low	Unscored	Watchlist
3006	6	285	1510	814	128	269	1596

P1 - Act now (KEV / high EPSS)

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-20079	10.0	CRIT	Yes	0.758	cisco:secure_firewall_management_center	A vulnerability in the web interface of Cisco Secure Firewall Management Center (FMC) Software could allow an unauthenticated, remote attacker to bypass authentication and execute script files on an affected device to obtain root access to the underlying operating system. This vulnerability is due to an improper system process that is created at boot time. An attacker could exploit this vulnerability by s...
CVE-2026-76460	10.0	CRIT	Yes		cisco:identity_services_engine	A vulnerability in an API of Cisco Identity Services Engine (ISE) could allow an unauthenticated, remote attacker to bypass authentication. This vulnerability is due to insufficient authentication control on an API endpoint. An attacker could exploit this vulnerability by sending a crafted request to an affected API endpoint. A successful exploit could allow the attacker to gain unauthorized access to the affec...
CVE-2026-20349	8.6	HIGH	Yes	0.022	cisco:adaptive_security_appliance_software, cisco:secure_firewall_threat_defense	A vulnerability in the Remote Access SSL VPN service for Cisco Secure Firewall Adaptive Security Appliance (ASA) Software and Cisco Secure Firewall Threat Defense (FTD) Software could allow an unauthenticated, remote attacker to cause the device to reload unexpectedly, resulting in a denial of service (DoS) condition. This vulnerability is due to insufficient error checking when processing HTTP requests. ...
CVE-2026-20316	5.3	MEDI	Yes	0.112	cisco:secure_firewall_management_center	A vulnerability in the web interface of Cisco Secure Firewall Management Center (FMC) Software could allow an unauthenticated, remote attacker to log in to an affected device using a low-privileged account to access sensitive data within the impacted systems. This vulnerability is due to the presence of static user credentials for a low-privileged account. An attacker could exploit this vulnerability by us...
CVE-2026-58704			Yes	0.001	google:pixel	Google Pixel devices contain an improper authorization vulnerability in the cellular modem. A logic error may allow an attacker to bypass permission checks and escalate privileges.
CVE-2026-87886			Yes		acronis:backup	Acronis Backup plugin for cPanel & WHM and extension for Plesk contains an incorrect default permissions vulnerability that could allow for privilege escalation.

P2 - High (CVSS >= 9.0 or 7.0+ with EPSS >= 0.10)

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-20130	10.0	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC), engineering teams have conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-20130 are...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-20192	10.0	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) engineering teams have conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-20192 are ...
CVE-2026-45618	10.0	CRIT		0.009		LiquidJS is a Shopify/GitHub Pages compatible template engine. Prior to version 10.26.0, it is possible to execute arbitrary code with crafted templates. Version 10.26.0 patches the issue.
CVE-2026-65381	10.0	CRIT		0.002	apple:macos	A validation issue existed in the entitlement verification. This issue was addressed with improved validation of the process entitlement. This issue is fixed in macOS Golden Gate 27, macOS Sequoia 15.8, macOS Tahoe 26.7. A malicious app may be able to break out of its sandbox.
CVE-2026-70416	10.0	CRIT				Dell ObjectScale, versions prior to 4.4.0.0, contains a Deserialization of Untrusted Data vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to Remote execution.
CVE-2026-76423	10.0	CRIT				A vulnerability in the REST API of Cisco ISE and Cisco ISE-PIC could allow an unauthenticated, remote attacker to gain administrative access to an affected device. This vulnerability is due to the REST API web service being exposed with insufficient authorization checks. An attacker could exploit this vulnerability by sending a crafted HTTP request to the exposed REST API port. A successful exploit could allow ...
CVE-2026-82617	10.0	CRIT		0.003	apache:opennlp	The two built-in name-finder patterns exposed by opennlp.tools.namefind.RegexNameFinderFactory - DEFAULT_REGEX_NAME_FINDER.EMAIL and DEFAULT_REGEX_NAME_FINDER.URL - contain ambiguous nested quantifiers. An application that obtains these finders through RegexNameFinderFactory.getDefaultRegexNameFinders(...) and then applies them to untrusted text through RegexNameFinder.find(String[]) or RegexNameFinder.find(String...
CVE-2026-83099	10.0	CRIT		0.004		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Forms. While the vulnerability is in Oracle Forms, attacks may significantly impact additional products (scope chang...
CVE-2026-87230	10.0	CRIT		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. While the vulnerability is in Oracle Hyperion Financial Management, attacks may significantly impact ad...
CVE-2026-92808	10.0	CRIT				A server-side request forgery (SSRF) vulnerability exists in the UnifiedLogin service of Altium Enterprise Server. An unauthenticated network attacker can cause the server to issue outbound HTTP requests to a destination of the attacker's choosing, including internal services that are reachable only from the server itself. One such internal service exposes server configuration and credential material without a...
CVE-2026-16338	9.9	CRIT		0.006		IBM DataStage on Cloud Pak for Data 5.4.0.0 IBM DataStage could allow a remote authenticated attacker to perform an arbitrary file write due to improper validation of file paths.
CVE-2026-20234	9.9	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) engineering teams have conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-20234 are ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-20307	9.9	CRIT				A vulnerability in the web-based management interface of Cisco ISE could allow an authenticated, remote attacker to execute arbitrary commands on the underlying operating system of an affected device. To exploit this vulnerability, the attacker must have at least low-privileged administrative credentials. This vulnerability is due to insecure deserialization of a user-supplied Java byte stream. An attacker coul...
CVE-2026-20322	9.9	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Nexus Dashboard engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-20322 are related to improper access control issues that are grouped unde...
CVE-2026-20324	9.9	CRIT				A vulnerability in the sftunnel inter-device communication protocol of Cisco Secure Firewall Management Center (FMC) Software could allow an authenticated, remote attacker to execute arbitrary commands as root. This vulnerability exists because a registered sftunnel peer has incorrect permissions to write an arbitrary file to any location on the device. An attacker could exploit this vulnerability by hijacking ...
CVE-2026-20325	9.9	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Nexus Dashboard engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-20325 are related to improper neutralization of special elements used in ...
CVE-2026-20329	9.9	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Secure Adaptive Security Appliance Software, Cisco Secure Firewall Threat Defense Software and Cisco Secure Firewall Management Center Software engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabil...
CVE-2026-20330	9.9	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Secure Adaptive Security Appliance Software, Cisco Secure Firewall Threat Defense Software and Cisco Secure Firewall Management Center Software engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabil...
CVE-2026-20332	9.9	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Secure Adaptive Security Appliance Software, Cisco Secure Firewall Threat Defense Software and Cisco Secure Firewall Management Center Software engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabil...
CVE-2026-71163	9.9	CRIT		0.003		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Access Manager. While the vulnerability is in Oracle Access Manager, attacks may significantly impact additional prod...
CVE-2026-73945	9.9	CRIT		0.003		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Access Manager. While the vulnerability is in Oracle Access Manager, attacks may significantly impact additional prod...
CVE-2026-73948	9.9	CRIT		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Composer). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. While the vulnerability is in Oracle WebCenter Portal, attacks may significantly impact additional products (s...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-76669	9.9	CRIT		0.004		Privilege escalation vulnerabilities exist in the API of HPE Networking EdgeConnect SD-WAN Orchestrator. Successful exploitation could allow a remote low-privileged authenticated user to escalate their privileges to those of an administrative user, leading to complete system compromise.
CVE-2026-76670	9.9	CRIT		0.004		Privilege escalation vulnerabilities exist in the API of HPE Networking EdgeConnect SD-WAN Orchestrator. Successful exploitation could allow a remote low-privileged authenticated user to escalate their privileges to those of an administrative user, leading to complete system compromise.
CVE-2026-76672	9.9	CRIT		0.004		A vulnerability exists in the SD-WAN Orchestrator that may lead to the exposure of sensitive configuration information. An authenticated remote attacker with read-only privileges could exploit this vulnerability by sending a specially crafted request to the cache synchronization endpoint. Successful exploitation could result in the disclosure of sensitive third-party API tokens and credentials, potentially enablin...
CVE-2026-78155	9.9	CRIT		0.003	ongres:stackgres	privilege escalation in StackGres operator allows a low-privilege tenant who owns a database to gain administrator privileges
CVE-2026-82997	9.9	CRIT		0.005		Vulnerability in the Service Delivery Platform product of Oracle Fusion Middleware (component: Messaging Enabler). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via T3, IIOP to compromise Service Delivery Platform. While the vulnerability is in Service Delivery Platform, attacks may significantly impact add...
CVE-2026-82998	9.9	CRIT		0.005		Vulnerability in the Service Delivery Platform product of Oracle Fusion Middleware (component: Messaging Enabler). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via T3, IIOP to compromise Service Delivery Platform. While the vulnerability is in Service Delivery Platform, attacks may significantly impact add...
CVE-2026-82999	9.9	CRIT		0.005		Vulnerability in the Service Delivery Platform product of Oracle Fusion Middleware (component: Messaging Enabler). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Service Delivery Platform. While the vulnerability is in Service Delivery Platform, attacks may significantly impact additio...
CVE-2026-83031	9.9	CRIT		0.005		Vulnerability in the Oracle WebCenter Sites product of Oracle Fusion Middleware (component: WebCenter Sites). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Sites. While the vulnerability is in Oracle WebCenter Sites, attacks may significantly impact additional product...
CVE-2026-83038	9.9	CRIT		0.003		Vulnerability in the Oracle WebLogic Server product of Oracle Fusion Middleware (component: TopLink Integration). Supported versions that are affected are 12.2.1.4.0, 14.1.1.0.0, 14.1.2.0.0 and 15.1.1.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebLogic Server. While the vulnerability is in Oracle WebLogic Server, attacks may significant...
CVE-2026-83039	9.9	CRIT		0.005		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Composer). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. While the vulnerability is in Oracle WebCenter Portal, attacks may significantly impact additional products (s...
CVE-2026-83055	9.9	CRIT		0.004		Vulnerability in the Oracle Internet Directory product of Oracle Fusion Middleware (component: OID LDAP Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with network access via LDAP to compromise Oracle Internet Directory. While the vulnerability is in Oracle Internet Directory, attacks may significantly impact additiona...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83056	9.9	CRIT		0.005		Vulnerability in the Oracle Internet Directory product of Oracle Fusion Middleware (component: OID LDAP Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with network access via LDAP to compromise Oracle Internet Directory. While the vulnerability is in Oracle Internet Directory, attacks may significantly impact additiona...
CVE-2026-83057	9.9	CRIT		0.005		Vulnerability in the Oracle Internet Directory product of Oracle Fusion Middleware (component: OID LDAP Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with network access via LDAP to compromise Oracle Internet Directory. While the vulnerability is in Oracle Internet Directory, attacks may significantly impact additiona...
CVE-2026-83058	9.9	CRIT		0.004		Vulnerability in the Oracle Internet Directory product of Oracle Fusion Middleware (component: OID LDAP Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with network access via LDAP to compromise Oracle Internet Directory. While the vulnerability is in Oracle Internet Directory, attacks may significantly impact additiona...
CVE-2026-83282	9.9	CRIT		0.003		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). The supported version that is affected is 12.2.1.4.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. While the vulnerability is in Oracle Business Intelligence Enterprise Editi...
CVE-2026-87172	9.9	CRIT		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. While the vulnerability is in Oracle Hyperion Financial Management, attacks may significantly impact add...
CVE-2026-87719	9.9	CRIT		0.006		GitLab has remediated an issue in GitLab EE affecting all versions from 18.3 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that under certain conditions could allow an authenticated user with Duo Chat access to obtain Advanced Search instance configurations and sensitive credentials using a specially crafted GraphQL subscription argument to bypass serialization and perform server object lookup.
CVE-2023-27168	9.8	CRIT		0.013	xpand-it:write-back_manager	An arbitrary file upload vulnerability in Xpand IT Write-back Manager v2.3.1 allows attackers to execute arbitrary code via a crafted jsp file.
CVE-2025-59953	9.8	CRIT				LMDeploy is a toolkit for compressing, deploying, and serving large language models. Starting in version 0.9.1 and prior to version 0.10.2, the LMdeploy implements an rpc server (AsyncRPCServer in zmq_rpc.py) for supporting the RPC communications. In its core functionality call_and_response(), I found it will directly use the pickles.loads() to deserialize the received messages without any sanitization, hence resu...
CVE-2026-10579	9.8	CRIT		0.003		A flaw was found in Picketlink Federation SAML; the unsolicited response handler would accept forged assertions with no verification or validation, permitting an unauthed attacker to authenticate as any principal in any role. This could lead to information disclosure, access to restricted operations, or other flaws.
CVE-2026-12351	9.8	CRIT		0.009		IBM MQ 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 LTS, and 10.0.0.0 could allow a remote attacker to execute arbitrary code due to unsafe JNDI lookup processing when the IVT application is deployed.
CVE-2026-12793	9.8	CRIT		0.004		The JetFormBuilder — Dynamic Blocks Form Builder plugin for WordPress is vulnerable to Privilege Escalation in all versions up to, and including, 3.6.2. This is due to the plugin not validating that a submitted form ID belongs to a JetFormBuilder form before parsing the referenced post's content as form schema and executing an Advanced Validation server-side callback. This makes it possible for unauthenticated att...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-14349	9.8	CRIT		0.004		The TrueBooker – Appointment Booking and Scheduler System plugin for WordPress is vulnerable to authorization bypass in all versions up to, and including, 1.2.3. This is due to the plugin not properly verifying that a user is authorized to perform an action. This makes it possible for unauthenticated attackers to modify the email address of arbitrary user accounts, including administrators, which can be leveraged ...
CVE-2026-19773	9.8	CRIT		0.006		libwebsockets HTTP/2 HPACK Path Header Parsing Out-Of-Bounds Write Remote Code Execution Vulnerability. This vulnerability allows remote attackers to execute arbitrary code on affected installations of libwebsockets. Authentication is not required to exploit this vulnerability. The specific flaw exists within the parsing of HTTP/2 HPACK path header. The issue results from the lack of proper validation of user-sup...
CVE-2026-20242	9.8	CRIT				A vulnerability in the External Database Access feature of Cisco Secure Firewall Management Center (FMC) Software could allow an unauthenticated, remote attacker to execute arbitrary commands as root on an affected device. This vulnerability is due to insecure deserialization of a user-supplied Java byte stream from a host that is configured in the external database access list. An attacker could exploit t...
CVE-2026-20326	9.8	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Nexus Dashboard engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-20326 are related to missing authentication for critical function issues that ...
CVE-2026-27546	9.8	CRIT		0.01		An unauthenticated remote attacker can exploit an authentication bypass in the _account_log function to log in as an admin, even when accounts are properly configured.
CVE-2026-27565	9.8	CRIT		0.009		An unauthenticated remote attacker can upload a malicious IODD file that places and executes a shell script with root privileges. The shell script remains active even after a reboot.
CVE-2026-37152	9.8	CRIT		0.002		TOTOLINK X5000R V9.1.0cu.2415_B20250515 was discovered to contain a hardcoded password for root access.
CVE-2026-50027	9.8	CRIT		0.005		mcp-memory-service is a semantic memory layer for AI applications. Prior to 10.67.1, all HTTP routes under /api/documents/* in mcp-memory-service are served without any authentication dependency, even when the server is configured with an API key (MCP_API_KEY) or OAuth. An unauthenticated remote attacker can upload arbitrary content into the memory store (write), retrieve stored document content (read), and perman...
CVE-2026-53006	9.8	CRIT		0.004	linux:linux_kernel, redhat:enterprise_linux	In the Linux kernel, the following vulnerability has been resolved: ipv6: fix possible UAF in icmpv6_rcv() Caching saddr and daddr before pskb_pull() is problematic since skb->head can change. Remove these temporary variables: - We only access &ipv6_hdr(skb)->saddr and &ipv6_hdr(skb)->daddr when net_dbg_ratelimited() is called in the slow path. - Avoid potential future misuse after pskb_pull() call.
CVE-2026-54334	9.8	CRIT		0.004		UEFI Firmware Parser parses BIOS, Intel ME, and UEFI firmware structures including volumes, file systems, and files. Prior to 1.14, ReadCLen() in uefi_firmware/compression/Tiano/Decompress.c reads Number from GetBits(Sd, CBIT) with CBIT = 9 and can obtain 511 entries for the 510-element Sd->mCLen heap array because its loop does not enforce Index < NC. The CharC == 2 run-length path can additionally request up to ...
CVE-2026-54337	9.8	CRIT		0.004		Fireshare facilitates self-hosted media and link sharing. Prior to version 1.6.14, an argument Injection in the video upload function allows unauthenticated attacker to write/overwrite system files. Version 1.6.14 fixes the issue.
CVE-2026-57127	9.8	CRIT		0.009		PraisonAI is a multi-agent teams system. Prior to 4.6.58, recipe serve installs APIKeyAuthMiddleware or JWTAuthMiddleware when an operator selects api-key or JWT authentication, but each middleware forwards requests when PRAISONAI_API_KEY or PRAISONAI_JWT_SECRET and the corresponding recipe value are absent. Unauthenticated clients can then reach recipe execution, input, and output surfaces and may trigger connect...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-57131	9.8	CRIT		0.01		PraisonAI is a multi-agent teams system. Prior to 4.6.58, praisonai.jobs.server.create_app mounts praisonai.jobs.router.create_router under /api/v1/runs without authentication or per-job authorization. Network clients can submit attacker-controlled prompts and agent configuration, list and read jobs, stream results, and cancel or delete other jobs, exposing service credentials and connected tool capabilities to un...
CVE-2026-57148	9.8	CRIT		0.004		PraisonAI is a multi-agent teams system. Prior to 0.1.6, praisonai_platform/services/auth_service.py falls back to the public dev-secret-change-me HS256 signing key when PLATFORM_JWT_SECRET is unset, while the startup and token-issuance guards are disabled because PLATFORM_ENV also defaults to dev. An unauthenticated attacker can sign a JWT containing an attacker-chosen sub value, and AuthService._verify_token() a...
CVE-2026-57967	9.8	CRIT		0.007	apache:artemis	An unauthenticated remote attacker can craft a CORE protocol SESSION_REATTACH packet to steal an existing session and assume ongoing execution of the previously authenticated session. This issue affects Apache Artemis: from 2.50.0 through 2.56.0; Apache ActiveMQ Artemis: from 1.0.0 through 2.44.0. Users are recommended to upgrade to version 2.57.0, which fixes the issue.
CVE-2026-59243	9.8	CRIT		0.004	apache:apache-airflow-providers-fab	The FAB auth manager's Azure AD OAuth login defaulted `verify_signature=False` when decoding the ID token, so an attacker able to present a forged or unsigned (`alg:none`) ID token to the OAuth callback could bypass authentication and log in as an arbitrary user, including one holding the Admin role (CVE-347). Deployments running the FAB auth manager with the Azure AD OAuth login path under its default configurati...
CVE-2026-59318	9.8	CRIT		0.002	vmware:spring_ai	In Spring AI's tool calling support, the per-request tool list is advertised to the model as a boundary but is not fully enforced when a tool call is dispatched. Under certain conditions, a tool that was not made available to the current request could be invoked, potentially leading to privilege escalation. Affected versions: Spring AI: 2.0.0 Spring AI: 1.1.0 through 1.1.8 Spring AI: 1.0.0 through 1.0.9
CVE-2026-61560	9.8	CRIT		0.007		`@zereight/mcp-gitlab` is a Model Context Protocol server for GitLab. Prior to version 2.1.27, the SSE transport mode (`SSE=true`) exposes all MCP tools without any authentication. The `upload_markdown` tool reads arbitrary files from the server's local filesystem via an unsanitized `file_path` parameter and uploads them to a GitLab project. Combined, any unauthenticated network-reachable attacker can read `/proc/...
CVE-2026-63695	9.8	CRIT		0.005		Dell SmartFabric OS10 Software, versions prior to 10.6.1.3, contains a Session Fixation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to Session theft.
CVE-2026-65414	9.8	CRIT		0.01	apple:ipados, apple:iphone_os, apple:macos, apple:visionos, apple:watchos	An out-of-bounds write issue was addressed with improved bounds checking. This issue is fixed in iOS 26.7 and iPadOS 26.7, iOS 27 and iPadOS 27, macOS Golden Gate 27, macOS Sequoia 15.8, macOS Tahoe 26.7, tvOS 27, visionOS 27, watchOS 27. A remote attacker may be able to cause unexpected app termination or arbitrary code execution.
CVE-2026-66302	9.8	CRIT		0.005	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	External control of file name or path in Skype for Business allows an unauthorized attacker to execute code over a network.
CVE-2026-68839	9.8	CRIT		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Mass Storage Class Driver allows an unauthorized attacker to execute code over a network.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-69829	9.8	CRIT		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Shell allows an unauthorized attacker to execute code over a network.
CVE-2026-69910	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Windows Hyper-V allows an unauthorized attacker to execute code over a network.
CVE-2026-70296	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds write in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-70748	9.8	CRIT		0.003		Vulnerability in the Oracle WebLogic Server product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0, 14.1.1.0.0, 14.1.2.0.0 and 15.1.1.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via T3, IIOP to compromise Oracle WebLogic Server. Successful attacks of this vulnerability can result in takeover of Oracle WebLogic Serv...
CVE-2026-70756	9.8	CRIT		0.004		Vulnerability in the Oracle WebLogic Server product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0, 14.1.1.0.0, 14.1.2.0.0 and 15.1.1.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via T3, IIOP to compromise Oracle WebLogic Server. Successful attacks of this vulnerability can result in takeover of Oracle WebLogic Serv...
CVE-2026-70757	9.8	CRIT		0.003		Vulnerability in the Oracle WebLogic Server product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0, 14.1.1.0.0, 14.1.2.0.0 and 15.1.1.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via T3, IIOP to compromise Oracle WebLogic Server. Successful attacks of this vulnerability can result in takeover of Oracle WebLogic Serv...
CVE-2026-70913	9.8	CRIT		0.003		Vulnerability in the Oracle Identity Manager product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Identity Manager. Successful attacks of this vulnerability can result in takeover of Oracle Identity Manager. CVSS 3.1 Base Score 9...
CVE-2026-73849	9.8	CRIT		0.005		Emlog is an open source website building system. In 2.6.26 and earlier, install.php accepts action=reinstall without authentication and deliberately skips the already-installed check because the guard runs only when \$act != 'reinstall'. A remote attacker can submit hostname, dbuser, dbpasswd, dbname, dbprefix, username, password, and email values to cause file_put_contents('config.php', \$config) to overwrite the c...
CVE-2026-73940	9.8	CRIT		0.004		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via T3, IIOP to compromise Oracle Access Manager. Successful attacks of this vulnerability can result in takeover of Oracle Access Manager. CVSS 3...
CVE-2026-73947	9.8	CRIT		0.003		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Access Manager. Successful attacks of this vulnerability can result in takeover of Oracle Access Manager. CVSS 3.1 B...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-73950	9.8	CRIT		0.004		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Access Manager. Successful attacks of this vulnerability can result in takeover of Oracle Access Manager. CVSS 3.1 B...
CVE-2026-73953	9.8	CRIT		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Portlet Services). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Portal. CVSS 3.1 ...
CVE-2026-73956	9.8	CRIT		0.005		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Composer). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Portal. CVSS 3.1 Base Sco...
CVE-2026-73961	9.8	CRIT		0.005		Vulnerability in the Oracle JDeveloper product of Oracle Fusion Middleware (component: ADF Faces). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle JDeveloper. Successful attacks of this vulnerability can result in takeover of Oracle JDeveloper. CVSS 3.1 Base Score 9.8 (Confident...
CVE-2026-73963	9.8	CRIT		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Portlet Services). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Portal. CVSS 3.1 ...
CVE-2026-76673	9.8	CRIT		0.005		Vulnerabilities have been identified in the API of EdgeConnect SD-WAN Orchestrator that could potentially allow an unauthenticated remote actor to circumvent existing authentication controls. Successful exploitation could allow an attacker to gain administrative privileges leading to complete compromise of the EdgeConnect SD-WAN Orchestrator host.
CVE-2026-76674	9.8	CRIT		0.011		Buffer overflow vulnerabilities exist in the underlying operating system of HPE Networking EdgeConnect SD-WAN Gateways that could allow an unauthenticated remote attacker to execute arbitrary code. Successful exploitation could allow an attacker to execute arbitrary commands on the underlying operating system leading to complete system compromise.
CVE-2026-78573	9.8	CRIT		0.004	ibm:contextforge	IBM ContextForge MCP Gateway 1.0.0 through 1.0.7 could allow a remote attacker to gain administrative access due to the use of default credentials.
CVE-2026-79724	9.8	CRIT		0.005	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow a remote attacker to execute arbitrary OS commands due to improper neutralization of special elements used in an OS command.
CVE-2026-81204	9.8	CRIT		0.006	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow a remote attacker to execute arbitrary code due to code injection during graph construction.
CVE-2026-81467	9.8	CRIT		0.038	dell:latitude_3330, dell:latitude_3420, dell:latitude_3440, dell:latitude_3450, dell:latitude_5440, dell:latitude_5450,	Dell ThinOS 10, versions prior to 2605_10. 2616, contains an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to Command execution.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-82994	9.8	CRIT		0.005		Vulnerability in the Oracle Platform Security for Java product of Oracle Fusion Middleware (component: Centralized Thirdparty Jars). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via LDAP to compromise Oracle Platform Security for Java. Successful attacks of this vulnerability can result in takeover of Ora...
CVE-2026-82995	9.8	CRIT		0.005		Vulnerability in the Oracle Platform Security for Java product of Oracle Fusion Middleware (component: Centralized Thirdparty Jars). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via SOAP to compromise Oracle Platform Security for Java. Successful attacks of this vulnerability can result in takeover of Ora...
CVE-2026-83000	9.8	CRIT		0.005		Vulnerability in the Service Delivery Platform product of Oracle Fusion Middleware (component: Messaging Enabler). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Service Delivery Platform. Successful attacks of this vulnerability can result in takeover of Service Delivery Platform. CV...
CVE-2026-83035	9.8	CRIT		0.005		Vulnerability in the Oracle WebCenter Sites product of Oracle Fusion Middleware (component: WebCenter Sites). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Sites. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Sites. CVSS 3.1 Base...
CVE-2026-83036	9.8	CRIT		0.005		Vulnerability in the Oracle WebCenter Sites product of Oracle Fusion Middleware (component: WebCenter Sites). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Sites. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Sites. CVSS 3.1 Base...
CVE-2026-83037	9.8	CRIT		0.005		Vulnerability in the Oracle WebCenter Sites product of Oracle Fusion Middleware (component: WebCenter Sites). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Sites. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Sites. CVSS 3.1 Base...
CVE-2026-83042	9.8	CRIT		0.005		Vulnerability in the Oracle Identity Manager product of Oracle Fusion Middleware (component: OIM Legacy UI). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Identity Manager. Successful attacks of this vulnerability can result in takeover of Oracle Identity Manager. CVSS 3.1 Bas...
CVE-2026-83054	9.8	CRIT		0.004		Vulnerability in the Oracle Internet Directory product of Oracle Fusion Middleware (component: OID LDAP Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via LDAP to compromise Oracle Internet Directory. Successful attacks of this vulnerability can result in takeover of Oracle Internet Directory. CVSS...
CVE-2026-83060	9.8	CRIT		0.005		Vulnerability in the Oracle Internet Directory product of Oracle Fusion Middleware (component: OID LDAP Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via LDAP to compromise Oracle Internet Directory. Successful attacks of this vulnerability can result in takeover of Oracle Internet Directory. CVSS...
CVE-2026-83061	9.8	CRIT		0.005		Vulnerability in the Oracle Internet Directory product of Oracle Fusion Middleware (component: OID LDAP Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via LDAP to compromise Oracle Internet Directory. Successful attacks of this vulnerability can result in takeover of Oracle Internet Directory. CVSS...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83062	9.8	CRIT		0.005		Vulnerability in the Oracle Internet Directory product of Oracle Fusion Middleware (component: OID LDAP Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via LDAP to compromise Oracle Internet Directory. Successful attacks of this vulnerability can result in takeover of Oracle Internet Directory. CVSS...
CVE-2026-83066	9.8	CRIT		0.005		Vulnerability in the Oracle Internet Directory product of Oracle Fusion Middleware (component: OID LDAP Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via T3, IIOP to compromise Oracle Internet Directory. Successful attacks of this vulnerability can result in takeover of Oracle Internet Directory. ...
CVE-2026-83094	9.8	CRIT		0.005		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Forms. Successful attacks of this vulnerability can result in takeover of Oracle Forms. CVSS 3.1 Base Score 9.8 (Con...
CVE-2026-83095	9.8	CRIT		0.005		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Forms. Successful attacks of this vulnerability can result in takeover of Oracle Forms. CVSS 3.1 Base Score 9.8 (Con...
CVE-2026-83098	9.8	CRIT		0.004		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Forms. Successful attacks of this vulnerability can result in takeover of Oracle Forms. CVSS 3.1 Base Score 9.8 (Con...
CVE-2026-83100	9.8	CRIT		0.005		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Forms. Successful attacks of this vulnerability can result in takeover of Oracle Forms. CVSS 3.1 Base Score 9.8 (Con...
CVE-2026-83108	9.8	CRIT		0.004		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Forms. Successful attacks of this vulnerability can result in takeover of Oracle Forms. CVSS 3.1 Base Score 9.8 (Con...
CVE-2026-83151	9.8	CRIT		0.004		Vulnerability in the Service Delivery Platform product of Oracle Fusion Middleware (component: Messaging Enabler). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via SOAP to compromise Service Delivery Platform. Successful attacks of this vulnerability can result in takeover of Service Delivery Platform. CV...
CVE-2026-83232	9.8	CRIT		0.003		Vulnerability in the Oracle Data Integrator product of Oracle Fusion Middleware (component: Console / Repository Explorer). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Data Integrator. Successful attacks of this vulnerability can result in takeover of Oracle Data Integrator....
CVE-2026-83261	9.8	CRIT		0.004		Vulnerability in the Oracle Product Lifecycle Analytics product of Oracle Supply Chain (component: Core). The supported version that is affected is 3.6.1. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Product Lifecycle Analytics. Successful attacks of this vulnerability can result in takeover of Oracle Product Lifecycle Analytics. CVSS 3.1 Bas...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83269	9.8	CRIT		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle BI Publisher. Successful attacks of this vulnerability can result in takeover of Oracle BI Publisher. CVSS 3.1 Base...
CVE-2026-83283	9.8	CRIT		0.004		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). The supported version that is affected is 12.2.1.4.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can result in takeover of Oracle ...
CVE-2026-83327	9.8	CRIT		0.005		Vulnerability in the Oracle Applications Framework product of Oracle E-Business Suite (component: Personalization). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via SOAP to compromise Oracle Applications Framework. Successful attacks of this vulnerability can result in takeover of Oracle Applications Framework. CVSS ...
CVE-2026-83339	9.8	CRIT		0.005		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Enterprise Capture. Successful attacks of this vulnerability can result in takeover of Oracle WebCen...
CVE-2026-83355	9.8	CRIT		0.004		Vulnerability in the Oracle Enterprise Manager for Fusion Middleware product of Oracle Enterprise Manager (component: Metrics). Supported versions that are affected are 13.5 and 24.1. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Enterprise Manager for Fusion Middleware. Successful attacks of this vulnerability can result in takeover of Oracle...
CVE-2026-83452	9.8	CRIT		0.005		Vulnerability in the Oracle Document Management and Collaboration product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Document Management and Collaboration. Successful attacks of this vulnerability can result in takeover of Or...
CVE-2026-83462	9.8	CRIT		0.005		Vulnerability in the Oracle Mobile Application Server product of Oracle E-Business Suite (component: MWA Terminal Server). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Mobile Application Server. Successful attacks of this vulnerability can result in takeover of Oracle Mobile Application S...
CVE-2026-84520	9.8	CRIT		0.001	apple:macos	A buffer overflow was addressed with improved size validation. This issue is fixed in macOS Golden Gate 27. A local attacker may be able to cause unexpected system termination or corrupt kernel memory.
CVE-2026-84561	9.8	CRIT		0.002	apple:ipados, apple:iphone_os, apple:macos, apple:tvos, apple:visionos, apple:watchos	A double free issue was addressed with improved memory management. This issue is fixed in iOS 26.7 and iPadOS 26.7, iOS 27 and iPadOS 27, macOS Golden Gate 27, macOS Sequoia 15.8, macOS Tahoe 26.7, tvOS 27, visionOS 27, watchOS 27. An app may be able to cause unexpected system termination or corrupt kernel memory.
CVE-2026-84609	9.8	CRIT		0.002		A permissions issue was addressed with improved path validation. This issue is fixed in iOS 27 and iPadOS 27, macOS Golden Gate 27, macOS Sequoia 15.8, macOS Tahoe 26.7, tvOS 27, visionOS 27, watchOS 27. An app may be able to modify protected system files.
CVE-2026-87184	9.8	CRIT		0.005		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via SQL to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management....

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87188	9.8	CRIT		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management...
CVE-2026-88617	9.8	CRIT		0.002		SmartAdmin v3.30.0 contains an authorization flaw in the configuration query endpoint. This allows a remote attacker to escalate privileges.
CVE-2026-89778	9.8	CRIT		0.002		In the Linux kernel, the following vulnerability has been resolved: isofs: fix out-of-bounds page array access on empty zisofs block zisofs_uncompress_block()'s empty-block fast path returns pcount << PAGE_SHIFT, ignoring the incoming poffset, unlike the decompression path which returns bytes produced relative to poffset. zisofs_fill_pages() uses that return to advance its page cursor, so when the zisofs block s...
CVE-2026-89783	9.8	CRIT		0.002		In the Linux kernel, the following vulnerability has been resolved: xfrm6: fix out-of-bounds write in xfrm6_input_addr() when secpath is full The depth check in xfrm6_input_addr() is off by one: if (1 + sp->len == XFRM_MAX_DEPTH) goto drop; ... sp->xvec[sp->len++] = x; xfrm_input() can leave sp->len == XFRM_MAX_DEPTH, and the transport-mode receive path re-enters IPv6 input via xfrm_trans_reinj...
CVE-2026-89788	9.8	CRIT		0.002		In the Linux kernel, the following vulnerability has been resolved: ksmbd: fix tree connection use-after-free in smb2_tree_connect() ksmbd_tree_conn_connect() publishes a new tree connection in sess->tree_conns with a single reference and returns its pointer to smb2_tree_connect(). The handler continues to initialize the object and build the response after publication. A concurrent session logoff can erase the c...
CVE-2026-89847	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Avoid double completion in async IOCB timeout qla2x00_async_iocb_timeout() tries to abort a timed-out async IOCB. When qla24xx_async_abort_cmd() fails, both the SRB_LOGIN_CMD path and the SRB_CTRL_VP/default path scan outstanding_cmds[] for the SRB and then call sp->done(sp, QLA_FUNCTION_TIMEOUT) unconditionally, without checking ...
CVE-2026-89857	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Hold qpair lock when sending NVMe LS reject qla_nvme_ls_reject_iocb() allocates from and advances the request ring through __qla2x00_alloc_iochs() (which assumes the hardware_lock is held) and qla2x00_start_iochs() (which advances the ring and rings the request-in doorbell), but takes no lock itself. Two of its callers invoke it w...
CVE-2026-89969	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: nvmet-tcp: fix out-of-bounds write when receiving an over-long PDU nvmet_tcp_try_recv_pdu() reads a PDU header into the fixed 128-byte queue->pdu union, then computes the remaining payload length as queue->left = hdr->hlen - queue->offset + hdgst; and reads that many more bytes into &queue->pdu + queue->offset, without ever bounding the resul...
CVE-2026-89970	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: nvmet-auth: Synchronize timeout work during SQ teardown nvmet_auth_sq_free() cancels auth_expired_work with cancel_delayed_work(). If the work has already started, cancellation does not wait for the callback. Transport teardown can consequently free or reuse the queue containing struct nvmet_sq while nvmet_auth_expired_work() still accesses that...
CVE-2026-89972	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: nvme: add missing SRCU grace period in error path nvme_alloc_ns() error path at out_unlink_ns removes ns from the namespace head siblings list with list_del_rcu(&ns->siblings) but does not wait for SRCU readers before freeing the namespace struct. Multipath code iterates the head->list under srcu_read_lock() in nvme_find_path() and nvme_mpath_re...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89990	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: ceph: lock mutex in ceph_mds_check_access() MDS session OPEN handling replaces mdsc->s_cap_auths under mdsc->mutex, freeing the previous array and its strings. ceph_mds_check_access() traverses this array without holding the mutex. A concurrent session reopen can therefore free the array while it is being inspected, resulting in a use-after-fr...
CVE-2026-90012	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: spi: Fix DMA mapping ownership on partial map failure If RX mapping fails after TX mapping succeeds, __spi_map_msg() unmaps TX but leaves tx_sg_mapped set. If TX mapping fails on a later transfer, mappings created for earlier transfers remain active. In both cases, cur_{tx,rx}_dma_dev have not yet been updated because they are assigned only aft...
CVE-2026-90036	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during blocked-lock reaping A bare lock owner -- its only remaining reference a blocked lock on nn->blocked_locks_lru -- holds a raw pointer to its nfs4_client but no reference keeping the client alive. When the per-net laundromat reaps such a lock, freeing the nbl drops the owner reference held through flc_ow...
CVE-2026-90037	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during close_lru reaping An nfs4_openowner left on nn->close_lru after its final CLOSE keeps its last closed stateid in oo_last_closed_stid, holding only a raw pointer to its nfs4_client. The laundromat reaps timed-out entries, drops nn->client_lock, and calls nfs4_put_stid(), which dereferences the client thr...
CVE-2026-90038	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during export state revocation nfsd4_revoke_export_states() has the same use-after-free as nfsd4_revoke_states(): it drops nn->client_lock across revoke_one_stid() and the following read of clp->cl_minorversion, but the stateid reference it holds does not pin the client. A teardown racing the dropped lock can...
CVE-2026-90042	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: ceph: properly decrypt filenames in vmlalloc() buffers The fscrypt subsystem uses the scatterlist crypto API, inheriting its requirement that any buffers are in the linear mapping region. However, the messenger client uses kmmalloc() to create buffers for messages, which will occasionally place those buffers in the vmlalloc() region when physical ...
CVE-2026-90048	9.8	CRIT				In the Linux kernel, the following vulnerability has been resolved: fs/ntfs3: fix slab-out-of-bounds write in ni_create_attr_list() ni_create_attr_list() allocates a fixed buffer of al_aligned(record_size) (== record_size) bytes and then walks every attribute of the primary MFT record, writing one ATTR_LIST_ENTRY per attribute and advancing the cursor by le_size(name_len), with no check against the end of the bu...
CVE-2026-91843	9.8	CRIT				A stack overflow during the unauthenticated login process may allow an attacker to run arbitrary code remotely with root privileges.
CVE-2026-12944	9.6	CRIT		0.002		IBM Langflow OSS 1.0.0 through 1.10.0 can allow attackers to execute arbitrary Python code with root privileges (UID=0) on the Langflow server by submitting components containing socket or urllib imports. This enables: (1) AWS credential theft via IMDSv1 SSRF with full IAM role permissions, (2) arbitrary file exfiltration from the container filesystem, and (3) lateral movement to internal services (PostgreSQL, Red...
CVE-2026-20331	9.6	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Secure Adaptive Security Appliance Software, Cisco Secure Firewall Threat Defense Software and Cisco Secure Firewall Management Center Software engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabil...
CVE-2026-61568	9.6	CRIT		0.003		`@zereight/mcp-gitlab` is a Model Context Protocol server for GitLab. Versions prior to 2.1.30 expose the Streamable HTTP MCP endpoint without an effective Host or Origin allowlist. A malicious web page can use DNS rebinding to route browser requests to a victim's local MCP listener while preserving an attacker-controlled `Host` and `Origin`. The server accepts those headers and reaches the MCP initialization path...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-73962	9.6	CRIT		0.003		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTPS to compromise Oracle Access Manager. While the vulnerability is in Oracle Access Manager, attacks may significantly impact additional pro...
CVE-2026-82107	9.6	CRIT		0.003	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to obtain sensitive information and bypass security restrictions due to improper authentication.
CVE-2026-83029	9.6	CRIT		0.004		Vulnerability in the Oracle Managed File Transfer product of Oracle Fusion Middleware (component: MFT Runtime Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Managed File Transfer. While the vulnerability is in Oracle Managed File Transfer, attacks may significantly impa...
CVE-2026-83040	9.6	CRIT		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Portlet Services). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via SOAP to compromise Oracle WebCenter Portal. Successful attacks require human interaction from a person other than the attacker and while the vuln...
CVE-2026-83043	9.6	CRIT		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Composer). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks require human interaction from a person other than the attacker and while the vulnerabilit...
CVE-2026-87186	9.6	CRIT		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. W...
CVE-2026-15640	9.5	CRIT		0.003		Under certain conditions a valid SAML IdP response may be used to impersonate another Secret Server user.
CVE-2026-73453	9.5	CRIT		0.007		An unauthenticated P4Runtime (Programming Protocol-Independent Packet Processors Runtime) client can achieve arbitrary code execution under certain conditions on affected platforms running Arista EOS configured with P4Runtime. P4Runtime is disabled by default in Arista EOS. By crafting a malicious packet during the initiation of a P4Runtime session, an attacker can obtain complete administrative control over the c...
CVE-2026-77411	9.5	CRIT				RabbitMQ amqp091-go is a Go AMQP 0.9.1 client. Prior to 1.13.0, readLongstr in read.go returns an empty string and a nil error when a declared AMQP longstr length exceeds 0x7FFFFFFF instead of returning ErrSyntax. The function leaves the declared field bytes unread, while readTable treats the operation as successful and continues parsing from the wrong offset. A malicious or compromised broker can provide an overs...
CVE-2026-78225	9.5	CRIT		0.004		A hardcoded cryptographic server key vulnerability exists in the deployer-ng Update Controller component of Wartsilä FOS-Onboard.
CVE-2026-43114	9.4	CRIT		0.004	linux:linux_kernel	In the Linux kernel, the following vulnerability has been resolved: netfilter: nft_set_pipapo_avx2: don't return non-matching entry on expiry New test case fails unexpectedly when avx2 matching functions are used. The test first loads a ranomly generated pipapo set with 'ipv4 . port' key, i.e. nft -f foo. This works. Then, it reloads the set after a flush: (echo flush set t s; cat foo) nft -f - This is ex...
CVE-2026-58146	9.4	CRIT				WNC T-Mobile 5G Box IDU router is vulnerable to OS command injection vulnerability. The vulnerability exists within the /cgi-bin/portal.cgi endpoint, specifically through the cli_cookie POST parameter. The cli_cookie parameter value is directly concatenated into a find command string without proper sanitization. This allows a remote, unauthenticated attacker to inject and execute arbitrary shell commands as root o...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-66887	9.4	CRIT		0.002		The affected products are missing authorization on state-changing CGI's and session checks are not performed.
CVE-2026-66890	9.4	CRIT		0.002		The affected products use hard-coded credentials, which could allow remote access to files with root privileges where FTP is reachable.
CVE-2026-68491	9.4	CRIT		0.003		An insufficient check allowed for the overwrite of arbitrary files via a symlink.
CVE-2026-73447	9.4	CRIT		0.008		A privileged attacker can exploit certain operation to execute arbitrary commands with root privileges, leading to full device compromise. An authenticated user can exploit gRPC Network Security Interface (gNSI) Certz service on Arista EOS-based products to escalate privileges and execute arbitrary OS commands via a crafted Certz Rotate request. The Bootz service is also affected.
CVE-2026-73461	9.4	CRIT		0.003		On affected EOS platforms with AAA-based gRPC authorization enabled for OpenConfig, gRPC requests of an authenticated user to OpenConfig may use the wrong privilege level, resulting in an authorization using the wrong AAA method list. This does not impact non-gRPC OpenConfig requests such as NETCONF.
CVE-2026-77179	9.4	CRIT		0.002		On macOS, the virtio-fs host server used by Docker Sandboxes improperly follows symlinks when reopening an unlinked file from a stored path. A malicious guest can replace a parent directory with a symlink, escape the shared workspace, and read or modify arbitrary host files as the VMM user, potentially achieving host code execution.
CVE-2026-77405	9.4	CRIT				RabbitMQ amqp091-go is a Go AMQP 0.9.1 client. Prior to 1.13.0, tlsConfigFromURI in uri.go creates tls.Config values without setting MinVersion to tls.VersionTLS12. Builds using a Go runtime whose default permits TLS 1.0 or TLS 1.1 can therefore negotiate an obsolete protocol version when connecting through an amqps URI. A network attacker able to influence TLS negotiation with such a legacy build may weaken trans...
CVE-2026-81046	9.4	CRIT		0.004	dell:latitude_3330, dell:latitude_3420, dell:latitude_3440, dell:latitude_3450, dell:latitude_5440, dell:latitude_5450,	Dell ThinOS 10, versions prior to 2605_10.2616, contain a Protection Mechanism Failure vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to Arbitrary Code Execution within the application context.
CVE-2026-85192	9.4	CRIT		0.005		Joomla Extension - regularlabs.com - Authenticated, privileged remote code execution in Conditional Content extension for Joomla < 8.0.0 - Conditional Content Pro accepts inline PHP Condition Rules in article syntax. In affected versions, the PHP is passed to the Conditions evaluator without checking who authored the article. Joomla's normal Author text filter preserves the syntax, so publishing the article causes...
CVE-2026-90680	9.4	CRIT		0.005		A security flaw has been discovered in D-Link DIR-823G 1.0.2B05_20181207. The impacted element is the function strcpy of the file /HNAP1/SetStaticRouteSettings of the component HNAP1. The manipulation of the argument PAddress/SubnetMask/Gateway results in stack-based buffer overflow. The attack can be launched remotely.
CVE-2026-90937	9.4	CRIT		0.003		froxlor versions before 2.2.5 fail to validate newline characters in subdomain redirect URLs, allowing authenticated customers to inject arbitrary nginx or Apache configuration directives. Attackers can supply URLs containing literal newlines that are written verbatim into vhost config files during cron rebuild, enabling web server configuration corruption, denial of service, or hijacking of HTTP responses across ...
CVE-2022-4995	9.3	CRIT		0.007		Weaver (Fanwei) E-cology 9.0 versions prior to 10.52 contain a file upload vulnerability that allows a remote, unauthenticated attacker to upload arbitrary files, including JSP webshells, by submitting a multipart/form-data POST request to /workrelate/plan/util/uploaderOperate.jsp with arbitrary secId and planDetailId field values. Successful exploitation results in remote code execution under the privileges of th...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-15639	9.3	CRIT		0.004		An attacker can craft a malicious link that, if used by a legitimate user, may cause the user's browser to run JavaScript supplied by the attacker.
CVE-2026-25550	9.3	CRIT		0.009		Seagull Software BarTender 2010, 2016, and 2019 contain an unauthenticated remote code execution vulnerability in the .NET Remoting service exposed on TCP port 7375 via BtSystem.Service.exe. The service registers an unauthenticated singleton endpoint — BarTenderSystem for BarTender 2016 <= R9, and DataServiceSingleton for BarTender 2019 <= R10 — configured with BinaryServerFormatterSinkProvider and TypeFilterLevel...
CVE-2026-40855	9.3	CRIT				WNC T-Mobile 5G Box IDU router is vulnerable to a command injection. The vulnerability exists in the ping functionality within the /cgi-bin/portal.cgi endpoint, specifically affecting the ping_ip, ping_size, and ping_times POST parameters. The root cause is the failure to verify and sanitize user-supplied input before incorporating it into a system command. This allows an authenticated attacker to execute arbitrar...
CVE-2026-45052	9.3	CRIT		0.003		Open Access Management (OpenAM) is an access management solution. Prior to 16.1.1, the Liberty Web Services SOAP receiver permits unauthenticated remote requests to write persistent entries through SOAPReceiver and DiscoveryService into a user's Liberty Discovery store and the shared root-realm Discovery branch. The server-side handlers bypass requester LDAP and identity ACLs, and the global path uses an internal ...
CVE-2026-46316	9.3	CRIT		0.004	linux:linux_kernel	In the Linux kernel, the following vulnerability has been resolved: KVM: arm64: vgic-its: Drop the translation cache reference only for the erased entry vgic_its_invalidate_cache() walks the per-ITS translation cache with xa_for_each() and drops the cache's reference on each entry with vgic_put_irq(). It puts the iterated pointer, though, rather than the value returned by xa_erase(). The function is called from...
CVE-2026-53975	9.3	CRIT		0.011		OpenChamber 1.11.7 contains an unauthenticated remote code execution vulnerability that allows remote attackers to execute arbitrary shell commands by sending crafted POST requests to the /api/fs/exec endpoint, which passes commands verbatim to Node.js spawn() without any allowlist, blocklist, or argument validation. The authentication middleware becomes a no-op when UI_PASSWORD is not configured, matching the def...
CVE-2026-53976	9.3	CRIT		0.019		OpenChamber 1.11.7 contains a path traversal vulnerability in the file-serving endpoints /api/fs/read, /api/fs/stat, and /api/fs/raw that allows unauthenticated remote attackers to read arbitrary files by supplying the allowOutsideWorkspace=true query parameter alongside an absolute path, bypassing the workspace boundary check in resolveReadPathFromContext. Attackers can exploit the vacuuous isPathWithinRoot guard ...
CVE-2026-58147	9.3	CRIT				WNC T-Mobile 5G Box IDU router contains an OS command injection vulnerability in the portal.cgi component's password change functionality. The application improperly neutralizes special elements in the http_passwd_hidden and http_passwdConfirm_hidden parameters, allowing an authenticated attacker to execute arbitrary commands on the underlying operating system with root privileges.This issue has been fixed in firm...
CVE-2026-69110	9.3	CRIT		0.005		OpenCode Studio before 2.4.4 contains a missing authentication vulnerability that allows unauthenticated remote attackers to read arbitrary files within the temp and static/music directories by directly accessing the GET /api/tmp/:tmpFile and GET /api/music/:fileName endpoints. Attackers can retrieve intermediate audio, video artifacts, and subtitles belonging to other users' jobs, and additionally delete any vide...
CVE-2026-73172	9.3	CRIT				Nozomi Networks Labs identified a CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability in the edgserver management service of Advantech EKI-1242EIMS in firmware version V1.06.01 that allows a remote unauthenticated attacker to execute arbitrary OS commands as root via crafted requests to TCP port 5058.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-73807	9.3	CRIT		0.007		The mySCADA myPRO Manager command API does not properly enforce authentication for privileged functions. An unauthenticated attacker with network access to the affected API could exploit this vulnerability to access privileged management functions.
CVE-2026-73957	9.3	CRIT		0.003		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Portlet Services). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks require human interaction from a person other than the attacker and while the vuln...
CVE-2026-81855	9.3	CRIT		0.005		A hardcoded cryptographic client authentication key vulnerability exists in the robot testing framework component of Wärtsilä FOS-Onboard.
CVE-2026-83027	9.3	CRIT		0.003		Vulnerability in the Oracle Identity Manager Connector product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Identity Manager Connector executes to compromise Oracle Identity Manager Connec...
CVE-2026-85595	9.3	CRIT		0.004	traefik:traefik	Traefik versions before v2.11.55 and versions v3.0.0 through v3.7.10 contain an authentication bypass vulnerability in the digestAuth middleware where unknown usernames receive an empty secret instead of rejection. Attackers can compute a valid digest response using the empty secret and arbitrary credentials to bypass authentication on any digestAuth-protected route without a valid username or password.
CVE-2026-89082	9.3	CRIT				HP has identified potential security vulnerabilities in the HP Advance software that may enable elevation of privilege, remote code execution, or arbitrary file write under certain conditions, impacting the HP Advance server hosting the software.
CVE-2026-89083	9.3	CRIT				HP has identified potential security vulnerabilities in the HP Advance software that may enable elevation of privilege, remote code execution, or arbitrary file write under certain conditions, impacting the HP Advance server hosting the software.
CVE-2026-89775	9.3	CRIT		0.002		In the Linux kernel, the following vulnerability has been resolved: KVM: arm64: Handle negative S1 walk levels in VNCR TLB size evaluation Computing the effects of a TLB invalidation involves looking at the size of the mapping cached by the TLB. For S1 mappings such as VNCR, this is deducted from the combination of the base granule size and the mapping level. However, this implies that the S1 MMU is *on*. When ...
CVE-2026-89914	9.3	CRIT				In the Linux kernel, the following vulnerability has been resolved: KVM: arm64: Sign-extend VA for range-based TLBI invalidation When the decode_range_tlb() helper was moved to be used for S1 TLBIs, the required sign extension was omitted. Add it. As a result, special care must be taken to not overflow PA bits when this is used for S2 invalidation.
CVE-2026-89915	9.3	CRIT				In the Linux kernel, the following vulnerability has been resolved: KVM: arm64: Remove VM-wide VNCR mapping counter The global VNCR mapping counter is used to decide whether an L1 provided VNCR page is mapped in L0 on any CPU at the point of dealing with a TLB invalidation. It is incremented when a mapping is made in the fixmap, and decremented when unmapped. As it turns out, this tracking has several flaws: -...
CVE-2026-89916	9.3	CRIT				In the Linux kernel, the following vulnerability has been resolved: KVM: arm64: Make VNCR invalidation participate in MMU invalidation retry A VNCR TLB invalidation can occur on one vcpu while another vcpu is faulting in this same page. Without correctly handling this, we can end up with the following scenario: - vcpu A walks the PTs to translate VNCR - before vcpu A is able to grab the MMU lock to insert the T...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89918	9.3	CRIT				In the Linux kernel, the following vulnerability has been resolved: KVM: arm64: Correctly handle end of VA space TLBI invalidation Our TLB invalidation by VA code is based on comparing two ranges, one defined by the TLB, and one defined by the TLBI instruction. Each range is defined by a start and a size. However, the way the comparison is done doesn't account for address rollover, as it compares an address wit...
CVE-2026-89930	9.3	CRIT				In the Linux kernel, the following vulnerability has been resolved: KVM: nVMX: Service local TLB flushes on failed nested VM-Enter KVM services local TLB flushes on "full" nested VM-Exits (through <code>__nested_vmx_vmexit()</code>), but not if a nested VM-Enter fails (e.g. due to failed VMCS checks in <code>nested_vmx_enter_non_root_mode()</code>). However, it is possible that KVM had queued TLB flushes that need to be performed, even ...
CVE-2026-90049	9.3	CRIT				In the Linux kernel, the following vulnerability has been resolved: net: skbuff: don't <code>skb_tx_error()</code> the source <code>skb</code> in <code>skb_zerocopy()</code> <code>skb_zerocopy()</code> copies frags from <code>@from</code> into <code>@to</code> . On an <code>skb_orphan_frags()</code> failure it calls <code>skb_tx_error(@from)</code> , a destructive operation on the source <code>skb</code> the copy helper does not own. That completes <code>@from</code> 's zerocopy uarg and clears <code>SKBFL_ALL_ZEROCOPY</code> , including the <code>SKBFL_SHARED_F...</code>
CVE-2026-90945	9.3	CRIT		0.005		Crawlab through 0.6.3 uses a hard-coded HMAC-SHA256 secret for JWT token signing that cannot be overridden via configuration or environment variables. Unauthenticated attackers can forge valid administrator tokens to access administrative APIs and execute code on worker nodes.
CVE-2026-90961	9.3	CRIT		0.005		The <code>LdapAuth</code> and <code>LinOTPAuth</code> authentication plugins in MISP contain an authentication bypass vulnerability. Both <code>LdapAuthenticate</code> and <code>LinOTPAAuthenticate</code> replace CakePHP's <code>FormAuthenticate</code> class but fail to replicate its <code>_checkFields()</code> input validation guard. As a result, the email and password fields extracted from the login request are passed to downstream authentication logic without verifying that they are non-e...
CVE-2026-91104	9.3	CRIT				HP has identified and remediated multiple externally reported vulnerabilities within HPLIP. The findings affect several software components that could potentially enable remote code execution, privilege escalation, denial of service, information disclosure, or unauthorized file modification under certain conditions.
CVE-2026-91106	9.3	CRIT				HP has identified and remediated multiple externally reported vulnerabilities within HPLIP. The findings affect several software components that could potentially enable remote code execution, privilege escalation, denial of service, information disclosure, or unauthorized file modification under certain conditions.
CVE-2026-91939	9.3	CRIT		0.006		Cotonti 1.0.0 Comments plugin passes the <code>ci GET</code> parameter to <code>unserialize()</code> without <code>allowed_classes</code> restriction, allowing unauthenticated attackers to instantiate arbitrary PHP classes with attacker-controlled properties. Attackers can exploit PHP object injection through crafted serialized payloads to trigger gadget chains and achieve database manipulation or code execution.
CVE-2026-92717	9.3	CRIT				Covenant through 0.6 registers the CovenantHub SignalR hub without an <code>Authorize</code> attribute, allowing unauthenticated callers to invoke <code>CreateHttpListener</code> and receive a signed JWT token. Attackers can use the obtained token to authenticate against the entire operator API and access grunts, credentials, binaries, events, and the operator roster.
CVE-2026-92720	9.3	CRIT				Kubero through 3.1.1 fails to apply authentication guards to the notifications API endpoints, allowing unauthenticated attackers to read webhook secrets and service URLs. Attackers can retrieve stored credentials and register malicious webhooks to intercept pipeline events or suppress alerting by deleting existing configurations.
CVE-2026-92787	9.3	CRIT				Feast through 0.66.0 fails to verify JWT token signatures before establishing user identity, allowing attackers to bypass all role-based access control by presenting an unverified token with a hardcoded claim value. Attackers can obtain trusted internal identity and gain unchecked read and write access to all entities, feature views, data sources, and permission policies on the server.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-92805	9.3	CRIT				UVdesk Community Skeleton through 1.1.8 fails to authenticate or validate installation state on wizard endpoints in ConfigureHelpdesk controller actions. Unauthenticated attackers can repoint the database and create super administrator accounts by submitting crafted requests to wizard endpoints, gaining full control of the instance.
CVE-2026-69204	9.2	CRIT		0.003		Http4s is a Scala interface for HTTP services. Prior to 0.23.35 and 1.0.0-M47, Ember HTTP/1.1 does not reject messages containing both Transfer-Encoding and Content-Length, so an intermediary and Ember can select different body framing rules. When ember-server is behind a keep-alive intermediary that forwards both headers and frames by Content-Length, an unauthenticated attacker can smuggle a second request, bypas...
CVE-2026-73456	9.2	CRIT				Under certain circumstances on affected platforms running Arista EOS with gRPC Network Packet Sampling Interface (gNPSI) enabled, an unauthenticated gNPSI client can craft a malicious request to allow arbitrary code execution, granting an attacker full administrative control over the compromised switch.
CVE-2026-73458	9.2	CRIT		0.004		On affected platforms running Arista EOS with authenticated Bidirectional Forwarding Detection (BFD) sessions configured, a specially crafted packet can cause the BFD session(s) to go down. This may result in undesirable network changes because various routing protocols monitor status on BFD session(s).
CVE-2026-82067	9.2	CRIT		0.003	mongodb:mongodb	Improper handling of case sensitivity in the configuration validation component of MongoDB Server may cause the authorization subsystem to remain in a default disabled state during server startup. An unauthenticated user with network access to a deployment where this condition occurs can perform arbitrary administrative operations, resulting in full impact of data confidentiality, integrity, and availability.
CVE-2026-90562	9.2	CRIT		0.004		LangBot before 4.10.11 generates password recovery keys with only 24 bits of entropy and applies no rate limiting to the unauthenticated reset-password endpoint. Remote attackers knowing the administrator email can exhaust the keyspace through concurrent requests to reset the admin password and gain account access.
CVE-2026-91949	9.2	CRIT		0.004		FreeRDP server versions before 3.31.0 contain a protocol negotiation bypass vulnerability that allows unauthenticated attackers to establish RDSTLS connections despite server policy disabling them. Attackers can send incompatible protocol requests, receive negotiation failures, then complete TLS handshake and enter RDSTLS to bypass pre-authentication transport restrictions.
CVE-2026-92576	9.2	CRIT				HKUDS nanobot before 0.3.0 contains a server-side request forgery vulnerability in the WebFetchTool component where the _validate_url() function fails to block internal IP ranges and private addresses. Attackers can send messages instructing the bot to fetch cloud metadata endpoints, localhost services, and RFC 1918 addresses to extract IAM credentials and internal service data.
CVE-2026-92578	9.2	CRIT				WWBN AVideo through 29.0 contains an authentication bypass vulnerability where the stored password hash is accepted as a valid login credential through two independent code paths in loginFromRequest() and encryptPasswordVerify(). Attackers who obtain the stored users.password hash value can authenticate as any user by submitting the hash directly to login endpoints, completely bypassing password verification.
CVE-2026-92749	9.2	CRIT				SafeLine through 9.4.1 derives the management console session-signing secret from a time-seeded math/rand generator, allowing attackers to reconstruct the key offline. Unauthenticated remote attackers who can bound the install timestamp can regenerate the secret and forge valid administrator session cookies to gain control of protected sites.
CVE-2026-92785	9.2	CRIT				Angel through 3.3.0 deserializes untrusted setAlgoMetrics payload using Kryo without class registration or allowlist validation. Unauthenticated network attackers can instantiate arbitrary classes or exhaust coordinator memory by sending crafted serialized objects to the master RPC endpoint.
CVE-2023-27172	9.1	CRIT		0.007	xpand-it:write-back_manager	Xpand IT Write-back Manager v2.3.1 uses weak secret keys to sign JWT tokens. This allows attackers to easily obtain the secret key used to sign JWT tokens via a bruteforce attack.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2024-33668	9.1	CRIT		0.004	zammad:zammad	An issue was discovered in Zammad before 6.3.0. The Zammad Upload Cache uses insecure, partially guessable FormIDs to identify content. An attacker could try to brute force them to upload malicious content to article drafts they have no access to.
CVE-2024-45163	9.1	CRIT		0.008		The Mirai botnet through 2024-08-19 mishandles simultaneous TCP connections to the CNC (command and control) server. Unauthenticated sessions remain open, causing resource consumption. For example, an attacker can send a recognized username (such as root), or can send arbitrary data.
CVE-2026-15638	9.1	CRIT		0.002		An unauthenticated user with access to Secret Server could leverage a padding oracle to decrypt or encrypt data using one of the server's cryptographic keys. The key itself is not exposed.
CVE-2026-20176	9.1	CRIT				A vulnerability in Cisco ISE could allow an authenticated, remote attacker to execute arbitrary commands on the underlying operating system of an affected device. To exploit this vulnerability, the attacker must have valid high-privileged administrative credentials. This vulnerability is due to insufficient validation of user-supplied input. An attacker could exploit this vulnerability by sending a crafted HTTP...
CVE-2026-20194	9.1	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC), engineering teams have conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-20194 are...
CVE-2026-20211	9.1	CRIT				A vulnerability in Cisco ISE could allow an authenticated, remote attacker to execute arbitrary commands on the underlying operating system of an affected device. To exploit this vulnerability, the attacker must have valid high-privileged administrative credentials. This vulnerability is due to insecure deserialization of Java objects by the affected software. An attacker could exploit this vulnerability by sen...
CVE-2026-20237	9.1	CRIT				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC), engineering teams have conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-20237 are...
CVE-2026-20284	9.1	CRIT				A vulnerability in the SXP REST API of Cisco ISE could allow an authenticated, remote attacker to conduct SQL injection attacks. This vulnerability is due to insufficient validation of user-supplied input in REST API calls. An attacker could exploit this vulnerability by sending crafted input to an affected device. A successful exploit could allow the attacker to view or modify data on the underlying database f...
CVE-2026-20305	9.1	CRIT				A vulnerability in the diagnostic tools of Cisco ISE and ISE-PIC could allow an authenticated, remote attacker to perform command injection attacks on the underlying operating system and elevate privileges to root. To exploit this vulnerability, the attacker must have valid administrative credentials. This vulnerability is due to improper validation of user-supplied input. An attacker could exploit this vu...
CVE-2026-20306	9.1	CRIT				A vulnerability in the REST API of Cisco ISE and ISE-PIC could allow an authenticated, remote attacker to perform command injection attacks on the underlying operating system and elevate privileges to root. To exploit this vulnerability, the attacker must have valid administrative credentials. This vulnerability is due to improper validation of user-supplied input. An attacker could exploit this vulnerability b...
CVE-2026-20341	9.1	CRIT				A vulnerability in the sftunnel inter-device communication protocol of Cisco Secure FMC Software could allow an authenticated, remote attacker to obtain root privileges. This vulnerability is due to unsecured deserialization of untrusted data over the sftunnel management connection. An attacker could exploit this vulnerability by sending crafted sftunnel remote procedure calls (RPCs). A successful exploit ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-33186	9.1	CRIT		0.016	grpc:grpc	gRPC-Go is the Go language implementation of gRPC. Versions prior to 1.79.3 have an authorization bypass resulting from improper input validation of the HTTP/2 `:path` pseudo-header. The gRPC-Go server was too lenient in its routing logic, accepting requests where the `:path` omitted the mandatory leading slash (e.g., `Service/Method` instead of `/Service/Method`). While the server successfully routed these reques...
CVE-2026-39830	9.1	CRIT		0.006	golang:crypto	A malicious SSH peer could send unsolicited global request responses to fill an internal buffer, blocking the connection's read loop. The blocked goroutine could not be released by calling Close(), resulting in a resource leak per connection. Unsolicited global responses are now discarded.
CVE-2026-43790	9.1	CRIT		0.003	apple:macos	The issue was addressed with improved memory handling. This issue is fixed in macOS Golden Gate 27, macOS Sequoia 15.8, macOS Tahoe 26.7. A remote attacker may be able to cause unexpected system termination or corrupt kernel memory.
CVE-2026-45764	9.1	CRIT		0.004	oisf:suricata	Suricata is a network Intrusion Detection System, Intrusion Prevention System and Network Security Monitoring engine. Prior to versions 7.0.16 and 8.0.5, a protocol change while processing HTTP/2 traffic could lead to type confusion in Suricata. Crafted traffic may cause Suricata to crash, resulting in denial of service. Versions 7.0.16 and 8.0.5 contain a fix. As a workaround, disable HTTP/2 parsing if it is not ...
CVE-2026-48746	9.1	CRIT		0.012	vllm:vllm	vLLM is an inference and serving engine for large language models (LLMs). From 0.3.0 until 0.22.0, a vulnerability in ASGI web servers and starlette's trust on those web servers enables an authentication bypass of the OpenAI API AuthenticationMiddleware. It allows to use the API without providing the configured VLLM_API_KEY or --api-key. This vulnerability is fixed in 0.22.0.
CVE-2026-49364	9.1	CRIT		0.004	apache:artemis	An unauthenticated network-adjacent attacker can leverage discovery to capture cluster administrative credentials during the initial cluster connection handshake. This issue affects Apache Artemis: from 2.50.0 through 2.56.0; Apache ActiveMQ Artemis: from 1.0.0 through 2.44.0. Users are recommended to upgrade to version 2.57.0, which fixes the issue.
CVE-2026-52824	9.1	CRIT		0.021		Kimai is an open-source time tracking application. Prior to 2.58.0, the official Docker image sets APP_SECRET to the public value change_this_to_something_unique in Dockerfile, and .docker/entrypoint.sh neither replaces nor rejects that value before Symfony uses it as kernel.secret. An unauthenticated attacker who reaches a deployment that did not override APP_SECRET, knows a username, correctly guesses the accoun...
CVE-2026-53713	9.1	CRIT		0.004		Envoy Gateway is an open source project for managing Envoy Proxy as a standalone or Kubernetes-based application gateway. Prior to 1.7.4 and 1.8.1, to_absolute_normalized_path in internal/gatewayapi/luavalidator/security.lua does not collapse redundant separators before is_critical_path evaluates Lua submitted through EnvoyExtensionPolicy during default Strict validation. Linux resolves a double-slash absolute pat...
CVE-2026-61594	9.1	CRIT				djust provides Phoenix LiveView-style reactive server-side rendering for Django with Rust-powered performance. Prior to version 1.0.7, the live (WebSocket) transport authorizes a mount via `check_view_auth`, not Django's `View.dispatch()` chain. As a result, standard Django authorization — `LoginRequiredMixin`, `PermissionRequiredMixin`, `UserPassesTestMixin`, `@method_decorator(login_required, name="dispatch")`, ...
CVE-2026-63696	9.1	CRIT		0.003		Dell SmartFabric OS10 Software, versions prior to 10.6.1.3, contains a Download of Code Without Integrity Check vulnerability. A high privileged attacker with remote access could potentially exploit this vulnerability, leading to Code execution.
CVE-2026-67593	9.1	CRIT		0.006	apache:artemis	A remote attacker can craft an Openwire RemoveSubscriptionInfo command to cause the deletion of a queue on the Artemis broker before the connection authentication and authorization stage or at any time thereafter. This issue affects Apache Artemis: from 2.50.0 through 2.56.0; Apache ActiveMQ Artemis: from 1.0.0 through 2.44.0. Users are recommended to upgrade to version 2.57.0, which fixes the issue.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-73944	9.1	CRIT		0.003		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Access Manager. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificat...
CVE-2026-73946	9.1	CRIT		0.003		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Access Manager. While the vulnerability is in Oracle Access Manager, attacks may significantly impact additional pro...
CVE-2026-73952	9.1	CRIT		0.003		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Portlet Services). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificati...
CVE-2026-75156	9.1	CRIT		0.002		Apache Airflow FAB provider versions 3.7.3 through 3.8.0 do not validate the issuer or audience of Azure AD `id_token`s during OAuth login. Deployments are affected only when the FAB auth manager is configured with Azure AD as an OAuth provider. Because the signing keys are fetched from Microsoft's **multi-tenant** JWKS endpoint, an `id_token` minted in *any* Azure tenant — including one the attacker creates — pas...
CVE-2026-75513	9.1	CRIT				Marten is a .NET Transactional Document DB and Event Store on PostgreSQL. From version 7.0.0 until 9.13.0, several Marten LINQ and tenant-management paths interpolate runtime, potentially attacker-controlled strings into single-quoted SQL literals without escaping or parameterization. The primary confirmed vector is a dictionary indexer key used by Where filters in src/Marten/Linq/Members/Dictionaries/DictionaryIt...
CVE-2026-76675	9.1	CRIT		0.013		A command injection vulnerability exists in the command line interface of EdgeConnect SD-WAN Gateways. Successful exploitation could allow an authenticated remote attacker with high privileges to execute arbitrary commands on the underlying operating system leading to complete system compromise.
CVE-2026-77408	9.1	CRIT				RabbitMQ amqp091-go is a Go AMQP 0.9.1 client. Prior to 1.13.0, the writeShortstr function in write.go casts the byte length of AMQP shortstr property values to uint8 without first rejecting values longer than 255 bytes. An application that accepts an oversized CorrelationId, ReplyTo, MessageId, Expiration, UserId, AppId, ContentType, ContentEncoding, or Type value can therefore serialize a wrapped length and only...
CVE-2026-78299	9.1	CRIT		0.003		In Eclipse Embedded CDT versions 6.0 to 6.7 if the CMSIS-Pack archive extracts a compromised CMSIS pack the archive extraction can extract files to locations outside of the pack, allowing writing of arbitrary files to other locations on disk.
CVE-2026-80424	9.1	CRIT		0.004	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to create arbitrary files due to path traversal during archive extraction.
CVE-2026-81642	9.1	CRIT		0.005		In NLnet Labs Unbound up to and including 1.26.0, a vulnerability was found in the DNSSEC validator that enables denial of service and possible remote code execution as a result of digesting DNSKEYs. A DNSKEY with an owner compression pointer to its own RDATA can overflow the digest buffer. Remote code execution is possible through attacker controlled data. An adversary can exploit the vulnerability by controlling...
CVE-2026-83001	9.1	CRIT		0.005		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Access Manager. While the vulnerability is in Oracle Access Manager, attacks may significantly impact additional pro...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83006	9.1	CRIT		0.005		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle WebCenter Enterprise Capture. While the vulnerability is in Oracle WebCenter Enterprise Capture, attacks may s...
CVE-2026-83064	9.1	CRIT		0.005		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Runtime Tools). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. While the vulnerability is in Oracle WebCenter Portal, attacks may significantly impact additional produ...
CVE-2026-83103	9.1	CRIT		0.005		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Forms. While the vulnerability is in Oracle Forms, attacks may significantly impact additional products (scope chang...
CVE-2026-83104	9.1	CRIT		0.004		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Forms. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access...
CVE-2026-83107	9.1	CRIT		0.005		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Forms. While the vulnerability is in Oracle Forms, attacks may significantly impact additional products (scope chang...
CVE-2026-83149	9.1	CRIT		0.003		Vulnerability in Oracle Application Testing Suite. The supported version that is affected is 13.3.0.1. Easily exploitable vulnerability allows low privileged attacker having Test Manager for Web Apps privilege with network access via HTTP to compromise Oracle Application Testing Suite. While the vulnerability is in Oracle Application Testing Suite, attacks may significantly impact additional products (scope cha...
CVE-2026-83154	9.1	CRIT		0.003		Vulnerability in the Siebel CRM End User product of Oracle Siebel CRM (component: Open UI). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via SOAP to compromise Siebel CRM End User. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical data or all Siebel ...
CVE-2026-83196	9.1	CRIT		0.004		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Siebel CRM Deployment. While the vulnerability is in Siebel CRM Deployment, attacks may significantly impact additional products (scope change). S...
CVE-2026-83197	9.1	CRIT		0.004		Vulnerability in the Siebel Apps - Financial Services product of Oracle Siebel CRM (component: Financial Accounts). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel Apps - Financial Services. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete ...
CVE-2026-83201	9.1	CRIT		0.003		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical d...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83202	9.1	CRIT		0.004		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical d...
CVE-2026-83229	9.1	CRIT		0.004		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Siebel Management Console). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Siebel CRM Deployment. While the vulnerability is in Siebel CRM Deployment, attacks may significantly impact additional products (scope change)...
CVE-2026-83260	9.1	CRIT		0.005		Vulnerability in the Oracle Agile PLM product of Oracle Supply Chain (component: Event Java PX). The supported version that is affected is 9.3.6. Easily exploitable vulnerability allows high privileged attacker with network access via T3, IIOP to compromise Oracle Agile PLM. While the vulnerability is in Oracle Agile PLM, attacks may significantly impact additional products (scope change). Successful attacks o...
CVE-2026-83268	9.1	CRIT		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle BI Publisher. While the vulnerability is in Oracle BI Publisher, attacks may significantly impact additional produc...
CVE-2026-84625	9.1	CRIT		0.002		A permissions issue was addressed with additional sandbox restrictions. This issue is fixed in iOS 27 and iPadOS 27, macOS Golden Gate 27, visionOS 27, watchOS 27. An app may be able to fingerprint the user.
CVE-2026-86881	9.1	CRIT		0.001	apple:ipados, apple:iphone_os, apple:macos, apple:tvos, apple:visionos, apple:watchos	A certificate validation issue was addressed with improved certificate validation. This issue is fixed in iOS 26.7 and iPadOS 26.7, iOS 27 and iPadOS 27, macOS Golden Gate 27, macOS Sequoia 15.8, macOS Tahoe 26.7, tvOS 27, visionOS 27, watchOS 27. An attacker with a compromised intermediate certificate authority may be able to issue certificates with arbitrary extended key usages.
CVE-2026-87128	9.1	CRIT		0.004		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in unauthorized creatio...
CVE-2026-87129	9.1	CRIT		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in unauthorized creatio...
CVE-2026-87170	9.1	CRIT		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification...
CVE-2026-87173	9.1	CRIT		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification ...
CVE-2026-87175	9.1	CRIT		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87176	9.1	CRIT		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification ...
CVE-2026-87189	9.1	CRIT		0.005		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows high privileged attacker with network access via Oracle Net to compromise Oracle Hyperion Financial Management. While the vulnerability is in Oracle Hyperion Financial Management, attacks may significantly imp...
CVE-2026-87214	9.1	CRIT		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. While the vulnerability is in Oracle Hyperion Financial Management, attacks may significantly impact ad...
CVE-2026-87217	9.1	CRIT		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification...
CVE-2026-87223	9.1	CRIT		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification...
CVE-2026-89022	9.1	CRIT		0.003		BookStack before 26.05.5 contains an authentication bypass vulnerability in its social login implementation that allows unauthenticated attackers to sign in as arbitrary users by authenticating through a different social provider sharing the same driver_id namespace. Attackers can authenticate at one enabled social provider using a user ID that matches an account linked to a different social provider, bypassing cr...
CVE-2026-89779	9.1	CRIT		0.002		In the Linux kernel, the following vulnerability has been resolved: fs/ntfs3: validate ef->size covers the record's name and value When an EA record has a non-zero ef->size, ntfs_read_ea() only checks that the record fits in the remaining buffer (ea_size > bytes), not that ef->size is large enough to hold the record's own name_len + 1 + elength. A crafted image can pass validation with, e.g., ef->size = 24 but ...
CVE-2026-89786	9.1	CRIT		0.002		In the Linux kernel, the following vulnerability has been resolved: ext4: fix out-of-bounds read in ext4_read_inline_dir() ext4_read_inline_dir() can read a dirent header past the end of its inline buffer, triggering a slab-out-of-bounds read during getdents64(): BUG: KASAN: slab-out-of-bounds in __ext4_check_dir_entry Read of size 2 at addr ffff88800f3dd23c by task exploit/148 ... __ext4_check_dir_en...
CVE-2026-89846	9.1	CRIT				In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Bound rsp_info_len to avoid OOB sense-data read In qla2x00_status_entry(), the FWI2 status path advances sense_data and shrinks par_sense_len by rsp_info_len: if (IS_FWI2_CAPABLE(ha)) { sense_data += rsp_info_len; par_sense_len -= rsp_info_len; } rsp_info_len is a 32-bit value taken directly from the target's FCP response ...
CVE-2026-90011	9.1	CRIT				In the Linux kernel, the following vulnerability has been resolved: scsi: target: iscsi: Reserve a terminator byte for the login payload iscsi_target_check_login_request() rejects a login PDU whose DataSegmentLength exceeds MAX_KEY_VALUE_PAIRS, but the test is '>' and login->req_buf is allocated with exactly MAX_KEY_VALUE_PAIRS bytes. Since iscsit_get_login_rx() receives payload_length + padding bytes, where p...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-90711	9.1	CRIT		0.002		proxy-addr is a Node.js module that determines a request's client address behind trusted reverse proxies, and it backs Express req.ip and req.ips. In versions 1.1.0 through 2.0.7, a trust subnet written in IPv4-mapped IPv6 notation with an IPv4-sized prefix, such as ::ffff:10.0.0.0/8 instead of the correct ::ffff:10.0.0.0/104, is accepted without error but trusts every IPv4 address on the internet rather than the ...
CVE-2026-92395	9.1	CRIT				@fastify/proxy-addr is a Fastify plugin that determines a request's client address behind trusted reverse proxies, and it backs Fastify request.ip and request.ips. In versions 3.0.0 through 5.1.0, a trust subnet written in IPv4-mapped IPv6 notation with an IPv4-sized prefix, such as ::ffff:10.0.0.0/8 instead of the correct ::ffff:10.0.0.0/104, is accepted without error but trusts every IPv4 address on the internet...
CVE-2023-54397	9.0	CRIT		0.004		Tornado before 6.3.3 contains an HTTP request smuggling vulnerability due to improper parsing of Content-Length headers accepting non-standard characters. Attackers can send crafted HTTP requests with these characters to bypass proxy validation and smuggle requests when deployed behind certain proxies.
CVE-2024-14029	9.0	CRIT		0.004		Tornado before 6.4.1 ignores duplicate Transfer-Encoding: chunked headers, treating requests as having no message body and parsing the chunked body as a subsequent request. Attackers can exploit this inconsistency when Tornado is deployed behind proxies to perform HTTP request smuggling, enabling access control bypass, cache poisoning, or connection desynchronization.
CVE-2026-18691	9.0	CRIT		0.002	mongodb:mongodb	An issue in MongoDB Server's intra-cluster connection setup could allow a party with suitable network access to influence which authentication mechanism is used when one replica set member connects to another. Under certain conditions, this could cause the cluster's shared internal credential to be transmitted in a less-protected form, potentially allowing that credential to be recovered. If recovered, the credent...
CVE-2026-61549	9.0	CRIT		0.002		Woodpecker is a CI/CD engine. From 1.0.0 until 3.16.0, pipeline/backend/kubernetes/backend_options.go defines backend_options.kubernetes.serviceAccountName, and the Kubernetes backend in pipeline/backend/kubernetes/pod.go copies that pipeline-step value directly into the pod specification without administrator authorization. Any user with Push permission on a connected repository can therefore run pipeline pods un...
CVE-2026-76420	9.0	CRIT				A vulnerability in the internal configuration of the Apache JServ Protocol (AJP) connector for Cisco Secure FMC Software could allow an unauthenticated, remote attacker to impersonate a peer device. This vulnerability is due to incorrect initialization of encryption parameters for the AJP connector at boot time. An attacker could exploit this vulnerability by sending crafted packets to the AJP connector. A...
CVE-2026-77638	9.0	CRIT		0.002	torproject:tor	Tor before 0.4.9.11 is prone to a race condition where in just the right circumstances a rendezvous point could man-in-the-middle (impersonate) the onion service that the client was trying to reach.
CVE-2026-77866	9.0	CRIT		0.005		Server-Side Request Forgery (SSRF) vulnerability in Slab safeurl allows an attacker who controls a validated URL to reach internal network destinations the library is configured to block. Only IPv4 addresses are matched against the reserved ranges and the blocklist. Every other address is treated as matching nothing, so a destination that is rejected in its IPv4 form is accepted when written as an IPv6 address, I...
CVE-2026-77972	9.0	CRIT		0.003		Time-of-check Time-of-use (TOCTOU) Race Condition in Slab safeurl allows an attacker who controls a hostname's DNS responses to reach internal network destinations that validation rejected. Validation returns a verdict and not the address it approved, so the HTTP clients the library ships receive the original hostname and resolve it a second time when the request is made. An attacker who controls the authoritativ...
CVE-2026-83105	9.0	CRIT		0.004		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Forms. While the vulnerability is in Oracle Forms, attacks may significantly impact additional products (scope cha...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-91932	9.0	CRIT		0.008		Flowise before 3.1.4 contains a validation bypass vulnerability in MCP server configuration allowing authenticated attackers remote code execution through an unvalidated cwd parameter. Attackers can bypass path validation using clean filenames in the args array while controlling the working directory to execute malicious code.

Watchlist matches (other priorities)

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83304	8.9	HIGH		0.004		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Analytics Web General). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. While the vulnerability is in Oracle Busin...
CVE-2026-12728	8.8	HIGH		0.006		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 could allow an authenticated attacker to execute arbitrary code due to a deserialization of untrusted data.
CVE-2026-13293	8.8	HIGH		0.006		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 could allow a remote authenticated attacker to execute arbitrary code on the system due to the deserialization of untrusted data.
CVE-2026-16428	8.8	HIGH		0.005		IBM DataStage on Cloud Pak for Data 5.4.0.0 IBM DataStage could allow a remote authenticated attacker to execute arbitrary code due to improper configuration of the XSLT transformation engine.
CVE-2026-16466	8.8	HIGH		0.009		IBM DataStage on Cloud Pak for Data 5.4.0.0 IBM DataStage could allow a remote authenticated attacker to execute arbitrary commands due to os command injection.
CVE-2026-16673	8.8	HIGH		0.004		IBM DataStage on Cloud Pak for Data 5.4.0.0 IBM DataStage could allow a remote authenticated attacker to execute arbitrary OS commands due to improper neutralization of special characters in the PxPeek name property.
CVE-2026-20333	8.8	HIGH				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Secure Adaptive Security Appliance Software, Cisco Secure Firewall Threat Defense Software and Cisco Secure Firewall Management Center Software engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabil...
CVE-2026-20336	8.8	HIGH				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Secure Adaptive Security Appliance Software, Cisco Secure Firewall Threat Defense Software and Cisco Secure Firewall Management Center Software engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabil...
CVE-2026-20340	8.8	HIGH				A vulnerability in Cisco Secure FMC Software could allow an authenticated, remote attacker to execute arbitrary commands at the root privilege level. This vulnerability is due to unsecured deserialization of web-management user-controlled data. An attacker could exploit this vulnerability by authenticating to the device and sending a crafted HTTP payload. A successful exploit could allow the attacker to sa...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-20344	8.8	HIGH				A vulnerability in the web-based management interface of Cisco Secure FMC Software could allow an authenticated, remote attacker to perform a SQL injection attack against an affected device. To exploit this vulnerability, the attacker must have a valid account on the device with the role of Security Approver, Access Admin, or Network Admin. This vulnerability is due to insufficient validation of user-supplied i...
CVE-2026-20360	8.8	HIGH				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Nexus Dashboard engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-20360 are related to information exposure and insecure handling issues that ar...
CVE-2026-20361	8.8	HIGH				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Nexus Dashboard engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-20361 are related to SQL injection issues that are grouped under the Common We...
CVE-2026-53071	8.8	HIGH		0.003	linux:linux_kernel	In the Linux kernel, the following vulnerability has been resolved: Bluetooth: l2cap: Add missing chan lock in l2cap_ecred_reconf_rsp l2cap_ecred_reconf_rsp() calls l2cap_chan_del() without holding l2cap_chan_lock(). Every other l2cap_chan_del() caller in the file acquires the lock first. A remote BLE device can send a crafted L2CAP ECRED reconfiguration response to corrupt the channel list while another thread ...
CVE-2026-58076	8.8	HIGH		0.005	apache:airflow	Apache Airflow's serialization layer reconstructed exception nodes by calling `import_string()` on a class name taken from the serialized blob and instantiating it with arguments from the same blob, with no restriction on what could be imported. An operator's `executor_config` reaches that branch, so a Dag author could place a value there that causes an arbitrary callable to be imported and invoked -- for example ...
CVE-2026-61599	8.8	HIGH				djust provides Phoenix LiveView-style reactive server-side rendering for Django with Rust-powered performance. Prior to version 1.0.7, the djust live transport resolves the LiveView to mount from a client-supplied dotted path by calling `__import__(module_path, ...)`. The module is imported — running its top-level code (import side effects) — before the framework checks that the resolved object is a `LiveView` sub...
CVE-2026-62706	8.8	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.
CVE-2026-63506	8.8	HIGH				Tina is a headless content management system. Prior to @tinacms/auth 1.1.4 and next-tinacms-azure 15.0.1, isAuthorized accepts a request-controlled clientID and asks isUserAuthorized to validate the bearer token against that selected TinaCloud app instead of the self-hosted site's configured app. An attacker with any TinaCloud account can submit the attacker's own app ID and valid token to a victim endpoint, causi...
CVE-2026-66814	8.8	HIGH		0.004	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Insufficient granularity of access control in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-66818	8.8	HIGH		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper privilege management in SQL Server allows an authorized attacker to elevate privileges over a network.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-66819	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper neutralization of special elements used in an sql command ('sql injection') in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-66820	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper neutralization of special elements used in an sql command ('sql injection') in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-67370	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper neutralization of special elements used in an sql command ('sql injection') in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-67373	8.8	HIGH		0.006	microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67380	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67381	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-67384	8.8	HIGH		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Integer overflow or wraparound in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67385	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use after free in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67388	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67587	8.8	HIGH		0.006	apache:airflow	Apache Airflow's Task SDK rebuilt a `Callback` object from serialized data by re-running its constructor, which imports the module named by the stored callback path. Because `SyncCallback` is itself an Airflow class it passes the default `allowed_deserialization_classes` allow-list, so tightening that setting does not help. A Dag author — who controls a task instance's `next_kwargs` through the task execution API ...
CVE-2026-69860	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Imaging Component allows an unauthorized attacker to execute code over a network.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-70203	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Media Player allows an unauthorized attacker to execute code over a network.
CVE-2026-70915	8.8	HIGH		0.003		Vulnerability in the Oracle Identity Manager product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with network access via T3, IIOP to compromise Oracle Identity Manager. Successful attacks of this vulnerability can result in takeover of Oracle Identity Manager. CVSS 3.1 Base Scor...
CVE-2026-71047	8.8	HIGH		0.004		Vulnerability in the Oracle Identity Manager product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Identity Manager. Successful attacks of this vulnerability can result in takeover of Oracle Identity Manager. CVSS 3.1 Base Score 8....
CVE-2026-71336	8.8	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Integer overflow or wraparound in Windows Work Folder Service allows an authorized attacker to execute code over a network.
CVE-2026-73942	8.8	HIGH		0.004		Vulnerability in the Oracle Identity Manager product of Oracle Fusion Middleware (component: OIM Legacy UI). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Identity Manager. Successful attacks of this vulnerability can result in takeover of Oracle Identity Manager. CVSS 3.1 Base...
CVE-2026-73949	8.8	HIGH		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Portlet Services). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Portal. CVSS 3.1 B...
CVE-2026-73959	8.8	HIGH		0.005		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Composer). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Portal. CVSS 3.1 Base Scor...
CVE-2026-75624	8.8	HIGH		0.004	ibm:aix, ibm:app_connect_enterprise, linux:linux_kernel, microsoft:windows	IBM App Connect Enterprise 13.0.1.0 through 13.0.8.1, and 12.0.1.0 through 12.0.12.27 could allow a remote authenticated attacker to bypass security restrictions due to incorrect authorization.
CVE-2026-76059	8.8	HIGH		0.005	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 An attacker who could submit custom component source code could bypass the static security scanner by crafting an annotated class-body assignment that resolved to a dangerous callable through alias tracking; the resolved value was never checked against the dangerous callable blacklist due to the logic error. If the crafted component reached the runtime execution path, the atta...
CVE-2026-76409	8.8	HIGH				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Nexus Dashboard engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-76409 are related to improper limitation of a pathname issues that are grouped...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-77495	8.8	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-78569	8.8	HIGH		0.005	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow an authenticated attacker to execute arbitrary code due to an incomplete denylist in the security scanner.
CVE-2026-78571	8.8	HIGH		0.006	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow a remote authenticated attacker to execute arbitrary code due to an unguarded eval() call on attacker-controlled input.
CVE-2026-78575	8.8	HIGH		0.005	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow a remote authenticated attacker to execute arbitrary commands due to improper validation of command-line arguments in the MCP stdio server configuration.
CVE-2026-79742	8.8	HIGH		0.006	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow a remote authenticated attacker to execute arbitrary code due to an incomplete environment variable blocklist.
CVE-2026-81211	8.8	HIGH		0.003	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow a remote authenticated attacker to execute arbitrary Python code due to improper authorization of custom components in stored flows.
CVE-2026-81550	8.8	HIGH		0.006	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to execute arbitrary code due to improper neutralization of special elements used in an OS command.
CVE-2026-81940	8.8	HIGH		0.006	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow a remote authenticated attacker to execute arbitrary code due to improper neutralization of special characters in flow display names.
CVE-2026-81941	8.8	HIGH		0.008	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 allows an authenticated non-administrative user could execute arbitrary operating system commands on the server at the privilege level of the application process by constructing a flow with an MCP Tools component configured to use a local stdio subprocess transport. This bypasses both the LANGFLOW_CUSTOM_COMPONENT_ADMIN_ONLY and LANGFLOW_BLOCK_CODE_INTERPRETER_COMPONENTS serve...
CVE-2026-82095	8.8	HIGH		0.006	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to execute arbitrary code due to improper neutralization of special elements used in an OS command.
CVE-2026-82097	8.8	HIGH		0.004	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to execute arbitrary code due to a Server-Side Request Forgery (SSRF) vulnerability.
CVE-2026-82098	8.8	HIGH		0.008	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to execute arbitrary commands due to improper neutralization of special elements used in an OS command.
CVE-2026-82099	8.8	HIGH		0.004	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to execute arbitrary code due to improper neutralization of special elements used in an OS command.
CVE-2026-82964	8.8	HIGH				Improper preservation of permissions in the Avast sandbox minifilter driver (aswSnx.sys) on Windows allows a local, low-privileged attacker executing inside the sandbox to escape file isolation and escalate to SYSTEM. When the sandbox virtualizes a file it copies the original security descriptor, but the driver opened the virtualization target object with GENERIC_WRITE and FILE_WRITE_ATTRIBUTES only, omitting W...
CVE-2026-83005	8.8	HIGH		0.004		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Enterprise Capture. Successful attacks of this vulnerability can result in takeover of Oracle WebCent...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83008	8.8	HIGH		0.005		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via T3, IIOP to compromise Oracle WebCenter Enterprise Capture. Successful attacks of this vulnerability can result in takeover of Oracle Web...
CVE-2026-83009	8.8	HIGH		0.004		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Enterprise Capture. Successful attacks of this vulnerability can result in takeover of Oracle WebCent...
CVE-2026-83013	8.8	HIGH		0.004		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Enterprise Capture. Successful attacks of this vulnerability can result in takeover of Oracle WebCent...
CVE-2026-83017	8.8	HIGH		0.004		Vulnerability in the PeopleSoft Enterprise PeopleTools product of Oracle PeopleSoft (component: Report Distribution). Supported versions that are affected are 8.61-8.63. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise PeopleSoft Enterprise PeopleTools. Successful attacks of this vulnerability can result in takeover of PeopleSoft Enterprise PeopleTools. C...
CVE-2026-83032	8.8	HIGH		0.005		Vulnerability in the Oracle WebCenter Sites product of Oracle Fusion Middleware (component: WebCenter Sites). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Sites. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Sites. CVSS 3.1 Base ...
CVE-2026-83033	8.8	HIGH		0.005		Vulnerability in the Oracle WebCenter Sites product of Oracle Fusion Middleware (component: WebCenter Sites). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Sites. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Sites. CVSS 3.1 Base ...
CVE-2026-83053	8.8	HIGH		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Runtime Tools). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Portal. CVSS 3.1 Base...
CVE-2026-83069	8.8	HIGH		0.004		Vulnerability in the Oracle Fusion Middleware Control product of Oracle Fusion Middleware (component: Framework). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Fusion Middleware Control. Successful attacks of this vulnerability can result in takeover of Oracle Fusion Middleware...
CVE-2026-83086	8.8	HIGH		0.005		Vulnerability in the Siebel CRM Cloud Applications product of Oracle Siebel CRM (component: Siebel Cloud Manager). Supported versions that are affected are 22.3-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Cloud Applications. Successful attacks of this vulnerability can result in takeover of Siebel CRM Cloud Applications. CVSS 3.1 Bas...
CVE-2026-83090	8.8	HIGH		0.004		Vulnerability in the Oracle Spares Management product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Spares Management. Successful attacks of this vulnerability can result in takeover of Oracle Spares Management. CVSS 3.1 Base Sco...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83119	8.8	HIGH		0.004		Vulnerability in the Oracle User Management product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.6-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle User Management. Successful attacks of this vulnerability can result in takeover of Oracle User Management. CVSS 3.1 Base Score 8.8...
CVE-2026-83120	8.8	HIGH		0.004		Vulnerability in the Oracle Alert product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Alert. Successful attacks of this vulnerability can result in takeover of Oracle Alert. CVSS 3.1 Base Score 8.8 (Confidentiality, Integrity a...
CVE-2026-83121	8.8	HIGH		0.004		Vulnerability in the Oracle Marketing product of Oracle E-Business Suite (component: Audience). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Marketing. Successful attacks of this vulnerability can result in takeover of Oracle Marketing. CVSS 3.1 Base Score 8.8 (Confidentiality, Integrity ...
CVE-2026-83122	8.8	HIGH		0.004		Vulnerability in the Oracle Report Manager product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTPS to compromise Oracle Report Manager. Successful attacks of this vulnerability can result in takeover of Oracle Report Manager. CVSS 3.1 Base Score 8.8 (...
CVE-2026-83124	8.8	HIGH		0.004		Vulnerability in the Oracle Sales Online product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Sales Online. Successful attacks of this vulnerability can result in takeover of Oracle Sales Online. CVSS 3.1 Base Score 8.8 (Confide...
CVE-2026-83125	8.8	HIGH		0.003		Vulnerability in the Oracle Report Manager product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Report Manager. Successful attacks of this vulnerability can result in takeover of Oracle Report Manager. CVSS 3.1 Base Score 8.8 (C...
CVE-2026-83136	8.8	HIGH		0.003		Vulnerability in the Oracle Spares Management product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Spares Management. Successful attacks of this vulnerability can result in takeover of Oracle Spares Management. CVSS 3.1 Base Sco...
CVE-2026-83137	8.8	HIGH		0.003		Vulnerability in the Oracle Spares Management product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Spares Management. Successful attacks of this vulnerability can result in takeover of Oracle Spares Management. CVSS 3.1 Base Sco...
CVE-2026-83148	8.8	HIGH		0.005		Vulnerability in Oracle Application Testing Suite. The supported version that is affected is 13.3.0.1. Easily exploitable vulnerability allows low privileged attacker having Test Manager for Web Apps privilege with network access via HTTP to compromise Oracle Application Testing Suite. Successful attacks of this vulnerability can result in takeover of Oracle Application Testing Suite. CVSS 3.1 Base Score 8.8 (C...
CVE-2026-83153	8.8	HIGH		0.004		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTPS to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deployment. CVSS 3.1 Base Score 8.8 (Confident...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83160	8.8	HIGH		0.005		Vulnerability in the RDBMS component of Oracle Database Server. Supported versions that are affected are 23.4.0-23.26.3. Easily exploitable vulnerability allows low privileged attacker having Create Table privilege with network access via Oracle Net to compromise RDBMS. Successful attacks of this vulnerability can result in takeover of RDBMS. CVSS 3.1 Base Score 8.8 (Confidentiality, Integrity and Availability i...
CVE-2026-83163	8.8	HIGH		0.005		Vulnerability in the Oracle Application Object Library product of Oracle E-Business Suite (component: Attachments / File Upload). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Application Object Library. Successful attacks of this vulnerability can result in takeover of Oracle Application ...
CVE-2026-83164	8.8	HIGH		0.004		Vulnerability in the Oracle Customer Interaction History product of Oracle E-Business Suite (component: Outcome-Result). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Customer Interaction History. Successful attacks of this vulnerability can result in takeover of Oracle Customer Interactio...
CVE-2026-83165	8.8	HIGH		0.003		Vulnerability in the Oracle Customer Interaction History product of Oracle E-Business Suite (component: User Interface). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTPS to compromise Oracle Customer Interaction History. Successful attacks of this vulnerability can result in takeover of Oracle Customer Interacti...
CVE-2026-83168	8.8	HIGH		0.004		Vulnerability in the Oracle Applications Manager product of Oracle E-Business Suite (component: Oracle Diagnostics Interfaces). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTPS to compromise Oracle Applications Manager. Successful attacks of this vulnerability can result in takeover of Oracle Applications Manage...
CVE-2026-83180	8.8	HIGH		0.005		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deployment. CVSS 3.1 Base Score 8.8 (Confidenti...
CVE-2026-83189	8.8	HIGH		0.004		Vulnerability in the Oracle User Management product of Oracle E-Business Suite (component: Proxy User Delegation). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle User Management. Successful attacks of this vulnerability can result in takeover of Oracle User Management. CVSS 3.1 Base Score 8...
CVE-2026-83194	8.8	HIGH		0.005		Vulnerability in the Oracle Depot Repair product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.10-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Depot Repair. Successful attacks of this vulnerability can result in takeover of Oracle Depot Repair. CVSS 3.1 Base Score 8.8 (Confid...
CVE-2026-83199	8.8	HIGH		0.004		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deployment. CVSS 3.1 Base Score 8.8 (Confidenti...
CVE-2026-83205	8.8	HIGH		0.004		Vulnerability in the Oracle Applications Framework product of Oracle E-Business Suite (component: Personalization). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Applications Framework. Successful attacks of this vulnerability can result in takeover of Oracle Applications Framework. CVSS 3...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83208	8.8	HIGH		0.005		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Migration). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via SQL to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deployment. CVSS 3.1 Base Score 8.8 (Confidentiality, Integr...
CVE-2026-83209	8.8	HIGH		0.004		Vulnerability in the Siebel CRM Development product of Oracle Siebel CRM (component: Workflow). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Development. Successful attacks of this vulnerability can result in takeover of Siebel CRM Development. CVSS 3.1 Base Score 8.8 (Confidentiality, Int...
CVE-2026-83210	8.8	HIGH		0.004		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via SQL to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deployment. CVSS 3.1 Base Score 8.8 (Confidentia...
CVE-2026-83212	8.8	HIGH		0.004		Vulnerability in the Siebel Apps - Self Service product of Oracle Siebel CRM (component: Helpdesk/Training). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel Apps - Self Service. Successful attacks of this vulnerability can result in takeover of Siebel Apps - Self Service. CVSS 3.1 Base Score 8.8 ...
CVE-2026-83271	8.8	HIGH		0.005		Vulnerability in the RDBMS component of Oracle Database Server. Supported versions that are affected are 19.3-19.32, 21.3-21.23 and 23.4.0-23.26.3. Easily exploitable vulnerability allows low privileged attacker having Execute on DBMS_REDEFINITION privilege with network access via Oracle Net to compromise RDBMS. Successful attacks of this vulnerability can result in takeover of RDBMS. CVSS 3.1 Base Score 8.8 (C...
CVE-2026-83301	8.8	HIGH		0.004		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Service Administration UI). The supported version that is affected is 12.2.1.4.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can result in takeover of ...
CVE-2026-83306	8.8	HIGH		0.005		Vulnerability in the Oracle JDeveloper product of Oracle Fusion Middleware (component: Resource Catalog Services). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle JDeveloper. Successful attacks of this vulnerability can result in takeover of Oracle JDeveloper. CVSS 3.1 Base Score...
CVE-2026-83315	8.8	HIGH		0.005		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via SOAP to compromise Oracle BI Publisher. Successful attacks of this vulnerability can result in takeover of Oracle BI Publisher. CVSS 3.1 Base ...
CVE-2026-83329	8.8	HIGH		0.004		Vulnerability in the Oracle Applications Framework product of Oracle E-Business Suite (component: Personalization). Supported versions that are affected are 12.2.9-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Applications Framework. Successful attacks of this vulnerability can result in takeover of Oracle Applications Framework. CVSS 3...
CVE-2026-83331	8.8	HIGH		0.004		Vulnerability in the Oracle Applications Framework product of Oracle E-Business Suite (component: Personalization). Supported versions that are affected are 12.2.9-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Applications Framework. Successful attacks of this vulnerability can result in takeover of Oracle Applications Framework. CVSS 3...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83335	8.8	HIGH		0.004		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Analytics Server). Supported versions that are affected are 8.2.0.0.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can result in takeove...
CVE-2026-83338	8.8	HIGH		0.004		Vulnerability in the Oracle Applications Manager product of Oracle E-Business Suite (component: Oracle Diagnostics Interfaces). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Applications Manager. Successful attacks of this vulnerability can result in takeover of Oracle Applications Manager...
CVE-2026-83340	8.8	HIGH		0.004		Vulnerability in the Oracle Identity Manager product of Oracle Fusion Middleware (component: Security). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Identity Manager. Successful attacks of this vulnerability can result in takeover of Oracle Identity Manager. CVSS 3.1 Base Scor...
CVE-2026-83348	8.8	HIGH		0.005		Vulnerability in the RDBMS component of Oracle Database Server. Supported versions that are affected are 19.3-19.32, 21.3-21.23 and 23.4.0-23.26.3. Easily exploitable vulnerability allows low privileged attacker having Create DB Link privilege with network access via Oracle Net to compromise RDBMS. Successful attacks of this vulnerability can result in takeover of RDBMS. CVSS 3.1 Base Score 8.8 (Confidentiality...
CVE-2026-83410	8.8	HIGH		0.004		Vulnerability in the Oracle Coherence product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0, 14.1.1.0.0, 14.1.2.0.0 and 15.1.1.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via multiple protocols to compromise Oracle Coherence. Successful attacks of this vulnerability can result in takeover of Oracle Coherence. CVSS ...
CVE-2026-83411	8.8	HIGH		0.003		Vulnerability in the Oracle Coherence product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 14.1.1.0.0, 14.1.2.0.0 and 15.1.1.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Coherence. Successful attacks of this vulnerability can result in takeover of Oracle Coherence. CVSS 3.1 Base Score 8.8 (Confid...
CVE-2026-83423	8.8	HIGH		0.003		Vulnerability in the Oracle JDeveloper product of Oracle Fusion Middleware (component: Security Framework). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle JDeveloper. Successful attacks of this vulnerability can result in takeover of Oracle JDeveloper. CVSS 3.1 Base Score 8.8 (C...
CVE-2026-83444	8.8	HIGH		0.004		Vulnerability in the Oracle Product Hub product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Hub. Successful attacks of this vulnerability can result in takeover of Oracle Product Hub. CVSS 3.1 Base Score 8.8 (Confidenti...
CVE-2026-83445	8.8	HIGH		0.004		Vulnerability in the Oracle Complex Maintenance, Repair and Overhaul product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTPS to compromise Oracle Complex Maintenance, Repair and Overhaul. Successful attacks of this vulnerability can result in takeover...
CVE-2026-83454	8.8	HIGH		0.005		Vulnerability in the Oracle Document Management and Collaboration product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Document Management and Collaboration. Successful attacks of this vulnerability can result in takeover of Ora...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83456	8.8	HIGH		0.005		Vulnerability in the Oracle Demand Signal Repository product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Demand Signal Repository. Successful attacks of this vulnerability can result in takeover of Oracle Demand Signal Reposito...
CVE-2026-83479	8.8	HIGH		0.004		Vulnerability in the Oracle Contracts product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.14-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Contracts. Successful attacks of this vulnerability can result in takeover of Oracle Contracts. CVSS 3.1 Base Score 8.8 (Confidentiality...
CVE-2026-83941	8.8	HIGH		0.007	microsoft:entra_id	Missing authorization in Entra ID allows an authorized attacker to elevate privileges over a network.
CVE-2026-84858	8.8	HIGH				ScadaLTS 2.8.1-release-candidate build 0 is affected by an Authenticated Remote Code Execution via Scripting Sandbox Bypass The DWR "DataSourceEditDwr" class exposes the "validateScript" method that compiles and executes attacker-supplied JavaScript via the Rhino scripting engine. There are no authorization checks on this method and so it is possible for an attacker with access to a low privilege user to abuse ...
CVE-2026-84860	8.8	HIGH				ScadaLTS 2.8.1-release-candidate build 0 is affected by an Authorization Bypass Spring Security gates DWR endpoints by URL path pattern, but DWR itself dispatches method calls based on the POST body parameters c0-scriptName and c0-methodName. The crossDomainSessionSecurity setting in web.xml is set to false, which disables DWR's built-in origin validation. This means any authenticated user can invoke any DWR me...
CVE-2026-87150	8.8	HIGH		0.005		Vulnerability in the Oracle Bills of Material product of Oracle E-Business Suite (component: Setup Workbench). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Bills of Material. Successful attacks of this vulnerability can result in takeover of Oracle Bills of Material. CVSS 3.1 Base Score 8...
CVE-2026-87155	8.8	HIGH		0.005		Vulnerability in the Oracle Product Hub product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Hub. Successful attacks of this vulnerability can result in takeover of Oracle Product Hub. CVSS 3.1 Base Score 8.8 (Confidenti...
CVE-2026-87162	8.8	HIGH		0.004		Vulnerability in the Oracle Contract Lifecycle Management for Public Sector product of Oracle E-Business Suite (component: Award/PO). Supported versions that are affected are 12.2.13-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Contract Lifecycle Management for Public Sector. Successful attacks of this vulnerability can result in takeo...
CVE-2026-87163	8.8	HIGH		0.005		Vulnerability in the Oracle Purchasing product of Oracle E-Business Suite (component: Other issue). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Purchasing. Successful attacks of this vulnerability can result in takeover of Oracle Purchasing. CVSS 3.1 Base Score 8.8 (Confidentiality, Inte...
CVE-2026-87165	8.8	HIGH		0.004		Vulnerability in the Oracle Contract Lifecycle Management for Public Sector product of Oracle E-Business Suite (component: ECC For Award and IDV). The supported version that is affected is V16. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Contract Lifecycle Management for Public Sector. Successful attacks of this vulnerability can result in ta...
CVE-2026-87179	8.8	HIGH		0.005		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management....

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87180	8.8	HIGH		0.005		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management....
CVE-2026-87181	8.8	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management....
CVE-2026-87182	8.8	HIGH		0.001		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. While the vulnerability is in Oracle Hyperion Fi...
CVE-2026-87185	8.8	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management....
CVE-2026-87187	8.8	HIGH		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. S...
CVE-2026-87201	8.8	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management....
CVE-2026-87202	8.8	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via SQL to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management. ...
CVE-2026-87204	8.8	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management....
CVE-2026-87224	8.8	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management....
CVE-2026-87226	8.8	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management....

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87227	8.8	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management....
CVE-2026-87238	8.8	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via SQL to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management. ...
CVE-2026-88064	8.8	HIGH				Backstage is an open framework for building developer portals. Prior to 1.14.6 and from 1.15.0 until 1.15.4, the @backstage/plugin-techdocs-node package insufficiently validates mkdocs.yml supplied by an authenticated user who can register or modify a TechDocs source. Unsafe Python YAML tags, markdown_extensions names and configuration, theme options, and extra_templates values can reach the documentation generato...
CVE-2026-89774	8.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: Bluetooth: SCO: hold sk properly in sco_conn_ready sk deref in sco_conn_ready must be done either under conn->lock, or holding a refcount, to avoid concurrent close. conn->sk and parent sk is currently accessed without either, and without checking parent->sk_state: [Task 1] [Task 2] sco_sock_release sc...
CVE-2026-89777	8.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: vfio/pci: clear vdev->msi_perm after freeing it on init failure vfio_msi_cap_len() lazily allocates the per-device MSI permission table: vdev->msi_perm = kmalloc_obj(struct perm_bits, GFP_KERNEL_ACCOUNT); if (!vdev->msi_perm) return -ENOMEM; ret = init_pci_cap_msi_perm(vdev->msi_perm, len, flags); if (ret) { kfree(vdev->msi_perm); re...
CVE-2026-89804	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/nouveau/dmem: fix mismatched DMA unmap size for large folios Device-private THP migration maps migration buffers with page_size() and records that length in dma_info->size. For a compound folio page_size() is PAGE_SIZE << order, but two teardown sites still pass a literal PAGE_SIZE to dma_unmap_page(): - nouveau_dmem_migrate_to_ram() on ...
CVE-2026-89811	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/amdkfd: Add TLB flush after MES queue eviction/suspension MES (Micro Engine Scheduler) does not perform heavy-weight TLB invalidation after unmapping queues, unlike HWS which does this automatically. This causes a race condition where in-flight DMA descriptors can access memory that has been unmapped, leading to page faults and GPU queue han...
CVE-2026-89844	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Hold vport_slock for host map update in report ID acquisition qla24xx_report_id_acquisition() format-1 handling drops vport_slock after taking the vport reference and then calls qla_update_host_map() without the lock. That reaches qla_update_vp_map(), which mutates the ha->host_map btree via btree_insert32()/btree_update32()/btree...
CVE-2026-89849	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Reject non-SCSI SRB on status IOCB fast path qla2x00_status_entry() filters out non-TYPE_SRB entries and the SRB_NVME_CMD, SRB_BIDI_CMD and SRB_TM_CMD types, then falls through to a SCSI fast path that assumes the command is an SRB_SCSI_CMD. The first thing on that path, qla_chk_edif_rx_sa_delete_pending(), and the subsequent hand...
CVE-2026-89860	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Initialize NVMe abort_work once at submission qla_nvme_fcp_abort() and qla_nvme_ls_abort() ran INIT_WORK() on priv->abort_work immediately before schedule_work(). INIT_WORK() reinitializes the work_struct, resetting its list head and clearing the pending bit. If an abort is issued more than once for the same command (for example, ...
CVE-2026-89898	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: cec: extron-da-hd-4k-plus: add sanity check Add check to prevent overflowing msg.msg[] in case the incoming data is malformed.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89907	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: LoongArch: KVM: Validate MSI data before routing it to EIOINTC pch_msi_set_irq() passes e->msi.data straight into eiointc_set_irq() as the irq number. The MSI data comes from userspace, that either via a KVM_IRQ_ROUTING_MSI entry set with KVM_SET_GSI_ROUTING (used by irqfd and KVM_IRQ_LINE) or directly via KVM_SIGNAL_MSI, and is never checked ag...
CVE-2026-89908	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: LoongArch: KVM: Preserve memslot arch flags on KVM_MR_FLAGS_ONLY kvm_arch_prepare_memory_region() computes new->arch.flags, i.e. whether a memslot is KVM_MEM_HUGEPAGE_CAPABLE or KVM_MEM_HUGEPAGE_INCAPABLE, only for KVM_MR_CREATE and KVM_MR_MOVE, and returns early for every other change. But the generic code allocates a zeroed memslot for every c...
CVE-2026-89913	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: KVM: arm64: vgic-v3: take an LPI reference in vgic_v3_save_pending_tables vgic_v3_save_pending_tables() iterates dist->ipi_xa using xa_for_each() and dereferences the returned struct vgic_irq in the loop body without holding a reference on the LPI. The xarray iterator only provides temporary RCU coverage while looking up the current entry. That...
CVE-2026-89928	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: KVM: x86/mmu: Consume the locked rmap value in the lockless rmap walk __kvm_rmap_lock() deliberately elides the rmap lock when it observes an empty rmap. In that case kvm_rmap_lock_readonly() also re-enables preemption and returns zero, so the caller holds neither the rmap lock nor a preemption reference. The elision documents the invariant it...
CVE-2026-89929	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: KVM: nVM: Ensure INVVPID is emulated on the correct physical CPU When emulating INVVPID, KVM executes INVVPID on the physical CPU using vpid02 (instead of the L1 assigned VPID), after doing some validations on the operands. However, it is possible that the physical CPU KVM executes INVVPID on is different from the CPU L2 is running on. For exam...
CVE-2026-89932	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: KVM: nVMX: Always flush vpid02 on first use Make sure vpid02 is always flushed on first use by setting last_vpid=0 when allocating vpid02. nested_vmx_transition_tlb_flush() will always detect a VPID change on first VM-Enter after VMXON, because VPID=0 in vmcs12 is not allowed if L1 enables VPID. This avoids using stale TLB entries from a previ...
CVE-2026-89951	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: batman-adv: fix stale receive device on merged fragments Fragment reassembly reuses the skb from the highest-numbered buffered fragment as the merged packet. When that fragment was received on a hard interface which is deleted before the chain completes, the merged skb can re-enter the receive path with a stale skb->dev and skb_iif. batadv_batm...
CVE-2026-89957	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: s390/vfio-ap: Fix hot-unplug skipped when last AP adapter or domain removed The vfio_ap_mdev_hot_unplug_cfg() function uses the return value of bitmap_andnot() to determine whether the guest APCB needs to be updated. However, bitmap_andnot() returns false when the resulting destination bitmap is empty. This means that if the only adapter, domain...
CVE-2026-89959	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: s390/vfio-ap: Fix control domain removal in vfio_ap_mdev_cfg_remove The vfio_ap_config_remove function uses the bitmap_andnot function to clear bits from the matrix_mdev->matrix.adm bitmap (specifies the control domains assigned to the mdev). This prevents the explicitly unplugged control domains from being removed the KVM guest. The bitmap_and ...
CVE-2026-89960	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: s390/vfio-ap: fix stale pqap_hook pointer on error in vfio_ap_mdev_set_kvm() In vfio_ap_mdev_set_kvm(), kvm->arch.crypto.pqap_hook is set to &matrix_mdev->pqap_hook before the update locks are acquired and the mdev list is checked for a conflicting assignment. If another mdev is already attached to the same KVM instance, the function returns -EP...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89995	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: dma-direct: return struct page from dma_direct_alloc_from_pool() Commit 5b138c534fda ("dma-direct: factor out a dma_direct_alloc_from_pool helper") changed dma_direct_alloc_from_pool() to return the CPU address from dma_alloc_from_pool(). That fits dma_direct_alloc(), but dma_direct_alloc_pages() also uses the helper and expects a struct page *....
CVE-2026-90000	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: HID: rmi: fix OOB access with undersized RMI reports The hid-rmi driver sizes its writeReport/readReport buffer purely from the report descriptor supplied by the device, with no minimum bound: data->input_report_size = hid_report_len(input_report); data->output_report_size = hid_report_len(output_report); alloc_size = data->output_report_si...
CVE-2026-90018	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: staging: rtl8723bs: fix OOB read / stack overflow in rtw_get_wps_attr() rtw_get_wps_attr() walks WPS attributes inside a WPS IE taken from a wireless management frame. For each candidate attribute it only checks that the fixed 4-byte attribute header (2-byte ID + 2-byte length) fits inside the IE: if (attr_ptr + 4 > wps_ie + wps_ielen) break...
CVE-2026-90041	8.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: HID: sony: clean up device list on probe failure sony_input_configured() adds some controllers to sony_device_list before HID core registers their input devices. input_register_device() can fail after the callback returns successfully. sony_probe() then observes that HID_CLAIMED_INPUT is clear and unwinds, but only stops the HID hardware. The de...
CVE-2026-92122	8.8	HIGH				Jenkins Script Security Plugin 1415.v9a_f9b_3a_c253d and earlier does not check the method called through the proxy created when a sandboxed script coerces a value to an interface, if the value inherits a method of the same name as an interface method, allowing attackers with permission to define and run sandboxed scripts, including Pipelines, to bypass the sandbox protection and execute arbitrary code in the cont...
CVE-2026-92123	8.8	HIGH				Jenkins Script Security Plugin 1415.v9a_f9b_3a_c253d and earlier does not intercept operations performed on a null receiver (method calls, property and attribute accesses, and array accesses), allowing attackers with permission to define and run sandboxed scripts, including Pipelines, to bypass the sandbox protection and execute arbitrary code in the context of the Jenkins controller JVM.
CVE-2026-92124	8.8	HIGH				Jenkins Script Security Plugin 1415.v9a_f9b_3a_c253d and earlier checks the operations Groovy will perform with the elements it reads from a collection that a sandboxed script casts to another type but performs the cast on the collection itself, allowing attackers with permission to define and run sandboxed scripts, including Pipelines, to bypass the sandbox protection and execute arbitrary code in the context of ...
CVE-2026-92125	8.8	HIGH				Jenkins Script Security Plugin 1415.v9a_f9b_3a_c253d and earlier does not reject the @GroovyASTTransformationClass annotation, allowing attackers with permission to define and run sandboxed scripts, including Pipelines, to run an arbitrary AST transformation at compile time, bypassing the sandbox protection and executing arbitrary code in the context of the Jenkins controller JVM.
CVE-2026-92137	8.8	HIGH				Jenkins Robot Framework Plugin 6.2.2 and earlier does not check that the archive directory configured for Robot Framework report files is contained within the build directory on the Jenkins controller, allowing attackers with Item/Configure permission to create or replace arbitrary files on the Jenkins controller file system with attacker-specified content, which can lead to remote code execution.
CVE-2026-18697	8.7	HIGH		0.003	mongodb:mongodb	An issue in MongoDB Server's aggregation framework could allow an unauthenticated party to cause a mongos (router) process to terminate unexpectedly by submitting a specially formed aggregation command. This could result in a denial of service, disrupting client connections routed through the affected mongos instance.
CVE-2026-55839	8.7	HIGH		0.003		Kestra is an open-source, event-driven orchestration platform. Prior to 1.3.24, Kestra's custom Markdown parser in ui/src/utlils/markdown_plugins/link.ts allows a user with permission to create or update a Flow description to inject JavaScript event-handler attributes through the custom [[link]] syntax, causing stored cross-site scripting when another user opens the description or information panel in the Flow list...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-73926	8.7	HIGH		0.003		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Access Manager. While the vulnerability is in Oracle Access Manager, attacks may significantly impact additional pro...
CVE-2026-75516	8.7	HIGH				The RabbitMQ Java client library allows Java and JVM-based applications to connect to and interact with RabbitMQ nodes. Prior to 5.34.0, AMQConnection.start() applies Math.min(maxInboundMessageBodySize, frameMax) after Connection.Tune negotiation even though AMQP defines frameMax value zero as unlimited and ConnectionFactory.DEFAULT_FRAME_MAX is zero. When the client default and server-negotiated value are both ze...
CVE-2026-79994	8.7	HIGH		0.001		The guest-to-host Unix-domain socket relay in Docker Sandboxes validates that a socket path is inside an authorized workspace, but later reconnects using the pathname. A malicious guest can replace an intermediate directory with a symlink between validation and connection, causing the host to connect to an arbitrary AF_UNIX socket outside the shared workspace. This can expose data or host-side capabilities provide...
CVE-2026-82028	8.7	HIGH		0.004		Magistrala before 1.0.0 contains a SQL injection vulnerability in the timescale-reader and postgres-reader HTTP API services that allows authenticated attackers to inject arbitrary SQL by supplying a malicious format query parameter that is interpolated directly into the FROM clause without parameterization or identifier quoting. Attackers with a self-registered account can substitute arbitrary subqueries to achie...
CVE-2026-82064	8.7	HIGH		0.003	mongodb:mongodb	A security issue in MongoDB Server allows an unauthenticated network user to cause a denial of service on a specific type of replica set member. The server contains an assertion in its read concern processing logic that can be reached without authentication, and the assertion's assumptions about internal state do not hold for all member configurations, causing the server process to terminate.
CVE-2026-82075	8.7	HIGH		0.003	mongodb:mongodb	An uncontrolled resource consumption weakness exists in the request-handling path of the MongoDB sharded-cluster router process. A client that has network access to a router port and has not authenticated can supply connection-monitoring parameters that cause the server to expend CPU resources without any rate limiting, degrading or denying service to legitimate clients. No authentication, elevated privileges, or ...
CVE-2026-83025	8.7	HIGH		0.003		Vulnerability in the Oracle Identity Manager Connector product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Identity Manager Connector. While the vulnerability is in Oracle Identity Manager Connector, attacks may significantly i...
CVE-2026-83135	8.7	HIGH		0.004		Vulnerability in the Oracle iStore product of Oracle E-Business Suite (component: Shopping Cart). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle iStore. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Oracle iStore, attack...
CVE-2026-83144	8.7	HIGH		0.004		Vulnerability in the Siebel Apps - Customer Order Management product of Oracle Siebel CRM (component: Order Management). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel Apps - Customer Order Management. Successful attacks require human interaction from a person other than the attacker and while t...
CVE-2026-83145	8.7	HIGH		0.004		Vulnerability in the Siebel Apps - Customer Order Management product of Oracle Siebel CRM (component: Order Management). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel Apps - Customer Order Management. Successful attacks require human interaction from a person other than the attacker and while t...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83310	8.7	HIGH		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle BI Publisher. Successful attacks require human interaction from a person other than the attacker and while the vulne...
CVE-2026-84408	8.7	HIGH		0.011		QND contains an improper access control vulnerability in a named pipe, which may allow a local attacker who is logged in to a Windows PC where the affected product's client is installed to execute arbitrary commands with SYSTEM privileges.
CVE-2026-86831	8.7	HIGH				Improper validation of pod identifier uniqueness in aws-network-policy-agent in Amazon EKS Network Policy Agent before v1.4.0 might allow an authenticated remote user to bypass NetworkPolicy enforcement on co-located pods in other namespaces via crafted pod and namespace names that produce pod identifier collisions. To remediate this issue, users should upgrade to Amazon EKS Network Policy Agent 1.4.0 or later ...
CVE-2026-87171	8.7	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTPS to compromise Oracle Hyperion Financial Management. While the vulnerability is in Oracle Hyperion Financial Management, attacks may significantly impact...
CVE-2026-87178	8.7	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows high privileged attacker with network access via SQL to compromise Oracle Hyperion Financial Management. While the vulnerability is in Oracle Hyperion Financial Management, attacks may significantly impact add...
CVE-2026-87817	8.7	HIGH		0.003	gitpython_project:gitpython	GitPython before 3.1.60 fails to properly validate the git directory location, allowing attackers to impersonate the git directory using tracked files like gitdir, commondir, and HEAD. Attackers can execute arbitrary code by placing a malicious pre-commit hook in the tracked hooks directory that executes when a victim calls index.commit() on a cloned or opened repository.
CVE-2026-87819	8.7	HIGH		0.003	gitpython_project:gitpython	GitPython before 3.1.60 contains a regular expression denial of service vulnerability in Actor.name_email_regex that processes commit author and committer fields. Attackers can craft a commit object with a malformed author field containing an unterminated angle bracket to cause quadratic backtracking, exhausting CPU resources for over two minutes per commit access.
CVE-2026-90776	8.7	HIGH		0.005		Nodemailer versions 9.1.0 through 10.0.4 contain a quadratic time complexity vulnerability in the addressparser component when parsing email addresses with RFC 5322 comments. Attackers can craft malicious email headers with comment-separated atoms to consume excessive CPU and block the Node.js event loop for several seconds, causing denial of service.
CVE-2026-92466	8.7	HIGH				zlt2000 microservices-platform through 6.0.0 contains a missing authorization vulnerability where the zlt.security.auth.urlPermission.enable flag defaults to false, disabling all permission checks after authentication. Authenticated users with no roles can access administrative APIs including user management, role assignment, and Elasticsearch index operations by bypassing the disabled authorization enforcement.
CVE-2026-92580	8.7	HIGH				In AVideo through 29.0, the CloneSite plugin is vulnerable to stored OS command injection. In plugin/CloneSite/cloneClient.json.php (line ~270) the stored SSH password is substituted into the command string `sshpass -p '{password}' rsync ...` with a plain str_replace and no escaping, so a single quote in the password breaks out of the quoted word and injects arbitrary shell. The password is written through the adm...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-92593	8.7	HIGH				Craft CMS versions 5.10.0 through 5.10.12 contain an incomplete fix for CVE-2026-55794: the Controller::getPostedRedirectUrl() -> View::renderObjectTemplate() sink remained unsandboxed, and the same fix commit added a self-signing oracle in Cp::elementLabelHtml(). Because Craft/Yii HMAC tokens are not bound to a parameter name, an authenticated low-privilege control panel user with edit rights on a single element ...
CVE-2026-92596	8.7	HIGH				Nodemailer before 9.1.0 contains a quadratic time complexity vulnerability in the addressparser component that allows remote attackers to cause denial of service by supplying a crafted comma-separated address list. Attackers can send a single email with a large number of addresses to block the Node.js event loop for extended periods, consuming 100% CPU and freezing the process.
CVE-2026-92762	8.7	HIGH				Pelican Panel versions before 1.0.0-beta35 enforce startup write permissions only through disabled form controls rather than server-side authorization checks. Attackers with startup.read permission can craft Livewire state updates to invoke afterStateUpdated callbacks and modify startup commands, docker images, and variables to execute arbitrary commands in the container.
CVE-2024-20260	8.6	HIGH		0.006		Update for September 16, 2026: The original 1.0 version of this advisory was specific to the Cisco Adaptive Security Virtual Appliance (ASAv) and Cisco Secure Firewall Threat Defense Virtual (FTDv) models. However, it was later found that this vulnerability affects all Cisco Secure Firewall Adaptive Security Appliance (ASA) Software and Cisco Secure Firewall Threat Defense (FTD) Software platforms. A vulnerabil...
CVE-2026-20135	8.6	HIGH				A vulnerability in the TLS 1.3 implementation in Cisco Secure Firewall Threat Defense (FTD) Software could allow an unauthenticated, remote attacker to cause an affected device to reload unexpectedly, resulting in a denial of service (DoS) condition. This vulnerability is due to improper buffer management during the TLS 1.3 connection. An attacker could exploit this vulnerability by sending a crafted TLS 1.3 pa...
CVE-2026-20154	8.6	HIGH				A vulnerability in the system rate-limiting process for syslog message 419002 of Cisco Secure Firewall Adaptive Security Appliance (ASA) Software and Cisco Secure Firewall Threat Defense (FTD) Software could allow an unauthenticated, remote attacker to cause high CPU utilization on an affected device, resulting in a denial of service (DoS) condition. This vulnerability is due to improper rate limiting for syslo...
CVE-2026-20249	8.6	HIGH				A vulnerability in the certification authentication feature of Internet Key Exchange version 2 (IKEv2) for Cisco Secure Firewall Adaptive Security Appliance (ASA) Software and Cisco Secure Firewall Threat Defense (FTD) Software could allow an unauthenticated, remote attacker to cause an affected device to reload unexpectedly. This vulnerability is due to a logic error during the certificate authentication ...
CVE-2026-20250	8.6	HIGH				A vulnerability in Datagram TLS (DTLS) message handling of Cisco Secure Firewall Adaptive Security Appliance (ASA) Software and Cisco Secure Firewall Threat Defense (FTD) Software for Cisco Secure Firewall 3100 Series and 4200 Series devices could allow an unauthenticated, remote attacker to cause a denial of service (DoS) condition on an affected device. This vulnerability is due to improper resource managemen...
CVE-2026-20295	8.6	HIGH				A vulnerability in the sftunnel inter-device communication protocol of Cisco Secure FMC Software and Cisco Secure FTD Software could allow an unauthenticated, remote attacker to exhaust the available memory of an affected device. This vulnerability is due to improper management of memory resources during sftunnel TLS connection setup. An attacker could exploit this vulnerability by sending crafted sftunnel TLS ...
CVE-2026-20352	8.6	HIGH				A vulnerability in the RADIUS feature of Cisco Identity Services Engine (ISE) could allow an unauthenticated, remote attacker to cause a denial of service (DoS) condition on an affected device. This vulnerability is due to improper handling of certain RADIUS requests. An attacker could exploit this vulnerability by sending a crafted RADIUS request directly to an affected device. A successful exploit could allow...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-54628	8.6	HIGH		0.003		Anyquery is an SQL query engine built on top of SQLite. Prior to 0.4.5, anyquery server exposes URL-capable SQLite virtual table modules such as json_reader and log_reader through its unauthenticated MySQL-compatible server port without restricting outbound destinations. A remote attacker can provide a loopback, private-network, or link-local cloud metadata URL, causing go-getter in the Anyquery server process to ...
CVE-2026-55691	8.6	HIGH		0.003		The EmbedVideo Extension is a MediaWiki extension which adds a parser function called #ev and various parser tags for embedding video clips from various video sharing services. Prior to 4.1.0, EmbedHtmlFormatter::toHtml in includes/EmbedService/EmbedHtmlFormatter.php passes the user-supplied class value directly to sprintf while constructing a figure element. A quote in the class value can terminate the class attr...
CVE-2026-56100	8.6	HIGH		0.003		SpringBlade versions from 2.7.3 up to but not including 5.0.0 contain a privilege escalation vulnerability that allows authenticated attackers to create system administrator accounts by sending crafted POST requests to an unprotected internal Feign user-creation endpoint exposed via @RestController without authorization checks. Attackers can exploit the gateway's authentication filter, which only validates JWT par...
CVE-2026-73941	8.6	HIGH		0.003		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Access Manager. While the vulnerability is in Oracle Access Manager, attacks may significantly impact additional pro...
CVE-2026-81213	8.6	HIGH		0.004	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow a remote attacker to obtain sensitive information from internal network resources due to improper validation of user-supplied URLs.
CVE-2026-83023	8.6	HIGH		0.004		Vulnerability in the Oracle Identity Manager Connector product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Identity Manager Connector. While the vulnerability is in Oracle Identity Manager Connector, attacks may significantly im...
CVE-2026-83074	8.6	HIGH		0.003		Vulnerability in the Siebel CRM Cloud Applications product of Oracle Siebel CRM (component: Siebel Cloud Manager). Supported versions that are affected are 22.3-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via SSH to compromise Siebel CRM Cloud Applications. While the vulnerability is in Siebel CRM Cloud Applications, attacks may significantly impact additional produ...
CVE-2026-83093	8.6	HIGH		0.004		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Forms. While the vulnerability is in Oracle Forms, attacks may significantly impact additional products (scope chang...
CVE-2026-83203	8.6	HIGH		0.004		Vulnerability in the Siebel CRM End User product of Oracle Siebel CRM (component: Open UI). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM End User. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Siebel CRM End User acc...
CVE-2026-83284	8.6	HIGH		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via SOAP to compromise Oracle BI Publisher. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or freque...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83305	8.6	HIGH		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle BI Publisher. Successful attacks of this vulnerability can result in unauthorized access to critical data or compl...
CVE-2026-87273	8.6	HIGH		0.001		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows unauthenticated attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. Successful attacks require human interaction from a person other than the attacker and while the vul...
CVE-2026-11729	8.5	HIGH		0.003		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 could allow an authenticated attacker to execute arbitrary code in client applications due to unsafe deserialization that enables JNDI injection attacks.
CVE-2026-18111	8.5	HIGH		0.003		Concrete CMS 9 before 9.5.3 was vulnerable to stored cross-site scripting (XSS) in the Feature, Feature Link, Hero Image, and Image blocks and before Concrete 8.5.21 in the feature and Image blocks because the external link URL was insufficiently validated by the link filter and was rendered without output escaping. A user with page-editing permissions (such as Add Block combined with Edit Contents on a single pag...
CVE-2026-67378	8.5	HIGH		0.005	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Untrusted pointer dereference in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67379	8.5	HIGH		0.006	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Stack-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-70341	8.5	HIGH		0.006		Use after free in Microsoft Edge (Chromium-based) allows an authorized attacker to execute code over a network.
CVE-2026-73220	8.5	HIGH		0.003		CVAT is an open source interactive video and image annotation tool for computer vision. From 2.68.0 until 2.70.0, the audio-task annotation guide renderer in cvat-ui/src/audio/components/annotation-page/audio-workspace/top-bar/audio-right-group.tsx passes attacker-controlled guide Markdown to MDEditor without the rehype-sanitize plugin. A user who can create or edit an annotation guide can store malicious JavaScri...
CVE-2026-76412	8.5	HIGH				A vulnerability in the remote diagnostics debugger of Cisco Secure FMC Software could allow an authenticated, remote attacker to enable the remote diagnostics debugger service. This vulnerability is due to an error when checking the privilege level of a user who is invoking remote diagnostics. An attacker could exploit this vulnerability by authenticating to the device, either through the web-based management i...
CVE-2026-79708	8.5	HIGH		0.003		GitLab has remediated an issue in GitLab EE affecting all versions from 19.0 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that, under certain conditions could have allowed an authenticated user with developer permissions to execute a policy test pipeline on projects within their group and access protected CI/CD variables restricted to higher-privileged roles, due to insufficient scope validation.
CVE-2026-80436	8.5	HIGH		0.003	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to cause a denial of service by deleting arbitrary RabbitMQ queues or exchanges due to improper authorization.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-81207	8.5	HIGH		0.002	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 allows any authenticated tenant — with no project membership or role — fully controls scheme/host/port/path of an outbound fetch originating from a shared-infrastructure pod, and the WSDL body is reflected verbatim to the caller. The ds-canvas pod sits on the OpenShift overlay with reach to co-tenant services, in-cluster CP4D APIs, and link-local addresses. Scope is Chan...
CVE-2026-81540	8.5	HIGH		0.004	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to overwrite ruleset files belonging to other tenants due to a path traversal vulnerability.
CVE-2026-82993	8.5	HIGH		0.003		Vulnerability in the PeopleSoft Enterprise PeopleTools product of Oracle PeopleSoft (component: Business Interlink). Supported versions that are affected are 8.61-8.63. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise PeopleSoft Enterprise PeopleTools. While the vulnerability is in PeopleSoft Enterprise PeopleTools, attacks may significantly impact additi...
CVE-2026-83002	8.5	HIGH		0.004		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Access Manager. While the vulnerability is in Oracle Access Manager, attacks may significantly impact additional pr...
CVE-2026-83003	8.5	HIGH		0.003		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via SOAP to compromise Oracle WebCenter Enterprise Capture. While the vulnerability is in Oracle WebCenter Enterprise Capture, attacks may si...
CVE-2026-83007	8.5	HIGH		0.003		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Enterprise Capture. While the vulnerability is in Oracle WebCenter Enterprise Capture, attacks may si...
CVE-2026-83045	8.5	HIGH		0.002		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Runtime Tools). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. While the vulnerability is in Oracle WebCenter Portal, attacks may significantly impact additional produc...
CVE-2026-83049	8.5	HIGH		0.003		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Security Framework). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. While the vulnerability is in Oracle WebCenter Portal, attacks may significantly impact additional p...
CVE-2026-83083	8.5	HIGH		0.003		Vulnerability in the Oracle Marketing product of Oracle E-Business Suite (component: Audience). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Marketing. While the vulnerability is in Oracle Marketing, attacks may significantly impact additional products (scope change). Successful attacks ...
CVE-2026-83172	8.5	HIGH		0.003		Vulnerability in the Oracle Sales Online product of Oracle E-Business Suite (component: OSO Other). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Sales Online. While the vulnerability is in Oracle Sales Online, attacks may significantly impact additional products (scope change). Successfu...
CVE-2026-83267	8.5	HIGH		0.003		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Publisher Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle BI Publisher. While the vulnerability is in Oracle BI Publisher, attacks may significantly impact additional produc...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83272	8.5	HIGH		0.004		Vulnerability in the Oracle Text component of Oracle Database Server. Supported versions that are affected are 19.3-19.32, 21.3-21.23 and 23.4.0-23.26.3. Difficult to exploit vulnerability allows low privileged attacker having Create Index privilege with network access via Oracle Net to compromise Oracle Text. While the vulnerability is in Oracle Text, attacks may significantly impact additional products (scope...
CVE-2026-83302	8.5	HIGH		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Publisher Security). The supported version that is affected is 12.2.1.4.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle BI Publisher. While the vulnerability is in Oracle BI Publisher, attacks may significantly impact additional products (scope change). Succes...
CVE-2026-83303	8.5	HIGH		0.003		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via SOAP to compromise Oracle BI Publisher. While the vulnerability is in Oracle BI Publisher, attacks may significantly impact additional product...
CVE-2026-83309	8.5	HIGH		0.003		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: Web Server). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle BI Publisher. While the vulnerability is in Oracle BI Publisher, attacks may significantly impact additional products (scope c...
CVE-2026-83311	8.5	HIGH		0.003		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via SOAP to compromise Oracle BI Publisher. While the vulnerability is in Oracle BI Publisher, attacks may significantly impact additional product...
CVE-2026-83321	8.5	HIGH		0.003		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Analytics Actions). Supported versions that are affected are 8.2.0.0.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. While the vulnerability is in Oracle Business Intelligence En...
CVE-2026-83425	8.5	HIGH		0.004		Vulnerability in the Oracle Complex Maintenance, Repair and Overhaul product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.12-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Complex Maintenance, Repair and Overhaul. While the vulnerability is in Oracle Complex Maintenance, Repai...
CVE-2026-83449	8.5	HIGH		0.003		Vulnerability in the Oracle Bills of Material product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Bills of Material. While the vulnerability is in Oracle Bills of Material, attacks may significantly impact additional products (...)
CVE-2026-83451	8.5	HIGH		0.003		Vulnerability in the Oracle Product Workbench product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Workbench. While the vulnerability is in Oracle Product Workbench, attacks may significantly impact additional products...
CVE-2026-83490	8.5	HIGH		0.003		Vulnerability in the Oracle iRecruitment product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle iRecruitment. While the vulnerability is in Oracle iRecruitment, attacks may significantly impact additional products (scope change). ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87161	8.5	HIGH		0.002		Vulnerability in the Oracle HRMS (India) product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle HRMS (India). While the vulnerability is in Oracle HRMS (India), attacks may significantly impact additional products (scope change). ...
CVE-2026-87177	8.5	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. While the vulnerability is in Oracle Hyperion Financial Management, attacks may significantly impact add...
CVE-2026-88765	8.5	HIGH		0.007		GitLab has remediated an issue in GitLab EE affecting all versions from 12.3 to 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 under certain conditions could allow an authenticated user to achieve remote code execution by importing a specially crafted Git project export to overflow the Unicode conversion buffer used in Advanced Search indexing.
CVE-2026-20334	8.4	HIGH				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Secure Adaptive Security Appliance Software, Cisco Secure Firewall Threat Defense Software and Cisco Secure Firewall Management Center Software engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabil...
CVE-2026-68955	8.4	HIGH		0.002		The installer for Rakuten Kobo Desktop Application (Windows version) insecurely loads Dynamic Link Libraries. If there is a crafted DLL at the same directory when invoking the affected installer, arbitrary code may be executed with the privileges of the user who performed the installation.
CVE-2026-76825	8.4	HIGH				RestrictedPython is a tool that helps define a subset of the Python language for accepting program input in a trusted environment. Prior to 8.4, RestrictedPython could allow a sandbox escape when a custom import policy or globals exposed the standard library string module, the string.Formatter class, a Formatter instance, or a Formatter subclass to restricted code. The string.Formatter methods format, get_field, g...
CVE-2026-82049	8.4	HIGH		0.002		In CPython 3.13 and earlier, the tarfile module's data and tar extraction filters are vulnerable to crafted archives containing a hard link to a symbolic link. Such archives may cause extraction to modify the permissions or modification time of a file outside the destination directory, or expose the contents of that file within the extracted tree.
CVE-2026-83264	8.4	HIGH		0.002		Vulnerability in the Oracle Product Lifecycle Analytics product of Oracle Supply Chain (component: Installation Issues). The supported version that is affected is 3.6.1. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Product Lifecycle Analytics executes to compromise Oracle Product Lifecycle Analytics. While the vulnerability is in Oracle Product Li...
CVE-2026-87219	8.4	HIGH		0.001		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. While the vulnerability is in Oracle Hyperion Fi...
CVE-2026-87259	8.4	HIGH		0.001		Vulnerability in the Oracle Agile Engineering Data Management product of Oracle Supply Chain (component: Engineering Communication Interface). The supported version that is affected is 6.2.1. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Agile Engineering Data Management executes to compromise Oracle Agile Engineering Data Management. While the vul...
CVE-2026-89781	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: fs/ntfs3: fix out-of-bounds read in read_log_rec_buf() read_log_rec_buf() copies a log record into a caller buffer starting at u32 off = lsn_to_page_off(log, lsn) + log->record_header_len; log->record_header_len (and log->data_off, used for the following pages) comes verbatim from the on-disk restart area and is only checked for 8-byte alignm...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89782	8.4	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: fs/ntfs3: reject restart table growth beyond U16_MAX entries During \$LogFile replay, log_replay() indexes the transaction table by the transact_id taken from the log record header. check_log_rec() only verifies that transact_id is non-zero and properly aligned, not its magnitude, so a crafted image can request an arbitrarily large index. alloc...
CVE-2026-89795	8.4	HIGH				In the Linux kernel, the following vulnerability has been resolved: PCI: Allow per function PCI slots to fix slot reset on s390 On s390 systems, which use a machine level hypervisor, PCI devices are always accessed through a form of PCI pass-through which fundamentally operates on a per PCI function granularity. This is also reflected in the s390 PCI hotplug driver which creates hotplug slots for individual PCI ...
CVE-2026-89806	8.4	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/sysfb: ofdrm: Fix integer overflow in fb_size calculation The framebuffer size calculation `fb_size = linebytes * height` can overflow when both values are large (e.g., 46341 * 46341 > INT_MAX). Since linebytes and height are both int types, the multiplication is performed as int * int, which results in undefined behavior on overflow. Use c...
CVE-2026-89856	8.4	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Clamp MSI-X derived queue counts to avoid truncation ha->msix_count is u16, but ha->max_req_queues, ha->max_rsp_queues and ha->max_qpairs are u8. Deriving the queue count as "ha->max_req_queues = ha->msix_count - 1" therefore truncates: a board (or a misconfigured/malicious hot-plugged device) advertising 257 MSI-X vectors yields ...
CVE-2026-89877	8.4	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: saa7164: fix cleanup on resource allocation failure saa7164_dev_setup() adds the device to the global saa7164_devlist before requesting the PCI BAR memory regions. If get_resources() fails, saa7164_dev_setup() decrements the device count and returns an error, but leaves the device on saa7164_devlist. The probe error path then frees the d...
CVE-2026-89885	8.4	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: platform: mtk-mdp3: Fix SCP device refcounting mdp_probe() first tries to get the SCP handle with scp_get(). When that fails, it falls back to looking up the SCP platform device with __get_pdev_by_id() and then reads its driver data. The fallback lookup returns the platform device with a reference, just like scp_get() does. However, the ...
CVE-2026-89904	8.4	HIGH				In the Linux kernel, the following vulnerability has been resolved: LoongArch: Fix acpi_package_ids[] array overflow With LoongArch virt machine, a typical setting is one core per socket, there will max 256 sockets (packages) on one VM. With PPTT acpi table, array acpi_package_ids[] will be overflowed. Here change the array size of acpi_package_ids[] with the max value of MAX_PACKAGES and KVM_MAX_VCPUS.
CVE-2026-89943	8.4	HIGH				In the Linux kernel, the following vulnerability has been resolved: ASoC: loongson: Fix error handling in ACPI property parsing In loongson_card_parse_acpi(), the return value of device_property_read_string() for the `codec-dai-name` property was ignored. If the property is missing or invalid, an uninitialized pointer would be used later, potentially leading to undefined behavior. Fix this by checking the retur...
CVE-2026-89980	8.4	HIGH				In the Linux kernel, the following vulnerability has been resolved: ALSA: harmony: initialize locks before requesting IRQ snd_harmony_create() registers the IRQ before initializing h->lock and h->mixer_lock. A pending interrupt can invoke the handler while these locks are uninitialized. Initialize both locks before requesting the IRQ so the handler always sees valid lock state.
CVE-2026-89992	8.4	HIGH				In the Linux kernel, the following vulnerability has been resolved: cpuidle: dt_idle_genpd: kfree() the original name allocation dt_idle_pd_alloc() kasprintf(s) the full node path, then points pd->name at kbasename() of that string. dt_idle_pd_free() kfree(s) pd->name, which is no longer the start of the allocation. Copy the basename instead.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-20323	8.3	HIGH				A vulnerability in the sftunnel inter-device communication protocol of Cisco Secure FMC Software and Cisco Secure FTD Software could allow an unauthenticated, adjacent attacker to impersonate the peer device and obtain access at the level of the manager role, which is equivalent to root. This vulnerability is due to improper management of the TLS certificate for the sftunnel management connection. An attac...
CVE-2026-69646	8.3	HIGH		0.002	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Improper verification of cryptographic signature in Skype for Business allows an unauthorized attacker to perform spoofing over an adjacent network.
CVE-2026-83026	8.3	HIGH		0.002		Vulnerability in the Oracle Identity Manager Connector product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Difficult to exploit vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Identity Manager Connector executes to compromise Oracle Identity Manager Conn...
CVE-2026-83030	8.3	HIGH		0.004		Vulnerability in the Oracle Managed File Transfer product of Oracle Fusion Middleware (component: MFT Runtime Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via T3, IIOP to compromise Oracle Managed File Transfer. Successful attacks of this vulnerability can result in unauthorized creation, deletio...
CVE-2026-83285	8.3	HIGH		0.004		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: BI Search). The supported version that is affected is 12.2.1.4.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can result in unauthorized creation, dele...
CVE-2026-83307	8.3	HIGH		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle BI Publisher. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificatio...
CVE-2026-87125	8.3	HIGH		0.003		Vulnerability in the Oracle Financials for Asia/Pacific product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.8-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Financials for Asia/Pacific. Successful attacks of this vulnerability can result in unauthorized creation, deletion or...
CVE-2026-87210	8.3	HIGH		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. S...
CVE-2026-91936	8.3	HIGH		0.003		Flowise versions before 3.1.4 contain a script injection vulnerability in Docker image build workflows where workflow_dispatch inputs are directly interpolated into shell run blocks. Attackers with repository write access can inject shell metacharacters through inputs like tag_version and node_version to execute arbitrary commands and steal AWS credentials and Docker Hub tokens.
CVE-2026-91943	8.3	HIGH		0.003		Crawl4AI before 0.9.3 contains a server-side request forgery vulnerability in PDFContentScrapingStrategy where _get_pdf_path() re-downloads targets with Python requests without egress validation. Authenticated attackers can supply URLs that redirect to internal addresses or use DNS rebinding to access internal services, exfiltrating responses through PDF text extraction in crawl results.
CVE-2026-17467	8.2	HIGH		0.003		IBM Cloud Pak for Data System (Yosemite 1.0) 3.0.5.2 could allow a remote attacker to obtain sensitive information due to the use of weak or deprecated cryptographic protocols.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-76413	8.2	HIGH				A vulnerability in Cisco Adaptive Security Device Manager (ASDM) single sign-on (SSO) handler for Cisco Secure FMC Software could allow an unauthenticated, remote attacker to log in as the Cisco ASDM administrator user. This vulnerability is due to improper management of the Cisco ASDM SSO token. An attacker could exploit this vulnerability by performing session token forgery techniques. A successful exploit co...
CVE-2026-78252	8.2	HIGH		0.004		GitLab has remediated an issue in GitLab CE/EE affecting all versions from 15.3 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that, under certain conditions, an authenticated user could have induced a targeted user to perform unintended state-changing HTTP requests due to improper sanitization of user-controlled data in the Markdown JSON table renderer.
CVE-2026-83047	8.2	HIGH		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Runtime Tools). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...
CVE-2026-83078	8.2	HIGH		0.004		Vulnerability in the Siebel CRM Cloud Applications product of Oracle Siebel CRM (component: Siebel Cloud Manager). Supported versions that are affected are 22.3-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM Cloud Applications. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete acce...
CVE-2026-83085	8.2	HIGH		0.002		Vulnerability in the Siebel CRM Cloud Applications product of Oracle Siebel CRM (component: Siebel Cloud Manager). Supported versions that are affected are 22.3-26.7. Easily exploitable vulnerability allows low privileged attacker with access to the physical communication segment attached to the hardware where the Siebel CRM Cloud Applications executes to compromise Siebel CRM Cloud Applications. While the vulne...
CVE-2026-83087	8.2	HIGH		0.003		Vulnerability in the Siebel CRM Cloud Applications product of Oracle Siebel CRM (component: Siebel Cloud Manager). Supported versions that are affected are 22.3-26.7. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Cloud Applications. While the vulnerability is in Siebel CRM Cloud Applications, attacks may significantly impact additional pro...
CVE-2026-83181	8.2	HIGH		0.003		Vulnerability in the Siebel CRM Development product of Oracle Siebel CRM (component: Workspaces). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM Development. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Siebel CRM Dev...
CVE-2026-83215	8.2	HIGH		0.004		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Siebe...
CVE-2026-83234	8.2	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Experience Manager). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability...
CVE-2026-83236	8.2	HIGH		0.002		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Experience Manager). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks require human interac...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83248	8.2	HIGH		0.004		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result i...
CVE-2026-83265	8.2	HIGH		0.004		Vulnerability in the Oracle Web Services Manager product of Oracle Fusion Middleware (component: Web Services Agent). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Web Services Manager. Successful attacks of this vulnerability can result in unauthorized access to critical dat...
CVE-2026-83266	8.2	HIGH		0.004		Vulnerability in the Oracle JDeveloper product of Oracle Fusion Middleware (component: Resource Catalog Services). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle JDeveloper. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...
CVE-2026-83343	8.2	HIGH		0.004		Vulnerability in the Oracle Utilities Network Management System product of Oracle Utilities Applications (component: System Wide). Supported versions that are affected are 2.5.0.2.0-2.5.0.2.13, 2.6.0.1.0-2.6.0.12B, 2.6.0.2.0-2.6.0.2.10A and 25.12.0.0.0-25.12.0.0.3. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Utilities Network Management Syste...
CVE-2026-83418	8.2	HIGH		0.003		Vulnerability in the Oracle Communications Cloud Native Core Security Edge Protection Proxy product of Oracle Communications (component: SEPP). Supported versions that are affected are 26.1.200 and 25.2.201. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Communications Cloud Native Core Security Edge Protection Proxy. While the vulnerability i...
CVE-2026-83435	8.2	HIGH		0.003		Vulnerability in the Oracle Bills of Material product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.13-12.2.15. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Bills of Material. While the vulnerability is in Oracle Bills of Material, attacks may significantly impact additional product...
CVE-2026-83438	8.2	HIGH		0.003		Vulnerability in the Oracle Engineering product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Engineering. While the vulnerability is in Oracle Engineering, attacks may significantly impact additional products (scope change). ...
CVE-2026-83461	8.2	HIGH		0.003		Vulnerability in the Oracle Mobile Application Server product of Oracle E-Business Suite (component: MWA Terminal Server). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Mobile Application Server. Successful attacks of this vulnerability can result in unauthorized access to critical data o...
CVE-2026-83465	8.2	HIGH		0.002		Vulnerability in the Oracle Mobile Application Server product of Oracle E-Business Suite (component: MWA Terminal Server). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Mobile Application Server. Successful attacks require human interaction from a person other than the attacker and while ...
CVE-2026-85596	8.2	HIGH		0.002	traefik:traefik	Traefik versions >= v3.7.0 and <= v3.7.10 contain an authentication bypass in the Kubernetes Ingress NGINX provider. The TLS option generated for an Ingress carrying the nginx.ingress.kubernetes.io/auth-tls-secret annotation was named after the Ingress namespace and name. As a result, two Ingress objects sharing the same host, the same client CA secret, and the same client-authentication mode produced two distinct...
CVE-2026-85921	8.2	HIGH		0.003		Double free in Windows Secure Kernel Mode allows an authorized attacker to elevate privileges locally.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87174	8.2	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...
CVE-2026-87196	8.2	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complet...
CVE-2026-87197	8.2	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complet...
CVE-2026-87200	8.2	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification...
CVE-2026-87228	8.2	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complet...
CVE-2026-87229	8.2	HIGH		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification...
CVE-2026-87266	8.2	HIGH		0.004		Vulnerability in the Oracle Agile PLM product of Oracle Supply Chain (component: Application Server). The supported version that is affected is 9.3.6. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Agile PLM. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Oracle Agile PLM a...
CVE-2026-88032	8.2	HIGH		0.002	mongodb:java_driver	A use-after-free in the reactive client-side encryption component of the MongoDB Java Driver can cause native resources to be freed while an affected encrypted operation is still using them when the operation is cancelled. A party able to cause such an operation to be cancelled may cause the hosting application process to terminate. Reaching the issue requires an affected reactive encryption configuration that ret...
CVE-2026-89973	8.2	HIGH				In the Linux kernel, the following vulnerability has been resolved: nvme-tcp: check the data direction of a C2HData PDU nvme_tcp_handle_c2h_data() finds the request by command id and checks that it has a payload, but it does not check that the command asked for data to be read. A controller that answers a write command with C2HData therefore reaches nvme_tcp_rcv_data(), where _copy_to_iter() hits WARN_ON_ONCE(...
CVE-2026-92591	8.2	HIGH				Craft CMS 5.0.0 through 5.10.12 treats a database connection failure as meaning that Craft is not installed, which makes anonymous installer actions — including install/validate-site — reachable on an installed production site whenever PHP remains available but the configured MySQL endpoint does not. The action accepts a site name, serializes it through Site::getName(), and expands \${NAME} expressions using App::e...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-11728	8.1	HIGH		0.006		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 could allow a remote attacker to cause a denial of service or potentially execute arbitrary code in the client due to a heap buffer overflow when receiving messages from a malicious queue manager or through a man-in-the-m...
CVE-2026-12355	8.1	HIGH		0.004		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 could allow an attacker to perform JNDI injection attacks due to insufficient input validation, potentially leading to information disclosure or remote code execution.
CVE-2026-12666	8.1	HIGH		0.003		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 Classes for Java could allow an authenticated attacker to obtain sensitive information or cause a denial of service due to XML external entity injection in MQRFH2 header processing.
CVE-2026-16335	8.1	HIGH		0.004		IBM DataStage on Cloud Pak for Data 5.4.0.0 IBM DataStage could allow a remote authenticated attacker to read, write, or delete arbitrary files due to a path traversal vulnerability.
CVE-2026-18215	8.1	HIGH		0.002	redhat:build_of_keycloak	Keycloak provides a way to let users log in using Microsoft accounts while restricting access to a specific organization (tenant). A flaw was discovered where this restriction is ignored when using the token exchange feature. This means an attacker with a valid Microsoft token from a completely different organization could gain access to the Keycloak realm, potentially accessing sensitive data or performing unauth...
CVE-2026-20335	8.1	HIGH				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Secure Adaptive Security Appliance Software, Cisco Secure Firewall Threat Defense Software and Cisco Secure Firewall Management Center Software engineering team has conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabil...
CVE-2026-58065	8.1	HIGH		0.007	apache:apache-airflow-providers-git	The Apache Airflow Git provider runs its git-over-SSH operations with `StrictHostKeyChecking=no` by default, disabling SSH host-key verification. An attacker who can intercept the network path between an Airflow worker and the Git server can impersonate the server (man-in-the-middle), capturing the SSH deploy key or injecting malicious repository content. Deployments that use the Git DAG bundle or Git provider to ...
CVE-2026-59245	8.1	HIGH		0.006	apache:apache-airflow-providers-fab	In the Apache Airflow FAB auth manager, a DAG whose `dag_id` is `DAGs` collided with the global all-DAGs permission resource name produced by `resource_name()`, so a user granted per-DAG `access_control` on that one DAG was silently granted the global all-DAGs permission (privilege escalation). The escalation triggers when a DAG named `DAGs` exists and a lower-privileged user is given per-DAG access to it, grantin...
CVE-2026-63671	8.1	HIGH				MDC is a tool to take regular Markdown and write documents interacting deeply with a Vue component. Prior to 0.22.1, @nuxtjs/mdc uses parseMarkdown with allowDangerousHtml enabled by default and relies on validateProps, validateProp, and unsafeLinkPrefix to remove executable URLs from untrusted Markdown. validateProp checks only attributes named href or src, allowing an SVG xlink:href value represented as xLinkHre...
CVE-2026-69813	8.1	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in Windows DNS allows an unauthorized attacker to execute code over a network.
CVE-2026-69858	8.1	HIGH		0.007	microsoft:windows_server_2022, microsoft:windows_server_2025	Use after free in Windows DNS allows an unauthorized attacker to execute code over a network.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-69989	8.1	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in DNS Server allows an unauthorized attacker to execute code over a network.
CVE-2026-70342	8.1	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Ancillary Function Driver for WinSock allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-70563	8.1	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper link resolution before file access ('link following') in Windows Shell allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-73951	8.1	HIGH		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Portlet Services). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in takeover of Oracle WebCenter Portal. CVSS 3....
CVE-2026-73954	8.1	HIGH		0.003		Vulnerability in the PeopleSoft Enterprise PeopleTools product of Oracle PeopleSoft (component: Business Interlink). Supported versions that are affected are 8.61-8.63. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise PeopleSoft Enterprise PeopleTools. Successful attacks of this vulnerability can result in takeover of PeopleSoft Enterprise PeopleTools....
CVE-2026-73958	8.1	HIGH		0.003		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Authentication Engine). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Access Manager. Successful attacks of this vulnerability can result in takeover of Oracle Access Manager. CVSS 3.1...
CVE-2026-78450	8.1	HIGH		0.005	microsoft:windows_10_1809, microsoft:windows_server_2019, microsoft:windows_server_2022, microsoft:windows_server_2025	Use after free in Reliable Multicast Transport Driver (RMCAT) allows an unauthorized attacker to execute code over a network.
CVE-2026-81268	8.1	HIGH		0.003	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow a remote authenticated attacker to execute flows and obtain sensitive information due to insufficient session expiration of API keys after user deactivation.
CVE-2026-81551	8.1	HIGH		0.005	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to arbitrarily write to or delete files on shared storage due to a path traversal vulnerability.
CVE-2026-83010	8.1	HIGH		0.003		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle WebCenter Enterprise Capture. Successful attacks require human interaction from a person other than the attack...
CVE-2026-83011	8.1	HIGH		0.004		Vulnerability in the Oracle Platform Security for Java product of Oracle Fusion Middleware (component: Centralized Thirdparty Jars). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Platform Security for Java. Successful attacks of this vulnerability can result in takeover of O...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83014	8.1	HIGH		0.004		Vulnerability in the PeopleSoft Enterprise PeopleTools product of Oracle PeopleSoft (component: Cube Manager). Supported versions that are affected are 8.61-8.63. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise PeopleSoft Enterprise PeopleTools. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access...
CVE-2026-83019	8.1	HIGH		0.004		Vulnerability in the PeopleSoft Enterprise PeopleTools product of Oracle PeopleSoft (component: SQR). Supported versions that are affected are 8.61-8.63. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise PeopleSoft Enterprise PeopleTools. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all ...
CVE-2026-83067	8.1	HIGH		0.003		Vulnerability in the Oracle JDeveloper product of Oracle Fusion Middleware (component: ADF Shared Components). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle JDeveloper. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification acces...
CVE-2026-83072	8.1	HIGH		0.004		Vulnerability in the Oracle Applications Framework product of Oracle E-Business Suite (component: Search Bean [Incl. Advanced]). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Applications Framework. Successful attacks of this vulnerability can result in unauthorized creation, deletion or...
CVE-2026-83073	8.1	HIGH		0.002		Vulnerability in the Siebel CRM Cloud Applications product of Oracle Siebel CRM (component: Siebel Cloud Manager). Supported versions that are affected are 22.3-26.7. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Siebel CRM Cloud Applications executes to compromise Siebel CRM Cloud Applications. Successful att...
CVE-2026-83089	8.1	HIGH		0.004		Vulnerability in the Oracle Alert product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Alert. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical data or all...
CVE-2026-83101	8.1	HIGH		0.003		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Forms. Successful attacks of this vulnerability can result in takeover of Oracle Forms. CVSS 3.1 Base Score 8.1 (C...
CVE-2026-83132	8.1	HIGH		0.004		Vulnerability in the Oracle iStore product of Oracle E-Business Suite (component: Shopping Cart). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle iStore. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical data or all Ora...
CVE-2026-83143	8.1	HIGH		0.004		Vulnerability in the Siebel Apps - Life Sciences product of Oracle Siebel CRM (component: eDetailing). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel Apps - Life Sciences. Successful attacks require human interaction from a person other than the attacker. Successful attacks of this vulnerabilit...
CVE-2026-83152	8.1	HIGH		0.004		Vulnerability in the Oracle Project Intelligence product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Project Intelligence. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83169	8.1	HIGH		0.004		Vulnerability in the Oracle One-to-One Fulfillment product of Oracle E-Business Suite (component: Java Server Issues). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle One-to-One Fulfillment. Successful attacks of this vulnerability can result in takeover of Oracle One-to-One Fulfillment. ...
CVE-2026-83174	8.1	HIGH		0.004		Vulnerability in the Oracle CRM Technical Foundation product of Oracle E-Business Suite (component: Application Framework). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle CRM Technical Foundation. Successful attacks of this vulnerability can result in unauthorized creation, deletion or mod...
CVE-2026-83177	8.1	HIGH		0.004		Vulnerability in the Oracle One-to-One Fulfillment product of Oracle E-Business Suite (component: Documents). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle One-to-One Fulfillment. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access...
CVE-2026-83191	8.1	HIGH		0.004		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Difficult to exploit vulnerability allows unauthenticated attacker with network access via TCP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deployment. CVSS 3.1 Base Score 8.1 (Confiden...
CVE-2026-83192	8.1	HIGH		0.003		Vulnerability in the Siebel CRM End User product of Oracle Siebel CRM (component: Open UI). Supported versions that are affected are 17.0-26.7. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM End User. Successful attacks of this vulnerability can result in takeover of Siebel CRM End User. CVSS 3.1 Base Score 8.1 (Confidentiality, Integrity ...
CVE-2026-83220	8.1	HIGH		0.002		Vulnerability in the Siebel CRM Integration product of Oracle Siebel CRM (component: Event Publish and Subscribe). Supported versions that are affected are 23.6-26.7. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Siebel CRM Integration executes to compromise Siebel CRM Integration. Successful attacks of this v...
CVE-2026-83245	8.1	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result...
CVE-2026-83246	8.1	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result...
CVE-2026-83254	8.1	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result ...
CVE-2026-83255	8.1	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83256	8.1	HIGH		0.004		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result ...
CVE-2026-83258	8.1	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result...
CVE-2026-83286	8.1	HIGH		0.004		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can r...
CVE-2026-83297	8.1	HIGH		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via LDAP to compromise Oracle BI Publisher. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificatio...
CVE-2026-83299	8.1	HIGH		0.004		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Analytics Web General). The supported version that is affected is 12.2.1.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can result in takeover of O...
CVE-2026-83308	8.1	HIGH		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via SOAP to compromise Oracle BI Publisher. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificatio...
CVE-2026-83314	8.1	HIGH		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: Web Service API). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via SOAP to compromise Oracle BI Publisher. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification acc...
CVE-2026-83351	8.1	HIGH		0.003		Vulnerability in the RDBMS component of Oracle Database Server. Supported versions that are affected are 23.4.0-23.26.3. Difficult to exploit vulnerability allows unauthenticated attacker with network access via Oracle Net to compromise RDBMS. Successful attacks of this vulnerability can result in takeover of RDBMS. CVSS 3.1 Base Score 8.1 (Confidentiality, Integrity and Availability impacts). CVSS Vector: (CVS...
CVE-2026-83357	8.1	HIGH		0.003		Vulnerability in the Oracle GraalVM for JDK, Oracle GraalVM product of Oracle Java SE (component: Compiler). The supported version that is affected is Oracle GraalVM for JDK 17: 23.0.13.1; Oracle GraalVM for JDK 21: 23.1.12.1; Oracle GraalVM: 25.0.4.1. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle GraalVM for JDK, Oracle GraalVM. Successful...
CVE-2026-83408	8.1	HIGH		0.003		Vulnerability in the Oracle GraalVM for JDK, Oracle GraalVM product of Oracle Java SE (component: Compiler). The supported version that is affected is Oracle GraalVM for JDK 17: 23.0.13.1; Oracle GraalVM for JDK 21: 23.1.12.1; Oracle GraalVM: 25.0.4.1. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle GraalVM for JDK, Oracle GraalVM. Successful...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83412	8.1	HIGH		0.004		Vulnerability in the Oracle Coherence product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0, 14.1.1.0.0, 14.1.2.0.0 and 15.1.1.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via TCP to compromise Oracle Coherence. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification a...
CVE-2026-83422	8.1	HIGH		0.004		Vulnerability in the Oracle Identity Manager product of Oracle Fusion Middleware (component: OIM Legacy UI). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Identity Manager. Successful attacks require human interaction from a person other than the attacker. Successful attacks o...
CVE-2026-83428	8.1	HIGH		0.004		Vulnerability in the Oracle Demand Signal Repository product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Demand Signal Repository. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modif...
CVE-2026-83429	8.1	HIGH		0.004		Vulnerability in the Oracle Demand Signal Repository product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Demand Signal Repository. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modif...
CVE-2026-83430	8.1	HIGH		0.004		Vulnerability in the Oracle Product Workbench product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Workbench. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access...
CVE-2026-83432	8.1	HIGH		0.004		Vulnerability in the Oracle Depot Repair product of Oracle E-Business Suite (component: Estimate and Actual Charges). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Depot Repair. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access t...
CVE-2026-83434	8.1	HIGH		0.003		Vulnerability in the Oracle Product Workbench product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Workbench. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access...
CVE-2026-83439	8.1	HIGH		0.004		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: helidon-security-providers-idcs-mapper). Supported versions that are affected are 3.0.0-3.2.20 and 4.0.0-4.5.4. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access...
CVE-2026-83446	8.1	HIGH		0.004		Vulnerability in the Oracle Financials Common Modules product of Oracle E-Business Suite (component: Common Components). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Financials Common Modules. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modif...
CVE-2026-83447	8.1	HIGH		0.004		Vulnerability in the Oracle Bills of Material product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Bills of Material. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83448	8.1	HIGH		0.003		Vulnerability in the Oracle Bills of Material product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Bills of Material. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access...
CVE-2026-83455	8.1	HIGH		0.004		Vulnerability in the Oracle Demand Signal Repository product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Demand Signal Repository. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modif...
CVE-2026-83457	8.1	HIGH		0.004		Vulnerability in the Oracle Demand Signal Repository product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Demand Signal Repository. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modif...
CVE-2026-83464	8.1	HIGH		0.003		Vulnerability in the Oracle Mobile Application Server product of Oracle E-Business Suite (component: MWA Terminal Server). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Mobile Application Server. Successful attacks of this vulnerability can result in takeover of Oracle Mobile Application...
CVE-2026-83477	8.1	HIGH		0.003		Vulnerability in the Oracle Work in Process product of Oracle E-Business Suite (component: Workbenches). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Work in Process executes to compromise Oracle Work in Process. Successful attacks of this vulner...
CVE-2026-87152	8.1	HIGH		0.004		Vulnerability in the Oracle Installed Base product of Oracle E-Business Suite (component: Create Item Instance). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Installed Base. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to c...
CVE-2026-87153	8.1	HIGH		0.004		Vulnerability in the Oracle Product Hub product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Hub. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical...
CVE-2026-87154	8.1	HIGH		0.004		Vulnerability in the Oracle Product Hub product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Hub. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical...
CVE-2026-87157	8.1	HIGH		0.004		Vulnerability in the Oracle Order Management product of Oracle E-Business Suite (component: Product Diagnostic Tools). Supported versions that are affected are 12.2.4-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Order Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification acc...
CVE-2026-87159	8.1	HIGH		0.003		Vulnerability in the Oracle HRMS (India) product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle HRMS (India). Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critic...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87166	8.1	HIGH		0.004		Vulnerability in the Oracle Purchasing product of Oracle E-Business Suite (component: Other issue). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Purchasing. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical data or a...
CVE-2026-87167	8.1	HIGH		0.003		Vulnerability in the Oracle Purchasing product of Oracle E-Business Suite (component: G-Invoicing). Supported versions that are affected are 12.2.11-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Purchasing. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical data or ...
CVE-2026-87168	8.1	HIGH		0.003		Vulnerability in the Oracle Purchasing product of Oracle E-Business Suite (component: G-Invoicing). Supported versions that are affected are 12.2.10-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Purchasing. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical data or ...
CVE-2026-87218	8.1	HIGH		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. S...
CVE-2026-87231	8.1	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Manageme...
CVE-2026-87232	8.1	HIGH		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. S...
CVE-2026-87234	8.1	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification ...
CVE-2026-87241	8.1	HIGH		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. S...
CVE-2026-87265	8.1	HIGH		0.003		Vulnerability in the Oracle Purchasing product of Oracle E-Business Suite (component: Other issue). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Purchasing. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical data or a...
CVE-2026-87286	8.1	HIGH		0.002		Vulnerability in the Oracle GraalVM product of Oracle Java SE (component: Compiler). The supported version that is affected is Oracle GraalVM: 25.0.4.1. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle GraalVM. Successful attacks of this vulnerability can result in takeover of Oracle GraalVM. CVSS 3.1 Base Score 8.1 (Confidentiality, Integrity ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87287	8.1	HIGH		0.002		Vulnerability in the Oracle GraalVM product of Oracle Java SE (component: Compiler). The supported version that is affected is Oracle GraalVM: 25.0.4.1. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle GraalVM. Successful attacks of this vulnerability can result in takeover of Oracle GraalVM. CVSS 3.1 Base Score 8.1 (Confidentiality, Integrity ...
CVE-2026-87288	8.1	HIGH		0.002		Vulnerability in the Oracle GraalVM product of Oracle Java SE (component: Compiler). The supported version that is affected is Oracle GraalVM: 25.0.4.1. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle GraalVM. Successful attacks of this vulnerability can result in takeover of Oracle GraalVM. CVSS 3.1 Base Score 8.1 (Confidentiality, Integrity ...
CVE-2026-89848	8.1	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Quiesce response IRQ before freeing request queue qla2xxx_delete_qpair() deletes the request queue before the response queue. qla25xx_delete_req_que() frees the request queue memory (kfree(req) in qla25xx_free_req_que()), but the response-queue MSI-X is only released later, in qla25xx_free_rsp_que(). In that window the response in...
CVE-2026-89861	8.1	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Hold vport reference in qla24xx_report_id_acquisition() In the format 1 path, the virtual port is located on ha->vp_list while holding vport_slock, but the lock is dropped before vp is used: qla_update_host_map() is called and VP_IDX_ACQUIRED/REGISTER_FC4_NEEDED/ REGISTER_FDMI_NEEDED are set on vp. No reference is taken across tha...
CVE-2026-89999	8.1	HIGH				In the Linux kernel, the following vulnerability has been resolved: HID: wacom: validate report length in wacom_intuos_pro2_bt_irq wacom_intuos_pro2_bt_irq() receives the wire report length in `len` but never consults it before parsing. After the report-id gate it unconditionally calls wacom_intuos_pro2_bt_pen() and then, selected by features.type, a fixed chain of sub-parsers, none of which receive `len`: wac...
CVE-2026-55225	8.0	HIGH		0.002		Strimzi provides a way to run an Apache Kafka cluster on Kubernetes or OpenShift in various deployment configurations. In Strimzi 1.0.0 and earlier, an attacker who can create a Kafka custom resource can set Kafka.spec.entityOperator watchedNamespace to a target namespace, causing the Cluster Operator to create a Role with full Secret CRUD permissions there and bind it to the Entity Operator ServiceAccount in the ...
CVE-2026-69423	8.0	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Video Driver allows an authorized attacker to elevate privileges over a network.
CVE-2026-69503	8.0	HIGH		0.008	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Stack-based buffer overflow in Windows USB Driver allows an authorized attacker to elevate privileges over a network.
CVE-2026-83081	8.0	HIGH		0.002		Vulnerability in the Oracle Banking Corporate Lending product of Oracle Financial Services Applications (component: Core). Supported versions that are affected are 14.5.0.0.0-14.9.0.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Banking Corporate Lending executes to compromise Oracle Banking Corpor...
CVE-2026-83138	8.0	HIGH		0.003		Vulnerability in the Oracle Spares Management product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Spares Management. While the vulnerability is in Oracle Spares Management, attacks may significantly impact additional product...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83157	8.0	HIGH		0.003		Vulnerability in the Oracle Applications Manager product of Oracle E-Business Suite (component: Command Line - RapidClone). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Applications Manager. While the vulnerability is in Oracle Applications Manager, attacks may significantly impact add...
CVE-2026-83170	8.0	HIGH		0.003		Vulnerability in the Oracle One-to-One Fulfillment product of Oracle E-Business Suite (component: Documents). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with access to the physical communication segment attached to the hardware where the Oracle One-to-One Fulfillment executes to compromise Oracle One-to-One Fulfillment. Successful atta...
CVE-2026-83178	8.0	HIGH		0.004		Vulnerability in the Oracle Application Object Library product of Oracle E-Business Suite (component: Core). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Application Object Library. While the vulnerability is in Oracle Application Object Library, attacks may significantly impact additi...
CVE-2026-83450	8.0	HIGH		0.004		Vulnerability in the Oracle Bills of Material product of Oracle E-Business Suite (component: Setup Workbench). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Bills of Material. While the vulnerability is in Oracle Bills of Material, attacks may significantly impact additional products (s...
CVE-2026-83483	8.0	HIGH		0.004		Vulnerability in the Oracle Advanced Benefits product of Oracle E-Business Suite (component: Self-serv What-if Analysis). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Advanced Benefits. While the vulnerability is in Oracle Advanced Benefits, attacks may significantly impact additional ...
CVE-2026-85469	8.0	HIGH				A flaw was found in quay-builder-qemu. A remote attacker could exploit this by compromising the upstream `Noelware/docker-manifest-action` used in the release workflow, which is pinned to a mutable branch. This allows the attacker to inject arbitrary code, leading to the exfiltration of sensitive registry credentials or the publication of malicious images. The workflow also exposes the default GitHub token, increa...
CVE-2026-87164	8.0	HIGH		0.002		Vulnerability in the Oracle Banking Branch product of Oracle Financial Services Applications (component: Reports). Supported versions that are affected are 14.5.0.0.0-14.9.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Banking Branch. Successful attacks require human interaction from a person other than the attacker and while the vulnera...
CVE-2026-87243	8.0	HIGH		0.001		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. ...
CVE-2026-87245	8.0	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with access to the physical communication segment attached to the hardware where the Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. Su...
CVE-2026-89947	8.0	HIGH				In the Linux kernel, the following vulnerability has been resolved: clk: meson: align gxbb_32k_clk_sel number of parents with actual count The following out-of-bounds read has been observed by Christian on a GXBB WeTek Hub: ===== BUG: KASAN: global-out-of-bounds in __clk_register+0x1b70/0x2418 Read of size 8 at addr ffff66320cf88e0 by task swapper/0/1...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89954	8.0	HIGH				In the Linux kernel, the following vulnerability has been resolved: mtd: afs: validate v2 image info bounds The AFS v2 parser uses footer[8] to locate the image information block inside the current erase block, then uses the image information region_count to walk entries from a fixed local array. The footer offset and region count come from flash contents and are not checked against the erase block or the local ...
CVE-2026-92127	8.0	HIGH				Jenkins Script Security Plugin 1415.v9a_f9b_3a_c253d and earlier automatically approves the classpath entries in an item configuration when a user with Overall/Administer permission copies the item, or updates that configuration through the REST API or CLI, allowing attackers able to define classpath entries to execute arbitrary code in the context of the Jenkins controller JVM.
CVE-2026-92134	8.0	HIGH				Jenkins Warnings Plugin 13.10258.va_17d49a_78c3b_ and earlier does not validate the analysis results ID when a job configuration is submitted through the REST API, allowing attackers with Item/Configure permission to use a javascript: scheme URL as identifier, resulting in a stored cross-site scripting (XSS) vulnerability.
CVE-2026-92135	8.0	HIGH				Jenkins Coverage Plugin 3.3358.v9487dde48783 and earlier does not validate the coverage results ID when a job configuration is submitted through the REST API, allowing attackers with Item/Configure permission to use a javascript: scheme URL as identifier, resulting in a stored cross-site scripting (XSS) vulnerability.
CVE-2026-92136	8.0	HIGH				Jenkins OWASP Dependency-Check Plugin 5.6.4 and earlier does not escape CWE values from Dependency-Check reports on the Jenkins UI, resulting in a stored cross-site scripting (XSS) vulnerability exploitable by attackers with Item/Configure permission.
CVE-2026-83022	7.9	HIGH		0.002		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle WebCenter Enterprise Capture executes to compromise Oracle WebCent...
CVE-2026-83079	7.9	HIGH		0.002		Vulnerability in the Siebel CRM Cloud Applications product of Oracle Siebel CRM (component: Siebel Cloud Manager). Supported versions that are affected are 22.3-26.7. Easily exploitable vulnerability allows high privileged attacker with logon to the infrastructure where Siebel CRM Cloud Applications executes to compromise Siebel CRM Cloud Applications. While the vulnerability is in Siebel CRM Cloud Applications,...
CVE-2026-83096	7.9	HIGH		0.002		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Forms. Successful attacks require human interaction from a person other than the attacker and while the vulnerabili...
CVE-2026-89911	7.9	HIGH				In the Linux kernel, the following vulnerability has been resolved: KVM: arm64: Correctly cap TLBI Range to the architectural limit TLB Invalidation by Range has a fairly powerful way of encoding pretty large ranges in a small number of bits. This range can be based on an arbitrary VA, which means it is pretty easy for a guest to generate an overflow should the hypervisor be naive enough to add the range to the bas...
CVE-2026-17133	7.8	HIGH		0.001		IBM App Connect Enterprise 13.0.1.0 through 13.0.8.0, and 12.0.1.0 through 12.0.12.27 could allow a local attacker to execute arbitrary code due to improper neutralization of special elements used in an OS command.
CVE-2026-17156	7.8	HIGH		0.001		IBM App Connect Enterprise 13.0.1.0 through 13.0.8.0, and 12.0.1.0 through 12.0.12.27 could allow a local attacker to execute arbitrary code due to insecure deserialization.
CVE-2026-17416	7.8	HIGH		0.001		IBM App Connect Enterprise 13.0.1.0 through 13.0.8.0, and 12.0.1.0 through 12.0.12.27 could allow a local attacker to execute arbitrary code due to insecure deserialization.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-27238	7.8	HIGH		0.002	adobe:indesign, apple:macos, microsoft:windows	InDesign Desktop versions 20.5.2, 21.2 and earlier are affected by a Heap-based Buffer Overflow vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-45998	7.8	HIGH		0.001	linux:linux_kernel	In the Linux kernel, the following vulnerability has been resolved: rxrpc: Fix potential UAF after skb_unshare() failure If skb_unshare() fails to unshare a packet due to allocation failure in rxrpc_input_packet(), the skb pointer in the parent (rxrpc_io_thread()) will be NULL'd out. This will likely cause the call to trace_rxrpc_rx_done() to oops. Fix this by moving the unsharing down to where rxrpc_input_cal...
CVE-2026-46117	7.8	HIGH		0.001	linux:linux_kernel	In the Linux kernel, the following vulnerability has been resolved: RDMA/mana: Remove user triggerable WARN_ON() in mana_ib_create_qp_rss() Sashiko points out that the user can specify WQs sharing the same CQ as a part of the uAPI and this will trigger the WARN_ON() then go on to corrupt the kernel. Just reject it outright and fail the QP creation.
CVE-2026-53000	7.8	HIGH		0.001	linux:linux_kernel, redhat:enterprise_linux	In the Linux kernel, the following vulnerability has been resolved: netfilter: nat: use kfree_rcu to release ops Florian Westphal says: "Historically this is not an issue, even for normal base hooks: the data path doesn't use the original nf_hook_ops that are used to register the callbacks. However, in v5.14 I added the ability to dump the active netfilter hooks from userspace. This code will peek back into t...
CVE-2026-53016	7.8	HIGH		0.001	linux:linux_kernel	In the Linux kernel, the following vulnerability has been resolved: crypto: ccp - copy IV using skcipher ivsize AF_ALG rfc3686-ctr-aes-ccp requests pass an 8-byte IV to the driver. ccp_aes_complete() restores AES_BLOCK_SIZE bytes into the caller's IV buffer while RFC3686 skciphers expose an 8-byte IV, so the restore overruns the provided buffer. Use crypto_skcipher_ivsize() to copy only the algorithm's IV length.
CVE-2026-59974	7.8	HIGH				Stanza is a Stanford NLP Python library for tokenization, sentence segmentation, NER, and parsing of many human languages. Prior to 1.14.0, stanza.resources.common.unzip in stanza/resources/common.py passes downloaded model and resource archives to zipfile.ZipFile.extractall without validating member paths, and the vulnerable extraction path is reachable through stanza.download and stanza.install_corenlp. A malici...
CVE-2026-63325	7.8	HIGH				Redocly CLI makes OpenAPI validation, linting, and documentation workflows easier. Prior to version 2.33.0 of @redocly/respect-core and @redocly/cli, the respect command dynamically evaluates \$faker runtime expressions in Arazzo descriptions. A crafted expression can traverse constructor, prototype, or __proto__ properties in packages/respect-core/src/modules/context-parser/get-value-from-context.ts, reach the Jav...
CVE-2026-67309	7.8	HIGH		0.005	traefik:traefik	Traefik versions >= v3.7.0 and <= v3.7.7 contain a path traversal vulnerability in the Kubernetes Ingress NGINX provider's RewriteTarget middleware (generated from the nginx.ingress.kubernetes.io/rewrite-target annotation). When an Ingress path uses a regex that captures attacker-controlled text without requiring a path separator (e.g., path /api.(*) with rewrite target /\$1), a crafted request such as /api../admin...
CVE-2026-69270	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69295	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Driver allows an authorized attacker to elevate privileges locally.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-69307	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69571	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69584	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows USB Video Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69687	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer underflow (wrap or wraparound) in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69707	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69822	7.8	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Numeric truncation error in Windows Kerberos allows an authorized attacker to elevate privileges locally.
CVE-2026-69841	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Encrypting File System (EFS) allows an authorized attacker to elevate privileges locally.
CVE-2026-69844	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Win32K allows an authorized attacker to elevate privileges locally.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-69864	7.8	HIGH		0.002	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Use after free in Windows Hello allows an authorized attacker to elevate privileges locally.
CVE-2026-69900	7.8	HIGH		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Untrusted pointer dereference in Kernel Streaming WOW Thunk Service Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69907	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper handling of insufficient permissions or privileges in Windows Enterprise App Management allows an authorized attacker to elevate privileges locally.
CVE-2026-69921	7.8	HIGH		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Heap-based buffer overflow in Windows Print Spooler Components allows an authorized attacker to elevate privileges locally.
CVE-2026-70564	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Print Spooler Components allows an authorized attacker to elevate privileges locally.
CVE-2026-70569	7.8	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Out-of-bounds read in Windows Spaceport.sys allows an authorized attacker to elevate privileges locally.
CVE-2026-71334	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NFS Portmapper allows an authorized attacker to elevate privileges locally.
CVE-2026-77500	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Release of invalid pointer or reference in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-82992	7.8	HIGH		0.002		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Installation). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Siebel CRM Deployment executes to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deployment. CVS...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-82996	7.8	HIGH		0.002		Vulnerability in the Oracle Platform Security for Java product of Oracle Fusion Middleware (component: Centralized Thirdparty Jars). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Platform Security for Java executes to compromise Oracle Platform Security for Java. Successful attacks...
CVE-2026-83018	7.8	HIGH		0.002		Vulnerability in the PeopleSoft Enterprise PeopleTools product of Oracle PeopleSoft (component: SQR). Supported versions that are affected are 8.61-8.63. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where PeopleSoft Enterprise PeopleTools executes to compromise PeopleSoft Enterprise PeopleTools. Successful attacks of this vulnerability can result in takeover of...
CVE-2026-83024	7.8	HIGH		0.002		Vulnerability in the Oracle Identity Manager Connector product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Identity Manager Connector executes to compromise Oracle Identity Manager Connector. Successful attacks of this vulnerability ...
CVE-2026-83071	7.8	HIGH		0.002		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Machine Learning). Supported versions that are affected are 8.2.0.0.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Business Intelligence Enterprise Edition executes to compromise Oracle Business Intelligence Enterprise Editi...
CVE-2026-83118	7.8	HIGH		0.002		Vulnerability in the Applications DBA product of Oracle E-Business Suite (component: AD Utilities). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Applications DBA executes to compromise Applications DBA. Successful attacks of this vulnerability can result in takeover of Applications DBA. CVSS 3.1 Bas...
CVE-2026-83147	7.8	HIGH		0.002		Vulnerability in the PeopleSoft Enterprise FIN Inventory Brazil product of Oracle PeopleSoft (component: Inventory). The supported version that is affected is 9.1. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where PeopleSoft Enterprise FIN Inventory Brazil executes to compromise PeopleSoft Enterprise FIN Inventory Brazil. Successful attacks of this vulnerabil...
CVE-2026-83159	7.8	HIGH		0.001		Vulnerability in the Applications DBA product of Oracle E-Business Suite (component: ADPatch). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with logon to the infrastructure where Applications DBA executes to compromise Applications DBA. Successful attacks require human interaction from a person other than the attacker. Successful attack...
CVE-2026-83211	7.8	HIGH		0.002		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Siebel CRM Deployment executes to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deploy...
CVE-2026-83214	7.8	HIGH		0.001		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Siebel CRM Deployment executes to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deploy...
CVE-2026-83216	7.8	HIGH		0.001		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Siebel CRM Deployment executes to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deploy...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83247	7.8	HIGH		0.002		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows unauthenticated attacker with logon to the infrastructure where Oracle Commerce Guided Search / Oracle Commerce Experience Manager executes to compromise Oracle Commerce Guided Search / Orac...
CVE-2026-83249	7.8	HIGH		0.001		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Commerce Guided Search / Oracle Commerce Experience Manager executes to compromise Oracle Commerce Guided Search / Ora...
CVE-2026-83253	7.8	HIGH		0.001		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Endeca Application Controller). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows unauthenticated attacker with logon to the infrastructure where Oracle Commerce Guided Search / Oracle Commerce Experience Manager executes to compromise Oracle Comme...
CVE-2026-83288	7.8	HIGH		0.002		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: BI Search). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Business Intelligence Enterprise Edition executes to compromise Oracle Business Intelligence Enterprise ...
CVE-2026-83290	7.8	HIGH		0.002		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). Supported versions that are affected are 8.2.0.0.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Business Intelligence Enterprise Edition executes to compromise Oracle Business Intelligence Enterprise Edit...
CVE-2026-83291	7.8	HIGH		0.002		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). Supported versions that are affected are 8.2.0.0.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Business Intelligence Enterprise Edition executes to compromise Oracle Business Intelligence Enterprise Edit...
CVE-2026-83293	7.8	HIGH		0.002		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: FNDN). The supported version that is affected is 12.2.1.4.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Business Intelligence Enterprise Edition executes to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of...
CVE-2026-83294	7.8	HIGH		0.002		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows unauthenticated attacker with logon to the infrastructure where Oracle Business Intelligence Enterprise Edition executes to compromise Oracle Business Intelligence En...
CVE-2026-83317	7.8	HIGH		0.002		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Installation). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Business Intelligence Enterprise Edition executes to compromise Oracle Business Intelligence Enterpri...
CVE-2026-83336	7.8	HIGH		0.002		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Analytics Server). Supported versions that are affected are 8.2.0.0.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Business Intelligence Enterprise Edition executes to compromise Oracle Business Intelligence Enterprise Editi...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83337	7.8	HIGH		0.002		Vulnerability in the Oracle Middleware Common Libraries and Tools product of Oracle Fusion Middleware (component: Remote Diagnostic Agent). Supported versions that are affected are 12.2.1.4.0, 14.1.1.0.0, 14.1.2.0.0 and 15.1.1.0.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Middleware Common Libraries and Tools executes to compromise Oracle Middl...
CVE-2026-83342	7.8	HIGH		0.001		Vulnerability in the Oracle Utilities Network Management System product of Oracle Utilities Applications (component: System Wide). Supported versions that are affected are 2.4.0.1.0-2.4.0.1.33, 2.5.0.1.0-2.5.0.1.19, 2.5.0.2.0-2.5.0.2.13, 2.6.0.1.0-2.6.0.12B, 2.6.0.2.0-2.6.0.2.10A and 25.12.0.0.0-25.12.0.0.3. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Or...
CVE-2026-83353	7.8	HIGH		0.001		Vulnerability in the Oracle WebCenter Content product of Oracle Fusion Middleware (component: Content Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle WebCenter Content executes to compromise Oracle WebCenter Content. Successful attacks of this vulnerability can result in tak...
CVE-2026-83420	7.8	HIGH		0.002		Vulnerability in the PeopleSoft Enterprise FIN Engineering Brazil product of Oracle PeopleSoft (component: Engineering). The supported version that is affected is 9.1. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where PeopleSoft Enterprise FIN Engineering Brazil executes to compromise PeopleSoft Enterprise FIN Engineering Brazil. Successful attacks of this vu...
CVE-2026-85892	7.8	HIGH		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Microsoft Edge (Chromium-based) allows an authorized attacker to elevate privileges locally.
CVE-2026-87216	7.8	HIGH		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can res...
CVE-2026-87268	7.8	HIGH		0.002		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. Successful attacks of this vulnerability can result in takeover of Oracle VM VirtualBox. Note: This v...
CVE-2026-87269	7.8	HIGH		0.001		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. Successful attacks of this vulnerability can result in takeover of Oracle VM VirtualBox. Note: This v...
CVE-2026-87270	7.8	HIGH		0.001		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. Successful attacks of this vulnerability can result in takeover of Oracle VM VirtualBox. Note: This v...
CVE-2026-87271	7.8	HIGH		0.002		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. Successful attacks of this vulnerability can result in takeover of Oracle VM VirtualBox. Note: This v...
CVE-2026-87272	7.8	HIGH		0.002		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. Successful attacks of this vulnerability can result in takeover of Oracle VM VirtualBox. CVSS 3.1 Bas...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89789	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: gtp: add synchronize_net() in gtp_newlink() error path to prevent use-after-free gtp_newlink()'s error path frees tid_hash and addr_hash without waiting for an RCU grace period after clearing sk_user_data. A concurrent gtp_encap_recv() in softirq may still hold the gtp_dev pointer obtained via rcu_dereference_sk_user_data() and access the freed ...
CVE-2026-89791	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: perf: Fix use-after-free when perf mmap() revival races with the last munmap() perf_mmap_close() drops rb->mmap_count *without* holding event->mmap_mutex (the refcount_dec_and_test() right before the refcount_dec_and_mutex_lock() of event->mmap_count). A concurrent perf_mmap_rb() can slot its entire "revival" path into that window (perf_mmap hol...
CVE-2026-89793	7.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ublk: clear VM_MAYWRITE on read-only ublk char device mmap ublk_ch_mmap() rejects mmap requests with VM_WRITE set, but never clears VM_MAYWRITE on the resulting read-only mapping. This allows a userspace daemon to mmap the per-queue command buffer PROT_READ, then upgrade it to PROT_WRITE via mprotect(), since VM_MAYWRITE was never cleared. The ...
CVE-2026-89799	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: bpf: Disable preemption in bpf_get_stackid The get_perf_callchain call needs disabled preemption plus we need it disabled as long as we access its returned trace entries buffer. Note the bpf_get_stackid_pe function is executed already with preemption disabled.
CVE-2026-89801	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/nouveau/uvmm: fix premature region free on failed OP_UNMAP_SPARSE In nouveau_uvmm_bind_job_submit()'s OP_UNMAP_SPARSE arm, op->reg is set from nouveau_uvma_region_find(), which only looks the region up and takes no reference; a region's sole reference is its membership in uvmm->region_mt. Two failure paths leave op->reg set: the -ENOENT chec...
CVE-2026-89803	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/nouveau: unsubscribe the channel-kill event before the fence context nouveau_channel_del() tears the fence context down first and only drops the channel-kill subscription later, in the middle of the nvif object teardown: if (chan->fence) nouveau_fence(chan->cli->drm)->context_del(chan); ... nvif_object_dtor(&chan->vram); nvif_event_dt...
CVE-2026-89805	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/pagemap: Fix folio allocation fallback and use-after-put drm_pagemap_migrate_populate_ram_pfn() had two issues when populating RAM PFNs with higher-order folios: 1. The higher-order vma_alloc_folio()/folio_alloc() calls did not pass __GFP_NOWARN, so a THP allocation failure under memory pressure would spam the kernel log, and there wa...
CVE-2026-89808	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/amdkfd: Fix the case that vm range is hole at svm_migrate_copy_to_vram When migration vm range is hole at cpu side(MIGRATE_PFN_MIGRATE set + MIGRATE_PFN_VALID unset) driver still allocates device pages. There is no dma map of src pages and migration. j is 0 and svm_migrate_copy_memory_gart() will return an uninitialized r. That can trigger o...
CVE-2026-89810	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/amdkfd: Fix error path at svm_migrate_copy_to_ram If page migration from device to sys ram fails for some reasons driver needs release and unlock allocated system pages. To do that driver should use page physical address, or pfn, then get struct page*. Current driver uses dma address(for adev) that is not correct with IOMMU enabled, or even ...
CVE-2026-89814	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/amdgpu: clamp the isolation index for rings outside a partition adev->isolation[] has one slot per partition, but a ring that is not assigned to one keeps AMDGPU_XCP_NO_PARTITION, which is ~0, so indexing the array with it is out of bounds. SDMA submissions hit this on both the isolation enforcement and the VM flush path and trip UBSAN. Fal...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89815	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/ttm: Drop tt->restore after successful restore ttm_pool_restore_and_alloc() can successfully complete the restore process via ttm_pool_restore_commit(), but tt->restore is not dropped afterward. As a result, subsequent backup/restore flows observe what appears to be a completed restore, while in reality shmem handles are still installed in t...
CVE-2026-89819	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/amd/display: validate plane degamma LUT size for private color prop Unlike the CRTC degamma path, which is guarded by amdgpu_dm_verify_lut_sizes(), the per-plane degamma LUT size was never validated before use. __set_dm_plane_degamma() passed the user-supplied size straight into __is_lut_linear() and, for a non-linear LUT, into __set_input_t...
CVE-2026-89823	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm: fix race between partial drm_dev_register() failure and ioctl If drm_dev_register() fails after registering a minor (e.g. render minor registered, primary minor fails), userspace could have opened the first minor and entered a drm_dev_enter() critical section. Since the unplugged flag was never set, the ioctl proceeds while the error path t...
CVE-2026-89825	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/panthor: fix firmware control interface bounds checks panthor_init_cs_iface() and panthor_init_csg_iface() validate firmware control interface offsets with 32-bit arithmetic and the size of the host wrapper structures. The offsets are derived from firmware-provided strides, so the arithmetic can wrap before the bounds check, and the host wra...
CVE-2026-89829	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: f2fs: fix to pass folio->index to f2fs_sanity_check_node_footer() Otherwise in f2fs_sanity_check_node_footer(), it will check the same nid incorrectly.
CVE-2026-89832	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: f2fs: fix to clear dirty flag on folio in error path If node block is corrupted due to chksum mismatch or inconsistent footer info, it needs to drop clear flag of node folio, in order to persist inconsistent node data to storage.
CVE-2026-89836	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: f2fs: fix folio_nr_pages() race after put in large folio invalidate Our v6.18 based Android system is continually suffering livelock and bad page stat as shown in[1] which related to broken xarray slot status. By investigating big folio operations within f2fs, we find below races and fix it by get the nr_pages before drop the refcount and folio_l...
CVE-2026-89841	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: f2fs: only redirty pinned folios in redirty_blocks redirty_blocks() pins folios with read_cache_folio() and then walks the same range again with filemap_lock_folio() to redirty them and drop the references it took. Commit 5951fee46bef ("f2fs: Use a folio in redirty_blocks()") changed the second pass to a do/while loop. If read_cache_folio() fai...
CVE-2026-89854	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Fix cs84xx use-after-free on host teardown qla84xx_put_chip() drops the last reference to ha->cs84xx and frees it via __qla84xx_chip_release() without clearing ha->cs84xx. During teardown it ran before scsi_remove_host(), which is what removes the 84xx_fw_version host sysfs attribute. A concurrent read of that attribute in the win...
CVE-2026-89870	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: zoran: Avoid freeing a registered video_device twice zoran_init_video_device() installs zoran_vdev_release() as the video_device release callback through zoran_template. After video_register_device() succeeds, video_unregister_device() drops the registered video_device reference and the V4L2 core eventually invokes that release callback, ...
CVE-2026-89873	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: v4l2-ctrls: validate HEVC EXT SPS RPS counts The HEVC SPS control carries the short-term and long-term RPS counts that decoder drivers use to walk the matching EXT SPS dynamic arrays. Reject SPS values that exceed the HEVC limits of 64 short-term sets and 32 long-term references so drivers cannot later index beyond those controls. Also r...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89875	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: ti: vpe: quiesce overflow recovery before freeing streams The VIP overflow recovery worker is armed from the hardirq handler when a FIFO overflow is detected, and the list-complete path looks the stream up through the VPDMA list private pointer. Both keep touching stream, port and device state; the recovery worker also resets the parser a...
CVE-2026-89880	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: rtl2832_sdr: release URBs and stream buffers on start_streaming() failure rtl2832_sdr_start_streaming() calls rtl2832_sdr_alloc_stream_bufs(), rtl2832_sdr_alloc_urbs() and rtl2832_sdr_submit_urbs() in sequence and shares a single err: label that only unlocks the mutex and returns. When alloc_urbs() succeeds but submit_urbs() fails, or whe...
CVE-2026-89882	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: rkvddec: hevc: guard INTER_REF_PIC_SET_PRED index underflow st_ref_pic_set_prediction() computes the reference RPS index as st_rps_idx - (delta_idx_minus1 + 1) per HEVC spec equation 7-59. Both operands are u8, so when delta_idx_minus1 + 1 exceeds the current index the subtraction wraps and the subsequent array access at calculated_rps_st_...
CVE-2026-89883	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: rc: sunxi-cir: Unregister rc device on probe failure After rc_register_device() succeeds, later probe failures must undo the registration with rc_unregister_device(). The current error path jumps to the allocation cleanup label and only calls rc_free_device(), leaving the rc device registration and resources created by rc_register_device(...
CVE-2026-89887	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: i2c: ov7740: fix use-after-destroy in remove The ov7740_remove() function had a severe teardown order bug where it destroyed the driver's mutex before freeing the V4L2 control handler which relies on that mutex, leading to a use-after-destroy kernel panic. Furthermore, the driver explicitly called v4l2_ctrl_handler_free() and mutex_destro...
CVE-2026-89888	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: i2c: ov02a10: fix endpoint parsing use-after-free The ov02a10_check_hwcfg() function calls fwnode_handle_put(ep) immediately after allocating and parsing the endpoint. However, it subsequently calls fwnode_property_read_u32() using the same 'ep' handle, leading to a potential use-after-free. Additionally, reading the optional 'ovti,mipi-...
CVE-2026-89890	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: go7007: defer the ALSA v4l2 put until card release go7007_snd_init() already takes a v4l2_device reference for the ALSA side, but go7007_snd_remove() drops it immediately after calling snd_card_free_when_closed(). That is too early when a userspace process still has the capture PCM open. The ALSA card and its PCM callbacks remain alive u...
CVE-2026-89893	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: cx23885: cancel NetUP CI work before teardown netup_ci_exit() frees a netup_ci_state while its work item, netup_read_ci_status(), may still be pending or running on the system workqueue. The worker obtains the state with container_of() and dereferences it, so it must not outlive the state. netup_ci_init() queues the initial status read, ...
CVE-2026-89894	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: cx231xx: reject geometry changes while the VBI queue is busy vidioc_s_fmt_vid_cap() and vidioc_s_std() change the device-wide dev->width / dev->norm but only refuse the change when the *video* queue (dev->vidq) is busy. The VBI queue (dev->vbiq) shares that same geometry: cx231xx_init_vbi_isoc() latches dma_q->lines_per_field from dev->no...
CVE-2026-89899	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: cec: disable delayed work before freeing an interrupted transmit cec_transmit_msg_fh() drops adap->lock to wait for a blocking transmit in wait_for_completion_killable(). If that wait is interrupted by a signal, cancel_delayed_work_sync() can run before the CEC kthread arms the reply timeout via schedule_delayed_work(&data->work) in cec_t...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89902	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: LoongArch: Avoid preempt count underflow without probe LoongArch uses break 11 for the breakpoint placed after an instruction that Kprobes executes out of line. Since userspace can issue the same break instruction, do_bp() can reach kprobe_singlestep_handler() when there is no current probe. The handler actually returns false in this case, but ...
CVE-2026-89903	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: LoongArch: Do not save/restore percpu base register in rethook trampoline The rethook trampoline saves \$r21 (\$u0), the percpu base, into its frame at entry and restores it at exit. Inbetween rethook_trampoline_handler() may schedule via preempt_enable_notrace(). If the task migrates to another CPU, the frame's \$r21 holds the old CPU's percpu ba...
CVE-2026-89906	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: LoongArch: BPF: Refactor jump offset calculation in tail call The old macro-based jmp_offset calculation derives the jump distance from a stale prior-pass code stride, which can lead to wrong branch offsets and soft lockups under extra JIT passes. Fix this by calculating the offset directly on the absolute target: "ctx->offset[insn + 1] - ctx->...
CVE-2026-89919	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: KVM: s390: keyop: use mmu_lock to read gmap->asce Every other dat_* consumer in this file (kvm_s390_get_skeys, set_skeys, get_cmma_bits, set_cmma_bits, MEM_CLR_CMMMA, kvm_s390_fixup_prefix, kvm_test_age_gfn, kvm_age_gfn) reads kvm->arch.gmap->asce *inside* the mmu_lock read-side. keyop is the only outlier. gmap->asce is mutated under write_lock(...
CVE-2026-89920	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: KVM: s390: Fix memory corruption by not reinjecting CK machine checks Channel-subsystem damage machine checks are for the host channel subsystem. The guest channel subsystem is emulated in the userspace VMM. There is no point in forwarding such machine checks into the guest. This also simplifies the machine check reinjection and avoids kfree of...
CVE-2026-89922	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: KVM: s390: Take srcu when importing watchpoint data __import_wp_info() backs up the original guest memory contents of a watchpoint with read_guest_abs(), which is kvm_read_guest() and therefore resolves the memslot via __kvm_memslots(). That requires kvm->srcu (or kvm->slots_lock) to be held, otherwise a concurrent memslot update can free the me...
CVE-2026-89938	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: iio: chemical: atlas-sensor: use iio_trigger_poll_nested() to fix remove UAF The atlas driver requests its hardware data-ready IRQ with devm_request_threaded_irq(); its threaded handler queues an irq_work, atlas_work_handler(), that calls iio_trigger_poll(data->trig). The IRQ is devm-managed, so free_irq() runs from the devres unwind after atla...
CVE-2026-89940	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: iio: buffer: Tie IIO dma fence lock lifetime to the fence The `iio_dma_fence` implementation currently uses a lock embedded in the `iio_dmabuf_priv`. But the `iio_dma_fence` can outlive the `iio_dmabuf_priv`, which can cause a use-after-free. Tie the lifetime of the lock to the lifetime of the fence by embedding them in the same struct. We can...
CVE-2026-89941	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: iio: buffer: Make IIO DMA fence release RCU-safe The `dma_fence` documentation states that if a custom release implementation is provided, the `dma_fence` object must be freed in an RCU-safe way. The current `iio_dma_fence` implementation uses `kfree()`, which might result in a use-after-free. Remove the custom `release` implementation. This ma...
CVE-2026-89942	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: iio: buffer: Fix potential use-after-free in anonymous buffer release An anonymous buffer handle holds a reference to the underlying IIO device. The reference is dropped in the buffer handle's release function. If the device has been removed, either through unbind or hot-unplug, the buffer handle might hold the last reference. The release funct...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89961	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: powerpc/mm: fix wrong addr_pfn tracking in compound vmemmap population vmemmap_populate_compound_pages() uses addr_pfn to determine the PFN offset within a compound page and to decide whether the current vmemmap slot should be populated as a head page mapping or should reuse a tail page mapping. However, addr_pfn is advanced manually in paralle...
CVE-2026-89965	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: nvdimmbtt: reject an arena whose nfree is below the lane count The BTT info block's nfree field, the number of reserve free blocks, is read from the medium without validation. btt_freelist_init() and btt_rtt_init() size the per-lane freelist[] and rtt[] arrays by nfree, but the I/O path indexes them by the lane from nd_region_acquire_lane(), w...
CVE-2026-89967	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: mm/migrate_device: avoid out-of-bounds writes for compound folios migrate_device_range() and migrate_device_pfns() clear the entries following a compound folio so that the PFN arrays retain their page-granular representation. If a compound folio extends beyond the end of the caller-provided range, the loops clear all following folio entries wit...
CVE-2026-89979	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: ALSA: pcm: Fix race between non-atomic ops and trigger-start We protect the races of the concurrent state transitions between atomic PCM ops, but the checks between the non-atomic ops (hw_params, hw_free and prepare) and the atomic ops aren't perfect; there is a check of the conflicting PCM state at the beginning of hw_params & co, but the atomi...
CVE-2026-89985	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: memcg: keep folio's objcg same as its node memcg_reparent_objcgs() has an inherent assumption that a folio's objcg is the objcg of the folio's node. Folio migration across nodes breaks that assumption: the new folio simply inherits the old folio's objcg while living on a different node. Once the assumption is broken, the reparenting of the fol...
CVE-2026-89986	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: mm/mempolicy: fix sleeping allocation in alloc_pages_bulk_weighted_interleave() syzbot reported a sleeping function called from invalid context splat in bucket_table_alloc(). When rhashtable_insert_slow() rehashes the table under rcu_read_lock(), it calls bucket_table_alloc(..., GFP_ATOMIC __GFP_NOWARN). If the bucket table allocation uses v...
CVE-2026-89988	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: kprobes: Protect kprobe_blacklist with RCU __within_kprobe_blacklist() traverses kprobe_blacklist without holding kprobe_mutex. When a module is unloaded, kprobe_remove_area_blacklist() removes blacklist entries and immediately frees them with kfree(). A concurrent call to within_kprobe_blacklist() can therefore dereference freed memory. Furthe...
CVE-2026-89994	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: dmaengine: fsl-edma: tracing: no ptr dereference during log output The fsl edma events store a pointer to a struct fsl_edma_engine in the ringbuffer and dereference it when a log entry is printed. At this time, the pointer may no longer be valid. Event injection can be used to trigger a crash: \$ cd /sys/kernel/tracing \$ echo 'value = 0' > even...
CVE-2026-89997	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: dm: fix resume-vs-remove race If the user issues the resume ioctl and the remove ioctl at the same time, it may be possible that the device is resumed after it is suspended in __dm_destroy. The result is that the table is destroyed without calling the postsuspend method. Dm targets expect that they may be removed only after the postsuspend meth...
CVE-2026-89998	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: dm: fix race when loading and unloading a table If the userspace calls two concurrent table load ioctls and one of them succeeds and the other fails, there is a race condition because dm_setup_md_queue walks &md->table_devices without any lock. If the walk races with dm_table_destroy -> free_devices -> dm_put_table_device, there is access to inv...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-90001	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: HID: bpf: serialize device reference release in struct_ops destroy path __hid_bpf_ops_destroy_device() and hid_bpf_unreg() can race on the same registration reference, double-putting struct hid_device and freeing it while hid_destroy_device() still uses it. Serialize the remove/NULL decision under hdev->bpf.prog_list_lock so exactly one path re...
CVE-2026-90002	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: ftrace: Take trace_array reference before accessing its ftrace_ops The trace instance files set_ftrace_filter and set_ftrace_notrace was updated to work with specific trace instances (trace_arrays). The issue is that when these files are opened, there is a small race window where it will use the ftrace_ops from the inode->private pointer to get ...
CVE-2026-90003	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: futex: Prevent rcuwait use-after-free during requeue PI On PREEMPT_RT, FUTEX_CMP_REQUEUE_PI can trigger a KASAN report (slab-out-of-bounds) in futex_requeue_pi_complete() invocation of rcuwait_wake_up(). The futex_q used by futex_wait_requeue_pi() is allocated on the waiter's stack. An early wakeup can race with a PI requeue as follows: ...
CVE-2026-90007	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: pm8001: Use rollback index when freeing MSI-X vectors pm8001_request_msix() unwinds previously registered handlers with free_irq() when request_irq() fails. The rollback loop uses the failing index i for every iteration instead of the already registered vector index j. That passes the wrong IRQ/dev_id pair to free_irq() and leaves the ear...
CVE-2026-90008	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: megaraid_sas: Limit NVMe request size to the PRP chain frame megasas_make_prp_nvme() builds a command's PRP list in cmd->sg_frame, a DMA pool buffer of instance->max_chain_frame_sz bytes, spending one entry per NVMe page of the transfer plus one per page of the buffer for the chain pointer. The loop runs until the transfer is described and...
CVE-2026-90009	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: bsg: Fix TOCTOU in io_uring passthrough command setup scsi_bsg_uring_cmd() reads bsg_uring_cmd from the shared mmap'd SQE. Userspace can change a field after we check it and before we use it. request_len is the sharp case: it can grow past sizeof(cmd->cmd) after the bound check and overflow cmd->cmd in copy_from_user(). READ_ONCE() th...
CVE-2026-90010	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: bsg: Cap io_uring sense copy to max_response_len Completion copied cmd->sense_len to the user response buffer without honoring max_response_len. After a valid sense, the midlayer sets sense_len to the real length (up to SCSI_SENSE_BUFFERSIZE), so a smaller user buffer was overrun.
CVE-2026-90013	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: tracing: Take trace_array reference when opening options file The options files do not take the trace_array reference for the options they represent. This could cause a use-after-free kernel crash if one of these files is opened by one task and another task removes the instance that the option is for. Because it doesn't take a reference upon ope...
CVE-2026-90014	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: tracing: Have show_event_filters/triggers files take trace array ref The newly added files show_event_filters and show_event_triggers that show all filters or triggers that are set within the trace array do not take a reference for the trace array it is showing. Without taking a reference, the trace_array may be freed via "rmdir" while a task is...
CVE-2026-90022	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: usb: gadget: f_midi2: fix use-after-free in string attribute show path f_midi2_opts_str_show() takes the string lock internally, but its callers dereference the opts->info.<field> pointer before calling it, outside the lock. This races with f_midi2_opts_str_store(), which frees the old string under opts->lock when the attribute is written concu...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-90026	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: usb: typec: qcom-pmic: cancel reset_work on stop pdphy_stop() disables IRQs but leaves reset_work pending. If the IRQ handler schedules it just before disable_irq(), the work runs after remove() frees the struct via devm. Call cancel_work_sync() after disabling IRQs to close the window. This issue was found by an in-house static analysis tool.
CVE-2026-90027	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: usb: typec: qcom-pmic-typec: disable cc_debounce_dwork on stop cc_debounce_dwork is queued from the set_cc() and start_toggling() callbacks, which run from TCPM's kthread worker. port_stop() returns before tcpm_unregister_port() destroys that worker. Flushing the worker during unregister may therefore run a callback which queues the delayed wo...
CVE-2026-90030	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: usb: dwc3: clear forceRM when issuing EndTransfer The forceRM bit of the DEPCMD register controls the behavior of the EndTransfer command used to stop an active transfer. Older DWC3 programming guide revisions recommended setting forceRM=1 when issuing EndTransfer. Newer programming guide revisions recommend issuing EndTransfer with forceRM clea...
CVE-2026-90032	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: usbtv: keep device alive while ALSA card exists The ALSA PCM callbacks store the driver state in pcm->private_data. An open PCM file can outlive USB disconnect because usbtv_audio_free() uses snd_card_free_when_closed(). The disconnect path can then drop the V4L2 device reference and free struct usbtv before ALSA releases the substream, s...
CVE-2026-90043	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: zram: fix slot lock bit position on big-endian 64-bit The slot lock is a bit operation on the whole __lock word, which flags and ac_time alias as two u32s. On little-endian the lock bit lands in the position ZRAM_ENTRY_LOCK reserves in flags, so the aliasing works out. On 64-bit big-endian it lands in ac_time instead: with ZRAM_TRACK_ENTRY_ACT...
CVE-2026-90044	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: usb: gadget: f_fs: Fix Use-After-Free in AIO error path In ffs_epfile_write_iter() and ffs_epfile_read_iter(), when ffs_epfile_io() fails with an error other than -EIOCBQUEUED, the io_data structure ('p') is freed. However, for AIO operations, the kiocb cancel function was already armed and kiocb->private was set to 'p'. If a concurrent cancel ...
CVE-2026-90045	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: USB: gadget: ffs: fix mm lifetime handling io_data stores a pointer to the submitting task's mm_struct, but does not currently hold a reference to it while async requests are pending. This can result in a use-after-free if the task exits before completion handling finishes. Take a reference with mmgrab() when queuing the read request and relea...
CVE-2026-90046	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: mm/page_alloc: don't spin_trylock() in NMI on UP Patch series "mm/page_alloc: fixes for free_pages_nolock() on RT/UP". Pre-existing bugs found by Sashiko during review of this other series: https://lore.kernel.org/all/20260703-alloc-trylock-v5-0-c87b714e19d3@google.com/ I have not reproduced these bugs, and I suspect there is no real-world use...
CVE-2026-90047	7.8	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/xe: Don't hand out the flat CCS storage as usable VRAM get_flat_ccs_offset() reads the base of the flat CCS storage from the hardware, scales it by the number of enabled L3 nodes, and rounds the result up to 128K. Everything below that offset is then handed to the VRAM allocator as usable memory. Rounding a limit that means "usable memory ...
CVE-2026-13210	7.7	HIGH		0.004		GitLab has remediated an issue in GitLab CE/EE affecting all versions from 15.7 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that under certain conditions could have allowed an authenticated user to access CI/CD variables outside their intended environment scope due to improper input validation in the environment scope pattern matcher.
CVE-2026-16432	7.7	HIGH		0.003		IBM DataStage on Cloud Pak for Data 5.4.0.0 IBM DataStage PxXMLInput operator could allow a remote authenticated attacker to obtain sensitive information due to an XML external entity (XXE) injection.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-18692	7.7	HIGH		0.004	mongodb:mongodb	An issue in MongoDB Server's handling of timeseries bucket lifecycle could allow an authenticated user with write privileges to cause an internal reference to be used after the underlying memory has been freed. Subsequent operations could then result in a server crash or, potentially, execution of unintended code.
CVE-2026-19407	7.7	HIGH		0.005		Bucket Squatting in Google Cloud Gemini Enterprise Agent Platform SDK for Python versions prior to 1.166.1 allows an attacker to achieve Remote Code Execution (RCE) and tenant-project token theft.
CVE-2026-20342	7.7	HIGH				A vulnerability in a specific file download API of Cisco Secure FMC Software could allow an authenticated, remote attacker to download arbitrary files from an affected system. This vulnerability exists because user input is not being sanitized. An attacker could exploit this vulnerability by sending a crafted HTTPS request. A successful exploit could allow the attacker to download arbitrary files from the affec...
CVE-2026-29811	7.7	HIGH		0.003		CyberPanel before 2.4.4 attempts to detect an "alais" domain (i.e., a second domain that serves the same content as a primary domain; normally spelled "alias") via an ORM query filter rather than a Python "if" statement.
CVE-2026-31278	7.7	HIGH		0.002		An issue in the /api/v2/setting/adserversetting endpoint of Suprema BioStar 2 before 2.9.12 and and BioStar X before 1.0.2 allows attackers to obtain Active Directory service account credentials in cleartext by supplying a crafted GET request.
CVE-2026-45794	7.7	HIGH		0.005		Open Access Management (OpenAM) is an access management solution. Prior to 16.1.1, the anonymous Push Notification SNS callback handled by SnsMessageResource falls back to a CTS predicate blob after a messageId expires from the in-memory dispatcher, treats top-level blob keys as Java class names for Class.forName, and deserializes attacker-controlled JSON through Jackson. A low-privileged user who starts Push Regi...
CVE-2026-73496	7.7	HIGH		0.003		MCP Atlassian is a Model Context Protocol (MCP) server for Atlassian products (Confluence and Jira). Prior to 0.22.0, the confluence_upload_attachment and confluence_upload_attachments tools pass a client-controlled file_path through src/mcp_atlassian/confluence/attachments.py upload_attachment, and the jira_update_issue_attachments parameter reaches src/mcp_atlassian/jira/attachments.py upload_attachment, without...
CVE-2026-81210	7.7	HIGH		0.002	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 concatenates three caller-supplied strings into a String.format path on the shared /ds-storage RWX PVC and returns the file with no project ACL — pure IDOR plus traversal. Read is constrained to files named job.log/error.log, but DataStage job logs routinely carry connection strings, {dsnextenc} ciphertxts (decryptable via d2-f023), and customer-data row samples. This i...
CVE-2026-81897	7.7	HIGH		0.002		In Concrete CMS below CMS 9.5.3, the save_control action in the Express entities forms dashboard controller did not validate the anti-CSRF token. By causing an authenticated administrator to submit a forged cross-site request, a remote attacker without credentials could write attacker-controlled headline and body values to an existing Express form Text control. Those values were emitted without output encoding by ...
CVE-2026-83012	7.7	HIGH		0.004		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Enterprise Capture. While the vulnerability is in Oracle WebCenter Enterprise Capture, attacks may si...
CVE-2026-83041	7.7	HIGH		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Portlet Services). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. While the vulnerability is in Oracle WebCenter Portal, attacks may significantly impact additional pro...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83048	7.7	HIGH		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Runtime Tools). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. While the vulnerability is in Oracle WebCenter Portal, attacks may significantly impact additional produc...
CVE-2026-83068	7.7	HIGH		0.004		Vulnerability in the Oracle Enterprise Manager for Oracle Database product of Oracle Enterprise Manager (component: Core). The supported version that is affected is 24.1. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Enterprise Manager for Oracle Database. While the vulnerability is in Oracle Enterprise Manager for Oracle Database, attacks may ...
CVE-2026-83070	7.7	HIGH		0.004		Vulnerability in the PeopleSoft Enterprise PRTL Interaction Hub product of Oracle PeopleSoft (component: Enterprise Portal). The supported version that is affected is 9.1. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise PeopleSoft Enterprise PRTL Interaction Hub. While the vulnerability is in PeopleSoft Enterprise PRTL Interaction Hub, attacks may signi...
CVE-2026-83084	7.7	HIGH		0.004		Vulnerability in the Oracle Marketing product of Oracle E-Business Suite (component: Audience). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Marketing. While the vulnerability is in Oracle Marketing, attacks may significantly impact additional products (scope change). Successful attacks ...
CVE-2026-83088	7.7	HIGH		0.004		Vulnerability in the RDBMS component of Oracle Database Server. Supported versions that are affected are 23.4.0-23.26.3. Easily exploitable vulnerability allows low privileged attacker having Authenticated User privilege with network access via Oracle Net to compromise RDBMS. While the vulnerability is in RDBMS, attacks may significantly impact additional products (scope change). Successful attacks of this vuln...
CVE-2026-83116	7.7	HIGH		0.004		Vulnerability in the Oracle Order Management product of Oracle E-Business Suite (component: Product Diagnostic Tools). Supported versions that are affected are 12.2.5-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Order Management. While the vulnerability is in Oracle Order Management, attacks may significantly impact additional products...
CVE-2026-83127	7.7	HIGH		0.003		Vulnerability in the Oracle Sales Offline product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Sales Offline. While the vulnerability is in Oracle Sales Offline, attacks may significantly impact additional products (scope change)...
CVE-2026-83129	7.7	HIGH		0.004		Vulnerability in the Oracle Sales product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Sales. While the vulnerability is in Oracle Sales, attacks may significantly impact additional products (scope change). Successful attacks o...
CVE-2026-83131	7.7	HIGH		0.003		Vulnerability in the Oracle Web Applications Desktop Integrator product of Oracle E-Business Suite (component: File download). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTPS to compromise Oracle Web Applications Desktop Integrator. While the vulnerability is in Oracle Web Applications Desktop Integrator, attac...
CVE-2026-83134	7.7	HIGH		0.004		Vulnerability in the Oracle iStore product of Oracle E-Business Suite (component: Shopping Cart). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle iStore. While the vulnerability is in Oracle iStore, attacks may significantly impact additional products (scope change). Successful attacks of t...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83141	7.7	HIGH		0.004		Vulnerability in the Oracle Field Service product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Field Service. While the vulnerability is in Oracle Field Service, attacks may significantly impact additional products (scope change)...
CVE-2026-83142	7.7	HIGH		0.004		Vulnerability in the Oracle Proposals product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Proposals. While the vulnerability is in Oracle Proposals, attacks may significantly impact additional products (scope change). Successful...
CVE-2026-83146	7.7	HIGH		0.003		Vulnerability in the Siebel CRM End User product of Oracle Siebel CRM (component: Open UI). Supported versions that are affected are 17.0-26.7. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM End User. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Siebel CRM End User, att...
CVE-2026-83166	7.7	HIGH		0.004		Vulnerability in the Oracle Customer Interaction History product of Oracle E-Business Suite (component: Outcome-Result). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Customer Interaction History. While the vulnerability is in Oracle Customer Interaction History, attacks may significantly ...
CVE-2026-83233	7.7	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Experience Manager). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. While the vulnerability is in Oracle Comm...
CVE-2026-83243	7.7	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Experience Manager). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. While the vulnerability is in Oracle Comm...
CVE-2026-83287	7.7	HIGH		0.004		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Presentation Services). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via SOAP to compromise Oracle Business Intelligence Enterprise Edition. While the vulnerability is in Oracle Business...
CVE-2026-83312	7.7	HIGH		0.003		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: E-Business Suite - XDO). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle BI Publisher. While the vulnerability is in Oracle BI Publisher, attacks may significantly impact additional produ...
CVE-2026-83313	7.7	HIGH		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle BI Publisher. While the vulnerability is in Oracle BI Publisher, attacks may significantly impact additional product...
CVE-2026-83319	7.7	HIGH		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: Web Service API). The supported version that is affected is 12.2.1.4.0. Easily exploitable vulnerability allows low privileged attacker with network access via SOAP to compromise Oracle BI Publisher. While the vulnerability is in Oracle BI Publisher, attacks may significantly impact additional products (scope change). Successful a...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83356	7.7	HIGH		0.003		Vulnerability in the Enterprise Command Center Framework product of Oracle E-Business Suite (component: Security). The supported version that is affected is V16. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Enterprise Command Center Framework. While the vulnerability is in Enterprise Command Center Framework, attacks may significantly impact addition...
CVE-2026-83437	7.7	HIGH		0.003		Vulnerability in the Oracle Engineering product of Oracle E-Business Suite (component: Change Management). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Engineering. While the vulnerability is in Oracle Engineering, attacks may significantly impact additional products (scope change). Succ...
CVE-2026-83485	7.7	HIGH		0.004		Vulnerability in the Oracle Product Hub product of Oracle E-Business Suite (component: Item Catalog). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Hub. While the vulnerability is in Oracle Product Hub, attacks may significantly impact additional products (scope change). Successfu...
CVE-2026-83486	7.7	HIGH		0.004		Vulnerability in the Oracle Product Hub product of Oracle E-Business Suite (component: Item Catalog). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Hub. While the vulnerability is in Oracle Product Hub, attacks may significantly impact additional products (scope change). Successfu...
CVE-2026-83487	7.7	HIGH		0.004		Vulnerability in the Oracle Product Hub product of Oracle E-Business Suite (component: Item Catalog). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Hub. While the vulnerability is in Oracle Product Hub, attacks may significantly impact additional products (scope change). Successfu...
CVE-2026-87124	7.7	HIGH		0.004		Vulnerability in the Oracle iRecruitment product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle iRecruitment. While the vulnerability is in Oracle iRecruitment, attacks may significantly impact additional products (scope change). ...
CVE-2026-87127	7.7	HIGH		0.003		Vulnerability in the Oracle Purchasing product of Oracle E-Business Suite (component: G-Invoicing). Supported versions that are affected are 12.2.10-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Purchasing. While the vulnerability is in Oracle Purchasing, attacks may significantly impact additional products (scope change). Successful a...
CVE-2026-87134	7.7	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via TCP to compromise Oracle Hyperion Data Relationship Management. While the vulnerability is in Oracle Hyperion Data Relationship Management, at...
CVE-2026-87141	7.7	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. While the vulnerability is in Oracle Hyperion Data Relationship Management, a...
CVE-2026-87147	7.7	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. While the vulnerability is in Oracle Hyperion Data Relationship Management...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87151	7.7	HIGH		0.004		Vulnerability in the Oracle Bills of Material product of Oracle E-Business Suite (component: Setup Workbench). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Bills of Material. While the vulnerability is in Oracle Bills of Material, attacks may significantly impact additional products (scop...
CVE-2026-87183	7.7	HIGH		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows high privileged attacker with logon to the infrastructure where Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. Successful attacks require human interaction fr...
CVE-2026-87256	7.7	HIGH		0.004		Vulnerability in the Oracle Agile PLM product of Oracle Supply Chain (component: Application Server). The supported version that is affected is 9.3.6. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Agile PLM. While the vulnerability is in Oracle Agile PLM, attacks may significantly impact additional products (scope change). Successful attacks o...
CVE-2026-87257	7.7	HIGH		0.004		Vulnerability in the Oracle Agile PLM product of Oracle Supply Chain (component: SDK). The supported version that is affected is 9.3.6. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Agile PLM. While the vulnerability is in Oracle Agile PLM, attacks may significantly impact additional products (scope change). Successful attacks of this vulnerab...
CVE-2026-87264	7.7	HIGH		0.003		Vulnerability in the PeopleSoft Enterprise PeopleTools product of Oracle PeopleSoft (component: Integration Broker). Supported versions that are affected are 8.61-8.63. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise PeopleSoft Enterprise PeopleTools. While the vulnerability is in PeopleSoft Enterprise PeopleTools, attacks may significantly impact additi...
CVE-2026-87996	7.7	HIGH		0.002	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.9.6 until 0.11.1, SafePlaywrightURLLoader in backend/open_webui/retrieval/web/utlis.py validated a user-controlled hostname in Python and then let the Playwright browser resolve it again in the sync and async request interceptors. An authenticated user controlling authoritative DNS could return a public address to validati...
CVE-2026-90025	7.7	HIGH				In the Linux kernel, the following vulnerability has been resolved: usb: typec: ucsi: displayport: Fix OOB altmode array index The UCSI displayport driver indexes the connector's port altmode array with the GET_CURRENT_CAM response after checking it is not 0xff. The port altmode array is UCSI_MAX_ALTMODES elements long. If the PPM returns an invalid GET_CURRENT_CAM response above UCSI_MAX_ALTMODES and not equal ...
CVE-2026-92784	7.7	HIGH				@refinedev/inferencer through 7.0.0 fails to escape API field names when interpolating them into generated JSX source code. Attackers controlling the data provider can inject malicious JavaScript through crafted JSON property names that execute in the developer's browser when the Inferencer page renders.
CVE-2026-71327	7.6	HIGH		0.004	traefik:traefik	Traefik is an open source HTTP reverse proxy and load balancer. From 3.0.0 until 3.6.25 and 3.7.10, Traefik's Kubernetes Gateway API provider in pkg/provider/kubernetes/gateway/httproute.go, grpcroute.go, tcproute.go, and tlroute.go builds HTTPRoute, GRPCRoute, TCPRoute, and TLSRoute router and service identities by hyphen-concatenating namespace, route name, Gateway identity, entry point, and rule index, allowin...
CVE-2026-73943	7.6	HIGH		0.003		Vulnerability in the Oracle Identity Manager product of Oracle Fusion Middleware (component: OIM Legacy UI). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Identity Manager. While the vulnerability is in Oracle Identity Manager, attacks may significantly impact additional produ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-76425	7.6	HIGH				A vulnerability in the APIs of Cisco ISE could allow an authenticated, remote attacker to conduct SQL injection attacks against the backend database. This vulnerability is due to insufficient validation of certain parameters that are concatenated directly into an SQL query. An attacker could exploit this vulnerability by sending a crafted request that contains SQL statements to an affected endpoint. A successfu...
CVE-2026-82053	7.6	HIGH		0.002	mongodb:mongodb	A security issue exists in MongoDB's LDAP authorization integration where pooled LDAP connections can retain stale authentication identities after user authentication under certain configurations. Subsequent authorization queries may execute under an unintended LDAP identity rather than the expected one. This can result in incorrect role assignments based on the LDAP directory's access control configuration, poten...
CVE-2026-83052	7.6	HIGH		0.003		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Runtime Tools). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. While the vulnerability is in Oracle WebCenter Portal, attacks may significantly impact additional produ...
CVE-2026-83091	7.6	HIGH		0.003		Vulnerability in the Oracle Field Service product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Field Service. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all...
CVE-2026-83126	7.6	HIGH		0.003		Vulnerability in the Oracle Sales Online product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Sales Online. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Ora...
CVE-2026-83207	7.6	HIGH		0.003		Vulnerability in the Siebel CRM Development product of Oracle Siebel CRM (component: Integration - Scripting). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Development. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable cras...
CVE-2026-83320	7.6	HIGH		0.003		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: Administration). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle BI Publisher. Successful attacks require human interaction from a person other than the attacker and while the vulnerabili...
CVE-2026-87131	7.6	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks require human interaction from a person other than the att...
CVE-2026-87132	7.6	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks require human interaction from a person other than the att...
CVE-2026-87133	7.6	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. While the vulnerability is in Oracle Hyperion Data Relationship Management, ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87137	7.6	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks require human interaction from a person other than the att...
CVE-2026-87144	7.6	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks require human interaction from a person other than the att...
CVE-2026-87233	7.6	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. While the vulnerability is in Oracle Hyperion Financial Management, attacks may significantly impact ad...
CVE-2026-87250	7.6	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks require human interaction from a person other than the attacker and while the vulnera...
CVE-2026-87258	7.6	HIGH		0.003		Vulnerability in the Oracle Agile PLM product of Oracle Supply Chain (component: Folders, Files & Attachments). The supported version that is affected is 9.3.6. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Agile PLM. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Oracle Agil...
CVE-2025-14871	7.5	HIGH		0.006		GitLab has remediated an issue in GitLab CE/EE affecting all versions from 18.4.6 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that under certain conditions could have allowed an unauthenticated user to cause denial of service due to improper resource allocation limits in the GraphQL complexity calculation logic.
CVE-2026-1168	7.5	HIGH		0.006		GitLab has remediated an issue in GitLab CE/EE affecting all versions from 18.4.6 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that under certain conditions could have allowed an unauthenticated user to cause denial of service due to improper resource allocation limits in the GraphQL complexity calculation logic.
CVE-2026-11926	7.5	HIGH		0.003		IBM Verify Identity Access could allow a remote attacker to cause a denial of service due to insufficient validation of incoming request resources.
CVE-2026-11929	7.5	HIGH		0.002		IBM Security Verify Identity Access Reverse Proxy in certain configurations may provide weaker than expected cryptographic validation of user supplied data.
CVE-2026-12354	7.5	HIGH		0.005		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 could allow an authenticated attacker to execute arbitrary code on the application server due to improper validation of JNDI names in the Resource Adapter Installation Verification Test application.
CVE-2026-12358	7.5	HIGH		0.004		IBM Verify Identity Access could allow a remote attacker to cause a denial of service due to insufficient validation of incoming request resources.
CVE-2026-13260	7.5	HIGH		0.004		IBM Verify Identity Access could allow a remote attacker to cause a denial of service due to insufficient validation of incoming request resources.
CVE-2026-15955	7.5	HIGH		0.004		IBM Db2 11.5.0 through 11.5.9, and 12.1.0 through 12.1.5 could allow a remote attacker to perform an arbitrary file write due to improper validation of file paths.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-18706	7.5	HIGH		0.003	mongodb:mongodb	An issue in MongoDB Server's \$graphLookup aggregation stage could allow an authenticated user able to issue aggregation and memory-management commands to cause an internal reference to be used after the underlying memory has been freed. This could result in a server crash or, potentially, execution of unintended code.
CVE-2026-19290	7.5	HIGH		0.004		IBM Sterling File Gateway 6.2.0.0 through 6.2.0.6_1, 6.2.1.0 - 6.2.1.2, 6.2.2.0 - 6.2.2.1 could allow a remote attacker to obtain sensitive information due to improper access control.
CVE-2026-19534	7.5	HIGH		0.004	nodejs:undici	undici's WebSocket client crashes the whole Node.js process during the opening handshake when a server responds with a subprotocol that the client never requested. A default WebSocket connection sends no subprotocol, but if the server's 101 response includes a Sec-WebSocket-Protocol header, undici dereferences a null value while checking it against the requested list and throws an uncaught TypeError. Because that ...
CVE-2026-20247	7.5	HIGH				A vulnerability in Cisco ISE could allow an unauthenticated, remote attacker to conduct SQL injection attacks on an affected device. This vulnerability is due to improper validation of user-supplied input. An attacker could exploit this vulnerability by sending a crafted request to an affected device. A successful exploit could allow the attacker to modify data in the underlying database.
CVE-2026-20343	7.5	HIGH				A vulnerability in a critical API for Cisco Secure FMC Software could allow an unauthenticated, remote attacker to download sensitive files and use unbounded disk space. This vulnerability exists because a critical API lacks authentication. An attacker could exploit this vulnerability by repeatedly invoking the API. A successful exploit could allow the attacker to download sensitive files that should be re...
CVE-2026-49362	7.5	HIGH		0.006	apache:artemis	An unauthenticated remote attacker can create arbitrary durable queues via the CORE protocol, leading to unauthorized broker state manipulation and potential denial of service. This issue affects Apache Artemis: from 2.50.0 through 2.56.0; Apache ActiveMQ Artemis: from 1.0.0 through 2.44.0. Users are recommended to upgrade to version 2.57.0, which fixes the issue.
CVE-2026-49363	7.5	HIGH		0.005	apache:artemis	An unauthenticated remote attacker connecting with the CORE protocol can discover cluster node details by sending a SUBSCRIBE_TOPOLOGY request prior to authentication. This issue affects Apache Artemis: from 2.50.0 through 2.56.0; Apache ActiveMQ Artemis: from 1.0.0 through 2.44.0. Users are recommended to upgrade to version 2.57.0, which fixes the issue.
CVE-2026-49486	7.5	HIGH		0.004	apache:apache-airflow-providers-ftp	The Apache Airflow FTP provider's `FTPSHook.get_conn()` created an `ftplib.FTP_TLS` connection but never called `prot_p()`, so although the control channel was TLS-protected the data channel was transmitted in cleartext. Any deployment using `FTPSHook` or `FTPSTransmitOperator` to move files over FTPS exposed file contents and credentials-in-transit to a network attacker able to observe the data connection. Up...
CVE-2026-53752	7.5	HIGH		0.004		docx4j is an open source Java library for creating, editing, and saving OpenXML packages, including DOCX, PPTX, and XLSX files. Prior to 11.5.14, PropertyResolver and adjacent helpers recursively follow the WordprocessingML w:basedOn style inheritance chain without cycle detection. A well-formed DOCX containing mutually based styles causes unbounded recursion in PropertyResolver.fillPPRStack and related effective-...
CVE-2026-57098	7.5	HIGH		0.006	microsoft:remote_desktop_client	Improper verification of cryptographic signature in Windows RDP Client allows an unauthorized attacker to disclose information over a network.
CVE-2026-59279	7.5	HIGH		0.004	vmware:spring_ai	The MCP Streamable HTTP server transport (WebFlux and WebMvc variants) does not place any limit on the number of sessions it retains, and by default does not require clients to be authenticated. As a result, a remote attacker can cause the server to accumulate an unbounded number of sessions over time, gradually exhausting available memory and ultimately causing a Denial of Service that affects all legitimate clie...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-63126	7.5	HIGH				Wire provides gRPC and protocol buffers for Android, Kotlin, Swift, and Java. Prior to 6.4.5 and 7.0.0-alpha04, Wire protobuf readers do not consistently validate attacker-controlled lengths against the current logical message boundary before advancing cursors, pointers, limits, slices, or allocations. In Kotlin, ProtoAdapter.decode(ByteArray) and ProtoAdapter.decode(ByteString) use ByteArrayProtoReader32.internal...
CVE-2026-66304	7.5	HIGH		0.007	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Server-side request forgery (ssrf) in Skype for Business allows an unauthorized attacker to disclose information over a network.
CVE-2026-66307	7.5	HIGH		0.006	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Integer underflow (wrap or wraparound) in Skype for Business allows an unauthorized attacker to deny service over a network.
CVE-2026-67211	7.5	HIGH		0.003	apache:opennlp	OOM Denial of Service via Unbounded Map Pre-Sizing in Apache OpenNLP SymSpellModelSerializer Versions Affected: - 3.0.0-M4 - 3.0.0-M5 (The opennlp-spellcheck extension was introduced in 3.0.0-M4. Releases 1.x and 2.x do not contain the affected code.) Description: The SymSpellModelSerializer.create() method reads two 32-bit signed integer count fields (unigramCount and bigramCount) from a binary SymSpell mod...
CVE-2026-67376	7.5	HIGH		0.008	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Integer overflow or wraparound in SQL Server allows an unauthorized attacker to deny service over a network.
CVE-2026-68968	7.5	HIGH		0.004	apache:airflow	Apache Airflow's Backfill API authorized a request against a Dag id supplied by the caller whenever the `backfill_id` path segment failed to parse. The authorization dependency parsed it with `int()` while the route handler parsed it as pydantic's `NonNegativeInt`, which accepts values `int()` rejects (`1.0` coerces to `1`); FastAPI resolves dependencies before endpoint validation, so the two acted on different Da...
CVE-2026-69852	7.5	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine
CVE-2026-69881	7.5	HIGH		0.012	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Null pointer dereference in Windows IKE Extension allows an unauthorized attacker to deny service over a network.
CVE-2026-69890	7.5	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Virtual Trusted Platform Module allows an authorized attacker to elevate privileges locally.
CVE-2026-71330	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of sensitive system information to an unauthorized control sphere in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to disclose information over a network.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-72928	7.5	HIGH		0.006	microsoft:windows_server_2025	Use after free in Windows DNS allows an authorized attacker to execute code over a network.
CVE-2026-73566	7.5	HIGH		0.004		node-tar is a tar archive manipulation library for Node.js. Prior to 7.5.21, node-tar's filesFilter in src/list.ts uses the recursive mapHas helper to walk an archive entry path upward with path.dirname() and no segment cap when tar.t(...) or tar.x(...) receives a non-empty member-selection list. A crafted GNU L or PAX x long-path header with thousands of slash-separated segments reaches this.filter(entry.path, en...
CVE-2026-73960	7.5	HIGH		0.004		Vulnerability in the PeopleSoft Enterprise PeopleTools product of Oracle PeopleSoft (component: Ren Server). Supported versions that are affected are 8.61-8.63. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise PeopleSoft Enterprise PeopleTools. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repea...
CVE-2026-76442	7.5	HIGH		0.004		As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Secure Email Gateway and Cisco Secure Email and Web Manager engineering team has conducted a comprehensive internal security review. This review resulted in software hardening releases that address multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-76442 are related to issues with impr...
CVE-2026-77494	7.5	HIGH		0.012	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77498	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77499	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77501	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77502	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77886	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-77888	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77889	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77890	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77893	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77895	7.5	HIGH		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-81265	7.5	HIGH		0.002	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5.
CVE-2026-81875	7.5	HIGH				HAPI FHIR is a complete implementation of the HL7 FHIR standard for healthcare interoperability in Java. Prior to version 6.9.12, SHCParser in org.hl7.fhir.r5/src/main/java/org/hl7/fhir/r5/elementmodel/SHCParser.java can consume attacker-controlled Smart Health Card JWT content whose header contains zip: "DEF" and whose small raw-DEFLATE payload expands to a very large value. SHCParser.decodeJWT() passes the decod...
CVE-2026-81876	7.5	HIGH				HAPI FHIR is a complete implementation of the HL7 FHIR standard for healthcare interoperability in Java. Prior to version 6.9.12, SHCParser in org.hl7.fhir.r5/src/main/java/org/hl7/fhir/r5/elementmodel/SHCParser.java can enter an infinite loop while processing attacker-controlled Smart Health Card JWT content whose header contains zip: "DEF" and whose raw-DEFLATE payload is empty or truncated. SHCParser.decodeJWT(...
CVE-2026-83028	7.5	HIGH		0.003		Vulnerability in the Oracle Identity Manager Connector product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Difficult to exploit vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Identity Manager Connector executes to compromise Oracle Identity Manager Conn...
CVE-2026-83034	7.5	HIGH		0.004		Vulnerability in the Oracle WebCenter Sites product of Oracle Fusion Middleware (component: WebCenter Sites). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Sites. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83051	7.5	HIGH		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Runtime Tools). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...
CVE-2026-83065	7.5	HIGH		0.003		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Runtime Tools). The supported version that is affected is 14.1.2.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle WebCenter Portal executes to compromise Oracle WebCenter Portal. Successful attacks of this ...
CVE-2026-83075	7.5	HIGH		0.004		Vulnerability in the Siebel CRM Cloud Applications product of Oracle Siebel CRM (component: Siebel Cloud Manager). Supported versions that are affected are 22.3-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM Cloud Applications. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete acce...
CVE-2026-83106	7.5	HIGH		0.003		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Forms. Successful attacks of this vulnerability can result in takeover of Oracle Forms. CVSS 3.1 Base Score 7.5 (Co...
CVE-2026-83110	7.5	HIGH		0.004		Vulnerability in the Oracle Marketing product of Oracle E-Business Suite (component: Audience). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Marketing. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Oracle Marketing ...
CVE-2026-83114	7.5	HIGH		0.003		Vulnerability in the Oracle Quality product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Quality. Successful attacks of this vulnerability can result in takeover of Oracle Quality. CVSS 3.1 Base Score 7.5 (Confidentiality, Int...
CVE-2026-83115	7.5	HIGH		0.003		Vulnerability in the Oracle Applications Manager product of Oracle E-Business Suite (component: Command Line - RapidClone). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Applications Manager. Successful attacks of this vulnerability can result in unauthorized access to critical data or c...
CVE-2026-83128	7.5	HIGH		0.004		Vulnerability in the Oracle Sales Offline product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Sales Offline. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to al...
CVE-2026-83133	7.5	HIGH		0.003		Vulnerability in the Oracle iStore product of Oracle E-Business Suite (component: Shopping Cart). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle iStore. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Oracle iStore acce...
CVE-2026-83156	7.5	HIGH		0.003		Vulnerability in the Oracle XML Developers Kit component of Oracle Database Server. Supported versions that are affected are 19.3-19.32, 21.3-21.23 and 23.4.0-23.26.3. Difficult to exploit vulnerability allows low privileged attacker having XDKC privilege with network access via Oracle Net to compromise Oracle XML Developers Kit. Successful attacks of this vulnerability can result in takeover of Oracle XML Deve...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83167	7.5	HIGH		0.003		Vulnerability in the Oracle Application Object Library product of Oracle E-Business Suite (component: Core). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Application Object Library. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete a...
CVE-2026-83182	7.5	HIGH		0.004		Vulnerability in the Siebel CRM Development product of Oracle Siebel CRM (component: Configuration Tools). Supported versions that are affected are 17.0-26.7. Difficult to exploit vulnerability allows low privileged attacker with network access via SQL to compromise Siebel CRM Development. Successful attacks of this vulnerability can result in takeover of Siebel CRM Development. CVSS 3.1 Base Score 7.5 (Confiden...
CVE-2026-83183	7.5	HIGH		0.005		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (...)
CVE-2026-83204	7.5	HIGH		0.004		Vulnerability in the Oracle Sourcing product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Sourcing. Successful attacks of this vulnerability can result in takeover of Oracle Sourcing. CVSS 3.1 Base Score 7.5 (Confidentiality, ...)
CVE-2026-83213	7.5	HIGH		0.003		Vulnerability in the Siebel CRM End User product of Oracle Siebel CRM (component: Reports). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM End User. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Siebel CRM End User acc...
CVE-2026-83222	7.5	HIGH		0.003		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via multiple protocols to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repe...
CVE-2026-83223	7.5	HIGH		0.003		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Siebel Remote). Supported versions that are affected are 17.0-26.7. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deployment. CVSS 3.1 Base Score 7.5 (Confidentiality,...)
CVE-2026-83225	7.5	HIGH		0.003		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (c...
CVE-2026-83226	7.5	HIGH		0.003		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deployment. CVSS 3.1 Base Score 7.5 (Confiden...
CVE-2026-83227	7.5	HIGH		0.003		Vulnerability in the Siebel CRM Integration product of Oracle Siebel CRM (component: EAI). Supported versions that are affected are 17.0-26.7. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Integration. Successful attacks of this vulnerability can result in takeover of Siebel CRM Integration. CVSS 3.1 Base Score 7.5 (Confidentiality, Integr...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83228	7.5	HIGH		0.005		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (c...
CVE-2026-83235	7.5	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Experience Manager). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability...
CVE-2026-83241	7.5	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks require human interaction from a...
CVE-2026-83257	7.5	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result ...
CVE-2026-83262	7.5	HIGH		0.004		Vulnerability in the Oracle Product Lifecycle Analytics product of Oracle Supply Chain (component: Installation Issues). The supported version that is affected is 3.6.1. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Lifecycle Analytics. Successful attacks of this vulnerability can result in takeover of Oracle Product Lifecycle Analyti...
CVE-2026-83263	7.5	HIGH		0.003		Vulnerability in the Oracle Product Lifecycle Analytics product of Oracle Supply Chain (component: Installation Issues). The supported version that is affected is 3.6.1. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Lifecycle Analytics. Successful attacks of this vulnerability can result in takeover of Oracle Product Lifecycle Analyti...
CVE-2026-83270	7.5	HIGH		0.004		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0 and 26.01.0.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can result in u...
CVE-2026-83276	7.5	HIGH		0.003		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: helidon-webclient-http2). Supported versions that are affected are 4.0.0-4.5.4. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP/2 to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) o...
CVE-2026-83280	7.5	HIGH		0.005		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: helidon-webserver-http2). Supported versions that are affected are 4.0.0-4.5.4. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP/2 to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) o...
CVE-2026-83281	7.5	HIGH		0.005		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: helidon-webserver). Supported versions that are affected are 4.0.0-4.5.4. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCP to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of Helidon...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83289	7.5	HIGH		0.004		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Analytics Web General). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via SOAP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability ca...
CVE-2026-83292	7.5	HIGH		0.003		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). Supported versions that are affected are 8.2.0.0.0 and 26.01.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can result in take...
CVE-2026-83295	7.5	HIGH		0.004		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Presentation Services). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via SOAP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability ca...
CVE-2026-83296	7.5	HIGH		0.003		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: BI Search). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can result in ...
CVE-2026-83318	7.5	HIGH		0.004		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: Administration). Supported versions that are affected are 8.2.0.0.0, 12.2.1.4.0 and 26.01.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle BI Publisher. Successful attacks of this vulnerability can result in takeover of Oracle BI Publisher. CVSS 3.1 Base Scor...
CVE-2026-83323	7.5	HIGH		0.001		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). The supported version that is affected is 26.01.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Business Intelligence Enterprise Edition executes to compromise Oracle Business Intelligence Enterprise Edition. Succe...
CVE-2026-83326	7.5	HIGH		0.004		Vulnerability in the Siebel CRM Integration product of Oracle Siebel CRM (component: Open Integration). Supported versions that are affected are 25.12-26.7. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM Integration. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Siebel ...
CVE-2026-83330	7.5	HIGH		0.005		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: WebSocket). Supported versions that are affected are 4.0.0-4.5.4. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of Helidon. CVSS ...
CVE-2026-83333	7.5	HIGH		0.005		Vulnerability in the Oracle Net Services component of Oracle Database Server. Supported versions that are affected are 23.4.0-23.26.3. Easily exploitable vulnerability allows unauthenticated attacker with network access via Oracle Net to compromise Oracle Net Services. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of Orac...
CVE-2026-83341	7.5	HIGH		0.004		Vulnerability in the Oracle Applications Manager product of Oracle E-Business Suite (component: Command Line - RapidClone). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Applications Manager. Successful attacks of this vulnerability can result in unauthorized access to critical data or c...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83349	7.5	HIGH		0.005		Vulnerability in the Oracle Net Services component of Oracle Database Server. Supported versions that are affected are 19.3-19.32, 21.3-21.23 and 23.4.0-23.26.3. Easily exploitable vulnerability allows unauthenticated attacker with network access via Oracle Net to compromise Oracle Net Services. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable ...
CVE-2026-83350	7.5	HIGH		0.005		Vulnerability in the Oracle Net Services component of Oracle Database Server. Supported versions that are affected are 21.3-21.23 and 23.4.0-23.26.3. Easily exploitable vulnerability allows unauthenticated attacker with network access via Oracle Net to compromise Oracle Net Services. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (compl...
CVE-2026-83415	7.5	HIGH		0.003		Vulnerability in the Oracle Coherence product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0, 14.1.1.0.0, 14.1.2.0.0 and 15.1.1.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Coherence. Successful attacks of this vulnerability can result in takeover of Oracle Coherence. CVSS 3.1 Base Sco...
CVE-2026-83424	7.5	HIGH		0.003		Vulnerability in the Oracle JDeveloper product of Oracle Fusion Middleware (component: Oracle JDeveloper). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle JDeveloper. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access ...
CVE-2026-83463	7.5	HIGH		0.003		Vulnerability in the Oracle Mobile Application Server product of Oracle E-Business Suite (component: MWA Terminal Server). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Mobile Application Server executes to compromise Oracle Mobile Application Se...
CVE-2026-83489	7.5	HIGH		0.004		Vulnerability in the Oracle Banking Origination product of Oracle Financial Services Applications (component: Onboarding Batch Processes). Supported versions that are affected are 14.5.0.0.0-14.9.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Banking Origination. Successful attacks of this vulnerability can result in takeover of Oracle B...
CVE-2026-85189	7.5	HIGH		0.002		Joomla Extension - regularlabs.com - Privileged stored XSS via executable URL schemes in Modals extension for Joomla < 17.0.0 - Modals treats a destination using an executable browser URL scheme as an ordinary modal URL. The value can reach both the generated link and the iframe-loading path. Authored content can consequently become JavaScript in a visitor's browser without using Modals' separate Pro JavaScript Ev...
CVE-2026-85191	7.5	HIGH		0.002		Joomla Extension - regularlabs.com - Privileged stored XSS via rta-alias option in Tabs & Accordions extension for Joomla < 3.1.0 - Tabs & Accordions rewrites links matching an item alias into calls to its browser API. The affected renderer places the alias inside a quoted JavaScript argument in an HTML onclick attribute without securing both the JavaScript-string and HTML-attribute contexts. A crafted data-rta-...
CVE-2026-85756	7.5	HIGH				SSH.NET is a Secure Shell (SSH) library for .NET. Prior to 2026.0.0, ScpClient places caller-supplied remote paths into the command used to run scp on the server, and the default RemotePathTransformation.DoubleQuote transformation cannot safely quote every remote command interpreter. When an application passes an attacker-controlled path to a shell-based server, shell metacharacters not neutralized by the active l...
CVE-2026-87136	7.5	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in unauthorized access ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87138	7.5	HIGH		0.005		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via SOAP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in unauthorized ability ...
CVE-2026-87139	7.5	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in takeover of Oracle H...
CVE-2026-87140	7.5	HIGH		0.004		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in takeover of Oracle H...
CVE-2026-87148	7.5	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in unauthorized ability ...
CVE-2026-87190	7.5	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Managemen...
CVE-2026-87193	7.5	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complet...
CVE-2026-87194	7.5	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complet...
CVE-2026-87199	7.5	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequent...
CVE-2026-87203	7.5	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Managemen...
CVE-2026-87205	7.5	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complet...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87211	7.5	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complet...
CVE-2026-87215	7.5	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequentl...
CVE-2026-87221	7.5	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complet...
CVE-2026-87222	7.5	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequent...
CVE-2026-87237	7.5	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Managemen...
CVE-2026-87247	7.5	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Managemen...
CVE-2026-87254	7.5	HIGH		0.003		Vulnerability in the Oracle Agile PLM product of Oracle Supply Chain (component: Folders, Files & Attachments). The supported version that is affected is 9.3.6. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Agile PLM. Successful attacks of this vulnerability can result in takeover of Oracle Agile PLM. CVSS 3.1 Base Score 7.5 (Confidentiality,...
CVE-2026-87276	7.5	HIGH		0.001		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Difficult to exploit vulnerability allows low privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. Successful attacks require human interaction from a person other than the attacker and while the vu...
CVE-2026-87277	7.5	HIGH		0.005		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows unauthenticated attacker with network access via RDP to compromise Oracle VM VirtualBox. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of ...
CVE-2026-87289	7.5	HIGH		0.005		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: helidon-webserver-static-content). Supported versions that are affected are 4.0.0-4.5.4. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87776	7.5	HIGH		0.004		compression is a Node.js and Express compression middleware. In versions before 1.8.2, when a client aborts the connection while a compressed response is still being sent, the zlib stream created to compress that response is never destroyed, so each aborted compressed response leaks its native zlib memory. A remote unauthenticated attacker can repeatedly open requests and disconnect early, exhausting the available...
CVE-2026-87908	7.5	HIGH		0.003		multipart is a Node.js library for parsing multipart/form-data request bodies. In versions from 2.1.0 up to but not including 4.3.1, the parser does not bound the amount of memory used while accumulating the headers of a single multipart part. An unauthenticated attacker can send a single request whose part carries a very large volume of header bytes, forcing the parser to buffer all of them and exhausting the pr...
CVE-2026-88853	7.5	HIGH		0.002		Joomla Extension - regularlabs.com - Privileged stored XSS via event handler option in Modals Pro extension for Joomla < 17.0.0 - Modals Pro intentionally supports JavaScript Events such as on-open and on-closed. Affected versions do not distinguish trusted extension configuration from event code supplied in ordinary article content. A lower-privileged author can therefore use a documented executable feature which...
CVE-2026-89863	7.5	HIGH				In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: edif: Fix NULL pointer deref in RX SA delete check qla_chk_edif_rx_sa_delete_pending() obtains the SCSI command via GET_CMD_SP(sp) and immediately dereferences cmd->sc_data_direction. That command pointer can be NULL: the firmware may post a status completion for a command that has already been returned or aborted. The caller qla...
CVE-2026-89897	7.5	HIGH				In the Linux kernel, the following vulnerability has been resolved: media: cec: Serialize exclusive follower delivery cec_receive_notify() reads the exclusive follower pointer without the adapter lock. Serialize the no-follower check and message delivery against mode changes and release.
CVE-2026-89968	7.5	HIGH				In the Linux kernel, the following vulnerability has been resolved: nvmet-tcp: reject unsolicited H2CData PDUs nvmet_tcp_handle_h2c_data_pdu() accepts an H2CData PDU after only checking that its TTAG is a valid in-range command index and that the command's data buffers are mapped. It never checks that the target has actually solicited that data by sending an R2T for the command. A remote host can abuse this. It...
CVE-2026-89971	7.5	HIGH				In the Linux kernel, the following vulnerability has been resolved: nvme: skip the zoned limits update if the zone info query failed nvme_query_zone_info() returns either a negative errno or a positive NVMe status code, but nvme_update_ns_info_block() only tests for the negative case: ret = nvme_query_zone_info(ns, lbaf, &zi); if (ret < 0) goto out; If the device fails the Identify Namespace (I/O Command S...
CVE-2026-89974	7.5	HIGH				In the Linux kernel, the following vulnerability has been resolved: nvme-fc: fix double free of fabrics options when nvme_add_ctrl() fails nvme_create_ctrl() owns the fabrics options and frees them whenever ->create_ctrl() returns an error, so a transport must not free them on its own error paths. nvme-fc tracks this by testing ctrl->ctrl.opts in nvme_fc_ctrl_free(), which requires nvme_fc_init_ctrl() to clear ...
CVE-2026-92128	7.5	HIGH				Jenkins Script Security Plugin 1415.v9a_f9b_3a_c253d and earlier downloads a JAR file specified by URL twice, confirming the approval of the first download and loading the classpath entries from the second, allowing attackers able to define classpath entries to execute arbitrary code in the context of the Jenkins controller JVM.
CVE-2026-92129	7.5	HIGH				Jenkins Script Security Plugin 1415.v9a_f9b_3a_c253d and earlier does not check calls from sandboxed scripts to methods added dynamically to a class at runtime, allowing attackers with permission to define and run sandboxed scripts, including Pipelines, to bypass the sandbox protection and execute code outside the sandbox.
CVE-2026-9336	7.5	HIGH		0.002	ibm:websphere_application_server	IBM WebSphere Application Server 9.0, and 8.5 is vulnerable to a denial of service, caused by sending a specially-crafted HTTP request to an administrative endpoint. A remote attacker could exploit this vulnerability to cause the server to exhaust filesystem space.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-20222	7.4	HIGH				A vulnerability in the EIGRP implementation in Cisco Secure Firewall Adaptive Security Appliance (ASA) Software and Cisco Secure Firewall Threat Defense (FTD) Software could allow an unauthenticated, adjacent attacker to cause the device to reload unexpectedly, resulting in a denial of service (DoS) condition. This vulnerability is due to improper resource management when handling EIGRP update messages. An atta...
CVE-2026-59825	7.4	HIGH		0.003		Mastodon is a free, open-source social network server based on ActivityPub. Prior to 4.4.19 and from 4.5.0 until 4.5.12, Mastodon's app/models/concerns/user/ldap_authenticable.rb mutates OpenSSL::SSL::SSLContext::DEFAULT_PARAMS when LDAP authentication uses LDAP_TLS_NO_VERIFY=true, disabling SSL and TLS certificate verification globally for requests made by puma web processes while sidekiq background jobs remain u...
CVE-2026-83102	7.4	HIGH		0.003		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Forms. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification acc...
CVE-2026-83162	7.4	HIGH		0.003		Vulnerability in the Oracle Application Object Library product of Oracle E-Business Suite (component: Core). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTPS to compromise Oracle Application Object Library. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification...
CVE-2026-83184	7.4	HIGH		0.003		Vulnerability in the Oracle Application Object Library product of Oracle E-Business Suite (component: Core). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Application Object Library. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification ...
CVE-2026-83218	7.4	HIGH		0.003		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical...
CVE-2026-83334	7.4	HIGH		0.003		Vulnerability in the Oracle Web Services Manager product of Oracle Fusion Middleware (component: Web Services Security). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via SOAP to compromise Oracle Web Services Manager. Successful attacks of this vulnerability can result in unauthorized access to critica...
CVE-2026-84003	7.4	HIGH		0.004	microsoft:azureVmsal-node	Authentication bypass by capture-replay in Microsoft Authentication Library (MSAL) for Node.js allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-87130	7.4	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with network access via SMTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in unauthorized creat...
CVE-2026-87143	7.4	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with network access via TCP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in unauthorized creati...
CVE-2026-87195	7.4	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with network access via TLS to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificatio...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87198	7.4	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificati...
CVE-2026-87206	7.4	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificati...
CVE-2026-87212	7.4	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with network access via SQL to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificatio...
CVE-2026-87213	7.4	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificati...
CVE-2026-87235	7.4	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with network access via SSH to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificatio...
CVE-2026-87242	7.4	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows unauthenticated attacker with network access via TLS to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modificatio...
CVE-2026-67260	7.3	HIGH		0.008	apache:airflow	Apache Airflow 3.3.0 moved human-in-the-loop tasks from the triggerer to a new `awaiting_input` task state swept by the scheduler. That sweep deserializes the task instance's `next_kwargs` without an allow-list, so a Dag author — who controls that value through the task execution API — can cause an arbitrary module import and object instantiation inside the scheduler process, or terminate the scheduler job. No non...
CVE-2026-67326	7.3	HIGH		0.003	gitpython_project:gitpython	GitPython before 3.1.50 fails to validate newline characters in the section parameter of config_writer(), allowing attackers to inject arbitrary section headers into .git/config. Attackers can inject newlines to create a forged [core] section with hooksPath pointing to attacker-controlled directories, achieving remote code execution when git hooks are triggered.
CVE-2026-69097	7.3	HIGH		0.003	gitpython_project:gitpython	GitPython before 3.1.53 fails to properly escape section names in git config files, allowing attackers to inject arbitrary configuration directives through malicious submodule names. Attackers can inject core.sshCommand or other dangerous config keys into the victim's .git/config via create_submodule or clone_from operations, achieving remote code execution when git performs ssh operations.
CVE-2026-73955	7.3	HIGH		0.002		Vulnerability in the PeopleSoft Enterprise PeopleTools product of Oracle PeopleSoft (component: Charting). Supported versions that are affected are 8.61-8.63. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise PeopleSoft Enterprise PeopleTools. Successful attacks require human interaction from a person other than the attacker. Successful attacks of this vul...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-75092	7.3	HIGH		0.001		A privilege escalation flaw was found in the scan_mysql actor of leapp-upgrade-el9toel10 (provided by leapp-repository). During RHEL 9 to RHEL 10 upgrades, the actor runs: mysqld --validate-config --log-error-verbosity=2 directly as root in the Leapp actor context, bypassing the packaged MySQL systemd unit that normally starts the daemon as User=mysql. A process compromised as the mysql OS identity can write a ve...
CVE-2026-83155	7.3	HIGH		0.002		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with access to the physical communication segment attached to the hardware where the Siebel CRM Deployment executes to compromise Siebel CRM Deployment. Successful attacks of this vulnerabili...
CVE-2026-83185	7.3	HIGH		0.003		Vulnerability in the Oracle Common Applications product of Oracle E-Business Suite (component: CRM User Management Framework). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Common Applications. Successful attacks require human interaction from a person other than the attacker. Successful a...
CVE-2026-83190	7.3	HIGH		0.002		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Siebel CRM Deployment executes to compromise Siebel CRM Deployment. Successful attacks require human interaction from a person other than the attacker. ...
CVE-2026-83193	7.3	HIGH		0.002		Vulnerability in the Siebel Apps - Life Sciences product of Oracle Siebel CRM (component: Life Sciences). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Siebel Apps - Life Sciences executes to compromise Siebel Apps - Life Sciences. Successful attacks require human interaction from a person other than the ...
CVE-2026-83242	7.3	HIGH		0.002		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Experience Manager). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability...
CVE-2026-83277	7.3	HIGH		0.002		Vulnerability in the Oracle Agile PLM MCAD Connector product of Oracle Supply Chain (component: CAX Client). The supported version that is affected is 3.6. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Agile PLM MCAD Connector executes to compromise Oracle Agile PLM MCAD Connector. While the vulnerability is in Oracle Agile PLM MCAD Connector, atta...
CVE-2026-85386	7.3	HIGH				Concrete CMS before 9.5.4 did not sanitize XML and XSLT documents uploaded through a public Form Block file-upload question. Plain XML uploads were validated by file extension only and stored as publicly accessible files that were served inline from the application's own origin. An unauthenticated visitor could therefore store an XML document containing an xml-stylesheet processing instruction that referenced an a...
CVE-2026-87145	7.3	HIGH		0.002		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in unauthorized update,...
CVE-2026-87260	7.3	HIGH		0.003		Vulnerability in the Oracle Agile Engineering Data Management product of Oracle Supply Chain (component: Engineering Communication Interface). The supported version that is affected is 6.2.1. Easily exploitable vulnerability allows low privileged attacker with access to the physical communication segment attached to the hardware where the Oracle Agile Engineering Data Management executes to compromise Oracle Agi...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87261	7.3	HIGH		0.001		Vulnerability in the Oracle Agile Engineering Data Management product of Oracle Supply Chain (component: Engineering Communication Interface). The supported version that is affected is 6.2.1. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Agile Engineering Data Management executes to compromise Oracle Agile Engineering Data Management. While the vul...
CVE-2026-89910	7.3	HIGH				In the Linux kernel, the following vulnerability has been resolved: LoongArch: KVM: Fix uninitialized stack variable issue with dmsintc Variable vector[] is declared on stack in function dmsintc_inject_irq() and sometimes it is used without initialized. Here fix this issue.
CVE-2026-11934	7.2	HIGH		0.003		IBM Verify Identity Access could allow an administrator to execute additional commands they are not entitled to due to improper validation of user supplied input.
CVE-2026-18690	7.2	HIGH		0.003	mongodb:mongodb	An issue in MongoDB Server could allow an authenticated user with a limited database-scoped role to perform an action against protected system collections that their assigned privileges should not permit. This could result in critical system collections being dropped and recreated without proper authorization.
CVE-2026-18693	7.2	HIGH		0.002	mongodb:mongodb	An issue in MongoDB Server's handling of timeseries collections could allow an authenticated user with write privileges to cause an internal data structure to become inconsistent through certain document insertions. A subsequent insert into the affected bucket could then result in the server accessing memory outside its intended bounds, potentially causing a server crash (denial of service), exposure of limited me...
CVE-2026-73966	7.2	HIGH		0.004		Vulnerability in the Siebel Apps - Marketing product of Oracle Siebel CRM (component: Marketing). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Siebel Apps - Marketing. Successful attacks of this vulnerability can result in takeover of Siebel Apps - Marketing. CVSS 3.1 Base Score 7.2 (Confidentiality...
CVE-2026-76424	7.2	HIGH				A vulnerability in the REST API of Cisco ISE could allow an authenticated, remote attacker to upload or copy arbitrary files on an affected device. This vulnerability is due to insufficient validation in file operations. An attacker could exploit this vulnerability by uploading a file with a crafted path. A successful exploit could allow the attacker to upload files to arbitrary locations and execute arbitrary ...
CVE-2026-82061	7.2	HIGH		0.003	mongodb:mongodb	A use-after-free security issue exists in the server's query execution memory tracking subsystem. An authenticated user with read privileges can trigger a write to freed heap memory through a sequence of standard database commands, leading to server process crash or potential memory corruption. No user interaction is required.
CVE-2026-82071	7.2	HIGH		0.003	mongodb:mongodb	Insufficient validation of storage engine configuration options in MongoDB Server allows an authenticated user with write privileges to supply crafted parameters during collection creation that override internal storage metadata. This results in an out-of-bounds memory write in the server process, causing a denial of service via server crash, with potential for further impact including arbitrary code execution.
CVE-2026-83004	7.2	HIGH		0.001		Vulnerability in the Oracle WebCenter Enterprise Capture product of Oracle Fusion Middleware (component: Client Bundle). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Difficult to exploit vulnerability allows low privileged attacker with logon to the infrastructure where Oracle WebCenter Enterprise Capture executes to compromise Oracle WebCenter Enterprise Capture. Successful attacks requi...
CVE-2026-83016	7.2	HIGH		0.001		Vulnerability in the PeopleSoft Enterprise PeopleTools product of Oracle PeopleSoft (component: SQR). Supported versions that are affected are 8.61-8.63. Difficult to exploit vulnerability allows high privileged attacker with logon to the infrastructure where PeopleSoft Enterprise PeopleTools executes to compromise PeopleSoft Enterprise PeopleTools. Successful attacks require human interaction from a person othe...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83063	7.2	HIGH		0.004		Vulnerability in the Oracle Internet Directory product of Oracle Fusion Middleware (component: OID LDAP Server). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows high privileged attacker with network access via LDAP to compromise Oracle Internet Directory. Successful attacks of this vulnerability can result in takeover of Oracle Internet Directory. CVSS...
CVE-2026-83082	7.2	HIGH		0.005		Vulnerability in the Oracle Marketing product of Oracle E-Business Suite (component: Audience). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Marketing. Successful attacks of this vulnerability can result in takeover of Oracle Marketing. CVSS 3.1 Base Score 7.2 (Confidentiality, Integrity...
CVE-2026-83112	7.2	HIGH		0.005		Vulnerability in the Oracle Lease and Finance Management product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.7-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Lease and Finance Management. Successful attacks of this vulnerability can result in takeover of Oracle Lease and Fin...
CVE-2026-83117	7.2	HIGH		0.005		Vulnerability in the Applications DBA product of Oracle E-Business Suite (component: AD Utilities). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Applications DBA. Successful attacks of this vulnerability can result in takeover of Applications DBA. CVSS 3.1 Base Score 7.2 (Confidentiality, Integ...
CVE-2026-83176	7.2	HIGH		0.005		Vulnerability in the Oracle Common Applications product of Oracle E-Business Suite (component: CRM User Management Framework). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Common Applications. Successful attacks of this vulnerability can result in takeover of Oracle Common Applications. ...
CVE-2026-83188	7.2	HIGH		0.005		Vulnerability in the Oracle Depot Repair product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Depot Repair. Successful attacks of this vulnerability can result in takeover of Oracle Depot Repair. CVSS 3.1 Base Score 7.2 (Confid...
CVE-2026-83195	7.2	HIGH		0.005		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows high privileged attacker with network access via TCP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in takeover of Siebel CRM Deployment. CVSS 3.1 Base Score 7.2 (Confidenti...
CVE-2026-83273	7.2	HIGH		0.005		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). The supported version that is affected is 26.01.0.0.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can result in takeover of Oracle...
CVE-2026-83298	7.2	HIGH		0.005		Vulnerability in the Oracle BI Publisher product of Oracle Analytics (component: BI Platform Security). The supported version that is affected is 12.2.1.4.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle BI Publisher. Successful attacks of this vulnerability can result in takeover of Oracle BI Publisher. CVSS 3.1 Base Score 7.2 (Confidentialit...
CVE-2026-83322	7.2	HIGH		0.005		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). Supported versions that are affected are 8.2.0.0.0 and 26.01.0.0.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can result in takeo...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83325	7.2	HIGH		0.005		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). Supported versions that are affected are 8.2.0.0.0 and 26.01.0.0.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. Successful attacks of this vulnerability can result in takeo...
CVE-2026-83328	7.2	HIGH		0.005		Vulnerability in the Oracle Applications Framework product of Oracle E-Business Suite (component: Personalization). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Applications Framework. Successful attacks of this vulnerability can result in takeover of Oracle Applications Framework. CVSS ...
CVE-2026-83344	7.2	HIGH		0.005		Vulnerability in the Oracle Identity Manager Connector product of Oracle Fusion Middleware (component: Database Application Table). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Identity Manager Connector. Successful attacks of this vulnerability can result in takeover of Orac...
CVE-2026-83440	7.2	HIGH		0.005		Vulnerability in the Oracle Product Hub product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Product Hub. Successful attacks of this vulnerability can result in takeover of Oracle Product Hub. CVSS 3.1 Base Score 7.2 (Confident...
CVE-2026-83442	7.2	HIGH		0.005		Vulnerability in the Oracle Product Hub product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Product Hub. Successful attacks of this vulnerability can result in takeover of Oracle Product Hub. CVSS 3.1 Base Score 7.2 (Confident...
CVE-2026-83453	7.2	HIGH		0.004		Vulnerability in the Oracle Document Management and Collaboration product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Document Management and Collaboration. Successful attacks of this vulnerability can result in takeover of Or...
CVE-2026-83481	7.2	HIGH		0.004		Vulnerability in the Oracle Contracts product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.14-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Contracts. Successful attacks of this vulnerability can result in takeover of Oracle Contracts. CVSS 3.1 Base Score 7.2 (Confidentialit...
CVE-2026-83482	7.2	HIGH		0.004		Vulnerability in the Oracle Contracts product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.14-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Contracts. Successful attacks of this vulnerability can result in takeover of Oracle Contracts. CVSS 3.1 Base Score 7.2 (Confidentialit...
CVE-2026-87207	7.2	HIGH		0.005		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows high privileged attacker with network access via SQL to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management....
CVE-2026-87239	7.2	HIGH		0.005		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87244	7.2	HIGH		0.005		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management...
CVE-2026-87246	7.2	HIGH		0.005		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in takeover of Oracle Hyperion Financial Management...
CVE-2026-87976	7.2	HIGH				Apache NiFi Registry 0.4.0 through 2.11.0 are subject to path manipulation when storing extension bundle content using group, artifact, and version coordinates from uploaded NAR manifests. The default file persistence provider used coordinates as filesystem path components without rejected parent-directory names, and the path-containment check compared an unnormalized resolved path. An authenticated user authorize...
CVE-2026-12667	7.1	HIGH		0.004		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 could allow an authenticated attacker to read files from a vulnerable .NET client or cause limited denial of service due to improper handling of XML external entities in RFH2 folder parsing.
CVE-2026-12752	7.1	HIGH		0.005		IBM Business Automation Workflow containers and traditional is vulnerable to an XML external entity injection (XXE) attack when processing XML data. A remote attacker could exploit this vulnerability to expose sensitive information or consume memory resource.
CVE-2026-12756	7.1	HIGH		0.005		IBM Business Automation Workflow containers and traditional is vulnerable to an XML external entity injection (XXE) attack when processing XML data. A remote attacker could exploit this vulnerability to expose sensitive information or consume memory resources.
CVE-2026-13107	7.1	HIGH		0.004		IBM Business Automation Workflow containers and traditional may use programming model artifacts that are vulnerable to XML Entity Injection attacks by default.
CVE-2026-13275	7.1	HIGH		0.003		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 Managed File Transfer could allow an authenticated attacker to read arbitrary files or perform server-side request forgery due to XML external entity injection in reply message processing.
CVE-2026-13285	7.1	HIGH		0.004		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 is vulnerable to an XML external entity injection (XXE) attack when processing XML data. A remote attacker could exploit this vulnerability to expose sensitive information or consume memory resources.
CVE-2026-13287	7.1	HIGH		0.004		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 is vulnerable to an XML external entity injection (XXE) attack when processing XML data. A remote attacker could exploit this vulnerability to expose sensitive information or consume memory resources.
CVE-2026-18687	7.1	HIGH		0.002	mongodb:mongodb	MongoDB Server's handling of a Queryable Encryption maintenance operation did not properly validate certain request parameters against the collection's encrypted field configuration before use. An authenticated user with readWrite privileges could submit a specially formed request that leads to a server crash or excessive internal writes, resulting in resource exhaustion and corruption of encrypted index data.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-18688	7.1	HIGH		0.003	mongodb:mongodb	An issue in MongoDB Server's aggregation framework could allow an authenticated user to trigger an out-of-bounds memory read by providing a specially formed numeric parameter in a certain aggregation pipeline stage. This could result in a server crash (denial of service) and may potentially expose a limited amount of memory contents.
CVE-2026-18694	7.1	HIGH		0.003	mongodb:mongodb	An issue in MongoDB Server's geospatial query processing could allow an authenticated user with write privileges to cause certain malformed geometry data to be stored and later processed without proper validation. Subsequent queries against this data could then result in the server accessing memory outside its intended bounds. This could result in a server crash (denial of service) and may expose a limited amount ...
CVE-2026-18695	7.1	HIGH		0.003	mongodb:mongodb	An issue in MongoDB Server's handling of certain query predicates against time-series collections with a metaField could allow an authenticated user with write access to cause the server process to terminate unexpectedly, resulting in a denial of service.
CVE-2026-18701	7.1	HIGH		0.003	mongodb:mongodb	An issue in MongoDB Server's query subsystem could allow an authenticated user with read privileges to cause the server process to terminate unexpectedly by submitting a specially formed query filter. This could result in a denial of service.
CVE-2026-18704	7.1	HIGH		0.002	mongodb:mongodb	An issue in MongoDB Server's aggregation framework could allow an authenticated user with only read privileges to perform write operations against collections they should not be able to modify. This is due to an internal-use aggregation stage being reachable by external clients without an appropriate authorization check on its embedded operations.
CVE-2026-18705	7.1	HIGH		0.003	mongodb:mongodb	An issue in MongoDB Server's Atlas Vector Search feature could allow an authenticated user with read access to one view to retrieve documents from a different, protected view over the same underlying collection. This is due to insufficient handling of certain user-supplied fields when constructing an internal request forwarded to the search process.
CVE-2026-20300	7.1	HIGH				A vulnerability in Cisco ISE could allow an authenticated, remote attacker to conduct SQL injection attacks on an affected device. To exploit this vulnerability, the attacker must have at least low-privileged administrative credentials. This vulnerability is due to improper validation of user-supplied input. An attacker could exploit this vulnerability by sending a crafted request to an affected device. A succe...
CVE-2026-21586	7.1	HIGH		0.003		This High severity Improper Authorization vulnerability was introduced in versions 7.4.0, 7.13.0, 8.5.0, 8.9.0, 9.0.1, 9.1.0, 9.2.0, 9.3.1, 9.4.0, 9.5.1, 10.0.2, 10.1.0, and 10.2.0 of Confluence Data Center. This Improper Authorization vulnerability, with a CVSS Score of 7.1, allows an authenticated attacker to gain unintended access and can lead to the exposure of resources or functionality, possibly providing...
CVE-2026-21587	7.1	HIGH		0.003		This High severity Improper Authorization vulnerability was introduced in version 11.3.0 of Jira Service Management Data Center. This Improper Authorization vulnerability, with a CVSS Score of 7.1, allows an authenticated attacker to gain unintended access and can lead to the exposure of resources or functionality, possibly providing attackers with sensitive information or even execute arbitrary code. Atla...
CVE-2026-21588	7.1	HIGH		0.003		This High severity DoS (Denial of Service) vulnerability was introduced in versions 8.9.0, 9.0.1, 9.1.0, 9.2.0, 9.3.1, 9.4.0, 9.5.1, 10.0.2, 10.1.0, and 10.2.0 of Confluence Data Center. This DoS (Denial of Service) vulnerability, with a CVSS Score of 7.1, allows an authenticated attacker to cause a resource to be unavailable for its intended users by temporarily or indefinitely disrupting services of a host co...
CVE-2026-46054	7.1	HIGH		0.001	linux:linux_kernel	In the Linux kernel, the following vulnerability has been resolved: selinux: fix overlays mmap() and mprotect() access checks The existing SELinux security model for overlays is to allow access if the current task is able to access the top level file (the "user" file) and the mounter's credentials are sufficient to access the lower level file (the "backing" file). Unfortunately, the current code does not prop...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-66305	7.1	HIGH		0.003	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Use of client-side authentication in Skype for Business allows an authorized attacker to perform spoofing over a network.
CVE-2026-76821	7.1	HIGH		0.005		OpenCTI is an open source platform for managing cyber threat intelligence knowledge and observables. Prior to 7.260706.0, the JSON ingestion mapper's extractWithRegexp formula function compiled a user-supplied regular expression with the JavaScript RegExp engine in opencti-platform/opencti-graphql/src/parser/json-mapper.ts without validating its complexity. An authenticated user with JSON mapper creation permission...
CVE-2026-80350	7.1	HIGH		0.003		OneUptime's webhook target check rejects private and loopback addresses given in IPv4 form and a small set of IPv6 forms, but has no case for the IPv4-mapped IPv6 range. The webhook delivery path calls SSRFProtection.validateWebhookTargetIsSafe, and the host-literal screening inside Common/Server/Utils/SSRFProtection.ts, performed by isBlockedHostnameLiteral, rejects private and loopback IPv4 ranges and tests an I...
CVE-2026-80380	7.1	HIGH		0.001	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote attacker to perform unauthorized actions due to cross-site request forgery.
CVE-2026-82052	7.1	HIGH		0.004	mongodb:mongodb	The \$regexFindAll expression can be used by an authenticated user who can run aggregation pipeline stages to crash a MongoDB server (mongod). Under certain specific conditions the regex match can start in the middle of a multi-code-unit character, triggering an assertion during query execution.
CVE-2026-82054	7.1	HIGH		0.003	mongodb:mongodb	A security issue exists in MongoDB server's JSON Pointer parser used during \$jsonSchema query filter processing. When a find command includes a specially crafted \$jsonSchema filter field, the parser processes the input without enforcing adequate limits on iteration count or total allocation size, resulting in significant memory amplification. Under concurrent request load, the cumulative memory consumption can ex...
CVE-2026-82055	7.1	HIGH		0.003	mongodb:mongodb	A security issue exists in MongoDB's 2dsphere index key generation that can cause a server crash due to a null pointer dereference. When a specially crafted GeoJSON document is inserted into a collection with a 2dsphere index, an inconsistency in geometry parsing can leave an internal object in an invalid, partially initialized state. During subsequent index key generation, access to this improperly initialized ob...
CVE-2026-82057	7.1	HIGH		0.003	mongodb:mongodb	A security issue was discovered in MongoDB where an authenticated user with readWrite privileges could crash the mongod server process. By specifying a custom WiredTiger storage configuration option with an incompatible value during collection creation, a user could cause a type confusion in the storage engine layer. When documents were subsequently read from the misconfigured collection, the resulting mismatch in...
CVE-2026-82058	7.1	HIGH		0.003	mongodb:mongodb	A flaw in MongoDB's JSON Schema validation error generation code allows an authenticated user with readWrite privileges to crash the mongod server. When a BSON document containing an array with a malformed numeric field name fails a \$jsonSchema items type constraint, the error generation path performs unsafe numeric conversion on the user-controlled field name without proper exception handling, resulting in an unc...
CVE-2026-82065	7.1	HIGH		0.003	mongodb:mongodb	A security issue in the MongoDB Server's storage engine integration layer allows an authenticated user with collection creation privileges to cause a persistent denial of service. Insufficient validation of user-supplied storage configuration options permits values that, once persisted to durable metadata, trigger a fatal assertion failure when the metadata is subsequently read by diagnostic operations. The corrup...
CVE-2026-82068	7.1	HIGH		0.003	mongodb:mongodb	A security issue in MongoDB Server allows an authenticated user with write privileges to trigger a persistent fatal assertion crash by sending specially crafted retryable write commands. The crash state is durably persisted, causing the server process to repeatedly crash on restart and potentially propagating to additional nodes in a sharded cluster. Manual intervention is required to restore service availability.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-82070	7.1	HIGH		0.002	mongodb:mongodb	A security issue in MongoDB Server's diagnostic reporting interface allows an authenticated user with monitoring privileges to access insufficiently protected credentials from concurrent administrative operations. The same credentials are properly redacted in server log output, but the diagnostic interface omits equivalent redaction. Successful exploitation requires a valid authenticated session with monitoring-le...
CVE-2026-82073	7.1	HIGH		0.003	mongodb:mongodb	A security issue in the MongoDB Server aggregation framework allows an authenticated user with limited read privileges to bypass view-level authorization checks and access data from unauthorized collections when Atlas Search features are in use. The issue stems from insufficient validation of an internal command parameter that can be set by external clients, causing a security check to be improperly skipped.
CVE-2026-82074	7.1	HIGH		0.002	mongodb:mongodb	MongoDB Server contains an incorrect authorization vulnerability in the aggregation framework. An authenticated user with minimal privileges can craft a specially formatted aggregation request that causes the server's authorization subsystem to evaluate a different operation than what is actually executed, resulting in unauthorized read access to collection data within the target database.
CVE-2026-83044	7.1	HIGH		0.004		Vulnerability in the Oracle XML Gateway product of Oracle E-Business Suite (component: Install). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle XML Gateway. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Oracle XML Gate...
CVE-2026-83046	7.1	HIGH		0.004		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Runtime Tools). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete ...
CVE-2026-83050	7.1	HIGH		0.002		Vulnerability in the Oracle WebCenter Portal product of Oracle Fusion Middleware (component: Runtime Tools). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle WebCenter Portal. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete ...
CVE-2026-83080	7.1	HIGH		0.003		Vulnerability in the Oracle Banking Branch product of Oracle Financial Services Applications (component: Reports). Supported versions that are affected are 14.5.0.0.0-14.9.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Banking Branch. Successful attacks require human interaction from a person other than the attacker. Successful attacks o...
CVE-2026-83092	7.1	HIGH		0.003		Vulnerability in the Oracle Field Service product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Field Service. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to cr...
CVE-2026-83111	7.1	HIGH		0.002		Vulnerability in the Oracle Partner Management product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Partner Management. While the vulnerability is in Oracle Partner Management, attacks may significantly impact additional produ...
CVE-2026-83113	7.1	HIGH		0.003		Vulnerability in the Oracle Quality product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Quality. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Oracle Qual...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83123	7.1	HIGH		0.004		Vulnerability in the Oracle Report Manager product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTPS to compromise Oracle Report Manager. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to ...
CVE-2026-83130	7.1	HIGH		0.003		Vulnerability in the Oracle Site Hub product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Site Hub. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical data ...
CVE-2026-83158	7.1	HIGH		0.001		Vulnerability in the Oracle Applications Manager product of Oracle E-Business Suite (component: Command Line - RapidClone). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Applications Manager executes to compromise Oracle Applications Manager. Successful attacks of this vulnerability can result...
CVE-2026-83161	7.1	HIGH		0.003		Vulnerability in the Oracle Project Intelligence product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Project Intelligence. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification ...
CVE-2026-83171	7.1	HIGH		0.003		Vulnerability in the Oracle One-to-One Fulfillment product of Oracle E-Business Suite (component: Documents). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle One-to-One Fulfillment. While the vulnerability is in Oracle One-to-One Fulfillment, attacks may significantly impact additional pro...
CVE-2026-83173	7.1	HIGH		0.004		Vulnerability in the Oracle One-to-One Fulfillment product of Oracle E-Business Suite (component: Documents). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle One-to-One Fulfillment. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete acces...
CVE-2026-83179	7.1	HIGH		0.003		Vulnerability in the Oracle Common Applications Calendar product of Oracle E-Business Suite (component: Applications Calendar). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Common Applications Calendar. Successful attacks of this vulnerability can result in unauthorized creation, delet...
CVE-2026-83186	7.1	HIGH		0.004		Vulnerability in the Oracle Common Applications Calendar product of Oracle E-Business Suite (component: Applications Calendar). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Common Applications Calendar. Successful attacks of this vulnerability can result in unauthorized creation, deletio...
CVE-2026-83187	7.1	HIGH		0.003		Vulnerability in the Oracle Common Applications Calendar product of Oracle E-Business Suite (component: Applications Calendar). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Common Applications Calendar. Successful attacks of this vulnerability can result in unauthorized creation, deletio...
CVE-2026-83206	7.1	HIGH		0.003		Vulnerability in the Oracle Banking Corporate Lending Process Management product of Oracle Financial Services Applications (component: Base). Supported versions that are affected are 14.5.0.0.0-14.9.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Banking Corporate Lending Process Management. Successful attacks require human interaction fr...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83217	7.1	HIGH		0.002		Vulnerability in the Siebel CRM End User product of Oracle Siebel CRM (component: Open UI). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM End User. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Siebel CRM End User acce...
CVE-2026-83219	7.1	HIGH		0.001		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Siebel CRM Deployment executes to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized creation, delet...
CVE-2026-83221	7.1	HIGH		0.002		Vulnerability in the Siebel CRM Integration product of Oracle Siebel CRM (component: EAI). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via SOAP to compromise Siebel CRM Integration. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Siebel CRM Integration...
CVE-2026-83224	7.1	HIGH		0.004		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Server Infrastructure). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Siebel...
CVE-2026-83230	7.1	HIGH		0.002		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Siebel Management Console). Supported versions that are affected are 17.0-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Si...
CVE-2026-83237	7.1	HIGH		0.004		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result in...
CVE-2026-83238	7.1	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result in...
CVE-2026-83240	7.1	HIGH		0.001		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Commerce Guided Search / Oracle Commerce Experience Manager executes to compromise Oracle Commerce Guided Search / Oracl...
CVE-2026-83244	7.1	HIGH		0.002		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Commerce Guided Search / Oracle Commerce Experience Manager executes to...
CVE-2026-83259	7.1	HIGH		0.004		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result in...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83300	7.1	HIGH		0.004		Vulnerability in the Oracle XML Gateway product of Oracle E-Business Suite (component: Install). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle XML Gateway. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Oracle XML Gate...
CVE-2026-83324	7.1	HIGH		0.003		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: BI Platform Security). Supported versions that are affected are 8.2.0.0.0 and 26.01.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Business Intelligence Enterprise Edition. While the vulnerability is in Oracle Business Intelligen...
CVE-2026-83332	7.1	HIGH		0.003		Vulnerability in the Oracle Applications Framework product of Oracle E-Business Suite (component: Personalization). Supported versions that are affected are 12.2.9-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Applications Framework. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...
CVE-2026-83345	7.1	HIGH		0.004		Vulnerability in the Oracle XML Gateway product of Oracle E-Business Suite (component: Install). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle XML Gateway. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Oracle XML Gate...
CVE-2026-83352	7.1	HIGH		0.004		Vulnerability in the Oracle XML Gateway product of Oracle E-Business Suite (component: Install). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle XML Gateway. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Oracle XML Gate...
CVE-2026-83417	7.1	HIGH		0.003		Vulnerability in the Oracle Communications Cloud Native Core Security Edge Protection Proxy product of Oracle Communications (component: SEPP). Supported versions that are affected are 26.1.200 and 25.2.201. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Communications Cloud Native Core Security Edge Pro...
CVE-2026-83436	7.1	HIGH		0.003		Vulnerability in the Oracle Depot Repair product of Oracle E-Business Suite (component: Recall Management). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Depot Repair. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Ora...
CVE-2026-83484	7.1	HIGH		0.003		Vulnerability in the Oracle US Federal Human Resources product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle US Federal Human Resources. Successful attacks of this vulnerability can result in unauthorized creation, deletion or m...
CVE-2026-87126	7.1	HIGH		0.004		Vulnerability in the Oracle Report Manager product of Oracle E-Business Suite (component: Reports Security). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Report Manager. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all ...
CVE-2026-87135	7.1	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in unauthorized access t...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87142	7.1	HIGH		0.003		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTPS to compromise Oracle Hyperion Data Relationship Management. Successful attacks require human interaction from a person other than the a...
CVE-2026-87146	7.1	HIGH		0.002		Vulnerability in the Oracle Hyperion Data Relationship Management product of Oracle Hyperion (component: Access and security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Data Relationship Management. Successful attacks of this vulnerability can result in unauthorized access t...
CVE-2026-87149	7.1	HIGH		0.002		Vulnerability in the Oracle Contract Lifecycle Management for Public Sector product of Oracle E-Business Suite (component: Award/PO). Supported versions that are affected are 12.2.8-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Contract Lifecycle Management for Public Sector. Successful attacks of this vulnerability can result in unaut...
CVE-2026-87156	7.1	HIGH		0.003		Vulnerability in the Oracle Product Hub product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Hub. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Ora...
CVE-2026-87158	7.1	HIGH		0.003		Vulnerability in the Oracle Order Management product of Oracle E-Business Suite (component: Enterprise Command Center). The supported version that is affected is V16. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Order Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to ...
CVE-2026-87160	7.1	HIGH		0.002		Vulnerability in the Oracle HRMS (India) product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTPS to compromise Oracle HRMS (India). Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all ...
CVE-2026-87191	7.1	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...
CVE-2026-87192	7.1	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...
CVE-2026-87208	7.1	HIGH		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...
CVE-2026-87209	7.1	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87220	7.1	HIGH		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. S...
CVE-2026-87225	7.1	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...
CVE-2026-87236	7.1	HIGH		0.004		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete...
CVE-2026-87249	7.1	HIGH		0.003		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Hyperion Financial Management. Successful attacks require human interaction from a person other than the attacker. Successful attacks ...
CVE-2026-87262	7.1	HIGH		0.003		Vulnerability in the Oracle Agile Engineering Data Management product of Oracle Supply Chain (component: Engineering Communication Interface). The supported version that is affected is 6.2.1. Easily exploitable vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Agile Engineering Data Management executes to compromise Oracle Ag...
CVE-2026-87818	7.1	HIGH		0.002	gitpython_project:gitpython	GitPython 3.1.59 fails to restrict the --no-index option in the high-level diff API, allowing attackers to read arbitrary filesystem paths as repository operands. Attackers can combine --no-index with -l/--ignore-matching-lines to create a content-dependent Boolean oracle, repeatedly querying local files to recover single-line secrets through distinguishable success or error responses.
CVE-2026-87999	7.1	HIGH		0.002	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. Prior to 0.11.1, POST /api/v1/retrieval/process/web and POST /api/v1/retrieval/process/web/search in backend/open_webui/retrieval/web/utlis.py treated Python's globally routable address classification as proof that a destination was external. An authenticated user could make an Azure-hosted instance fetch and return content from ...
CVE-2026-89792	7.1	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: ksmbd: prevent out-of-bounds reads in share config responses Validate IPC share configuration payload sizes before consuming variable-length fields. Bound veto list parsing and account for the separator byte when deriving the path length.
CVE-2026-89818	7.1	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/amdgpu/vcn: fix integer overflow in dec_msg buffer count check If the supplied msg[2] (num_buffers) is 0x3FFFFFFF, the expression 6 + num_buffers * 4 wraps to 2 and the bounds check passes, letting the parser loop far past the end of the message BO. Triggering it additionally requires a ~4GiB mapping so that msg[1] survives the earlier "head...
CVE-2026-89826	7.1	HIGH				In the Linux kernel, the following vulnerability has been resolved: drm/panthor: harden firmware build-info bounds checks panthor_fw_read_build_info() checks whether the metadata range fits in the firmware image with hdr.meta_start + hdr.meta_size. Both fields are u32, so the addition can wrap and let an out-of-bounds range pass validation. The function also reads the "git_sha: " prefix without first checking t...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89838	7.1	HIGH				In the Linux kernel, the following vulnerability has been resolved: f2fs: limit recovery filename logging to stored length F2FS stores recovery filenames as a length plus a fixed-size i_name buffer. The buffer is not NUL-terminated, but recover_inode() and recover_dentry() print it with %s. For a 255-byte filename, recovery logging can read past i_name into the following raw inode fields. Print the name with ...
CVE-2026-89840	7.1	HIGH				In the Linux kernel, the following vulnerability has been resolved: f2fs: validate MOVE_RANGE destination size F2FS_IOC_MOVE_RANGE checks the source range, but not the destination end before updating i_size. A source hole can expose this: __clone_blkaddrs() skips NULL_ADDR entries and returns success, so the caller can still extend the destination inode with unchecked pos_out + len. Reject destination overflow ...
CVE-2026-89912	7.1	HIGH				In the Linux kernel, the following vulnerability has been resolved: KVM: arm64: vgic-its: Don't dereference a NULL collection on ITT save MAPC with V=0 drops ite->collection but leaves the ITE on the device's ITT list, and vgic_its_save_ite() dereferences it unconditionally. A guest that issues MAPD, MAPTI and then MAPC(V=0) therefore oopses the host when the VMM issues KVM_DEV_ARM_ITS_SAVE_TABLES to migrate it....
CVE-2026-89927	7.1	HIGH				In the Linux kernel, the following vulnerability has been resolved: KVM: x86: hyper-v: Clamp stimer deadline to avoid livelock Fix an issue where userspace or the guest can program an Hyper-V synthetic timer to have a deadline in the past via integer overflow, preventing the CPU from making progress and triggering an RCU stall. Hyper-V's SynIC exposes 4 per-vCPU synthetic timers to the guest, which are emulated...
CVE-2026-90016	7.1	HIGH				In the Linux kernel, the following vulnerability has been resolved: staging: rtl8723bs: fix OOB read in rtw_restruct_wmm_ie() rtw_restruct_wmm_ie() scans in_ie for a WMM IE with: while (i < in_len) { ... if (i + 5 < in_len && in_ie[i] == 0xDD && ...) { ... break; } i += (in_ie[i] + 1) + 2); /* to the next IE element */ } When the "i + 5 < in_len" match check fails simply because i is within 5 by...
CVE-2026-90017	7.1	HIGH				In the Linux kernel, the following vulnerability has been resolved: staging: rtl8723bs: fix OOB read in rtw_action_frame_parse() rtw_action_frame_parse() takes a frame_len parameter but never actually checks it before indexing into the frame body: const u8 *frame_body = frame + sizeof(struct ieee80211_hdr_3addr); ... c = frame_body[0]; ... a = frame_body[1]; frame_body already points 24 bytes (sizeof(stru...
CVE-2026-92299	7.1	HIGH		0.003		@jitsi/electron-sdk before 10.0.5 exposes getDesktopSources() via contextBridge without requiring an active getDisplayMedia() picker, allowing any script in the meeting page to enumerate screens and windows. Attackers can call the jitsi-screen-sharing-get-sources IPC route to retrieve desktop thumbnails at arbitrary resolution without user consent or operating system permission prompts.
CVE-2026-92456	7.1	HIGH				yshop-crm through 2.1.3 fails to enforce authorization on the saveRedisSet and getRedisSet endpoints in CrmCustomerController, allowing any authenticated back-office user to read and modify installation-wide lead-allocation and customer auto-recycling policy. Attackers can invoke these endpoints to manipulate shared Redis keys controlling customer auto-recycling behavior, causing mass customer data deletion, disab...
CVE-2026-92468	7.1	HIGH				zlt2000 microservices-platform through 6.0.0 contains an authorization bypass vulnerability in the search-center service that allows authenticated attackers to read any Elasticsearch index by specifying the index name in POST /search/{indexName} and GET /agg/requestStat/{indexName}/{routing} path variables. Attackers can query arbitrary indices including sys_user to retrieve sensitive user records and password has...
CVE-2026-92750	7.1	HIGH				Harness through 3.3.0 omits access control validation in the infrastructure provider read endpoint, allowing authenticated users to retrieve provider configurations from spaces they do not belong to. Attackers can query the GET /api/v1/infraproviders endpoint with arbitrary space identifiers to expose sensitive provider metadata including Docker endpoints, TLS certificate paths, and cloud project identifiers.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-12150	7.0	HIGH		0.002		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 could allow a remote attacker with a trusted TLS client certificate to cause a denial of service and potentially affect memory contents due to improper validation of deeply nested certificate data during TLS certificate p...
CVE-2026-18696	7.0	HIGH		0.003	mongodb:mongodb	An issue in MongoDB Server's applyOps command could allow an authenticated user with specific non-default privileges to perform certain data-definition operations, such as dropping or modifying collections, against collections they do not have permission to manipulate. This is due to an inconsistency in how the target collection is determined between the authorization check and the actual operation.
CVE-2026-68840	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows USB Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-68904	7.0	HIGH				node-opcua is an OPC UA implementation for TypeScript and Node.js. From 2.0.0 until 2.170.0, node-opcua clients using the default keepSessionAlive setting can enter a repeated reconnection cycle when an OPC UA server's clock skew causes BadInvalidTimestamp responses. ClientSessionKeepAliveManager._ping_server treated the server-originated ServiceFault as a network outage and forced a transport reconnect, while Cli...
CVE-2026-69319	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows USB Video Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69413	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69422	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Use after free in Windows USB Video Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69814	7.0	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Use after free in Windows Credential Providers allows an authorized attacker to elevate privileges locally.
CVE-2026-69816	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Accounts Control allows an authorized attacker to elevate privileges locally.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-69817	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Bluetooth Port Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69818	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Use after free in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69834	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows ALPC allows an authorized attacker to elevate privileges locally.
CVE-2026-69838	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Print Spooler Components allows an authorized attacker to elevate privileges locally.
CVE-2026-69859	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Time-of-check time-of-use (toctou) race condition in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69866	7.0	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69889	7.0	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Bluetooth Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69891	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Media allows an authorized attacker to elevate privileges locally.
CVE-2026-69896	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Use after free in Windows Error Reporting allows an authorized attacker to elevate privileges locally.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-69911	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Microsoft Windows Search Component allows an authorized attacker to elevate privileges locally.
CVE-2026-70283	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Incorrect authorization in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-70562	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Double free in Windows Audio Service allows an authorized attacker to elevate privileges locally.
CVE-2026-70565	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows AF_UNIX Socket Provider allows an authorized attacker to elevate privileges locally.
CVE-2026-70567	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Double free in Windows Display Enhancement Service allows an authorized attacker to elevate privileges locally.
CVE-2026-70568	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Defender Firewall Service allows an authorized attacker to elevate privileges locally.
CVE-2026-71332	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Secure Socket Tunneling Protocol (SSTP) allows an authorized attacker to elevate privileges locally.
CVE-2026-71333	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Access Connection Manager allows an authorized attacker to elevate privileges locally.
CVE-2026-73022	7.0	HIGH		0.002	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Modern Device Management (MDM) allows an authorized attacker to elevate privileges locally.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-76159	7.0	HIGH		0.001		Incorrect Permission Assignment for Critical Resource in the configuration loader of Duplicati for Windows versions before v2.4.0.0 allows a local low-privileged attacker to escalate privileges to NT AUTHORITY\SYSTEM via an attacker-controlled preload.json file.
CVE-2026-77894	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Installer allows an authorized attacker to elevate privileges locally.
CVE-2026-77899	7.0	HIGH		0.002	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2012	Use after free in Windows Security Center allows an authorized attacker to elevate privileges locally.
CVE-2026-82062	7.0	HIGH		0.004	mongodb:mongodb	A security issue in MongoDB Server allows an authenticated user with elevated internal privileges to bypass a disabled feature gate in the applyOps command by specifying an internal replication mode value that was not intended to be client-selectable. This bypass enables execution of container operations that are disabled by default in production configurations, allowing direct storage-engine writes to arbitrary i...
CVE-2026-83015	7.0	HIGH		0.001		Vulnerability in the PeopleSoft Enterprise PeopleTools product of Oracle PeopleSoft (component: Cube Manager). Supported versions that are affected are 8.61-8.63. Difficult to exploit vulnerability allows low privileged attacker with logon to the infrastructure where PeopleSoft Enterprise PeopleTools executes to compromise PeopleSoft Enterprise PeopleTools. Successful attacks of this vulnerability can result in ...
CVE-2026-83150	7.0	HIGH		0.001		Vulnerability in Oracle Application Testing Suite. The supported version that is affected is 13.3.0.1. Difficult to exploit vulnerability allows unauthenticated attacker with logon to the infrastructure where Oracle Application Testing Suite executes to compromise Oracle Application Testing Suite. Successful attacks require human interaction from a person other than the attacker. Successful attacks of this vuln...
CVE-2026-83231	7.0	HIGH		0.002		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: helidon-dbclient-mongodb). Supported versions that are affected are 3.0.0-3.2.20 and 4.0.0-4.5.4. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all He...
CVE-2026-83239	7.0	HIGH		0.001		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Endeca Application Controller). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Commerce Guided Search / Oracle Commerce Experience Manager executes to compromise Oracle Comm...
CVE-2026-83252	7.0	HIGH		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result...
CVE-2026-83316	7.0	HIGH		0.001		Vulnerability in the Oracle Business Intelligence Enterprise Edition product of Oracle Analytics (component: Platform Security). The supported version that is affected is 26.01.0.0.0. Difficult to exploit vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Business Intelligence Enterprise Edition executes to compromise Oracle Business Intelligence Enterprise Edition. Succe...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83368	7.0	HIGH		0.002		Vulnerability in the Oracle GraalVM for JDK, Oracle GraalVM Enterprise Edition, Oracle GraalVM product of Oracle Java SE (component: Compiler). The supported version that is affected is Oracle GraalVM for JDK 17: 23.0.13.1; Oracle GraalVM for JDK 21: 23.1.12.1; Oracle GraalVM Enterprise Edition: 21.3.19.1; Oracle GraalVM: 25.0.4.1. Difficult to exploit vulnerability allows unauthenticated attacker with network a...
CVE-2026-85594	7.0	HIGH		0.002	traefik:traefik	Traefik versions from v3.7.1 fail to enforce crossProviderNamespaces restrictions on the traefik.ingress.kubernetes.io/service.middlewares Service annotation in the Kubernetes Ingress provider. A namespace-limited tenant excluded from the allowlist can attach an operator-owned middleware to its Service, and if that middleware injects backend credentials, recover them at a controlled backend.
CVE-2026-87240	7.0	HIGH		0.001		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Difficult to exploit vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can r...
CVE-2026-53941	6.9	MEDI		0.004		Inspektor Gadget is a set of tools and framework for data collection and system inspection on Kubernetes clusters and Linux hosts using eBPF. From 0.27.0 until 0.53.1, the uprobe library resolver can allow an unprivileged container to consume excessive CPU and block other containers from starting by supplying a crafted /etc/ld.so.cache file while an uprobe-based gadget is active. The parser in pkg/uprobetracer/ldc...
CVE-2026-90439	6.9	MEDI		0.003		NGINX Plus and NGINX Open Source have a vulnerability in the ngx_http_v3_module module. When using HTTP/3 with OpenSSL versions <= OpenSSL 3.5.0 under certain configurations, a limited heap buffer overflow could happen while processing a TLS handshake. This can happen in a non-deterministic manner that is beyond the attacker's control. This may cause a heap buffer overflow in the NGINX worker process leading to a ...
CVE-2026-92215	6.9	MEDI		0.004		A vulnerability has been found in a2ui-project a2ui up to 0.10.7. Affected by this vulnerability is the function httpx.get of the file agent_sdks/python/a2ui_agent/src/a2ui/extensions/file_resolve/file_resolver.py of the component FileResolver. The manipulation leads to server-side request forgery. It is possible to initiate the attack remotely. The identifier of the patch is 2bb8423060308bbdea8ba468dabed4fc256d18...
CVE-2026-13265	6.8	MEDI		0.002		IBM MQ 9.1.0.0 through 9.1.0.37 LTS, 9.2.0.0 through 9.2.0.43 LTS, 9.3.0.0 through 9.3.0.41 LTS, 9.3.0.0 through 9.3.5.1 CD, 9.4.0.0 through 9.4.0.25 LTS, 9.4.0.0 through 9.4.5.1 CD, and 10.0.0.0 could allow an authenticated attacker with MFT publish authority to obtain sensitive information or cause a denial of service due to XML external entity injection in the mqweb MFT REST API.
CVE-2026-20248	6.8	MEDI				A vulnerability in the DNS over TCP implementation of Cisco Secure Firewall Adaptive Security Appliance (ASA) Software and Cisco Secure Firewall Threat Defense (FTD) Software could allow an unauthenticated, remote attacker to cause the TCP DNS response handler to unexpectedly restart, causing the device to reload. This vulnerability is due to a logic error when parsing a DNS query and tracking the size of ...
CVE-2026-53196	6.8	MEDI		0.003	linux:linux_kernel	In the Linux kernel, the following vulnerability has been resolved: USB: serial: io_ti: fix heap overflow in get_manuf_info() get_manuf_info() reads le16_to_cpu(rom_desc->Size) bytes from the device I2C EEPROM into a buffer allocated with kmalloc_obj(), which is sizeof(struct edge_ti_manuf_descriptor) = 10 bytes. The Size field comes from the device and is only validated (in check_i2c_image()) to make sure the ...
CVE-2026-55770	6.8	MEDI		0.004		OpenBao is an open source identity-based secrets management system. Prior to 2.5.5, OpenBao used EscapeLDAPValue, an RFC 4514 distinguished-name escaping function, where RFC 4515 LDAP search-filter escaping was required in sdk/helper/ldaputil/client.go GetUserDN. With the LDAP authentication backend configured for an Active Directory UPNDomain path or UserDN and UserAttr binding, an attacker-controlled username co...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-69490	6.8	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Mass Storage Class Driver allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-73965	6.8	MEDI		0.003		Vulnerability in the Siebel CRM Deployment product of Oracle Siebel CRM (component: Cloud Gateway). Supported versions that are affected are 17.0-26.7. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Deployment. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critical data or ...
CVE-2026-77401	6.8	MEDI				Zope AccessControl provides a general security framework for use in Zope. Prior to 7.4, applications that allow untrusted users to create and execute AccessControl-controlled Python code do not safely guard str.format and str.format_map when those methods are reached through a str subclass. In both ImplPython.py and cAccessControl.c, Python formatting can recursively access attributes and subscriptions using unres...
CVE-2026-77892	6.8	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	No cwe for this issue in Windows Boot Manager allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-81326	6.8	MEDI		0.001		QND uses a hard-coded cryptographic key, which may allow a local attacker who is logged in to a Windows PC where the affected product's client is installed to obtain administrator credentials, including an ID and password.
CVE-2026-83076	6.8	MEDI		0.003		Vulnerability in the Oracle HR Intelligence product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle HR Intelligence. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access t...
CVE-2026-83278	6.8	MEDI		0.002		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: helidon-integrations-neo4j). Supported versions that are affected are 3.0.0-3.2.20 and 4.0.0-4.5.4. Difficult to exploit vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Helidon executes to compromise Helidon. Successful attacks of this vulnerability can r...
CVE-2026-83441	6.8	MEDI		0.003		Vulnerability in the Oracle Product Hub product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Hub. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to critic...
CVE-2026-83491	6.8	MEDI		0.002		Vulnerability in the Oracle iRecruitment product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Difficult to exploit vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle iRecruitment executes to compromise Oracle iRecruitment. Successful attacks of this vulne...
CVE-2026-87252	6.8	MEDI		0.002		Vulnerability in the Oracle Agile PLM product of Oracle Supply Chain (component: Application Server). The supported version that is affected is 9.3.6. Difficult to exploit vulnerability allows unauthenticated attacker with access to the physical communication segment attached to the hardware where the Oracle Agile PLM executes to compromise Oracle Agile PLM. Successful attacks of this vulnerability can result i...
CVE-2026-92140	6.8	MEDI				Jenkins Gitee Plugin 1301.v8957053c7902 and earlier does not escape the sender name from Gitee push webhook payloads in build causes, resulting in a stored cross-site scripting (XSS) vulnerability exploitable by attackers able to trigger builds via the Jenkins Gitee Plugin webhook endpoint.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-69820	6.7	MEDI		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Heap-based buffer overflow in Windows Hello allows an authorized attacker to elevate privileges locally.
CVE-2026-87248	6.7	MEDI		0.002		Vulnerability in the Oracle Hyperion Financial Management product of Oracle Hyperion (component: Security). The supported version that is affected is 11.2.26.0.000. Easily exploitable vulnerability allows high privileged attacker with logon to the infrastructure where Oracle Hyperion Financial Management executes to compromise Oracle Hyperion Financial Management. Successful attacks of this vulnerability can re...
CVE-2026-69469	6.6	MEDI		0.004	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Integer overflow or wraparound in Windows USB Audio Class driver (usbaudio.sys) allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-11864	6.5	MEDI		0.004		IBM Cloud Pak for Business Automation 26.0.0 through 26.0.0 Interim Fix 001, 25.0.0 through 25.0.0 Interim Fix 005, 24.0.1 through 24.0.1 Interim Fix 008, and 24.0.0 through 24.0.0 Interim Fix 009 is vulnerable to an XPath injection vulnerability, which could allow an authenticated attacker to exfiltrate sensitive application data and/or determine the structure of the XML document.
CVE-2026-12759	6.5	MEDI		0.004		IBM Cloud Pak for Business Automation could allow an authenticated user to cause a denial of service due to uncontrolled resource consumption.
CVE-2026-12765	6.5	MEDI		0.002		IBM Langflow OSS 1.0.0 through 1.10.2 is vulnerable to server-side request forgery (SSRF). This may allow an unauthenticated attacker to send unauthorized requests from the system, potentially leading to network enumeration or facilitating other attacks.
CVE-2026-12767	6.5	MEDI		0.002		IBM Langflow OSS 1.0.0 through 1.11.5 is vulnerable to server-side request forgery (SSRF). This may allow an unauthenticated attacker to send unauthorized requests from the system, potentially leading to network enumeration or facilitating other attacks.
CVE-2026-15396	6.5	MEDI		0.003		IBM WebSphere Application Server 9.0, and 8.5 and IBM WebSphere Application Server - Liberty are vulnerable to HTTP request smuggling, caused by improper parsing of the HTTP transfer-encoding request header. By sending a specially crafted HTTP transfer-encoding request header, an attacker could exploit this vulnerability to poison the web cache, bypass web application firewall protection, and conduct XSS attacks.
CVE-2026-15412	6.5	MEDI		0.002		IBM WebSphere Application Server 9.0, and 8.5 and IBM WebSphere Application Server - Liberty could allow a remote attacker to conduct phishing attacks, using an open redirect attack. By persuading a victim to visit a specially crafted Web site, a remote attacker could exploit this vulnerability to spoof the URL displayed to redirect a user to a malicious Web site that would appear to be trusted. This could allow t...
CVE-2026-15634	6.5	MEDI		0.003		IBM WebSphere Application Server 9.0, and 8.5 and IBM WebSphere Application Server - Liberty are vulnerable to HTTP request smuggling, caused by improper parsing of the HTTP transfer-encoding request header. By sending a specially crafted HTTP transfer-encoding request header, an attacker could exploit this vulnerability to poison the web cache, bypass web application firewall protection, and conduct XSS attacks.
CVE-2026-16104	6.5	MEDI		0.002	redhat:build_of_keycloak	A flaw was found in the authentication configuration endpoint of the keycloak-services component, which is the core engine for Red Hat Build of Keycloak identity and access management. The issue occurs because the system fails to mask sensitive configuration values, such as reCAPTCHA secret keys, when they are requested by administrators with view-only permissions. This can lead to the exposure of third-party serv...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-16187	6.5	MEDI		0.003		IBM WebSphere Application Server 9.0, and 8.5 could allow a remote attacker to bypass authentication and obtain sensitive information by sending a crafted unauthenticated request.
CVE-2026-16702	6.5	MEDI		0.003		IBM Db2 11.5.0 through 11.5.9, and 12.1.0 through 12.1.5 for Linux, UNIX and Windows (includes DB2 Connect Server) could allow a remote authenticated attacker to cause a denial of service due to a null pointer dereference.
CVE-2026-17463	6.5	MEDI		0.005		IBM Db2 11.5.0 through 11.5.9, and 12.1.0 through 12.1.5 for Linux, UNIX and Windows (includes DB2 Connect Server) could allow a remote authenticated attacker to cause a denial of service due to uncontrolled resource consumption.
CVE-2026-20283	6.5	MEDI				A vulnerability in the IPsec Open API endpoint of Cisco ISE could allow an authenticated, remote attacker to inject arbitrary commands on the underlying operating system. This vulnerability is due to insufficient validation of user-supplied input in IPsec Open API calls. An attacker could exploit this vulnerability by sending crafted input to the IPsec Open API endpoint on an affected device. A successful...
CVE-2026-20287	6.5	MEDI				As part of Cisco's ongoing commitment to proactive security and product quality, the Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) engineering teams have conducted a comprehensive internal security review. This review resulted in a software hardening release that addresses multiple internally discovered vulnerabilities. The vulnerabilities tracked by CVE-2026-20287 are ...
CVE-2026-20288	6.5	MEDI		0.004	cisco:unified_computing_system, cisco:unified_computing_system_e-series_software	A vulnerability in the web-based management interface of Cisco IMC could allow an authenticated, remote attacker with Admin privileges to execute arbitrary commands on the underlying operating system of an affected system and elevate privileges to root. This vulnerability is due to improper validation of user-supplied input. An attacker could exploit this vulnerability by entering crafted inputs to t...
CVE-2026-48828	6.5	MEDI		0.007	apache:airflow	The Bulk Variables API in Apache Airflow called the redactor without passing the variable's key, so the key-based `should_hide_value_for_key` check (which triggers on secret-suffixed key names like `*_password` / `*_token` / `*_secret`) could not fire for JSON-decodable variable values. An authenticated UI/API user with bulk Variable read permission could retrieve plaintext values from JSON variables whose key wou...
CVE-2026-48892	6.5	MEDI		0.007	apache:airflow	The Config API in Apache Airflow surfaced per-key secrets-backend overrides (environment variables like `AIRFLOW__SECRETS__BACKEND_KWARG__SECRET_ID` and `AIRFLOW__WORKERS__SECRETS__BACKEND_KWARG__SECRET_ID`) as synthetic config options whose option names were not in `sensitive_config_values`, so the masker did not redact them. An authenticated UI/API user with Config read permission could retrieve plaintext secrets...
CVE-2026-48987	6.5	MEDI		0.003		pyLoad is a free and open-source download manager written in Python. Prior to 0.5.0b3.dev101, EventManager in src/pyload/core/managers/event_manager.py appends a Client object to the clients list for each unique uuid submitted to the authenticated getEvents API endpoint, but get_events does not invoke the available clean method to remove inactive clients. An authenticated user can repeatedly submit unique UUID val...
CVE-2026-49296	6.5	MEDI		0.004	apache:airflow	Before apache-airflow 3.3.0, a user authorized to read one Dag could disclose the source of other Dags co-located in the same source file. `GET /api/v2/dagSources/{dag_id}` — and the equivalent Dag-source view in the UI — returned the entire source file without redacting Dags the caller was not authorized to read, bypassing per-DAG read authorization. Deployments that co-locate multiple Dags in a single file and r...
CVE-2026-49487	6.5	MEDI		0.007	apache:airflow	In Apache Airflow before 3.3.0, the REST API task-instance detail and list endpoints returned a deferred task's trigger kwargs without masking. When a deferred operator passed a secret (for example a provider API key) into its trigger, any authenticated user with DAG-scoped task-instance read access for that DAG could read that secret in clear text while the task was deferred. Users should upgrade to apache-airflo...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-53716	6.5	MEDI		0.007		Envoy Gateway is an open source project for managing Envoy Proxy as a standalone or Kubernetes-based application gateway. Prior to 1.7.4 and 1.8.1, getFileFromGZ in internal/wasm/httpfetcher.go calls io.ReadAll on a gzip.Reader without limiting decompressed output when a tenant-controlled EnvoyExtensionPolicy.spec.wasm[].code.http.url points to a reachable compressed Wasm payload. The 256 MiB compressed-input cap ...
CVE-2026-53719	6.5	MEDI		0.007		Envoy Gateway is an open source project for managing Envoy Proxy as a standalone or Kubernetes-based application gateway. Prior to 1.7.4 and 1.8.1, translateSecurityPolicyForRoute in internal/gatewayapi/securitypolicy.go dereferences a nil authorization value when a namespace-scoped tenant creates a SecurityPolicy targeting a TCPRoute and omits spec.authorization. The persistent object triggers the panic on every ...
CVE-2026-57822	6.5	MEDI		0.005	apache:artemis	When the broker is processing message-based management requests, sent by an authenticated messaging client that is authorized with MANAGE permission to perform management-via-messaging, the parameter processing can trigger Java deserialization of certain method parameters that the broker will not utilise. The permitted types allow to craft a payload causing excessive computation and pinning the processing thread, ...
CVE-2026-59244	6.5	MEDI		0.002	apache:airflow	Apache Airflow's secrets masker did not mask `var.json` Variable values whose value is a dict in the Rendered Templates UI — the dict value failed an `isinstance(str)` guard — so a secret stored as a JSON Variable and referenced in a template via `var.json` was displayed in cleartext to any user with access to that task's Rendered Templates view. Users are advised to upgrade to apache-airflow 3.3.1 or later, which...
CVE-2026-62597	6.5	MEDI		0.002		Vulnerability in the Oracle Enterprise Manager Base Platform product of Oracle Enterprise Manager (component: Event Management). Supported versions that are affected are 13.5 and 24.1. Easily exploitable vulnerability allows low privileged attacker with network access via SOAP to compromise Oracle Enterprise Manager Base Platform. Successful attacks of this vulnerability can result in unauthorized creation, de...
CVE-2026-62801	6.5	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper limitation of a pathname to a restricted directory ('path traversal') in Windows PowerShell allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-62949	6.5	MEDI				AsyncSSH is a Python package which provides an asynchronous client and server implementation of the SSHv2 protocol on top of the Python asyncio framework. Prior to 2.24.0, _process_channel_open and _process_channel_open_confirmation in asyncssh/connection.py accept a peer-supplied send_pktsize value of zero. When channel data reaches SSHChannel._flush_send_buf in asyncssh/channel.py, the zero value causes each loo...
CVE-2026-65017	6.5	MEDI		0.004	apache:airflow	Apache Airflow's Config API did not mask team-scoped sensitive configuration values in multi-team deployments. When an administrator has enabled multi-team mode and exposed the Config API, an authenticated Viewer holding only configuration-read access — with no prior access to the secret — could read a team-scoped Celery broker URL, including its embedded credentials, in cleartext, while the equivalent global opti...
CVE-2026-66303	6.5	MEDI		0.008	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Null pointer dereference in Skype for Business allows an authorized attacker to deny service over a network.
CVE-2026-66306	6.5	MEDI		0.005	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Generation of error message containing sensitive information in Skype for Business allows an unauthorized attacker to disclose information over a network.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-66308	6.5	MEDI		0.006	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Out-of-bounds read in Skype for Business allows an authorized attacker to deny service over a network.
CVE-2026-66816	6.5	MEDI		0.007	microsoft:sql_server_2022, microsoft:sql_server_2025	Insufficient logging in SQL Server allows an authorized attacker to bypass a security feature over a network.
CVE-2026-67369	6.5	MEDI		0.007	microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67383	6.5	MEDI		0.01	microsoft:sql_server_2025	Generation of error message containing sensitive information in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67386	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use of uninitialized resource in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67633	6.5	MEDI		0.008	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to deny service over a network.
CVE-2026-68868	6.5	MEDI		0.005	apache:apache-airflow-providers-google	The Google Cloud Secret Manager secrets backend in Apache Airflow's Google provider never applied the team scope when resolving Connections and Variables: the caller's `team_name` was accepted by the backend but dropped at the internal call boundary, so every lookup resolved against the team-agnostic secret name. In a deployment running multi-team mode with this backend, a task or Dag belonging to one team resolve...
CVE-2026-68871	6.5	MEDI		0.003	apache:apache-airflow-providers-apache-yandex	The Yandex Lockbox secrets backend in Apache Airflow's Yandex provider resolved a team-scoped Connection or Variable id through the team-agnostic lookup when the team-scoped lookup missed. In a deployment running multi-team mode with this backend, a caller in one team could resolve a secret belonging to another team by supplying an id that spells out that team's namespace, obtaining its credentials in full. No unu...
CVE-2026-68872	6.5	MEDI		0.003	apache:apache-airflow-providers-amazon	The AWS Systems Manager Parameter Store and Secrets Manager backends in Apache Airflow's Amazon provider resolved a team-scoped Connection or Variable id through the team-agnostic lookup when the team-scoped lookup missed. In a deployment running multi-team mode with either backend, a caller in one team could resolve a secret belonging to another team by supplying an id that spells out that team's namespace, obtai...
CVE-2026-68969	6.5	MEDI		0.004	apache:airflow	Apache Airflow wrote Variable values and Connection `extra` contents to the audit log in cleartext when they were submitted through the bulk endpoints (`PATCH /api/v2/variables` and `PATCH /api/v2/connections`). The audit-log masking recognised only top-level request fields, and a bulk request nests its entities two levels below, so no masking was applied to them. Any authenticated user with audit-log read access ...
CVE-2026-68970	6.5	MEDI		0.002	apache:airflow	Apache Airflow's Task SDK did not mask the contents of a Variable whose JSON value is a list, so secrets stored in that shape appeared in cleartext in task logs and in the Rendered Templates UI. Masking was applied only when the deserialized value was a string or a dict; a list at the top level matched neither and was returned unmasked. Any authenticated user able to read the logs or rendered templates of a task t...
CVE-2026-68971	6.5	MEDI		0.003	apache:airflow	Apache Airflow's asset materialization endpoint (`POST /api/v2/assets/{asset_id}/materialize`) and the XCom result check on `wait_dag_run_until_finished` authorized the target Dag without its team, unlike every other authorization site. A team-aware auth manager distinguishes a team-scoped Dag from a global one by that field -- the Keycloak auth manager, for example, checks the `DAG` resource instead of `DAG:<team...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-69839	6.5	MEDI		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Uncaught exception in Windows iSCSI Target Service allows an authorized attacker to deny service over a network.
CVE-2026-70019	6.5	MEDI		0.011	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Windows hard link in Windows Compressed Folder allows an unauthorized attacker to disclose information over a network.
CVE-2026-70755	6.5	MEDI		0.003		Vulnerability in the Oracle Web Applications Desktop Integrator product of Oracle E-Business Suite (component: File download). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Web Applications Desktop Integrator. Successful attacks of this vulnerability can result in unauthorized access to c...
CVE-2026-75880	6.5	MEDI		0.004	apache:artemis	An authenticated client could attach a consumer with a selector containing crafted wildcard usage that results in excessive evaluation during message delivery attempts, occupying a shared broker thread and leading to denial of service. This issue affects Apache Artemis: from 2.50.0 through 2.56.0; Apache ActiveMQ Artemis: from 1.0.0 through 2.44.0. Users are recommended to upgrade to version 2.57.0, which fixes...
CVE-2026-76438	6.5	MEDI				A vulnerability in the web-based management interface of Cisco BroadWorks CommPilot Application Software could allow an authenticated, remote attacker with low privileges to alter configurations on an affected device. This vulnerability is due to missing authorization checks. An attacker could exploit this vulnerability by sending a crafted HTTP request. A successful exploit could allow the attacker to alt...
CVE-2026-79725	6.5	MEDI		0.003	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow a remote authenticated attacker to read arbitrary files due to improper access control.
CVE-2026-80378	6.5	MEDI		0.003	ibm:datastage_on_cloud_pak_for_d ata	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to cause a denial of service due to improper authorization.
CVE-2026-81554	6.5	MEDI		0.005	ibm:datastage_on_cloud_pak_for_d ata	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to obtain sensitive information due to an absolute-path traversal vulnerability.
CVE-2026-82092	6.5	MEDI		0.005	ibm:datastage_on_cloud_pak_for_d ata	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to obtain sensitive information due to an absolute-path traversal vulnerability.
CVE-2026-82100	6.5	MEDI		0.004	ibm:datastage_on_cloud_pak_for_d ata	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to cause a denial of service due to a path traversal vulnerability.
CVE-2026-83097	6.5	MEDI		0.005		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Forms. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification acces...
CVE-2026-83140	6.5	MEDI		0.004		Vulnerability in the Oracle Field Service product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Field Service. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83175	6.5	MEDI		0.004		Vulnerability in the Oracle Application Object Library product of Oracle E-Business Suite (component: Core). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Application Object Library. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete ac...
CVE-2026-83200	6.5	MEDI		0.004		Vulnerability in the Oracle Process Manufacturing Intelligence product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via Oracle Net to compromise Oracle Process Manufacturing Intelligence. Successful attacks of this vulnerability can result in unauthorized a...
CVE-2026-83250	6.5	MEDI		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result...
CVE-2026-83251	6.5	MEDI		0.003		Vulnerability in the Oracle Commerce Guided Search / Oracle Commerce Experience Manager product of Oracle Commerce (component: Forge). The supported version that is affected is 11.4.0. Difficult to exploit vulnerability allows unauthenticated attacker with network access via TLS to compromise Oracle Commerce Guided Search / Oracle Commerce Experience Manager. Successful attacks of this vulnerability can result ...
CVE-2026-83347	6.5	MEDI		0.004		Vulnerability in the Oracle Net Services component of Oracle Database Server. Supported versions that are affected are 23.4.0-23.26.3. Easily exploitable vulnerability allows unauthenticated attacker with network access via TCPS to compromise Oracle Net Services. Successful attacks require human interaction from a person other than the attacker. Successful attacks of this vulnerability can result in unauthorized...
CVE-2026-83433	6.5	MEDI		0.003		Vulnerability in the Oracle Depot Repair product of Oracle E-Business Suite (component: Depot Repair Diagnostics). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows high privileged attacker with network access via HTTP to compromise Oracle Depot Repair. Successful attacks of this vulnerability can result in unauthorized creation, deletion or modification access to ...
CVE-2026-83443	6.5	MEDI		0.004		Vulnerability in the Oracle Assets product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Assets. Successful attacks of this vulnerability can result in unauthorized access to critical data or complete access to all Oracle Assets...
CVE-2026-83460	6.5	MEDI		0.003		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: LRA). Supported versions that are affected are 4.0.0-4.5.4. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized update, insert or delete access to some of Helidon accessible data as well as unauthorized ...
CVE-2026-84859	6.5	MEDI				ScadaLTS 2.8.1-release-candidate build 0 is affected by an Authenticated Blind SQL Injection The /api/events/search endpoint accepts a JSON body containing a sortBy array. The values in this array are concatenated directly into the SQL ORDER BY clause without any sanitization or parameterization. This allows authenticated users with the ROLE_USER role to perform time-based and boolean-based blind SQL injection ...
CVE-2026-84993	6.5	MEDI				MikroORM is a TypeScript ORM for Node.js based on Data Mapper, Unit of Work and Identity Map patterns. Prior to 6.6.16 and 7.1.7, the shared SQL layer validates the field key of an orderBy clause but does not validate its direction value before AbstractSqlPlatform.getOrderByExpression concatenates it into an ORDER BY clause. Applications that bind attacker-controlled request data to the direction in em.find(), em....
CVE-2026-92139	6.5	MEDI				Jenkins Bitbucket Push and Pull Request Plugin 4.0.1 and earlier trusts values provided in the webhook payload, including certain URLs, and uses configured Bitbucket credentials to connect to those URLs, allowing attackers to capture Bitbucket credentials stored in Jenkins by sending a crafted webhook payload.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-92237	6.5	MEDI		0.001		Insertion of sensitive information into log file in the slow query logging feature in Devolutions PowerShell Universal 2026.2.5 and earlier allows an authenticated user with log read permission to obtain application tokens, data protection key material and other stored credentials via SQL parameter values written to the system log on instances backed by Microsoft SQL Server.
CVE-2024-11222	6.4	MEDI		0.003		GitLab has remediated an issue in GitLab CE/EE affecting all versions from 13.0 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that under certain conditions could have allowed a developer user to perform actions in the context of another user's merge request commit due to a race condition issue in pipeline creation.
CVE-2026-12749	6.4	MEDI		0.003		IBM Cloud Pak for Business Automation is vulnerable to stored cross-site scripting. This vulnerability allows an authenticated user to embed arbitrary JavaScript code in the Web UI thus altering the intended functionality potentially leading to credentials disclosure within a trusted session.
CVE-2026-12750	6.4	MEDI		0.003		IBM Cloud Pak for Business Automation is vulnerable to stored cross-site scripting. This vulnerability allows an authenticated user to embed arbitrary JavaScript code in the Web UI thus altering the intended functionality potentially leading to credentials disclosure within a trusted session.
CVE-2026-16185	6.4	MEDI		0.002		IBM WebSphere Application Server 9.0, and 8.5 could allow a remote attacker to bypass authentication on an admin console servlet.
CVE-2026-69874	6.4	MEDI		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Untrusted pointer dereference in Windows ALPC allows an authorized attacker to elevate privileges locally.
CVE-2026-77887	6.4	MEDI		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an authorized attacker to execute code locally.
CVE-2026-77891	6.4	MEDI		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an authorized attacker to execute code locally.
CVE-2026-83077	6.4	MEDI		0.003		Vulnerability in the Siebel CRM Cloud Applications product of Oracle Siebel CRM (component: Siebel Cloud Manager). Supported versions that are affected are 22.3-26.7. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Siebel CRM Cloud Applications. While the vulnerability is in Siebel CRM Cloud Applications, attacks may significantly impact additional produ...
CVE-2026-14275	6.3	MEDI		0.003		IBM i Access Family 1.1.2.0 through 1.1.9.15 IBM i Access Client Solutions could allow an authenticated user to execute arbitrary commands with normal user privileges on the system due to improper validation of user supplied input in a STRPCCMD CL command.
CVE-2026-14276	6.3	MEDI		0.003		IBM i Access Family 1.1.2.0 through 1.1.9.15 IBM i Access Client Solutions could allow an authenticated user to execute arbitrary commands with normal user privileges on the system due to improper validation of user supplied input in a malicious emulator macro RunProgram action.
CVE-2026-14277	6.3	MEDI		0.005		IBM i Access Family 1.1.2.0 through 1.1.9.15 could allow an authenticated user to execute arbitrary commands with normal user privileges on the system due to improper validation of user supplied input in a session file.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83354	6.3	MEDI		0.002		Vulnerability in the Oracle Coherence product of Oracle Fusion Middleware (component: Core). The supported version that is affected is 15.1.1.0.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Coherence. While the vulnerability is in Oracle Coherence, attacks may significantly impact additional products (scope change). Successful attacks of ...
CVE-2026-84048	6.3	MEDI		0.003		Joomla Extension - joomgalleryfriends.net - Unauthenticated arbitrary file upload via the TUS endpoint in JoomGallery < 4.4.1 - The TUS endpoint allows arbitrary file uploads, however neither file name nor file extension are under attacker control. Code execution requires non-standard server configuration.
CVE-2026-19543	6.2	MEDI		0.002		IBM Common Licensing Agent 9.0, Agent 9.0.0.1, Agent 9.0.0.2, ART 9.0, ART 9.0.0.1, and ART 9.0.0.2 performs input validation exclusively on the client side and fails to enforce the same restrictions on the server side. An attacker can modify requests to bypass validation controls and submit unauthorized values, potentially resulting in unintended application behavior.
CVE-2026-55846	6.2	MEDI		0.001		Allure 2 is the version 2.x branch of Allure Report, a multi-language test reporting tool. Prior to 2.39.0, the HTTP server started by allure serve and allure open uses URI.getPath() in Commands.setUpServer() in allure-commandline/src/main/java/io/qameta/allure/Commands.java and passes the percent-decoded request path to reportDirectory.resolve() without normalizing the result or confirming that it remains inside ...
CVE-2026-13276	6.1	MEDI		0.002		IBM Verify Identity Access 11.0.0 through 11.0.3 Interim Fix 001 and IBM Security Verify Access 10.0.0 through 10.0.9.2 Interim Fix 001 and IBM Verify Identity Access Container 11.0.0 through 11.0.3 Interim Fix 001 and IBM Security Verify Access Container 10.0.0 through 10.0.9.2 Interim Fix 001.
CVE-2026-20309	6.1	MEDI				A vulnerability in the web-based management interface of Cisco Identity Services Engine (ISE) could allow an unauthenticated, remote attacker to conduct a reflected cross-site scripting (XSS) attack against a user of the interface. This vulnerability exists because the web-based management interface does not properly validate user-supplied input. An attacker could exploit this vulnerability by persuading a user...
CVE-2026-62280	6.1	MEDI		0.002		Open Access Management (OpenAM) is an access management solution. From 13.0.0 until 16.1.2, the OAuth2 authorize endpoint's display=wap consent page reflects request-derived values through ConsentRequiredResource and wap/authorize.ftl without HTML escaping. An attacker can induce a user with an active OpenAM session to follow a crafted authorization link and execute JavaScript in the OpenAM origin, enabling sessio...
CVE-2026-63523	6.1	MEDI		0.007	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Improper neutralization of input during web page generation ('cross-site scripting') in Skype for Business allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-69642	6.1	MEDI		0.003	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Improper neutralization of input during web page generation ('cross-site scripting') in Skype for Business allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-77490	6.1	MEDI		0.003		Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Edge (Chromium-based) allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-87169	6.1	MEDI		0.003		Vulnerability in the Oracle Contract Lifecycle Management for Public Sector product of Oracle E-Business Suite (component: Wage Determination Online). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Contract Lifecycle Management for Public Sector. Successful attacks require human interactio...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87253	6.1	MEDI		0.002		Vulnerability in the Oracle Agile PLM product of Oracle Supply Chain (component: Web Client). The supported version that is affected is 9.3.6. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Agile PLM. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Oracle Agile PLM, attacks ma...
CVE-2026-87278	6.1	MEDI		0.001		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows unauthenticated attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. Successful attacks require human interaction from a person other than the attacker. Successful attac...
CVE-2026-87279	6.1	MEDI		0.001		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or freque...
CVE-2026-88033	6.1	MEDI		0.003	mongodb:java_driver	Improper neutralization of special elements in data query logic in the GridFS component of the MongoDB Java Driver can cause a caller-supplied structured file identifier to be interpreted as a query condition rather than as a literal identifier. An authenticated user who can influence the identifier passed by an affected application may obtain stored file content beyond the intended target or cause all GridFS file...
CVE-2026-88034	6.1	MEDI		0.003	mongodb:c\+\+_driver	Improper neutralization of special elements in data query logic in the GridFS component of the MongoDB C++ Driver can cause a caller-supplied structured file identifier to be interpreted as a query condition rather than as a literal identifier. An authenticated user who can influence the identifier passed by an affected application may obtain stored file content beyond the intended target or cause all GridFS file ...
CVE-2026-88036	6.1	MEDI		0.003	mongodb:c_driver	Improper neutralization of special elements in data query logic in the GridFS component of the MongoDB C Driver can cause a caller-supplied structured file identifier to be interpreted as a query condition rather than as a literal identifier. An authenticated user who can influence the identifier passed by an affected application may obtain stored file content beyond the intended target or cause all GridFS file ch...
CVE-2026-18061	6.0	MEDI		0.003	amazon:advanced_jdbc_wrapper	Improper restriction of XML external entity references in the RemoteQueryCachePlugin in AWS Advanced JDBC Wrapper 3.3.0 through 4.2.0 might allow an actor with write access to the shared cache infrastructure to disclose sensitive files from application hosts that read cached query results, including stored database and IAM role credentials, via crafted XML data in a cached column value. To remediate this issue,...
CVE-2026-18069	6.0	MEDI		0.001		IBM i 7.6, 7.5, 7.4, and 7.3 could allow a local attacker to obtain ownership of arbitrary file system objects due to a time-of-check to time-of-use (TOCTOU) race condition.
CVE-2026-18699	6.0	MEDI		0.003	mongodb:mongodb	An issue in MongoDB Server's query planner could allow an authenticated user with read-level privileges to cause the server process to terminate unexpectedly by submitting a specially formed query against a collection with a text index. This could result in a denial of service, affecting connected clients and in-flight operations.
CVE-2026-18700	6.0	MEDI		0.003	mongodb:mongodb	An issue in MongoDB Server's geospatial validation could allow an authenticated user with write privileges to cause an internal reference to be used after the underlying memory has been freed, through concurrent operations against a collection using a certain type of validator. This could result in a server crash, leading to a denial of service.
CVE-2026-82056	6.0	MEDI		0.002	mongodb:mongodb	A race condition in MongoDB server's text index query parsing can cause a heap use-after-free read when handling upsert retry paths. Under certain concurrent index lifecycle operations, a raw pointer to internal text index metadata may be dereferenced after the underlying structures have been freed, leading to a server crash. An authenticated user with readWrite privileges can trigger this condition through specif...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-82059	6.0	MEDI		0.003	mongodb:mongodb	An internal aggregation expression in MongoDB Server was incorrectly registered as accessible to any authenticated user rather than being restricted to internal cluster operations. By crafting a malformed index specification within this expression, an authenticated user with read-only privileges could trigger an assertion failure in the index key generation code path. In certain build configurations, this assertio...
CVE-2026-82063	6.0	MEDI		0.003	mongodb:mongodb	A use-after-free security issue in the cursor management component of MongoDB Server allows an authenticated user to cause a denial of service. Under specific timing conditions during cursor operations, a stale pointer to a freed resource may be retained and subsequently dereferenced during cursor cleanup, leading to a server process crash.
CVE-2026-86338	6.0	MEDI		0.003		Ash field_policies are documented to protect against filter-based information disclosure: when a field the actor may not see is referenced in a filter, it is replaced with an expression that evaluates to nil, so a filter cannot be used as a yes/no oracle to read a value the actor cannot see. This nilling was applied to attributes but not to calculations or aggregates. A user-supplied filter reference to a calcula...
CVE-2026-87282	6.0	MEDI		0.002		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows high privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. While the vulnerability is in Oracle VM VirtualBox, attacks may significantly impact additional prod...
CVE-2026-87283	6.0	MEDI		0.001		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows high privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. While the vulnerability is in Oracle VM VirtualBox, attacks may significantly impact additional prod...
CVE-2026-87285	6.0	MEDI		0.002		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows high privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. While the vulnerability is in Oracle VM VirtualBox, attacks may significantly impact additional prod...
CVE-2026-16089	5.9	MEDI		0.001	redhat:build_of_keycloak	A flaw was found in the keycloak-services component of Red Hat Build of Keycloak. The issue occurs because OAuth 2.0 authorization codes are not properly bound to the client that originally requested them. An attacker who can intercept an authorization code can modify it to be redeemed by their own client, potentially allowing them to obtain access tokens for a victim's identity.
CVE-2026-16435	5.9	MEDI		0.003		IBM WebSphere Application Server 9.0, and 8.5 is affected by an authentication bypass vulnerability when using XD or Intelligent-Management features.
CVE-2026-17495	5.9	MEDI		0.004		moment is a JavaScript date library for parsing, validating, manipulating, and formatting dates. In versions 2.29.2 through 2.30.1, a specially crafted non-string object passed to moment.locale() can bypass the locale-name path-traversal guard. The guard assumes the input is a string, so an object whose match() method satisfies the check while its toString() returns a traversal path reaches an internal require() c...
CVE-2026-18709	5.9	MEDI		0.001	mongodb:mongodb	An issue in MongoDB Server could allow an authenticated user with direct network access to a shard to improperly commit or abort an in-progress prepared transaction, bypassing the intended transaction coordination process. This could result in cross-shard data inconsistency, cluster clock corruption, and violation of transaction atomicity guarantees.
CVE-2026-70091	5.9	MEDI		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows DNS allows an unauthorized attacker to deny service over a network.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-79652	5.9	MEDI		0.002		A flaw was found in the JWT Bearer authorization grant implementation within the keycloak-services component of Red Hat Build of Keycloak. This component handles various OAuth2 and OpenID Connect grant types used for issuing access tokens. The issue occurs because the JWT Bearer grant fails to check if a client requires user consent before issuing a token. This allows an authenticated attacker with valid client cr...
CVE-2026-82561	5.9	MEDI				Apache NiFi 1.5.0 through 2.11.0 provide REST API methods that replace the entire contents of a Process Group using a client-supplied flow definition, covering Process Group flow replacement together with versioned flow update and rebase operations. Framework authorization for these methods was limited to read and write privileges on the Process Group itself, unlike the corresponding asynchronous update request me...
CVE-2026-85024	5.9	MEDI		0.003	nodejs:undici	undici bundles a WebSocket client whose permessage-deflate size-limit cleanup removes all listeners from the internal zlib inflate stream, including its error listener, while that stream can still emit. When a remote peer sends a compressed payload that crosses the built-in 128 MiB decompressed-payload limit and then contains a malformed DEFLATE byte, the inflate stream emits a data error with no listener attached...
CVE-2026-87123	5.9	MEDI		0.003		hbs is an Express view engine wrapper for Handlebars. Version 4.3.0 can crash the Node.js process during output escaping when an async helper, registered with registerAsyncHelper, resolves to an object whose toHTML property is truthy but not callable. Handlebars escapeExpression calls the toHTML method on any value that has a truthy toHTML, so such a value throws a TypeError, and because the async substitution run...
CVE-2026-92081	5.9	MEDI		0.004		fastify is a fast and low-overhead web framework for Node.js. In versions before 5.12.5, when a route registers a response trailer via reply.trailer() and is served over HTTP/2, fastify unconditionally sets the Transfer-Encoding: chunked header, which is forbidden on HTTP/2, so Node.js throws while serializing the response headers. The exception is not caught and becomes an uncaughtException, so a single unauthent...
CVE-2026-20120	5.8	MEDI				A vulnerability in the access control list (ACL) Object Group Search (OGS) implementation of Cisco Secure Firewall Adaptive Security Appliance (ASA) Software and Cisco Secure Firewall Threat Defense (FTD) Software could allow an unauthenticated, remote attacker to bypass configured access controls. This vulnerability is due to a logic error in populating group access control policies (ACPs) with OGS configured....
CVE-2026-20290	5.8	MEDI				A vulnerability in SSL/TLS certificate parsing in the Snort 2 Detection Engine of Cisco Secure Firewall Threat Defense (FTD) Software could allow an unauthenticated, remote attacker to cause the Snort 2 Detection Engine to restart. This vulnerability is due to incomplete validation of the SSL certificate. An attacker could exploit this vulnerability by sending a crafted SSL connection setup request to be parsed...
CVE-2026-54246	5.7	MEDI		0.003		Skipper is an HTTP router and reverse proxy for service composition. Prior to 0.27.13, the routesrv component serves cluster-wide control-plane data without application-layer authentication through /routes, /routes/{zone}, /swarm/redis/shards, and /swarm/valkey/shards. The handlers registered in routesrv/routesrv.go, eskipBytes.ServeHTTP in routesrv/eskipbytes.go, RedisHandler.ServeHTTP in routesrv/redishandler.go...
CVE-2026-88035	5.7	MEDI		0.001	mongodb:c_driver	A size check in the client-side authentication path of the MongoDB C Driver can wrap around, so an unusually large user-name value is accepted and copied past the end of a small buffer. A party able to set the driver's connection settings may cause the application that embeds the driver to terminate unexpectedly. Reaching this code requires a build in which the optional external SASL authentication backend is pres...
CVE-2026-50166	5.5	MEDI		0.002		Kuma is a modern Envoy-based service mesh that can run on every cloud across both Kubernetes and VMs. Prior to 2.7.26, 2.9.16, 2.11.14, 2.12.11, and 2.13.7, a kumactl profile manually configured for an HTTPS control plane without --ca-cert-file disables TLS peer verification and sends API tokens over the unverified connection. An attacker on the network path can intercept user or administrator API tokens and act a...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-68830	5.5	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper link resolution before file access ('link following') in Windows Universal Plug and Play (UPnP) Device Host allows an authorized attacker to disclose information locally.
CVE-2026-68831	5.5	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Files or directories accessible to external parties in Windows Defender Firewall Service allows an authorized attacker to disclose information locally.
CVE-2026-68842	5.5	MEDI		0.004	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1	Exposure of sensitive system information to an unauthorized control sphere in Windows MIDI Service Module allows an authorized attacker to disclose information locally.
CVE-2026-69286	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to disclose information locally.
CVE-2026-69343	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Overlay Filter allows an authorized attacker to disclose information locally.
CVE-2026-69457	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Driver allows an authorized attacker to disclose information locally.
CVE-2026-69527	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Mass Storage Class Driver allows an authorized attacker to disclose information locally.
CVE-2026-69808	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Win32K allows an authorized attacker to disclose information locally.
CVE-2026-69862	5.5	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Wireless Wide Area Network Service allows an authorized attacker to disclose information locally.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-70145	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Microsoft Windows Search Component allows an authorized attacker to disclose information locally.
CVE-2026-77491	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows GDI allows an unauthorized attacker to disclose information locally.
CVE-2026-83274	5.5	MEDI		0.001		Vulnerability in the Oracle Agile PLM MCAD Connector product of Oracle Supply Chain (component: CAX Client). The supported version that is affected is 3.6. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Agile PLM MCAD Connector executes to compromise Oracle Agile PLM MCAD Connector. Successful attacks of this vulnerability can result in unauthorize...
CVE-2026-83279	5.5	MEDI		0.002		Vulnerability in the Oracle Agile PLM MCAD Connector product of Oracle Supply Chain (component: CAX Client). The supported version that is affected is 3.6. Easily exploitable vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Agile PLM MCAD Connector executes to compromise Oracle Agile PLM MCAD Connector. Successful attacks of this vulnerability can result in unauthorize...
CVE-2026-90522	5.5	MEDI		0.005		A vulnerability was determined in jaychouchannel Tourism-Management-System up to d984d172dceca907f8b447efbdb06dc233f7938d. Impacted is the function resetPass of the file UsersController.java of the component Password Recovery. This manipulation causes weak password recovery. The attack can be initiated remotely. The exploit has been publicly disclosed and may be utilized. Continious delivery with rolling releases ...
CVE-2026-90619	5.5	MEDI		0.014		A vulnerability has been found in 0x4m4 HexStrike AI up to d689933ff579d839c676c82b231f8e98326c5f04. Impacted is an unknown function of the file hexstrike_server.py of the component Execute Endpoint. The manipulation of the argument code/script leads to os command injection. It is possible to initiate the attack remotely. The exploit has been disclosed to the public and may be used. This product is using a rolling...
CVE-2026-90690	5.5	MEDI		0.013		A weakness has been identified in 0x4m4 HexStrike AI up to d689933ff579d839c676c82b231f8e98326c5f04. The affected element is the function subprocess.Popen of the file hexstrike_server.py of the component API Tools Endpoint. Executing a manipulation of the argument additional_args/target/username/password/scan_type/payload can lead to os command injection. The attack can be launched remotely. The exploit has been m...
CVE-2026-90710	5.5	MEDI		0.005		A vulnerability was determined in taisan tarzan-cms 1.0.0. This issue affects the function openConnection of the file com/tarzan/cms/modules/admin/service/biz/ThemeService.java of the component Theme Download Function. Executing a manipulation of the argument httpUrl can lead to server-side request forgery. The attack may be launched remotely. The exploit has been publicly disclosed and may be utilized. The projec...
CVE-2026-92399	5.5	MEDI				A vulnerability was determined in GPAC 26.07.0. This affects the function rmt_client_handle_ws_frame of the file src/utlis/rmt_ws.c of the component WebSocket Handler. Executing a manipulation of the argument payload_size can lead to heap-based buffer overflow. It is possible to launch the attack remotely. The exploit has been publicly disclosed and may be utilized. Upgrading to version abi-16.26 is able to mitiga...
CVE-2026-11918	5.4	MEDI		0.003		IBM ContextForge MCP Gateway <= v1.0.4 IBM mcp-context-forge could allow an authenticated user to bypass protection mechanisms due to incomplete recursive inspection of nested payload content.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-12742	5.4	MEDI		0.002		IBM Business Automation Workflow containers and traditional could allow an authenticated attacker to trigger restricted import actions due to missing authorization controls.
CVE-2026-12751	5.4	MEDI		0.003		IBM Cloud Pak for Business Automation is vulnerable to HTML injection. A remote attacker could inject malicious HTML code, which when viewed, would be executed in the victim's Web browser within the security context of the hosting site.
CVE-2026-12758	5.4	MEDI		0.003		IBM Cloud Pak for Business Automation could allow a remote attacker to bypass authorization and invoke restricted endpoints due to improper validation of HTTP headers.
CVE-2026-12766	5.4	MEDI		0.002		IBM Langflow OSS 1.0.0 through 1.11.2 is vulnerable to server-side request forgery (SSRF). This may allow an authenticated attacker to send unauthorized requests from the system, potentially leading to network enumeration or facilitating other attacks.
CVE-2026-12910	5.4	MEDI		0.003		GitLab has remediated an issue in GitLab CE/EE affecting all versions from 18.6 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that under certain conditions could have allowed an authenticated user to bypass SAML SSO sign-in restrictions and authenticate without SSO due to missing authentication enforcement checks.
CVE-2026-15887	5.4	MEDI		0.002		IBM WebSphere Application Server 9.0, and 8.5 is affected by blind server-side request forgery when processing SOAP requests.
CVE-2026-16186	5.4	MEDI		0.002		IBM WebSphere Application Server 9.0, and 8.5 is affected by a reflected cross-site scripting vulnerability.
CVE-2026-17047	5.4	MEDI		0.001		IBM Db2 Mirror for i 7.4, 7.5, and 7.6 could allow a remote attacker to obtain sensitive information due to improper request validation.
CVE-2026-17628	5.4	MEDI		0.003		IBM Langflow OSS 1.0.0 through 1.10.2 could allow a remote authenticated attacker to change the password of an account due to improper authentication.
CVE-2026-18570	5.4	MEDI		0.001	redhat:build_of_keycloak	A flaw was found in the full-scope-disabled client-policy executor within the keycloak-services component. This component is responsible for enforcing security policies during client registration and configuration in Red Hat Build of Keycloak. The issue occurs because the executor only validates the fullScopeAllowed field when it is explicitly provided in a request. By omitting this field, a delegated user can byp...
CVE-2026-19273	5.4	MEDI		0.003		IBM Sterling B2B Integrator 6.2.0.0 through 6.2.0.6_2, 6.2.1.0 - 6.2.1.2, 6.2.2.0 - 6.2.2.1 and IBM Sterling File Gateway 6.2.0.0 through 6.2.0.6_2, 6.2.1.0 - 6.2.1.2, 6.2.2.0 - 6.2.2.1 Standard Edition could allow a remote authenticated attacker to bypass security restrictions due to improper authentication.
CVE-2026-48523	5.4	MEDI		0.001	pyjwt_project:pyjwt	PyJWT is a JSON Web Token implementation in Python. From 2.9.0 to 2.12.1, there is a verifier-side algorithm allow-list bypass when jwt.decode() or jwt.decode_complete() are called with a PyJWK key. The token header alg is checked against the caller-supplied algorithms allow-list, but signature verification is performed with the algorithm bound to the PyJWK object instead of the header algorithm. An attacker who c...
CVE-2026-55226	5.4	MEDI		0.002		Strimzi provides a way to run an Apache Kafka cluster on Kubernetes or OpenShift in various deployment configurations. In Strimzi 1.0.0 and earlier, deploying only the Topic Operator or only the User Operator through the Kafka custom resource leaves the Entity Operator ServiceAccount with RBAC permissions for both components. The excess permissions can allow access to KafkaUser custom resources and Secrets when th...
CVE-2026-59242	5.4	MEDI		0.006	apache:airflow	Apache Airflow's XCom `GET /api/v2/{...}/xcomEntries/{key}?deserialize=true` endpoint passed a string-literal payload through `BaseXCom.deserialize_value` without the `_check_forbidden_xcom_keys` guard, allowing an authenticated API user with XCom write-and-read access to instantiate arbitrary `airflow.*` classes on the API server (CWE-502). An authenticated user who can write an XCom value and then read it back w...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-68076	5.4	MEDI		0.003	apache:airflow	Apache Airflow's environment-variable secrets backend resolved a team-scoped Connection or Variable from the wrong team's scope. The guard meant to prevent this only ran when no team scope was supplied, and its pattern could not match a team name containing an underscore, which team names are allowed to contain. When the guard did not apply, the lookup fell through to an unconditional global read that resolved the...
CVE-2026-78415	5.4	MEDI		0.002		IBM Sterling Secure Proxy 6.2.0.0 through 6.2.1.2 could allow a remote authenticated attacker to perform UI spoofing and phishing attacks due to improper neutralization of user-supplied HTML markup.
CVE-2026-7884	5.4	MEDI		0.002		IBM Cognos Analytics 12.1.0 through 12.1.3 FP1, and 12.0.4 through 12.0.4 FP2 allows a non-privileged user to edit their given name and surname to include malicious JavaScript code. When an administrator later accesses the user account management panel and views that user's permissions, the malicious JavaScript code is executed. This could result in the cookies from the administrator being compromised.
CVE-2026-83198	5.4	MEDI		0.002		Vulnerability in the Oracle Field Service product of Oracle E-Business Suite (component: Internal Operations). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Field Service. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in O...
CVE-2026-83346	5.4	MEDI		0.002		Vulnerability in the Oracle Fusion Middleware Control product of Oracle Fusion Middleware (component: Framework). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Fusion Middleware Control. Successful attacks require human interaction from a person other than the attacker and whil...
CVE-2026-83419	5.4	MEDI		0.003		Vulnerability in the Oracle Communications Cloud Native Core Security Edge Protection Proxy product of Oracle Communications (component: SEPP). Supported versions that are affected are 26.1.200 and 25.2.201. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Communications Cloud Native Core Security Edge Protection Proxy. Successful attacks of this ...
CVE-2026-83431	5.4	MEDI		0.002		Vulnerability in the Oracle Product Workbench product of Oracle E-Business Suite (component: WebUI). Supported versions that are affected are 12.2.3-12.2.15. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Product Workbench. Successful attacks require human interaction from a person other than the attacker and while the vulnerability is in Oracle ...
CVE-2026-83488	5.4	MEDI		0.003		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: helidon-microprofile-security). Supported versions that are affected are 4.0.0-4.5.4. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized update, insert or delete access to some of Helidon accessible data ...
CVE-2026-84397	5.4	MEDI				Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-91021	5.4	MEDI		0.001		Trilium Notes, version v0.103.0 and earlier, contains a stored cross-site scripting (XSS) vulnerability in the share renderer for webView notes due to improper HTML escaping of user-controlled #webViewSrc values. This vulnerability allows attackers with note-authoring privileges to inject arbitrary JavaScript that executes for any user who opens the shared note, including administrators.
CVE-2026-92132	5.4	MEDI				Jenkins Gradle Plugin 2.19.1252.v15196b_5a_6e10 and earlier requests build scan data from the build scan link detected in the build log, even when a Develocity server URL is configured in the global configuration, allowing attackers able to control the build log to capture the Develocity access key configured in the global configuration by having Jenkins connect to an attacker-specified URL.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-92133	5.4	MEDI				Jenkins GitLab Plugin 1.2149.vcfc32c82b_f7f and earlier caches the GitLab API client built for alternative GitLab API token credentials under a cache key derived from the credentials ID alone, omitting the folder in which the credentials are resolved, allowing attackers with Item/Configure permission to access GitLab API token credentials they are not entitled to use.
CVE-2026-10556	5.3	MEDI		0.002		Mattermost versions 11.9.x <= 11.9.0, 11.8.x <= 11.8.4, 11.7.x <= 11.7.7, 10.11.x <= 10.11.22 fail to validate null entries in Microsoft Graph webhook notification payloads, which allows an unauthenticated attacker to crash the Microsoft Calendar plugin process and deny calendar integration service to all users on the instance via a crafted {{POST}} request to the public webhook endpoint.. Mattermost Advisory ID: ...
CVE-2026-16188	5.3	MEDI		0.003		IBM WebSphere Application Server 9.0, and 8.5 could allow a remote attacker to inject forged log entries into the server's administrative log.
CVE-2026-18065	5.3	MEDI		0.003		IBM i 7.6, 7.5, 7.4, and 7.3 could allow a remote unauthenticated attacker to gain access to sensitive information through session IP binding bypass in Navigator for i.
CVE-2026-18698	5.3	MEDI		0.002	mongodb:mongodb	An issue in MongoDB Server could allow an authenticated user with a limited database-scoped role to perform an action against protected system collections that should require more specific privileges. This could result in exposure of collection metadata and, on certain deployment configurations, unauthorized modification of system collection data.
CVE-2026-18702	5.3	MEDI		0.002	mongodb:mongodb	An issue in MongoDB Server could allow an authenticated user with limited, database-scoped privileges to modify diagnostic logging settings that affect the entire server rather than just the intended database. This could allow suppression of diagnostic logging server-wide, potentially obscuring unauthorized activity, or degrade operational monitoring by causing excessive log volume.
CVE-2026-18707	5.3	MEDI		0.003	mongodb:mongodb	An issue in MongoDB Server could allow an authenticated user, including one with no assigned privileges, to cause the server process to terminate unexpectedly by submitting a specially formed aggregation command. This could result in a denial of service.
CVE-2026-18708	5.3	MEDI		0.003	mongodb:mongodb	An issue in MongoDB Server's JavaScript scripting engine could allow an authenticated user with write privileges to cause code they control to be executed within the query scope of other users, through a specially crafted stored value processed during an internal maintenance cycle. This could result in corruption of query results affecting other users and denial of service targeted at their operations on the same ...
CVE-2026-20121	5.3	MEDI				A vulnerability in the access control list (ACL) Object Group Search (OGS) implementation of Cisco Secure Firewall Adaptive Security Appliance (ASA) Software and Cisco Secure Firewall Threat Defense (FTD) Software could allow an unauthenticated, remote attacker to bypass configured access controls. This vulnerability is due to a logic error in populating group access control policies (ACPs) with OGS configured....
CVE-2026-50024	5.3	MEDI		0.004		GitHacker is a tool that restores Git repositories from exposed .git directories. In 1.1.7 and earlier, add_head_file_tasks parses an attacker-controlled ref path from .git/HEAD and joins unvalidated path segments onto temp_dst/.git/logs/, allowing a malicious server to make GitHacker read an arbitrary local file when a victim runs the tool against the server's URL. add_hashes_parsed then scans the file for 40-cha...
CVE-2026-68870	5.3	MEDI		0.002		The Azure Key Vault secrets backend in Apache Airflow's Microsoft Azure provider resolved a team-scoped Connection or Variable id through the team-agnostic lookup when the team-scoped lookup missed. In a deployment running multi-team mode with this backend, a caller in one team could resolve a secret belonging to another team by supplying an id that spells out that team's namespace, obtaining its credentials in fu...
CVE-2026-69116	5.3	MEDI		0.002		FlyEnv before 4.18.0 fails to sanitize HTML from markdown rendering and AI chat content passed to Vue v-html directives. Attackers can inject malicious scripts through markdown sources or chat messages that execute in the Electron renderer process with access to Node.js APIs and the filesystem.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-76433	5.3	MEDI				A vulnerability in the client provisioning download feature of Cisco ISE and Cisco ISE-PIC could allow an unauthenticated, remote attacker to access protected files on an affected device. This vulnerability is due to insufficient validation of directory traversal character sequences in a user-supplied path when the software processes provisioning resource requests. An attacker could exploit this vulnerability b...
CVE-2026-76439	5.3	MEDI				A vulnerability in the endpoint posture status reporting functionality of the guest portal web application of Cisco ISE could allow an unauthenticated, remote attacker to submit forged posture status events into the endpoint posture pipeline. This vulnerability is due to insufficient authentication on an internal interface that is exposed through the guest portal. An attacker could exploit this vulnerability by...
CVE-2026-76444	5.3	MEDI				A vulnerability in an internal service of Cisco ISE and Cisco ISE-PIC could allow an unauthenticated, remote attacker to retrieve sensitive configuration information from an affected device. This vulnerability is due to missing authentication on the Policy Runtime Repository Table (PRRT) service. An attacker could exploit this vulnerability by sending a crafted request to an affected device. A successful exploi...
CVE-2026-76447	5.3	MEDI				A vulnerability in the Online Certificate Status Protocol (OCSP) responder of Cisco ISE and Cisco ISE-PIC could allow an unauthenticated, remote attacker to cause an administrative reload of the OCSP responder certificate and key material. This vulnerability is due to missing authentication on a function of the OCSP responder. An attacker could exploit this vulnerability by sending a crafted request to an affec...
CVE-2026-81176	5.3	MEDI				Svelte devalue is a JavaScript library that serializes values into strings when JSON.stringify isn't sufficient for the job. Prior to 5.9.2, devalue.parse does not reject out-of-bounds indices that are greater than or equal to values.length in src/parse.js. A specially crafted untrusted payload can make the parser alternate between array representations, producing quadratic work as the payload grows and causing de...
CVE-2026-81205	5.3	MEDI		0.003	miniorange:ldap_V_active_directory_integration	Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection') vulnerability in Drupal LDAP / Active Directory Integration allows LDAP Injection. This issue affects LDAP / Active Directory Integration versions: from 0.0.0 to 2.2.1.
CVE-2026-82066	5.3	MEDI		0.002	mongodb:mongodb	A heap out-of-bounds read security issue exists in the query planning component of MongoDB Server. An authenticated user with database read and write privileges can trigger the security issue through crafted query operations, causing the server to read memory beyond allocated buffer boundaries. The revealed memory contents may be partially observable through diagnostic query statistics output.
CVE-2026-82837	5.3	MEDI		0.004		GitLab has remediated an issue in GitLab CE/EE affecting all versions from 10.1.0 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that certain conditions could have allowed an authenticated user to access sensitive credentials and tokens without transiting the expected proxy due to improper authorization checks on internal data emission endpoints.
CVE-2026-83109	5.3	MEDI		0.003		Vulnerability in the Oracle Forms product of Oracle Fusion Middleware (component: Forms Services, C/S, Charmode). Supported versions that are affected are 12.2.1.19.0 and 14.1.2.0.0. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Oracle Forms. Successful attacks of this vulnerability can result in unauthorized read access to a subset of Oracle Forms ...
CVE-2026-83458	5.3	MEDI		0.004		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: JSON). Supported versions that are affected are 4.0.0-4.5.4. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized ability to cause a partial denial of service (partial DOS) of Helidon. CVSS 3.1 Base Score 5...
CVE-2026-83459	5.3	MEDI		0.004		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: helidon-media-multipart). Supported versions that are affected are 3.0.0-3.2.20. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized ability to cause a partial denial of service (partial DOS) of Helidon. C...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-83480	5.3	MEDI		0.003		Vulnerability in the Helidon product of Oracle Fusion Middleware (component: WebSocket). Supported versions that are affected are 4.0.0-4.5.4. Easily exploitable vulnerability allows unauthenticated attacker with network access via HTTP to compromise Helidon. Successful attacks of this vulnerability can result in unauthorized ability to cause a partial denial of service (partial DOS) of Helidon. CVSS 3.1 Base Sc...
CVE-2026-84501	5.3	MEDI		0.002		An unauthenticated attacker can inject arbitrary fake log lines into Apache ZooKeeper's operational log by sending a crafted add_auth("ensemble", ...) request containing newline characters (\n). When the ensemble name doesn't match, EnsembleAuthenticationProvider.handleAuthentication() logs the raw, unsanitized name via LOG.warn(). Because SLF4J's {} placeholder preserves embedded newlines, the attacker can forge ...
CVE-2026-87267	5.3	MEDI		0.003		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Difficult to exploit vulnerability allows low privileged attacker with network access via RDP to compromise Oracle VM VirtualBox. Successful attacks of this vulnerability can result in unauthorized ability to cause a hang or frequently repeatable crash (complete DOS) of...
CVE-2026-87859	5.3	MEDI		0.004		morgan is an HTTP request logger middleware for Node.js. In versions before 1.12.1, its escapeLogField() function does not escape the double quote character, which delimits the quoted fields of the Apache combined log format that morgan emits. An unauthenticated remote attacker who controls a value written to a quoted field, such as the User-Agent or Referer header, can include a double quote to close that field e...
CVE-2026-88932	5.3	MEDI		0.003		multer is a Node.js middleware for handling multipart/form-data uploads. In versions 2.2.0 through 2.3.0, when a request using disk storage is aborted mid-upload, file writes that complete after multer has already run its abort cleanup are not removed, so each aborted upload can leave an orphaned file on disk. A remote unauthenticated attacker can repeatedly start and abort uploads to accumulate orphaned files and...
CVE-2026-90848	5.3	MEDI		0.003		A weakness has been identified in Governikus AusweisApp up to 2.5.4. Affected is an unknown function of the component StartPAOSResponse Handler. Executing a manipulation of the argument ResultMessage can lead to cross site scripting. The attack can be launched remotely. Upgrading to version 2.5.5 is able to address this issue. It is recommended to upgrade the affected component. This CVE was requested by the vendor.
CVE-2026-91851	5.3	MEDI		0.003		Affected versions of MISP incorrectly filter dashboard templates that are restricted to a specific permission flag. DashboardsController::listTemplates() allowed a template when either: - its restrict_to_permission_flag matched one of the current user's permission flags, or - restrict_to_permission_flag equaled integer 0 However, restrict_to_permission_flag is a varchar. MySQL therefore performed num...
CVE-2026-91857	5.3	MEDI		0.002		Affected versions of MISP expose several state-changing controller actions without restricting them to POST. The affected actions are: - EventReportsController::purgeUnusedPictures() - NoticelistsController::enableNoticelist() - ServersController::removeOrphanedCorrelations() - WorkflowsController::rebuildRedis() The patch adds allowMethod(['post']) to each action, preventing them from being trig...
CVE-2026-91967	5.3	MEDI		0.003		AVideo through 29.0 contains a blind server-side request forgery vulnerability in the getHeaderContentTypeFromURL function that issues get_headers() calls guarded only by format validation. Authenticated users with canUpload permission can store attacker-chosen URLs as video links, triggering vulnerable function execution on every video watch page render to probe internal hosts using content-type oracles and timin...
CVE-2026-92184	5.3	MEDI		0.003		A security flaw has been discovered in ag-ui-protocol ag-ui 0.3.0. Affected is the function urllib.request.urlopen of the file integrations/aws-strands/python/src/ag_ui_strands/utlis.py of the component Multimodal Content. The manipulation of the argument Value results in server-side request forgery. The attack can be executed remotely. The patch is identified as bf0c34df34cbb4b1992bc37c9bffe6dd54bb189. It is adv...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-92402	5.3	MEDI				A security flaw has been discovered in ChangeWeDer crm up to c07bd4c97141521af6475034bc58523beed51bbd. This issue affects the function index of the file UserController.java of the component top.upstudy.crm.controller.UserController. The manipulation results in missing authorization. The attack can be launched remotely. This product does not use versioning. This is why information about affected and unaffected rele...
CVE-2026-92568	5.3	MEDI				MLRun through 1.11.0 contains a server-side request forgery vulnerability in the WebhookNotification handler that allows authenticated users to make the API server send arbitrary HTTP requests to internal addresses. Attackers can update a run with a malicious webhook notification that executes when the run reaches a terminal state, enabling requests to internal services, Kubernetes APIs, or cloud metadata endpoint...
CVE-2026-92778	5.3	MEDI				CMAK through 3.0.0.6 fails to apply the scheduled leader election feature toggle to HTML form routes, allowing attackers to bypass the feature gate. Attackers can access the form endpoints to start and stop the recurring election scheduler, disrupting leadership across managed Kafka clusters.
CVE-2026-9338	5.3	MEDI		0.003	ibm:websphere_application_server	IBM WebSphere Application Server 9.0, and 8.5 is vulnerable to a denial of service, caused by sending a specially-crafted request. A remote attacker could exploit this vulnerability to trigger excessive resource consumption, potentially leading to reduced availability of the affected service.
CVE-2026-19280	5.2	MEDI		0.001		IBM i 7.6, 7.5, 7.4, and 7.3 could allow a denial of service as a result of a buffer overflow in a PASE process. An authenticated attacker could leverage this to terminate their own process.
CVE-2026-49131	5.1	MEDI		0.002		OPNsense before 26.1.9 contains a stored cross-site scripting vulnerability that allows authenticated attackers with firewall rule management privileges to inject arbitrary HTML or JavaScript by embedding payloads in the firewall rule description field via the filter API endpoint. The unsanitized description value is persisted and later rendered through the default cell formatter in opnsense_bootstrap.js, which ass...
CVE-2026-49132	5.1	MEDI		0.001		OPNsense before 26.1.9 contains a stored cross-site scripting vulnerability that allows authenticated attackers to inject arbitrary HTML or JavaScript by embedding payloads in the certificate description field via the trust certificate API. The unsanitized description value is persisted and later rendered in the Dashboard Certificates widget through Certificates.js, which interpolates the raw value into HTML attri...
CVE-2026-61597	5.1	MEDI				djust provides Phoenix LiveView-style reactive server-side rendering for Django with Rust-powered performance. Prior to version 1.0.7, many djust built-in component template tags (djust.components.template_tags.*) render a developer/user-supplied URL into an href / action attribute, HTML-escaping it with conditional_escape but never validating the URL scheme. HTML escaping prevents attribute breakout but do...
CVE-2026-82069	5.1	MEDI		0.003	mongodb:mongodb	A security issue in MongoDB Server's query statistics serialization on the router allows users with monitoring privileges to access unredacted search query text from other users' operations. An improper conditional check in the serialization logic causes the data redaction mechanism to be bypassed when processing search queries through the sharded cluster router. This results in sensitive query literals being stor...
CVE-2026-90563	5.1	MEDI		0.002		A vulnerability was determined in maliangnansheng bbs-springboot 3.0.0. This affects the function utils.toToc of the file ArticleController.java. This manipulation causes cross site scripting. The attack is possible to be carried out remotely.
CVE-2026-90957	5.1	MEDI		0.002		Affected versions of MISP serve uploaded SVG images inline without a restrictive browser sandbox. The commit explains that SVG files are XML documents rather than passive bitmap images. While scripts inside SVG do not execute when the SVG is rendered through a normal , they can execute when the SVG is navigated to directly or embedded as a document. In that case, malicious <script> elements, event handlers,...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-91942	5.1	MEDI		0.002		crawl4ai before 0.9.3 contains a DOM-based cross-site scripting vulnerability in the Docker Playground UI that assigns untrusted crawl results to element.innerHTML. Attackers can craft malicious PDFs with event-handler markup to execute JavaScript in the Playground origin and steal API tokens from sessionStorage for authenticated API abuse.
CVE-2026-92002	5.1	MEDI		0.004		Affected versions of MISP use Redis to throttle repeated authentication-failure log entries. The intent is to avoid excessive duplicate logs while still recording failed authentication activity. However, User->setupRedis() returns false when Redis cannot be reached. The vulnerable _shouldLog() logic only returned true when a Redis instance existed and no throttle key was present. Therefore, when Redis was unavai...
CVE-2026-92234	5.1	MEDI		0.002		QloApps through 1.7.0 reflects unescaped child feature names into back-office validation error messages in the Hotel Reservation System feature management page. Authenticated back-office users who follow a crafted link can execute injected JavaScript in their administrative session via the child_features parameter.
CVE-2026-92590	5.1	MEDI				Craft CMS versions from 5.7.0 before 5.10.13 contain a stored cross-site scripting vulnerability in the Generated Fields feature that disables Twig autoescaping and fails to encode cached values. Content editors can inject malicious JavaScript through editable fields that executes in authenticated Control Panel sessions of higher-privileged users viewing element indexes.
CVE-2026-55244	5.0	MEDI		0.002		ASTEVAL is an evaluator of Python expressions and statements. Prior to 1.0.9, FROM_PY in asteval/astutils.py exposes BaseException, SystemExit, KeyboardInterrupt, and GeneratorExit to expressions evaluated by asteval.Interpreter.eval(), while run() and eval() in asteval/asteval.py catch Exception rather than these non-Exception BaseException subclasses. When an attacker-controlled expression raises one of these cl...
CVE-2026-79723	5.0	MEDI		0.002	langflow:langflow	IBM Langflow OSS 1.0.0 through 1.11.5 could allow a remote authenticated attacker to obtain sensitive information due to improper validation of user-controlled API endpoints.
CVE-2026-80434	5.0	MEDI		0.002	ibm:datastage_on_cloud_pak_for_data	IBM DataStage on Cloud Pak for Data 5.4.0.0 could allow a remote authenticated attacker to manipulate runtime caches and cause a denial of service due to an insecure direct object reference.
CVE-2026-19729	4.9	MEDI		0.005		A flaw was found in the key provider component of the keycloak-services library, which is the core engine for the Red Hat Build of Keycloak. The issue occurs because a previous fix for path probing was incomplete, allowing a realm administrator to still submit arbitrary filesystem paths as keystore parameters. This can be used to determine the existence and readability of files on the server, potentially exposing ...
CVE-2026-20072	4.9	MEDI				A vulnerability in the web-based management interface of Cisco ISE could allow an authenticated, remote attacker to obtain sensitive information from network users that are outside the security group that the attacker is assigned to. This vulnerability exists because certain files lack proper authorization enforcement. An attacker with administrative privileges and management rights over network users co...
CVE-2026-20235	4.9	MEDI				A vulnerability in the API of Cisco Identity Services Engine (ISE) could allow an authenticated, remote attacker to view sensitive information on an affected device. To exploit this vulnerability, the attacker must have valid administrative credentials. This vulnerability is due to insufficient validation of user-supplied parameters in API requests. An attacker could exploit this vulnerability by sending a craf...
CVE-2026-20282	4.9	MEDI				A vulnerability in Cisco ISE could allow an authenticated, remote attacker to obtain write access on the underlying operating system of an affected device. This vulnerability is due to insufficient validation of user-supplied input. An attacker could exploit this vulnerability by sending a crafted HTTP request to an affected device. A successful exploit could allow the attacker to obtain write access to the und...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-48737	4.9	MEDI		0.002		pyLoad is a free and open-source download manager written in Python. Prior to 0.5.0b3.dev101, is_global_address in src/pyload/core/utis/web/check.py relies on Python's global-address classification without examining IPv4 destinations embedded in 6to4 or NAT64 IPv6 addresses. A low-privileged user can submit an IPv6 literal through parse_urls to the pre-resolution is_global_host guard. Because host_to_ip is pinned...
CVE-2026-76426	4.9	MEDI				A vulnerability in the REST API of Cisco ISE and Cisco ISE-PIC could allow an authenticated, remote attacker to conduct SQL injection attacks against the monitoring database. This vulnerability is due to insufficient validation of specific parameters that are then concatenated into an SQL statement. An attacker could exploit this vulnerability by sending a crafted request that contains SQL statements in one of ...
CVE-2026-76427	4.9	MEDI				A vulnerability in the offline profiler feed service of Cisco ISE could allow an authenticated, remote attacker to read arbitrary files that are stored on an affected device. This vulnerability is due to the parsing of attacker-controlled feed metadata with an XML parser that does not disable external entity resolution. An attacker could exploit this vulnerability by uploading a crafted offline feed package thr...
CVE-2026-76428	4.9	MEDI				A vulnerability in the REST APIs of Cisco ISE and Cisco ISE-PIC could allow an authenticated, remote attacker to conduct SQL injection attacks against the session database. This vulnerability is due to certain parameters being concatenated directly into SQL clauses without parameterization. An attacker could exploit this vulnerability by sending a crafted request that contains SQL statements in one of the affec...
CVE-2026-76431	4.9	MEDI				A vulnerability in the file management function of the web-based management interface of Cisco ISE and Cisco ISE-PIC could allow an authenticated, remote attacker to delete arbitrary files and directories on an affected device. To exploit this vulnerability, the attacker must have valid administrative credentials. This vulnerability is due to improper validation of directory traversal character sequences in a u...
CVE-2026-76432	4.9	MEDI				A vulnerability in the web-based management interface of Cisco ISE and Cisco ISE-PIC could allow an authenticated, remote attacker with administrative-level privileges to write arbitrary files on an affected device. This vulnerability exists because the affected software does not properly validate directory traversal character sequences in a user-supplied file path during the upload process. An attacker could e...
CVE-2026-76434	4.9	MEDI				A vulnerability in the certificate import functionality of the web-based management interface of Cisco ISE and Cisco ISE-PIC could allow an authenticated, remote attacker to read arbitrary files from the affected system. To exploit this vulnerability, the attacker must have valid administrative credentials. This vulnerability is due to insufficient validation of user-supplied input by the affected feature. An a...
CVE-2026-76446	4.9	MEDI				A vulnerability in an API of Cisco ISE and Cisco ISE-PIC could allow an authenticated, remote attacker to read specific files on the underlying operating system of an affected device. This vulnerability is due to improper restriction of XML external entity references. An attacker could exploit this vulnerability by sending a crafted request to an affected device. A successful exploit could allow the attack...
CVE-2026-76448	4.9	MEDI				A vulnerability in Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) could allow an authenticated, remote attacker to conduct an SQL or HQL injection attack on an affected device. This vulnerability is due to insufficient validation of user-supplied input to the affected APIs before it is used to build database queries. An attacker could exploit this vulnerability by sendin...
CVE-2026-76449	4.9	MEDI				A vulnerability in Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) could allow an authenticated, remote attacker to conduct an SQL or HQL injection attack on an affected device. This vulnerability is due to insufficient validation of user-supplied input to the affected APIs before it is used to build database queries. An attacker could exploit this vulnerability by sendin...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-76450	4.9	MEDI				A vulnerability in Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) could allow an authenticated, remote attacker to conduct an SQL or HQL injection attack on an affected device. This vulnerability is due to insufficient validation of user-supplied input to the affected APIs before it is used to build database queries. An attacker could exploit this vulnerability by sendin...
CVE-2026-76451	4.9	MEDI				A vulnerability in Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) could allow an authenticated, remote attacker to conduct an SQL or HQL injection attack on an affected device. This vulnerability is due to insufficient validation of user-supplied input to the affected APIs before it is used to build database queries. An attacker could exploit this vulnerability by sendin...
CVE-2026-16189	4.8	MEDI		0.002		IBM WebSphere Application Server 9.0, and 8.5 could allow a remote attacker to inject forged log entries into the server's administrative log.
CVE-2026-71325	4.8	MEDI		0.001	traefik:traefik	Traefik is an open-source edge router that makes publishing services a fun and easy experience. Prior to 2.11.54, 3.6.25, and 3.7.10, cross-namespace @kubernetescrd references are not rejected for TraefikService backend references resolved by the service resolver. A tenant confined by RBAC to a single namespace can therefore bind its own router to a TraefikService owned by another namespace and expose or reroute t...
CVE-2026-78546	4.8	MEDI		0.001		Out-of-bounds read vulnerability in Citirx Workspace app for Windows. This issue affects Workspace app for Windows: before 2603.11 Current Release (CR), before 2507.1 LTSR CU3, and before LTSR 2607.
CVE-2026-86472	4.8	MEDI		0.002		fast-uri is a dependency-free RFC 3986 URI parser for Node.js, used by Fastify and ajv. In versions before 2.4.7, from 3.0.0 through 3.1.7, and from 4.0.0 through 4.1.4, fast-uri folds the host to lowercase before it percent-decodes the host, so a percent-encoded uppercase octet such as %41 decodes to a literal A that is never folded. For a scheme-relative reference such as //host there is no scheme, so the host c...
CVE-2026-86818	4.8	MEDI		0.002		fast-uri is a dependency-free RFC 3986 URI parser for Node.js, used by Fastify and ajv, that added a mailto scheme parser in version 4.1.3. In versions 4.1.3 and 4.1.4, the mailto parser compares each query field name to the reserved names to, subject, and body while the name is still percent-encoded, and decodes it only when storing it as a generic header, so a percent-encoded spelling of a reserved field name is...
CVE-2026-90570	4.8	MEDI		0.003		A vulnerability has been found in linlinjava litemall 1.4.0/1.5.0/1.6.0/1.7.0/1.8.0. This issue affects the function AdminGoodsService.validate of the file litemall-vue/src/views/items/detail/index.vue of the component Product Detail. Such manipulation of the argument detail leads to cross site scripting. The attack may be launched remotely. The project was informed of the problem early through an issue report but...
CVE-2026-13277	4.7	MEDI		0.003		IBM Verify Identity Access could allow a remote attacker to conduct phishing attacks, using an open redirect attack. By persuading a victim to visit a specially crafted Web site, a remote attacker could exploit this vulnerability to spoof the URL displayed to redirect a user to a malicious Web site that would appear to be trusted. This could allow the attacker to obtain highly sensitive information or conduct furt...
CVE-2026-19619	4.7	MEDI		0.003		GitLab has remediated an issue in GitLab CE/EE affecting all versions from 19.0 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that under certain conditions could have allowed an unauthenticated user to execute arbitrary JavaScript in the context of a targeted user's session due to improper sanitization of pasted HTML content in the Content Editor.
CVE-2026-20350	4.7	MEDI				A vulnerability in the web-based management interface of Cisco ThousandEyes Virtual Appliance could allow an authenticated, remote attacker to inject arbitrary operating system commands. This vulnerability is due to improper validation of user-supplied input to the web-based management interface. An attacker could exploit this vulnerability by saving configuration details that contain malicious values. A succes...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-68849	4.7	MEDI		0.002	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Out-of-bounds read in Windows Bluetooth Port Driver allows an authorized attacker to disclose information locally.
CVE-2026-69832	4.7	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of sensitive system information to an unauthorized control sphere in Windows Win32K allows an authorized attacker to disclose information locally.
CVE-2026-69853	4.7	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use of uninitialized resource in Windows Win32K allows an authorized attacker to disclose information locally.
CVE-2026-69895	4.7	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Spaceport.sys allows an authorized attacker to disclose information locally.
CVE-2026-69548	4.6	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows RNDIS allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-87275	4.6	MEDI		0.001		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows high privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. While the vulnerability is in Oracle VM VirtualBox, attacks may significantly impact additional prod...
CVE-2026-92627	4.6	MEDI				A heap-use-after-free vulnerability exists in H5T__conv_f_f() in src/H5Tconv.c in HDF5 before 1.14.2. When converting a compound datatype containing floating-point members during a dataset read, a temporary buffer allocated with calloc() is freed and subsequently read from within the same conversion routine. An attacker who can supply a crafted HDF5 file containing a specially constructed compound datatype can tri...
CVE-2026-78547	4.4	MEDI		0.002		Out-of-bounds write vulnerability in Citrix Citrix Workspace app for Windows. This issue affects Citrix Workspace app for Windows: before 2603.11 Current Release (CR), before 2507.1 LTSR CU3, and before LTSR 2607.
CVE-2026-86341	4.4	MEDI		0.003		GitLab has remediated an issue in GitLab EE affecting all versions from 17.1 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that, under certain conditions, an authenticated user with Owner or Maintainer permissions could have silently disabled protected environment deployment approval requirements, allowing unapproved deployments to reach production, due to improper access control checks performed after...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-87274	4.4	MEDI		0.001		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Difficult to exploit vulnerability allows low privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. Successful attacks require human interaction from a person other than the attacker. Successful atta...
CVE-2026-16794	4.3	MEDI		0.003		GitLab has remediated an issue in GitLab EE affecting all versions from 18.11 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that under certain conditions could have allowed an authenticated user with the Security Manager role to execute arbitrary CI/CD jobs and access protected variables within group projects due to improper authorization controls on compliance framework management.
CVE-2026-18251	4.3	MEDI		0.001		IBM i 7.6, 7.5, 7.4, and 7.3 could allow a remote attacker to obtain sensitive information due to improper validation of the WebSocket origin.
CVE-2026-18515	4.3	MEDI		0.003		IBM i 7.6, 7.5, 7.4, and 7.3 could allow a remote authenticated attacker to place files into the file system with Navigator for i when they should be blocked by Navigator configuration. This could allow attackers to upload files onto the system to places the Navigator support did not intend, but only if the profile could already do that by itself.
CVE-2026-20285	4.3	MEDI				A vulnerability in the web-based management interface of Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) could allow an authenticated, remote attacker to modify parts of the configuration on an affected device. This vulnerability is due to the lack of server-side validation of Administrator permissions. An attacker could exploit this vulnerability by submitting ...
CVE-2026-20286	4.3	MEDI				A vulnerability in the web-based management interface of Cisco Identify Services Engine (ISE) could allow an authenticated, remote attacker to modify parts of the configuration on an affected device. This vulnerability is due to the lack of server-side validation of Administrator permissions. An attacker could exploit this vulnerability by submitting a crafted HTTP request to an affected system. A suc...
CVE-2026-48891	4.3	MEDI		0.006	apache:airflow	A bug in Apache Airflow's ``ui/dependencies`` scheduling graph endpoint applied the caller's readable-Dag filter to the top-level serialized Dag key but still emitted referenced Dag IDs through the ``dep.source`` and ``dep.target`` fields of trigger / sensor dependency entries. An authenticated UI user with read permission on some Dags could enumerate the identifiers of other Dags they were not authorized to read by in...
CVE-2026-54183	4.3	MEDI		0.005	apache:airflow	Apache Airflow's secrets masker hides values stored under sensitive key names when they are displayed in the UI. The masker's recursion-depth limit did not descend into values nested inside a list, tuple, or set beyond that limit, so an Airflow Variable holding such a deeply-nested value was shown unmasked in the Variables UI. The exposure is limited to the UI: any authenticated user who can see the Variable in th...
CVE-2026-54247	4.3	MEDI		0.002		Skipper is an HTTP router and reverse proxy for service composition. Prior to 0.26.22, Handler in dataclients/kubernetes/admission/admission.go passes the body of requests to the Kubernetes admission endpoint at :9443/admission directly to io.ReadAll(r.Body) without a size limit. An attacker with in-cluster network access and a valid Kubernetes client certificate can send a very large body that causes unbounded me...
CVE-2026-59308	4.3	MEDI		0.002	vmware:spring_ai	In Spring AI's Semantic Cache support, the context hash used to isolate cached responses between different system prompts could allow cached responses to be shared across unrelated contexts. Affected versions: Spring AI: 2.0.0
CVE-2026-61911	4.3	MEDI		0.002	cyrus:imap	An issue was discovered in Cyrus IMAP before 3.12.4. There is a Sieve mailbox existence oracle. An authenticated user could install a Sieve script that probed whether another user's private mailbox existed, or read the value of shared mailbox annotations, by observing which fileinto branch fired during LMTP delivery.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-73019	4.3	MEDI		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper resolution of path equivalence in Windows URL Moniker allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-7514	4.3	MEDI		0.003		GitLab has remediated an issue in GitLab CE/EE affecting all versions from 13.9 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that an authenticated user with developer-role permissions could substitute package file content and hide packages from their owners due to improper authorization checks in the Generic Package Registry.
CVE-2026-75792	4.3	MEDI		0.003		IBM Sterling Secure Proxy 6.2.0.0 through 6.2.1.2 could allow a remote authenticated attacker to view administrative user interface components due to client-side authorization bypass.
CVE-2026-8030	4.3	MEDI		0.004		GitLab has remediated an issue in GitLab CE/EE affecting all versions from 13.0 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that under certain conditions could have allowed an authenticated user to prevent another user from modifying their group settings due to improper validation of group URL slugs during namespace transfers.
CVE-2026-83416	4.3	MEDI		0.004		Vulnerability in the Oracle Coherence product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0, 14.1.1.0.0, 14.1.2.0.0 and 15.1.1.0.0. Easily exploitable vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Coherence. Successful attacks of this vulnerability can result in unauthorized ability to cause a partial denial of...
CVE-2026-89321	4.3	MEDI		0.003		Publishing limits the compressed size of a VSIX (ovsx.publishing.max-content-size, 512 MB by default) but nothing limited how large an entry becomes when opened. On the first request to /vscode/unpkg/{namespace}/{extension}/{version}/{path}, WebResourceService opened the entry with ZipFile.getInputStream() and passed the decompressed stream to Files.copy(), which ran to the end of the stream without counting b...
CVE-2026-92141	4.3	MEDI				Jenkins Keycloak Authentication Plugin 2.4.1 and earlier does not restrict the redirect URL after login, allowing attackers to perform phishing attacks.
CVE-2026-12763	4.2	MEDI		0.001		IBM Langflow OSS 1.0.0 through 1.11.5 could allow an authenticated attacker to access another user's MCP server context due to improper cache key isolation in the MCP Tools component.
CVE-2026-18151	4.2	MEDI		0.001		IBM i 7.6, 7.5, 7.4, and 7.3 could allow a remote authenticated attacker to obtain sensitive information due to a race condition during the WebSocket handshake process.
CVE-2026-59341	4.2	MEDI		0.003		A security vulnerability exists in the Sealed Secrets controller's unauthenticated POST endpoints. By submitting a modified payload containing custom Go template logic in spec.template.data, an attacker with internal network access can abuse the handler as a decryption oracle to recover the full plaintext of any sealed secret. The POST /v1/verify and /v1/rotate handlers call Unseal() to decrypt target secrets, ...
CVE-2026-87280	4.2	MEDI		0.001		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows high privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. Successful attacks require human interaction from a person other than the attacker. Successful attac...
CVE-2026-92131	4.2	MEDI				Jenkins Pipeline: Groovy Libraries Plugin 805.va_fc79344957d and earlier does not restrict the library path provided to the library Pipeline step to a relative path inside the SCM checkout, and follows symbolic links to locations outside of the SCM checkout when retrieving the library, resulting in a path traversal vulnerability, allowing attackers able to configure Pipelines to read files in a resources directory...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-92138	4.2	MEDI				The OAuth authorization endpoint in Jenkins Bitbucket Server Integration Plugin 6.0.1 and earlier reads the `oauth_callback` URL from the submitted form rather than from the server-side stored request token, allowing attackers to hijack the OAuth flow and obtain an access token on behalf of the victim.
CVE-2026-20071	3.8	LOW				A vulnerability in the SSID bring-your-own-device (BYOD) onboarding workflow of Cisco ISE could allow an unauthenticated, adjacent attacker to hijack the onboarding session of another user and access protected 802.1X networks. This vulnerability is due to insufficient authentication checks that are performed while a user is being onboarded. An attacker could exploit this vulnerability by spoofing th...
CVE-2026-69200	3.7	LOW				node-opcua is an OPC UA implementation for TypeScript and Node.js. Prior to node-opcua-client 2.145.0, the internal fieldsToJson method in packages/node-opcua-client/source/alarms_and_conditions/client_alarm.ts directly assigns unsanitized field names and allows a __proto__.pollutedKey path to modify Object.prototype. Successful exploitation requires an application to expose attacker-controlled event fields to fie...
CVE-2026-86071	3.7	LOW				Junrar is an open source Java RAR archive library. Prior to version 7.6.1, LocalFolderExtractor in src/main/java/com/github/junrar/LocalFolderExtractor.java can create directories outside the intended extraction root when processing a crafted archive entry. LocalFolderExtractor.createFile() validates only the final canonical file path, while LocalFolderExtractor.makeFile() creates intermediate path segments with u...
CVE-2026-19086	3.3	LOW		0.001		IBM i 7.6, 7.5, 7.4, and 7.3 could allow a denial of service as a result of a buffer overflow in a PASE process. An authenticated attacker could leverage this to terminate their own process.
CVE-2026-87281	3.2	LOW		0.002		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows high privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. While the vulnerability is in Oracle VM VirtualBox, attacks may significantly impact additional prod...
CVE-2026-87284	3.2	LOW		0.001		Vulnerability in the Oracle VM VirtualBox product of Oracle Virtualization (component: Core). The supported version that is affected is 7.2.16. Easily exploitable vulnerability allows high privileged attacker with logon to the infrastructure where Oracle VM VirtualBox executes to compromise Oracle VM VirtualBox. While the vulnerability is in Oracle VM VirtualBox, attacks may significantly impact additional prod...
CVE-2026-16190	3.1	LOW		0.002		IBM WebSphere Application Server 9.0, and 8.5 is affected by an authorization bypass vulnerability.
CVE-2026-3855	3.1	LOW		0.003		GitLab has remediated an issue in GitLab CE/EE affecting all versions from 18.2.7 before 19.1.8, 19.2 before 19.2.6, and 19.3 before 19.3.2 that under certain conditions could have allowed an authenticated user with project-level permissions to access restricted file contents on the server or cause denial of service due to improper validation of parameters in the Terraform state upload functionality.
CVE-2026-83369	3.1	LOW		0.002		Vulnerability in the Oracle Access Manager product of Oracle Fusion Middleware (component: Access SDK). Supported versions that are affected are 12.2.1.4.0 and 14.1.2.1.0. Difficult to exploit vulnerability allows low privileged attacker with network access via HTTP to compromise Oracle Access Manager. Successful attacks of this vulnerability can result in unauthorized ability to cause a partial denial of servi...
CVE-2026-92130	3.1	LOW				Jenkins Pipeline: Multibranch Plugin 841.vec5b_9e1806ec and earlier does not set the appropriate context for credentials lookup in the resolveScm Pipeline step, allowing attackers with Item/Configure permission to access and capture credentials they are not entitled to.
CVE-2026-83414	2.5	LOW		0.001		Vulnerability in the Oracle Coherence product of Oracle Fusion Middleware (component: Core). The supported version that is affected is 15.1.1.0.0. Difficult to exploit vulnerability allows low privileged attacker with logon to the infrastructure where Oracle Coherence executes to compromise Oracle Coherence. Successful attacks of this vulnerability can result in unauthorized read access to a subset of Oracle C...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-18703	2.3	LOW		0.001	mongodb:mongodb	An issue in MongoDB Server could allow a party with a valid client certificate and a corresponding user account to authenticate using a certificate-based authentication method, even when an administrator has configured the server to restrict authentication to other mechanisms. This could allow authentication through a method the administrator intended to disable.
CVE-2026-82060	2.3	LOW		0.002	mongodb:mongodb	In MongoDB, insufficient validation of shard key values during document insertion allowed authenticated users to store documents with specially crafted, operator-shaped objects as shard key values in sharded collections. When change stream events for such documents were processed with the updateLookup full document mode, the crafted values were embedded into internal post-image lookup queries without proper saniti...
CVE-2026-86089	2.3	LOW				Apache NiFi 2.11.0 supports migrating the contents of a version-controlled Process Group into a Connector using REST API methods that list eligible migration sources and submit migration requests. The framework authorized both methods against the target Connector alone, without evaluating access to the Process Groups involved. The absence of Process Group authorization allowed an authenticated user with read acces...
CVE-2026-92359	2.3	LOW				A security flaw has been discovered in ag-ui-protocol ag-ui 0.3.0. The affected element is the function create_strands_app of the file integrations/aws-strands/python/src/ag_ui_strands/utlis.py of the component CORSMiddleware. The manipulation results in permissive cross-domain policy with untrusted domains. The attack may be launched remotely. The attack requires a high level of complexity. The exploitability is ...
CVE-2026-81925	2.1	LOW		0.004		Concrete CMS before 9.5.3 improperly neutralized a user-supplied custom date format when rendering conversation messages, resulting in reflected cross-site scripting. An attacker could execute arbitrary JavaScript in the browser of a user who was tricked into submitting a crafted POST request to the conversation view endpoint. Exploitation was aided by the absence of a CSRF token on the endpoint, which allowed the...
CVE-2026-90511	2.1	LOW		0.002		A vulnerability was detected in GongShengyue OnlineBooks up to dfc5eacc08d3b0396c266049548618f6fb9587ea. This vulnerability affects unknown code of the file src/cn/ylcto/book/servlet/BooksServlet.java of the component listSplit Interface. The manipulation of the argument column results in sql injection. The attack may be performed from remote. The exploit is now public and may be used. This product utilizes a roll...
CVE-2026-90598	2.1	LOW		0.002		A vulnerability was detected in jaygajera17 E-commerce-project-springBoot up to 5e74a46b4b70623d0e4a0c9c4aee3bd1777185d2. The impacted element is the function UserController.updateUser of the file UserController.java. Performing a manipulation of the argument userId results in authorization bypass. It is possible to initiate the attack remotely. The exploit is now public and may be used. This product is using a ro...
CVE-2026-81926	2.0	LOW		0.003		Concrete CMS 9.4.0 through 9.5.2 did not escape colliding page paths before rendering them in the location panel's duplicate-path confirmation dialog. The panel's check endpoint returned the submitted path unmodified in its JSON response, and client-side JavaScript inserted each value into the dialog as raw HTML, so a crafted page path executed script in the editor's authenticated browser session. The Concrete CMS...
CVE-2026-83413	1.9	LOW		0.001		Vulnerability in the Oracle Coherence product of Oracle Fusion Middleware (component: Core). Supported versions that are affected are 12.2.1.4.0, 14.1.1.0.0, 14.1.2.0.0 and 15.1.1.0.0. Difficult to exploit vulnerability allows high privileged attacker with logon to the infrastructure where Oracle Coherence executes to compromise Oracle Coherence. Successful attacks of this vulnerability can result in unauthori...
CVE-2025-64059	1.8	LOW		0.002		Grav 1.7.50.2 allows admins to enter JavaScript via the Home Page editor. NOTE: the relevance of this for stored XSS is disputed because admins are allowed to modify templates, install plugins, and upload other executable content.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-81927	1.8	LOW		0.003		Concrete CMS before 9.5.3 contained a stored cross-site scripting vulnerability in SVG file handling. When SVG processing was set to the non-default "Reject files containing potentially harmful elements" mode (concrete.file_manager.images.svg_sanitization.action = reject), uploaded SVGs were checked only against a small built-in blocklist covering the script element and on* event-handler attributes; the broader en...
CVE-2026-54280	1.7	LOW		0.003	aiohttp:aiohttp	AIOHTTP is an asynchronous HTTP client/server framework for asyncio and Python. Prior to 3.14.1, payload resources are not closed correctly when a client disconnects in the middle of a write. If a payload is using an open file or similar limited resource, then an attacker may be able to cause resource starvation temporarily until garbage collection or similar closes the file. This vulnerability is fixed in 3.14.1.
CVE-2026-91842	1.2	LOW		0.004		A vulnerability has been found in OpenBankProject OBP-API up to 1.10.1. This impacts the function Kryolnjection.invert of the file obp-api/src/main/scala/code/api/cache/Redis.scala of the component KryolnHandler. Such manipulation leads to deserialization. The attack can be launched remotely. A high complexity level is associated with this attack. The exploitability is said to be difficult. The exploit has been dis...
CVE-2026-91835	0.9	LOW		0.001		A vulnerability was detected in OpenClaw ClawScan up to 0.1.6. The impacted element is the function IsBinaryFile of the file internal/runner/static_scanner.go of the component File Classifier. The manipulation results in interpretation conflict. Attacking locally is a requirement. The exploit is now public and may be used. Upgrading to version 0.1.7 is sufficient to resolve this issue. The patch is identified as 0...
CVE-2026-91836	0.9	LOW		0.003		A flaw has been found in OpenClaw ClawScan up to 0.1.6. This affects an unknown function of the file internal/runner/static_scanner.go of the component Static Scanner. This manipulation causes incomplete comparison with missing factors. It is possible to launch the attack on the local host. The exploit has been published and may be used. Upgrading to version 0.1.7 mitigates this issue. Patch name: 9f6a6fbb9f113734...
CVE-2026-81866	0.5	LOW				Apache NiFi 2.9.0 through 2.11.0 provide Connector configuration update and verification REST API methods that do not enforce authorization checking on Assets and Secrets referenced in proposed configuration. Updating or verifying a Connector configuration step can apply Asset and Secret references, but framework authorization was limited to write privileges on the Connector itself. As a result of the missing auth...
CVE-2026-11921				0.001		IBM Verify Identity Access containers may not apply management password change operations correctly.
CVE-2026-11927				0.002		IBM Security Verify Identity Access reverse proxy may allow parameters to be injected in requests to third party services.
CVE-2026-11928				0.001		IBM Verify Identity Access is vulnerable to a buffer overflow attack.
CVE-2026-12101				0.001		IBM Verify Identity Access could allow an administrator to execute additional commands they are not entitled to due to improper validation of user supplied requests.
CVE-2026-13272				0.001		IBM Verify Identity Access is missing origin validation which could allow a remote attacker to perform operations as the victim and potentially launch further attacks against the systems.
CVE-2026-13327				0.001		Improper certificate validation on LDAPS connections to Active Directory in Devolutions Server 2026.2.16 and earlier allows a network-positioned attacker to intercept privileged directory service credentials via a spoofed domain controller certificate.
CVE-2026-59739				0.002		Information disclosure via SetWatches reconnect replay in Apache ZooKeeper due to missing ACL check. An attacker can discover ACL-restricted paths by registering exists-watches on non-existent paths, then reconnecting after the paths are created with restricted ACLs. Issue is caused by incomplete fix for CVE-2024-23944 (ZOOKEEPER-4799). The fix added ACL checking to WatchManager.triggerWatch(). However, DataTree.s...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-59969				0.001		Apache ZooKeeper quorum TLS fails to enforce peer hostname verification in FIPS-mode deployments. When <code>sslQuorum=true</code> , <code>zookeeper.fips-mode=true</code> , <code>ssl.quorum.hostnameVerification=true</code> , and <code>ssl.quorum.clientHostnameVerification=true</code> are enabled, the Java SSLSocket quorum path accepts a CA-trusted peer certificate whose SAN does not match the connected host. A malicious or misissued peer certificate can therefore join...
CVE-2026-68536						Server-Side Request Forgery / Local File Inclusion in Apache MyFace Core. Older unsupported versions may also be affected. Users are recommended to upgrade to versions 2.3.12, 2.3-next-M9, 3.0.4, 4.0.4, or 4.1.4, which fix this issue.
CVE-2026-70469						Apache NiFi 2.11.0 disabled support for gzip-encoded HTTP requests for the application REST API and rejected requests that included the standard Content-Encoding header indicating gzip encoding. The framework enforcement filter did not check multiple instances of the Content-Encoding header and did not reject non-standard identifiers for gzip encoding, allowing a malicious client to send crafted requests that coul...
CVE-2026-76186				0.002		Apache Airflow Keycloak provider: from Airflow 3.3 the Keycloak auth manager takes a user's identity from the signed Airflow session token but takes the Keycloak access and refresh tokens used for every authorization decision from separate, unauthenticated cookies, and never checks that the two describe the same subject. A user who holds any valid Airflow login of their own, together with another subject's Keycloa...
CVE-2026-76187				0.002		Apache Airflow Keycloak provider: the unauthenticated token endpoint accepts a client-credentials grant for any confidential client registered in the Keycloak realm, not only the client configured for Airflow. No allowlist restricts which client ids may authenticate, so the credentials of an unrelated application that happens to share the realm are valid Airflow login credentials, and Airflow mints a signed sessio...
CVE-2026-79993				0.002		The <code>`deleteContainer`</code> opcode (0x14/20) is processed without verifying the caller's ACL permissions, allowing any authenticated client to delete specific znodes in the data tree regardless of the ACL restrictions on the znode or its parent. This opcode is considered internal-only and the official client doesn't have API for it, but a client that can open a plain TCP session on the ZooKeeper client port (2181 by def...
CVE-2026-82310				0.003		Apache Airflow FAB provider: deactivating a user account does not stop tokens issued to that account before deactivation. Password authentication correctly rejects the disabled account, but the Core API continues to accept an existing, unexpired token naming it, and lets that token mint a replacement — so the account keeps its role-scoped access indefinitely after an administrator has disabled it. The user replays...
CVE-2026-82311				0.002		Apache Airflow FAB provider: resetting a user's password does not delete that user's existing database-backed sessions, despite documented behaviour that it does. The cleanup compares the string identifier Flask-Login stores in the session against the user's integer database identifier, so the comparison never matches and no session is removed. An attacker who already holds a copy of the victim's session cookie ke...
CVE-2026-84088				0.002		The Xpro Addons — 140+ Widgets for Elementor WordPress plugin before 1.7.9 does not validate or sanitize a widget link setting before storing and using it in a JavaScript navigation call, allowing users with the contributor role and above to inject and store JavaScript that executes in the browser of anyone who interacts with the affected widget.
CVE-2026-84439				0.003		When audit logging is enabled (<code>zookeeper.audit.enable=true</code>), an unauthenticated attacker can inject arbitrary fields into Apache ZooKeeper's audit log by sending a digest authentication request with tab characters (<code>\t</code>) embedded in the username. Because the audit log uses tab-separated key=value format, the injected tabs are parsed as legitimate field separators, allowing the attacker to spoof audit results (e.g., ...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-86444				0.002		The LearnPress WordPress plugin before 4.4.7 does not escape a user supplied value before using it in an HTML attribute on a public page, allowing unauthenticated attackers to execute arbitrary JavaScript in the browser of anyone who opens a crafted link, including a logged in administrator. Only sites running a classic, non-block are affected.
CVE-2026-86462				0.002		Apache Airflow FAB provider: changing a user's password through the Admin user-edit PATCH endpoint does not invalidate that user's existing database-backed sessions. An attacker who already holds a copy of the victim's session cookie keeps full access as that user after the password change, so the password reset does not evict them. Affects deployments using the FAB auth manager with database-backed sessions; an a...
CVE-2026-86465				0.002		Apache Airflow Akeyless provider: the Akeyless secrets backend's team-scope guard can be bypassed with a user-controlled key. In a multi-team deployment, a Dag author scoped to one team can supply a Variable key containing a path separator that causes the backend to resolve a secret belonging to a different team, because the lookup path is concatenated from an unvalidated key after the team-scoped lookup misses. T...
CVE-2026-86466				0.001		Apache Airflow FAB provider: the Authentik OAuth path in the FAB auth manager does not validate the issuer or audience claims of the id_token it accepts. An attacker holding a token that the same Authentik identity provider minted for a different client application can present it to Airflow and be authenticated as the user it names, because the audience claim is never checked. Affects deployments using the FAB aut...
CVE-2026-86784				0.002		The Visualizer WordPress plugin before 4.0.8 does not sanitise and escape a chart's JSON data source configuration before outputting it back in the chart editor, allowing users with the Contributor role and above to store JavaScript that executes in the browser of any higher-privileged user, such as an administrator, who reviews the affected chart.
CVE-2026-86792				0.005		Apache Airflow Apache Kafka provider versions 1.15.0 before 2.0.0 resolve dotted-path strings found in a Kafka connection's `extra` field into Python callables via `import_string`, with no allowlist, and hand them to the confluent-kafka client which invokes them. Deployments that have enabled the Kafka event producer — `dag_run_events_enabled` or `task_instance_events_enabled`, both disabled by default — build tha...
CVE-2026-88593						kkFileView 5.0.0 through 5.0.2 allows reflected XSS via the /onlinePreview endpoint. The OnlinePreviewController passes the user-controlled page and kkagent request parameters to FreeMarker templates without sanitization, and the templates insert these values into raw JavaScript contexts.
CVE-2026-89776				0.002		In the Linux kernel, the following vulnerability has been resolved: vxlan: vnifilter: enforce exact length of GROUP/GROUP6 attributes The VXLAN VNI filter entry policy declares the GROUP/GROUP6 address attributes as NLA_BINARY with only a maximum length, so validate_nla() accepts a payload shorter than the address. The GROUP consumer reads it with nla_get_in_addr(), an unconditional 4-byte load, so a short attri...
CVE-2026-89780				0.002		In the Linux kernel, the following vulnerability has been resolved: net: qualcomm: rmnet: restore skb->dev on deaggregated frames rmnet_map_deaggregate() allocates each sub-frame with alloc_skb() and leaves skb->dev NULL. __rmnet_map_ingress_handler() assigns skb->dev = ep->egress_dev only on the data path, but a MAP command frame is dispatched to rmnet_map_command() before that, so rmnet_map_send_ack() runs net...
CVE-2026-89784				0.002		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: check rpc_sockaddr2uaddr() return value in rpcb_register_inet4/6 rpcb_register_inet4() and rpcb_register_inet6() store the result of rpc_sockaddr2uaddr() into map->r_addr without checking it for NULL. rpc_sockaddr2uaddr() returns NULL when its final kstrdup() fails, and the unchecked NULL is then carried into the synchronous RPCBPROC_SET...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89785				0.002		In the Linux kernel, the following vulnerability has been resolved: fs/ntfs3: fix out-of-bounds read of INDEX_ROOT in reparse/objid init ntfs_reparse_init() and ntfs_objid_init() parse the index root of the \$Extend/\$Reparse and \$Extend/\$Objid metafiles (the INDEX_ROOT attributes named \$R and \$O). They read its type and rule fields through resident_data(), which does not check that the resident attribute is large...
CVE-2026-89787				0.002		In the Linux kernel, the following vulnerability has been resolved: ext4: check dir entry fits before reading the hash trailer in ext4_search_dir() For casefolded encrypted directories ext4 stores an 8-byte hash trailer after the name (EXT4_DIRENT_HASHES()), at an offset derived from de->name_len. On the sb_no_casefold_compat_fallback() path ext4_match() reads that trailer, but ext4_search_dir()'s by-hand pre-c...
CVE-2026-89790				0.002		In the Linux kernel, the following vulnerability has been resolved: ipv6: avoid divide by zero in rt6_multipath_rebalance rt6_multipath_rebalance() calculates the total eligible nexthop weight in one pass and programs upper bounds in a second pass. Since RTM_NEWROUTE is RTNL-free, a concurrent ignore_routes_with_linkdown update can make the first pass return zero while the second sees an eligible nexthop, causin...
CVE-2026-89794						In the Linux kernel, the following vulnerability has been resolved: ksmbd: zero pipe read compound padding Compound response handling extends the last response iov to an eight-byte boundary. smb2_read_pipe() allocates only the payload size, so the alignment padding can expose up to seven bytes of uninitialized kernel heap memory. Allocate the aligned size and clear the unused tail before pinning the response b...
CVE-2026-89796						In the Linux kernel, the following vulnerability has been resolved: mm/damon/core: avoid infinite kdamond_merge_regions() internal loop Patch series "mm/damon: unurgent fixes for infinite loop, NULL de-ref and races", v1.1. Sashiko found a few issues in DAMON that could cause infinite loop, NULL dereference and monitoring results degradation. The first two sounds scary but the infinite loop happens only under ...
CVE-2026-89797						In the Linux kernel, the following vulnerability has been resolved: power: supply: ab8500_fg: fix use-after-free on remove ab8500_fg_remove() destroys the driver workqueue while the threaded interrupt handlers are still armed; they are devm-managed and freed only after ->remove() returns, so a handler that fires in that window queues work on the freed workqueue. Tear the workqueue down through devm instead, reg...
CVE-2026-89798						In the Linux kernel, the following vulnerability has been resolved: rpcrdma: arm rn_done before publishing the notification rpcrdma_rn_register() inserts @rn into rd_xa with xa_alloc() before storing the caller's callback in rn->rn_done. The xarray makes @rn reachable to rpcrdma_remove_one(), which walks rd_xa and invokes rn->rn_done(rn) for every registered notification. A device removal that races a fresh regi...
CVE-2026-89800						In the Linux kernel, the following vulnerability has been resolved: drm/nouveau/uvmm: clear the dirty flag when unwinding an OP_UNMAP_SPARSE A successful OP_UNMAP_SPARSE marks its region dirty with nouveau_uvma_region_dirty() and defers the teardown to nouveau_uvmm_bind_job_cleanup(); it does not remove the region from uvmm->region_mt. If a later op in the job fails, the unwind path never clears reg->dirty (set...
CVE-2026-89802						In the Linux kernel, the following vulnerability has been resolved: drm/nouveau/uvmm: fix NULL deref unwinding an OP_MAP_SPARSE op Each bind_job_op is zeroed by kzalloc_obj() in bind_job_op_from_uop(), and the OP_MAP_SPARSE case in nouveau_uvmm_bind_job_submit() only creates a region, so op->ops stays NULL for a successfully processed sparse map. If a later op in the same job fails, the reverse unwind loop revi...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89807						In the Linux kernel, the following vulnerability has been resolved: drm/amdkfd: guard against NULL restore_mqd in CRIU queue restore Both create_queue_cpsch() and create_queue_nocpsch() unconditionally call mqd_mgr->restore_mqd() when a CRIU restore is in progress (qd != NULL), with no NULL guard. On any system where restore_mqd is not implemented for the given queue type, a user holding CAP_CHECKPOINT_RESTORE c...
CVE-2026-89809						In the Linux kernel, the following vulnerability has been resolved: drm/amdkfd: fix scope of mqd_mgr dereference in pqm_debugfs_mqds Reading /sys/kernel/debug/kfd/mqds while a process holds an active KFD queue triggers a NULL pointer dereference because the for loop that calls mqd_mgr->debugfs_show_mqd() is incorrectly placed outside the if (pqm->q) block that initializes mqd_mgr. The queue list can contain ent...
CVE-2026-89812						In the Linux kernel, the following vulnerability has been resolved: drm/amdgpu: force complete the MES ring fences on reset The MES scheduler ring has no drm scheduler (no_scheduler = true), so it is skipped by the force-completion loop in amdgpu_device_pre_asic_reset(). It uses a polling fence whose hw value lives in wb (GTT) memory and survives a MODE1 reset, while fence_drv.sync_seq keeps advancing for every ...
CVE-2026-89813						In the Linux kernel, the following vulnerability has been resolved: drm/amdgpu: force complete the KIQ ring fences on reset Like the MES scheduler ring, the KIQ ring sets no_scheduler = true and uses a polling fence, so it is skipped by the force-completion loop in amdgpu_device_pre_asic_reset(). Its hw fence value lives in wb (GTT) memory and survives a MODE1 reset while fence_drv.sync_seq keeps advancing, so a...
CVE-2026-89816						In the Linux kernel, the following vulnerability has been resolved: drm: Fix drm_crtc_commit leak if signaled when PAGE_FLIP_EVENT is used Commit 1c6ceeee6ebb ("drm/atomic: Fix memleak on ERESTARTSYS during non-blocking commits") fixed a very similar issue when the event was allocated by drm_atomic_helper_setup_commit() itself. However, if the event is allocated in prepare_signaling(), it will also be set to NU...
CVE-2026-89817						In the Linux kernel, the following vulnerability has been resolved: drm/gud: NUL-terminate TV mode names read from the device gud_connector_add_tv_mode() reads a buffer of fixed-size mode names from the USB device and passes pointers into it to drm_mode_create_tv_properties_legacy(), which calls strlen() on each one. Nothing guarantees the device NUL-terminates a name, so strlen() can run past the end of a slot ...
CVE-2026-89820						In the Linux kernel, the following vulnerability has been resolved: drm/amd/display: fix dc_lock leak on GPU reset error paths On GPU reset, dm_suspend() takes dc_lock and leaves it for dm_resume() to drop. If amdgpu_dm_commit_zero_streams() or dm_dmub_hw_init() fails, the function returns with the lock still held. The matching resume path is then skipped, so every later dc_lock take hangs. Release the cached D...
CVE-2026-89821						In the Linux kernel, the following vulnerability has been resolved: drm/amd/display: avoid divide-by-zero in __is_lut_linear() __is_lut_linear() computes the expected value of each entry with expected = i * MAX_DRM_LUT_VALUE / (size - 1); If it is ever called with a single-entry LUT, size - 1 is zero and the kernel takes a divide error (#DE). A LUT with fewer than two entries cannot describe a linear mapping ...
CVE-2026-89822						In the Linux kernel, the following vulnerability has been resolved: drm/i915: Guard against NULL driver_data in i915_pci_probe() pci_match_device() can return the dummy pci_device_id_any entry when a device is force-bound via sysfs driver_override, in which case ->driver_data is unset (NULL). i915_pci_probe() casts it to struct intel_device_info * unconditionally and dereferences intel_info->require_force_probe,...
CVE-2026-89824						In the Linux kernel, the following vulnerability has been resolved: drm/panel-edp: fix i2c adapter leak on probe failure Make sure to drop the i2c adapter reference on probe failure (e.g. probe deferral) and on driver unbind also if a devicetree redundantly uses the 'ddc-i2c-bus' property to point to the aux ddc bus.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89827						In the Linux kernel, the following vulnerability has been resolved: drm/amdgpu: avoid force-completing uninitialized UVD rings uvd_v7_0_sw_init() does not initialize the UVD decode ring for an SR-IOV VF. However, amdgpu_uvd_resume() unconditionally force-completes the decode ring when restoring its fence sequence. Skip fence completion when the fence driver is not initialized.
CVE-2026-89828						In the Linux kernel, the following vulnerability has been resolved: drm/amdgpu: Fix init ordering in amdgpu_vram_mgr_init() drmm_cgroup_register_region() is called before INIT_LIST_HEAD() and gpu_buddy_init() in amdgpu_vram_mgr_init(). If it fails, the function returns early and bypasses those initializations. Since adev->mman.initialized is set to true before amdgpu_vram_mgr_init() is called, a failure trigger...
CVE-2026-89830						In the Linux kernel, the following vulnerability has been resolved: f2fs: fix valid block count leak on data block allocation failure In __allocate_data_block(), when allocating a new data block (dn->data_blkaddr == NULL_ADDR), inc_valid_block_count() is called first to increment total_valid_block_count and i_blocks. If the subsequent f2fs_allocate_data_block() fails, the function returns the error directly with...
CVE-2026-89831						In the Linux kernel, the following vulnerability has been resolved: f2fs: protect critical_task_priority updates with s_umount The sysfs store path already takes s_umount for GC thread control entries, and ckpt_thread_ioprio is covered as well. critical_task_priority also updates checkpoint or GC kthread scheduling state, but it is not covered by that serialization. It can race with remount or teardown paths th...
CVE-2026-89833						In the Linux kernel, the following vulnerability has been resolved: f2fs: fix to avoid potential deadlock in f2fs_fsync_node_pages() There is potential deadlock in race condition: Thread A Thread B - fsync - f2fs_do_sync_file - f2fs_fsync_node_pages - last_fsync_dnode - folio_get(last_folio) - f2fs_setattr - f2fs_truncate - f2fs_truncate_blocks - f2fs_do_truncate_blocks ...
CVE-2026-89834						In the Linux kernel, the following vulnerability has been resolved: f2fs: fix to migrate all curseg types during free_segment_range In free_segment_range(), the curseg evacuation loop only iterates up to NR_CURSEG_PERSIST_TYPE (0..5), missing non-persistent in-memory curseg types such as CURSEG_COLD_DATA_PINNED and CURSEG_ALL_DATA_ATGC. Even though these in-memory curseg types are not saved in the on-disk check...
CVE-2026-89835						In the Linux kernel, the following vulnerability has been resolved: f2fs: avoid NULL checkpoint thread access in sysfs checkpoint_merge can be enabled even when no checkpoint merge thread is running. A read-only mount is one case: f2fs does not start f2fs_issue_ckpt there, but ckpt_thread_ioprio is still writable through sysfs. The ckpt_thread_ioprio store path updates the saved ioprio value and, when checkpoint...
CVE-2026-89837						In the Linux kernel, the following vulnerability has been resolved: f2fs: fix dentry folio leak in find_in_level find_in_level() gets a dentry folio with f2fs_find_data_folio() before calling find_in_block(). If find_in_block() returns an error, the function stores the error in res_folio and breaks out of the loop without dropping the dentry folio. This leaks the folio reference on the find_in_block() error pa...
CVE-2026-89839						In the Linux kernel, the following vulnerability has been resolved: f2fs: use the mount idmap for the owner check in f2fs_xattr_advise_set() f2fs_xattr_advise_set() calls inode_owner_or_capable() with &nop_mnt_idmap before allowing the "system.advise" xattr to be set, instead of the idmap that the VFS passes to the ->set() handler. f2fs supports idmapped mounts, so on such a mount this checks the caller's fsuid...
CVE-2026-89842						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Skip NVMe LS reject IOCB when FW not started qla_nvme_xmt_ls_rsp() bails out to the out: label when firmware is not started (!ha->flags.fw_started), but the out: path unconditionally calls qla_nvme_ls_reject_iocb(), which ends in qla2x00_start_ioCBS() and an unconditional doorbell write to the request queue in-pointer register. Th...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89843						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Zero-init bsg stack buffers to avoid info leak Several bsg handlers stage their request/reply in an uninitialized 256-byte on-stack buffer (uint8_t bsg[DMA_POOL_SIZE]) and fill it via sg_copy_to_buffer(), which only copies as many bytes as the user-supplied request payload. When the request is shorter than the structure, the remain...
CVE-2026-89845						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Avoid req_q_map double-read in qla2x00_error_entry() qla2x00_error_entry() reads ha->req_q_map[que] twice: once for the NULL check and again when assigning it to req. The map slot is cleared by qla25xx_free_req_que() (ha->req_q_map[que_id] = NULL under mq_lock) during queue teardown, while the response-queue interrupt that drives ...
CVE-2026-89850						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Don't query firmware state while chip is down qla2x00_fw_state_show() initializes rval to QLA_FUNCTION_FAILED and jumps to the out: label when the chip is down or EEH is busy. The out: block then re-issued qla2x00_get_firmware_state() because rval != QLA_SUCCESS, defeating the chip-down/EEH-busy guards and issuing a mailbox comman...
CVE-2026-89851						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Fix FCE trace enable parsing in debugfs qla2x00_dfs_fce_write() called kstrtoul() with a NULL result pointer, so a successful parse would dereference NULL and oops. Worse, the int return value (0 on success, negative errno on failure) was assigned to the unsigned long enable flag, inverting the intended logic: a valid number was t...
CVE-2026-89852						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Zero mailbox struct in qla2x00_get_firmware_state() The mbx_cmd_t is allocated on the stack but left uninitialized. qla2x00_mailbox_command() has several early-return paths (PCI permanent failure, device failed, EEH busy, ISP abort pending, mailbox access timeout, purge mbox) that return without writing the input mailbox registers...
CVE-2026-89853						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Fix FCE trace use-after-free during firmware dump qla2x00_free_fce_trace() freed and cleared ha->fce while holding only fce_mutex. The firmware-dump consumers qla27xx_fwdt_entry_t264() and qla25xx_copy_fce() read ha->fce (NULL check followed by a copy of the buffer) under hardware_lock and never take fce_mutex. A debugfs FCE disab...
CVE-2026-89855						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Serialize flash version read in reset handler The "update cache versions without reset" sysfs reset operation (0x20261) calls get_flash_version(), which reads hardware flash registers, without holding ha->optrom_mutex. The VPD update path serializes the same call under optrom_mutex, so this reset path can interleave its flash regi...
CVE-2026-89858						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Bound image count in qla2x00_update_fru_versions() qla2x00_update_fru_versions() copies the user-supplied BSG request into a fixed 256-byte stack buffer (bsg[DMA_POOL_SIZE]) and then iterates list->count times over the qla_image_version array embedded in that buffer, advancing the image pointer each iteration. count is taken direc...
CVE-2026-89859						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Zero dport diagnostics buffer to avoid info leak qla2x00_do_dport_diagnostics() allocates the qla_dport_diag response buffer with kcalloc_obj() (non-zeroing) and, on success, copies the full sizeof(*dd) back to user space via sg_copy_from_buffer(). The inbound sg_copy_to_buffer() only fills as many bytes as the user request payloa...
CVE-2026-89862						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Fix BSG job leak on validate flash image error path qla28xx_validate_flash_image() returns QLA_SUCCESS (0) unconditionally, telling the FC BSG transport (fc_bsg_host_dispatch()) that the driver owns and will complete the request. But bsg_job_done() is guarded by "if (!rval)", so on the error path (rval == -EINVAL) neither the driv...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89864						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Bound i2c->length in I2C bsg handlers struct qla_i2c_access carries a 16-bit length field alongside a fixed 64-byte buffer: struct qla_i2c_access { uint16_t device, offset, option, length; uint8_t buffer[0x40]; } __packed; qla2x00_write_i2c() and qla2x00_read_i2c() use the user-supplied i2c->length without any bounds chec...
CVE-2026-89865						In the Linux kernel, the following vulnerability has been resolved: scsi: qla2xxx: Zero SFP DMA buffer in FRU/I2C bsg handlers The FRU and I2C bsg handlers stage their transfer in a DMA_POOL_SIZE (256-byte) bounce buffer obtained from dma_pool_alloc(), which does not zero the allocation. They initialize only a few leading bytes before handing the buffer to qla2x00_write_sfp(). qla2x00_write_sfp() can override t...
CVE-2026-89866						In the Linux kernel, the following vulnerability has been resolved: media: chips-media: wave5: Resume device before setting EOS flag Setting the EOS flag talks to the firmware via send_firmware_command(), which accesses VPU registers. Both the STREAMOFF path (wave5_vpu_dec_job_abort()) and the V4L2_DEC_CMD_STOP path (wave5_vpu_dec_stop()) can run while the device is runtime suspended, so those register accesses ...
CVE-2026-89867						In the Linux kernel, the following vulnerability has been resolved: media: chips-media: wave5: Defer job_finish() only when a DEC_PIC was queued Decoder instances sharing a VPU also share one v4l2_m2m job slot, released when the running context calls v4l2_m2m_job_finish(). While draining, device_run() defers job_finish() once EOS is sent (sent_eos), expecting a later finish_decode() (from a DEC_PIC completion IR...
CVE-2026-89868						In the Linux kernel, the following vulnerability has been resolved: media: chips-media: wave5: Add timeout while stop_streaming When stop_streaming is called, an infinite loop may occur in some cases. Add a bounded poll of the queue status: loop until the queues drain, sleeping briefly between polls, and bail out once VPU_DEC_STOP_TIMEOUT elapses.
CVE-2026-89869						In the Linux kernel, the following vulnerability has been resolved: media: qcom: iris: use disable_irq() during power-off The IRQ is registered as a threaded IRQ. Using disable_irq_nosync() in iris_vpu_power_off() does not wait for an already queued threaded IRQ handler to complete before returning. As a result, a threaded IRQ handler may still run after the VPU has been powered down and access hardware regist...
CVE-2026-89871						In the Linux kernel, the following vulnerability has been resolved: media: video-i2c: fix kthread error pointer left in kthread_vid_cap on failure kthread_run() returns an ERR_PTR on failure, not NULL. When start_streaming() fails, data->kthread_vid_cap is left holding this error pointer instead of being cleared. This causes two subsequent bugs: 1. A future call to start_streaming() sees a non-NULL kthread_vid_...
CVE-2026-89872						In the Linux kernel, the following vulnerability has been resolved: media: v4l2-fwnode: Fix fwnode leak in v4l2_fwnode_parse_link In v4l2_fwnode_parse_link(), the remote endpoint fwnode reference is acquired using fwnode_graph_get_remote_endpoint(). This reference is properly released in the error paths, but it is leaked on the success path. Add the missing fwnode_handle_put() before returning 0 to prevent the ...
CVE-2026-89874						In the Linux kernel, the following vulnerability has been resolved: media: v4l2-async: avoid deleting unlinked ASC entry on link error v4l2_async_match_notify() creates ancillary media links before adding asc->asc_subdev_entry to sd->asc_list. If ancillary link creation fails, the function jumps to err_call_unbind while asc_subdev_entry has not been linked yet. Async connections are zero-allocated, so the list ...
CVE-2026-89876						In the Linux kernel, the following vulnerability has been resolved: media: tda18250: fix possible integer overflow Integer overflow may occur, when variable exp equals to zero. Result of shift 1 << (exp - 1) may then leads to undefined behavior.

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89878						In the Linux kernel, the following vulnerability has been resolved: media: s2255: check firmware size before reading trailing marker s2255_probe() reads a 4-byte marker and version from the last 8 bytes of the firmware blob (fw->data[fw_size - 8] and [fw_size - 4]). If the firmware file is shorter than 8 bytes, fw_size - 8 underflows and the access reads out of bounds. Validate the firmware size before indexing.
CVE-2026-89879						In the Linux kernel, the following vulnerability has been resolved: media: s2255: bound JPEG frame size before copying into the buffer s2255_fillbuff() memcpy()s vc->jpg_size bytes of a captured JPEG/MJPEG frame into the vb2 plane. vc->jpg_size is taken verbatim from the S2255_MARKER_FRAME header the device sends (pdword[4] in save_frame()) and, unlike the frame payload length just above it, is never bounded: ...
CVE-2026-89881						In the Linux kernel, the following vulnerability has been resolved: media: rtl2832_sdr: use vb2_video_unregister_device() on remove to fix DMA leak rtl2832_sdr_remove() runs on USB disconnect and clears dev->udev to NULL before any pending streaming teardown has run. When user space later closes its file descriptor, vb2 calls rtl2832_sdr_stop_streaming() which in turn calls rtl2832_sdr_free_stream_bufs(). That h...
CVE-2026-89884						In the Linux kernel, the following vulnerability has been resolved: media: platform: mtk-mdp3: fix NULL deref on failed SCP lookup Add the missing sanity check after looking up the SCP to avoid dereferencing a NULL-pointer in case its driver has not yet been bound.
CVE-2026-89886						In the Linux kernel, the following vulnerability has been resolved: media: intel/ipu6: fix async notifier cleanup leak on parse error isys_notifier_init() calls v4l2_async_nf_init() and then adds fwnode remote subdevs in a loop with v4l2_async_nf_add_fwnode_remote(). If an endpoint parse or add fails partway through the loop, it jumps to err_parse and returns without calling v4l2_async_nf_cleanup(), leaking ever...
CVE-2026-89889						In the Linux kernel, the following vulnerability has been resolved: media: i2c: imx415: Release runtime PM reference on VBLANK error The VBLANK path returned immediately when programming VMAX failed after pm_runtime_get_if_in_use() had taken a runtime PM reference. Break out of the switch instead so the common pm_runtime_put() path is used.
CVE-2026-89891						In the Linux kernel, the following vulnerability has been resolved: media: em28xx: fix use-after-free of dev_next->devlist on disconnect When a device with has_dual_ts=1 is probed and the is_audio_only path is taken, both dev and dev->dev_next are added to the global em28xx_devlist via em28xx_init_extension(). However, during disconnect, em28xx_close_extension(dev) only calls list_del(&dev->devlist), leaving dev...
CVE-2026-89892						In the Linux kernel, the following vulnerability has been resolved: media: em28xx: defer audio-only extension registration The audio-only path registers extensions while probing the primary device. For a dual-TS board, this happens before dev_next is created. The duplicate device inherits is_audio_only and is then independently inserted into em28xx_devlist. The list is intended to contain only primary devices: ...
CVE-2026-89895						In the Linux kernel, the following vulnerability has been resolved: media: cobalt: Avoid freeing ALSA private data twice snd_cobalt_card_create() stores cobsc in sc->private_data and installs snd_cobalt_card_private_free() as sc->private_free. From that point, snd_card_free(sc) releases cobsc through the ALSA card cleanup path. If cobalt_alsa_init() fails after snd_cobalt_card_create(), the err_exit_free path c...
CVE-2026-89896						In the Linux kernel, the following vulnerability has been resolved: media: cedrus: fix memory leak in cedrus_init_ctrls() In cedrus_init_ctrls(), the V4L2 control handler is initialized before allocating memory for ctx->ctrls. If this allocation fails, the function returns -ENOMEM without freeing the previously allocated handler resources, leading to a memory leak. Fix this by calling v4l2_ctrl_handler_free() o...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89900						In the Linux kernel, the following vulnerability has been resolved: media: cec: core: Fix kmemleak due to missed rc_free_device() call The commit dccc0c3ddf8f ("media: rc: fix race between unregister and urb/irq callbacks") removed the implicit call to rc_free_device() from rc_unregister_device(). However, the commit missed to remove the NULL assignment of adap->rc that is now causing rc_free_device() to never b...
CVE-2026-89901						In the Linux kernel, the following vulnerability has been resolved: media: airspy: use vb2_video_unregister_device() on disconnect to fix NULL deref airspy_disconnect() clears s->udev under v4l2_lock, but airspy_stop_streaming() unconditionally calls airspy_ctrl_msg() and airspy_free_stream_bufs() afterwards. If a streaming user closes the device after disconnect, stop_streaming() runs and dereferences the NULL ...
CVE-2026-89905						In the Linux kernel, the following vulnerability has been resolved: LoongArch: BPF: Move arena register slot below TCC context Currently, the stack layout places the optional arena register slot above the tail call counter context. When arena_vm_start is dynamically enabled, it shifts the relative offset of the tcc_ptr slot within the stack frame, causing hardcoded tracking macros to mismatch and leading to memo...
CVE-2026-89909						In the Linux kernel, the following vulnerability has been resolved: LoongArch: KVM: Free init resources if kvm_init() fails kvm_loongarch_init() calls kvm_loongarch_env_init() to allocate the per-CPU kvm_context (vmcs) and kvm_loongarch_ops and to register the perf callbacks, and then calls kvm_init(). If kvm_init() fails its result is returned directly, but since module_init() does not run the module_exit() stu...
CVE-2026-89917						In the Linux kernel, the following vulnerability has been resolved: KVM: arm64: Handle VNCR TLB invalidation race with vcpu_put() VNCR unmapping While VNCR TLB invalidation always occurs under the MMU lock, vcpu_put() doesn't, while it unmaps the VNCR page. The problem is that the invalidation evaluates vncr_tlb::cpu to decide whether an unmapping needs to take place (cpu != -1) before performing it. On the oth...
CVE-2026-89921						In the Linux kernel, the following vulnerability has been resolved: KVM: s390: Zero initialize data structures for inject_pfault_token __kvm_inject_pfault_token() only sets .type and .u.ext.ext_params2 of the on-stack struct kvm_s390_irq but the full ext substructure is copied into the cpu local variable on inject. ext_params and pad contain stale stack values. Interrupt delivery only uses ext_params2, so nothi...
CVE-2026-89923						In the Linux kernel, the following vulnerability has been resolved: KVM: s390: Free guest debug data on vcpu destroy kvm_s390_clear_bp_data() is only called from kvm_arch_vcpu_ioctl_set_guest_debug(), i.e. when user space changes or disables debugging. A vCPU that is destroyed while hardware breakpoints are still armed - the normal case when the VMM just exits or crashes - leaks hw_bp_info, hw_wp_info and all ol...
CVE-2026-89924						In the Linux kernel, the following vulnerability has been resolved: KVM: s390: Fix old_data leak in guest debug error path __import_wp_info() allocates a per-watchpoint old_data buffer to back up the original guest memory contents. If a later watchpoint of the same KVM_SET_GUEST_DEBUG request fails to import, kvm_s390_import_bp_data() jumps to the error label, which frees the wp_info array but not the old_data b...
CVE-2026-89925						In the Linux kernel, the following vulnerability has been resolved: KVM: s390: Fix memory leak in guest debug handling bp_data is freed only for the error case by kfree(bp_data). Every successful KVM_SET_GUEST_DEBUG will leak bp_data.
CVE-2026-89926						In the Linux kernel, the following vulnerability has been resolved: KVM: s390: Fix length check __import_wp_info() struct kvm_hw_breakpoint::len is a __u64 that is fully controlled by user space. This is then assigned to wp_info->len, which is an int. The bounds check is done on the truncated value while the allocation uses the untruncated one: wp_info->len = bp_data->len; [...] if (wp_info->len < 0 wp_in...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89931						In the Linux kernel, the following vulnerability has been resolved: KVM: nVMX: Ensure KVM_REQ_GET_NESTED_STATE_PAGES is cleared on VM-Exit Always check and clear KVM_REQ_GET_NESTED_STATE_PAGES when emulating a nested VM-Exit to ensure the request is cleared, even when KVM was built with CONFIG_KVM_HYPERV=n, as KVM subtly relies on the "check" to clear the flag and thus avoid double-mapping the vmcs12 pages, e.g....
CVE-2026-89933						In the Linux kernel, the following vulnerability has been resolved: iio: pressure: dps310: fix NULL pointer dereference on ACPI probe When the device is enumerated through its ACPI HID (IFX3100), i2c_client_get_device_id() returns NULL: the ACPI-derived client name does not match the driver's i2c_device_id table. dps310_probe() then dereferences that NULL pointer in "iio->name = id->name" and crashes the kernel ...
CVE-2026-89934						In the Linux kernel, the following vulnerability has been resolved: iio: light: ltrf216a: fix runtime PM reference leak in error path ltrf216a_get_lux() acquires a runtime PM reference by calling ltrf216a_set_power_state(data, true). However, if ltrf216a_read_data() fails, the function returns immediately without dropping the reference. This leaves the runtime PM usage count unbalanced, preventing the device fr...
CVE-2026-89935						In the Linux kernel, the following vulnerability has been resolved: iio: light: apds9306: fix PM reference leak in apds9306_read_data() apds9306_read_data() calls pm_runtime_resume_and_get() but several error paths return directly without calling pm_runtime_put_autosuspend(), leaking the runtime PM reference and preventing the device from autosuspending. Use PM_RUNTIME_ACQUIRE_AUTOSUSPEND() and PM_RUNTIME_ACQUI...
CVE-2026-89936						In the Linux kernel, the following vulnerability has been resolved: iio: dac: m62332: Fix regulator reference count imbalance m62332_set_value() enables the Vcc regulator on every write of a non-zero value and disables it on every write of zero, without tracking the channel's current state. Because the regulator is reference counted, changing a channel directly from one non-zero value to another enables it more ...
CVE-2026-89937						In the Linux kernel, the following vulnerability has been resolved: iio: chemical: sgp30: Handle IAQ thread creation failure kthread_run() can fail and return an error pointer, but sgp_probe() stores it and returns success, so the device is registered without its IAQ thread and sgp_remove() later passes the error pointer to kthread_stop(). Return the error from probe instead.
CVE-2026-89939						In the Linux kernel, the following vulnerability has been resolved: iio: chemical: atlas-sensor: fix PM reference leak in buffer postenable atlas_buffer_postenable() acquires a runtime PM reference with pm_runtime_resume_and_get() but returns the result of atlas_set_interrupt() directly. If atlas_set_interrupt() fails, the runtime PM reference is leaked and the device can never autosuspend. Add pm_runtime_put_a...
CVE-2026-89944						In the Linux kernel, the following vulnerability has been resolved: ASoC: hdac_hda: Fix hlink refcount leak on component registration failure hdac_hda_dev_probe() gets the HDA link with snd_hdac_ext_bus_link_get() before registering the ASoC component. If component registration fails, the function returns without dropping the link reference. Always call snd_hdac_ext_bus_link_put() after the registration attempt...
CVE-2026-89945						In the Linux kernel, the following vulnerability has been resolved: ASoC: cs35l34: drain threaded IRQ before runtime suspend cs35l34_runtime_suspend() currently switches the codec into regcache_cache_only(true), asserts reset low, and powers the device off without first quiescing the threaded IRQ registered by devm_request_threaded_irq(). That leaves a window where cs35l34_irq_thread() can still run after suspen...
CVE-2026-89946						In the Linux kernel, the following vulnerability has been resolved: ASoC: cs35l33: drain threaded IRQ before runtime suspend cs35l33_runtime_suspend() currently switches the codec into regcache_cache_only(true) and powers it down without first quiescing the threaded IRQ registered by devm_request_threaded_irq(). That leaves a window where cs35l33_irq_thread() can still run after suspend has closed off live regis...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89948						In the Linux kernel, the following vulnerability has been resolved: batman-adv: bla: fix freeing of claims on meshif deletion When the mesh interface is getting deleted, then batadv_bla_del_backbone_claims() (via batadv_bla_purge_backbone_gw()) could make sure that all claims gets removed. But this function is only executed when bat_priv->bla.claim_hash is not NULL. And since batadv_bla_free() is always setting ...
CVE-2026-89949						In the Linux kernel, the following vulnerability has been resolved: batman-adv: dat: avoid unaligned fault in IP extraction Independent of the alignment of the ARP packet in the SKB, either the batadv_arp_ip_src or the batadv_arp_ip_dst will have an unaligned access (on HW without native unaligned read support). Use get_unaligned() to handle this properly on all architectures.
CVE-2026-89950						In the Linux kernel, the following vulnerability has been resolved: batman-adv: mcast: linearize skbuff for packet generation batadv_mcast_forw_packet() and batadv_mcast_forw_scrape() is not only called (indirectly) by the unsharing+linearizing batadv_recv_mcast_packet() handler. When it is called (indirectly) by batadv_mcast_forw_mcsend() then it will be unshared but not linearized. The SKB_LINEAR_ASSERT() can ...
CVE-2026-89952						In the Linux kernel, the following vulnerability has been resolved: mtd: rawnand: validate ONFI extended parameter page sections nand_flash_detect_ext_param_page() allocates the length declared by the ONFI parameter page, then treats the data as a fixed header followed by variable-length sections. It reads that header and advances over sections without first proving that the fixed page and each current section f...
CVE-2026-89953						In the Linux kernel, the following vulnerability has been resolved: mtd: mtdoops: free page bitmap when the backing MTD is removed mtdoops_notify_add() allocates oops_page_used when the configured MTD device is registered. mtdoops_notify_remove() detaches from that device but leaves the bitmap allocated. If the same MTD device is later registered again, the add path allocates a new bitmap and overwrites the ol...
CVE-2026-89955						In the Linux kernel, the following vulnerability has been resolved: s390/vfio-ap: Fix NULL deref in status_show() during queue probe When vfio_ap_mdev_probe_queue() creates the sysfs attribute group, the queue's driver data has not yet been set. A concurrent read of the 'status' attribute can therefore call dev_get_drvdata() and get NULL, which is then passed directly to vfio_ap_mdev_for_queue() where q->apqn is...
CVE-2026-89956						In the Linux kernel, the following vulnerability has been resolved: s390/vfio-ap: Fix missing lock required to access list of ap_matrix_mdev objects In order to traverse or add/remove ap_matrix_mdev objects in the matrix_dev->mdev_list, the matrix_dev->guests_lock mutex must be held. There are two functions that access the list without holding the mutex: vfio_ap_mdev_probe function ~~~~~ T...
CVE-2026-89958						In the Linux kernel, the following vulnerability has been resolved: s390/vfio-ap: Fix dereference matrix_mdev->kvm without checking for NULL The ap_driver structure has two fields which are function pointers to callbacks: *.on_config_changed: called at the start of the AP bus scan function to notify the device driver that the host AP configuration has changed and the...
CVE-2026-89962						In the Linux kernel, the following vulnerability has been resolved: powerpc/kexec_file: Prevent kexec range truncation Sashiko AI review pointed out the following issue. The __merge_memory_ranges() function incorrectly handles overlapping memory ranges when merging them. Although sort_memory_ranges() sorts all ranges by their start address in ascending order beforehand, the merge logic remains defective in two ...
CVE-2026-89963						In the Linux kernel, the following vulnerability has been resolved: powerpc/kexec_file: Fix null-ptr-def in extra size calculation A static Sashiko AI review identified a potential NULL pointer dereference in kexec_extra_fdt_size_ppc64(). On platforms without any reserved memory regions, get_reserved_memory_ranges() can return 0 while leaving 'rmem' unallocated as NULL. Passing it directly leads to a kernel pan...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89964						In the Linux kernel, the following vulnerability has been resolved: parisc: eisa: Fix infinite loop when parsing invalid IRQ value When an invalid value is passed via the "eisa_irq_edge=" kernel command line parameter (e.g. "eisa_irq_edge=16,5"), eisa_irq_setup() prints an error message and continues without advancing the current position. As a result the same invalid value is parsed again and again, causing an...
CVE-2026-89966						In the Linux kernel, the following vulnerability has been resolved: mm/hugetlb_cma: fix null nodemask dereference in hugetlb_cma_alloc_frozen_folio alloc_buddy_hugetlb_folio_with_mpol() can pass a NULL nodemask to alloc_fresh_hugetlb_folio() as a fallback to allocate from all nodes. If order is gigantic, alloc_fresh_hugetlb_folio() propagates the NULL nodemask down to hugetlb_cma_alloc_frozen_folio() via alloc_...
CVE-2026-89975						In the Linux kernel, the following vulnerability has been resolved: nvme-fabrics: fix DHCHAP secret leak on parse failure nvme_parse_options() duplicates dhchap_secret and dhchap_ctrl_secret with match_strdup() before validating the DHHC-1: representation. If validation fails, the parser returns -EINVAL before the temporary string in p is assigned to opts->dhchap_secret or opts->dhchap_ctrl_secret. nvme_create_...
CVE-2026-89976						In the Linux kernel, the following vulnerability has been resolved: accel/ethosu: fix job completion fence cleanup ethosu_jocctl_submit_job() allocates done_fence before validating buffer handles. Errors after allocation call ethosu_job_err_cleanup(), which frees the job but leaks the uninitialized fence. A scheduler dependency error also lets ethosu_job_run() return before dma_fence_init(). Normal cleanup then ...
CVE-2026-89977						In the Linux kernel, the following vulnerability has been resolved: accel/ethosu: check MMIO mapping errors in probe devm_platform_ioremap_resource() returns an error pointer when the register resource cannot be mapped. ethosu_probe() stores it and continues until initialization dereferences it through MMIO accessors. Return the mapping error before initializing the device.
CVE-2026-89978						In the Linux kernel, the following vulnerability has been resolved: accel/amdxdna: return early from a zero-length flush SYNC_BO does not constrain its size, so a request for zero bytes reaches drm_cflush_virt_range(), which ends with an unconditional clflushopt(end - 1). For an empty range that is the byte before the mapping, and abo->mem.kva comes from vmap(), so the access lands in the guard page below the v...
CVE-2026-89981						In the Linux kernel, the following vulnerability has been resolved: arm64: Don't read GMID_EL1 when MTE is disabled __cpuinfo_store_cpu() gates the GMID_EL1 read on the raw ID_AA64PFR1_EL1, so it reads the register even when the kernel has disabled MTE (CONFIG_ARM64_MTE=n or arm64.nomte). KVM sets HCR_EL2.TID5 in that case, and pKVM injects an UNDEF the host cannot handle: Internal error: Oops - Undefined ins...
CVE-2026-89982						In the Linux kernel, the following vulnerability has been resolved: i2c: mux: Fix channel node leak on adapter add failure i2c_mux_add_adapter() takes a reference to the Device Tree channel node before registering the new adapter. If adapter registration fails, the error path frees the private data without dropping that reference. Release the channel node before freeing the private data.
CVE-2026-89983						In the Linux kernel, the following vulnerability has been resolved: i2c: core: fix debugfs UAF on adapter removal i2c_del_adapter() frees the adapter's debugfs directory before it unregisters the adapter device, but the new_device sysfs attribute stays writable until device_del(). A write racing with removal still reaches i2c_device_probe(), which passes the freed adap->debugfs to debugfs_create_dir() as the new...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-89984						In the Linux kernel, the following vulnerability has been resolved: perf/x86/intel: Fix kernel address leakages in LBR stack Before Arch LBR gained CPL filtering support, a user-only branch stack could still contain kernel addresses. As a result, kernel branch records may be exposed to user space even when PERF_SAMPLE_BRANCH_USER is requested. For example, on Intel Tiger Lake, the following command can still re...
CVE-2026-89987						In the Linux kernel, the following vulnerability has been resolved: mm/huge_memory: transfer the pmd dirty bit to the folio on zap zap_huge_pmd_folio() propagates the pmd young bit to the folio for the file case, but not the dirty bit. The pte path does propagate it, in zap_present_folio_ptes() and so does the pmd split path, in __split_huge_pmd_locked(). For most file mappings the omission is harmless, becaus...
CVE-2026-89989						In the Linux kernel, the following vulnerability has been resolved: ima: Check for ERR_PTR from dentry_path() in validate_hash_algo() dentry_path() returns ERR_PTR(-ENAMETOOLONG) when the path exceeds the buffer. validate_hash_algo() passes the result straight to integrity_audit_msg() without checking. ERR_PTR is not NULL, so integrity_audit_message() sees a valid pointer and calls strlen() on it, which faults: ...
CVE-2026-89991						In the Linux kernel, the following vulnerability has been resolved: bpf: Fix infinite loop in pcpu_freelist push with one possible CPU __pcpu_freelist_push() can loop forever when only one CPU is possible and an NMI re-enters pcpu_freelist_push() while the interrupted context holds that CPU's freelist lock. After the current-CPU fast path fails, the fallback loop walks cpu_possible_mask while skipping the curre...
CVE-2026-89993						In the Linux kernel, the following vulnerability has been resolved: dmaengine: dw-edma: Initialize IRQ data before requesting IRQs dw_edma_irq_request() passes struct dw_edma_irq to request_irq() before dw_edma_channel_setup() fills the back pointer. A shared interrupt can therefore enter the handler with dw_irq->dw still NULL, leading to a NULL pointer dereference. Set the back pointer before installing each h...
CVE-2026-89996						In the Linux kernel, the following vulnerability has been resolved: dma-buf: dma-heap: don't publish fd before copy_to_user() succeeds DMA_HEAP_IOCTL_ALLOC allocates a dma-buf and installs an fd into the caller's fd table via dma_buf_fd() -> fd_install() before dma_heap_ioctl() copies the result back to userspace. If the trailing copy_to_user() fails, userspace never learns the fd number, but the fd (and the un...
CVE-2026-90004						In the Linux kernel, the following vulnerability has been resolved: mm/damon/core: handle region split failure in apply_min_nr_regions() damon_apply_min_nr_regions() repeatedly split each region until its size becomes small enough to meet the user-defined low limit of the number of regions. The loop assumes the split operation (damon_split_region_at()) will always succeed and create the new region. But the ope...
CVE-2026-90005						In the Linux kernel, the following vulnerability has been resolved: samples/damon/wsse: handle damon_start() failure Patch series "samples/damon: handle damon_{start,stop}() failures". All DAMON sample modules are not correctly handling failures from damon_start(). Among those, mtier also has an additional problem for handling of damon_stop() failures. wsse and prcl also have a problem in their damon_call() f...
CVE-2026-90006						In the Linux kernel, the following vulnerability has been resolved: samples/damon/mtier: handle damon_stop() failure damon_sample_mtier_stop() assumes its damon_stop() call will always successfully stops the two DAMON contexts. Hence it deallocates the two DAMON contexts after the damon_stop() call. However, if a given context is already stopped, damon_stop() fails and returns an error while letting the DAMON ...
CVE-2026-90015						In the Linux kernel, the following vulnerability has been resolved: xhci: fix lost bounce buffers on TDs spanning several ring segments When a TD reaches a link TRB with data that is not aligned to the endpoint's wMaxPacketSize, xhci_align_td() stages the unalignable tail through the bounce buffer of the ring segment holding that link TRB. xhci_unmap_td_bounce_buffer() later unmaps it and, for IN transfers, copi...

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-90019						In the Linux kernel, the following vulnerability has been resolved: usb: gadget: fix null pointer dereference in usb_put_function_instance() usb_put_function_instance() attempts to dereference fd inside fi struct to get mod in uvc_alloc_inst() error path. However, fd is not allocated until later in try_get_usb_function_instance() after allocating fi in uvc_alloc_inst() and thus guranteed to be null in error path...
CVE-2026-90020						In the Linux kernel, the following vulnerability has been resolved: USB: gadget: fix NULL pointer dereference in gadget_dev_ioctl() gadget_dev_ioctl() reads dev->gadget before acquiring dev->lock, but dev->state is checked after acquiring the lock. Therefore a concurrent bind can change the device state between these operations, which can leave ioctl with a stale NULL gadget pointer and causing a NULL pointer de...
CVE-2026-90021						In the Linux kernel, the following vulnerability has been resolved: usb: gadget: f_midi: initialize work in f_midi_alloc() f_midi_alloc initializes free_ref to 1 and it can only be incremented when a sound card is registered via f_midi_register_card(). f_midi_register_card() is only called in f_midi_bind() which actually performs INIT_WORK. If f_midi_bind() is never run, work is not initialized and the if condit...
CVE-2026-90023						In the Linux kernel, the following vulnerability has been resolved: usb: gadget: f_mass_storage: fix null pointer dereference in fsg_common_set_num_buffers() Previously fsg_num_buffers_validate() was removed as it was not necessary due to Kconfig setting the limits for n from 2 to 256 with default as 2. However, setting the page content in such a way that kstrtou8() reflects n value as either 0 or 1 bypasses the...
CVE-2026-90024						In the Linux kernel, the following vulnerability has been resolved: usb: gadget: midi2: Fix null-pointer dereference in f_midi2_free_ep_reqs A null-pointer dereference occurs in f_midi2_free_ep_reqs() when attempting to clean up an endpoint that was never initialized. When configuring the MIDI 2.0 gadget via configs and setting the block direction to SNDRV_UMP_DIR_INPUT, the initialization of the midi1_ep_out ...
CVE-2026-90028						In the Linux kernel, the following vulnerability has been resolved: usb: typec: hd3ss3220: track VBUS enable state per consumer regulator_is_enabled() reports the aggregate regulator state, not whether this consumer holds an enable reference. If another consumer enables VBUS first, the driver can skip its own regulator_enable() call and later attempt to drop a reference it never acquired, triggering an unbalance...
CVE-2026-90029						In the Linux kernel, the following vulnerability has been resolved: usb: storage: realtek_cr: fix use-after-free on disconnect realtek_cr_destructor() calls timer_delete() before the chip containing the timer is freed. The timer callback may still be running and can rearm itself, resulting in a use-after-free. Use timer_shutdown_sync() to wait for the callback and prevent further rearming. Do this unconditional...
CVE-2026-90031						In the Linux kernel, the following vulnerability has been resolved: usb-storage: ene_ub6250: fix race between scan work and probe ene_ub6250_probe() calls usb_stor_probe2(), which starts the usb-storage infrastructure and schedules the delayed scan work. The driver then calls ene_get_card_type(), which sends an ENE command through ene_send_scsi_cmd() and the usb-storage bulk transfer helpers. Both the delayed ...
CVE-2026-90033						In the Linux kernel, the following vulnerability has been resolved: ALSA: usb-audio: fix OOB write in snd_usbmidi_us122l_output() The snd_usbmidi_us122l_output() picks a count of 2 on anything slower than high speed and never relates it to ep->max_transfer. The URB buffer holds exactly max_transfer bytes, so a device declaring a one byte bulk endpoint takes two bytes from snd_rawmidi_transmit(), and the memset ...
CVE-2026-90034						In the Linux kernel, the following vulnerability has been resolved: usb: image: mdc800: change kcalloc() to kzalloc() Change the kcalloc() calls in usb_mdc800_init() for irq_urb_buffer and download_urb_buffer to kzalloc(), avoiding potential stack leaks if a shorter message is received in mdc800_usb_irq() and mdc800_usb_download_notify()

CVE	CVSS	Sev	KEV	EPSS	Vendor / Product	Description
CVE-2026-90035						In the Linux kernel, the following vulnerability has been resolved: drm/amd/display: fix division by zero in get_estimated_bw() get_estimated_bw() divides by link->dpia_bw_alloc_config.bw_granularity, which is zeroed by reset_bw_alloc_struct() and only populated once DP_TUNNELING_BW_ALLOC_CAP_CHANGED has been handled. link_dp_dpia_handle_bw_alloc_status(), the DPCD interrupt handler, calls get_estimated_bw() wh...
CVE-2026-90039						In the Linux kernel, the following vulnerability has been resolved: NFSD: Guard admin state-revocation walks with NFSD_NET_UP Writing to /proc/fs/nfsd/unlock_filesystem, or sending the NFSD_CMD_UNLOCK_FILESYSTEM or NFSD_CMD_UNLOCK_EXPORT netlink command, walks the NFSv4 client hash tables to revoke open state and cancel async COPY operations. All three handlers gate that walk on nn->nfsd_serv, but a listener ad...
CVE-2026-90040						In the Linux kernel, the following vulnerability has been resolved: KVM: SEV: Forcefully invalidate SNP VMs if its backing gmem page is zapped Wire up a gmem_invalidate_range() call for SNP VMs, and use it to force vCPUs to reload/recheck their guest-provided VMs if the backing gmem page is being invalidated, e.g. is being PUNCH_HOLE'd. Use the same core logic to handle invalidations as VMX does for the APIC-...
CVE-2026-90971				0.001		Server-Side Request Forgery (SSRF) in the VMware synchronization feature in Devolutions Server 2026.2.16 and earlier allows a low-privileged authenticated user to obtain other users' credentials and reach internal or cloud-metadata network endpoints via a crafted connection definition submitted for datacenter discovery.
CVE-2026-92021				0.002		Use-after-free in the JavaScript Engine: JIT component. This vulnerability was fixed in Firefox ESR 140.16 and Thunderbird 140.16.
CVE-2026-92040				0.002		Use-after-free in the JavaScript: WebAssembly component. This vulnerability was fixed in Firefox 156 and Thunderbird 156.
CVE-2026-92126						Jenkins Script Security Plugin 1415.v9a_f9b_3a_c253d and earlier does not reject @Builder annotations whose builderStrategy member names an arbitrary class, allowing attackers with permission to define and run sandboxed scripts, including Pipelines, to execute code outside the sandbox if a suitable class is present on the classpath of the component that evaluates the script.

P3/P4 items (2717) are in the Excel report. Unsourced CVEs are newly published and awaiting NVD analysis; re-check tomorrow's report.