

Daily Vulnerability Report - 2026-09-08

Window (UTC): 2026-09-08T00:00 to 2026-09-09T00:00 | Sources: NVD, CISA KEV, EPSS, Vulnrichment, GHSA, OSV | Generated 2026-09-17 13:15:46 UTC

Total	New	Updated	KEV added	KEV	Critical	High	Medium	Unscored	Watchlist
1693	1678	0	15	18	102	979	496	131	447

New today - published in this report window

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-84869	New	9.9	CRIT	Yes	0.007	connectwise:screenconnect	A condition in the ScreenConnect client may allow files to be transferred and executed through an active remote session without authorization or Host confirmation in certain circumstances. ScreenConnect servers are not impacted.
CVE-2026-81963	New	7.8	HIGH	Yes	0.006	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Improper link resolution before file access ('link following') in Windows Update Stack allows an authorized attacker to elevate privileges locally.
CVE-2026-85880	New	7.8	HIGH	Yes	0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows ALPC allows an authorized attacker to elevate privileges locally.
CVE-2026-60004	New		CRIT		0.868	Go:gitea.dev	### Summary Gitea's `diffpatch` endpoint can be abused to install and execute a Git hook from repository-controlled content. An attacker with ordinary write access to a repository can execute arbitrary shell commands as the Gitea OS user. With default open registration, an unauthenticated visitor can obtain the required write access by registering an account and creating a...
CVE-2026-44756	New	10.0	CRIT		0.003		A memory safety vulnerability exists in the Extended Passport Protocol (EPP) processing library. Under specific conditions, an unauthenticated attacker could exploit a crafted network request containing a malformed EPP header, potentially resulting in undefined behavior and abnormal program termination. Successful exploitation may have a high impact on the confidentiality, i...
CVE-2026-82004	New	10.0	CRIT		0.014	adobe:campaign	Adobe Campaign Classic (ACC) is affected by an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability that could result in arbitrary code execution in the context of the current user. An attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is ...
CVE-2026-12645	New	9.9	CRIT		0.012		A Missing Authorization vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-12646	New	9.9	CRIT		0.012		A Missing Authorization vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-12647	New	9.9	CRIT		0.012		A Missing Authorization vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-12650	New	9.9	CRIT		0.015		A Deserialization of Untrusted Data vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-19232	New	9.9	CRIT		0.006	adobe:experience_manager	Adobe Experience Manager is affected by an Incorrect Authorization vulnerability that could result in arbitrary code execution in the context of the current user, potentially gaining elevated access or control over the victim's account or session. A low-privileged attacker could exploit this vulnerability to gain elevated access or control over the victim's account or sessio...
CVE-2026-26084	New	9.9	CRIT		0.002		A improper access control vulnerability in Fortinet FortiSandbox 5.0.0 through 5.0.5, FortiSandbox 4.4.0 through 4.4.8, FortiSandbox Cloud 5.0.4 through 5.0.5, FortiSandbox PaaS 5.0.4 through 5.0.5 may allow attacker to access sensitive information via crafted HTTP requests.
CVE-2026-48273	New	9.9	CRIT		0.019	adobe:coldfusion	ColdFusion is affected by an Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') vulnerability that could result in arbitrary code execution in the context of the current user. A low-privileged attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is changed.
CVE-2026-78234	New	9.9	CRIT		0.002		A flaw was found in hawtio-operator. The operator reads the OpenShift Service CA private signing key from the openshift-service-ca namespace and uses it to mint client certificates with a Subject Common Name (CN) supplied by the author of a namespaced Hawtio custom resource. Because the operator ships a ClusterRole that aggregates Hawtio CR permissions into the edit and admi...
CVE-2026-86464	New	9.9	CRIT		0.004		In the current development version of Eclipse aeriOS, for which no official release has yet been published, the Identity Manager (IdM) deployment included insecure default configurations and credentials for security-sensitive services. The Helm chart exposed the Keycloak service and its PostgreSQL backing database through Kubernetes NodePort services by default, while th...
CVE-2026-12744	New	9.8	CRIT		0.022		A Deserialization of Untrusted Data vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote unauthenticated attacker to execute arbitrary code on the server.
CVE-2026-12745	New	9.8	CRIT		0.021		A Deserialization of Untrusted Data vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote unauthenticated attacker to execute arbitrary code on the server.
CVE-2026-28606	New	9.8	CRIT		0.003	google:android	In handleBondStateChanged of AdapterService.java, there is a possible way to skip pairing due to a logic error in the code. This could lead to remote escalation of privilege without user consent with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-49921	New	9.8	CRIT		0.003		In multiple locations, there is a possible memory safety issue due to a heap buffer overflow. This could lead to remote code execution with no additional execution privileges needed. User interaction is not needed for exploitation.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-58240	New	9.8	CRIT		0.003		SAP NetWeaver Message Server does not sufficiently validate the authenticity of internal application server components during registration. An unauthenticated attacker with network access to the affected service could exploit this weakness to register an unauthorized component and potentially perform unauthorized actions within the application environment, resulting in a hig...
CVE-2026-58822	New	9.8	CRIT		0.003		In multiple functions of ftsmooth.c, there is a possible memory safety issue due to improper casting. This could lead to remote code execution with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-61516	New	9.8	CRIT		0.004		Netis NX10 firmware V4.0.1.5808 and V3.0.0.4142 contain an information disclosure vulnerability that allows unauthenticated attackers to retrieve the administrator password by sending a request to the sysinfo action in the web management interface without a valid session. Attackers can replay the exposed credential against the login handler to establish a fully authenticated...
CVE-2026-66302	New	9.8	CRIT		0.005	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	External control of file name or path in Skype for Business allows an unauthorized attacker to execute code over a network.
CVE-2026-68839	New	9.8	CRIT		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Mass Storage Class Driver allows an unauthorized attacker to execute code over a network.
CVE-2026-69276	New	9.8	CRIT		0.009		Integer underflow (wrap or wraparound) in Microsoft UxTheme Library (uxtheme.dll) allows an unauthorized attacker to execute code over a network.
CVE-2026-69408	New	9.8	CRIT		0.01		Integer overflow or wraparound in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.
CVE-2026-69431	New	9.8	CRIT		0.009		Heap-based buffer overflow in Telnet Client allows an unauthorized attacker to execute code over a network.
CVE-2026-69463	New	9.8	CRIT		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code over a network.
CVE-2026-69491	New	9.8	CRIT		0.009		Heap-based buffer overflow in Windows Microsoft DirectMusic allows an unauthorized attacker to execute code over a network.
CVE-2026-69493	New	9.8	CRIT		0.01		Out-of-bounds read in Windows Event Logging Service allows an unauthorized attacker to execute code over a network.
CVE-2026-69496	New	9.8	CRIT		0.01		Heap-based buffer overflow in Windows Compressed Folder allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69525	New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Desktop Services allows an unauthorized attacker to execute code over a network.
CVE-2026-69579	New	9.8	CRIT		0.01		Use after free in Windows Message Queuing allows an unauthorized attacker to execute code over a network.
CVE-2026-69586	New	9.8	CRIT		0.01		Integer overflow or wraparound in Microsoft Windows PDF allows an unauthorized attacker to execute code over a network.
CVE-2026-69590	New	9.8	CRIT		0.01		Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine
CVE-2026-69595	New	9.8	CRIT		0.011		Use after free in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to execute code over a network.
CVE-2026-69715	New	9.8	CRIT		0.01		Out-of-bounds read in Windows Direct Show allows an unauthorized attacker to execute code over a network.
CVE-2026-69730	New	9.8	CRIT		0.011		Use after free in Windows DNS allows an unauthorized attacker to execute code over a network.
CVE-2026-69768	New	9.8	CRIT		0.009		Heap-based buffer overflow in Windows RNDIS allows an unauthorized attacker to execute code over a network.
CVE-2026-69769	New	9.8	CRIT		0.009		Heap-based buffer overflow in Windows HTTP Print Provider allows an unauthorized attacker to execute code over a network.
CVE-2026-69819	New	9.8	CRIT		0.009		Out-of-bounds write in RPC Runtime allows an unauthorized attacker to execute code over a network.
CVE-2026-69824	New	9.8	CRIT		0.01		Integer underflow (wrap or wraparound) in Microsoft Standard XPS allows an unauthorized attacker to execute code over a network.
CVE-2026-69829	New	9.8	CRIT		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Shell allows an unauthorized attacker to execute code over a network.
CVE-2026-69845	New	9.8	CRIT		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Heap-based buffer overflow in Windows DHCP Server allows an unauthorized attacker to execute code over a network.
CVE-2026-69910	New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Windows Hyper-V allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-70296	New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds write in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-71374	New	9.8	CRIT		0.003		Deserialization of untrusted data vulnerability in Cosminexus Component Container. This issue affects Cosminexus Component Container: from 11-70-01 before 11-70-03, from 11-60 before 11-60-03, from 11-50 through 11-50-03, from 11-40 through 11-40-03, from 11-30 through 11-30-08, from 11-20 before 11-20-10, from 11-10 through 11-10-11, from 11-00 before 11-00-13, from 09-87 ...
CVE-2026-71376	New	9.8	CRIT		0.01		OS command injection vulnerability in Cosminexus Component Container. This issue affects Cosminexus Component Container: from 11-70-01 before 11-70-03, from 11-60 before 11-60-03, from 11-50 through 11-50-03, from 11-40 through 11-40-03, from 11-30 through 11-30-08, from 11-20 before 11-20-10, from 11-10 through 11-10-11, from 11-00 before 11-00-13, from 09-87 before 09-87-...
CVE-2026-71377	New	9.8	CRIT		0.003		Command Argument Injection Vulnerability in Cosminexus Component Container. This issue affects Cosminexus Component Container: from 11-70-01 before 11-70-03, from 11-60 before 11-60-03, from 11-50 through 11-50-03, from 11-40 through 11-40-03, from 11-30 through 11-30-08, from 11-20 before 11-20-10, from 11-10 through 11-10-11, from 11-00 through 11-00-12, from 09-87 before...
CVE-2026-72979	New	9.8	CRIT		0.01		Use after free in Windows DHCP Server allows an unauthorized attacker to execute code over a network.
CVE-2026-72982	New	9.8	CRIT		0.009		Stack-based buffer overflow in Windows Netlogon allows an unauthorized attacker to execute code over a network.
CVE-2026-72983	New	9.8	CRIT		0.009		Use after free in Windows Internet Connection Sharing (ICS) allows an unauthorized attacker to execute code over a network.
CVE-2026-73009	New	9.8	CRIT		0.009		Use after free in Windows Secure Socket Tunneling Protocol (SSTP) allows an unauthorized attacker to execute code over a network.
CVE-2026-73010	New	9.8	CRIT		0.009		Use after free in Windows Failover Cluster allows an unauthorized attacker to execute code over a network.
CVE-2026-73025	New	9.8	CRIT		0.009		Weak authentication in Windows iSCSI allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-77089	New	9.8	CRIT		0.003	commvault:commvault	Command Center API contained an authentication bypass issue affecting privilege management. Software customers upgrade to resolved maintenance release. Update Command Center.
CVE-2026-77092	New	9.8	CRIT		0.002	commvault:commvault	Content Extractor contained a deserialization of untrusted data issue affecting privilege management. Software customers upgrade to resolved maintenance release. Update Content Extractor.
CVE-2026-77098	New	9.8	CRIT		0.003	commvault:commvault	Private Metrics Server contained an SQL injection condition affecting database operations. Software customers upgrade to resolved maintenance release. Update Private Metrics Server.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-77493	New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Double free in Microsoft Graphics Component allows an unauthorized attacker to execute code over a network.
CVE-2026-78445	New	9.8	CRIT		0.009	microsoft:windows_server_2012, microsoft:windows_server_2016, microsoft:windows_server_2019, microsoft:windows_server_20	Use after free in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to execute code over a network.
CVE-2026-78509	New	9.8	CRIT		0.01	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Heap-based buffer overflow in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.
CVE-2026-78510	New	9.8	CRIT		0.01	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-79569	New	9.8	CRIT		0.004		Movie_Recommend v1.0.0 was discovered to contain a SQL injection vulnerability in the sort parameter at /loadingmore. This vulnerability allows attackers to access sensitive database information via a crafted SQL statement.
CVE-2026-79570	New	9.8	CRIT		0.003		mfish-nocode-pro v1.0.0 was discovered to contain a SQL injection vulnerability in the tableName parameter at /sys/dbConnect/data. This vulnerability allows attackers to access sensitive database information via a crafted SQL statement.
CVE-2026-79574	New	9.8	CRIT		0.005		An issue in the gateway server of mpush v0.8.1 allows attackers to execute arbitrary code via sending a crafted broadcast message.
CVE-2026-79576	New	9.8	CRIT		0.003		An issue in the Single-Sign On (SSO) component of Digital-Infrastructure v9.6.7 allows attackers to authenticate as any user, including the Admin, without a password.
CVE-2026-79577	New	9.8	CRIT		0.003		An issue in the /cas/login component of sso-master v1.0.0 allows attackers to authenticate into the application without a password via sending a crafted POST request.
CVE-2026-65669	New	9.6	CRIT		0.007		Improper neutralization of special elements in output used by a downstream component ('injection') in SQL Server allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-81376	New	9.6	CRIT		0.006	microsoft:visual_studio_code	Incomplete comparison with missing factors in Visual Studio Code allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-76969	New	9.4	CRIT		0.003		@sap/cds-mtxs NPM library does not perform sufficient checks on certain functionality used in multitenant CAP applications with extensibility enabled. An unauthenticated attacker could send specially crafted requests to obtain sensitive credentials and abuse them to replace or delete tenant data. Successful exploitation can result in a high impact on availability and integri...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-82533	New	9.4	CRIT		0.006		DeepSeek Harness before 0.1.2-alpha.1 contains an authentication bypass vulnerability that grants unauthenticated access to its local HTTP agent-control API by accepting a client-supplied loopback Host header in place of validating the actual TCP connection origin. On the default configuration, a confined tool-executed process can reach the loopback API without any port expo...
CVE-2026-62645	New	9.3	CRIT		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). Information is exposed through the web interface that can be used to calculate the current and past session ID numbers. This could allow an attacker to bypass the authentication and gain unauthorized access to the device.
CVE-2026-62647	New	9.3	CRIT		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). A random number generator is used to generate security-relevant values (such as session identifiers used for authentication purposes) that is not initialized with a True Random Number Generator (TRNG), resulting in a predictable sequence of generated values. This could allow an unauthenticated remot...
CVE-2026-69356	New	9.3	CRIT		0.007		Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Exchange Server allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-76200	New	9.3	CRIT		0.005	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by an attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field, potentially gaining elevated access or control over the victim's account or session...
CVE-2026-76201	New	9.3	CRIT		0.005	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by an attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field, potentially gaining elevated access or control over the victim's account or session...
CVE-2026-78997	New	9.3	CRIT		0.003		UC Browser for Android (package com.UCMobile.intl, version 13.7.8.1314) contains a Universal Cross-Site Scripting vulnerability that allows an attacker to execute arbitrary JavaScript in the context of any origin. An attacker hosts a specially crafted URL on a UC-owned domain (via a reflected XSS) that leverages the browser's internal JavaScript bridge to register a deferred...
CVE-2026-67367	New	9.2	CRIT		0.008		A vulnerability has been identified in SIMOVE Fleetmanager V3.1 (All versions < V3.1.13), SIMOVE Fleetmanager V3.2 (All versions < V3.2.4), SIMOVE Fleetmanager V3.3 (All versions < V3.3.2), SIMOVE Fleetmanager V4.0 (All versions < V4.0.1), SIPLANT V1.7 (All versions), SIPLANT V2.2 (All versions), SIPLANT V3.0 (All versions), SIPLANT V3.1 (All versions < V3.1.4). Affected dev...
CVE-2026-82067	New	9.2	CRIT		0.003	mongodb:mongodb	Improper handling of case sensitivity in the configuration validation component of MongoDB Server may cause the authorization subsystem to remain in a default disabled state during server startup. An unauthenticated user with network access to a deployment where this condition occurs can perform arbitrary administrative operations, resulting in full impact of data confidenti...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-84197	New	9.2	CRIT		0.002		In Eclipse Ditto's Node.js JavaScript client, all released versions of @eclipse-ditto/ditto-javascript-client-node from 2.0.0 to 3.9.0 and of its predecessor package @eclipse-ditto/ditto-javascript-client-node_1.0 from 1.0.0 to 2.1.0, the WebSocket transport hard-codes rejectUnauthorized: false when creating the underlying ws WebSocket. Certificate chain and hostname validat...
CVE-2026-62646	New	9.1	CRIT		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). A session identifier is generated using an algorithm with insufficient randomness, resulting in a token with low entropy that can be predicted or brute-forced within a feasible number of attempts. This could allow an unauthenticated remote attacker to derive valid session identifiers and bypass auth...
CVE-2026-69641	New	9.1	CRIT		0.008		Missing authorization in Microsoft Exchange Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-73309	New	9.1	CRIT		0.005	xenforo:xenforo	XenForo before 2.3.13 contains an authentication bypass vulnerability in the OAuth2 token endpoint that allows unauthenticated attackers to obtain valid token pairs by submitting empty values for client_secret and code_verifier parameters. Attackers can exploit PHP truthy evaluation logic, which treats empty strings as false and skips client secret validation and PKCE code v...
CVE-2026-73311	New	9.1	CRIT		0.004	xenforo:xenforo	XenForo before 2.3.13 contains an OAuth2 authorization code reuse vulnerability that allows attackers to obtain unauthorized token pairs by submitting a previously used authorization code. Attackers can exploit the failure to invalidate or mark authorization codes as consumed after initial token issuance to receive an independent token pair for the same user and scopes, bypa...
CVE-2026-73312	New	9.1	CRIT		0.004	xenforo:xenforo	XenForo before 2.3.13 contains a refresh token replay vulnerability that allows attackers to reuse a refresh token multiple times by exploiting the failure to mark tokens as consumed when the parent access token has expired. Attackers can repeatedly submit the same refresh token to generate additional independent token pairs, achieving persistent unauthorized access for the ...
CVE-2026-75156	New	9.1	CRIT		0.002		Apache Airflow FAB provider versions 3.7.3 through 3.8.0 do not validate the issuer or audience of Azure AD `id_token`s during OAuth login. Deployments are affected only when the FAB auth manager is configured with Azure AD as an OAuth provider. Because the signing keys are fetched from Microsoft's **multi-tenant** JWKS endpoint, an `id_token` minted in *any* Azure tenant — ...
CVE-2026-75746	New	9.1	CRIT		0.011		ColdFusion is affected by an Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') vulnerability that could result in arbitrary code execution in the context of the current user. An attacker with high privileges could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is cha...
CVE-2026-79571	New	9.1	CRIT		0.003		Incorrect access control in the SellerAuthorizeAspect component of springboot-project v1.0.0 allows unauthenticated attackers to access all seller management interfaces and list all products/orders, put products on/off sale, finish/cancel orders, and modify categories without authentication.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86729	New	9.1	CRIT		0.002		WWBN AVideo through commit e01e41ecc (no patched version available) exposes get_api_preauthorize in plugin/API/API.php as a second, undocumented login path. Unlike get_api_signIn, which enforces a rate limit of 10 attempts per 5 minutes via checkRateLimit(), get_api_preauthorize performs the same credential check with no throttling for any client, allowing unlimited remote p...
CVE-2026-86840	New	9.1	CRIT		0.002		The `vtoken-minting` and `slpx` pallets in Bifrost contain an improper authorization vulnerability in channel commission attribution. A signed account can supply an arbitrary registered `channel_id` when minting tokens without verifying that the caller is authorized to mint on behalf of that channel. This allows an attacker to inflate a channel's recorded mint volume and cau...
CVE-2026-53581	New	9.0	CRIT		0.003		OPNsense is a FreeBSD based firewall and routing platform. Prior to version 26.1.9 of opnsense/core and version 26.4_20 of BE/opnsense/core, a path traversal vulnerability in the NTP configuration module allows an attacker to overwrite arbitrary files on the system as the root user. By manipulating the GPS or PPS serial port parameter, an attacker with access to the NTP conf...
CVE-2026-66768	New	9.0	CRIT		0.003		SAP GUI for Java does not correctly enforce the trust level policy for certain functions invoked from a connected backend system. A low-privileged attacker could exploit this weakness by manipulating a connected backend system to trigger affected functionality. This could allow arbitrary command execution on the victim's machine, leading to a high impact on the confidentiality...
CVE-2026-69854	New	9.0	CRIT		0.006		Improper authentication in Spring Cloud Azure allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-85982	New	9.0	CRIT		0.002		The Auth0 AD/LDAP Connector is vulnerable to stored Cross-Site Scripting (XSS) issues due to improper HTML encoding of data in search results and updater log content displayed in the admin panel. An authenticated user with privileges to modify directory attributes, or a low-privileged local user on the host where the connector is installed, could insert script content. This ...
CVE-2026-50093	New	8.9	HIGH		0.002		A vulnerability has been identified in Siveillance Control Pro V3.0 (All versions < V3.0.12.2173), Siveillance Control Pro V4.0 (All versions < V4.0.9.2178), Siveillance Control V3.0 (All versions < V3.0.22.2177), Siveillance Control V4.0 (All versions < V4.0.11.2177). A vulnerability in the OIS web module allows an attacker to upload arbitrary files to the server. Successfu...
CVE-2026-12648	New	8.8	HIGH		0.015		A Deserialization of Untrusted Data vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-12651	New	8.8	HIGH		0.015		A Deserialization of Untrusted Data vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-16502	New	8.8	HIGH		0.005		The Live Composer – Free WordPress Website Builder plugin for WordPress is vulnerable to PHP Object Injection in all versions up to, and including, 2.1.18 via deserialization of untrusted input . This makes it possible for authenticated attackers, with contributor-level access and above, to inject a PHP Object. No known POP chain is present in the vulnerable software, which ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-18851	New	8.8	HIGH		0.01	ivanti:endpoint_manager_mobile	Missing authorization in Ivanti Endpoint Manager Mobile before version 12.10.0.0, 12.9.0.2, and 12.8.0.4 allows a remote authenticated attacker to escalate their privileges to admin.
CVE-2026-28609	New	8.8	HIGH		0.003	google:android	In read of MatroskaExtractor.cpp, there is a possible out-of-bounds write due to improper casting. This could lead to remote code execution with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28618	New	8.8	HIGH		0.003	google:android	In dec_frm_prepare of oapv.c, there is a possible OOB write due to a heap buffer overflow. This could lead to remote code execution with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28666	New	8.8	HIGH		0.003		In multiple functions of LocalImageResolver.java, there is a possible Remote Persistent Denial of Service due to a DNG image rendering check bypass. This could lead to remote escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-30754	New	8.8	HIGH		0.003		A memory corruption vulnerability exists in FFmpeg before 8.1. The RTP encoding process. In the nal_send function in libavformat/rtpenc_h264_hevc.c, a negative size parameter (size=-3) is passed to memcpy when transmitting H.264/HEVC streams via RTP using a crafted input file. This was detected using AddressSanitizer.
CVE-2026-49879	New	8.8	HIGH		0.003		In multiple functions of rw_t3t.cc, there is a possible out of bounds write due to an integer overflow. This could lead to remote code execution with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-49882	New	8.8	HIGH		0.003		In rw_mfc_handle_read_op of rw_mfc.cc, there is a possible memory safety issue due to a heap buffer overflow. This could lead to remote code execution with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-62706	New	8.8	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.
CVE-2026-62744	New	8.8	HIGH		0.008		Heap-based buffer overflow in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.
CVE-2026-62895	New	8.8	HIGH		0.007		Permissive cross-domain policy with untrusted domains in Azure Arc allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-65772	New	8.8	HIGH		0.009		Deserialization of untrusted data in Microsoft Dynamics 365 allows an authorized attacker to execute code over a network.
CVE-2026-66814	New	8.8	HIGH		0.004	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Insufficient granularity of access control in SQL Server allows an authorized attacker to elevate privileges over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-66818	New	8.8	HIGH		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper privilege management in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-66819	New	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper neutralization of special elements used in an sql command ('sql injection') in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-66820	New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper neutralization of special elements used in an sql command ('sql injection') in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-67368	New	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper link resolution before file access ('link following') in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-67370	New	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper neutralization of special elements used in an sql command ('sql injection') in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-67373	New	8.8	HIGH		0.006	microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67380	New	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67381	New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-67384	New	8.8	HIGH		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Integer overflow or wraparound in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67385	New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use after free in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67388	New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-67631	New	8.8	HIGH		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67638	New	8.8	HIGH		0.007	microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67639	New	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67642	New	8.8	HIGH		0.005	microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67643	New	8.8	HIGH		0.008	microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-68775	New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-68786	New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-68828	New	8.8	HIGH		0.004		Heap-based buffer overflow in Remote Desktop Client allows an unauthorized attacker to execute code over a network.
CVE-2026-69266	New	8.8	HIGH		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Integer overflow or wraparound in Windows DHCP Server allows an unauthorized attacker to execute code over a network.
CVE-2026-69268	New	8.8	HIGH		0.007	microsoft:sharepoint_server	Improper access control in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.
CVE-2026-69273	New	8.8	HIGH		0.005	microsoft:sharepoint_server	Improper access control in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.
CVE-2026-69282	New	8.8	HIGH		0.005	microsoft:sharepoint_server	Improper access control in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.
CVE-2026-69285	New	8.8	HIGH		0.006	microsoft:365_apps, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Heap-based buffer overflow in Microsoft Office allows an unauthorized attacker to execute code over a network.
CVE-2026-69291	New	8.8	HIGH		0.006		Heap-based buffer overflow in Windows Volume Manager Extension Driver allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69334	New	8.8	HIGH		0.008		Heap-based buffer overflow in Windows Volume Manager Extension Driver allows an unauthorized attacker to execute code over a network.
CVE-2026-69355	New	8.8	HIGH		0.008		External control of file name or path in Microsoft Exchange Server allows an authorized attacker to execute code over a network.
CVE-2026-69360	New	8.8	HIGH		0.008		Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-69386	New	8.8	HIGH		0.008		Heap-based buffer overflow in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.
CVE-2026-69434	New	8.8	HIGH		0.008		Heap-based buffer overflow in Windows URL Moniker allows an unauthorized attacker to execute code over a network.
CVE-2026-69439	New	8.8	HIGH		0.007		Heap-based buffer overflow in .NET and Visual Studio allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-69442	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Heap-based buffer overflow in Microsoft Office allows an unauthorized attacker to execute code over a network.
CVE-2026-69461	New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code over a network.
CVE-2026-69464	New	8.8	HIGH		0.009	microsoft:sharepoint_server	Execution with unnecessary privileges in Microsoft Office SharePoint allows an authorized attacker to elevate privileges over a network.
CVE-2026-69465	New	8.8	HIGH		0.008	microsoft:sharepoint_server	Missing authorization in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.
CVE-2026-69485	New	8.8	HIGH		0.009		Use of uninitialized resource in Remote Desktop Client allows an authorized attacker to execute code over a network.
CVE-2026-69494	New	8.8	HIGH		0.008		Out-of-bounds read in Windows Event Logging Service allows an unauthorized attacker to execute code over a network.
CVE-2026-69495	New	8.8	HIGH		0.008		Heap-based buffer overflow in Windows Event Logging Service allows an unauthorized attacker to execute code over a network.
CVE-2026-69499	New	8.8	HIGH		0.008		Integer overflow or wraparound in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-69511	New	8.8	HIGH		0.008		Heap-based buffer overflow in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69518	New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Remote Desktop allows an unauthorized attacker to execute code over a network.
CVE-2026-69522	New	8.8	HIGH		0.008		Heap-based buffer overflow in Visual Studio allows an unauthorized attacker to execute code over a network.
CVE-2026-69529	New	8.8	HIGH		0.005	microsoft:365_apps, microsoft:access, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, microsoft:off	Heap-based buffer overflow in Microsoft Office Access allows an unauthorized attacker to execute code over a network.
CVE-2026-69547	New	8.8	HIGH		0.009		Heap-based buffer overflow in Windows DHCP Server allows an authorized attacker to execute code over a network.
CVE-2026-69551	New	8.8	HIGH		0.009		Use after free in Windows DNS allows an authorized attacker to execute code over a network.
CVE-2026-69556	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-69598	New	8.8	HIGH		0.008		Incorrect calculation of buffer size in Windows iSCSI allows an unauthorized attacker to execute code over a network.
CVE-2026-69601	New	8.8	HIGH		0.008		Heap-based buffer overflow in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.
CVE-2026-69603	New	8.8	HIGH		0.003		Heap-based buffer overflow in Windows Hyper-V allows an authorized attacker to execute code locally.
CVE-2026-69614	New	8.8	HIGH		0.009	microsoft:365_apps, microsoft:access, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Stack-based buffer overflow in Microsoft Office Access allows an unauthorized attacker to execute code over a network.
CVE-2026-69628	New	8.8	HIGH		0.009		Heap-based buffer overflow in Windows iSCSI allows an authorized attacker to execute code over a network.
CVE-2026-69629	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, microsoft:outlook	Heap-based buffer overflow in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69632	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Use after free in Microsoft Office allows an unauthorized attacker to execute code over a network.
CVE-2026-69649	New	8.8	HIGH		0.008		Heap-based buffer overflow in Windows Raw Image Extension allows an unauthorized attacker to execute code over a network.
CVE-2026-69669	New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Kernel allows an unauthorized attacker to execute code over a network.
CVE-2026-69671	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-69676	New	8.8	HIGH		0.012		Authentication bypass by capture-replay in Windows Kerberos allows an authorized attacker to execute code over a network.
CVE-2026-69678	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Use after free in Microsoft Office PowerPoint allows an unauthorized attacker to execute code over a network.
CVE-2026-69686	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Stack-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-69712	New	8.8	HIGH		0.009		Use after free in Windows Key Distribution Center allows an authorized attacker to execute code over a network.
CVE-2026-69716	New	8.8	HIGH		0.009	microsoft:sharepoint_server	Improper neutralization of special elements used in an sql command ('sql injection') in Microsoft Office SharePoint allows an authorized attacker to elevate privileges over a network.
CVE-2026-69722	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Stack-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-69724	New	8.8	HIGH		0.008	microsoft:sharepoint_server	Missing authorization in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69729	New	8.8	HIGH		0.009		Heap-based buffer overflow in Windows Credential Providers allows an authorized attacker to execute code over a network.
CVE-2026-69740	New	8.8	HIGH		0.003		Use after free in Windows Hello allows an authorized attacker to elevate privileges locally.
CVE-2026-69742	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, microsoft:publisher	Integer overflow or wraparound in Microsoft Office Publisher allows an unauthorized attacker to execute code over a network.
CVE-2026-69759	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Stack-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-69764	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, microsof	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-69767	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Use after free in Microsoft Office PowerPoint allows an unauthorized attacker to execute code over a network.
CVE-2026-69772	New	8.8	HIGH		0.008		Heap-based buffer overflow in Windows Network File System allows an unauthorized attacker to execute code over a network.
CVE-2026-69778	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:access, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, microsoft:off	Heap-based buffer overflow in Microsoft Office Access allows an unauthorized attacker to execute code over a network.
CVE-2026-69784	New	8.8	HIGH		0.003		Use after free in Windows Hello allows an authorized attacker to elevate privileges locally.
CVE-2026-69797	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Use after free in Microsoft Office PowerPoint allows an unauthorized attacker to execute code over a network.
CVE-2026-69860	New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Imaging Component allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-70203	New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Media Player allows an unauthorized attacker to execute code over a network.
CVE-2026-70351	New	8.8	HIGH		0.008		Integer overflow or wraparound in Microsoft WebP Image Extension allows an unauthorized attacker to execute code over a network.
CVE-2026-70586	New	8.8	HIGH		0.008		Heap-based buffer overflow in Windows Paint allows an unauthorized attacker to execute code over a network.
CVE-2026-71328	New	8.8	HIGH		0.006	microsoft:.net, microsoft:visual_studio_2022, microsoft:visual_studio_2026, microsoft:windows	Heap-based buffer overflow in Visual Studio allows an unauthorized attacker to execute code over a network.
CVE-2026-71336	New	8.8	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Integer overflow or wraparound in Windows Work Folder Service allows an authorized attacker to execute code over a network.
CVE-2026-71352	New	8.8	HIGH		0.007		Integer underflow (wrap or wraparound) in Windows Remote Access Connection Manager allows an authorized attacker to execute code over a network.
CVE-2026-72933	New	8.8	HIGH		0.008		Heap-based buffer overflow in Microsoft WDAC OLE DB provider for SQL allows an unauthorized attacker to execute code over a network.
CVE-2026-72940	New	8.8	HIGH		0.008		Heap-based buffer overflow in Windows Schannel allows an unauthorized attacker to execute code over a network.
CVE-2026-72950	New	8.8	HIGH		0.009		Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine
CVE-2026-72959	New	8.8	HIGH		0.009		Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine
CVE-2026-72960	New	8.8	HIGH		0.008		Heap-based buffer overflow in Windows Media Player allows an unauthorized attacker to execute code over a network.
CVE-2026-72972	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-72973	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-72986	New	8.8	HIGH		0.008		Heap-based buffer overflow in Graphic Fonts allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-73006	New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Microsoft Graphics Component allows an unauthorized attacker to execute code over a network.
CVE-2026-73012	New	8.8	HIGH		0.006		Heap-based buffer overflow in Windows Management Services allows an authorized attacker to elevate privileges over a network.
CVE-2026-73013	New	8.8	HIGH		0.006		Heap-based buffer overflow in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-73016	New	8.8	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Microsoft Graphics Component allows an unauthorized attacker to execute code over a network.
CVE-2026-73018	New	8.8	HIGH		0.008		Heap-based buffer overflow in Graphic Fonts allows an unauthorized attacker to execute code over a network.
CVE-2026-73023	New	8.8	HIGH		0.006		Heap-based buffer overflow in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-73028	New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper access control in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-77105	New	8.8	HIGH		0.002	commvault:commvault, linux:linux_kernel, microsoft:windows	CommServe contained a cryptographic signature verification issue affecting privilege management. Software customers upgrade to resolved maintenance release. Update CommServe and Web Server.
CVE-2026-77106	New	8.8	HIGH		0.003	commvault:commvault	Cvlaunchd contained a missing authorization issue affecting command execution authorization. Software customers upgrade to resolved maintenance release. Update all Commvault installations, including Commserve, Webserver, Command Center, Media Agents, Clients and HyperScale X.
CVE-2026-77480	New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Insufficient granularity of access control in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-77481	New	8.8	HIGH		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-77482	New	8.8	HIGH		0.008	microsoft:sql_server_2017, microsoft:sql_server_2019	Heap-based buffer overflow in SQL Server allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-77483	New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Weak authentication in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-77484	New	8.8	HIGH		0.011	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Deserialization of untrusted data in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-77486	New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019	Integer overflow or wraparound in SQL Server allows an unauthorized attacker to execute code over a network.
CVE-2026-77487	New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper access control in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-77495	New	8.8	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-77504	New	8.8	HIGH		0.006		Double free in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-77901	New	8.8	HIGH		0.006	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Null pointer dereference in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-77906	New	8.8	HIGH		0.008	microsoft:visual_studio_2026	Heap-based buffer overflow in Visual Studio allows an unauthorized attacker to execute code over a network.
CVE-2026-77907	New	8.8	HIGH		0.005	microsoft:visual_studio_2026	Heap-based buffer overflow in Visual Studio allows an unauthorized attacker to execute code over a network.
CVE-2026-77908	New	8.8	HIGH		0.007		Improper control of generation of code ('code injection') in Microsoft Dynamics 365 allows an authorized attacker to execute code over a network.
CVE-2026-78439	New	8.8	HIGH		0.006		Stack-based buffer overflow in Microsoft Graphics Component allows an unauthorized attacker to execute code over a network.
CVE-2026-78442	New	8.8	HIGH		0.006		Heap-based buffer overflow in Windows OLE DB allows an unauthorized attacker to execute code over a network.
CVE-2026-78456	New	8.8	HIGH		0.009	microsoft:sql_server_2022	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-78462	New	8.8	HIGH		0.005	microsoft:visual_studio_code	Authorization bypass through user-controlled key in Visual Studio Code allows an unauthorized attacker to bypass a security feature over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78463	New	8.8	HIGH		0.009		Improper control of generation of code ('code injection') in Remote Desktop Client allows an unauthorized attacker to execute code over a network.
CVE-2026-78504	New	8.8	HIGH		0.006	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Stack-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-78505	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Heap-based buffer overflow in Microsoft Office allows an unauthorized attacker to execute code over a network.
CVE-2026-78507	New	8.8	HIGH		0.006	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Use after free in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-78511	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-78512	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Numeric truncation error in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-78514	New	8.8	HIGH		0.006	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Use after free in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-78517	New	8.8	HIGH		0.006	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-78518	New	8.8	HIGH		0.009	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Out-of-bounds read in Microsoft Office Excel allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78519	New	8.8	HIGH		0.006	microsoft:365_apps, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, microsoft:outlook	Use of uninitialized resource in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.
CVE-2026-78521	New	8.8	HIGH		0.006	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-78524	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Out-of-bounds write in Microsoft Office allows an unauthorized attacker to execute code over a network.
CVE-2026-78525	New	8.8	HIGH		0.008	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Use after free in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.
CVE-2026-78526	New	8.8	HIGH		0.006	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-78834	New	8.8	HIGH		0.005		A code execution vulnerability exists in CMSimple 5.22 in the CoAuthors plugin. An authenticated low-privileged user who can modify page content and provide controlled imported content can trigger server-side execution by referencing crafted external or uploaded text content through the affected content import feature.
CVE-2026-79376	New	8.8	HIGH		0.002		An issue in the l2cap_handle_data() function of Bestechnic Co., Ltd BES2300 Bluetooth Audio SoC firmware v3.x and earlier allows attackers to cause a Denial of Service (DoS) via sending a crafted L2CAP packet.
CVE-2026-79602	New	8.8	HIGH		0.001		A guest with a PCI device assigned that has at least a BAR on the IO port space can trigger a BUG() in Xen.
CVE-2026-80074	New	8.8	HIGH		0.006		Heap-based buffer overflow in Remote Desktop Client allows an unauthorized attacker to execute code over a network.
CVE-2026-80077	New	8.8	HIGH		0.006		Heap-based buffer overflow in Remote Desktop Client allows an unauthorized attacker to execute code over a network.
CVE-2026-80080	New	8.8	HIGH		0.006	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Double free in Microsoft Office Word allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80081	New	8.8	HIGH		0.005	microsoft:365_apps	Use after free in Microsoft Office PowerPoint allows an unauthorized attacker to execute code over a network.
CVE-2026-80083	New	8.8	HIGH		0.002	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Untrusted pointer dereference in Windows Hyper-V allows an authorized attacker to execute code locally.
CVE-2026-80085	New	8.8	HIGH		0.005	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-80096	New	8.8	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Remote Desktop Services allows an authorized attacker to elevate privileges over a network.
CVE-2026-81352	New	8.8	HIGH		0.005		Heap-based buffer overflow in Microsoft Windows Codecs Library allows an unauthorized attacker to execute code over a network.
CVE-2026-81385	New	8.8	HIGH		0.01	microsoft:365_apps, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, microsoft:publisher	Deserialization of untrusted data in Microsoft Office Publisher allows an unauthorized attacker to execute code over a network.
CVE-2026-81952	New	8.8	HIGH		0.006	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-81955	New	8.8	HIGH		0.006		Heap-based buffer overflow in Microsoft Graphics Component allows an unauthorized attacker to execute code over a network.
CVE-2026-81996	New	8.8	HIGH		0.001	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an Incorrect Authorization vulnerability that could result in privilege escalation. A low-privileged attacker could exploit this vulnerability to gain elevated access. Exploitation of this issue does not require user interaction. Scope is changed.
CVE-2026-82536	New	8.8	HIGH		0.003		Roo-Code through 3.54.0 contains an auto-approve bypass vulnerability in the shell command parsing logic that allows attackers to execute denied shell commands by exploiting the omission of the bash pipe operator from the command parser's operator token set. Attackers can craft a command line with an allowlisted prefix followed by the stderr-redirecting pipe operator and a d...
CVE-2026-83941	New	8.8	HIGH		0.007	microsoft:entra_id	Missing authorization in Entra ID allows an authorized attacker to elevate privileges over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83992	New	8.8	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-83996	New	8.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Error Reporting allows an authorized attacker to elevate privileges locally.
CVE-2026-83998	New	8.8	HIGH		0.004		Heap-based buffer overflow in Remote Desktop Client allows an unauthorized attacker to execute code over a network.
CVE-2026-85877	New	8.8	HIGH		0.004	microsoft:windows_11_24h2	Heap-based buffer overflow in Windows Print Spooler Components allows an unauthorized attacker to execute code over a network.
CVE-2026-86076	New	8.8	HIGH		0.004	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the expression compiler sanitizer resolved through dynamically scoped this and did not reject reserved class member names. A class field named __sanitize could rebind the sanitizer and reach the Function constructor, enabling backend code execution and editor-preview JavaScript executi...
CVE-2026-86083	New	8.8	HIGH		0.004	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the legacy expression engine generated source text by calling the mutable global JSON.stringify while printing synthetic string literals and interpolating timezone data. An expression could replace JSON.stringify and cause later generated source to contain executable attacker-controlle...
CVE-2026-86730	New	8.8	HIGH		0.004		Craft CMS versions before 5.10.12 fail to properly cleanse string-typed field-layout elements, allowing authenticated control-panel users to inject Yii2 behavior attachments and event handlers. Attackers can post field-layout tab elements as JSON strings to bypass cleanse validation, then trigger arbitrary object instantiation and code execution through Craft::createObject().
CVE-2026-12611	New	8.7	HIGH		0.003		A client may issue HTTP/2 requests to a Jetty server that result in blocking writes that are never unblocked, eventually causing all threads to be blocked and the whole server to become unresponsive. This is caused by a race condition in the server when handling RST_STREAM frames and GOAWAY frames sent by the client. The race condition "resets" the HTTP2Flusher.termi...
CVE-2026-33197	New	8.7	HIGH		0.001		AMI APTIOV contains a vulnerability in BIOS where a privileged user may cause the "Incomplete List of Disallowed Inputs" by local access. Successful exploitation of this vulnerability may lead to arbitrary code execution and impact system Confidentiality, Integrity, and Availability.
CVE-2026-55250	New	8.7	HIGH		0.006		Maravel, a PHP framework oriented towards dependency injection, prior to version 10.74.0 has a high-severity Token Replay Vulnerability arising from a structural lifecycle mismatch between stateless token validation engines and high-performance relational caching layers. Any application with low cache memory that causes premature eviction to free up memory and applications r...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-62648	New	8.7	HIGH		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). The length of the URL component contained in pre-authenticated HTTP messages is not properly validated before appending additional data to it, resulting in an out-of-bounds write condition in memory. This could allow an unauthenticated remote attacker to crash the affected device, causing a reboot a...
CVE-2026-62649	New	8.7	HIGH		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). The web server does not properly limit or manage system resources when processing a high volume of concurrent HTTP requests. This could allow an unauthenticated remote attacker to cause the entire device to crash and reboot, resulting in a denial-of-service condition.
CVE-2026-62650	New	8.7	HIGH		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). Server-side authorization checks in the web-based management interface are not properly enforced, allowing role-based access control (RBAC) restrictions to be bypassed through manipulation of request data. This could allow an authenticated, low-privileged remote attacker to escalate privileges to an...
CVE-2026-73314	New	8.7	HIGH		0.005	xenforo:xenforo	XenForo before 2.3.13 contains a signature verification logic error in the PayPal REST webhook handler that allows unauthenticated attackers to bypass payment signature validation by submitting a webhook request with an unsupported auth_algo header value. When the algorithm cannot be mapped to a supported hash function, the verification function incorrectly returns true inst...
CVE-2026-73316	New	8.7	HIGH		0.002	xenforo:xenforo	XenForo before 2.3.13 contains a payment replay vulnerability in the PayPal REST payment provider that allows attackers to process the same webhook payload multiple times by exploiting a missing duplicate transaction ID check. Attackers can replay a valid webhook payload to trigger duplicate payment events, resulting in repeated subscription activations and unauthorized acco...
CVE-2026-77111	New	8.7	HIGH		0.005	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by an Incorrect Authorization vulnerability that could result in a Security feature bypass. An attacker with high privileges could leverage this vulnerability to bypass security measures and gain unauthorized write access, causing a limited disruption to availability. Exploitation of this issue does not require user interaction. Scope is changed.
CVE-2026-80219	New	8.7	HIGH		0.002		A flaw was found in hawtio-operator. When deploying Hawtio in cluster mode, the operator creates a cluster-scoped OAuthClient with automatic grant approval (GrantMethod: auto) and no client secret (public client). The redirect URIs are derived from the operator-created Route, whose hostname is tenant-controlled via the Hawtio CR spec.routeHostName field. A malicious tenant c...
CVE-2026-82064	New	8.7	HIGH		0.003	mongodb:mongodb	A security issue in MongoDB Server allows an unauthenticated network user to cause a denial of service on a specific type of replica set member. The server contains an assertion in its read concern processing logic that can be reached without authentication, and the assertion's assumptions about internal state do not hold for all member configurations, causing the server pro...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-82075	New	8.7	HIGH		0.003	mongodb:mongodb	An uncontrolled resource consumption weakness exists in the request-handling path of the MongoDB sharded-cluster router process. A client that has network access to a router port and has not authenticated can supply connection-monitoring parameters that cause the server to expend CPU resources without any rate limiting, degrading or denying service to legitimate clients. No ...
CVE-2026-86727	New	8.7	HIGH		0.003		AVideo through 29.0 contains an information disclosure vulnerability in plugin/Live/stats.json.php that allows unauthenticated attackers to retrieve stream keys and m3u8 URLs by accessing the endpoint without authentication. Attackers can enumerate private, unlisted, and group-restricted live streams by parsing the hidden_applications array in the JSON response to obtain sen...
CVE-2026-86732	New	8.7	HIGH		0.005		Craft CMS versions before 5.10.12 contain a remote code execution vulnerability in the element-index endpoint that allows authenticated content editors to instantiate arbitrary classes through the criteria parameter. Attackers can inject a malicious class via criteria[withTransforms][0][class] that reaches ImageTransforms::normalizeTransform(), then use a PHP gadget chain wi...
CVE-2026-86738	New	8.7	HIGH		0.003	snipeitapp:snipe-it	Snipe-IT versions before 8.7.0 contain a CSS injection vulnerability in the Custom CSS field due to incomplete sanitization that reverses HTML encoding on greater-than and double-quote characters. Superusers can plant malicious CSS payloads using @import and url() references to exfiltrate CSRF tokens from other superusers via attribute-selector rules, enabling account takeover.
CVE-2026-34223	New	8.6	HIGH		0.001		A vulnerability has been identified in Desigo CC ClickOnce Client V6 (All versions), Desigo CC ClickOnce Client V7 (All versions), Desigo CC family V8 (All versions), Desigo CC family V9 (All versions), Desigo CC Flex Client V6 (All versions), Desigo CC Flex Client V7 (All versions), Desigo CC Installed Client V6 (All versions), Desigo CC Installed Client V7 (All versions). ...
CVE-2026-61517	New	8.6	HIGH		0.016		Netis NX10 firmware V4.0.1.5808 and V3.0.0.4142 contain an OS command injection vulnerability in the ping diagnostic handler that allows authenticated administrators to execute arbitrary shell commands as root by injecting into the IpAddr parameter. The parameter is interpolated directly into a shell command executed through system() with an incomplete denylist that only blo...
CVE-2026-74239	New	8.6	HIGH		0.007	xenforo:xenforo	XenForo before 2.3.13 contains a path traversal vulnerability in the style archive importer on Windows deployments that allows authenticated non-super administrators with style permissions to write arbitrary files outside the intended extraction directory by using backslash-based traversal sequences in ZIP member names. Attackers can craft a malicious ZIP archive with backsl...
CVE-2026-75990	New	8.6	HIGH		0.002		Illustrator is affected by an Incorrect Authorization vulnerability that could result in arbitrary code execution in the context of the current user. An attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue requires user interaction in that a victim must open a malicious file. Scope is changed.
CVE-2026-75991	New	8.6	HIGH		0.002		Illustrator is affected by an Improper Input Validation vulnerability that could result in arbitrary code execution in the context of the current user. An attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue requires user interaction in that a victim must open a malicious file. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-76190	New	8.6	HIGH		0.01		ColdFusion is affected by an Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') vulnerability that could result in arbitrary code execution in the context of the current user. An attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is changed.
CVE-2026-76199	New	8.6	HIGH		0.002	adobe:photoshop, apple:macos, microsoft:windows	Photoshop Desktop is affected by an Uncontrolled Search Path Element vulnerability that could result in arbitrary code execution in the context of the current user. An attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue requires user interaction in that a victim must open a malicious file. Scope is changed.
CVE-2026-77109	New	8.6	HIGH		0.004	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by an Incorrect Authorization vulnerability that could result in privilege escalation. An attacker could leverage this vulnerability to gain elevated access to restricted resources. Exploitation of this issue does not require user interaction. Scope is changed.
CVE-2026-77774	New	8.6	HIGH		0.005	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by an Incorrect Authorization vulnerability that could result in a Security feature bypass. An attacker could leverage this vulnerability to bypass security measures and gain unauthorized read access. Exploitation of this issue does not require user interaction. Scope is changed.
CVE-2026-79721	New	8.6	HIGH		0.003		Code execution can occur in versions of the MLflow platform running version 0.0.1 or newer, enabling a maliciously crafted model artifact to execute arbitrary code on an end user's system when loaded by the project.
CVE-2026-80097	New	8.6	HIGH		0.004		Improper authentication in Microsoft Authenticator allows an unauthorized attacker to elevate privileges locally.
CVE-2026-86509	New	8.6	HIGH		0.004		A flaw has been found in D-Link DIR-895L A1_102b07. This impacts the function sendOffer/sendACK of the file udhpcpd/serverpacket.c of the component udhpcpd. This manipulation causes stack-based buffer overflow. The attack can only be done within the local network. The exploit has been published and may be used.
CVE-2026-86510	New	8.6	HIGH		0.005		A vulnerability has been found in D-Link DIR-822A A_101. Affected is the function tunnel_set_params of the component L2TP Control Message Parser. Such manipulation leads to out-of-bounds write. The attack can be launched remotely. The exploit has been disclosed to the public and may be used.
CVE-2026-86712	New	8.6	HIGH		0.004		SiYuan before 3.8.2 trusts the attacker-writable text/siyuan clipboard MIME type and skips sanitization in the paste handler, allowing code execution in the Node-enabled desktop renderer. Attackers can craft malicious web pages that write to the clipboard, and when pasted into SiYuan, injected scripts execute with full Node.js access through the Electron main process.
CVE-2026-86722	New	8.6	HIGH		0.003		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains an authentication bypass vulnerability where sqlDAL caches empty result sets that writeSql never invalidates. Attackers with a valid password can bypass email two-factor authentication on new devices because the confirmation code hash fails to generate from the stale cached empty result.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-58113	New	8.5	HIGH		0.002		A vulnerability has been identified in Teamcenter V2412 (All versions < V2412.0013), Teamcenter V2506 (All versions < V2506.0010), Teamcenter V2512 (All versions < V2512.2607), Teamcenter V2606 (All versions < V2606.2607). Affected applications do not properly encode user-supplied input reflected into HTML attribute contexts within the authentication redirect flow (/auth/ en...
CVE-2026-67378	New	8.5	HIGH		0.005	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Untrusted pointer dereference in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67379	New	8.5	HIGH		0.006	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Stack-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67636	New	8.5	HIGH		0.005	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-74860	New	8.5	HIGH		0.004		A flaw was found in libxml2 with Python bindings enabled. A remote attacker could exploit this vulnerability by providing a specially crafted XML document containing a Document Type Definition (DTD) with enumerated attribute values. This triggers a double-free error in the SAX attributeDecl callback handler, where a string is freed twice. This flaw can lead to a denial of se...
CVE-2026-75993	New	8.5	HIGH		0.004		ColdFusion is affected by a reflected Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this vulnerability to inject malicious scripts into a web page, potentially gaining elevated access or control over the victim's account or session. Exploitation of this issue requires user interaction in that a victim must open a malicious file. Scope is changed.
CVE-2026-76958	New	8.5	HIGH		0.002		SAP Integration Suite does not sufficiently validate XML documents accepted from untrusted sources in certain internal components. An attacker with low privileges could submit specially crafted XML payloads containing malicious external entity declarations. Successful exploitation could allow the attacker to read sensitive file contents from the server and expose them throug...
CVE-2026-85384	New	8.5	HIGH		0.002		A stack-based buffer overflow vulnerability exists in the httpd component of RE210 AC750 due to improper bounds checking in the splitString function when processing an uploaded configuration file. An authenticated attacker on the local network can upload a crafted configuration file to trigger the overflow, leading to remote code execution. Successful exploitation may a...
CVE-2026-69479	New	8.4	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69638	New	8.4	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code locally.
CVE-2026-75999	New	8.4	HIGH		0.004		ColdFusion is affected by an Improper Input Validation vulnerability that could result in arbitrary code execution in the context of the current user. A low-privileged attacker could exploit this vulnerability to execute arbitrary code. The vulnerable component is restricted to an administrative network zone by default. Exploitation of this issue requires user interaction in...
CVE-2026-77827	New	8.4	HIGH		0.002		Maono Link 3.8.13 MaonoAiServices Windows service allows local privilege escalation for a standard user account via improper write privileges in 'C:\ProgramData\Maono'. Fixed in 4.0.80.
CVE-2026-86819	New	8.4	HIGH		0.001		Waves Central for macOS contains a local privilege escalation in the privileged helper service. The helper authorizes connecting XPC clients by comparing the caller's code-signing certificate chain for equality with its own, rather than validating the caller against a pinned code requirement (application identifier and Team ID). A local, authenticated user can execute code w...
CVE-2026-19203	New	8.3	HIGH		0.003		A client may issue specially crafted HTTP/1.1 chunked requests to a Jetty server that cause Jetty and an intermediary proxy to interpret different request boundaries, potentially resulting in HTTP request smuggling. This is caused by Jetty accepting a lone LF character as a terminator in parts of chunked request parsing. Depending on the Jetty version and configured HTTP...
CVE-2026-69646	New	8.3	HIGH		0.002	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Improper verification of cryptographic signature in Skype for Business allows an unauthorized attacker to perform spoofing over an adjacent network.
CVE-2026-81821	New	8.3	HIGH		0.001		The vulnerability, if exploited, could allow a miscreant with read access to PIMBoards project files to decrypt and view sensitive information.
CVE-2026-81822	New	8.3	HIGH		0.001		The vulnerability, if exploited, could allow a miscreant with read access to PIMBoards project files to reverse engineer PIMBoards users' app-native passwords through computational brute-forcing of weak hashes, potentially allowing elevation to a PIMBoards administrator user.
CVE-2026-69846	New	8.2	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Secure Kernel Mode allows an authorized attacker to elevate privileges locally.
CVE-2026-69906	New	8.2	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Secure Kernel Mode allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-72958	New	8.2	HIGH		0.003		Double free in Windows Credential Guard allows an authorized attacker to elevate privileges locally.
CVE-2026-72961	New	8.2	HIGH		0.003		Out-of-bounds read in Windows Hyper-V allows an authorized attacker to elevate privileges locally.
CVE-2026-72962	New	8.2	HIGH		0.003		Heap-based buffer overflow in Windows USB Video Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-76191	New	8.2	HIGH		0.003	adobe:animate, apple:macos, microsoft:windows	Animate is affected by an Improper Control of Generation of Code ('Code Injection') vulnerability that could result in arbitrary code execution in the context of the current user. A low-privileged attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue requires user interaction in that a victim must open a malicious file. Scope is chan...
CVE-2026-76202	New	8.2	HIGH		0.004	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by an Incorrect Authorization vulnerability that could result in privilege escalation. An attacker could leverage this vulnerability to gain elevated access to sensitive information. Exploitation of this issue does not require user interaction.
CVE-2026-77097	New	8.2	HIGH		0.003	commvault:commvault	Private Metrics Server contained a missing authentication condition affecting metrics upload functionality and service availability. Software customers upgrade to resolved maintenance release. Update Private Metrics Server.
CVE-2026-77968	New	8.2	HIGH		0.002		A flaw was found in hawtio-operator. The operator's ClusterRole grants secrets: [create, get, list, update, watch] across all namespaces. While the operator uses a controller-runtime label-selector cache as a memory optimization, the ServiceAccount token authorizes read access to every Secret in the cluster. The operator also bypasses the cache via direct API calls. Compromi...
CVE-2026-81354	New	8.2	HIGH		0.002	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Heap-based buffer overflow in Windows Hello allows an authorized attacker to elevate privileges locally.
CVE-2026-81356	New	8.2	HIGH		0.003	microsoft:visual_studio_code	Inconsistent interpretation of http requests ('http request/response smuggling') in Visual Studio Code allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-81357	New	8.2	HIGH		0.003	microsoft:visual_studio_code	Server-side request forgery (ssrf) in Visual Studio Code allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-81378	New	8.2	HIGH		0.003	microsoft:visual_studio_code	Interpretation conflict in Visual Studio Code allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-81379	New	8.2	HIGH		0.003	microsoft:visual_studio_code	Not failing securely ('failing open') in Visual Studio Code allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-83939	New	8.2	HIGH		0.003	microsoft:windows_11_26h1	Untrusted pointer dereference in Windows Secure Kernel Mode allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86600	New	8.2	HIGH		0.003		In affected Snowflake drivers, WORKLOAD_IDENTITY authentication requests a cloud workload-identity token and attaches it to the login request without verifying that the configured host is a Snowflake endpoint. An attacker who can modify the connection configuration can cause the driver to mint a fresh attestation and send it to a host they control. The captured token can be ...
CVE-2026-47297	New	8.1	HIGH		0.008		Deserialization of untrusted data in SQL Server allows an unauthorized attacker to execute code over a network.
CVE-2026-55007	New	8.1	HIGH		0.007		Double free in Microsoft Exchange Server allows an unauthorized attacker to execute code over a network.
CVE-2026-69325	New	8.1	HIGH		0.006		Heap-based buffer overflow in Microsoft JScript allows an unauthorized attacker to execute code over a network.
CVE-2026-69380	New	8.1	HIGH		0.007		Missing authorization in Microsoft Exchange Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-69438	New	8.1	HIGH		0.007		Incorrect conversion between numeric types in Microsoft JScript allows an unauthorized attacker to execute code over a network.
CVE-2026-69510	New	8.1	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Stack-based buffer overflow in Windows DHCP Server allows an unauthorized attacker to execute code over a network.
CVE-2026-69524	New	8.1	HIGH		0.007		Use after free in Active Directory Domain Services allows an unauthorized attacker to execute code over a network.
CVE-2026-69530	New	8.1	HIGH		0.006		Use after free in Reliable Multicast Transport Driver (RMCAST) allows an unauthorized attacker to execute code over a network.
CVE-2026-69546	New	8.1	HIGH		0.007		Use after free in Active Directory Domain Services allows an unauthorized attacker to execute code over a network.
CVE-2026-69620	New	8.1	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Stack-based buffer overflow in Windows DHCP Server allows an unauthorized attacker to execute code over a network.
CVE-2026-69680	New	8.1	HIGH		0.003		Origin validation error in Windows DNS allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-69732	New	8.1	HIGH		0.007		Heap-based buffer overflow in Windows Link Layer Topology Discovery Protocol allows an unauthorized attacker to execute code over a network.
CVE-2026-69782	New	8.1	HIGH		0.006		Concurrent execution using shared resource with improper synchronization ('race condition') in DNS Server allows an unauthorized attacker to execute code over a network.
CVE-2026-69786	New	8.1	HIGH		0.007		Heap-based buffer overflow in Windows Text Shaping allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69813	New	8.1	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in Windows DNS allows an unauthorized attacker to execute code over a network.
CVE-2026-69827	New	8.1	HIGH		0.005		Concurrent execution using shared resource with improper synchronization ('race condition') in DNS Server allows an unauthorized attacker to execute code over a network.
CVE-2026-69858	New	8.1	HIGH		0.007	microsoft:windows_server_2022, microsoft:windows_server_2025	Use after free in Windows DNS allows an unauthorized attacker to execute code over a network.
CVE-2026-69989	New	8.1	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in DNS Server allows an unauthorized attacker to execute code over a network.
CVE-2026-70342	New	8.1	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Ancillary Function Driver for WinSock allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-70563	New	8.1	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper link resolution before file access ('link following') in Windows Shell allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-72936	New	8.1	HIGH		0.006		Use after free in Windows SMB Client allows an unauthorized attacker to execute code over a network.
CVE-2026-72981	New	8.1	HIGH		0.005		Use after free in IP Helper allows an unauthorized attacker to execute code over a network.
CVE-2026-72987	New	8.1	HIGH		0.006		Use after free in Windows DNS allows an unauthorized attacker to execute code over a network.
CVE-2026-73313	New	8.1	HIGH		0.004	xenforo:xenforo	XenForo before 2.3.13 contains a multi-factor authentication bypass vulnerability in the passkey TFA provider that allows an authenticated attacker to complete login as another user by submitting their own registered passkey credential during the WebAuthn assertion step. The passkey verification path performs a global credential lookup without validating that the matched cre...
CVE-2026-75021	New	8.1	HIGH		0.004		fastify-cli starts the Node.js Inspector when a debug flag is used, but it ignores the explicit bind address the user supplies and binds the Inspector to a broadly reachable address instead of the intended loopback. As a result the debugging interface can be exposed beyond the local machine, and because the Inspector protocol allows arbitrary code evaluation, a remote party ...
CVE-2026-77505	New	8.1	HIGH		0.005		Use after free in DNS Server allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78444	New	8.1	HIGH		0.005	microsoft:windows_10_1809, microsoft:windows_server_2019, microsoft:windows_server_2022, microsoft:windows_server_2025	Untrusted pointer dereference in Windows Failover Cluster allows an unauthorized attacker to execute code over a network.
CVE-2026-78449	New	8.1	HIGH		0.005		Use after free in Reliable Multicast Transport Driver (RMCAST) allows an unauthorized attacker to execute code over a network.
CVE-2026-78450	New	8.1	HIGH		0.005	microsoft:windows_10_1809, microsoft:windows_server_2019, microsoft:windows_server_2022, microsoft:windows_server_2025	Use after free in Reliable Multicast Transport Driver (RMCAST) allows an unauthorized attacker to execute code over a network.
CVE-2026-78626	New	8.1	HIGH		0.002		The Okta Access Gateway improperly handles input sanitization and regular expression evaluation within its Protected Rule authorization check, resulting in an authorization bypass when an administrator has explicitly configured a Protected Rule policy on one or more application resources.
CVE-2026-82066	New	8.1	HIGH		0.002	mongodb:mongodb	A heap out-of-bounds read security issue exists in the query planning component of MongoDB Server. An authenticated user with database read and write privileges can trigger the security issue through crafted query operations, causing the server to read memory beyond allocated buffer boundaries. The revealed memory contents may be partially observable through diagnostic query...
CVE-2026-83527	New	8.1	HIGH		0.015		An Authentication Bypass vulnerability in Sentry before R10.8.2, R10.7.3 and R10.6.4 allows a remote unauthenticated attacker to gain administrative level access.
CVE-2026-83997	New	8.1	HIGH		0.005	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Use after free in Windows Message Queuing allows an unauthorized attacker to execute code over a network.
CVE-2026-84393	New	8.1	HIGH		0.002		A improper validation of certificate with host mismatch vulnerability in Fortinet FortiOS 7.6.1 through 7.6.6, FortiProxy 7.6.2 through 7.6.6 may allow attacker to information disclosure via <insert attack vector here>
CVE-2026-86720	New	8.1	HIGH		0.003		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 fails to validate ownership of live_restreams_id in resendRestreamer.json.php, allowing authenticated users with canStream to access other users' restream destinations. Attackers can broadcast their live stream to victim-configured restream destinations by supplying arbitrary live_restreams_id values, hijack...
CVE-2026-86723	New	8.1	HIGH		0.003		AVideo through c3edcc274c389816d434acadac07ee78eaf330c1 contains an authentication bypass vulnerability in LoginControl::verifyChallenge() that uses loose comparison (==) instead of strict comparison (===) against unset session values. Attackers with only a password can submit an empty request to verifyChallenge.json.php to bypass PGP two-factor authentication and gain full ...
CVE-2026-28662	New	8.0	HIGH		0.001	google:android	In p2p_process_prov_disc_bootstrap_req of p2p_pd.c, there is a possible out of bounds write due to a heap buffer overflow. This could lead to remote (proximal/adjacent) code execution with no additional execution privileges needed. User interaction is not needed for exploitation.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-55277	New	8.0	HIGH		0.001		In checkUicListenConfigNeeded of RoutingManager.cpp, there is a possible out of bounds write due to a missing bounds check. This could lead to remote (proximal/adjacent) code execution with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-68827	New	8.0	HIGH		0.004		Integer underflow (wrap or wraparound) in Windows GDI+ allows an authorized attacker to elevate privileges over a network.
CVE-2026-68834	New	8.0	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges over a network.
CVE-2026-68838	New	8.0	HIGH		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges over a network.
CVE-2026-68876	New	8.0	HIGH		0.007		Heap-based buffer overflow in Windows Program Compatibility Assistant Service allows an authorized attacker to elevate privileges over a network.
CVE-2026-68878	New	8.0	HIGH		0.005		Stack-based buffer overflow in Windows Fast FAT Driver allows an authorized attacker to elevate privileges over a network.
CVE-2026-68880	New	8.0	HIGH		0.004		Heap-based buffer overflow in Windows Win32K allows an authorized attacker to elevate privileges over a network.
CVE-2026-68894	New	8.0	HIGH		0.006		Heap-based buffer overflow in Windows Error Reporting allows an authorized attacker to elevate privileges over a network.
CVE-2026-69271	New	8.0	HIGH		0.007		Heap-based buffer overflow in Microsoft Standard XPS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69301	New	8.0	HIGH		0.008		Stack-based buffer overflow in Windows Win32K allows an authorized attacker to elevate privileges over a network.
CVE-2026-69322	New	8.0	HIGH		0.007		Double free in Microsoft Windows Search Component allows an authorized attacker to elevate privileges over a network.
CVE-2026-69332	New	8.0	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69346	New	8.0	HIGH		0.007		Heap-based buffer overflow in Windows Print Spooler Components allows an authorized attacker to elevate privileges over a network.
CVE-2026-69365	New	8.0	HIGH		0.007		Out-of-bounds read in Microsoft Local Security Authority Server (lsasrv) allows an authorized attacker to elevate privileges over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69371	New	8.0	HIGH		0.007		Heap-based buffer overflow in Windows Overlay Filter allows an authorized attacker to elevate privileges over a network.
CVE-2026-69412	New	8.0	HIGH		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Stack-based buffer overflow in Windows DHCP Server allows an authorized attacker to execute code over an adjacent network.
CVE-2026-69418	New	8.0	HIGH		0.007		Heap-based buffer overflow in Volume Manager Driver allows an authorized attacker to elevate privileges over a network.
CVE-2026-69423	New	8.0	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Video Driver allows an authorized attacker to elevate privileges over a network.
CVE-2026-69427	New	8.0	HIGH		0.007		Out-of-bounds read in Windows VOLSnap.SYS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69458	New	8.0	HIGH		0.007		Out-of-bounds read in Windows BitLocker allows an authorized attacker to elevate privileges over a network.
CVE-2026-69462	New	8.0	HIGH		0.007		Heap-based buffer overflow in Windows Error Reporting allows an authorized attacker to elevate privileges over a network.
CVE-2026-69481	New	8.0	HIGH		0.007		Heap-based buffer overflow in Windows Enterprise App Management allows an authorized attacker to elevate privileges over a network.
CVE-2026-69503	New	8.0	HIGH		0.008	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Stack-based buffer overflow in Windows USB Driver allows an authorized attacker to elevate privileges over a network.
CVE-2026-69505	New	8.0	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69512	New	8.0	HIGH		0.008		Heap-based buffer overflow in Windows Spaceport.sys allows an authorized attacker to elevate privileges over a network.
CVE-2026-69619	New	8.0	HIGH		0.008		Out-of-bounds read in Windows exFAT File System allows an authorized attacker to elevate privileges over a network.
CVE-2026-69623	New	8.0	HIGH		0.009		Heap-based buffer overflow in Windows HTTP Print Provider allows an authorized attacker to execute code over a network.
CVE-2026-69625	New	8.0	HIGH		0.007		Heap-based buffer overflow in Windows Connected User Experiences and Telemetry allows an authorized attacker to elevate privileges over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69643	New	8.0	HIGH		0.008		Heap-based buffer overflow in Windows Spaceport.sys allows an authorized attacker to elevate privileges over a network.
CVE-2026-69681	New	8.0	HIGH		0.008		Heap-based buffer overflow in Virtual Hard Disk (VHD) Miniport Driver allows an authorized attacker to elevate privileges over a network.
CVE-2026-69689	New	8.0	HIGH		0.008		Out-of-bounds read in Windows Win32K allows an authorized attacker to elevate privileges over a network.
CVE-2026-69714	New	8.0	HIGH		0.008		Stack-based buffer overflow in Windows Device Association Service allows an authorized attacker to elevate privileges over a network.
CVE-2026-69717	New	8.0	HIGH		0.007		Untrusted pointer dereference in Windows Group Policy allows an authorized attacker to elevate privileges over a network.
CVE-2026-69727	New	8.0	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges over a network.
CVE-2026-69762	New	8.0	HIGH		0.007		Stack-based buffer overflow in Windows Win32K allows an authorized attacker to elevate privileges over a network.
CVE-2026-69773	New	8.0	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges over a network.
CVE-2026-69777	New	8.0	HIGH		0.005	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1	Heap-based buffer overflow in Windows DHCP Client allows an authorized attacker to elevate privileges over an adjacent network.
CVE-2026-69807	New	8.0	HIGH		0.009		Improper limitation of a pathname to a restricted directory ('path traversal') in Windows PowerShell allows an authorized attacker to elevate privileges over a network.
CVE-2026-69826	New	8.0	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges over a network.
CVE-2026-69847	New	8.0	HIGH		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows DHCP Server allows an authorized attacker to execute code over an adjacent network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69875	New	8.0	HIGH		0.008	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69876	New	8.0	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in Windows DHCP Server allows an authorized attacker to execute code over an adjacent network.
CVE-2026-83948	New	8.0	HIGH		0.004	microsoft:vm_repair	Improper neutralization of special elements used in a command ('command injection') in Microsoft Azure CLI allows an authorized attacker to execute code over a network.
CVE-2026-0065	New	7.8	HIGH		0.001	google:android	In areBackgroundActivityStartsAllowed of BackgroundLaunchProcessController.java, there is a possible unintended way to launch activities in the background due to a logic error in the code. This could lead to local escalation of privilege with User execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-0084	New	7.8	HIGH		0.001	google:android	In multiple functions of HostEmulationManager.java, there is a possible background activity launch due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28572	New	7.8	HIGH		0.001	google:android	In onCreate of InstallLaunch.kt, there is a possible misleading UI due to a tapjacking/overlay attack. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28583	New	7.8	HIGH		0.001	google:android	In validate_camera_metadata_structure of camera_metadata.c, there is a possible out of bounds write due to a logical error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28590	New	7.8	HIGH		0.001	google:android	In multiple locations, there is a possible improper encryption key validation due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28593	New	7.8	HIGH		0.001	google:android	In getItemList of SettingsFragment.java, there is a possible user interaction bypass due to misleading or insufficient UI. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28594	New	7.8	HIGH		0.001	google:android	In multiple locations, there is a possible use after free due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28599	New	7.8	HIGH		0.001	google:android	In addCreatorToken of ActivityManagerService.java, there is a possible Intent Redirection Bypass due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-28600	New	7.8	HIGH		0.001	google:android	In onCreate of PaymentDefaultDialog.java, there is a possible way to change default payment app due to a confused deputy. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28602	New	7.8	HIGH		0.001	google:android	In setClipboardAccessNotificationsEnabledForUser of ClipboardService.java, there is a possible multi-user isolation due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28603	New	7.8	HIGH		0.001	google:android	In assertSafeToStartCustomActivity of AppRestrictionsFragment.java, there is a possible read/write access to private files due to a confused deputy. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28607	New	7.8	HIGH		0.001	google:android	In multiple functions in multiple locations, there is a possible background activity launch bypass due to a confused deputy. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28611	New	7.8	HIGH		0.001	google:android	In multiple functions of NfcService.java, there is a possible silent payment session hijacking enablement due to a missing permission check. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28612	New	7.8	HIGH		0.001	google:android	In resolveActivity of ActivityStarter.java, there is a possible way to perform Intent Redirection attacks due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28614	New	7.8	HIGH		0.001	google:android	In onCreate of SlicePermissionActivity.java, there is a possible permission bypass due to a confused deputy. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28616	New	7.8	HIGH		0.001	google:android	In Setup Wizard, there is a possible way to force connection to a malicious network due to confused deputy. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28620	New	7.8	HIGH		0.001	google:android	In multiple locations, there is a possible unauthorized URI access due to a permissions bypass. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28624	New	7.8	HIGH		0.001	google:android	In multiple locations, there is a possible read/write access to files without the proper permissions due to a confused deputy. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28631	New	7.8	HIGH		0.001	google:android	In buildMiniResolver of IntentForwarderActivity.java, there is a possible consent bypass due to a tapjacking/overlay attack. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-28634	New	7.8	HIGH		0.001	google:android	In handleUssdRequest of PhoneInterfaceManager.java, there is a possible way to send a USSD request without permission due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28636	New	7.8	HIGH		0.001	google:android	In setupLayout of PickActivity.java, there is a possible bypass of the "Install unknown apps" security restriction due to a confused deputy. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28639	New	7.8	HIGH		0.001	google:android	In rw_mfc_handle_read_op of rw_mfc.cc, there is a possible out of bounds write due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28642	New	7.8	HIGH		0.001	google:android	In executeRequest of ActivityStarter.java, there is a possible background activity launch due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28644	New	7.8	HIGH		0.001	google:android	In startNextMatchingActivity of ActivityTaskManagerService.java, there is a possible permission bypass due to a confused deputy. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28650	New	7.8	HIGH		0.001	google:android	In setHiddenWhileSuspended of WindowState.java, there is a possible overlay bypass due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28653	New	7.8	HIGH		0.001	google:android	In multiple functions of rw_t3t.cc, there is a possible out of bounds write due to an integer overflow. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28655	New	7.8	HIGH		0.001	google:android	In multiple functions of RemoteViews.java, there is a possible background activity launch bypass due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28657	New	7.8	HIGH		0.001	google:android	In onActivityResult of AppWidgetConfigActivityProxy.java, there is a possible unauthorized URI permission grant due to a confused deputy. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28658	New	7.8	HIGH		0.001	google:android	In findMetaAuthUid of AccountsDb.java, there is a possible frp bypass due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28659	New	7.8	HIGH		0.001	google:android_xr	In MicroXR Blobstore, there is a possible way to access other app's files due to a missing permission check. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28663	New	7.8	HIGH		0.001		In buildIntentSenderForUser of LauncherAppsService.java, there is a possible way to launch an activity from the background due to BAL Bypass. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-28664	New	7.8	HIGH		0.001		In WriteImageToDisk of runtime_image.cc, there is a possible file tampering due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28668	New	7.8	HIGH		0.001		In LimitRealloc of malloc_limit.cpp, there is a possible use after free due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-45515	New	7.8	HIGH		0.001		In a2dp_vendor_opus_decoder_decode_packet of a2dp_vendor_opus_decoder.cc, there is a possible out of bounds write due to a heap buffer overflow. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-45520	New	7.8	HIGH		0.001		In onAttach of BiometricsSettingsBase.java, there is a possible authentication bypass due to a confused deputy. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-45531	New	7.8	HIGH		0.001		In read_boot_region of fsck.c, there is a possible out of bounds read due to a heap buffer overflow. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-49881	New	7.8	HIGH		0.001		In serviceClassExists of InCallController.java, there is a possible arbitrary code execution due to a logic error in the code. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-49884	New	7.8	HIGH		0.001		In rw_mfc_handle_read_op of rw_mfc.cc, there is a possible out of bounds write due to an incorrect bounds check. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-49887	New	7.8	HIGH		0.001		In maybeRemoveInvalidInstallerPackageName of InstallRepository.kt, there is a possible unauthorized app update due to a permissions bypass. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-49918	New	7.8	HIGH		0.001		In multiple functions, there is a possible out of bounds write due to an integer overflow. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-49919	New	7.8	HIGH		0.001		In tt_face_colr_blend_layer of ttcolr.c, there is a possible remote code execution due to an integer overflow. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-49927	New	7.8	HIGH		0.001		In multiple locations, there is a possible out of bounds write due to an integer overflow. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-49932	New	7.8	HIGH		0.001		In parseParts of PduParser.java, there is a possible out of bounds read due to a heap buffer overflow. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-55273	New	7.8	HIGH		0.001		In AppendCommentLine of AnnotationProcessor.cpp, there is a possible supply chain risk due to improper input validation. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-55285	New	7.8	HIGH		0.001		In openLogicalChannel of multiple files, there is a possible out-of-bounds write due to a missing bounds check. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-55294	New	7.8	HIGH		0.001		In ihevcd_get_tu_data_size of ihevcd_utils.c, there is a possible out of bounds write due to a heap buffer overflow. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-56172	New	7.8	HIGH		0.003		Use after free in Windows VHD miniport driver allows an authorized attacker to elevate privileges locally.
CVE-2026-56177	New	7.8	HIGH		0.003		Use after free in Windows Server allows an authorized attacker to elevate privileges locally.
CVE-2026-56198	New	7.8	HIGH		0.002		Out-of-bounds read in Microsoft Trace Data Helper allows an authorized attacker to elevate privileges locally.
CVE-2026-5729	New	7.8	HIGH		0.001		Use After Free vulnerability in Arm Ltd Valhall GPU Kernel Driver, Arm Ltd Arm 5th Gen GPU Architecture Kernel Driver allows a local non-privileged user process to perform valid GPU processing operations to access already freed memory. This issue affects Valhall GPU Kernel Driver: from r50p0 through r54p3, r55p0; Arm 5th Gen GPU Architecture Kernel Driver: from r50p0 thro...
CVE-2026-58599	New	7.8	HIGH		0.003		Heap-based buffer overflow in Microsoft Windows Codecs Library allows an unauthorized attacker to execute code locally.
CVE-2026-58600	New	7.8	HIGH		0.003		Heap-based buffer overflow in Microsoft Windows Codecs Library allows an unauthorized attacker to elevate privileges locally.
CVE-2026-58611	New	7.8	HIGH		0.002	microsoft:xbox_gaming_services	Improper authorization in Xbox Gaming Services allows an authorized attacker to elevate privileges locally.
CVE-2026-58820	New	7.8	HIGH		0.001		In multiple locations, there is a possible memory safety issue due to integer overflow. This could lead to local escalation of privilege with no additional execution privileges required.
CVE-2026-58823	New	7.8	HIGH		0.001		In stpropnci_process_std of stpropnci_std.cc, there is a possible memory safety issue due to a missing bounds check. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-58839	New	7.8	HIGH		0.001		In forEachLine of MountRegistry.cpp, there is a possible out of bounds read due to a buffer overflow. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-58846	New	7.8	HIGH		0.001		In kvm_iommu_map_sg of iommu.c, there is a possible use after free due to a missing permission check. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-58874	New	7.8	HIGH		0.001		In multiple functions of SmsController.java, there is a possible escalation of privilege due to a missing permission check. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-58941	New	7.8	HIGH		0.001		In multiple functions of iommu.c, there is a possible out of bounds read/write due to improper input validation. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-62697	New	7.8	HIGH		0.003		Use after free in Windows Push Notifications allows an authorized attacker to elevate privileges locally.
CVE-2026-62804	New	7.8	HIGH		0.003	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	External control of file name or path in Microsoft Office Word allows an unauthorized attacker to execute code locally.
CVE-2026-62810	New	7.8	HIGH		0.002		Heap-based buffer overflow in Active Directory Certificate Services (AD CS) allows an authorized attacker to elevate privileges locally.
CVE-2026-68787	New	7.8	HIGH		0.002	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code locally.
CVE-2026-68832	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-68841	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-68844	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Storage Spaces Controller allows an authorized attacker to execute code locally.
CVE-2026-68845	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Program Compatibility Assistant Service allows an authorized attacker to elevate privileges locally.
CVE-2026-68848	New	7.8	HIGH		0.002		Heap-based buffer overflow in Windows Print Spooler Components allows an authorized attacker to elevate privileges locally.
CVE-2026-68850	New	7.8	HIGH		0.002		Heap-based buffer overflow in Microsoft Account allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-68875	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Buffer over-read in Windows NTFS allows an authorized attacker to execute code locally.
CVE-2026-68877	New	7.8	HIGH		0.002		Heap-based buffer overflow in Windows Storage Spaces Controller allows an authorized attacker to execute code locally.
CVE-2026-68885	New	7.8	HIGH		0.003		Heap-based buffer overflow in Microsoft Standard XPS allows an authorized attacker to elevate privileges locally.
CVE-2026-68888	New	7.8	HIGH		0.003		Heap-based buffer overflow in Microsoft Standard XPS allows an authorized attacker to elevate privileges locally.
CVE-2026-68890	New	7.8	HIGH		0.002		Heap-based buffer overflow in Microsoft Standard XPS allows an authorized attacker to elevate privileges locally.
CVE-2026-68892	New	7.8	HIGH		0.002		Heap-based buffer overflow in Microsoft Standard XPS allows an authorized attacker to elevate privileges locally.
CVE-2026-68896	New	7.8	HIGH		0.004		Absolute path traversal in Microsoft Windows Search Component allows an authorized attacker to elevate privileges locally.
CVE-2026-69265	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-69269	New	7.8	HIGH		0.003		Integer underflow (wrap or wraparound) in Microsoft Standard XPS allows an authorized attacker to elevate privileges locally.
CVE-2026-69270	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69277	New	7.8	HIGH		0.003		Stack-based buffer overflow in Microsoft Local Security Authority Server (lsasrv) allows an authorized attacker to elevate privileges locally.
CVE-2026-69283	New	7.8	HIGH		0.002		Heap-based buffer overflow in Windows CD-ROM Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69284	New	7.8	HIGH		0.002		Heap-based buffer overflow in Windows DCOM Server allows an authorized attacker to elevate privileges locally.
CVE-2026-69289	New	7.8	HIGH		0.004		Improper link resolution before file access ('link following') in Windows Setup Files Cleanup allows an authorized attacker to elevate privileges locally.
CVE-2026-69290	New	7.8	HIGH		0.002		Stack-based buffer overflow in Windows Storage Spaces Controller allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69293	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69295	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69298	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69307	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69312	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-69323	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69324	New	7.8	HIGH		0.003		Access of resource using incompatible type ('type confusion') in Windows Performance Monitor allows an authorized attacker to elevate privileges locally.
CVE-2026-69328	New	7.8	HIGH		0.003		Untrusted search path in Windows Storage allows an authorized attacker to elevate privileges locally.
CVE-2026-69348	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69352	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69359	New	7.8	HIGH		0.003		Heap-based buffer overflow in Active Directory Domain Services allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69368	New	7.8	HIGH		0.002		Heap-based buffer overflow in Windows Overlay Filter allows an authorized attacker to elevate privileges locally.
CVE-2026-69377	New	7.8	HIGH		0.003		Missing authorization in Windows Modern Device Management (MDM) allows an authorized attacker to elevate privileges locally.
CVE-2026-69389	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Storage Management Provider allows an authorized attacker to elevate privileges locally.
CVE-2026-69391	New	7.8	HIGH		0.003		Stack-based buffer overflow in Windows Broker Infrastructure Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69392	New	7.8	HIGH		0.003		Use after free in Windows Shell allows an authorized attacker to elevate privileges locally.
CVE-2026-69407	New	7.8	HIGH		0.003		Integer overflow or wraparound in Volume Manager Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69420	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows VOLSnap.SYS allows an authorized attacker to elevate privileges locally.
CVE-2026-69421	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer underflow (wrap or wraparound) in Windows Kernel Mode Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69424	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Distributed File System (DFS) allows an authorized attacker to elevate privileges locally.
CVE-2026-69426	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows VOLSnap.SYS allows an authorized attacker to execute code locally.
CVE-2026-69432	New	7.8	HIGH		0.003		Heap-based buffer overflow in Volume Manager Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69433	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Error Reporting allows an authorized attacker to elevate privileges locally.
CVE-2026-69436	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Error Reporting allows an authorized attacker to elevate privileges locally.
CVE-2026-69444	New	7.8	HIGH		0.003		Heap-based buffer overflow in Microsoft Windows Speech allows an authorized attacker to elevate privileges locally.
CVE-2026-69445	New	7.8	HIGH		0.004		Improper limitation of a pathname to a restricted directory ('path traversal') in Windows Compressed Folder allows an authorized attacker to elevate privileges locally.
CVE-2026-69447	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Audio Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69450	New	7.8	HIGH		0.003		Out-of-bounds read in Windows Error Reporting allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69455	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Remote Access Connection Manager allows an authorized attacker to elevate privileges locally.
CVE-2026-69456	New	7.8	HIGH		0.003		Heap-based buffer overflow in Microsoft Windows Speech allows an authorized attacker to elevate privileges locally.
CVE-2026-69459	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Power Dependency Coordinator allows an authorized attacker to elevate privileges locally.
CVE-2026-69467	New	7.8	HIGH		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Stack-based buffer overflow in Microsoft Graphics Component allows an authorized attacker to elevate privileges locally.
CVE-2026-69475	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Untrusted pointer dereference in Windows Remote Desktop Services allows an authorized attacker to elevate privileges locally.
CVE-2026-69476	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69478	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69480	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Partition Management Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69489	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69508	New	7.8	HIGH		0.003		Stack-based buffer overflow in Windows MIDI Service Module allows an authorized attacker to elevate privileges locally.
CVE-2026-69509	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Fax Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69513	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Error Reporting allows an authorized attacker to elevate privileges locally.
CVE-2026-69528	New	7.8	HIGH		0.003		Missing authentication for critical function in Windows Shell allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69532	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-69534	New	7.8	HIGH		0.006		Improper neutralization of special elements used in a command ('command injection') in Windows Program Compatibility Assistant Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69535	New	7.8	HIGH		0.002		Numeric truncation error in Windows Spaceport.sys allows an authorized attacker to elevate privileges locally.
CVE-2026-69538	New	7.8	HIGH		0.002		Out-of-bounds read in Windows Spaceport.sys allows an authorized attacker to execute code locally.
CVE-2026-69541	New	7.8	HIGH		0.003		Heap-based buffer overflow in Virtual Hard Disk (VHD) Miniport Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69542	New	7.8	HIGH		0.002		Heap-based buffer overflow in Windows Camera Frame Server Monitor allows an authorized attacker to elevate privileges locally.
CVE-2026-69544	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows SMB Client allows an authorized attacker to elevate privileges locally.
CVE-2026-69561	New	7.8	HIGH		0.003		Out-of-bounds read in Windows CD-ROM Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69571	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69576	New	7.8	HIGH		0.003		Use after free in Graphic Fonts allows an authorized attacker to elevate privileges locally.
CVE-2026-69580	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69582	New	7.8	HIGH		0.003		Buffer over-read in Windows Volume Manager Extension Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69583	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69584	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows USB Video Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69585	New	7.8	HIGH		0.004		Incorrect type conversion or cast in Microsoft Windows Search Component allows an authorized attacker to elevate privileges locally.
CVE-2026-69589	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69592	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Universal Disk Format File System Driver (UDFS) allows an authorized attacker to elevate privileges locally.
CVE-2026-69593	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69594	New	7.8	HIGH		0.003		Heap-based buffer overflow in Microsoft Local Security Authority Server (lsasrv) allows an authorized attacker to elevate privileges locally.
CVE-2026-69604	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Audio Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69608	New	7.8	HIGH		0.003		Integer overflow or wraparound in Microsoft Windows Search Component allows an authorized attacker to elevate privileges locally.
CVE-2026-69612	New	7.8	HIGH		0.004		Absolute path traversal in Windows Error Reporting allows an authorized attacker to elevate privileges locally.
CVE-2026-69685	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Kerberos allows an authorized attacker to elevate privileges locally.
CVE-2026-69687	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer underflow (wrap or wraparound) in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69691	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Spaceport.sys allows an authorized attacker to elevate privileges locally.
CVE-2026-69707	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69709	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an authorized attacker to execute code locally.
CVE-2026-69720	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows MIDI Service Module allows an authorized attacker to elevate privileges locally.
CVE-2026-69725	New	7.8	HIGH		0.003		Double free in Windows Hello allows an authorized attacker to elevate privileges locally.
CVE-2026-69731	New	7.8	HIGH		0.003		Heap-based buffer overflow in HID class driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69738	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69758	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Universal Disk Format File System Driver (UDFS) allows an authorized attacker to elevate privileges locally.
CVE-2026-69785	New	7.8	HIGH		0.003		Untrusted search path in Windows Smart Card allows an authorized attacker to elevate privileges locally.
CVE-2026-69787	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69790	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Credential Providers allows an authorized attacker to elevate privileges locally.
CVE-2026-69799	New	7.8	HIGH		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Hello allows an authorized attacker to elevate privileges locally.
CVE-2026-69801	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Audio Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69821	New	7.8	HIGH		0.003		Improper encoding or escaping of output in Active Directory Certificate Services (AD CS) allows an authorized attacker to elevate privileges locally.
CVE-2026-69822	New	7.8	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Numeric truncation error in Windows Kerberos allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69841	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Encrypting File System (EFS) allows an authorized attacker to elevate privileges locally.
CVE-2026-69844	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69864	New	7.8	HIGH		0.002	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Use after free in Windows Hello allows an authorized attacker to elevate privileges locally.
CVE-2026-69900	New	7.8	HIGH		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Untrusted pointer dereference in Kernel Streaming WOW Thunk Service Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69907	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper handling of insufficient permissions or privileges in Windows Enterprise App Management allows an authorized attacker to elevate privileges locally.
CVE-2026-69921	New	7.8	HIGH		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Heap-based buffer overflow in Windows Print Spooler Components allows an authorized attacker to elevate privileges locally.
CVE-2026-70289	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Win32 Kernel Subsystem allows an authorized attacker to elevate privileges locally.
CVE-2026-70334	New	7.8	HIGH		0.004	microsoft:visual_studio_code	Incomplete list of disallowed inputs in Visual Studio Code allows an unauthorized attacker to bypass a security feature locally.
CVE-2026-70564	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Print Spooler Components allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-70569	New	7.8	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Out-of-bounds read in Windows Spaceport.sys allows an authorized attacker to elevate privileges locally.
CVE-2026-70572	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-70574	New	7.8	HIGH		0.003		Out-of-bounds read in Virtual Hard Disk (VHD) Miniport Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-70581	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-70583	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Core Messaging allows an authorized attacker to elevate privileges locally.
CVE-2026-70584	New	7.8	HIGH		0.003		Access of resource using incompatible type ('type confusion') in Windows Core Messaging allows an authorized attacker to elevate privileges locally.
CVE-2026-71334	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NFS Portmapper allows an authorized attacker to elevate privileges locally.
CVE-2026-71337	New	7.8	HIGH		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Stack-based buffer overflow in Windows Storage Management Provider allows an authorized attacker to elevate privileges locally.
CVE-2026-71343	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Remote Access Connection Manager allows an authorized attacker to execute code locally.
CVE-2026-71345	New	7.8	HIGH		0.003		Out-of-bounds write in Windows Spaceport.sys allows an authorized attacker to execute code locally.
CVE-2026-72929	New	7.8	HIGH		0.002		Improper validation of integrity check value in Windows Installer allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-72941	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72944	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Fax Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72946	New	7.8	HIGH		0.003		Heap-based buffer overflow in Storage Port Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-72953	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows USB Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-72957	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Deployment Services allows an authorized attacker to execute code locally.
CVE-2026-72965	New	7.8	HIGH		0.003		Use after free in Windows WebClient Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72967	New	7.8	HIGH		0.003		Heap-based buffer overflow in Windows Network Connection Broker allows an authorized attacker to elevate privileges locally.
CVE-2026-72988	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72990	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72991	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72992	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72993	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-72994	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72995	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72996	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72997	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73000	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73001	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73002	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73007	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-73011	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73014	New	7.8	HIGH		0.003		Missing authorization in Data Sharing Service Client allows an authorized attacker to elevate privileges locally.
CVE-2026-73015	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73020	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73021	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73024	New	7.8	HIGH		0.002		Heap-based buffer overflow in Windows Services for NFS ONCRPC XDR Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-73026	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-7476	New	7.8	HIGH		0.001		Use After Free vulnerability in Arm Ltd Bifrost GPU Kernel Driver, Arm Ltd Valhall GPU Kernel Driver, Arm Ltd Arm 5th Gen GPU Architecture Kernel Driver allows a local non-privileged user process to perform improper GPU memory processing operations to access already freed memory. This issue affects Bifrost GPU Kernel Driver: from r49p3 through r49p5, r51p0, from r54p1 thr...
CVE-2026-7477	New	7.8	HIGH		0.001		Use After Free vulnerability in Arm Ltd Bifrost GPU Kernel Driver, Arm Ltd Valhall GPU Kernel Driver, Arm Ltd Arm 5th Gen GPU Architecture Kernel Driver allows a local non-privileged user process to perform valid GPU memory processing operations to access already freed memory. This issue affects Bifrost GPU Kernel Driver: from r44p0 through r49p4, from r50p0 through r51p0...
CVE-2026-75631	New	7.8	HIGH		0.002	adobe:photoshop, apple:macos, microsoft:windows	Photoshop Desktop is affected by an out-of-bounds write vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75771	New	7.8	HIGH		0.002	adobe:photoshop, apple:macos, microsoft:windows	Photoshop Desktop is affected by an Integer Overflow or Wraparound vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-75862	New	7.8	HIGH		0.002	adobe:photoshop, apple:macos, microsoft:windows	Photoshop Desktop is affected by an Integer Overflow or Wraparound vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-75863	New	7.8	HIGH		0.002	adobe:photoshop, apple:macos, microsoft:windows	Photoshop Desktop is affected by an Integer Overflow or Wraparound vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-75992	New	7.8	HIGH		0.002		Illustrator is affected by an out-of-bounds write vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-76967	New	7.8	HIGH		0.002		SAP NetWeaver Business Client does not perform sufficient validation when processing certain locally stored data during application startup. An attacker with low privileges on the local system could replace this data with specially crafted content. When the application is next launched, the crafted content is processed and could lead to arbitrary code execution in the contex...
CVE-2026-77091	New	7.8	HIGH		0.001	commvault:commvault	DataCube contained a path traversal issue affecting security feature enforcement. Software customers upgrade to resolved maintenance release. Update Content Extractor and Index Store.
CVE-2026-77489	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Null pointer dereference in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-77500	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Release of invalid pointer or reference in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-77503	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an unauthorized attacker to elevate privileges locally.
CVE-2026-77904	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Volume Manager Extension Driver allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78447	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-78448	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-79907	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Double Free vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-79908	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an out-of-bounds write vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-79909	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Use After Free vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-80075	New	7.8	HIGH		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:wi	Heap-based buffer overflow in Windows Work Folders allows an authorized attacker to elevate privileges locally.
CVE-2026-80161	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an Access of Resource Using Incompatible Type ('Type Confusion') vulnerability that could result in arbitrary code execution in the context of the current user. An attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81353	New	7.8	HIGH		0.004		Heap-based buffer overflow in Microsoft Windows Codecs Library allows an unauthorized attacker to execute code locally.
CVE-2026-81386	New	7.8	HIGH		0.003	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Heap-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81388	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Stack-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81396	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Stack-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81397	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Heap-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81398	New	7.8	HIGH		0.003	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Heap-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81947	New	7.8	HIGH		0.003	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Heap-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81948	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Heap-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81949	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Integer overflow or wraparound in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81950	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Double free in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81951	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Heap-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81953	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Stack-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81954	New	7.8	HIGH		0.003	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Use after free in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81956	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Out-of-bounds read in Microsoft Office Excel allows an unauthorized attacker to execute code locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81957	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Out-of-bounds read in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81959	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Heap-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81960	New	7.8	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Heap-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-81973	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Use After Free vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81975	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Use After Free vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81976	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Use After Free vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81979	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an out-of-bounds write vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81980	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an out-of-bounds write vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81981	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an out-of-bounds write vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81983	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an out-of-bounds write vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81985	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Use After Free vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81986	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Use After Free vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81987	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an Integer Overflow or Wraparound vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81988	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Use After Free vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81989	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Use After Free vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81990	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Use After Free vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81992	New	7.8	HIGH		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Heap-based Buffer Overflow vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-82005	New	7.8	HIGH		0.002	adobe:photoshop, apple:macos, microsoft:windows	Photoshop Desktop is affected by an out-of-bounds write vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-82006	New	7.8	HIGH		0.002	adobe:photoshop, apple:macos, microsoft:windows	Photoshop Desktop is affected by a Heap-based Buffer Overflow vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-82007	New	7.8	HIGH		0.002	adobe:photoshop, apple:macos, microsoft:windows	Photoshop Desktop is affected by an Integer Overflow or Wraparound vulnerability that could result in arbitrary code execution in the context of the current user. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-83498	New	7.8	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Untrusted pointer dereference in Windows Virtualization-Based Security (VBS) Enclave allows an authorized attacker to elevate privileges locally.
CVE-2026-83942	New	7.8	HIGH		0.002	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Missing authorization in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-83952	New	7.8	HIGH		0.002	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Heap-based buffer overflow in Windows Resilient File System (ReFS) allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83954	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83955	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83967	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83968	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83969	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83970	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83971	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83972	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83973	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83974	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83975	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83976	New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83977	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83978	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83979	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83980	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83981	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83982	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83983	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83985	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83986	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83987	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83988	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83990	New	7.8	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Stack-based buffer overflow in Microsoft Graphics Component allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83995	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-84000	New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Microsoft Graphics Component allows an authorized attacker to execute code locally.
CVE-2026-85983	New	7.8	HIGH		0.001		The Auth0 AD/LDAP Connector improperly processes a configuration value during service startup. This allows a low-privileged user on the host system to modify the connector's configuration. When the service restarts, the modified configuration can lead to code execution with the privileges of the service account.
CVE-2026-9034	New	7.8	HIGH		0.001		Use After Free vulnerability in Arm Ltd Bifrost GPU Userspace Driver, Arm Ltd Valhall GPU Userspace Driver, Arm Ltd Arm 5th Gen GPU Architecture Userspace Driver allows a non-privileged user process to perform valid GPU processing operations, including via WebGL or WebGPU, to access already freed memory. This issue affects Bifrost GPU Userspace Driver: from r42p0 through ...
CVE-2026-19397	New	7.7	HIGH		0.002		Missing authentication for a critical function in ASUS Control Center Express Agent allows an unauthenticated nearby user to control the host via a direct connection to the agent when the host has an active login session. Refer to the ' Security Update for ASUS Control Center Express Agent ' section on the ASUS Security Advisory for more information.
CVE-2026-66767	New	7.7	HIGH		0.003		SAP NetWeaver Application Server for ABAP and ABAP Platform allows an unauthenticated user to send a specially crafted packet that triggers reprocessing of a previously buffered user request, potentially hijacking another user's session under narrow timing conditions. Successful exploitation could result in high impact on confidentiality and integrity, with low impact on ava...
CVE-2026-69683	New	7.7	HIGH		0.008	microsoft:sharepoint_server	Server-side request forgery (ssrf) in Microsoft Office SharePoint allows an authorized attacker to disclose information over a network.
CVE-2026-73315	New	7.7	HIGH		0.003	xenforo:xenforo	XenForo before 2.3.13 contains a server-side request forgery vulnerability in the PayPal REST webhook handler that allows unauthenticated attackers to cause the server to make outbound HTTP requests to arbitrary destinations by supplying a crafted certificate URL in webhook headers without scheme, hostname, or allowlist validation. Attackers can submit a crafted POST to the ...
CVE-2026-77909	New	7.7	HIGH		0.006		Insufficiently protected credentials in Azure CycleCloud allows an authorized attacker to disclose information over a network.
CVE-2026-78623	New	7.7	HIGH		0.002		The Okta Access Gateway does not sanitize SAML assertion values before interpolating them into database queries in the advanced mode datastore configuration. The unsanitized values are substituted directly into the query string prior to preparation, resulting in unintended SQL execution against the configured backend database.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-82537	New	7.7	HIGH		0.003		Roo-Code through 3.54.0 contains an auto-approve bypass vulnerability that allows attackers to execute denied shell commands by exploiting a word-boundary mismatch in comment handling between the approval gate's shell parser and bash. Attackers can craft a command string with an allowlisted word immediately followed by a hash character, separator, and denied command to pass ...
CVE-2026-9040	New	7.7	HIGH		0.001		A race condition vulnerability in Arm Ltd Bifrost GPU Kernel Driver, Arm Ltd Valhall GPU Kernel Driver, Arm Ltd Arm 5th Gen GPU Architecture Kernel Driver allows a local non-privileged user process to perform improper GPU memory processing operations to cause a denial of service or disclose sensitive information. This issue affects Bifrost GPU Kernel Driver: from r12p0 th...
CVE-2026-77110	New	7.6	HIGH		0.007	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by an Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') vulnerability that could result in a Security feature bypass. An attacker with high privileges could leverage this vulnerability to access unauthorized files or directories outside the intended restrictions, causing a limited disruption to availability. Exploitatio...
CVE-2026-82053	New	7.6	HIGH		0.002	mongodb:mongodb	A security issue exists in MongoDB's LDAP authorization integration where pooled LDAP connections can retain stale authentication identities after user authentication under certain configurations. Subsequent authorization queries may execute under an unintended LDAP identity rather than the expected one. This can result in incorrect role assignments based on the LDAP directo...
CVE-2026-86073	New	7.6	HIGH		0.002	n8n:n8n	n8n is an open source workflow automation platform. Prior to 2.37.7 and 2.38.1, the OAuth token endpoint bound an authorization code's first access token to the consented resource but did not bind its refresh token. Refreshing checked only that the requested resource was registered, not that it matched the original grant. An OAuth client approved for one workflow could subst...
CVE-2026-0860	New	7.5	HIGH		0.002		Exposure of Sensitive Information to an Unauthorized Actor vulnerability in Arm Ltd Valhall GPU Kernel Driver, Arm Ltd Arm 5th Gen GPU Architecture Kernel Driver allows a local non-privileged user process to perform improper GPU memory processing operations to gain access to sensitive kernel information. This issue affects Valhall GPU Kernel Driver: from r29p0 through r49...
CVE-2026-16025	New	7.5	HIGH		0.003		Improper validation of specified quantity in input vulnerability in PayTR Payment and Electronic Money Institution Inc. PayTR Virtual Pos iFrame API (v9x) WHMCS Module allows Input Data Manipulation. This issue affects PayTR Virtual Pos iFrame API (v9x) WHMCS Module: from v9.0.0 before v9.0.3.
CVE-2026-16037	New	7.5	HIGH		0.003		Observable timing discrepancy vulnerability in PayTR Payment and Electronic Money Institution Inc. PayTR Virtual Pos iFrame API (v9x) WHMCS Module allows Black Box Reverse Engineering. This issue affects PayTR Virtual Pos iFrame API (v9x) WHMCS Module: from v9.0.0 before v9.0.3.
CVE-2026-16497	New	7.5	HIGH		0.004		NVIDIA Triton Inference Server for Linux contains a vulnerability where an attacker could cause excessive iteration. A successful exploit of this vulnerability might lead to denial of service.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-28604	New	7.5	HIGH		0.002	google:android	In multiple locations, there is a possible use after free due to a race condition. This could lead to remote code execution with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-3174	New	7.5	HIGH		0.003		The Event Tickets and Registration plugin for WordPress is vulnerable to unauthorized modification of data due to a missing capability check on the Stripe OAuth return endpoint in all versions up to, and including, 5.27.4. This makes it possible for unauthenticated attackers to overwrite the site's Stripe merchant credentials (access tokens, publishable keys, and account ID)...
CVE-2026-47625	New	7.5	HIGH		0.004		NVIDIA Triton Inference Server for Linux contains a vulnerability where an attacker could abuse missing authorization. A successful exploit of this vulnerability might lead to information disclosure, data tampering, and denial of service.
CVE-2026-48888	New	7.5	HIGH		0.003		Allocation of Resources Without Limits or Throttling vulnerability in Automattic WooCommerce allows HTTP DoS. This issue affects WooCommerce: from n/a before 11.1.0.
CVE-2026-57098	New	7.5	HIGH		0.006	microsoft:remote_desktop_client	Improper verification of cryptographic signature in Windows RDP Client allows an unauthorized attacker to disclose information over a network.
CVE-2026-57099	New	7.5	HIGH		0.008		Allocation of resources without limits or throttling in ASP.NET Core allows an unauthorized attacker to deny service over a network.
CVE-2026-62759	New	7.5	HIGH		0.003		Authentication bypass by spoofing in Windows Netlogon allows an unauthorized attacker to perform spoofing over an adjacent network.
CVE-2026-62813	New	7.5	HIGH		0.006		Use after free in Active Directory Domain Services allows an authorized attacker to execute code over a network.
CVE-2026-66304	New	7.5	HIGH		0.007	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Server-side request forgery (ssrf) in Skype for Business allows an unauthorized attacker to disclose information over a network.
CVE-2026-66307	New	7.5	HIGH		0.006	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Integer underflow (wrap or wraparound) in Skype for Business allows an unauthorized attacker to deny service over a network.
CVE-2026-67376	New	7.5	HIGH		0.008	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Integer overflow or wraparound in SQL Server allows an unauthorized attacker to deny service over a network.
CVE-2026-68887	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Message Queuing Queue Manager allows an unauthorized attacker to deny service over a network.
CVE-2026-69329	New	7.5	HIGH		0.011		Out-of-bounds read in BranchCache allows an unauthorized attacker to deny service over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69342	New	7.5	HIGH		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-69378	New	7.5	HIGH		0.011		Uncontrolled recursion in Microsoft Exchange Server allows an unauthorized attacker to deny service over a network.
CVE-2026-69397	New	7.5	HIGH		0.006		Use after free in OpenSSH for Windows allows an unauthorized attacker to execute code over a network.
CVE-2026-69428	New	7.5	HIGH		0.011		Out-of-bounds read in Windows LDAP - Lightweight Directory Access Protocol allows an unauthorized attacker to deny service over a network.
CVE-2026-69429	New	7.5	HIGH		0.006		Heap-based buffer overflow in Windows IKE Extension allows an authorized attacker to execute code over a network.
CVE-2026-69443	New	7.5	HIGH		0.01		Out-of-bounds read in Windows Device Health Attestation (DHA) allows an unauthorized attacker to disclose information over a network.
CVE-2026-69514	New	7.5	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Remote Desktop Services allows an authorized attacker to execute code over a network.
CVE-2026-69539	New	7.5	HIGH		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Desktop Services allows an authorized attacker to execute code over a network.
CVE-2026-69587	New	7.5	HIGH		0.012		Null pointer dereference in Windows IKE Extension allows an unauthorized attacker to deny service over a network.
CVE-2026-69588	New	7.5	HIGH		0.012		Missing release of memory after effective lifetime in Windows TCP/IP allows an unauthorized attacker to deny service over a network.
CVE-2026-69599	New	7.5	HIGH		0.007	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Use after free in Windows Remote Desktop Services allows an authorized attacker to execute code over a network.
CVE-2026-69607	New	7.5	HIGH		0.006		Use after free in Windows Deployment Services allows an unauthorized attacker to execute code over a network.
CVE-2026-69631	New	7.5	HIGH		0.012		Integer overflow or wraparound in Windows DNS allows an unauthorized attacker to deny service over a network.
CVE-2026-69710	New	7.5	HIGH		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Hello allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69739	New	7.5	HIGH		0.009	microsoft:365_apps, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Out-of-bounds read in Microsoft Office allows an unauthorized attacker to disclose information over a network.
CVE-2026-69744	New	7.5	HIGH		0.011		Null pointer dereference in Windows Kerberos allows an unauthorized attacker to deny service over a network.
CVE-2026-69760	New	7.5	HIGH		0.011		Out-of-bounds read in Windows Kerberos allows an unauthorized attacker to deny service over a network.
CVE-2026-69793	New	7.5	HIGH		0.008		Improper validation of consistency within input in Windows TCP/IP allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-69803	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to disclose information over a network.
CVE-2026-69804	New	7.5	HIGH		0.005	microsoft:sharepoint_server	Time-of-check time-of-use (toctou) race condition in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.
CVE-2026-69805	New	7.5	HIGH		0.005		External control of file name or path in .NET allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-69809	New	7.5	HIGH		0.011		Missing release of memory after effective lifetime in Active Directory Domain Services allows an unauthorized attacker to deny service over a network.
CVE-2026-69852	New	7.5	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine
CVE-2026-69881	New	7.5	HIGH		0.012	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Null pointer dereference in Windows IKE Extension allows an unauthorized attacker to deny service over a network.
CVE-2026-69890	New	7.5	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Virtual Trusted Platform Module allows an authorized attacker to elevate privileges locally.
CVE-2026-69929	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to disclose information over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69930	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to disclose information over a network.
CVE-2026-70065	New	7.5	HIGH		0.012	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Missing release of memory after effective lifetime in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-70124	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to disclose information over a network.
CVE-2026-70570	New	7.5	HIGH		0.004		Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine
CVE-2026-70579	New	7.5	HIGH		0.01		Out-of-bounds read in Windows Mobile Broadband allows an unauthorized attacker to disclose information over a network.
CVE-2026-70587	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper null termination in Windows Remote Desktop Protocol allows an unauthorized attacker to disclose information over a network.
CVE-2026-71330	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of sensitive system information to an unauthorized control sphere in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to disclose information over a network.
CVE-2026-72923	New	7.5	HIGH		0.012		In Microsoft.OpenApi.YamlReader from 2.0.0-preview.11 until 2.12.0 and from 3.0.0 until 3.10.0, and in Microsoft.OpenApi.Readers prior to 1.6.30, a small YAML OpenAPI document containing nested anchors and aliases can cause uncontrolled resource consumption when parsed through the public YAML reader APIs. YAML is parsed through SharpYaml, which represents aliases as shared n...
CVE-2026-72928	New	7.5	HIGH		0.006	microsoft:windows_server_2025	Use after free in Windows DNS allows an authorized attacker to execute code over a network.
CVE-2026-72932	New	7.5	HIGH		0.01		Buffer over-read in Windows Message Queuing Queue Manager allows an unauthorized attacker to disclose information over a network.
CVE-2026-72943	New	7.5	HIGH		0.006		Use after free in Windows Deployment Services allows an authorized attacker to execute code over a network.
CVE-2026-72949	New	7.5	HIGH		0.011		Null pointer dereference in Windows SMB Server Network Transport Driver (srvnet.sys) allows an unauthorized attacker to deny service over a network.
CVE-2026-72954	New	7.5	HIGH		0.006		Use after free in Windows Deployment Services allows an authorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-72989	New	7.5	HIGH		0.008		Use of uninitialized resource in Windows Failover Cluster allows an unauthorized attacker to disclose information over a network.
CVE-2026-73017	New	7.5	HIGH		0.002	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Heap-based buffer overflow in Windows Graphics Kernel allows an authorized attacker to execute code locally.
CVE-2026-75998	New	7.5	HIGH		0.006		ColdFusion is affected by an Improper Access Control vulnerability that could lead to arbitrary file system read. An attacker could exploit this vulnerability to access sensitive files and directories outside the intended access scope. Exploitation of this issue does not require user interaction.
CVE-2026-77101	New	7.5	HIGH		0.003	commvault:commvault, linux:linux_kernel, microsoft:windows	CommServe contained a stack-based buffer overflow issue affecting service availability. Software customers upgrade to resolved maintenance release. Update CommServe.
CVE-2026-77102	New	7.5	HIGH		0.003	commvault:commvault, linux:linux_kernel, microsoft:windows	CommServe contained a heap-based buffer overflow issue affecting service availability. Software customers upgrade to resolved maintenance release. Update CommServe.
CVE-2026-77103	New	7.5	HIGH		0.003	commvault:commvault, linux:linux_kernel, microsoft:windows	CommServe contained an authentication bypass issue affecting access authorization and information disclosure. Software customers upgrade to resolved maintenance release. Update CommServe.
CVE-2026-77104	New	7.5	HIGH		0.004	commvault:commvault, linux:linux_kernel, microsoft:windows	CommServe contained a path traversal issue affecting information disclosure. Software customers upgrade to resolved maintenance release. Update CommServe.
CVE-2026-77108	New	7.5	HIGH		0.005	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by an Incorrect Authorization vulnerability that could result in privilege escalation. An attacker could leverage this vulnerability to gain elevated access to sensitive information. Exploitation of this issue does not require user interaction.
CVE-2026-77494	New	7.5	HIGH		0.012	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77498	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77499	New	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77501	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-77502	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77886	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77888	New	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77889	New	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77890	New	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77893	New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77895	New	7.5	HIGH		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77898	New	7.5	HIGH		0.005	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Heap-based buffer overflow in Microsoft Office allows an unauthorized attacker to execute code over a network.
CVE-2026-78523	New	7.5	HIGH		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in Windows DNS allows an unauthorized attacker to deny service over a network.
CVE-2026-78574	New	7.5	HIGH		0.001		The Okta Hyperdrive Integration plugin resolves a required assembly using a registry path within the current user's hive without integrity verification. The referenced path is loaded via Assembly.LoadFrom without signature validation, resulting in an unverified assembly executing within the context of the host process or elevated installer.
CVE-2026-78837	New	7.5	HIGH		0.003		A SQL injection vulnerability in the ap_form_{id} parameter in AppNitro MachForm v30 allows attackers to access sensitive database information via a crafted SQL statement.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-79377	New	7.5	HIGH		0.004		A heap overflow in the a2dp_decoder_sbc.cpp component of Bestechnic Co., Ltd BES2300 Bluetooth Audio SoC firmware v3.x and earlier allows attackers to cause a Denial of Service (DoS) via sending a crafted L2CAP packet.
CVE-2026-79378	New	7.5	HIGH		0.004		An issue in the btm_acl_handle() function of Bestechnic Co., Ltd BES2300 Bluetooth Audio SoC firmware v3.x and earlier allows attackers to cause a Denial of Service (DoS) via sending a crafted L2CAP packet.
CVE-2026-79572	New	7.5	HIGH		0.003		An XXE (XML External Entity) vulnerability in the level-rule module of Distribution Management v1.0.0 allows attackers to read sensitive files, scan internal networks, or launch server attacks via supplying a crafted XML payload.
CVE-2026-79575	New	7.5	HIGH		0.002		The JWT signing secret in yfexam-exam v2.0 is derived from the username and the current month instead of a random server-side key, making the secret key easily obtainable via a bruteforce attack.
CVE-2026-81355	New	7.5	HIGH		0.002		Heap-based buffer overflow in Virtual Hard Disk (VHD) Miniport Driver allows an authorized attacker to execute code locally.
CVE-2026-81381	New	7.5	HIGH		0.006	microsoft:visual_studio_code	Insufficiently protected credentials in GitHub Copilot and Visual Studio Code allows an unauthorized attacker to disclose information over a network.
CVE-2026-81790	New	7.5	HIGH		0.003		Missing Authorization vulnerability in Viszt Péter Csomagpontok és szállítási címkék WooCommerce-hez allows Exploiting Incorrectly Configured Access Control Security Levels. This issue affects Csomagpontok és szállítási címkék WooCommerce-hez: from n/a before 4.2.8.
CVE-2026-83989	New	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to deny service over a network.
CVE-2026-84001	New	7.5	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Key Distribution Center allows an unauthorized attacker to deny service over a network.
CVE-2026-85400	New	7.5	HIGH		0.004		Backend administrators without system maintainer privileges were able to schedule any of the configuration:read, configuration:set, and configuration:show commands. This allowed them to modify arbitrary system configuration, which is normally limited to system maintainers. As a consequence, this allowed them, for example, to gain system maintainer privileges or cause a denia...
CVE-2026-86075	New	7.5	HIGH		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 2.37.7 and 2.38.2, the OAuth Dynamic Client Registration endpoint bounded redirect_uris but accepted arbitrarily large client_name and grant_types values. An unauthenticated remote caller could repeatedly persist oversized values in oauth_clients and exhaust database storage. The affected validation is in packages/...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86711	New	7.5	HIGH		0.001		electerm before 5.3.15 exposes 40+ main-process functions through an unvalidated Electron IPC handler with no function-name allowlist or sender validation. Renderer-side script execution can invoke openFileWithEditor and other functions with arbitrary arguments to execute system commands in the main process.
CVE-2026-86721	New	7.5	HIGH		0.003		AVideo through commit c3edcc274c contains an authorization bypass vulnerability where a session cookie named 'key' with value 'value' overrides the \$_REQUEST['key'] parameter in saveLive.php and related endpoints. Attackers can publish to any user's RTMP stream without authentication by using the known constant stream key value to hijack live broadcasts.
CVE-2026-86728	New	7.5	HIGH		0.003		AVideo through 29.0 contains an authentication bypass vulnerability in plugin/PlayLists/epg.json.php that exposes live-stream keys and private EPG schedules to unauthenticated users. Attackers can request the endpoint with sequential user or playlist IDs to retrieve sensitive credentials, server identifiers, and complete programme schedules without authentication.
CVE-2026-19651	New	7.4	HIGH		0.003		IBM Enterprise Build of Quarkus 3.27.1 through 3.27.5, and 3.33.1 through 3.33.3 could allow an attacker to bypass authorization by manipulating URL query parameters due to incorrect mapping of values to untrusted query string input.
CVE-2026-69347	New	7.4	HIGH		0.003		Heap-based buffer overflow in Windows Fast FAT Driver allows an unauthorized attacker to execute code locally.
CVE-2026-71375	New	7.4	HIGH		0.002		Improper restriction of XML external entity reference vulnerability in Cosminexus Component Container. This issue affects Cosminexus Component Container: from 11-70-01 before 11-70-03, from 11-60 before 11-60-03, from 11-50 through 11-50-03, from 11-40 through 11-40-03, from 11-30 through 11-30-08, from 11-20 before 11-20-10, from 11-10 through 11-10-11, from 11-00 before 1...
CVE-2026-76196	New	7.4	HIGH		0.002	adobe:photoshop_mobile	Photoshop Mobile is affected by a Session Fixation vulnerability that could result in privilege escalation. An attacker could leverage this vulnerability to gain access to sensitive resources. Exploit depends on conditions beyond the attacker's control. Exploitation of this issue requires user interaction in that a victim must interact with a malicious webpage. Scope is chan...
CVE-2026-78461	New	7.4	HIGH		0.01	microsoft:visual_studio_code	Improper limitation of a pathname to a restricted directory ('path traversal') in Visual Studio Code allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-81383	New	7.4	HIGH		0.007	microsoft:visual_studio_code	Use of incorrectly-resolved name or reference in Visual Studio Code allows an unauthorized attacker to disclose information over a network.
CVE-2026-84003	New	7.4	HIGH		0.004	microsoft:azure/msal-node	Authentication bypass by capture-replay in Microsoft Authentication Library (MSAL) for Node.js allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-28613	New	7.3	HIGH		0.001	google:android	In initAppLinkTypeAndIntent of ChannellImpl.java, there is a possible launch an arbitrary intent due to improper input validation. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is needed for exploitation.
CVE-2026-28626	New	7.3	HIGH		0.001	google:android	In onCreate of SetupPassthroughActivity.java, there is a possible way to launch arbitrary activity due to Intent redirection . This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is needed for exploitation.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-28656	New	7.3	HIGH		0.001	google:android	In multiple functions of DeviceAdminAdd.java, there is a possible way to an overlay due to a tapjacking/overlay attack. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is needed for exploitation.
CVE-2026-45528	New	7.3	HIGH		0.001		In getManageSpaceActivityIntent of StorageManagerService.java, there is a possible LaunchAnyWhere chain due to an unsafe PendingIntent. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is needed for exploitation.
CVE-2026-69477	New	7.3	HIGH		0.004	microsoft:365_apps, microsoft:access, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Heap-based buffer overflow in Microsoft Office Access allows an authorized attacker to execute code locally.
CVE-2026-78627	New	7.3	HIGH		0.001		The Okta Hyperdrive Integration installer does not mask the OAuth client secret when passed as an MSI property. The credential is recorded in plaintext in the installer log, the Application Event Log, and the process command line, all of which are readable by an authenticated local user on the workstation.
CVE-2026-86806	New	7.3	HIGH		0.005		A weakness has been identified in opengeos GeoLibre up to 2.3.0. Impacted is the function _is_within_roots. This manipulation causes server-side request forgery. The attack can be initiated remotely. Upgrading to version 2.4.0 is recommended to address this issue. Patch name: b745f62e29fa37364686525a21eee5e5c0f8a369. It is recommended to upgrade the affected component.
CVE-2026-76561	New	7.2	HIGH		0.006		A flaw was found in Dogtag PKI, as used by FreeIPA's certificate authority component. The certificate profile import functionality does not fully validate uploaded profile content beyond the profile ID. An authenticated user with CA Administrator privileges can exploit Dogtag's ExternalProcessConstraint mechanism to execute arbitrary commands with attacker-controlled environ...
CVE-2026-81349	New	7.2	HIGH		0.007		Improper neutralization of special elements used in an os command ('os command injection') in Azure HDInsights allows an authorized attacker to elevate privileges over a network.
CVE-2026-81806	New	7.2	HIGH		0.002		Server-Side Request Forgery (SSRF) vulnerability in John Darrel Hide My WP Ghost allows Server Side Request Forgery. This issue affects Hide My WP Ghost: from n/a through 7.0.09.
CVE-2026-82061	New	7.2	HIGH		0.003	mongodb:mongodb	A use-after-free security issue exists in the server's query execution memory tracking subsystem. An authenticated user with read privileges can trigger a write to freed heap memory through a sequence of standard database commands, leading to server process crash or potential memory corruption. No user interaction is required.
CVE-2026-82071	New	7.2	HIGH		0.003	mongodb:mongodb	Insufficient validation of storage engine configuration options in MongoDB Server allows an authenticated user with write privileges to supply crafted parameters during collection creation that override internal storage metadata. This results in an out-of-bounds memory write in the server process, causing a denial of service via server crash, with potential for further impac...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-84387	New	7.2	HIGH		0.009		A improper neutralization of special elements used in a command ('command injection') vulnerability in Fortinet FortiSandbox 5.2.0, FortiSandbox 5.0.0 through 5.0.6, FortiSandbox 4.4.0 through 4.4.9 may allow attacker to execute unauthorized code or commands via <insert attack vector here>
CVE-2026-86733	New	7.2	HIGH		0.003	snipeitapp:snipe-it	Snipe-IT before 8.7.0 streams the SQL entry from an uploaded backup archive directly into the MySQL/MariaDB command-line client ('mysql') without the --binary-mode flag, so the client interprets lines beginning with backslash commands such as '\`' as local shell commands. An authenticated superadministrator who uploads a crafted ZIP backup (POST /admin/backups/upload) and tr...
CVE-2026-11573	New	7.1	HIGH		0.004		Uncontrolled recursion (CWE-674) in the QDomDocument/QDomNode serialization path of the Qt XML module (QtXml, qtbse). QDomElementPrivate::save() and QDomNodePrivate::save() recurse mutually, consuming one stack frame per level of element nesting with no depth limit, no configurable bound and no error return. A document with deeply nested elements parses successfully but exh...
CVE-2026-16769	New	7.1	HIGH		0.001		An unencrypted 'pause encryption request' message causes a denial of service in the in the RS9116W/SiWx917. See vulnerability B-E10 in the related paper below.
CVE-2026-20293	New	7.1	HIGH		0.001		A vulnerability in the Unified Extensible Firmware Interface (UEFI) Shell implementation of Cisco UCS Servers and UCS-based appliances could allow an authenticated attacker with valid credentials for a user account with the role of user or admin or an unauthenticated attacker with physical access to an affected device to bypass UEFI Secure Boot validation checks and exe...
CVE-2026-66305	New	7.1	HIGH		0.003	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Use of client-side authentication in Skype for Business allows an authorized attacker to perform spoofing over a network.
CVE-2026-68835	New	7.1	HIGH		0.005		Use after free in Windows Print Spooler Components allows an authorized attacker to elevate privileges over a network.
CVE-2026-68846	New	7.1	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Kernel allows an authorized attacker to elevate privileges over a network.
CVE-2026-68889	New	7.1	HIGH		0.004		Heap-based buffer overflow in Microsoft Standard XPS allows an authorized attacker to elevate privileges over a network.
CVE-2026-68893	New	7.1	HIGH		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in Windows Remote Desktop Licensing Service allows an authorized attacker to elevate privileges over a network.
CVE-2026-69272	New	7.1	HIGH		0.004		Heap-based buffer overflow in Microsoft Standard XPS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69274	New	7.1	HIGH		0.004		Use after free in Windows Win32K allows an authorized attacker to elevate privileges over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69296	New	7.1	HIGH		0.005		Use after free in Windows Device Association Service allows an authorized attacker to elevate privileges over a network.
CVE-2026-69305	New	7.1	HIGH		0.006		Use after free in Microsoft Windows Search Component allows an authorized attacker to elevate privileges over a network.
CVE-2026-69313	New	7.1	HIGH		0.005		Heap-based buffer overflow in Microsoft Standard XPS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69314	New	7.1	HIGH		0.005		Use after free in Windows Device Association Broker service allows an authorized attacker to elevate privileges over a network.
CVE-2026-69336	New	7.1	HIGH		0.005		Heap-based buffer overflow in Microsoft Standard XPS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69337	New	7.1	HIGH		0.007		Double free in Windows Registry allows an authorized attacker to elevate privileges over a network.
CVE-2026-69338	New	7.1	HIGH		0.005		Use after free in Remote Desktop Gateway Service allows an authorized attacker to elevate privileges over a network.
CVE-2026-69340	New	7.1	HIGH		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69357	New	7.1	HIGH		0.004		Use after free in Windows NDIS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69358	New	7.1	HIGH		0.005		Use of uninitialized resource in Remote Desktop Client allows an authorized attacker to execute code over a network.
CVE-2026-69364	New	7.1	HIGH		0.005		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Print Spooler Components allows an authorized attacker to elevate privileges over a network.
CVE-2026-69366	New	7.1	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Kernel allows an authorized attacker to elevate privileges over a network.
CVE-2026-69384	New	7.1	HIGH		0.004		Null pointer dereference in Virtual Hard Disk (VHD) Miniport Driver allows an unauthorized attacker to deny service locally.
CVE-2026-69396	New	7.1	HIGH		0.005		Use after free in Windows NDIS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69451	New	7.1	HIGH		0.007		Use after free in Windows Management Instrumentation allows an authorized attacker to elevate privileges over a network.
CVE-2026-69460	New	7.1	HIGH		0.005		Use after free in Windows Modern Device Management (MDM) allows an authorized attacker to elevate privileges over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69482	New	7.1	HIGH		0.003		Creation of temporary file in directory with insecure permissions in Windows Error Reporting allows an authorized attacker to perform tampering locally.
CVE-2026-69536	New	7.1	HIGH		0.004	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Use after free in Windows Remote Desktop Services allows an authorized attacker to execute code over a network.
CVE-2026-69553	New	7.1	HIGH		0.005		Missing authorization in Windows Hyper-V allows an authorized attacker to elevate privileges over a network.
CVE-2026-69597	New	7.1	HIGH		0.006		Use after free in Windows HTTP.sys allows an authorized attacker to elevate privileges over a network.
CVE-2026-69602	New	7.1	HIGH		0.006		Use after free in Windows PrintWorkflowUserSvc allows an authorized attacker to elevate privileges over a network.
CVE-2026-69688	New	7.1	HIGH		0.006		Heap-based buffer overflow in Windows Encrypting File System (EFS) allows an authorized attacker to elevate privileges over a network.
CVE-2026-69706	New	7.1	HIGH		0.004		Use after free in Windows Win32K allows an authorized attacker to elevate privileges over a network.
CVE-2026-69757	New	7.1	HIGH		0.007		Use after free in Windows TCP/IP allows an authorized attacker to elevate privileges over a network.
CVE-2026-69761	New	7.1	HIGH		0.005		Use after free in Windows TCP/IP allows an authorized attacker to elevate privileges over a network.
CVE-2026-69775	New	7.1	HIGH		0.005		Use after free in Windows DWM Core Library allows an authorized attacker to elevate privileges over a network.
CVE-2026-73321	New	7.1	HIGH		0.004	xenforo:xenforo	XenForo before 2.3.13 contains an uncontrolled recursion vulnerability in the BBCode parser that allows authenticated attackers to cause persistent denial of service by submitting a post with deeply nested BBCode tags. Attackers can craft a single malicious post with sufficient nesting depth to exceed PHP's stack limit, causing fatal errors that repeatedly terminate PHP-FPM ...
CVE-2026-81781	New	7.1	HIGH		0.002		Missing Authorization vulnerability in Unbounce Unbounce Landing Pages unbounce allows Exploiting Incorrectly Configured Access Control Security Levels. This issue affects Unbounce Landing Pages: from n/a through 1.1.4.
CVE-2026-81798	New	7.1	HIGH		0.001		Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') vulnerability in Easy Appointments allows DOM-Based XSS. This issue affects Easy Appointments: from n/a through 4.0.2.1.
CVE-2026-82052	New	7.1	HIGH		0.004	mongodb:mongodb	The \$regexFindAll expression can be used by an authenticated user who can run aggregation pipeline stages to crash a MongoDB server (mongod). Under certain specific conditions the regex match can start in the middle of a multi-code-unit character, triggering an assertion during query execution.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-82054	New	7.1	HIGH		0.003	mongodb:mongodb	A security issue exists in MongoDB server's JSON Pointer parser used during \$jsonSchema query filter processing. When a find command includes a specially crafted \$jsonSchema filter field, the parser processes the input without enforcing adequate limits on iteration count or total allocation size, resulting in significant memory amplification. Under concurrent request load, t...
CVE-2026-82055	New	7.1	HIGH		0.003	mongodb:mongodb	A security issue exists in MongoDB's 2dsphere index key generation that can cause a server crash due to a null pointer dereference. When a specially crafted GeoJSON document is inserted into a collection with a 2dsphere index, an inconsistency in geometry parsing can leave an internal object in an invalid, partially initialized state. During subsequent index key generation, ...
CVE-2026-82057	New	7.1	HIGH		0.003	mongodb:mongodb	A security issue was discovered in MongoDB where an authenticated user with readWrite privileges could crash the mongod server process. By specifying a custom WiredTiger storage configuration option with an incompatible value during collection creation, a user could cause a type confusion in the storage engine layer. When documents were subsequently read from the misconfigur...
CVE-2026-82058	New	7.1	HIGH		0.003	mongodb:mongodb	A flaw in MongoDB's JSON Schema validation error generation code allows an authenticated user with readWrite privileges to crash the mongod server. When a BSON document containing an array with a malformed numeric field name fails a \$jsonSchema items type constraint, the error generation path performs unsafe numeric conversion on the user-controlled field name without proper...
CVE-2026-82065	New	7.1	HIGH		0.003	mongodb:mongodb	A security issue in the MongoDB Server's storage engine integration layer allows an authenticated user with collection creation privileges to cause a persistent denial of service. Insufficient validation of user-supplied storage configuration options permits values that, once persisted to durable metadata, trigger a fatal assertion failure when the metadata is subsequently r...
CVE-2026-82068	New	7.1	HIGH		0.003	mongodb:mongodb	A security issue in MongoDB Server allows an authenticated user with write privileges to trigger a persistent fatal assertion crash by sending specially crafted retryable write commands. The crash state is durably persisted, causing the server process to repeatedly crash on restart and potentially propagating to additional nodes in a sharded cluster. Manual intervention is r...
CVE-2026-82070	New	7.1	HIGH		0.002	mongodb:mongodb	A security issue in MongoDB Server's diagnostic reporting interface allows an authenticated user with monitoring privileges to access insufficiently protected credentials from concurrent administrative operations. The same credentials are properly redacted in server log output, but the diagnostic interface omits equivalent redaction. Successful exploitation requires a valid ...
CVE-2026-82073	New	7.1	HIGH		0.003	mongodb:mongodb	A security issue in the MongoDB Server aggregation framework allows an authenticated user with limited read privileges to bypass view-level authorization checks and access data from unauthorized collections when Atlas Search features are in use. The issue stems from insufficient validation of an internal command parameter that can be set by external clients, causing a securi...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-82074	New	7.1	HIGH		0.002	mongodb:mongodb	MongoDB Server contains an incorrect authorization vulnerability in the aggregation framework. An authenticated user with minimal privileges can craft a specially formatted aggregation request that causes the server's authorization subsystem to evaluate a different operation than what is actually executed, resulting in unauthorized read access to collection data within the t...
CVE-2026-82076	New	7.1	HIGH		0.003	mongodb:mongodb	An integer overflow in the query planning component of MongoDB Server can allow an authenticated user with ordinary database-level read/write privileges to bypass an internal resource limit. Submitting a specially crafted query causes the server to consume memory without bound during query planning, and the resulting exhaustion terminates the server process. This may result ...
CVE-2026-84817	New	7.1	HIGH		0.001		Unauthenticated Cross Site Scripting (XSS) in JetFormBuilder <= 3.6.5.1 versions.
CVE-2026-84818	New	7.1	HIGH		0.001		Unauthenticated Cross Site Scripting (XSS) in Open User Map <= 1.4.50 versions.
CVE-2026-84820	New	7.1	HIGH		0.001		Unauthenticated Cross Site Scripting (XSS) in Unlimited Elements For Elementor (Free Widgets, Addons, Templates) <= 2.0.17 versions.
CVE-2026-86074	New	7.1	HIGH		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 2.37.7 and 2.38.2, the Instance AI credential setup flow accepted a credential test or verification URL without checking that it matched the workflow node's origin. Attacker-controlled fetched content could influence that URL after a user injected it into the setup flow, causing authenticated requests, redirects, o...
CVE-2026-86081	New	7.1	HIGH		0.003		n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the Git node clone operation matched an attacker-controlled destination path against the default N8N_BLOCK_FILE_PATTERNS regular expression. The pattern <code>^(./).git(/.)\$</code> allowed catastrophic backtracking and ran synchronously in the main n8n process. An authenticated workflow editor coul...
CVE-2026-86713	New	7.1	HIGH		0.004		PX4 Autopilot through 1.17.0 contains a use-after-free vulnerability in the load_mon module's stop path where <code>exit_and_cleanup()</code> deletes the LoadMon object and frees the performance counter before <code>perf_end()</code> attempts to access it. Attackers can trigger this vulnerability by issuing the load_mon stop command from any PXH or MAVLink shell, causing reads and writes through free...
CVE-2026-86718	New	7.1	HIGH		0.002		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a cross-site request forgery vulnerability in <code>deleteHistory.json.php</code> and <code>finishAll.json.php</code> that allows unauthenticated attackers to mutate live history by making GET requests without CSRF token validation. Attackers can craft malicious pages that trigger administrator browsers to delete all live tr...
CVE-2026-86724	New	7.1	HIGH		0.001		AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 contains a cross-site request forgery vulnerability in <code>plugin/YPTWallet/view/saveBalance.php</code> that allows attackers to set arbitrary wallet balances by relying only on session cookies without token validation. Attackers can craft a malicious webpage that, when loaded by an administrator, submits a POST request to ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86725	New	7.1	HIGH		0.003		AVideo through c3edcc274c389816d434acadac07ee78eaf330c1 contains a missing authorization vulnerability in the SocialMediaPublisher plugin's add.json.php endpoint that allows authenticated users to modify other users' OAuth token records. Attackers can supply arbitrary row IDs to overwrite another user's stored access_token and refresh_token, then delete the compromised recor...
CVE-2026-86734	New	7.1	HIGH		0.003	snipeitapp:snipe-it	Snipe-IT before 8.7.1 fails to validate the length of the note field in the POST /account/accept/{acceptance} endpoint, allowing authenticated users to submit unbounded input that reaches synchronous CommonMark rendering. Attackers can submit large note values to exhaust PHP worker CPU and cause denial of service through resource exhaustion in the markdown parsing pipeline.
CVE-2026-9331	New	7.1	HIGH		0.002		The EDD Product Catalog Feed by PixelYourSite plugin for WordPress is vulnerable to unauthorized modification of data that can lead to a denial of service due to a missing capability check on the wpeddpcf_delete_feed function in all versions up to, and including, 1.0.2. This makes it possible for authenticated attackers, with subscriber-level access and above, to delete arbi...
CVE-2026-50349	New	7.0	HIGH		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Ancillary Function Driver for WinSock allows an authorized attacker to elevate privileges locally.
CVE-2026-58848	New	7.0	HIGH		0.001		In multiple functions of alloc.c, there is a possible unauthorized read/write access due to a race condition. This could lead to local escalation of privilege with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-62653	New	7.0	HIGH		0.002		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). The input received over a proprietary communication protocol that is exposed when the device is placed into a special firmware-update mode is not properly validated, resulting in a memory corruption condition. This could allow an unauthenticated attacker with physical access to the device to cause a...
CVE-2026-62654	New	7.0	HIGH		0.001		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). A special maintenance mode can be activated via a physical key sequence during device boot, in which the device downloads and executes program code from a network server without verifying its authenticity or integrity. This could allow an attacker with physical access to the device to upload and exe...
CVE-2026-62694	New	7.0	HIGH		0.003		Use after free in Windows Installer allows an authorized attacker to elevate privileges locally.
CVE-2026-68824	New	7.0	HIGH		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Connected User Experiences and Telemetry allows an authorized attacker to elevate privileges locally.
CVE-2026-68825	New	7.0	HIGH		0.003		Use after free in Windows Bind Filter Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-68837	New	7.0	HIGH		0.002		Use after free in Windows File History Service allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-68840	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows USB Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-68847	New	7.0	HIGH		0.002		Use after free in Windows Connected User Experiences and Telemetry allows an authorized attacker to elevate privileges locally.
CVE-2026-68884	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-68897	New	7.0	HIGH		0.002		Heap-based buffer overflow in Microsoft Standard XPS allows an authorized attacker to elevate privileges locally.
CVE-2026-69275	New	7.0	HIGH		0.002		Use after free in Kernel Streaming WOW Thunk Service Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69279	New	7.0	HIGH		0.003		Use after free in Windows Cloud Files Mini Filter Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69280	New	7.0	HIGH		0.002		Use after free in Windows Push Notifications allows an authorized attacker to elevate privileges locally.
CVE-2026-69281	New	7.0	HIGH		0.003		Use after free in Windows License Manager allows an authorized attacker to elevate privileges locally.
CVE-2026-69287	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Desktop Services allows an authorized attacker to elevate privileges locally.
CVE-2026-69292	New	7.0	HIGH		0.002		Double free in Remote Desktop Gateway Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69299	New	7.0	HIGH		0.002		Use after free in Microsoft COM for Windows allows an authorized attacker to elevate privileges locally.
CVE-2026-69300	New	7.0	HIGH		0.002		Use after free in Windows Push Notifications allows an authorized attacker to elevate privileges locally.
CVE-2026-69309	New	7.0	HIGH		0.003		Double free in Windows Print Spooler Components allows an authorized attacker to elevate privileges locally.
CVE-2026-69310	New	7.0	HIGH		0.003		Use after free in Windows DNS allows an authorized attacker to elevate privileges locally.
CVE-2026-69311	New	7.0	HIGH		0.003		Use after free in Windows Audio Service allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69319	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows USB Video Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69331	New	7.0	HIGH		0.002		Use after free in Windows Remote Access Connection Manager allows an authorized attacker to elevate privileges locally.
CVE-2026-69333	New	7.0	HIGH		0.003		Use after free in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69335	New	7.0	HIGH		0.003		Use after free in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69341	New	7.0	HIGH		0.003		Use after free in Windows Image Acquisition allows an authorized attacker to elevate privileges locally.
CVE-2026-69362	New	7.0	HIGH		0.003		Use after free in Windows Error Reporting allows an authorized attacker to elevate privileges locally.
CVE-2026-69379	New	7.0	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Improper link resolution before file access ('link following') in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-69383	New	7.0	HIGH		0.002		External control of file name or path in Windows Shell allows an authorized attacker to elevate privileges locally.
CVE-2026-69385	New	7.0	HIGH		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows TCP/IP allows an authorized attacker to elevate privileges locally.
CVE-2026-69388	New	7.0	HIGH		0.003		Use after free in Windows Bluetooth Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69394	New	7.0	HIGH		0.003		Heap-based buffer overflow in Windows Audio Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69398	New	7.0	HIGH		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Bluetooth Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69401	New	7.0	HIGH		0.002		Use after free in Audio Video Control Transport Protocol allows an authorized attacker to elevate privileges locally.
CVE-2026-69404	New	7.0	HIGH		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows TCP/IP allows an authorized attacker to elevate privileges locally.
CVE-2026-69410	New	7.0	HIGH		0.003		Use after free in Windows Win32K allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69413	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69422	New	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Use after free in Windows USB Video Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69430	New	7.0	HIGH		0.003		Use after free in Windows Embedded Mode Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69440	New	7.0	HIGH		0.002		Time-of-check time-of-use (toctou) race condition in Windows MIDI Service Module allows an authorized attacker to elevate privileges locally.
CVE-2026-69441	New	7.0	HIGH		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Installer allows an authorized attacker to elevate privileges locally.
CVE-2026-69448	New	7.0	HIGH		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Bluetooth Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69466	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Time-of-check time-of-use (toctou) race condition in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-69468	New	7.0	HIGH		0.003		Heap-based buffer overflow in Windows Volume Manager Extension Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69470	New	7.0	HIGH		0.003		Use after free in Windows Connected User Experiences and Telemetry allows an authorized attacker to elevate privileges locally.
CVE-2026-69472	New	7.0	HIGH		0.003		Use after free in Windows Devices Human Interface allows an authorized attacker to elevate privileges locally.
CVE-2026-69473	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-69488	New	7.0	HIGH		0.003		Use after free in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69492	New	7.0	HIGH		0.003		Heap-based buffer overflow in Windows Partition Management Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69498	New	7.0	HIGH		0.003		Use after free in Windows Win32K allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69500	New	7.0	HIGH		0.003		Use after free in Windows Image Acquisition allows an authorized attacker to elevate privileges locally.
CVE-2026-69501	New	7.0	HIGH		0.002	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Untrusted pointer dereference in Windows Secure Kernel Mode allows an authorized attacker to elevate privileges locally.
CVE-2026-69516	New	7.0	HIGH		0.002		Use after free in Connected Devices Platform Service (Cdpsvc) allows an authorized attacker to elevate privileges locally.
CVE-2026-69517	New	7.0	HIGH		0.003		Use after free in Windows Wireless Networking allows an authorized attacker to elevate privileges locally.
CVE-2026-69540	New	7.0	HIGH		0.003		Use after free in Windows Audio Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69549	New	7.0	HIGH		0.003		Out-of-bounds read in Virtual Hard Disk (VHD) Miniport Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69560	New	7.0	HIGH		0.003		Use after free in Windows Work Folder Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69563	New	7.0	HIGH		0.002		Heap-based buffer overflow in Windows Program Compatibility Assistant Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69564	New	7.0	HIGH		0.003		Heap-based buffer overflow in Windows Online Certificate Status Protocol (OCSP) allows an authorized attacker to elevate privileges locally.
CVE-2026-69567	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-69573	New	7.0	HIGH		0.003		Use after free in Windows Universal Disk Format File System Driver (UDFS) allows an authorized attacker to elevate privileges locally.
CVE-2026-69574	New	7.0	HIGH		0.003		Use after free in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69575	New	7.0	HIGH		0.003		Use after free in Windows Storage Spaces Controller allows an authorized attacker to elevate privileges locally.
CVE-2026-69578	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Numeric truncation error in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-69581	New	7.0	HIGH		0.002		Use after free in Windows Device Association Service allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69600	New	7.0	HIGH		0.003		Use after free in Microsoft Windows Search Component allows an authorized attacker to elevate privileges locally.
CVE-2026-69605	New	7.0	HIGH		0.003		Use after free in Microsoft Install Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69606	New	7.0	HIGH		0.003		Use after free in Windows Shell allows an authorized attacker to elevate privileges locally.
CVE-2026-69610	New	7.0	HIGH		0.003		Buffer over-read in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69611	New	7.0	HIGH		0.003		Use after free in Virtual Hard Disk (VHD) Miniport Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69613	New	7.0	HIGH		0.003		Use after free in Windows Image Acquisition allows an authorized attacker to elevate privileges locally.
CVE-2026-69617	New	7.0	HIGH		0.003		Out-of-bounds read in Windows Resilient File System (ReFS) allows an authorized attacker to elevate privileges locally.
CVE-2026-69621	New	7.0	HIGH		0.003		Heap-based buffer overflow in Windows Fax Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69630	New	7.0	HIGH		0.003		Out-of-bounds read in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69645	New	7.0	HIGH		0.003		Use after free in Windows Message Queuing allows an authorized attacker to elevate privileges locally.
CVE-2026-69648	New	7.0	HIGH		0.003		Use after free in Windows Notification allows an authorized attacker to elevate privileges locally.
CVE-2026-69652	New	7.0	HIGH		0.003		Use after free in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69654	New	7.0	HIGH		0.003		Use after free in Windows Accounts Control allows an authorized attacker to elevate privileges locally.
CVE-2026-69682	New	7.0	HIGH		0.002		Use after free in Windows Host Guardian Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69692	New	7.0	HIGH		0.003		Use after free in Windows Audio Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69693	New	7.0	HIGH		0.003		Use after free in Windows Device Association Broker service allows an authorized attacker to elevate privileges locally.
CVE-2026-69694	New	7.0	HIGH		0.017		Deserialization of untrusted data in Windows IP Address Management (IPAM) Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69708	New	7.0	HIGH		0.003		Use after free in Windows Web Platform Storage allows an authorized attacker to elevate privileges locally.
CVE-2026-69711	New	7.0	HIGH		0.003		Use after free in Windows Device Association Service allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69735	New	7.0	HIGH		0.003		Use after free in Windows Broadcast DVR User Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69779	New	7.0	HIGH		0.002		Time-of-check time-of-use (toctou) race condition in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69791	New	7.0	HIGH		0.003		Use after free in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69806	New	7.0	HIGH		0.018		Exposure of sensitive information to an unauthorized actor in .NET allows an authorized attacker to elevate privileges locally.
CVE-2026-69814	New	7.0	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Use after free in Windows Credential Providers allows an authorized attacker to elevate privileges locally.
CVE-2026-69816	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Accounts Control allows an authorized attacker to elevate privileges locally.
CVE-2026-69817	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Bluetooth Port Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69818	New	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Use after free in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69834	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows ALPC allows an authorized attacker to elevate privileges locally.
CVE-2026-69838	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Print Spooler Components allows an authorized attacker to elevate privileges locally.
CVE-2026-69859	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Time-of-check time-of-use (toctou) race condition in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69866	New	7.0	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69889	New	7.0	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Bluetooth Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69891	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Media allows an authorized attacker to elevate privileges locally.
CVE-2026-69896	New	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Use after free in Windows Error Reporting allows an authorized attacker to elevate privileges locally.
CVE-2026-69911	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Microsoft Windows Search Component allows an authorized attacker to elevate privileges locally.
CVE-2026-70283	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Incorrect authorization in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-70562	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Double free in Windows Audio Service allows an authorized attacker to elevate privileges locally.
CVE-2026-70565	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows AF_UNIX Socket Provider allows an authorized attacker to elevate privileges locally.
CVE-2026-70567	New	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Double free in Windows Display Enhancement Service allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-70568	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Defender Firewall Service allows an authorized attacker to elevate privileges locally.
CVE-2026-70573	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-70577	New	7.0	HIGH		0.003		Use after free in Windows Modern Device Management (MDM) allows an authorized attacker to elevate privileges locally.
CVE-2026-70578	New	7.0	HIGH		0.003		Heap-based buffer overflow in Windows Credential Guard allows an authorized attacker to elevate privileges locally.
CVE-2026-70585	New	7.0	HIGH		0.003		Use after free in Windows Services for NFS ONCRPC XDR Driver allows an authorized attacker to execute code locally.
CVE-2026-71332	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Secure Socket Tunneling Protocol (SSTP) allows an authorized attacker to elevate privileges locally.
CVE-2026-71333	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Access Connection Manager allows an authorized attacker to elevate privileges locally.
CVE-2026-71340	New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows File History Service allows an authorized attacker to elevate privileges locally.
CVE-2026-71342	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Access Connection Manager allows an authorized attacker to elevate privileges locally.
CVE-2026-71351	New	7.0	HIGH		0.003		Double free in Windows Routing and Remote Access Service (RRAS) allows an authorized attacker to elevate privileges locally.
CVE-2026-71353	New	7.0	HIGH		0.002		Double free in Windows Routing and Remote Access Service (RRAS) allows an authorized attacker to elevate privileges locally.
CVE-2026-72926	New	7.0	HIGH		0.003		Use after free in Windows Internet Connection Sharing (ICS) allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-72930	New	7.0	HIGH		0.003		Use after free in Windows Secure Socket Tunneling Protocol (SSTP) allows an authorized attacker to execute code locally.
CVE-2026-72952	New	7.0	HIGH		0.003		Out-of-bounds read in Windows Spaceport.sys allows an authorized attacker to execute code locally.
CVE-2026-72963	New	7.0	HIGH		0.003		Use after free in Windows Modern Execution Server allows an authorized attacker to elevate privileges locally.
CVE-2026-73003	New	7.0	HIGH		0.002		Use after free in Windows Modern Device Management (MDM) allows an authorized attacker to elevate privileges locally.
CVE-2026-73005	New	7.0	HIGH		0.002		Use after free in Windows Authentication Methods allows an authorized attacker to elevate privileges locally.
CVE-2026-73022	New	7.0	HIGH		0.002	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Modern Device Management (MDM) allows an authorized attacker to elevate privileges locally.
CVE-2026-77485	New	7.0	HIGH		0.002	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use after free in SQL Server allows an authorized attacker to elevate privileges locally.
CVE-2026-77894	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Installer allows an authorized attacker to elevate privileges locally.
CVE-2026-77897	New	7.0	HIGH		0.003		Relative path traversal in Power Automate allows an authorized attacker to elevate privileges locally.
CVE-2026-77899	New	7.0	HIGH		0.002	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2012	Use after free in Windows Security Center allows an authorized attacker to elevate privileges locally.
CVE-2026-77905	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Management Instrumentation allows an authorized attacker to elevate privileges locally.
CVE-2026-78457	New	7.0	HIGH		0.002	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2022, microsof	Use after free in Windows Security Health Service allows an authorized attacker to elevate privileges locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78464	New	7.0	HIGH		0.002	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1	Time-of-check time-of-use (toctou) race condition in Windows MIDI Service Module allows an authorized attacker to elevate privileges locally.
CVE-2026-80093	New	7.0	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Cloud Files Mini Filter Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-81192	New	7.0	HIGH		0.001		`OpenTelemetry.Resources.Host` NuGet package, which provides OpenTelemetry resource detectors for host, is affected by an untrusted search path vulnerability on macOS. Prior to version 1.16.0-beta.2, the `host.id` resource attribute detector launches the `sh` and `ioreg` executables by bare name rather than by absolute path, so both are resolved through the `PATH` environmen...
CVE-2026-81389	New	7.0	HIGH		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Heap-based buffer overflow in Microsoft Office Excel allows an unauthorized attacker to execute code locally.
CVE-2026-82062	New	7.0	HIGH		0.004	mongodb:mongodb	A security issue in MongoDB Server allows an authenticated user with elevated internal privileges to bypass a disabled feature gate in the applyOps command by specifying an internal replication mode value that was not intended to be client-selectable. This bypass enables execution of container operations that are disabled by default in production configurations, allowing dir...
CVE-2026-83940	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83999	New	7.0	HIGH		0.002	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Improper link resolution before file access ('link following') in Windows Resilient File System (ReFS) Deduplication Service allows an authorized attacker to elevate privileges locally.
CVE-2026-85360	New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-86135	New	7.0	HIGH		0.002		A Cross-Site Request Forgery (CSRF) vulnerability in WatchGuard Dimension's database snapshot creation feature allows a remote attacker to trigger unauthorized snapshot creation by tricking an authenticated administrator into visiting a specially crafted web page.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-53933	New	6.9	MEDI		0.003		Maravel, a PHP framework oriented towards dependency injection, prior to version 10.73.1 has a side-channel information disclosure issue. When a route was compiled with dynamic placeholders (e.g., <code>/api/v1/users/{id}</code>), the raw string placeholder key was mistakenly registered into the flat static route checklist. An attacker scanning endpoints could intentionally pass the li...
CVE-2026-62652	New	6.9	MEDI		0.002		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). The device firmware contains binaries from which debugging symbols have not been removed. This could allow an unauthenticated attacker with access to the publicly available firmware update files to more easily reverse engineer the device's firmware, facilitating the identification of further vulnera...
CVE-2026-81531	New	6.9	MEDI		0.004		An information disclosure vulnerability has been identified in Omada Controller. An API endpoint intended for Controller initialization remains accessible after completion and may disclose account-related information to unauthenticated remote users. Successful exploitation may allow an attacker to remote query the affected endpoint that may facilitate user enumeratio...
CVE-2026-81823	New	6.9	MEDI		0.002		The vulnerability, if exploited, could allow an unauthenticated miscreant to perform read operations intended only for PIMBoards users, resulting in information disclosure. Write operations are not impacted.
CVE-2026-86804	New	6.9	MEDI		0.004		A vulnerability was identified in seakee CPA-Manager-Plus up to 1.11.10. This vulnerability affects the function CPAResource of the file <code>apps/manager-server/internal/http/controller/proxy/handler.go</code> of the component HTTP Handler. The manipulation leads to improper authorization. It is possible to initiate the attack remotely. Upgrading to version 1.11.11 is able to resolve t...
CVE-2026-86810	New	6.9	MEDI		0.007		A vulnerability was detected in Open-Web-Analytics up to 1.9.1. The impacted element is the function <code>checkCapabilityAndAuthenticateUser</code> of the file <code>Core/Controller.php</code> of the component Controller. Performing a manipulation results in improper authentication. The attack may be initiated remotely. Upgrading to version 1.10.0 is sufficient to resolve this issue. The patch is na...
CVE-2026-65812	New	6.8	MEDI		0.005		Insertion of sensitive information into sent data in Microsoft Teams for Android allows an authorized attacker to disclose information over a network.
CVE-2026-68833	New	6.8	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code with a physical attack.
CVE-2026-69415	New	6.8	MEDI		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Missing authentication for critical function in Windows DHCP Server allows an authorized attacker to elevate privileges over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69490	New	6.8	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Mass Storage Class Driver allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-69566	New	6.8	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code with a physical attack.
CVE-2026-71329	New	6.8	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code with a physical attack.
CVE-2026-71348	New	6.8	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Spaceport.sys allows an unauthorized attacker to execute code with a physical attack.
CVE-2026-71349	New	6.8	MEDI		0.004		Heap-based buffer overflow in Windows Spaceport.sys allows an unauthorized attacker to execute code with a physical attack.
CVE-2026-71350	New	6.8	MEDI		0.004		Heap-based buffer overflow in Windows Spaceport.sys allows an unauthorized attacker to execute code with a physical attack.
CVE-2026-72985	New	6.8	MEDI		0.003		Heap-based buffer overflow in Windows Volume Shadow Copy allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-72999	New	6.8	MEDI		0.003		Out-of-bounds read in Windows USB Hub Driver allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-74859	New	6.8	MEDI		0.001		The shell theme installer in gnome-tweaks extracts user-supplied ZIP archives without validating archive member paths. As a result, a crafted theme archive can write files outside ~/.themes by using ../ path traversal, absolute paths, or symlink entries.
CVE-2026-77892	New	6.8	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	No cwe for this issue in Windows Boot Manager allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-78451	New	6.8	MEDI		0.004	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Untrusted pointer dereference in Microsoft Windows SCSI Class System File allows an unauthorized attacker to elevate privileges with a physical attack.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78579	New	6.8	MEDI		0.002		The Okta Access Gateway does not sanitize SAML assertion attribute values before interpolating them into LDAP search filters in the LDAP datastore configuration. The raw values are substituted directly into the filter string and passed to the LDAP search operation, resulting in modification of the intended query logic.
CVE-2026-69350	New	6.7	MEDI		0.003		Heap-based buffer overflow in Windows Overlay Filter allows an authorized attacker to elevate privileges locally.
CVE-2026-69373	New	6.7	MEDI		0.003		Integer overflow or wraparound in Windows Overlay Filter allows an authorized attacker to elevate privileges locally.
CVE-2026-69449	New	6.7	MEDI		0.004		Heap-based buffer overflow in Windows BitLocker allows an authorized attacker to execute code locally.
CVE-2026-69820	New	6.7	MEDI		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Heap-based buffer overflow in Windows Hello allows an authorized attacker to elevate privileges locally.
CVE-2026-71339	New	6.7	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Installer allows an authorized attacker to elevate privileges locally.
CVE-2026-72927	New	6.7	MEDI		0.003		Heap-based buffer overflow in Winsock allows an authorized attacker to elevate privileges locally.
CVE-2026-72935	New	6.7	MEDI		0.003		Out-of-bounds read in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-72948	New	6.7	MEDI		0.004		Relative path traversal in Windows DNS allows an authorized attacker to elevate privileges locally.
CVE-2026-78625	New	6.7	MEDI		0.002		The Okta Access Gateway does not sanitize dashboard label values before writing them into generated PHP configuration files. The generated file is automatically included during authentication requests, resulting in execution with the privileges of the web server process.
CVE-2026-78630	New	6.7	MEDI		0.002		The Okta Access Gateway does not neutralize shell metacharacters in SNMP configuration values before a privileged script uses them to construct OS commands. An authenticated local user with access to the management interface can supply crafted values, resulting in the execution of arbitrary OS commands with root privileges.
CVE-2026-85981	New	6.7	MEDI		0.001		The administrative panel of the Auth0 AD/LDAP Connector (versions 6.5.0 and earlier) listens on the local loopback interface without requiring authentication. This allows a local, low-privileged user or process on the host system to access the panel's management endpoints without credentials. Through these endpoints, a local user can read configuration details, including pla...
CVE-2026-52486	New	6.6	MEDI		0.001		An issue in OpenDDS 3.33.x allows a local attacker to cause a denial of service via the verify function in the SignedDocument module

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69469	New	6.6	MEDI		0.004	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Integer overflow or wraparound in Windows USB Audio Class driver (usbaudio.sys) allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-78545	New	6.6	MEDI		0.004		The Okta Access Gateway does not sanitize the application label field before including it in the generated nginx configuration file. The unsanitized value is interpolated into an nginx server block directive, resulting in execution of injected directives.
CVE-2026-78550	New	6.6	MEDI		0.004		The Okta Access Gateway management console passes user-supplied input to eval() without sanitization during an authenticated administrator SSH session. As a result, the unsanitized input is executed directly, leading to code execution with the privileges of the management console.
CVE-2026-17509	New	6.5	MEDI		0.002		The WPML Multilingual CMS plugin for WordPress is vulnerable to time-based SQL Injection via the 'elementIds' parameter in all versions up to, and including, 4.9.5 due to insufficient escaping on the user supplied parameter and lack of sufficient preparation on the existing SQL query. This makes it possible for authenticated attackers, with Subscriber-level access and above...
CVE-2026-18021	New	6.5	MEDI		0.003		The The Beaver Builder Page Builder – Drag and Drop Website Builder plugin for WordPress is vulnerable to arbitrary shortcode execution in all versions up to, and including, 2.10.3.1. This is due to the software allowing users to execute an action that does not properly validate a value before running do_shortcode. This makes it possible for unauthenticated attackers to exec...
CVE-2026-44766	New	6.5	MEDI		0.002		SAP S/4HANA (Intercompany Matching and Reconciliation) allows a low-privileged authenticated user to inject malicious input into certain functions, which may be processed by the database without proper validation. This could allow the user to access sensitive information, resulting in high impact on confidentiality, with no impact on integrity and availability of the applica...
CVE-2026-53637	New	6.5	MEDI		0.003		Sylus is an Open Source eCommerce Framework on Symfony. Versions 2.0.0 through 2.0.17, 2.1.0 through 2.1.14, and 2.2.0 through 2.2.5 contain an improper workflow enforcement vulnerability in the cart `FormComponent`. When an order is completed while its cart page remains open, the stale LiveComponent does not detect the order's changed state and continues to permit cart act...
CVE-2026-55256	New	6.5	MEDI		0.003		In parsePartHeaders of multiple files, there is a possible persistent denial of service due to improper input validation. This could lead to remote denial of service with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-58649	New	6.5	MEDI		0.003		Origin validation error in .NET allows an unauthorized attacker to disclose information over a network.
CVE-2026-62437	New	6.5	MEDI		0.001		When guests are terminated, various pieces of cleanup need carrying out. The cleaning up of PCI devices which were assigned to guests, and the associated removal of tracking structures for IRQs used by the devices occurs relatively early in the process. Unfortunately after that point the guest about to be terminated could cause its device model (DM) to re-establish such tra...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-62762	New	6.5	MEDI		0.008		Null pointer dereference in Active Directory Domain Services allows an authorized attacker to deny service over a network.
CVE-2026-62801	New	6.5	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper limitation of a pathname to a restricted directory ('path traversal') in Windows PowerShell allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-64918	New	6.5	MEDI		0.005	microsoft:365_apps, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Insufficiently protected credentials in Microsoft Office allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-66303	New	6.5	MEDI		0.008	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Null pointer dereference in Skype for Business allows an authorized attacker to deny service over a network.
CVE-2026-66306	New	6.5	MEDI		0.005	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Generation of error message containing sensitive information in Skype for Business allows an unauthorized attacker to disclose information over a network.
CVE-2026-66308	New	6.5	MEDI		0.006	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Out-of-bounds read in Skype for Business allows an authorized attacker to deny service over a network.
CVE-2026-66816	New	6.5	MEDI		0.007	microsoft:sql_server_2022, microsoft:sql_server_2025	Insufficient logging in SQL Server allows an authorized attacker to bypass a security feature over a network.
CVE-2026-67369	New	6.5	MEDI		0.007	microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67383	New	6.5	MEDI		0.01	microsoft:sql_server_2025	Generation of error message containing sensitive information in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67386	New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use of uninitialized resource in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67389	New	6.5	MEDI		0.007	microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67390	New	6.5	MEDI		0.01	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Buffer over-read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67393	New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Buffer over-read in SQL Server allows an authorized attacker to disclose information over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-67624	New	6.5	MEDI		0.006		Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67629	New	6.5	MEDI		0.007		Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67630	New	6.5	MEDI		0.007		Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67633	New	6.5	MEDI		0.008	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to deny service over a network.
CVE-2026-67641	New	6.5	MEDI		0.006	microsoft:sql_server_2022, microsoft:sql_server_2025	Integer overflow or wraparound in SQL Server allows an authorized attacker to deny service over a network.
CVE-2026-67645	New	6.5	MEDI		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67648	New	6.5	MEDI		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use of uninitialized resource in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68776	New	6.5	MEDI		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use of uninitialized resource in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68777	New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68778	New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68779	New	6.5	MEDI		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68780	New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-68781	New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68784	New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68898	New	6.5	MEDI		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows iSCSI allows an unauthorized attacker to deny service over a network.
CVE-2026-69267	New	6.5	MEDI		0.003		Insufficient granularity of access control in Windows Connected User Experiences and Telemetry allows an authorized attacker to disclose information locally.
CVE-2026-69297	New	6.5	MEDI		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Storing passwords in a recoverable format in Windows DHCP Server allows an authorized attacker to disclose information over a network.
CVE-2026-69361	New	6.5	MEDI		0.008		Server-side request forgery (ssrf) in Microsoft Exchange Server allows an authorized attacker to perform spoofing over a network.
CVE-2026-69374	New	6.5	MEDI		0.011		Allocation of resources without limits or throttling in Windows SMB Server allows an authorized attacker to deny service over a network.
CVE-2026-69375	New	6.5	MEDI		0.006		Authorization bypass through user-controlled key in Microsoft Exchange Server allows an authorized attacker to perform tampering over a network.
CVE-2026-69395	New	6.5	MEDI		0.009		Use of externally-controlled format string in Active Directory Certificate Services (AD CS) allows an authorized attacker to disclose information over a network.
CVE-2026-69409	New	6.5	MEDI		0.01	microsoft:sharepoint_server	Execution with unnecessary privileges in Microsoft Office SharePoint allows an authorized attacker to disclose information over a network.
CVE-2026-69497	New	6.5	MEDI		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Missing release of memory after effective lifetime in Windows DHCP Server allows an authorized attacker to deny service over a network.
CVE-2026-69562	New	6.5	MEDI		0.009		Out-of-bounds read in SQL Server allows an unauthorized attacker to disclose information over a network.
CVE-2026-69624	New	6.5	MEDI		0.007		Incomplete list of disallowed inputs in Active Directory Certificate Services (AD CS) allows an authorized attacker to perform tampering over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69626	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Buffer over-read in Microsoft Office allows an unauthorized attacker to disclose information over a network.
CVE-2026-69636	New	6.5	MEDI		0.01	microsoft:sharepoint_server	Improper neutralization of special elements used in an sql command ('sql injection') in Microsoft Office SharePoint allows an authorized attacker to disclose information over a network.
CVE-2026-69719	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Buffer over-read in Microsoft Office Word allows an unauthorized attacker to disclose information over a network.
CVE-2026-69734	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Integer overflow or wraparound in Microsoft Office Word allows an unauthorized attacker to disclose information over a network.
CVE-2026-69781	New	6.5	MEDI		0.005	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Missing release of memory after effective lifetime in Windows DHCP Client allows an unauthorized attacker to deny service over an adjacent network.
CVE-2026-69839	New	6.5	MEDI		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Uncaught exception in Windows iSCSI Target Service allows an authorized attacker to deny service over a network.
CVE-2026-70019	New	6.5	MEDI		0.011	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Windows hard link in Windows Compressed Folder allows an unauthorized attacker to disclose information over a network.
CVE-2026-72938	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Access of resource using incompatible type ('type confusion') in Microsoft Office PowerPoint allows an unauthorized attacker to disclose information over a network.
CVE-2026-72939	New	6.5	MEDI		0.011		Null pointer dereference in Windows Routing and Remote Access Service (RRAS) allows an authorized attacker to deny service over a network.
CVE-2026-72942	New	6.5	MEDI		0.009		Out-of-bounds read in Windows Spaceport.sys allows an unauthorized attacker to disclose information over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-72956	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Untrusted pointer dereference in Microsoft Office PowerPoint allows an unauthorized attacker to disclose information over a network.
CVE-2026-72974	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Buffer over-read in Microsoft Office Excel allows an unauthorized attacker to disclose information over a network.
CVE-2026-72975	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Out-of-bounds read in Microsoft Office PowerPoint allows an unauthorized attacker to disclose information over a network.
CVE-2026-72977	New	6.5	MEDI		0.01	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Out-of-bounds read in Microsoft Office PowerPoint allows an unauthorized attacker to disclose information over a network.
CVE-2026-73029	New	6.5	MEDI		0.007	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Buffer over-read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-76000	New	6.5	MEDI		0.003		ColdFusion is affected by an Uncontrolled Resource Consumption vulnerability that could lead to application denial-of-service. An attacker could exploit this vulnerability to exhaust system resources, resulting in an application denial-of-service condition. Exploitation of this issue does not require user interaction.
CVE-2026-76968	New	6.5	MEDI		0.002		SAP Web Dispatcher, Internet Communication Manager and SAP Content Server allows an authenticated low-privileged attacker to access certain administrative functionality or interface and obtain sensitive information about the system state, resulting in information disclosure. This disclosed information could potentially be used to facilitate further attacks. This vulnerabilit...
CVE-2026-76971	New	6.5	MEDI		0.001		Due to a Server-Side Request Forgery (SSRF) vulnerability in SAP Manufacturing Integration and Intelligence, an attacker could cause the server to initiate arbitrary outbound requests. If processed by the application, this behavior could be combined with XML/XSL processing to enable execution of scripts. Successful exploitation could result in a low impact on the confidentialia...
CVE-2026-77896	New	6.5	MEDI		0.007		Integer overflow or wraparound in Remote Desktop Client allows an unauthorized attacker to deny service over a network.
CVE-2026-77911	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Out-of-bounds read in Microsoft Office Word allows an unauthorized attacker to disclose information over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78441	New	6.5	MEDI		0.007		Out-of-bounds read in Windows OLE DB allows an unauthorized attacker to disclose information over a network.
CVE-2026-78453	New	6.5	MEDI		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer underflow (wrap or wraparound) in Microsoft Windows SCSI Class System File allows an unauthorized attacker to disclose information over a network.
CVE-2026-78502	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Out-of-bounds read in Microsoft Office Word allows an unauthorized attacker to disclose information over a network.
CVE-2026-78503	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Out-of-bounds read in Microsoft Office Word allows an unauthorized attacker to disclose information over a network.
CVE-2026-78515	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Out-of-bounds read in Microsoft Office Excel allows an unauthorized attacker to disclose information over a network.
CVE-2026-78520	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Out-of-bounds read in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.
CVE-2026-78522	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, microsoft:word	Out-of-bounds read in Microsoft Office Word allows an unauthorized attacker to disclose information over a network.
CVE-2026-78838	New	6.5	MEDI		0.004		A reflected cross-site scripting (XSS) vulnerability in the grid_datasource.php component of AppNitro MachForm v30 allows attackers to execute arbitrary Javascript in the context of the victim's browser via injecting a crafted payload into the filter[filters][0][field] parameter.
CVE-2026-79379	New	6.5	MEDI		0.003		A buffer overflow in the SBC_DecodeFrames() function of Bestechnic Co., Ltd BES2300 Bluetooth Audio SoC firmware v3.x and earlier and fixed in v.5.0 allows attackers to cause a Denial of Service (DoS) via sending a crafted frame.
CVE-2026-79573	New	6.5	MEDI		0.003		L-ONE v1.0.0 was discovered to contain multiple SQL injection vulnerabilities in the /attachment/getBusinessUploadList component via the busid, id, and taskid parameters. This vulnerability allows attackers to access sensitive database information via a crafted SQL statement.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80073	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, microsoft:outlook	Out-of-bounds read in Microsoft Office Outlook allows an unauthorized attacker to disclose information over a network.
CVE-2026-80076	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Out-of-bounds read in Microsoft Office allows an unauthorized attacker to disclose information over a network.
CVE-2026-80078	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Out-of-bounds read in Microsoft Office allows an unauthorized attacker to disclose information over a network.
CVE-2026-80079	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, microsoft:word	Out-of-bounds read in Microsoft Office Word allows an unauthorized attacker to disclose information over a network.
CVE-2026-80082	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Out-of-bounds read in Microsoft Office allows an unauthorized attacker to disclose information over a network.
CVE-2026-80084	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Out-of-bounds read in Microsoft Office Outlook allows an unauthorized attacker to disclose information over a network.
CVE-2026-80086	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024	Out-of-bounds read in Microsoft Office PowerPoint allows an unauthorized attacker to disclose information over a network.
CVE-2026-80087	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Heap-based buffer overflow in Microsoft Office allows an unauthorized attacker to disclose information over a network.
CVE-2026-80088	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Out-of-bounds read in Microsoft Office Word allows an unauthorized attacker to disclose information over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80089	New	6.5	MEDI		0.009	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Out-of-bounds read in Microsoft Office allows an unauthorized attacker to disclose information over a network.
CVE-2026-80090	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Out-of-bounds read in Microsoft Office Word allows an unauthorized attacker to disclose information over a network.
CVE-2026-80091	New	6.5	MEDI		0.007	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Use of uninitialized resource in Microsoft Office allows an unauthorized attacker to disclose information over a network.
CVE-2026-81377	New	6.5	MEDI		0.008	microsoft:visual_studio_code	Improper limitation of a pathname to a restricted directory ('path traversal') in Visual Studio Code allows an unauthorized attacker to perform tampering over a network.
CVE-2026-81792	New	6.5	MEDI		0.002		Unauthenticated Privilege Escalation in Product Catalog Enquiry for WooCommerce by MultiVendorX <= 6.1.4 versions.
CVE-2026-81802	New	6.5	MEDI		0.002		Unauthenticated Insecure Direct Object References (IDOR) in WpEvently <= 5.6.0 versions.
CVE-2026-82059	New	6.5	MEDI		0.003	mongodb:mongodb	An internal aggregation expression in MongoDB Server was incorrectly registered as accessible to any authenticated user rather than being restricted to internal cluster operations. By crafting a malformed index specification within this expression, an authenticated user with read-only privileges could trigger an assertion failure in the index key generation code path. In cer...
CVE-2026-82069	New	6.5	MEDI		0.003	mongodb:mongodb	A security issue in MongoDB Server's query statistics serialization on the router allows users with monitoring privileges to access unredacted search query text from other users' operations. An improper conditional check in the serialization logic causes the data redaction mechanism to be bypassed when processing search queries through the sharded cluster router. This result...
CVE-2026-84282	New	6.5	MEDI		0.002		A Server-Side Request Forgery (SSRF) vulnerability exists in the ONLYOFFICE ownCloud Integration plugin version 9.12. The /apps/onlyoffice/ajax/settings/address endpoint does not sufficiently validate the user-supplied Document Server URL before initiating outbound connections. An authenticated administrator can manipulate the document server parameter to cause the ownCloud ...
CVE-2026-84391	New	6.5	MEDI		0.002		A use of uninitialized variable vulnerability in Fortinet FortiAnalyzer 7.6.3 through 7.6.6 may allow attacker to denial of service via <insert attack vector here>
CVE-2026-84685	New	6.5	MEDI		0.002		The react-native-auth0 SDK's web platform implementation does not scope its in-memory token cache to individual user sessions when operating in a server-side rendering (SSR) environment where module state persists across HTTP requests. Under the listed preconditions, tokens cached in module memory can be retrieved across subsequent requests processed by the same server runtime.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86077	New	6.5	MEDI		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 2.37.7 and 2.38.2, the /chat WebSocket route accepted a resumeToken and resumed a paused execution without checking that the target node supported chat messages. An anonymous form submitter who received that token could reuse it on the chat route to release a Send-and-Wait, non-chat HITL, or Wait approval gate. The...
CVE-2026-86078	New	6.5	MEDI		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 2.37.7 and 2.38.2, the Instance AI workflow summary used node names and connection keys from stored workflows as ordinary object keys. A workflow submitted through the REST API could contain __proto__ or constructor, causing nested writes to reach Object.prototype in the main n8n process and disrupt later requests....
CVE-2026-86079	New	6.5	MEDI		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the Elasticsearch and ElasticSecurity nodes interpolated workflow-controlled index and document identifiers directly into REST request paths. An identifier containing path separators or dot segments could select another index or a cluster administration endpoint under the stored Elasti...
CVE-2026-86082	New	6.5	MEDI		0.002	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the OpenAI Chat Model node enforced credential allowed-domain restrictions for normal calls but not for the model-search dropdown. A workflow editor could set options.baseUrl to an arbitrary host and make the searchModels path send the openAiApi credential there. The affected implement...
CVE-2026-86550	New	6.5	MEDI		0.003		NuBrowser lacks protocol whitelist validation for the S.browser_fallback_url field of intent://, allowing attackers to inject javascript: URLs via 302 redirects. This results in a universal cross-site scripting (UXSS) vulnerability that enables script execution within the origin of arbitrary websites.
CVE-2026-86597	New	6.5	MEDI		0.001		Insertion of sensitive information into log files in the Snowflake Python, Go, JDBC, Node.js, PHP PDO, and ODBC drivers allowed authentication tokens, query-result encryption keys, pre-signed cloud-storage URLs, and SAML assertions to be written to diagnostic logs in circumstances where the available log redaction did not cover all affected log paths and data types. An attac...
CVE-2026-86726	New	6.5	MEDI		0.003		AVideo through 29.0 contains an information disclosure vulnerability in restreamsActive.json.php that allows authenticated streamers to enumerate source stream keys and identities of all other streamers' active restreams. The endpoint fails to filter results by user ownership, exposing sensitive transmission credentials and streamer identity across all accounts to any user w...
CVE-2026-86731	New	6.5	MEDI		0.002		Craft CMS versions 5.0.0-RC1 through 5.10.11 are missing an admin-target guard in UsersController::actionActivateUser (the users/activate-user action). While the action requires the administrateUsers permission, it does not call requireAdmin() when the targeted user is an administrator, unlike the mirror action actionDeactivateUser. As a result, an authenticated control pane...
CVE-2026-12230	New	6.4	MEDI		0.002		The LearnPress – WordPress LMS Plugin for Create and Sell Online Courses plugin for WordPress is vulnerable to Stored Cross-Site Scripting via the 'layout_custom_css' parameter in all versions up to, and including, 4.3.9.1 due to insufficient input sanitization and output escaping. This makes it possible for authenticated attackers, with contributor-level access and above, t...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-33388	New	6.4	MEDI		0.003		An access control vulnerability was discovered in the Credentials Manager functionality due to insufficient validation of user privileges. A remote authenticated user with limited privileges can view a limited subset of the available entries in the Credentials Manager. The actual credential values are not directly visible, but the user can delete entries or edit their proper...
CVE-2026-69874	New	6.4	MEDI		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Untrusted pointer dereference in Windows ALPC allows an authorized attacker to elevate privileges locally.
CVE-2026-69878	New	6.4	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Heap-based buffer overflow in Windows DHCP Server allows an authorized attacker to execute code locally.
CVE-2026-70582	New	6.4	MEDI		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Management Instrumentation allows an authorized attacker to elevate privileges locally.
CVE-2026-71338	New	6.4	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Double free in Windows Failover Cluster allows an authorized attacker to elevate privileges locally.
CVE-2026-72947	New	6.4	MEDI		0.003		Integer underflow (wrap or wraparound) in Windows File History Service allows an authorized attacker to elevate privileges locally.
CVE-2026-76931	New	6.4	MEDI		0.002		The Zephyr Project Manager plugin for WordPress is vulnerable to Stored Cross-Site Scripting via the 'message' parameter in all versions up to, and including, 3.3.205 due to insufficient input sanitization and output escaping. This makes it possible for authenticated attackers, with Custom-level access and above, to inject arbitrary web scripts in pages that will execute whe...
CVE-2026-77887	New	6.4	MEDI		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an authorized attacker to execute code locally.
CVE-2026-77891	New	6.4	MEDI		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an authorized attacker to execute code locally.
CVE-2026-53639	New	6.3	MEDI		0.005		Syllus is an Open Source eCommerce Framework on Symfony. Starting in version 2.0.0 and prior to version 2.0.18, 2.1.15, and 2.2.6, the `GET /api/v2/shop/payment-requests/{hash}` and `PUT /api/v2/shop/payment-requests/{hash}` endpoints look up the payment request solely by the hash from the URL. No ownership check is performed against the authenticated customer or the underly...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81824	New	6.3	MEDI		0.002		The vulnerability, if exploited, could allow a miscreant to run arbitrary JavaScript code in a browser session of a PIMBoards user who was socially engineered to click on a malicious link.
CVE-2026-81904	New	6.3	MEDI		0.003		Concrete CMS below 9.5.3 registered view assets for every sub-block of a Stack, Container, or layout area without checking whether the requesting user could view that sub-block. An unauthenticated visitor could recover configuration values emitted by a restricted sub-block's asset registration — such as a site's configured Google Maps API key — from any public page embedding...
CVE-2026-81994	New	6.3	MEDI		0.003	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an Improperly Controlled Modification of Object Prototype Attributes ('Prototype Pollution') vulnerability that could lead to arbitrary file system read. An attacker could exploit this vulnerability to access sensitive files and directories outside the intended access scope. Exploitation of this issue requires user interaction in that a victim m...
CVE-2026-81997	New	6.3	MEDI		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an Incorrect Authorization vulnerability that could result in a Security feature bypass. An attacker could leverage this vulnerability to bypass security measures and gain unauthorized write access. Exploitation of this issue requires user interaction in that a victim must open a malicious file. Scope is changed.
CVE-2026-84942	New	6.3	MEDI		0.003		Improper input validation in the Vega expression function implementation in OpenSearch Dashboards allows a remote authenticated actor with dashboard write permissions to execute arbitrary JavaScript in the context of other users' browser sessions by saving a crafted Vega visualization. The checkForFunctionProperty validation routine failed to recurse into arrays of objects, ...
CVE-2026-86590	New	6.3	MEDI		0.004		In Eclipse Che versions 7.79.0 through 7.121.0, the dashboard backend's POST /dashboard/api/data/resolver endpoint passes a caller-supplied URL directly to an outbound HTTP GET request with no host filtering. An authenticated user can exploit this server-side request forgery (SSRF) to read responses from internal network addresses, including the cloud instance metadata servi...
CVE-2026-18090	New	6.1	MEDI		0.002		A flaw was found in gdk-pixbuf. This vulnerability allows a remote attacker to cause a heap out-of-bounds read by providing a specially crafted Apple Icon Image (.icns) file. The uncompress() function, which handles RLE-encoded ICNS icon data, fails to validate the source buffer's boundaries during decompression. This can lead to a denial of service, where the application cr...
CVE-2026-19872	New	6.1	MEDI		0.003		HTML::FormHandler versions before 0.410000 for Perl allow cross-site scripting via a submitted value rendered unescaped in an error message. The wrappers and renderers that emit a form's errors interpolate the error string straight into HTML with no escaping. Two of the library's own messages, no_match and not_allowed, splice the submitted value into that string, and a fail...
CVE-2026-63523	New	6.1	MEDI		0.007	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Improper neutralization of input during web page generation ('cross-site scripting') in Skype for Business allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-69642	New	6.1	MEDI		0.003	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	Improper neutralization of input during web page generation ('cross-site scripting') in Skype for Business allows an unauthorized attacker to perform spoofing over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-76002	New	6.1	MEDI		0.007		ColdFusion is affected by a reflected Cross-Site Scripting (XSS) vulnerability. If an attacker is able to convince a victim to visit a URL referencing a vulnerable page, malicious JavaScript content may be executed within the context of the victim's browser. Scope is changed.
CVE-2026-77654	New	6.1	MEDI		0.001		Improper Privilege Management vulnerability in Horizon Security Analyzer (formerly AlgoSec Firewall Analyzer) on Linux, 64 bit allows Privilege Escalation and Parameter Injection. A local user with access to the command line may escalate their privileges by abusing the parameters of a command that is approved in the sudoers file. This issue affects Horizon Security Analy...
CVE-2026-78738	New	6.1	MEDI		0.002		Silverpeas Core 6.4.6 is vulnerable to Cross Site Scripting (XSS) via the Document management file upload feature.
CVE-2026-78741	New	6.1	MEDI		0.002		Silverpeas Core <=6.4.6 is vulnerable to Cross Site Scripting (XSS) in the wysiwyg-CKEditor image upload feature.
CVE-2026-78742	New	6.1	MEDI		0.002		Silverpeas Core <=6.4.6 is vulnerable to Cross Site Scripting (XSS) via the Multimedia library application introduction.
CVE-2026-85484	New	6.1	MEDI		0.003		HTML::FormHandler versions before 0.410002 for Perl render option group labels and radio button labels into HTML without escaping. The Select, RadioGroup, CheckboxGroup and HorizCheckboxGroup widgets render a group label unescaped, Select into a label attribute and the other three into element content. RadioGroup also renders each radio button's own label unescaped. Any ap...
CVE-2026-85485	New	6.1	MEDI		0.002		HTML::FormHandler versions before 0.410002 for Perl render some error messages into HTML without escaping. The Table form layout and the Bootstrap 2 and 3 wrappers splice each error string straight into the surrounding markup. Version 0.410000, the fix for CVE-2026-19872, escaped the equivalent values in the other layouts and wrappers, and 0.410002 extended that to these th...
CVE-2026-85630	New	6.1	MEDI		0.003		HTML::FormHandler versions before 0.410002 for Perl render field attributes into HTML without escaping using the process_attrs method. Any application with fields or field labels where some attributes are built from data rather than literals allows attacker-influenced text in an attribute value that can override the field attributes or embed JavaScript in rendered pages. F...
CVE-2026-56101	New	6.0	MEDI		0.004		OpenBSD before commit 1ee99df contains an inverted comparison vulnerability in the ieee80211_michael_mic_failure() function within sys/net80211/ieee80211_crypto_tkip.c that allows unauthenticated attackers within RF range to trigger denial of service by sending two malformed TKIP frames separated by more than 60 seconds. Attackers can exploit the reversed TKIP MIC failure co...
CVE-2026-78216	New	6.0	MEDI		0.002		AshLua exposes Ash read actions to Lua scripts run through an eval action. A read call accepts an operation (list, min, max, first, sum, avg) that builds an ad-hoc Ash.Query.Aggregate over a named field and returns its raw value. Ash field policies redact forbidden fields on returned records (replacing them with %Ash.ForbiddenField{}), but that redaction does not apply to a...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78230	New	6.0	MEDI		0.002		AshAi exposes Ash read actions to language-model tool calls. The read tool accepts an aggregate result type (min, max, sum, avg) that builds an ad-hoc Ash.Query.Aggregate over a named field and returns its raw value. Ash field policies redact forbidden fields on returned records (replacing them with %Ash.ForbiddenField{}), but that redaction does not apply to aggregate valu...
CVE-2026-78552	New	6.0	MEDI		0.003		The Okta Access Gateway does not apply its Lua directive restriction to the application-level custom configuration field. The field is interpolated directly into the nginx server block without inspection, resulting in execution of injected directives.
CVE-2026-78622	New	6.0	MEDI		0.001		The Okta Verify for Windows uninstaller does not verify whether the user data directory is a filesystem junction before deleting its contents with elevated privileges. The delete operation follows the junction target, resulting in recursive deletion of unintended directory contents.
CVE-2026-82056	New	6.0	MEDI		0.002	mongodb:mongodb	A race condition in MongoDB server's text index query parsing can cause a heap use-after-free read when handling upsert retry paths. Under certain concurrent index lifecycle operations, a raw pointer to internal text index metadata may be dereferenced after the underlying structures have been freed, leading to a server crash. An authenticated user with readWrite privileges c...
CVE-2026-82063	New	6.0	MEDI		0.003	mongodb:mongodb	A use-after-free security issue in the cursor management component of MongoDB Server allows an authenticated user to cause a denial of service. Under specific timing conditions during cursor operations, a stale pointer to a freed resource may be retained and subsequently dereferenced during cursor cleanup, leading to a server process crash.
CVE-2026-16004	New	5.9	MEDI		0.001		Exposed IOCTL with Insufficient Access Control in Armoury Crate driver allows a local user to read and write arbitrary PCI/PCIe configuration space via crafted IOCTL requests by bypassing the driver's verification. Refer to the ' Security Update for Armoury Crate App' section on the ASUS Security Advisory for more information.
CVE-2026-69304	New	5.9	MEDI		0.008		Improper handling of highly compressed data (data amplification) in ASP.NET Core allows an unauthorized attacker to deny service over a network.
CVE-2026-69382	New	5.9	MEDI		0.004		Use of a broken or risky cryptographic algorithm in Microsoft Exchange Server allows an unauthorized attacker to disclose information over a network.
CVE-2026-70091	New	5.9	MEDI		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows DNS allows an unauthorized attacker to deny service over a network.
CVE-2026-72978	New	5.9	MEDI		0.008		Allocation of resources without limits or throttling in Active Directory Federation Services (AD FS) allows an unauthorized attacker to deny service over a network.
CVE-2026-73310	New	5.9	MEDI		0.004	xenforo:xenforo	XenForo before 2.3.13 contains an authorization flaw in the OAuth2 token endpoint that allows attackers controlling any allowlisted redirect URI to bypass redirect URI binding by submitting a different allowlisted URI than the one recorded at authorization time. Attackers can exchange an intercepted authorization code using a mismatched redirect URI to steal OAuth2 tokens fr...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75809	New	5.9	MEDI		0.001		Exposed IOCTL with insufficient access control in ASUS Armoury Crate allows a local user to disclosure information and disabling device functionality by bypassing driver authentication and using IOCTLs to read from and write to PCIe configuration space.Refer to the ' Security Update for Armoury Crate App ' section on the ASUS Security Advisory for more information.
CVE-2026-78620	New	5.9	MEDI		0.003		The Okta Access Gateway Kerberos configuration handler does not validate file paths specified in event payloads before writing file contents. The path from the event payload is used directly as the write destination, resulting in files being written to unintended locations on the appliance filesystem.
CVE-2026-16005	New	5.8	MEDI		0.001		Release of Invalid Pointer or Reference in Armoury Crate driver allows a local user to free arbitrary memory via a crafted IOCTL request by bypassing the driver's verification, which can corrupt data structures and cause a system crash (BSOD).Refer to the ' Security Update for Armoury Crate App ' section on the ASUS Security Advisory for more information.
CVE-2026-69559	New	5.8	MEDI		0.003		Origin validation error in Microsoft Teams for Android allows an authorized attacker to disclose information over a network.
CVE-2026-75811	New	5.8	MEDI		0.001		Improper Restriction of Software Interfaces to Hardware Features in ASUS Armoury Crate allows a local user to modify hardware configuration settings and potentially cause hardware damage by bypassing driver authentication and accessing critical model-specific registers.Refer to the ' Security Update for Armoury Crate App' section on the ASUS Security Advisory for more inform...
CVE-2026-16006	New	5.7	MEDI		0.001		Exposure of Sensitive System Information to an Unauthorized Control Sphere in Armoury Crate driver allows a local user to obtain kernel virtual addresses via a crafted IOCTL request by bypassing the driver's verification, potentially providing further insight into the kernel memory layout.Refer to the ' Security Update for Armoury Crate App ' section on the ASUS Security Ad...
CVE-2026-18023	New	5.7	MEDI		0.001		Sensitive Information in Resource Not Removed Before Reuse in ASUS Armoury Crate driver allows a local user to disclose sensitive information from uninitialized memory via a crafted IOCTL request that bypasses the driver's security verification mechanism. Refer to the ' Security Update for Armoury Crate App ' section on the ASUS Security Advisory for more information.
CVE-2026-68874	New	5.7	MEDI		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Program Compatibility Assistant Service allows an authorized attacker to disclose information over a network.
CVE-2026-69317	New	5.7	MEDI		0.008		Out-of-bounds read in Remote Desktop Client allows an authorized attacker to disclose information over a network.
CVE-2026-69349	New	5.7	MEDI		0.008		Use of uninitialized resource in Windows Management Instrumentation allows an authorized attacker to disclose information over a network.
CVE-2026-69372	New	5.7	MEDI		0.008		Out-of-bounds read in Windows Network File System allows an authorized attacker to deny service over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69393	New	5.7	MEDI		0.008		Out-of-bounds read in Windows Spaceport.sys allows an authorized attacker to disclose information over a network.
CVE-2026-69405	New	5.7	MEDI		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Missing release of memory after effective lifetime in Windows DHCP Server allows an authorized attacker to deny service over an adjacent network.
CVE-2026-69416	New	5.7	MEDI		0.006		Buffer over-read in Windows DHCP Server allows an authorized attacker to deny service over an adjacent network.
CVE-2026-69507	New	5.7	MEDI		0.008		Insertion of sensitive information into externally-accessible file or directory in Microsoft Windows Search Component allows an authorized attacker to disclose information over a network.
CVE-2026-69552	New	5.7	MEDI		0.009		Generation of error message containing sensitive information in Windows Print Spooler Components allows an authorized attacker to disclose information over a network.
CVE-2026-69569	New	5.7	MEDI		0.009		Untrusted pointer dereference in Windows Print Spooler Components allows an authorized attacker to deny service over a network.
CVE-2026-69572	New	5.7	MEDI		0.009		Out-of-bounds read in Windows SMB Client allows an authorized attacker to disclose information over a network.
CVE-2026-69591	New	5.7	MEDI		0.009	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to disclose information over a network.
CVE-2026-69637	New	5.7	MEDI		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an authorized attacker to deny service over an adjacent network.
CVE-2026-69679	New	5.7	MEDI		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an authorized attacker to deny service over an adjacent network.
CVE-2026-69723	New	5.7	MEDI		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of sensitive system information to an unauthorized control sphere in Windows Kernel allows an authorized attacker to disclose information over a network.
CVE-2026-75808	New	5.7	MEDI		0.001		Allocation of Resources Without Limits or Throttling in ASUS Armoury Crate allows a local user to cause a denial-of-service condition through system memory exhaustion by bypassing driver authentication and allocating an unrestricted amount of memory.Refer to the ' Security Update for Armoury Crate App ' section on the ASUS Security Advisory for more information.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75810	New	5.7	MEDI		0.001		Exposed Dangerous Method or Function in ASUS Armoury Crate allow a local user to cause a brief system stall by bypassing driver authentication and sending requests to trigger system management interrupts (SMIs). Repeatedly triggering SMI may lead to a denial-of-service (DoS) condition.Refer to the ' Security Update for Armoury Crate App ' section on the ASUS Security Advisor...
CVE-2026-78629	New	5.6	MEDI		0.001		The Okta Hyperdrive agent plugin returns a success response without a signed SAML assertion when the organization's policy requires no MFA for a given user. The response contains only a bare boolean validation indicator with no cryptographic artifact, resulting in an unverifiable authentication verdict being delivered to the relying application.
CVE-2026-28584	New	5.5	MEDI		0.001	google:android	In createSessionInternal of PackageInstallerService.java, there is a possible way to permanently DoS the device due to a logic error in the code. This could lead to local denial of service with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28596	New	5.5	MEDI		0.001	google:android	In parseInterventionFromXml of GameManagerService.java, there is a possible permanent denial of service due to resource exhaustion. This could lead to local denial of service with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28617	New	5.5	MEDI		0.001	google:android	In add of WifiNetworkSuggestionsManager.java, there is a possible persistent DOS due to resource exhaustion. This could lead to local denial of service with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28633	New	5.5	MEDI		0.001	google:android	In initForUserNoTracing of VoiceInteractionManagerService.java, there is a possible persistent denial of service due to resource exhaustion. This could lead to local denial of service with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-49883	New	5.5	MEDI		0.001	google:android	In checkReadPermission of PermissionsManager.java, there is a possible way to monitor sensitive device state data due to a missing permission check. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-54611	New	5.5	MEDI		0.005		InstantCMS is a free and open source content management system. Versions prior to 2.18.2 have a Remote Code Execution (RCE) issue that allows remote authenticated attackers to execute any PHP code via the component installer. It is possible to upload a malicious component into the server, however, it won't be installed, but upload files will be executed. Normally all php fil...
CVE-2026-68830	New	5.5	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper link resolution before file access ('link following') in Windows Universal Plug and Play (UPnP) Device Host allows an authorized attacker to disclose information locally.
CVE-2026-68831	New	5.5	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Files or directories accessible to external parties in Windows Defender Firewall Service allows an authorized attacker to disclose information locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-68842	New	5.5	MEDI		0.004	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1	Exposure of sensitive system information to an unauthorized control sphere in Windows MIDI Service Module allows an authorized attacker to disclose information locally.
CVE-2026-68843	New	5.5	MEDI		0.003		Use after free in Microsoft Office Word allows an authorized attacker to disclose information locally.
CVE-2026-68851	New	5.5	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Buffer over-read in Windows NTFS allows an authorized attacker to disclose information locally.
CVE-2026-68852	New	5.5	MEDI		0.003		Use of uninitialized resource in Microsoft Account allows an authorized attacker to disclose information locally.
CVE-2026-68873	New	5.5	MEDI		0.005	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Insertion of sensitive information into log file in Windows Program Compatibility Assistant Service allows an authorized attacker to disclose information locally.
CVE-2026-68881	New	5.5	MEDI		0.003		Out-of-bounds read in Microsoft Standard XPS allows an authorized attacker to disclose information locally.
CVE-2026-68886	New	5.5	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Network Connection Broker allows an authorized attacker to disclose information locally.
CVE-2026-68895	New	5.5	MEDI		0.003		Numeric truncation error in Internet Storage Name Service allows an authorized attacker to disclose information locally.
CVE-2026-69286	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to disclose information locally.
CVE-2026-69288	New	5.5	MEDI		0.003		Use of uninitialized resource in Windows GDI+ allows an authorized attacker to disclose information locally.
CVE-2026-69294	New	5.5	MEDI		0.003		Generation of error message containing sensitive information in Microsoft COM for Windows allows an authorized attacker to disclose information locally.
CVE-2026-69303	New	5.5	MEDI		0.004		Out-of-bounds read in Push Message Routing Service allows an authorized attacker to disclose information locally.
CVE-2026-69308	New	5.5	MEDI		0.004		Out-of-bounds read in Microsoft Standard XPS allows an authorized attacker to disclose information locally.
CVE-2026-69315	New	5.5	MEDI		0.005		Exposure of sensitive system information to an unauthorized control sphere in Windows License Manager allows an authorized attacker to disclose information locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69318	New	5.5	MEDI		0.004		Out-of-bounds read in Windows Imaging Component allows an authorized attacker to disclose information locally.
CVE-2026-69321	New	5.5	MEDI		0.003		Missing authentication for critical function in Windows Power Dependency Coordinator allows an authorized attacker to perform tampering locally.
CVE-2026-69339	New	5.5	MEDI		0.005		Exposure of sensitive system information to an unauthorized control sphere in Windows MIDI Service Module allows an authorized attacker to disclose information locally.
CVE-2026-69343	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Overlay Filter allows an authorized attacker to disclose information locally.
CVE-2026-69344	New	5.5	MEDI		0.004		Out-of-bounds read in Windows Print Spooler Components allows an authorized attacker to disclose information locally.
CVE-2026-69345	New	5.5	MEDI		0.004		Out-of-bounds read in Microsoft Standard XPS allows an authorized attacker to disclose information locally.
CVE-2026-69351	New	5.5	MEDI		0.005		Exposure of private personal information to an unauthorized actor in Windows Universal Plug and Play (UPnP) Device Host allows an authorized attacker to disclose information locally.
CVE-2026-69353	New	5.5	MEDI		0.004		Out-of-bounds read in Windows Text Shaping allows an authorized attacker to disclose information locally.
CVE-2026-69367	New	5.5	MEDI		0.004		Out-of-bounds read in Microsoft Standard XPS allows an authorized attacker to disclose information locally.
CVE-2026-69369	New	5.5	MEDI		0.003		Out-of-bounds read in Windows DNS allows an authorized attacker to disclose information locally.
CVE-2026-69376	New	5.5	MEDI		0.004		Out-of-bounds read in Microsoft Standard XPS allows an authorized attacker to disclose information locally.
CVE-2026-69390	New	5.5	MEDI		0.004		Out-of-bounds read in Windows Spaceport.sys allows an authorized attacker to disclose information locally.
CVE-2026-69403	New	5.5	MEDI		0.003		Missing authorization in Windows SMB Server allows an authorized attacker to disclose information locally.
CVE-2026-69406	New	5.5	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of sensitive system information to an unauthorized control sphere in Windows Kernel allows an authorized attacker to disclose information locally.
CVE-2026-69453	New	5.5	MEDI		0.003		Missing authorization in Microsoft Windows Search Component allows an authorized attacker to perform tampering locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69457	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Driver allows an authorized attacker to disclose information locally.
CVE-2026-69504	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to disclose information locally.
CVE-2026-69527	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Mass Storage Class Driver allows an authorized attacker to disclose information locally.
CVE-2026-69531	New	5.5	MEDI		0.003		Unintended proxy or intermediary ('confused deputy') in Microsoft Windows Speech allows an authorized attacker to perform tampering locally.
CVE-2026-69554	New	5.5	MEDI		0.003		Missing authentication for critical function in Microsoft Windows Search Component allows an authorized attacker to perform tampering locally.
CVE-2026-69568	New	5.5	MEDI		0.004		Out-of-bounds read in Windows Storage Spaces Controller allows an authorized attacker to disclose information locally.
CVE-2026-69609	New	5.5	MEDI		0.004		Out-of-bounds read in Windows Win32K allows an authorized attacker to disclose information locally.
CVE-2026-69616	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Remote Desktop Services allows an authorized attacker to disclose information locally.
CVE-2026-69618	New	5.5	MEDI		0.004		Out-of-bounds read in Windows SMB Client allows an authorized attacker to disclose information locally.
CVE-2026-69627	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Remote Desktop Licensing Service allows an authorized attacker to disclose information locally.
CVE-2026-69672	New	5.5	MEDI		0.004		Use of uninitialized resource in Windows DNS allows an authorized attacker to disclose information locally.
CVE-2026-69674	New	5.5	MEDI		0.003		Missing authentication for critical function in Windows Modern Device Management (MDM) allows an authorized attacker to bypass a security feature locally.
CVE-2026-69684	New	5.5	MEDI		0.005		Generation of error message containing sensitive information in Windows Error Reporting allows an authorized attacker to disclose information locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69741	New	5.5	MEDI		0.004		Out-of-bounds read in Windows Spaceport.sys allows an authorized attacker to disclose information locally.
CVE-2026-69770	New	5.5	MEDI		0.004		Use of uninitialized resource in Windows Spaceport.sys allows an authorized attacker to disclose information locally.
CVE-2026-69794	New	5.5	MEDI		0.004		Buffer over-read in Windows Encrypting File System (EFS) allows an authorized attacker to disclose information locally.
CVE-2026-69808	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Win32K allows an authorized attacker to disclose information locally.
CVE-2026-69862	New	5.5	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Wireless Wide Area Network Service allows an authorized attacker to disclose information locally.
CVE-2026-70145	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Microsoft Windows Search Component allows an authorized attacker to disclose information locally.
CVE-2026-70290	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use of uninitialized resource in Windows Win32 Kernel Subsystem allows an authorized attacker to disclose information locally.
CVE-2026-71341	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Partition Management Driver allows an authorized attacker to disclose information locally.
CVE-2026-72937	New	5.5	MEDI		0.004		Out-of-bounds read in Storage Port Driver allows an authorized attacker to disclose information locally.
CVE-2026-72945	New	5.5	MEDI		0.004		Use of uninitialized resource in Windows Task Scheduler allows an authorized attacker to disclose information locally.
CVE-2026-72964	New	5.5	MEDI		0.003		Missing authentication for critical function in Windows Internet Connection Sharing (ICS) allows an authorized attacker to perform tampering locally.
CVE-2026-72966	New	5.5	MEDI		0.003		Missing authorization in Windows Remote Access Connection Manager allows an authorized attacker to perform tampering locally.
CVE-2026-73004	New	5.5	MEDI		0.002		Missing authentication for critical function in Windows Autopilot allows an authorized attacker to perform tampering locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-73008	New	5.5	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of private personal information to an unauthorized actor in Windows Biometric Service allows an authorized attacker to disclose information locally.
CVE-2026-77488	New	5.5	MEDI		0.003	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Integer underflow (wrap or wraparound) in SQL Server allows an authorized attacker to disclose information locally.
CVE-2026-77491	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows GDI allows an unauthorized attacker to disclose information locally.
CVE-2026-77492	New	5.5	MEDI		0.003		Out-of-bounds read in Storage Port Driver allows an authorized attacker to disclose information locally.
CVE-2026-78454	New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows CD-ROM Driver allows an authorized attacker to disclose information locally.
CVE-2026-78506	New	5.5	MEDI		0.005	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Improper null termination in Microsoft Office Word allows an unauthorized attacker to disclose information locally.
CVE-2026-78513	New	5.5	MEDI		0.005	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Out-of-bounds read in Microsoft Office PowerPoint allows an unauthorized attacker to disclose information locally.
CVE-2026-79910	New	5.5	MEDI		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an out-of-bounds read vulnerability that could lead to disclosure of sensitive memory. An attacker could leverage this vulnerability to disclose sensitive information. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-80160	New	5.5	MEDI		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an out-of-bounds read vulnerability that could lead to disclosure of sensitive memory. An attacker could leverage this vulnerability to disclose sensitive information. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-80162	New	5.5	MEDI		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Use After Free vulnerability that could lead to disclosure of sensitive memory. An attacker could leverage this vulnerability to disclose sensitive information. Exploitation of this issue requires user interaction in that a victim must open a malicious file.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81387	New	5.5	MEDI		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Exposure of sensitive system information to an unauthorized control sphere in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.
CVE-2026-81390	New	5.5	MEDI		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Out-of-bounds read in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.
CVE-2026-81391	New	5.5	MEDI		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Use of uninitialized resource in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.
CVE-2026-81392	New	5.5	MEDI		0.005	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Out-of-bounds read in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.
CVE-2026-81393	New	5.5	MEDI		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Out-of-bounds read in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.
CVE-2026-81394	New	5.5	MEDI		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Exposure of sensitive system information to an unauthorized control sphere in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.
CVE-2026-81395	New	5.5	MEDI		0.005	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Out-of-bounds read in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.
CVE-2026-81399	New	5.5	MEDI		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Buffer over-read in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.
CVE-2026-81400	New	5.5	MEDI		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Out-of-bounds read in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.
CVE-2026-81401	New	5.5	MEDI		0.005	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Access of resource using incompatible type ('type confusion') in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81958	New	5.5	MEDI		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Use of uninitialized resource in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.
CVE-2026-81977	New	5.5	MEDI		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an Integer Underflow (Wrap or Wraparound) vulnerability that could lead to disclosure of sensitive memory. An attacker could leverage this vulnerability to disclose sensitive information. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81978	New	5.5	MEDI		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an out-of-bounds read vulnerability that could lead to disclosure of sensitive memory. An attacker could leverage this vulnerability to disclose sensitive information. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81982	New	5.5	MEDI		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an out-of-bounds read vulnerability that could lead to disclosure of sensitive memory. An attacker could leverage this vulnerability to disclose sensitive information. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81984	New	5.5	MEDI		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Use After Free vulnerability that could lead to disclosure of sensitive memory. An attacker could leverage this vulnerability to disclose sensitive information. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81991	New	5.5	MEDI		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an out-of-bounds read vulnerability that could lead to disclosure of sensitive memory. An attacker could leverage this vulnerability to disclose sensitive information. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-81993	New	5.5	MEDI		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by a Heap-based Buffer Overflow vulnerability that could lead to disclosure of sensitive memory. An attacker could leverage this vulnerability to disclose sensitive information. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-82001	New	5.5	MEDI		0.002	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an Uncontrolled Resource Consumption vulnerability that could lead to application denial-of-service. An attacker could exploit this vulnerability to exhaust system resources, resulting in an application denial-of-service condition. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-83501	New	5.5	MEDI		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Out-of-bounds read in Windows Virtualization-Based Security (VBS) Enclave allows an authorized attacker to disclose information locally.
CVE-2026-83949	New	5.5	MEDI		0.004	microsoft:365_apps, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, microsoft:word	Buffer over-read in Microsoft Office Word allows an unauthorized attacker to disclose information locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83951	New	5.5	MEDI		0.004	microsoft:365_apps, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, microsoft:word	Buffer over-read in Microsoft Office Word allows an unauthorized attacker to disclose information locally.
CVE-2026-83991	New	5.5	MEDI		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Missing authentication for critical function in Windows Cloud Files Mini Filter Driver allows an authorized attacker to perform tampering locally.
CVE-2026-85875	New	5.5	MEDI		0.004	microsoft:365_apps, microsoft:excel, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:of	Out-of-bounds read in Microsoft Office Excel allows an unauthorized attacker to disclose information locally.
CVE-2026-86084	New	5.5	MEDI		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the public OIDC login and callback endpoints completed authentication even when OIDC was not the enabled active authentication method. An Enterprise administrator who had configured and later disabled an identity provider still exposed a working route that could issue valid sessions. T...
CVE-2026-86511	New	5.5	MEDI		0.004		A vulnerability was found in java-json-tools jackson-coreutils 2.0. Affected by this vulnerability is the function BigDecimal.toPlainString of the file src/main/java/com/github/fge/jackson/JacksonUtils.java. Performing a manipulation results in resource consumption. The attack may be initiated remotely. The exploit has been made public and could be used. The project was info...
CVE-2026-86513	New	5.5	MEDI		0.004		A security flaw has been discovered in java-json-tools jackson-coreutils 2.0. This vulnerability affects the function TreePointer.tokensFromInput of the file src/main/java/com/github/fge/jackson/jsonpointer/TreePointer.java of the component JSON Pointer parser. The manipulation results in allocation of resources. The attack can be executed remotely. The exploit has been rele...
CVE-2026-86519	New	5.5	MEDI		0.003		A vulnerability was found in code-projects Student Crud Operation 1.0. This impacts an unknown function of the file /card_activation.sql of the component Backup File Handler. The manipulation results in information disclosure. The attack can be launched remotely. The exploit has been made public and could be used.
CVE-2026-86665	New	5.5	MEDI		0.004		A vulnerability was identified in aircheng-org iWebShop-5 up to 5.15. This issue affects the function Update::index of the file controllers/update.php. The manipulation leads to missing authorization. Remote exploitation of the attack is possible. The exploit is publicly available and might be used. The project was informed of the problem early through an issue report but ha...
CVE-2026-86666	New	5.5	MEDI		0.005		A security flaw has been discovered in aircheng-org iWebShop-5 up to 5.15. Impacted is the function upload_json/uploadFile of the file controllers/pic.php. The manipulation results in unrestricted upload. The attack can be executed remotely. The exploit has been released to the public and may be used for attacks. The project was informed of the problem early through an issue...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86669	New	5.5	MEDI		0.004		A vulnerability was detected in aircheng-org iWebShop-5 up to 5.15. This affects the function Login of the file controllers/systemseller.php. Performing a manipulation of the argument Name results in improper authentication. It is possible to initiate the attack remotely. The exploit is now public and may be used. The project was informed of the problem early through an issu...
CVE-2026-86672	New	5.5	MEDI		0.003		A vulnerability has been found in ningzichun Student Management System up to 98760f5711cf6dc8b4adca53a9e207ca49b02ebf. Affected is an unknown function of the file example.7z of the component Backup Handler. The manipulation leads to information disclosure. The attack can be initiated remotely. The exploit has been disclosed to the public and may be used. Continuous delivery ...
CVE-2026-86673	New	5.5	MEDI		0.003		A vulnerability was determined in ningzichun Student Management System up to 98760f5711cf6dc8b4adca53a9e207ca49b02ebf. Affected by this issue is the function mysqli_connect of the file config/database.php of the component Database Connection. This manipulation causes hard-coded credentials. The attack may be initiated remotely. The exploit has been publicly disclosed and may...
CVE-2026-86716	New	5.5	MEDI		0.003		A vulnerability was determined in Cesanta mJS up to 1.26. Affected is the function skip_spaces_and_comments of the file src/mjs_tok.c. Executing a manipulation can lead to heap-based buffer overflow. The attack can be launched remotely. The exploit has been publicly disclosed and may be utilized. The project was informed of the problem early through an issue report but has n...
CVE-2026-86808	New	5.5	MEDI		0.006		A security vulnerability has been detected in moltis-org moltis up to 20260818.10. The affected element is the function vault_unlock_handler/vault_recovery_handler of the file vault.rs. Such manipulation leads to missing authentication. The attack can be launched remotely. The exploit has been disclosed publicly and may be used. Upgrading to version 20260819.01 is sufficient...
CVE-2025-64542	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2025-64584	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2025-64588	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2025-64589	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2025-64610	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2025-64618	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2025-64830	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2025-64838	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2025-64854	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2025-64866	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2025-64868	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-19479	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-19612	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-19644	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-19713	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-2520	New	5.4	MEDI		0.002		The Online Scheduling and Appointment Booking System – Bookly plugin for WordPress is vulnerable to unauthorized modification of data due to a missing capability check on the 'updateAddon' function in all versions up to, and including, 27.2. This makes it possible for authenticated attackers, with Subscriber-level access and above, to update any plugin with a main file of 'm...
CVE-2026-27227	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-52307	New	5.4	MEDI		0.003		An authenticated stored cross-site scripting (XSS) vulnerability in the Column Management component of ClassCMS 1CMS v5.6 allows attackers to execute arbitrary web scripts or HTML via injecting a crafted payload into the title field.
CVE-2026-69402	New	5.4	MEDI		0.004	microsoft:sharepoint_server	Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Office SharePoint allows an authorized attacker to perform spoofing over a network.
CVE-2026-69417	New	5.4	MEDI		0.004	microsoft:sharepoint_server	Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Office SharePoint allows an authorized attacker to perform spoofing over a network.
CVE-2026-69690	New	5.4	MEDI		0.004	microsoft:sharepoint_server	Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Office SharePoint allows an authorized attacker to perform spoofing over a network.
CVE-2026-71356	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-71357	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-71388	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-71440	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-71565	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-72626	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-72627	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75629	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75635	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75636	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75637	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75639	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75640	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75642	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75643	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75644	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75646	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75647	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75651	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75652	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75657	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75659	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75660	New	5.4	MEDI		0.002	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75661	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75666	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75667	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75668	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75669	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75670	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75671	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75672	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75674	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75675	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75677	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75678	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75679	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75680	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75681	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75683	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75685	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75687	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75690	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75691	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75692	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75693	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75694	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75695	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75696	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75700	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75701	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75702	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75704	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75705	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75706	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75707	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75708	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75709	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75710	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75711	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75712	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75713	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75714	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75715	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75716	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75717	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75718	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75719	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75720	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75722	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75724	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75725	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a DOM-based Cross-Site Scripting (XSS) vulnerability. An attacker could exploit this issue by manipulating the DOM environment to execute malicious JavaScript within the context of the victim's browser. Exploitation of this issue requires user interaction in that a victim must visit a crafted webpage. Scope is changed.
CVE-2026-75727	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75729	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75730	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75731	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75733	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75734	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75735	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75736	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75737	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75738	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75739	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75740	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75741	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-75742	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-79905	New	5.4	MEDI		0.003	adobe:experience_manager	Adobe Experience Manager is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by a low-privileged attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field. Scope is changed.
CVE-2026-84385	New	5.4	MEDI		0.001		A improper access control vulnerability in Fortinet FortiSOAR PaaS 7.6.0 through 7.6.6, FortiSOAR PaaS 7.5.0 through 7.5.3, FortiSOAR PaaS 7.4 all versions, FortiSOAR PaaS 7.3 all versions, FortiSOAR on-premise 7.6.0 through 7.6.6, FortiSOAR on-premise 7.5.0 through 7.5.3, FortiSOAR on-premise 7.4 all versions, FortiSOAR on-premise 7.3 all versions may allow attacker to esca...
CVE-2026-86996	New	5.4	MEDI		0.002	n8n:n8n	n8n is an open source workflow automation platform. Prior to 2.37.7 and 2.38.2, the workflow setting named This workflow can be called by was enforced by the Execute Workflow node but not when a workflow was attached to an Agent as a tool. A user able to build an Agent could invoke a restricted workflow and read its returned data. The affected path is packages/cli/src/module...
CVE-2026-12962	New	5.3	MEDI		0.004		A Permissive Cross-domain Security Policy with Untrusted Domains in Armoury Crate allows a remote user to obtain a local user's NTLM hash by convincing the user to visit a crafted web page that sends a request containing a UNC path to the application's local service endpoint.Refer to the ' Security Update for Armoury Crate App ' section on the ASUS Security Advisory for more...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-19614	New	5.3	MEDI		0.002		The API is prone to XML external entity (XXE) injection. By default, XML external entity support is enabled. This issue affects NanoXML: 2.2.3.
CVE-2026-19625	New	5.3	MEDI		0.003		When a Quarkus application has multiple endpoints secured by individual OIDC provider tenants, such as "/oidc-provider1" that is secured by the OIDC Provider 1 and "/oidc-provider2" that is secured by the OIDC Provider 2, and an optional token introspection cache is also enabled, then a valid token issued by the OIDC Provider 1 that can be used to access "/oidc-provider1" ca...
CVE-2026-33389	New	5.3	MEDI		0.001		An improper certificate/host key validation vulnerability was discovered in the Smart Polling functionality, which established encrypted connections to target devices without validating the remote host's identity, and no option was provided to enable it. A man-in-the-middle attacker positioned between a sensor and a polled device can, during a polling session, impersonate th...
CVE-2026-33391	New	5.3	MEDI		0.003		An access control vulnerability was discovered in the Smart Polling configuration functionality due to insufficient validation of user privileges. An authenticated user with limited privileges can remotely bypass the intended access control of the web management interface and modify the Smart Polling discovery configuration. This allows the attacker to disrupt the visibility...
CVE-2026-47680	New	5.3	MEDI		0.003		The source-controller is a Kubernetes operator, specialised in artifacts acquisition from external sources such as Git, OCI, Helm repositories and S3-compatible buckets. In versions 0.0.17 through 1.8.4, an actor with the ability to influence the contents of a bucket referenced by a `Bucket` resource can cause source-controller to write fetched object data to paths outside t...
CVE-2026-70575	New	5.3	MEDI		0.008		Null pointer dereference in Windows Schannel allows an authorized attacker to deny service over a network.
CVE-2026-77132	New	5.3	MEDI		0.004		It has been discovered that several AJAX routes used for the backend localization wizard failed to perform authorization checks. This allowed authenticated, low-privileged backend users to access information about records and content elements that fall outside of their permitted range. Exploiting this vulnerability requires a low-privileged backend user account. This issue a...
CVE-2026-78446	New	5.3	MEDI		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Distributed File System (DFS) allows an authorized attacker to deny service over a network.
CVE-2026-78631	New	5.3	MEDI		0.001		The Okta Hyperdrive Agent writes the decoded SAML bearer assertion to a local application log file at the default log level on every successful MFA completion. This insertion of sensitive information into the log file makes a live authentication credential readable by any local user with access to the log file.
CVE-2026-81380	New	5.3	MEDI		0.006		Improper neutralization of special elements used in a command ('command injection') in GitHub Copilot and Visual Studio Code allows an unauthorized attacker to disclose information over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86080	New	5.3	MEDI		0.002	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the GitHub Trigger generated a webhook secret but discarded it when GitHub returned HTTP 422 and the node reused an existing webhook. Workflow static data then retained webhookId without webhookSecret, and X-Hub-Signature-256 verification accepted deliveries without a stored secret. Th...
CVE-2026-86714	New	5.3	MEDI		0.002		PX4 Autopilot through 1.17.0 contains a stack buffer over-read vulnerability in the netman system command that fails to validate interface name length. Attackers can supply interface names of 74 bytes or more via the -i option to read beyond buffer boundaries, leaking stack memory to console output or writing it into persistent network configuration files.
CVE-2026-86719	New	5.3	MEDI		0.001		WWBN AVideo through commit c3edcc274c389816d434acadac07ee78eaf330c1 (master) contains a cross-site request forgery vulnerability in the CustomizeUser plugin endpoint plugin/CustomizeUser/swapUser.json.php. The endpoint takes users_id from \$_REQUEST and invokes User::swapUser() without calling forbidIfNotPost() or forbidIfInvalidToken(), and the global autoCSRFGuard() check o...
CVE-2026-86737	New	5.3	MEDI		0.002	snipeitapp:snipe-it	snipe-it versions before 8.7.0 fail to enforce asset view authorization in the GET /hardware/{asset}/barcode endpoint. Authenticated attackers can iterate asset IDs to retrieve barcodes and enumerate asset tags across tenants, including soft-deleted and cross-company assets.
CVE-2026-11891	New	5.1	MEDI		0.001		Use After Free vulnerability in Arm Ltd Valhall GPU Userspace Driver, Arm Ltd Arm 5th Gen GPU Architecture Userspace Driver allows a non-privileged user process to perform valid GPU processing operations, including via WebGL or WebGPU, to access already freed memory. This issue affects Valhall GPU Userspace Driver: from r46p0 through r49p5, from r50p0 through r54p3, r55p0...
CVE-2026-12387	New	5.1	MEDI		0.001		Use After Free vulnerability in Arm Ltd Bifrost GPU Kernel Driver, Arm Ltd Valhall GPU Kernel Driver, Arm Ltd Arm 5th Gen GPU Architecture Kernel Driver allows a local non-privileged user process to perform valid GPU memory processing operations to access already freed memory. This issue affects Bifrost GPU Kernel Driver: from r41p0 through r49p5, from r50p0 through r51p0...
CVE-2026-33387	New	5.1	MEDI		0.002		A template injection vulnerability was discovered in the Dashboards functionality due to improper validation of an input parameter. An authenticated user with the required privileges can define a dashboard containing a malicious payload, or a victim can be socially engineered into importing a malicious dashboard. When the victim views or imports the dashboard, the payload ex...
CVE-2026-33920	New	5.1	MEDI		0.001		A cross-site request forgery vulnerability was discovered in the login functionality (both standard and SAML) due to missing validation of the anti-CSRF token. An attacker with a valid account can trick a victim into unknowingly authenticating with the attacker's credentials. Any operation performed by the victim in this state is attributed to the attacker's account, comprom...
CVE-2026-73317	New	5.1	MEDI		0.003	xenforo:xenforo	XenForo before 2.3.13 contains a missing authorization vulnerability in the ACP cache-rebuild dispatcher that allows limited administrators with only the rebuildCache permission to perform unauthorized approval queue actions by supplying an arbitrary job class and actor user ID in the POST body. Attackers can invoke the approval queue job under any user identity to approve q...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-73318	New	5.1	MEDI		0.003	xenforo:xenforo	XenForo before 2.3.13 contains a missing authorization vulnerability in the force-agreement controller that allows any ACP administrator to access and submit force-agreement forms regardless of their assigned permissions. Attackers can bypass the option permission declared in the navigation configuration to update the global policy last-updated timestamp, forcing all users t...
CVE-2026-73319	New	5.1	MEDI		0.003	xenforo:xenforo	XenForo before 2.3.13 contains a cross-site scripting vulnerability in the dynamic redirect handler that allows unauthenticated attackers to execute arbitrary JavaScript in the board origin by crafting a malicious javascript: URI that bypasses host validation. Attackers can embed the board hostname in the URI authority component and use percent-encoded newlines to evade serv...
CVE-2026-73320	New	5.1	MEDI		0.003	xenforo:xenforo	XenForo before 2.3.13 contains an unauthenticated information disclosure vulnerability that allows unauthenticated attackers to retrieve private unfurl records by supplying predictable auto-increment primary key IDs to the unfurl endpoint. Attackers can enumerate or predict result IDs and query the endpoint without any session, user, or visibility checks to obtain rendered p...
CVE-2026-84386	New	5.1	MEDI		0.001		A unverified ownership vulnerability in Fortinet FortiClientWindows 7.4.0 through 7.4.7, FortiClientWindows 7.2 all versions may allow attacker to improper access control via <insert attack vector here>
CVE-2026-86516	New	5.1	MEDI		0.002		A vulnerability was detected in elenavanengelenmaslova mocknest-serverless 0.9.0. The affected element is an unknown function of the file deployment/aws/shared/github-oidc-role.yaml of the component AWS GitHub OIDC Deployment Helper Script. Performing a manipulation results in improper privilege management. It is possible to initiate the attack remotely. The patch is named 6...
CVE-2026-72976	New	5.0	MEDI		0.004	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Out-of-bounds read in Microsoft Office Word allows an authorized attacker to disclose information locally.
CVE-2026-78635	New	5.0	MEDI		0.002		The Okta Privileged Access client URL handler does not insert an option terminator before appending the target value to the command-line arguments. When a scaleft:// protocol handler link contains a value beginning with a hyphen, the underlying CLI framework interprets it as a command-line flag, causing unintended modification of the SSH client's behavior.
CVE-2026-79904	New	5.0	MEDI		0.001	adobe:photoshop_mobile	Photoshop Mobile is affected by an Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') vulnerability that could result in a Security feature bypass. A low-privileged attacker could leverage this vulnerability to access unauthorized files or directories outside the intended restrictions. Exploit depends on conditions beyond the attacker's control. E...
CVE-2026-86735	New	5.0	MEDI		0.002	snipeitapp:snipe-it	snipe-it versions before 8.7.0 contain a server-side request forgery vulnerability in the ExternalUrl validation rule that fails to detect IPv6 transition addresses encoding private IPv4 targets. Attackers with super-admin privileges can configure webhook URLs using NAT64, 6to4, or Teredo transition addresses to bypass SSRF guards and access internal services or cloud metada...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-22575	New	4.9	MEDI		0.002		An improper access control vulnerability in Fortinet FortiManager 7.6.0 through 7.6.4, FortiManager 7.4.0 through 7.4.10, FortiManager 7.2 all versions, FortiManager Cloud 7.6.2 through 7.6.4, FortiManager Cloud 7.4.1 through 7.4.10, FortiManager Cloud 7.2 all versions may allow an administrator to bypass the approval process for workflow sessions via crafted HTTP or HTTPs r...
CVE-2026-68785	New	4.9	MEDI		0.008	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-78624	New	4.9	MEDI		0.004		The Okta Access Gateway backup restore function does not validate the filename embedded in an encrypted backup payload. This results in writing file contents to unintended locations on the appliance filesystem.
CVE-2026-86085	New	4.9	MEDI		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 2.37.7 and 2.38.2, the /rest/roles/:slug/assignments and /rest/roles/:slug/assignments/:projectId/members endpoints checked only whether the caller could manage the role type. A caller with role:manageProject could name a project the caller could not list and obtain member names and email addresses. The affected co...
CVE-2026-86993	New	4.9	MEDI		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, a Log Streaming event destination could reference a generic HTTP credential and decrypt whichever credential ID it named without an ownership check. A user with a custom global role carrying Log Streaming scopes could select a credential belonging to another project and send its decrypt...
CVE-2026-69474	New	4.8	MEDI		0.007		Use after free in Windows Overlay Filter allows an authorized attacker to disclose information over a network.
CVE-2026-69615	New	4.8	MEDI		0.004	microsoft:sharepoint_server	Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Office SharePoint allows an authorized attacker to perform spoofing over a network.
CVE-2026-78560	New	4.8	MEDI		0.002		The Okta Access Gateway includes an optional pass-through authentication source that accepts user identity from a client-supplied HTTP header without cryptographic validation. In architectures where this optional source is enabled without an upstream reverse proxy or firewall configured to sanitize and enforce client headers, an unauthenticated user can supply an arbitrary i...
CVE-2026-68849	New	4.7	MEDI		0.002	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Out-of-bounds read in Windows Bluetooth Port Driver allows an authorized attacker to disclose information locally.
CVE-2026-68891	New	4.7	MEDI		0.002		Out-of-bounds read in Microsoft Standard XPS allows an authorized attacker to disclose information locally.
CVE-2026-69316	New	4.7	MEDI		0.003		Buffer over-read in Windows Overlay Filter allows an authorized attacker to disclose information locally.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69425	New	4.7	MEDI		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1	Improper link resolution before file access ('link following') in Windows NTFS allows an authorized attacker to perform tampering locally.
CVE-2026-69483	New	4.7	MEDI		0.003		Out-of-bounds read in Windows Image Acquisition allows an authorized attacker to disclose information locally.
CVE-2026-69771	New	4.7	MEDI		0.003		Improper link resolution before file access ('link following') in Windows Container Manager Service allows an authorized attacker to bypass a security feature locally.
CVE-2026-69792	New	4.7	MEDI		0.002		Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Win32K allows an authorized attacker to bypass a security feature locally.
CVE-2026-69832	New	4.7	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of sensitive system information to an unauthorized control sphere in Windows Win32K allows an authorized attacker to disclose information locally.
CVE-2026-69853	New	4.7	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use of uninitialized resource in Windows Win32K allows an authorized attacker to disclose information locally.
CVE-2026-69895	New	4.7	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Spaceport.sys allows an authorized attacker to disclose information locally.
CVE-2026-72931	New	4.7	MEDI		0.003		Missing release of resource after effective lifetime in Windows Secure Socket Tunneling Protocol (SSTP) allows an authorized attacker to deny service locally.
CVE-2026-69381	New	4.6	MEDI		0.004		Out-of-bounds read in Windows Storage Port Driver allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-69548	New	4.6	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows RNDIS allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-76959	New	4.6	MEDI		0.001		SAP S/4HANA Finance (Advanced Payment Management) does not perform sufficient Cross-Site Request Forgery protection on certain requests due to this an attacker with low privileges could craft a malicious link or page. If an authenticated victim interacts with it, unintended actions could be triggered on the web server on their behalf. This results in a low impact on confiden...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78452	New	4.6	MEDI		0.005	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Out-of-bounds read in Microsoft Windows SCSI Class System File allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-78508	New	4.6	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows CD-ROM Driver allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-78971	New	4.6	MEDI		0.002		In Halo <= 2.25.4, the plugin management feature allows users to install/update malicious plugins, which could let attackers execute any command with Halo process permissions.
CVE-2026-0001	New	4.4	MEDI		0.002		Use After Free vulnerability in Arm Ltd Bifrost GPU Kernel Driver, Arm Ltd Valhall GPU Kernel Driver, Arm Ltd Arm 5th Gen GPU Architecture Kernel Driver allows a local non-privileged user process to perform valid GPU memory processing operations to access already freed memory. This issue affects Bifrost GPU Kernel Driver: from r41p0 through r49p5, from r50p0 through r51p0...
CVE-2026-69713	New	4.4	MEDI		0.003		Dependency on vulnerable third-party component in Windows Secure Boot allows an authorized attacker to bypass a security feature locally.
CVE-2026-72980	New	4.4	MEDI		0.003		Uncontrolled search path element in Windows Hello allows an authorized attacker to bypass a security feature locally.
CVE-2026-28627	New	4.3	MEDI		0.002	google:android	In btm_sec_encrypt_change of btm_sec.cc, there is a possible downgrade attack due to a logic error in the code. This could lead to remote information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-45527	New	4.3	MEDI		0.003		In convertCleanApertureToRect of HeifCleanAperture.cpp, there is a possible way to cause a temporary denial of service due to an integer overflow. This could lead to remote denial of service with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-53638	New	4.3	MEDI		0.002		Syllus is an Open Source eCommerce Framework on Symfony. Starting in version 2.0.0 and prior to version 2.0.18, 2.1.15, and 2.2.6, an authorization bypass vulnerability exists in the shop account API. The `PATCH /api/v2/shop/account/orders/{tokenValue}/payments/{paymentId}` endpoint, used by an authenticated shop customer to change the payment method of an order that has bee...
CVE-2026-73019	New	4.3	MEDI		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper resolution of path equivalence in Windows URL Moniker allows an unauthorized attacker to bypass a security feature over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-76962	New	4.3	MEDI		0.002		SAP S/4HANA (Manage Bank Chains app) does not perform sufficient authorization checks within certain affected functionality. An attacker with low privileges could send specially crafted requests to delete specific entries that should not be accessible to them. This results in a low impact on availability. There is no impact on confidentiality and integrity.
CVE-2026-76963	New	4.3	MEDI		0.002		Due to a missing authorization check in Application Server ABAP of SAP NetWeaver and ABAP Platform, an authenticated attacker could gain unauthorized access to sensitive system configuration information. Successful exploitation could result in exposure of security relevant settings and internal system details, resulting in low impact on confidentiality while integrity and av...
CVE-2026-76977	New	4.3	MEDI		0.002		SAP UI5 does not sufficiently validate the parent frame's origin against the configured allowlist. An unauthenticated attacker could host a malicious page to bypass framing restrictions. If an authenticated victim visits the attacker's page and interacts with it, the attacker could trick the victim into performing unintended actions, resulting in a low impact on integrity. T...
CVE-2026-78455	New	4.3	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Xbox allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-78516	New	4.3	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Buffer over-read in Windows Storage allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-79588	New	4.3	MEDI		0.001		U-speed WIFI4 N300 T1 Pro v1.0.0 is vulnerable to Cleartext transmission of administration credentials over HTTP.
CVE-2026-79603	New	4.3	MEDI		0.002		x86 PV guests can free memory pages while still keeping a stale TLB entry pointing to them. A TLB flush is only issued by Xen (if needed) when the page is re-used. Since it's possible for the page to be scrubbed ahead of the TLB flush, there's a window where a PV guest can modify an already scrubbed page.
CVE-2026-86736	New	4.3	MEDI		0.002	snipeitapp:snipe-it	snipe-it before 8.7.0 contains an incorrect calculation vulnerability in checkout request handling that allows authenticated users to corrupt the assets.requests_counter through duplicate submissions and cancellations without active requests. Attackers can repeatedly call cancel endpoints without active requests to drive the counter negative, or submit duplicate checkout req...
CVE-2026-86853	New	4.3	MEDI		0.002		A malicious webpage could repeatedly trigger external URL schemes, causing system prompts or external application launches. This could make Firefox for iOS temporarily unusable until the page is closed. This vulnerability was fixed in Firefox for iOS 155.1.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86994	New	4.3	MEDI		0.002	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the /rest/active-workflows endpoint returned every active workflow ID on the instance to any member regardless of sharing. Workflow activation, deactivation, and publication push events were also broadcast to clients that could not access the affected workflow, disclosing workflow IDs,...
CVE-2026-86995	New	4.3	MEDI		0.003	n8n:n8n	n8n is an open source workflow automation platform. Prior to 1.123.76, 2.37.7, and 2.38.2, the Git node validated the repository parameter for fetch or pull, but setUpstream wrote a branch.remote value into repository configuration without validating it. A later fetch or pull resolved the remote from that configuration instead of the checked parameter. An authenticated work...
CVE-2026-12285	New	4.0	MEDI		0.001		Use After Free vulnerability in Arm Ltd Bifrost GPU Kernel Driver, Arm Ltd Valhall GPU Kernel Driver, Arm Ltd Arm 5th Gen GPU Architecture Kernel Driver allows a local non-privileged user process to perform valid GPU memory processing operations to access already freed memory. This issue affects Bifrost GPU Kernel Driver: from r41p0 through r49p5, from r50p0 through r51p0...
CVE-2026-80159	New	4.0	MEDI		0.001	adobe:acrobat, adobe:acrobat_dc, adobe:acrobat_reader_dc, apple:macos, microsoft:windows	Acrobat Reader is affected by an Untrusted Search Path vulnerability that could result in privilege escalation. An attacker with high privileges could leverage this vulnerability to gain elevated access. Exploit depends on conditions beyond the attacker's control. Exploitation of this issue requires user interaction in that a victim must open a malicious file.
CVE-2026-49895	New	3.5	LOW		0.001		In get_eht_operation_channel_width of ieee802_11_common.c, there is a possible out of bounds read due to an incorrect bounds check. This could lead to remote (proximal/adjacent) information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-69904	New	3.5	LOW		0.006	microsoft:sharepoint_server	Server-side request forgery (ssrf) in Microsoft Office SharePoint allows an authorized attacker to disclose information over a network.
CVE-2026-75726	New	3.5	LOW		0.004	adobe:experience_manager	Adobe Experience Manager is affected by an Improper Input Validation vulnerability that could result in a Security feature bypass. A low-privileged attacker could leverage this vulnerability to bypass security measures and gain unauthorized limited write access. Exploitation of this issue requires user interaction in that a victim must visit a maliciously crafted URL or inte...
CVE-2026-76960	New	3.5	LOW		0.001		SAP S/4HANA Finance (Advanced Payment Management) does not perform sufficient Cross-Site Request Forgery protection on certain requests, due to this an attacker with low privileges could craft a malicious link or page. If an authenticated victim interacts with it, unintended actions could be triggered on the web server on their behalf. This results in a low impact on confide...
CVE-2026-76961	New	3.5	LOW		0.001		SAP S/4HANA Finance (Advanced Payment Management) does not perform sufficient Cross-Site Request Forgery protection on certain requests, due to this an attacker with low privileges could craft a malicious link or page. If an authenticated victim interacts with it, unintended actions could be triggered on the web server on their behalf. This results in a low impact on confide...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-0054	New	3.3	LOW		0.001	google:android	In isCallerAllowed of WalletContextualLocationsService.kt, there is a possible way to get wallet information due to a missing permission check. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28582	New	3.3	LOW		0.001	google:android	In onCreate of ConfirmDeviceCredentialActivity.java, there is a possible unauthorized access to and modification of device credentials due to a missing permission check. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28622	New	3.3	LOW		0.001	google:android	In getQueryBuilderInternal of MediaProvider.java, there is a possible way to retrieve location metadata due to a permissions bypass. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28623	New	3.3	LOW		0.001	google:android	In writeToParcel of BleRssiRangingCapabilities.java, there is a possible way to obtain the Bluetooth MAC address due to a missing permission check. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28630	New	3.3	LOW		0.001	google:android	In onCreate of ContactsPickerActivity.kt, there is a possible misleading UI due to a tapjacking/overlay attack. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28638	New	3.3	LOW		0.001	google:android	In multiple functions of XmpDataParser.java, there is a possible improper data sanitization due to a logic error in the code. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28660	New	3.3	LOW		0.001	google:android	In getAllSessions of multiple files, there is a possible confused deputy due to a logic error in the code. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-28671	New	3.3	LOW		0.001		In updateInternal of MediaProvider.java, there is a possible expose contents of files due to a race condition. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-45519	New	3.3	LOW		0.001		In screenArgsForPermissionCheckIfAny of multiple locations there is a possible risk of unauthorized access due to a confused deputy. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-45521	New	3.3	LOW		0.001		In openFile of AppFuseBridge.java, there is a possible information disclosure due to a missing permission check. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-45525	New	3.3	LOW		0.001		In multiple locations, there is a possible improper data sanitization due to a logic error in the code. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-55290	New	3.3	LOW		0.001		In setTo of ResourceTypes.cpp, there is a possible out-of-bounds heap read due to a missing bounds check. This could lead to local information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86564	New	3.3	LOW		0.001		A flaw was found in DPDK lib/vhost. Missing length validation before reading command_data in the virtio-net control-queue handler can cause an out-of-bounds read and a host process crash.
CVE-2026-28652	New	3.1	LOW		0.002	google:android	In multiple functions of RangingServiceImpl.java, there is a possible MITM due to a missing permission check. This could lead to remote information disclosure with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-48707	New	3.1	LOW		0.002		InstantCMS is a free and open source content management system. Versions prior to 2.18.2 have a Server-Side Request Forgery (SSRF) vulnerability in the file upload functionality ('system/core/uploader.php' at lines 509-532). When the "upload from URL" feature follows an HTTP redirect, the redirected target URL bypasses the private IP address blacklist check. This allows auth...
CVE-2026-84389	New	3.1	LOW		0.001		A url redirection to untrusted site ('open redirect') vulnerability in Fortinet FortiSIEM 7.5.0 through 7.5.1, FortiSIEM 7.4.1 through 7.4.2 may allow attacker to execute unauthorized code or commands via <insert attack vector here>
CVE-2026-86670	New	2.9	LOW		0.003		A flaw has been found in aircheng-org iWebShop-5 up to 5.15. This impacts an unknown function of the file controllers/admin.php of the component Authentication Storage. Executing a manipulation of the argument Password can lead to password hash with insufficient computational effort. It is possible to launch the attack remotely. A high complexity level is associated with thi...
CVE-2026-84392	New	2.7	LOW		0.003		A NULL Pointer Dereference vulnerability [CWE-476] vulnerability in Fortinet FortiOS 7.4 all versions, FortiOS 7.2 all versions, FortiPAM 1.9.0, FortiPAM 1.8 all versions, FortiPAM 1.7 all versions, FortiPAM 1.6 all versions, FortiPAM 1.5 all versions, FortiPAM 1.4 all versions, FortiPAM 1.3 all versions, FortiPAM 1.2 all versions, FortiPAM 1.1 all versions, FortiPAM 1.0 all...
CVE-2026-82060	New	2.3	LOW		0.002	mongodb:mongodb	In MongoDB, insufficient validation of shard key values during document insertion allowed authenticated users to store documents with specially crafted, operator-shaped objects as shard key values in sharded collections. When change stream events for such documents were processed with the updateLookup full document mode, the crafted values were embedded into internal post-im...
CVE-2026-82710	New	2.3	LOW		0.004		Improper Neutralization of Escape, Meta, or Control Sequences vulnerability in ash-project usage_rules allows a malicious package publisher to inject terminal control sequences into the output of mix usage_rules.search_docs. mix usage_rules.search_docs searches Hex documentation through search.hexdocs.pm, which indexes the documentation of every published package, and print...
CVE-2026-58234	New	2.2	LOW		0.002		SAP Process Integration (SOAP Adapter) allows a privileged user to send specially crafted requests containing deeply nested entity definitions, which under certain conditions could temporarily increase processor load and degrade system responsiveness. Successful exploitation results in low impact on availability with no impact on confidentiality and integrity.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86512	New	2.1	LOW		0.002		A vulnerability was identified in java-json-tools json-patch up to 1.13. This affects the function CopyOperation.apply/MoveOperation.apply of the file src/main/java/com/github/fge/jsonpatch/CopyOperation.java of the component Copy Move Operations. The manipulation leads to improper access controls. Remote exploitation of the attack is possible. The exploit is publicly availa...
CVE-2026-86514	New	2.1	LOW		0.003		A weakness has been identified in vgmstream up to r2117. This issue affects the function sscanf of the file src/meta/txt.h.c of the component txt.h-txtp. This manipulation causes stack-based buffer overflow. The attack is possible to be carried out remotely. The exploit has been made available to the public and could be used for attacks. Patch name: 4669d37a6af94866f6f0628678f...
CVE-2026-86515	New	2.1	LOW		0.003		A security vulnerability has been detected in vgmstream up to r2117. Impacted is the function add_entry of the file src/meta/txtp_parser.c of the component txtp. Such manipulation of the argument range_start/range_end leads to resource consumption. The attack may be performed from remote. The exploit has been disclosed publicly and may be used. The name of the patch is 4b6a0...
CVE-2026-86517	New	2.1	LOW		0.002		A flaw has been found in itsourcecode Sales and Inventory System 1.0. The impacted element is the function mysqli_query of the file /pages/us_searchfrm.php. Executing a manipulation of the argument ID can lead to sql injection. It is possible to launch the attack remotely. The exploit has been published and may be used.
CVE-2026-86518	New	2.1	LOW		0.002		A vulnerability has been found in code-projects Student Crud Operation 1.0. This affects an unknown function of the file /edit.php. The manipulation of the argument ID leads to sql injection. The attack can be initiated remotely. The exploit has been disclosed to the public and may be used.
CVE-2026-86668	New	2.1	LOW		0.003		A security vulnerability has been detected in aircheng-org iWebShop-5 up to 5.15. The impacted element is the function uploadFile of the file controllers/pic.php. Such manipulation of the argument outerSrc/selectPhoto leads to cross site scripting. The attack may be performed from remote. The exploit has been disclosed publicly and may be used. The project was informed of th...
CVE-2026-86674	New	2.1	LOW		0.002		A vulnerability was found in ningzichun Student Management System up to 98760f5711cf6dc8b4adca53a9e207ca49b02ebf. Affected by this vulnerability is the function session_start of the file login.php. The manipulation results in session fixation. The attack can be launched remotely. The exploit has been made public and could be used. This product does not use versioning. This ...
CVE-2026-86675	New	2.1	LOW		0.002		A vulnerability was identified in itsourcecode Sales and Inventory System 1.0. This affects an unknown part of the file /pages/us_edit.php. Such manipulation of the argument ID leads to sql injection. The attack may be launched remotely. The exploit is publicly available and might be used.
CVE-2026-16003	New	2.0	LOW		0.001		Exposed IOCTL with Insufficient Access Control in Armoury Crate driver allows a local user to add an arbitrary process identifier to the driver's whitelist via a crafted IOCTL request by bypassing the driver's verification.Refer to the ' Security Update for Armoury Crate App ' section on the ASUS Security Advisory for more information.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86644	New	2.0	LOW		0.003		A vulnerability was determined in star7th showdoc up to 3.9.1. This vulnerability affects unknown code of the file web_src/public/editor.md/editormd.js of the component API Page Save Endpoint. Executing a manipulation can lead to cross site scripting. The attack may be launched remotely. The exploit has been publicly disclosed and may be utilized. Upgrading to version 3.9.2 ...
CVE-2026-86667	New	2.0	LOW		0.002		A weakness has been identified in aircheng-org iWebShop-5 up to 5.15. The affected element is the function member_list of the file controllers/member.php. This manipulation of the argument Search causes sql injection. The attack is possible to be carried out remotely. The exploit has been made available to the public and could be used for attacks. The project was informed of...
CVE-2026-9215	New	1.8	LOW		0.001	netgear:xr1000, netgear:xr1000_firmware, netgear:xr1000v2, netgear:xr1000v2_firmware, netgear:xr500, netgear:xr500_firmw	A cross site request forgery (CSRF) vulnerability in the listed NETGEAR models allows an attacker who can leverage social engineering techniques on a router administrator to tamper with router configuration and disrupt router operations with active assistance from the router administrator. There is no confidentiality impact due to this vulnerability.
CVE-2026-9216	New	1.2	LOW		0.002	netgear:rax30, netgear:rax30_firmware, netgear:rax35, netgear:rax35_firmware, netgear:rax38, netgear:rax38_firmware, net	An insufficient input validation vulnerability in the listed NETGEAR RAX series models allows a network-adjacent attacker having network access (such as WiFi credentials) to crash the router's management UI. There is no confidentiality or integrity impact. A crash of the router's management UI does not impact the availability of the router's core services like WiFi network.
CVE-2026-12259	New		MODE		0.001	PyPI:nltk	NLTK's package downloader in nltk/downloader.py does not verify file integrity after download and before extraction. The download flow at lines 789-825: 1. File is downloaded to a temp path via HTTP 2. os.replace(tmp_filepath, filepath) moves it to the final location (line 799) 3. Extraction begins via _unzip_iter() (line 825) Between steps 2 and 3, there is no SHA-256 ver...
CVE-2026-15603	New		MODE		0.002	npm:morgan	### Impact Morgan writes attacker-controlled request data to the access log through its tokens. The 1.11.0 fix neutralizes C0 control characters, DEL, and backslash, but it does not escape the Unicode line separators `U+0085` (NEL), `U+2028` (LINE SEPARATOR), or `U+2029` (PARAGRAPH SEPARATOR). These code points are reachable through several tokens, including the request URL...
CVE-2026-45219	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-45220	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-49153	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-49154	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-49155	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-49156	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-50646	New		HIGH		0.01	NuGet:Microsoft.WindowsDesktop.App.p.Runtime.win-arm64, NuGet:Microsoft.WindowsDesktop.App.Runtime.win-x64, NuGet:Microsof	## Executive summary Microsoft is releasing this security advisory to provide information about a vulnerability in Windows Presentation Foundation (WPF). This advisory also provides guidance on what developers can do to update their applications to remove this vulnerability. A remote code execution vulnerability exists in Windows Presentation Foundation (WPF) in .NET 8, .NET...
CVE-2026-62383	New		MODE		0.002	PyPI:nltk	## Summary `IIPANCorpusReader` (`nltk/corpus/reader/ipipan.py`) exposes public methods, `channels()`, `domains()`, `categories()`, and `fileids(channels=...)`, that accept a caller supplied `fileids` list and read a file via a completely unprotected builtin `open()` call, with no `nltk.pathsec` involvement at all. A symlink placed inside the corpus root, with a name contain...
CVE-2026-62384	New		HIGH		0.006	PyPI:nltk	This is a new, distinct vulnerability : a bypass of the fix already published as [GHSA-xh95-f55m-82fw](https://github.com/nltk/nltk/security/advisories/GHSA-xh95-f55m-82fw) ("Path traversal in NLTK FramenetCorpusReader.frame() allows arbitrary XML file read, bypassing the nltk.pathsec sandbox"), not a duplicate of it. ## Summary The original advisory was fixed (PR [#358...
CVE-2026-62385	New		HIGH		0.004	PyPI:nltk	#### Summary Published `nltk==3.9.4` still contains several XML-reader entrypoints that build parser paths from caller-controlled selectors or trusted-looking index state without preserving the corpus-root boundary. #### Details - Vulnerability type: Path traversal and trusted-root bypass - Affected component: `FramenetCorpusReader.frame_by_name`, `FramenetCorpusRea...
CVE-2026-62815	New		CRIT		0.012	NuGet:Microsoft.Native.Quic.MsQuic.OpenSSL, NuGet:Microsoft.Native.Quic.MsQuic.Schannel	# Summary Use after free in Microsoft QUIC allows an unauthorized attacker to execute code over a network. # Details New network path creations and removals triggered by incoming packets can lead to a pointer invalidation. ## Patches - Guard path promotion [e0f55b5](https://github.com/microsoft/msquic/commit/e0f55b5fdc9ff0b4465976d066ebd22fb7e2b3b) # Impact An unauth...
CVE-2026-62900	New		MODE		0.005	NuGet:Microsoft.Build.Tasks.Git, NuGet:Microsoft.SourceLink.AzureRepos.Git	## Executive summary Microsoft is releasing this security advisory to provide information about a vulnerability in Microsoft.Build.Tasks.Git and Microsoft.SourceLink.AzureRepos.Git. This advisory also provides guidance on what developers can do to update their applications to remove this vulnerability. Improper removal of sensitive information before storage or transfer in...
CVE-2026-63312	New		HIGH		0.006	PyPI:nltk	## Summary Setting `nltk.pathsec.ENFORCE = True` is documented to sandbox all file access to allowed NLTK data directories and raise `PermissionError` on unauthorized access. However, `StreamBackedCorpusView` opens files via `builtins.open()` directly, bypassing `pathsec.validate_path()` entirely. An attacker who can influence the `fileid` argument can read arbitrary local f...
CVE-2026-65915	New		MODE		0.004	PyPI:nltk	#### Summary There's a logic bug in `FileSystemPathPointer.open()` inside `nltk/data.py` that makes the sandbox check permanently inert. The guard condition is always `False` — meaning any file the process can read is accessible by passing a `file://` URL to `nltk.data.load()`. --- #### Details In `nltk/data.py`, `FileSystemPathPointer.open()` was patched at some point wit...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69222	New		HIGH		0.004	npm:liquidjs	### Summary The `join` filter (`src/filters/array.ts:8-13`) charges `memoryLimit` by array element <code>**count**</code> , not by the string length it produces, letting a template bypass a configured `memoryLimit` and allocate strings far past budget — bounded only by V8/process limits, not by `memoryLimit`. ### Details <code>```js // src/filters/array.ts:8-13 export const join = argumentsT...</code>
CVE-2026-70613	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-70614	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-70626	New		HIGH		0.002	PyPI:nlk	### Summary <code>nlk.corpus.reader.api.CorporaReader.open()</code> can be used to read files outside the intended corpus root via a symlink placed inside that root. Although NLTK blocks absolute paths and <code>..</code> traversal, the current boundary check is only lexical and does not account for symlink resolution. This leads to an arbitrary local file read / filesystem sandbox bypass for app...
CVE-2026-71493	New		MODE		0.004	Go:github.com/infracost/infracost	### Impact Path traversal via link following in the Infracost config-template parser. The <code>`readFile`, `pathExists`, `isDir`, and `matchPaths`</code> template functions confined repo-supplied paths with a lexical <code>`filepath.Rel`</code> check plus a leaf-only <code>`os.Lstat`</code> : <code>``` {{ readFile "evil/file" }} ```</code> With an intermediate directory symlink committed in the repo (<code>`evil -> /`</code>), the path...
CVE-2026-71494	New		MODE		0.004	Go:github.com/infracost/infracost	### Impact Sensitive information exposure in the Infracost Terraform Cloud/Enterprise integration. Several code paths attached a configured secret token to a request whose host was taken straight from the scanned Terraform, with no check that the host was the trusted endpoint. The condition that matters is whether a Terraform Cloud/Enterprise (or registry) token is presen...
CVE-2026-72789	New		HIGH		0.003	Go:github.com/siyuan-note/siyuan/kernel	**CVE:** This vulnerability corresponds to [CVE-2026-72789](https://nvd.nist.gov/vuln/detail/CVE-2026-72789). ### Summary <code>`publishAccess.json`</code> is an opt-out list. The publish gate returns <code>*accessible*</code> for anything not explicitly listed in it. Encrypted notebooks are never written into that file, because only the administrator-gated <code>`setPublishAccess`</code> writes it and no part ...
CVE-2026-72790	New		MODE		0.002	Go:github.com/siyuan-note/siyuan/kernel	**CVE:** This vulnerability corresponds to [CVE-2026-72790](https://nvd.nist.gov/vuln/detail/CVE-2026-72790). ### Relationship to GHSA-8x84-r2ff-h8pq (please read first) <code>`getNotebookInfo`</code> is named in the earlier advisory GHSA-8x84-r2ff-h8pq, in its remediation section, which asked for reader filtering on both <code>`getNotebookConf`</code> and <code>`getNotebookInfo`</code> . Commit <code>`3bc014c7d`</code> appl...
CVE-2026-72925	New		MODE		0.002	crates.io:swc_html_minifier, npm:@swc/html	## Impact <code>`@swc/html`</code> minifies JSON contained in <code>`script`</code> elements such as <code>`application/json`</code> and <code>`application/ld+json`</code> by parsing and serializing the JSON value. Before the patched versions, JSON serialization could convert escaped less-than signs such as <code>`\u003C`</code> into literal <code>`<`</code> characters. If the JSON contained an escaped <code>`</script>`</code> sequence, the generated HTML could ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-73087	New		LOW		0.003	Go:github.com/amir20/dozzle	## Summary The `isBlockedIP` SSRF guard in Dozzle's webhook notification dispatcher blocks loopback, link-local, multicast, and unspecified addresses but does not recognize IPv6 transition mechanism addresses (RFC 3056 6to4, RFC 6052 NAT64, RFC 4380 Teredo) that embed arbitrary IPv4 addresses. An authenticated user can bypass the guard to reach loopback services, cloud meta...
CVE-2026-73262	New		MODE		0.002	PyPI:prowler, PyPI:prowler-cloud	## Summary Prowler's HTML output formatter inserts `finding.resource_tags` into the generated report without HTML escaping. A cloud principal who can create or edit a resource tag in an account that is later scanned can store HTML or JavaScript in that tag. When another user opens the generated Prowler HTML report, the payload executes in the report page. ## Impact This i...
CVE-2026-73294	New		CRIT		0.006	Go:github.com/semaphoreui/semaphore	# Summary An OS command injection in repository git_url handling lets any user holding the Manager or Owner role on any project (the normal project-collaborator roles) achieve remote code execution on the Semaphore server host. Using git's --upload-pack=<cmd> option, an attacker runs arbitrary commands. The command executes inside the main Semaphore server process (via the s...
CVE-2026-73558	New		MODE		0.003	PyPI:vlm	### Summary An integer overflow in the act_and_mul_kernel kernel can cause the output of one user request to be incorporated into the response of another request within the same inference batch. Under certain conditions, the last request in a batch can receive a partial or complete copy of the first user's inference result, resulting in cross-user data leakage. ### Details...
CVE-2026-73560	New		MODE		0.003	PyPI:vlm	### Summary `vlm/transformers_utils/processors/mimo_v2_omni.py` — the multimodal processor for `MiMoV2OmniForCausalLM` — issues `requests.get(...)` directly on user-supplied image and audio URL strings and `Image.open(...)` on user-supplied local paths, **without** the SSRF / `allowed_local_media_path` checks that `vlm.multimodal.utils.MediaConnector` was hardened with in...
CVE-2026-75595	New		CRIT		0.003	Maven:io.netty:netty-handler	### Summary A fragmented TLS ClientHello whose handshake header spans multiple records makes Netty silently fall back to the default SslContext; where per-SNI selection is the sole mTLS gate, an unauthenticated attacker can bypass the route's mTLS requirement. ### Details In `io.netty.handler.ssl.SslClientHelloHandler#decode` the guard that should wait for the 4-byte handsh...
CVE-2026-75596	New		MODE		0.004	Maven:io.netty:netty-handler	### Summary Netty's default SNI endpoint reparses and recopies previously received ClientHello fragments on every additional TLS handshake record. A remote peer can send a small first record that advertises a large ClientHello length and then drip the body in many tiny records, causing **superlinear (quadratic) CPU work** before the handshake completes. With 4095 one-byte...
CVE-2026-75604	New		CRIT		0.025	npm:next	## Impact A vulnerability in applications using Pages and App router without Cache Component can lead to remote code execution when the server is hosted on machines using a Windows filesystem. ## Workaround There is no known workaround for affected windows-hosted applications. You should upgrade immediately if your server is hosted on Windows.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-77037	New		HIGH		0.003	npm:multer	### Impact A vulnerability in multer `2.2.0` allows an attacker to trigger a Denial of Service (DoS) by aborting or truncating multipart uploads. When using `diskStorage`, the destination write stream is not closed if the upload is aborted before it finishes, so each failed request leaks an open file descriptor and retains its disk blocks until the process exits. Repeated f...
CVE-2026-77063	New		LOW		0.002	npm:multer	### Impact When `multer` is configured with an asynchronous `fileFilter`, the `limits.fileSize` limit can be bypassed. The `limit` event is registered inside the async `fileFilter` callback, so if a file exceeds `limits.fileSize` before that callback runs, the event is missed and the oversized upload is accepted instead of being rejected with a `LIMIT_FILE_SIZE` error. Ap...
CVE-2026-77078	New		HIGH		0.003	npm:multer	### Impact A vulnerability in multer allows a remote, unauthenticated attacker to crash the Node.js process with a single `multipart/form-data` request. Two specially crafted text field names cause an uncaught `RangeError: Invalid array length` inside multer's field parsing, which is not routed to the application error handler and terminates the process. All applications us...
CVE-2026-7809	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-78675	New		HIGH		0.001	PyPI:gitpython	# [HIGH] Arbitrary local file content disclosure via `[include]` directive in untrusted `.gitmodules` ('SubmoduleConfigParser` never disables `merge_includes`) - **CWE:** CWE-200 (Exposure of Sensitive Information) / CWE-73 (External Control of File Name or Path) - **Affected component:** `git/objects/submodule/base.py`, `Submodule._config_parser()` (~line 273) constructing...
CVE-2026-78676	New		CRIT		0.004	PyPI:gitpython	- **CWE:** CWE-88 (Argument Injection) / CWE-94 (Code Injection) — via a read-then-corrupt-on-rewrite config round trip, not a direct setter argument - **Affected component:** `git/config.py` — `GitConfigParser._read()` (multi-line value decoding, lines 444-541, esp. `string_decode()` at line 460 and its call sites at 519/541) and `GitConfigParser._write()`/`write_section()`...
CVE-2026-78677	New		HIGH		0.004	PyPI:gitpython	- **CWE:** CWE-73 (External Control of File Name or Path) / CWE-22 (Path Traversal, in the "escapes intended base directory" sense) - **Affected component:** `git/repo/base.py`, `Repo.unsafe_git_clone_options` (class attribute, lines 153-165) and `Repo._clone()` (lines 1477-1520), reached via the public `Repo.clone_from()` (line 1626) and `Repo.clone()` (line 1567) APIs. - *...
CVE-2026-78678	New		MODE		0.002	PyPI:gitpython	## Summary `Repo.blame()` / `Repo.blame_incremental()` guard forwarded revision options against `unsafe_git_revision_options`, but that denylist only contains the file-WRITE options `--output`/`-o`. `git blame` also honors `--contents <file>` and `-S <file>`, which cause the file's lines to be echoed into the blame result — an arbitrary file READ. Neither option is in the de...
CVE-2026-78679	New		MODE		0.002	PyPI:gitpython	## Summary `TagReference.create()` forwards a caller-influenced positional `reference` value into `git tag` without it ever being inspected by the unsafe-option guard, allowing an arbitrary file read (the file's contents are returned in-band as the annotated tag message). This is an incomplete-fix bypass of commit `3af0c251` (the fix for GHSA-3f7w-8rr8-f37f's tag instance). ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78681	New		HIGH		0.003	PyPI:nltk	Several XML parsing sites in NLTK still used `xml.etree.ElementTree` directly, which honours `<!ENTITY>` declarations in a document's internal DTD subset. A crafted document a few hundred bytes long can expand to megabytes in memory (each nesting level multiplies by ten), a denial-of-service. Affected call sites (<= 3.10.2): - `nltk.chunk.named_entity.load_ace_file` — parse...
CVE-2026-78682	New		HIGH		0.003	PyPI:nltk	### Summary Current NLTK source reopens SSRF in proxied environments. `pathsec.urlopen()` validates the requested hostname locally, but once proxy inheritance is enabled the real fetch is performed by the proxy rather than by the validated direct-connect socket path. ### Details - **Vulnerability type:** Server-side request forgery - **Affected component:** `nltk.pathsec`...
CVE-2026-78683	New		CRIT		0.003	PyPI:nltk	## Summary The NLTK library's `TransitionParser.parse()` method deserializes model files using `pickle_load()` with the default `restricted=False` parameter, allowing arbitrary Python code execution when loading a malicious model file. The library provides a `RestrictedUnpickler` class for safe deserialization, but it is never used by production code paths, leaving the vuln...
CVE-2026-79657	New		CRIT		0.012	PyPI:nltk	### Summary The current source tree still allows arbitrary code execution during supposedly safer allowlisted pickle loading. The allowlist trusts whole module namespaces instead of exact safe globals, so crafted pickles can invoke dangerous in-namespace callables through pickle REDUCE. ### Details - **Vulnerability type:** Remote code execution via unsafe deserialization...
CVE-2026-79674	New		HIGH		0.002	PyPI:nltk	## Summary NLTK corpus-reader constructors can still reach outside-root file and database reads before the `nltk.pathsec` sandbox boundary is enforced. The PoC shows the safe path blocked by `pathsec.open`, then `LinThesaurusCorpusReader` and `PanLexLiteCorpusReader` succeeding in the same process. ## Affected Product - Product: NLTK - Asset / component: `nltk.corpus.rea...
CVE-2026-79676	New		HIGH		0.003	PyPI:nltk	### Summary Several corpus readers still step outside NLTK's symlink-aware trusted-root model. They derive in-root paths from trusted corpus state, convert those paths back into plain strings, and reopen them with built-in `open()` rather than `nltk.pathsec.open()`. ### Details - **Vulnerability type:** Path traversal and symlink boundary bypass - **Affected component:** ...
CVE-2026-80205	New		HIGH		0.005	PyPI:nltk	### Summary NLTK's `Text.findall()` and `TokenSearcher.findall()` methods accept user-supplied regular expressions and pass them to the Python `re` engine without timeout or validation, enabling catastrophic backtracking (ReDoS). This issue is isolated to the `nltk.text` module and was resolved in a prior commit. ### Affected Code `nltk/text.py` — `TokenSearcher.findall()` ...
CVE-2026-80206	New		HIGH		0.003	PyPI:nltk	### Summary The NLTK `tgrep` module accepts user-supplied regular expressions and passes them to the Python `re` engine without a timeout or validation, enabling catastrophic backtracking (ReDoS). Applications that expose the `tgrep` API to external input are vulnerable to a single-request denial of service that blocks the Python process indefinitely. ### Affected Code `nlt...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81725	New		MODE		0.002	PyPI:nlk	### Summary `Pl196xCorpusReader` still parses whole TEI blocks with multiple lazy regexes over attacker-controlled text. A malformed file with many opening tags and no matching closing tags forces repeated rescans and produces quadratic CPU growth in public reader APIs. ### Details - **Vulnerability type:** Regular-expression denial of service - **Affected component:** `n...
CVE-2026-82333	New		HIGH		0.003	npm:multer	### Impact multer is vulnerable to a Denial of Service (DoS) via a crafted array index in multipart field names. The `append-field` dependency parses bracket notation in field names, and a large numeric index such as `items[4294967294]` forces allocation of a maximum-length sparse array. A following field with a non-numeric key on the same base then converts that array to a...
CVE-2026-82514	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-83605	New		HIGH		0.003	npm:@xmldom/xmldom, npm:xmldom	## Summary `Element.setAttribute()` in `@xmldom/xmldom` bypasses attribute name validation by calling the private `_createAttribute(name)` method, which performs no validation. The public `createAttribute()` method correctly validates names against an anchored `QName` pattern, but `setAttribute()` never uses it. The serializer escapes attribute *values* but trusts attribute...
CVE-2026-83606	New		HIGH		0.003	npm:@xmldom/xmldom	## Summary `@xmldom/xmldom`'s processing-instruction (PI) grammar regex exhibits quadratic-time backtracking (ReDoS) when parsing an **unterminated** processing instruction. A single small XML document containing `<>` + a target + a long run of whitespace and no closing `?>` forces the regular expression engine into O(n²) work, stalling the Node.js event loop. The input is ...
CVE-2026-83607	New		HIGH		0.003	npm:@xmldom/xmldom, npm:xmldom	## Summary `Document.createElement()` in `@xmldom/xmldom` accepts arbitrary strings as the `tagName` parameter with zero validation. The serializer emits the tag name verbatim into XML/HTML output. Critically, the `requireWellFormed: true` serializer option — the recommended mitigation from CVE-2026-41672, CVE-2026-41674, and CVE-2026-34601 — did NOT catch this, making it a...
CVE-2026-83608	New		HIGH		0.003	npm:@xmldom/xmldom, npm:xmldom	## Summary The `@xmldom/xmldom` serializer emits `DocumentType.name` verbatim into the `<!DOCTYPE ...>` declaration with no well-formedness guard. GHSA-f6ww-3ggp-fr8h (CVE-2026-41674) hardened the serializer's `requireWellFormed` path for a `DocumentType`'s sibling fields — `publicId`, `systemId`, and `internalSubset` — but it did **not** add any check for `name`. A `>` (or whi...
CVE-2026-83609	New		HIGH		0.003	npm:@xmldom/xmldom	## Summary An embedded line terminator bypasses xmldom's always-on, WHATWG-mandated creation-time name validation. `createElementNS`, `createAttributeNS`, `createDocumentType`, and `createAttribute` should reject a malformed qualified name with `InvalidCharacterError`, but a name whose first line is well-formed slips through and enters the DOM. On serialization it is emitte...
CVE-2026-83611	New		MODE		0.004	npm:@xmldom/xmldom, npm:xmldom	## Summary xmldom's parser silently accepts a **not-well-formed end tag** whose valid name is followed by trailing content — e.g. ` <a█junk>`. `application...<="" after="" allows="" and="" as="" both="" chromium="" closed,="" content="" discarded,="" element="" end-tag="" error="" even="" firefox="" input="" is="" name="" no="" only="" optional="" production="" reject="" reported,="" such="" td="" the="" though="" trailing="" whitespace="" xml=""></a█junk>`.>

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83612	New		HIGH		0.003	npm:@xmldom/xmldom	## Summary In HTML mode (`text/html`), a raw-text element (`script`, `style`, `textarea`, `title`) whose closing tag differs in case from its opening tag (e.g. ` <script>` for `<script>`) is mishandled by the parser, producing quadratic ($O(n^2)$) output growth — a small crafted document parses and serializes into output orders of magnitude larger, exhausting CPU and memory. A...</td></tr> <tr> <td>CVE-2026-83613</td><td>New</td><td></td><td>HIGH</td><td></td><td>0.003</td><td>npm:@xmldom/xmldom, npm:xmldom</td><td>## Summary xmldom builds the attribute collection of every parsed element by inserting attributes one at a time into a DOM `NamedNodeMap`. Each insertion first performs a linear scan of all already-inserted attributes to enforce the DOM uniqueness rule (no two attributes with the same qualified name / namespace+local-name). Parsing an element that carries `M` distinct a...</td></tr> <tr> <td>CVE-2026-83614</td><td>New</td><td></td><td>HIGH</td><td></td><td>0.004</td><td>npm:@xmldom/xmldom, npm:xmldom</td><td>## Summary `xmldom`'s malformed-input error-recovery path has two quadratic-time ($O(n^2)$) behaviors that a single crafted input triggers together, so a tiny, highly compressible document (tens of KB) stalls the Node.js event loop for multiple seconds. It is reachable from `DOMParser.parseFromString` under default options — i.e. from unauthenticated, network-delivered...</td></tr> <tr> <td>CVE-2026-83615</td><td>New</td><td></td><td>HIGH</td><td></td><td>0.004</td><td>npm:@xmldom/xmldom, npm:xmldom</td><td>## Summary When an element declares a namespace prefix, xmldom copies the entire in-scope namespace map into a fresh object and keeps that copy on the element while it is open on the parse stack. A crafted document that nests N elements, each declaring one unique prefix, therefore drives the parser to hold on the order of $N(N+1)/2 = O(N^2)$ namespace-map entries at its peak...</td></tr> <tr> <td>CVE-2026-83616</td><td>New</td><td></td><td>HIGH</td><td></td><td>0.003</td><td>npm:@xmldom/xmldom, npm:xmldom</td><td>## Summary `Document.createProcessingInstruction()` in `@xmldom/xmldom` performs no validation on the `target` parameter. The `requireWellFormed: true` serializer option validates only for `:` in the target and a case-insensitive `xml` prefix, but does not check for `>` characters. A `>` in the target breaks the processing instruction boundary (`<?...?>`), allowing injectio...</td></tr> <tr> <td>CVE-2026-83617</td><td>New</td><td></td><td>HIGH</td><td></td><td>0.003</td><td>npm:@xmldom/xmldom</td><td>## Summary An embedded line terminator bypasses the `requireWellFormed` serializer check for element and attribute names. The check was added to fix GHSA-w2rr-34g9-rvrj and GHSA-4w3w-2rp5-g8jm; a name whose first line is well-formed slips past it and is serialized verbatim, so the characters after the line terminator break out of the start/end tag or attribute. Callers who ...</td></tr> <tr> <td>CVE-2026-83618</td><td>New</td><td></td><td>HIGH</td><td></td><td>0.003</td><td>npm:@xmldom/xmldom</td><td>## Summary An embedded line terminator bypasses the `requireWellFormed` serializer check for a `DocumentType`'s publicId and systemId. The check was added to fix GHSA-f6ww-3ggp-fr8h; an id whose first line is a valid literal slips past it and is emitted verbatim into the `<!DOCTYPE ...>` declaration, so the markup after the line terminator breaks out into the surrounding docu...</td></tr> <tr> <td>CVE-2026-83619</td><td>New</td><td></td><td>HIGH</td><td></td><td>0.003</td><td>npm:@xmldom/xmldom</td><td>## Summary On the `@xmldom/xmldom` 0.8.x line, parsing an XML end tag whose name is followed by a long run of whitespace and then a non-whitespace character triggers quadratic-time regular-expression backtracking (ReDoS), so a single small crafted end tag stalls the Node.js event loop. It is reachable from `DOMParser.parseFromString` under default options, unauth...</td></tr> </table> </div></script>

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-84303	New		MODE		0.003	Go:google.golang.org/grpc	### Summary A vulnerability in the xDS RBAC HTTP filter implementation in grpc-go allows remote attackers to bypass authorization policies (specifically DENY rules) by using mixed-case or canonical-case header matchers (e.g., X-Role instead of x-role). Additionally, the safety guards introduced by gRFC A41 to block grpc- prefixed headers can be evaded via variations in casin...
CVE-2026-84363	New		MODE		0.003	npm:hono	### Summary Hono's query parsing does not stop at the URL fragment: a `?` appearing after a `#` is treated as the start of a query string. As a result, the application can read request parameters that no other component involved in handling the request can see. ### Details A fragment is never part of the query, and every standard URL consumer — browsers, `new URL()`, reve...
CVE-2026-84364	New		MODE		0.004	npm:hono	### Summary When `parseBody()` expands dot-separated form field names into nested objects, it does not limit the nesting depth or the total number of objects created. A request body well within a normal size limit can therefore allocate an object graph far larger than the request itself, and concurrent requests can exhaust the heap and terminate the process. ### Details E...
CVE-2026-84365	New		MODE		0.003	npm:hono	### Summary The fix released for CVE-2026-39408 does not cover every traversal sequence. `toSSG()` can still write files outside the configured output directory when a route parameter contains consecutive parent-directory segments. ### Details Static site generation builds each output path from the route path and the values supplied through `ssgParams`, then verifies that...
CVE-2026-84367	New		LOW		0.003	npm:jo	### Impact Applications are affected only if a schema renames keys with a regular-expression source and a `Joi.expression()` / `Joi.x()` target that interpolates the pattern's own match data, combined with `{ multiple: true }`, for example `.rename(/^x-(.+)\$/, Joi.x('{#1}'), { multiple: true })`. Because the target is rendered from the matched input key, an attacker who con...
CVE-2026-84368	New		LOW		0.003	npm:@hapi/joi, npm:jo	### Impact An application that passes attacker-controlled data into joi's custom message configuration (`messages()`, `message()`, `prefs({ messages })`, `Joi.extend({ messages })` or `rule({ message })`) lets the attacker write properties onto `Object.prototype`, where every object in the process then inherits them. A key named `__proto__` was treated as a language name, an...
CVE-2026-84369	New		MODE		0.003	npm:svgo	## Summary SVGO's opt-in `removeScripts` plugin did not inspect executable HTML content inside SVG ` <foreignobject>` elements. Applications that used this plugin as their only protection for untrusted SVG input could produce SVGs containing active HTML and expose users to cross-site scripting (XSS). SVGO is an optimizer rather than a comprehensive sanitization library, but...</foreignobject>
CVE-2026-84370	New		HIGH		0.003	npm:svgo	## Summary SVGO's opt-in `removeScripts` plugin failed to remove some executable links. Namespace-prefixed SVG anchors and URL schemes containing ASCII tabs or newlines could bypass its checks. Applications that used this plugin as their only protection for untrusted SVG input could expose users to cross-site scripting (XSS). SVGO is an optimizer rather than a comprehensiv...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-84373	New		MODE		0.004	npm:@vitest/mocker, npm:vitest	## Summary `@vitest/mocker` registers a redirect mock's target path without validating it against the dev server's file-serving allowlist. An attacker who can reach the dev server's WebSocket can register a redirect mock pointing outside the project root; when the mocked module is requested, the plugin's `load` hook returns `readFile(<attacker path>)` as the module source, d...
CVE-2026-84375	New		HIGH		0.004	npm:js-yaml	## Summary `maxTotalMergeKeys` does not count empty mappings. An attacker can repeatedly merge a large sequence of them and consume significant CPU without reaching the configured limit. ## Example ```yaml arr: &arr [{}, {}, {}] # N empty mappings targets: - <<: *arr # repeated K times ``` For every target, the loader iterates all `N` elements of `a...
CVE-2026-84376	New		MODE		0.004	npm:astro	## Summary Astro stripped a configured `base` path from request pathnames using a string-prefix check that did not verify a path-segment boundary. With `base: "/app"`, a request to `/appX/admin` was treated as being under the base and resolved internally to the `/admin` route, while middleware still observed the public pathname `/appX/admin`. Middleware that authorizes rout...
CVE-2026-84378	New		MODE		0.003	PyPI:httpx2	### Summary HTTPX2's Server-Sent Events (SSE) parser repeatedly copied and rescanned buffered text when a server split one unterminated line across many response chunks. The total work grows quadratically with the length of the line. An attacker-controlled or compromised SSE endpoint can exploit this behavior to consume excessive client CPU. ### Details Before version 2.1...
CVE-2026-84379	New		MODE		0.003	PyPI:httpx2	### Summary HTTPX2 serializes the per-file `Content-Type` and custom headers supplied through the `files=` tuple API directly into the `multipart/form-data` body without validating custom header names or values. An attacker who can influence upload metadata passed to HTTPX2 can use CR or LF characters to terminate a multipart part header and inject additional part headers o...
CVE-2026-84380	New		MODE		0.002	PyPI:httpx2	### Summary HTTPX2 can automatically add a `Content-Length` header to a request that already contains a caller-supplied `Transfer-Encoding` header. The resulting HTTP/1.1 request contains both framing headers, which can create an ambiguous message boundary and enable request smuggling or connection desynchronization when processed by intermediaries that disagree about which...
CVE-2026-84381	New		HIGH		0.001	PyPI:httplib2, PyPI:httpx2	### Summary httplib2 does not start TLS for `wss://` connections routed through a SOCKS5 proxy. The WebSocket opening handshake and all subsequent frames are sent in plaintext through the proxy path, despite the caller selecting the secure `wss` scheme. The transport flaw affects httplib2 releases before `2.10.0`. HTTPX2 exposed this behavior through its public `Client.w...
CVE-2026-84382	New		HIGH		0.004	PyPI:httpx2	### Summary When decoding a compressed response body (`gzip`, `deflate`, `br`, or `zstd`), HTTPX2 fully decompressed each network read before yielding content to the application. A small compressed input could therefore cause a large intermediate memory allocation, even when the application streamed the response to keep memory usage bounded. ### Details HTTPX2's default t...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-84445	New				0.007	Go:google.golang.org/grpc	A vulnerability exists in gRPC-Go servers configured with `xds.NewGRPCServer()` where a crafted request missing both `:authority` and `Host` headers can cause a server panic, resulting in a Denial of Service (DoS). Servers built with `xds.NewGRPCServer` install an xDS routing interceptor on every RPC. This interceptor looks up the request's `:authority` header to pick a vir...
CVE-2026-84452	New		HIGH		0.009	PyPI:winml-cli	Case Description: MSRC Notes: Attachments: 1 file(s) attached (1 mp4) Summary: The vulnerability lies in the 'serve/cli_api.py' component of the 'winml-cli' project, which exposes all winml CLI commands over HTTP without authentication. Although it binds to localhost by default, it sets 'allow_origins' to a wildcard, allowing any website to interact with the endpoint. This,...
CVE-2026-85061	New		CRIT		0.003	npm:maplibre-gl	#### Impact `DOM.sanitize()` in `src/util/dom.ts` iterated `elem.attributes` (a live `NamedNodeMap`) while calling `elem.removeAttribute()` in the same loop. Removing an attribute shifts subsequent attributes down by one index, causing the iterator to skip the adjacent attribute. An attacker can provide an HTML payload with consecutive dangerous attributes (such as ` <details...< td=""></details...<>
CVE-2026-85062	New		MODE		0.003	npm:colord	#### Impact `colord`'s CSS color string matchers described a number as `[+-]?d*\.?d+`. In that form `d*` and `d+` can match the same digits, so a run of *n* digits can be divided between them in O(n²) ways, and rejecting an input retries every division. Parsing is synchronous and uninterruptible, so a long malformed color string blocks the thread: input time to re...
CVE-2026-85063	New		MODE		0.003	npm:csv-parse	#### Impact With columns: true and group_columns_by_name: true, a duplicated `__proto__` header causes the duplicate-column branch to assign an array to obj['__proto__'], invoking the `__proto__` setter and replacing the parsed record object's prototype with attacker-controlled data. Fixed in 7.0.2 (Object.hasOwn duplicate check + Object.defineProperty assignment). #### Patches ...
CVE-2026-86477	New						Rejected reason: ** REJECT ** DO NOT USE THIS CANDIDATE NUMBER. Reason: This candidate was issued in error. Notes: All references and descriptions in this candidate have been removed to prevent accidental usage.
CVE-2026-92595	New		MODE			npm:nodemailer	#### Summary Nodemailer's `disableFileAccess` / `disableUrlAccess` options are a security sandbox that lets an application forbid untrusted message content (`html`/`text`/`attachment`/`path`/`href`) from reading local files or making outbound HTTP(S) requests. The fix for GHSA-wqvq-jvpq-h66f (commit `5f69497`) threaded these flags through the library's internal resolution path...
CVE-2026-92596	New		HIGH			npm:nodemailer	#### Summary Nodemailer's address parser (`lib/addressparser/index.js`) parses a list of comma-separated addresses in **quadratic time — O(n²)** in the number of addresses. A single crafted address string (e.g. a `To`, `Cc`, `Bcc`, `From`, or `Reply-To` value, or any value passed to the exported `addressparser`) therefore consumes CPU proportional to the **square** of its le...
CVE-2026-92597	New		MODE			npm:nodemailer	#### Summary Nodemailer's email-address parser treats an **RFC 5322 comment** `(...)` inside the domain as a point to **concatenate** the surrounding text, rather than as folding whitespace (CFWS) that **terminates** the domain. Consequently a recipient address such as `user@good-corp.com(x)evil.com` is parsed and **delivered to `good-corp.comevil.com`** (registrable domai...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-92598	New		MODE			npm:nodemailer	### Summary Nodemailer resolves an international (IDN / non-ASCII) recipient **domain** to a different Punycode <code>`xn--`</code> label than every UTS#46 conformant parser (web browsers, the WHATWG URL Standard, Node's <code>`url.domainToASCII`</code> , Python's <code>`idna`</code>). Its address normalizer (<code>`_normalizeAddress`</code> in <code>`lib/mime-node/index.js`</code>) uses the bundled **raw RFC#3492 Punycode codec with no U...
GHSA-26w7-cxv4-gfx2	New		CRIT			npm:astro	A vulnerability in <code>`libheif`</code> , used by the default Sharp image service in Astro, can lead to remote code execution when a malicious AVIF image is optimized. Projects are affected when an attacker can cause Astro to process an untrusted AVIF image. The fix was released in Astro 7.2.8, which requires Sharp 0.35.4.
GHSA-2q42-4q24-7rgv	New		HIGH			npm:@typespec/compiler, npm:@typespec/openapi3	### Summary The <code>`@typespec/openapi3`</code> emitter retains the value of a <code>`@versioned`</code> enum member and interpolates it into the output filename as <code>`{version}`</code> without sanitizing path separators or traversal components. The completed path reaches the compiler's <code>`emitFile()`</code> , which creates the parent directory and writes the file without verifying containment under <code>`emitterOutputDi...</code>
GHSA-2xp9-vwfh-vxw4	New		CRIT			npm:next	A vulnerability in the underlying <code>`libheif`</code> library used by <code>`sharp`</code> which Next.js uses for image optimization can lead to remote code execution when AVIF files are optimized. Until a fix has propagated, optimization of AVIF files is disabled.
GHSA-38hw-f37p-99jj	New					npm:i18nexus	--- _-= Per source details. Do not edit below this line.=-_ ## Source: ghsa-malware (37d8dfb4ceaec110414441ebad5da37dad342ef653a20499504385d9db1ffdac) Any computer that has this package installed or running should be considered fully compromised. All secrets and keys stored on that computer should be rotated immediately from a different computer. The package should be remo...
GHSA-3j7p-44mj-76hx	New					npm:krdpass-auth-react-native	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (3a74ab9e45d4f67b40e21dc7491aff1979b4bf79be24bc49b8588916c18b847f) package.json declares a preinstall script (preinstall.js) that runs automatically on <code>`npm install`</code> . The script collects <code>os.hostname()</code> , <code>os.userInfo()</code> , <code>homedir</code> , internal IP addresses, CI/repository identifiers (GITHUB_REPO...
GHSA-4qhr-qf46-fcrx	New		HIGH			NuGet:Microsoft.DiaSymReader.Native	### Duplicate Advisory This advisory has been withdrawn because it is a duplicate of GHSA-63gh-g2x5-x69v. This link is maintained to preserve external references. ### Original Description Heap-based buffer overflow in Visual Studio allows an unauthorized attacker to execute code over a network.
GHSA-57v5-wqx3-cgj4	New		MODE			Go:github.com/siyuan-note/siyuan/kernel	### Scope note (please read first) This endpoint does not exist in v3.7.3 or on master. It was introduced on the development branch by commit <code>`acfc02ee8`</code> ("Improve database field visibility across views", #11020) and is live on <code>`v3.7.4-alpha.1`</code> , so it will ship in v3.7.4 unless gated first. No released stable version is affected. ### Summary <code>`/api/av/getAttributeViewField...</code>
GHSA-8rcc-9ggm-659p	New					npm:@usemosaik/template-react-js	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (3174ac7cecb1869ae5ac87ea585de744f6b7d17b8c089b746384c2b7e2355a3) This template package ships files/vite.config.js which, after a benign Vite header, appends ~26KB of heavily obfuscated code (obfuscator.io-style string-array with rotation dispatcher, hex payloads XOR-decoded at runtime...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
GHSA-9cfw-xh4g-cc2f	New					npm:i18nexus-tools	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (558344f06c374c5eff9c870250d63a5e9f784ffe23f91182154d9c66c441ee0b) The package was found to contain malicious code or consuming dependency that contains malicious code ## Source: ghsa-malware (4708373dfb7211317f4ebae7bd11027043840e6db7a9f2d9aa3385611a2fdad8) Any computer that has this ...
GHSA-f4f2-cqgp-jc rx	New					npm:@web2apk/baileys	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (1ad4c3329ebb2fdeb3b9ddc93abcb5f3dab6773f7a7999ff96d063d49edc04d9) The package was found to contain malicious code or consuming dependency that contains malicious code ## Source: ghsa-malware (23d279de5770039164036b3717fa8188b73601e773d8647f1a4e1b6ac59c5a17) Any computer that has this ...
GHSA-j95f-988m-3j2f	New		HIGH			npm:@tiptap/core	## Summary `@tiptap/core` contains two quadratic regular-expression denial-of-service paths in its default Markdown attribute parsers. Pandoc-style block attributes use two unanchored greedy expressions that rescan repeated `__QUOTED_0` prefixes. Inline shortcode attributes use another unanchored greedy key expression that rescans a long word-character run when no equals si...
GHSA-mqvm-gmc 4-6rv2	New		HIGH			NuGet:Microsoft.DiaSymReader.Nativ e	### Duplicate Advisory This advisory has been withdrawn because it is a duplicate of GHSA-527h-q9f6-p7qx. This link is maintained to preserve external references. ### Original Description Heap-based buffer overflow in .NET and Visual Studio allows an unauthorized attacker to elevate privileges over a network.
GHSA-q72m-f2r4-w4cw	New		HIGH			NuGet:Microsoft.DiaSymReader.Nativ e	### Duplicate Advisory This advisory has been withdrawn because it is a duplicate of GHSA-2j8r-3c22-8565. This link is maintained to preserve external references. ### Original Description Heap-based buffer overflow in Visual Studio allows an unauthorized attacker to execute code over a network.
GHSA-rgj7-g3m4-5g8c	New		HIGH			npm:sharp	### Impact A number of vulnerabilities, two rated as "Critical" severity using CVSSv3, have been discovered and fixed in the upstream libheif dependency. These can lead to possible remote code execution (RCE) on glibc-based Linux when run under certain conditions. The attack vector for these claims to be "network" however sharp does not provide any networking features so th...
GHSA-v3f6-m9j2-437p	New		MODE			NuGet:Microsoft.AspNetCore.Server.I ISIntegration	### Duplicate Advisory This advisory has been withdrawn because it is a duplicate of GHSA-8cp2-47hg-mfgh. This link is maintained to preserve external references. ### Original Description Improper handling of highly compressed data (data amplification) in ASP.NET Core allows an unauthorized attacker to deny service over a network.
MAL-2026-16048	New					npm:punypump	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (6e56cc14096d20f679823bf15af9f44dff039e01f23d2082eba8020200d04a7f) The package presents itself as a console shim (index.js is a verbatim copy of console-browserify with description 'Emulate console for all the browsers'), but also ships library.js and test/sessionCtrl.js which auto-exec...
MAL-2026-16049	New					npm:tailwindcss-aspectratio-styles	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (9b995eb02f80f9037beda9f8a864f55109e054925175289df0c1b29ed8011bc3) src/index.js, referenced by the package main and executed on require(), performs an HTTP GET to http://tailwindlan.online, writes the response body to a sibling file, and immediately require()s that file, giving the oper...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
MAL-2026-16050	New					npm:@aspect-adv-ui/consent-manag er	--- _-= Per source details. Do not edit below this line.=_ ## Source: amazon-inspector (b30b507d6c71f746b0af2d19cbbb85357f15189e7e93118c75b4cb215adc0ece) @aspect-adv-ui/consent-manager 2.4.1 declares a postinstall hook (node setup.js) that fires automatically on every `npm install`. setup.js issues an HTTPS GET to a hardcoded webhook.site inspection endpoint (https://we...
MAL-2026-16051	New					npm:@umschool/analytics	--- _-= Per source details. Do not edit below this line.=_ ## Source: amazon-inspector (da14c2843514d3c9103335648bc81a8bce18fc173b27c2ab39ebe26c0abe028) @umschool/analytics@999.0.4 targets the internal @umschool npm scope with an implausibly high version number to force resolution over any private package of the same name. Its postinstall.js runs on npm install and colle...
MAL-2026-16052	New					npm:open-item-validator	--- _-= Per source details. Do not edit below this line.=_ ## Source: amazon-inspector (7ba5b55d57f4938bf2494d369d14434bb80ba6f6c712c7f8d89ae773c27dc457) On require(), index.js spawns a detached, unref'd background Node process (lib/check-items.js) that repeatedly HTTP-GETs a JSON payload from http://itemx.servegame.com:8888/api/x-realtime and executes the returned JavaSc...
MAL-2026-16056	New					npm:tailwind-aspect-styles	--- _-= Per source details. Do not edit below this line.=_ ## Source: amazon-inspector (4d63fe1e50dc7d704732a5e92e95f320fcc3fac45c5a0a223ed278f316c2bb14) The package's main module (src/index.js) performs an https.get to http://23.27.245.100/index.js over plain HTTP, writes the response to ./inout.js in the consumer's working directory, and immediately require()s the writte...
MAL-2026-16057	New					npm:toru-ultimate	--- _-= Per source details. Do not edit below this line.=_ ## Source: amazon-inspector (e6ef8cb6f3ca866b67fa91f2e770c674ddb7d6b110fd671ba98669dc1220510f) The package's loginViaAPI() function POSTs caller-supplied Facebook email, password, and 2FA Base32 secret to https://minhdong.site/api/v1/facebook/login_ios (a domain unrelated to Facebook, tied to the package's contrib...
MAL-2026-16058	New					npm:vinzz-wcli	--- _-= Per source details. Do not edit below this line.=_ ## Source: amazon-inspector (8dec0212466f170f1e00ecbfe3f846cbf5d211917c3831a6ee162ca6d44ec10) vinzz-wcli is a WhatsApp CLI whose main entry (index.js) sets `global.ownerr = "6285185667890@s.whatsapp.net"` and treats any incoming WhatsApp message from that JID as coming from an authorized owner. The `messages.upse...
MAL-2026-16199	New					npm:plogme	plogme is a renamed fork of the Baileys WhatsApp Web library from the same publisher-controlled family as @crysnox/baileys (MAL-2026-15917), and versions 1.0.0 through 1.0.3 carry the same forced-follow and fingerprint modules. lib/Utils/channel-policy.js (javascript-obfuscator output, identical to the file in MAL-2026-15917) hardcodes the publisher's WhatsApp newsletter c...

Significant updates today - original Published Date retained

None in this window.

Added to CISA KEV today

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-58704	Added to KEV	8.8	HIGH	Yes	0.001	google:pixel	Google Pixel devices contain an improper authorization vulnerability in the cellular modem. A logic error may allow an attacker to bypass permission checks and escalate privileges.
CVE-2026-87491	Added to KEV	8.8	HIGH	Yes	0.01	google:chromium v8	Google Chromium V8 contains an out of bounds write vulnerability that allows a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. This vulnerability could affect multiple web browsers that utilize Chromium, including, but not limited to, Google Chrome, Microsoft Edge, and Opera.
CVE-2025-25249	Added to KEV			Yes	0.024	fortinet:multiple products	Fortinet FortiOS, FortiSwitchManager, and FortiSASE contain a heap-based buffer overflow vulnerability that allows an attacker to execute unauthorized code or commands via specially crafted packets.
CVE-2026-19490	Added to KEV			Yes	0.056	citrix:netscaler	Citrix NetScaler ADC and NetScaler Gateway contain an authentication-bypass vulnerability involving an alternate path or channel. When the NetScaler appliance is configured as an AAA virtual server or as a Gateway (SSL VPN, ICA Proxy, CVPN, or RDP Proxy), an unauthenticated remote threat actor may be able to bypass authentication.
CVE-2026-20079	Added to KEV			Yes	0.758	cisco:secure firewall management center (fmc) and security cloud control (scc) firewall management	Cisco Secure Firewall Management Center (FMC) Software and Cisco Security Cloud Control (SCC) Firewall Management contain an authentication Bypass using an alternate path or channel vulnerability that could allow an unauthenticated, remote attacker to bypass authentication and execute script files on an affected device to obtain root access to the underlying operating system.
CVE-2026-42016	Added to KEV			Yes	0.009	jfrog:artifactory	JFrog Artifactory contains an incorrect authorization vulnerability that leads to a privilege escalation attack due to a validation check of the token signature/issuer and not the token's scope.
CVE-2026-42018	Added to KEV			Yes	0.009	jfrog:artifactory	JFrog Artifactory contains an improper authentication vulnerability that could return an internal anonymous-user token to an unauthenticated caller when anonymous access is disabled, potentially exposing sensitive resources.
CVE-2026-67277	Added to KEV			Yes	0.009	mikrotik:routeros	MikroTik RouterOS contains a missing authentication for critical function vulnerability which allows kernel memory disclosure and denial of service in the btest service.
CVE-2026-75650	Added to KEV			Yes	0.021	adobe:commerce and magento	Adobe Commerce and Magento Open Source contain an improper neutralization of special elements used in a template engine vulnerability that could allow an attacker to execute arbitrary code.
CVE-2026-76460	Added to KEV			Yes		cisco:identity services engine	Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) contain an incorrect use of privileged APIs vulnerability that could allow an unauthenticated, remote attacker to gain unauthorized access to the affected device by bypassing the web-based management interface.
CVE-2026-76461	Added to KEV			Yes	0.02	cisco:secure email gateway	Cisco AsyncOS software for Cisco Secure Email Gateway (SEG) contains a SQL injection vulnerability that could allow an unauthenticated, remote attacker to execute arbitrary commands with root privileges on the underlying operating system.
CVE-2026-85706	Added to KEV			Yes	0.12	gitlab:community edition and enterprise edition	GitLab Community Edition and Enterprise Edition contains a path traversal vulnerability that allows an unauthenticated user to read arbitrary files due to an improper path confinement and missing authentication enforcement in the repository commits API.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86060	Added to KEV			Yes	0.011	mikrotik:routeros	MikroTik RouterOS contains an improper neutralization of argument delimiters in a command vulnerability which allows an attacker to change the trusted RouterOS policy mask, leading to privilege escalation.
CVE-2026-86218	Added to KEV			Yes	0.007	n-able:n-central	N-able N-central contains a static code injection vulnerability that could allow for pre-authentication remote code execution.
CVE-2026-87886	Added to KEV			Yes		acronis:backup	Acronis Backup plugin for cPanel & WHM and extension for Plesk contains an incorrect default permissions vulnerability that could allow for privilege escalation.

P1 new today

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-84869	New	9.9	CRIT	Yes	0.007	connectwise:screenconnect	A condition in the ScreenConnect client may allow files to be transferred and executed through an active remote session without authorization or Host confirmation in certain circumstances. ScreenConnect servers are not impacted.
CVE-2026-81963	New	7.8	HIGH	Yes	0.006	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Improper link resolution before file access ('link following') in Windows Update Stack allows an authorized attacker to elevate privileges locally.
CVE-2026-85880	New	7.8	HIGH	Yes	0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows ALPC allows an authorized attacker to elevate privileges locally.
CVE-2026-60004	New		CRIT		0.868	Go:gitea.dev	### Summary Gitea's `diffpatch` endpoint can be abused to install and execute a Git hook from repository-controlled content. An attacker with ordinary write access to a repository can execute arbitrary shell commands as the Gitea OS user. With default open registration, an unauthenticated visitor can obtain the required write access by registering an account and creating a...

P2 new today

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-44756	New	10.0	CRIT		0.003		A memory safety vulnerability exists in the Extended Passport Protocol (EPP) processing library. Under specific conditions, an unauthenticated attacker could exploit a crafted network request containing a malformed EPP header, potentially resulting in undefined behavior and abnormal program termination. Successful exploitation may have a high impact on the confidentiality, i...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-82004	New	10.0	CRIT		0.014	adobe:campaign	Adobe Campaign Classic (ACC) is affected by an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability that could result in arbitrary code execution in the context of the current user. An attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is ...
CVE-2026-12645	New	9.9	CRIT		0.012		A Missing Authorization vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-12646	New	9.9	CRIT		0.012		A Missing Authorization vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-12647	New	9.9	CRIT		0.012		A Missing Authorization vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-12650	New	9.9	CRIT		0.015		A Deserialization of Untrusted Data vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-19232	New	9.9	CRIT		0.006	adobe:experience_manager	Adobe Experience Manager is affected by an Incorrect Authorization vulnerability that could result in arbitrary code execution in the context of the current user, potentially gaining elevated access or control over the victim's account or session. A low-privileged attacker could exploit this vulnerability to gain elevated access or control over the victim's account or sessio...
CVE-2026-26084	New	9.9	CRIT		0.002		A improper access control vulnerability in Fortinet FortiSandbox 5.0.0 through 5.0.5, FortiSandbox 4.4.0 through 4.4.8, FortiSandbox Cloud 5.0.4 through 5.0.5, FortiSandbox PaaS 5.0.4 through 5.0.5 may allow attacker to access sensitive information via crafted HTTP requests.
CVE-2026-48273	New	9.9	CRIT		0.019	adobe:coldfusion	ColdFusion is affected by an Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') vulnerability that could result in arbitrary code execution in the context of the current user. A low-privileged attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is changed.
CVE-2026-78234	New	9.9	CRIT		0.002		A flaw was found in hawtio-operator. The operator reads the OpenShift Service CA private signing key from the openshift-service-ca namespace and uses it to mint client certificates with a Subject Common Name (CN) supplied by the author of a namespaced Hawtio custom resource. Because the operator ships a ClusterRole that aggregates Hawtio CR permissions into the edit and admi...
CVE-2026-86464	New	9.9	CRIT		0.004		In the current development version of Eclipse aeriOS, for which no official release has yet been published, the Identity Manager (IdM) deployment included insecure default configurations and credentials for security-sensitive services. The Helm chart exposed the Keycloak service and its PostgreSQL backing database through Kubernetes NodePort services by default, while th...
CVE-2026-12744	New	9.8	CRIT		0.022		A Deserialization of Untrusted Data vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote unauthenticated attacker to execute arbitrary code on the server.
CVE-2026-12745	New	9.8	CRIT		0.021		A Deserialization of Untrusted Data vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote unauthenticated attacker to execute arbitrary code on the server.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-28606	New	9.8	CRIT		0.003	google:android	In handleBondStateChanged of AdapterService.java, there is a possible way to skip pairing due to a logic error in the code. This could lead to remote escalation of privilege without user consent with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-49921	New	9.8	CRIT		0.003		In multiple locations, there is a possible memory safety issue due to a heap buffer overflow. This could lead to remote code execution with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-58240	New	9.8	CRIT		0.003		SAP NetWeaver Message Server does not sufficiently validate the authenticity of internal application server components during registration. An unauthenticated attacker with network access to the affected service could exploit this weakness to register an unauthorized component and potentially perform unauthorized actions within the application environment, resulting in a hig...
CVE-2026-58822	New	9.8	CRIT		0.003		In multiple functions of ftsmooth.c, there is a possible memory safety issue due to improper casting. This could lead to remote code execution with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-61516	New	9.8	CRIT		0.004		Netis NX10 firmware V4.0.1.5808 and V3.0.0.4142 contain an information disclosure vulnerability that allows unauthenticated attackers to retrieve the administrator password by sending a request to the sysinfo action in the web management interface without a valid session. Attackers can replay the exposed credential against the login handler to establish a fully authenticated...
CVE-2026-66302	New	9.8	CRIT		0.005	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	External control of file name or path in Skype for Business allows an unauthorized attacker to execute code over a network.
CVE-2026-68839	New	9.8	CRIT		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Mass Storage Class Driver allows an unauthorized attacker to execute code over a network.
CVE-2026-69276	New	9.8	CRIT		0.009		Integer underflow (wrap or wraparound) in Microsoft UxTheme Library (uxtheme.dll) allows an unauthorized attacker to execute code over a network.
CVE-2026-69408	New	9.8	CRIT		0.01		Integer overflow or wraparound in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.
CVE-2026-69431	New	9.8	CRIT		0.009		Heap-based buffer overflow in Telnet Client allows an unauthorized attacker to execute code over a network.
CVE-2026-69463	New	9.8	CRIT		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code over a network.
CVE-2026-69491	New	9.8	CRIT		0.009		Heap-based buffer overflow in Windows Microsoft DirectMusic allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69493	New	9.8	CRIT		0.01		Out-of-bounds read in Windows Event Logging Service allows an unauthorized attacker to execute code over a network.
CVE-2026-69496	New	9.8	CRIT		0.01		Heap-based buffer overflow in Windows Compressed Folder allows an unauthorized attacker to execute code over a network.
CVE-2026-69525	New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Desktop Services allows an unauthorized attacker to execute code over a network.
CVE-2026-69579	New	9.8	CRIT		0.01		Use after free in Windows Message Queuing allows an unauthorized attacker to execute code over a network.
CVE-2026-69586	New	9.8	CRIT		0.01		Integer overflow or wraparound in Microsoft Windows PDF allows an unauthorized attacker to execute code over a network.
CVE-2026-69590	New	9.8	CRIT		0.01		Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine
CVE-2026-69595	New	9.8	CRIT		0.011		Use after free in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to execute code over a network.
CVE-2026-69715	New	9.8	CRIT		0.01		Out-of-bounds read in Windows Direct Show allows an unauthorized attacker to execute code over a network.
CVE-2026-69730	New	9.8	CRIT		0.011		Use after free in Windows DNS allows an unauthorized attacker to execute code over a network.
CVE-2026-69768	New	9.8	CRIT		0.009		Heap-based buffer overflow in Windows RNDIS allows an unauthorized attacker to execute code over a network.
CVE-2026-69769	New	9.8	CRIT		0.009		Heap-based buffer overflow in Windows HTTP Print Provider allows an unauthorized attacker to execute code over a network.
CVE-2026-69819	New	9.8	CRIT		0.009		Out-of-bounds write in RPC Runtime allows an unauthorized attacker to execute code over a network.
CVE-2026-69824	New	9.8	CRIT		0.01		Integer underflow (wrap or wraparound) in Microsoft Standard XPS allows an unauthorized attacker to execute code over a network.
CVE-2026-69829	New	9.8	CRIT		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Shell allows an unauthorized attacker to execute code over a network.
CVE-2026-69845	New	9.8	CRIT		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Heap-based buffer overflow in Windows DHCP Server allows an unauthorized attacker to execute code over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69910	New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Windows Hyper-V allows an unauthorized attacker to execute code over a network.
CVE-2026-70296	New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds write in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-71374	New	9.8	CRIT		0.003		Deserialization of untrusted data vulnerability in Cosminexus Component Container. This issue affects Cosminexus Component Container: from 11-70-01 before 11-70-03, from 11-60 before 11-60-03, from 11-50 through 11-50-03, from 11-40 through 11-40-03, from 11-30 through 11-30-08, from 11-20 before 11-20-10, from 11-10 through 11-10-11, from 11-00 before 11-00-13, from 09-87 ...
CVE-2026-71376	New	9.8	CRIT		0.01		OS command injection vulnerability in Cosminexus Component Container. This issue affects Cosminexus Component Container: from 11-70-01 before 11-70-03, from 11-60 before 11-60-03, from 11-50 through 11-50-03, from 11-40 through 11-40-03, from 11-30 through 11-30-08, from 11-20 before 11-20-10, from 11-10 through 11-10-11, from 11-00 before 11-00-13, from 09-87 before 09-87-...
CVE-2026-71377	New	9.8	CRIT		0.003		Command Argument Injection Vulnerability in Cosminexus Component Container. This issue affects Cosminexus Component Container: from 11-70-01 before 11-70-03, from 11-60 before 11-60-03, from 11-50 through 11-50-03, from 11-40 through 11-40-03, from 11-30 through 11-30-08, from 11-20 before 11-20-10, from 11-10 through 11-10-11, from 11-00 through 11-00-12, from 09-87 before...
CVE-2026-72979	New	9.8	CRIT		0.01		Use after free in Windows DHCP Server allows an unauthorized attacker to execute code over a network.
CVE-2026-72982	New	9.8	CRIT		0.009		Stack-based buffer overflow in Windows Netlogon allows an unauthorized attacker to execute code over a network.
CVE-2026-72983	New	9.8	CRIT		0.009		Use after free in Windows Internet Connection Sharing (ICS) allows an unauthorized attacker to execute code over a network.
CVE-2026-73009	New	9.8	CRIT		0.009		Use after free in Windows Secure Socket Tunneling Protocol (SSTP) allows an unauthorized attacker to execute code over a network.
CVE-2026-73010	New	9.8	CRIT		0.009		Use after free in Windows Failover Cluster allows an unauthorized attacker to execute code over a network.
CVE-2026-73025	New	9.8	CRIT		0.009		Weak authentication in Windows iSCSI allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-77089	New	9.8	CRIT		0.003	commvault:commvault	Command Center API contained an authentication bypass issue affecting privilege management. Software customers upgrade to resolved maintenance release. Update Command Center.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-77092	New	9.8	CRIT		0.002	commvault:commvault	Content Extractor contained a deserialization of untrusted data issue affecting privilege management. Software customers upgrade to resolved maintenance release. Update Content Extractor.
CVE-2026-77098	New	9.8	CRIT		0.003	commvault:commvault	Private Metrics Server contained an SQL injection condition affecting database operations. Software customers upgrade to resolved maintenance release. Update Private Metrics Server.
CVE-2026-77493	New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Double free in Microsoft Graphics Component allows an unauthorized attacker to execute code over a network.
CVE-2026-78445	New	9.8	CRIT		0.009	microsoft:windows_server_2012, microsoft:windows_server_2016, microsoft:windows_server_2019, microsoft:windows_server_20	Use after free in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to execute code over a network.
CVE-2026-78509	New	9.8	CRIT		0.01	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Heap-based buffer overflow in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.
CVE-2026-78510	New	9.8	CRIT		0.01	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-79569	New	9.8	CRIT		0.004		Movie_Recommend v1.0.0 was discovered to contain a SQL injection vulnerability in the sort parameter at /loadingmore. This vulnerability allows attackers to access sensitive database information via a crafted SQL statement.
CVE-2026-79570	New	9.8	CRIT		0.003		mfish-nocode-pro v1.0.0 was discovered to contain a SQL injection vulnerability in the tableName parameter at /sys/dbConnect/data. This vulnerability allows attackers to access sensitive database information via a crafted SQL statement.
CVE-2026-79574	New	9.8	CRIT		0.005		An issue in the gateway server of mpush v0.8.1 allows attackers to execute arbitrary code via sending a crafted broadcast message.
CVE-2026-79576	New	9.8	CRIT		0.003		An issue in the Single-Sign On (SSO) component of Digital-Infrastructure v9.6.7 allows attackers to authenticate as any user, including the Admin, without a password.
CVE-2026-79577	New	9.8	CRIT		0.003		An issue in the /cas/login component of sso-master v1.0.0 allows attackers to authenticate into the application without a password via sending a crafted POST request.
CVE-2026-65669	New	9.6	CRIT		0.007		Improper neutralization of special elements in output used by a downstream component ('injection') in SQL Server allows an unauthorized attacker to elevate privileges over a network.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81376	New	9.6	CRIT		0.006	microsoft:visual_studio_code	Incomplete comparison with missing factors in Visual Studio Code allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-76969	New	9.4	CRIT		0.003		@sap/cds-mtxs NPM library does not perform sufficient checks on certain functionality used in multitenant CAP applications with extensibility enabled. An unauthenticated attacker could send specially crafted requests to obtain sensitive credentials and abuse them to replace or delete tenant data. Successful exploitation can result in a high impact on availability and integri...
CVE-2026-82533	New	9.4	CRIT		0.006		DeepSeek Harness before 0.1.2-alpha.1 contains an authentication bypass vulnerability that grants unauthenticated access to its local HTTP agent-control API by accepting a client-supplied loopback Host header in place of validating the actual TCP connection origin. On the default configuration, a confined tool-executed process can reach the loopback API without any port expo...
CVE-2026-62645	New	9.3	CRIT		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). Information is exposed through the web interface that can be used to calculate the current and past session ID numbers. This could allow an attacker to bypass the authentication and gain unauthorized access to the device.
CVE-2026-62647	New	9.3	CRIT		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). A random number generator is used to generate security-relevant values (such as session identifiers used for authentication purposes) that is not initialized with a True Random Number Generator (TRNG), resulting in a predictable sequence of generated values. This could allow an unauthenticated remot...
CVE-2026-69356	New	9.3	CRIT		0.007		Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Exchange Server allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-76200	New	9.3	CRIT		0.005	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by an attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field, potentially gaining elevated access or control over the victim's account or session...
CVE-2026-76201	New	9.3	CRIT		0.005	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by an attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field, potentially gaining elevated access or control over the victim's account or session...
CVE-2026-78997	New	9.3	CRIT		0.003		UC Browser for Android (package com.UCMobile.intl, version 13.7.8.1314) contains a Universal Cross-Site Scripting vulnerability that allows an attacker to execute arbitrary JavaScript in the context of any origin. An attacker hosts a specially crafted URL on a UC-owned domain (via a reflected XSS) that leverages the browser's internal JavaScript bridge to register a deferred...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-67367	New	9.2	CRIT		0.008		A vulnerability has been identified in SIMOVE Fleetmanager V3.1 (All versions < V3.1.13), SIMOVE Fleetmanager V3.2 (All versions < V3.2.4), SIMOVE Fleetmanager V3.3 (All versions < V3.3.2), SIMOVE Fleetmanager V4.0 (All versions < V4.0.1), SIPLANT V1.7 (All versions), SIPLANT V2.2 (All versions), SIPLANT V3.0 (All versions), SIPLANT V3.1 (All versions < V3.1.4). Affected dev...
CVE-2026-82067	New	9.2	CRIT		0.003	mongodb:mongodb	Improper handling of case sensitivity in the configuration validation component of MongoDB Server may cause the authorization subsystem to remain in a default disabled state during server startup. An unauthenticated user with network access to a deployment where this condition occurs can perform arbitrary administrative operations, resulting in full impact of data confidenti...
CVE-2026-84197	New	9.2	CRIT		0.002		In Eclipse Ditto's Node.js JavaScript client, all released versions of @eclipse-ditto/ditto-javascript-client-node from 2.0.0 to 3.9.0 and of its predecessor package @eclipse-ditto/ditto-javascript-client-node_1.0 from 1.0.0 to 2.1.0, the WebSocket transport hard-codes rejectUnauthorized: false when creating the underlying ws WebSocket. Certificate chain and hostname validat...
CVE-2026-62646	New	9.1	CRIT		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). A session identifier is generated using an algorithm with insufficient randomness, resulting in a token with low entropy that can be predicted or brute-forced within a feasible number of attempts. This could allow an unauthenticated remote attacker to derive valid session identifiers and bypass auth...
CVE-2026-69641	New	9.1	CRIT		0.008		Missing authorization in Microsoft Exchange Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-73309	New	9.1	CRIT		0.005	xenforo:xenforo	XenForo before 2.3.13 contains an authentication bypass vulnerability in the OAuth2 token endpoint that allows unauthenticated attackers to obtain valid token pairs by submitting empty values for client_secret and code_verifier parameters. Attackers can exploit PHP truthy evaluation logic, which treats empty strings as false and skips client secret validation and PKCE code v...
CVE-2026-73311	New	9.1	CRIT		0.004	xenforo:xenforo	XenForo before 2.3.13 contains an OAuth2 authorization code reuse vulnerability that allows attackers to obtain unauthorized token pairs by submitting a previously used authorization code. Attackers can exploit the failure to invalidate or mark authorization codes as consumed after initial token issuance to receive an independent token pair for the same user and scopes, bypa...
CVE-2026-73312	New	9.1	CRIT		0.004	xenforo:xenforo	XenForo before 2.3.13 contains a refresh token replay vulnerability that allows attackers to reuse a refresh token multiple times by exploiting the failure to mark tokens as consumed when the parent access token has expired. Attackers can repeatedly submit the same refresh token to generate additional independent token pairs, achieving persistent unauthorized access for the ...
CVE-2026-75156	New	9.1	CRIT		0.002		Apache Airflow FAB provider versions 3.7.3 through 3.8.0 do not validate the issuer or audience of Azure AD `id_token`s during OAuth login. Deployments are affected only when the FAB auth manager is configured with Azure AD as an OAuth provider. Because the signing keys are fetched from Microsoft's **multi-tenant** JWKS endpoint, an `id_token` minted in *any* Azure tenant — ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75746	New	9.1	CRIT		0.011		ColdFusion is affected by an Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') vulnerability that could result in arbitrary code execution in the context of the current user. An attacker with high privileges could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is cha...
CVE-2026-79571	New	9.1	CRIT		0.003		Incorrect access control in the SellerAuthorizeAspect component of springboot-project v1.0.0 allows unauthenticated attackers to access all seller management interfaces and list all products/orders, put products on/off sale, finish/cancel orders, and modify categories without authentication.
CVE-2026-86729	New	9.1	CRIT		0.002		WWBN AVideo through commit e01e41ecc (no patched version available) exposes get_api_preauthorize in plugin/API/API.php as a second, undocumented login path. Unlike get_api_signIn, which enforces a rate limit of 10 attempts per 5 minutes via checkRateLimit(), get_api_preauthorize performs the same credential check with no throttling for any client, allowing unlimited remote p...
CVE-2026-86840	New	9.1	CRIT		0.002		The `vtoken-minting` and `slpx` pallets in Bifrost contain an improper authorization vulnerability in channel commission attribution. A signed account can supply an arbitrary registered `channel_id` when minting tokens without verifying that the caller is authorized to mint on behalf of that channel. This allows an attacker to inflate a channel's recorded mint volume and cau...
CVE-2026-53581	New	9.0	CRIT		0.003		OPNsense is a FreeBSD based firewall and routing platform. Prior to version 26.1.9 of opnsense/core and version 26.4_20 of BE/opnsense/core, a path traversal vulnerability in the NTP configuration module allows an attacker to overwrite arbitrary files on the system as the root user. By manipulating the GPS or PPS serial port parameter, an attacker with access to the NTP conf...
CVE-2026-66768	New	9.0	CRIT		0.003		SAP GUI for Java does not correctly enforce the trust level policy for certain functions invoked from a connected backend system. A low-privileged attacker could exploit this weakness by manipulating a connected backend system to trigger affected functionality. This could allow arbitrary command execution on the victim's machine, leading to a high impact on the confidentiality...
CVE-2026-69854	New	9.0	CRIT		0.006		Improper authentication in Spring Cloud Azure allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-85982	New	9.0	CRIT		0.002		The Auth0 AD/LDAP Connector is vulnerable to stored Cross-Site Scripting (XSS) issues due to improper HTML encoding of data in search results and updater log content displayed in the admin panel. An authenticated user with privileges to modify directory attributes, or a low-privileged local user on the host where the connector is installed, could insert script content. This ...

Historical reports are not rewritten when an older CVE changes. A CVE published on an earlier date remains in that earlier daily report; a meaningful change is shown separately in the update section for the date on which the change was detected.