

Daily Vulnerability Report - 2026-09-09

Window (UTC): 2026-09-09T00:00 to 2026-09-10T00:00 | Sources: NVD, CISA KEV, EPSS, Vulnrichment, GHSA, OSV | Generated 2026-09-17 13:17:17 UTC

Total	New	Updated	KEV added	KEV	Critical	High	Medium	Unscored	Watchlist
780	738	29	13	16	68	223	352	110	10

New today - published in this report window

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87491	New	8.8	HIGH	Yes	0.01	google:chrome	Out of bounds write in V8 in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-79696	New	10.0	CRIT		0.004		A Code Injection vulnerability in adk web in Google Cloud Agent Development Kit (ADK) for Python versions 2.0.0 through 2.6.0 on Python (OSS), Cloud Run, and GKE environments where pytest is installed allows an unauthenticated remote attacker to execute arbitrary code using a crafted test session replay.
CVE-2026-85978	New	10.0	CRIT		0.009		An unauthenticated remote code execution vulnerability exists in the Policy Manager console of Akana API Platform. A path normalization discrepancy between the authentication filter and the servlet dispatcher allows a crafted request to bypass authentication and reach an endpoint that evaluates attacker-supplied script code without sandboxing, resulting in arbitrary code exe...
CVE-2026-87827	New	10.0	CRIT		0.011		Certain KGUARD DVR devices running vulnerable firmware expose a system command execution service on all network interfaces without requiring authentication. A remote unauthenticated attacker with network access to the affected service can execute arbitrary system commands on the device, potentially resulting in complete compromise of the DVR. The vulnerability is known to h...
CVE-2026-67401	New	9.9	CRIT		0.01		A vulnerability in cPanel allows a mail-enabled account to achieve remote code execution as root through SQLi in EmailTrack component
CVE-2026-21095	New	9.8	CRIT		0.005	samsung:android	Heap-based buffer overflow in DNG decoder of libimagecodec.quram.so prior to SMR Sep-2026 Release 1 allows remote attackers to execute arbitrary code.
CVE-2026-21096	New	9.8	CRIT		0.005	samsung:android	Heap-based buffer overflow in JPEG decoder of libimagecodec.quram.so prior to SMR Sep-2026 Release 1 allows remote attackers to execute arbitrary code.
CVE-2026-36433	New	9.8	CRIT		0.005		An issue in Actions Semiconductor Co. Ltd Tool- Media Player Utilities v.4.46 allows a physically proximate attacker execute arbitrary code via the Production.dll and RdiskUpgrade.exe components
CVE-2026-41871	New	9.8	CRIT		0.008	apache:nutch	Missing Authorization, Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection') vulnerability in Apache Nutch Server (Nutch REST API). This issue affects Apache Nutch: from 1.10 through 1.22. Users are recommended to upgrade to version 1.23, which removes the Nutch Server. If an upgrade is not possible, user must restrict access to instances ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-56207	New	9.8	CRIT		0.005	apache:impala	Signature of Bearer token is not verified in last step of SAML2 authentication for Impala's hs2-http interface, allowing altering user name and acting as another user. This issue affects Apache Impala: >=4.0.0. Users are recommended to upgrade to version 4.5.2, which fixes this issue.
CVE-2026-71801	New	9.8	CRIT		0.005		An issue was discovered in s-pms SPMS-Server through v1.0. The application contains a hardcoded default access token secret within its core configuration file, which is not overridden or removed in the production environment profile. A remote, unauthenticated attacker can locally forge valid administrative session tokens to completely bypass the authentication mechanism gain...
CVE-2026-71805	New	9.8	CRIT		0.004		An arbitrary file upload and path traversal vulnerability exists in LZ-litchi 1.0.0. Unauthenticated remote attackers can upload arbitrary files and write them outside the intended storage directory via the directory parameter in POST /app-api/infra/file/upload.
CVE-2026-79689	New	9.8	CRIT		0.019	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to script injection.
CVE-2026-79941	New	9.8	CRIT		0.019	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in a Command ('Command Injection') vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to script injection.
CVE-2026-80172	New	9.8	CRIT		0.003	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Insufficient Verification of Data Authenticity vulnerability. An unauthenticated attacker with remote access could exploit this, leading to unauthorized access. This vulnerability is considered critical as an unauthenticated attacker can repeatedly reuse...
CVE-2026-85102	New	9.8	CRIT		0.003		Improper certificate trust validation during VPN negotiation in Check Point Quantum Security Gateway may allow an unauthenticated remote attacker to execute arbitrary code on the Gateway.
CVE-2026-85103	New	9.8	CRIT		0.004		A heap-based buffer overflow in VPN certificate ASN.1 decoding may allow an unauthenticated remote attacker to execute arbitrary code on Check Point Quantum Security Management and Quantum Security Gateway systems.
CVE-2026-87534	New	9.8	CRIT		0.002	google:android, google:chrome	Missing authorization in WebView in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via crafted network traffic. (Chromium security severity: Medium)
CVE-2026-87544	New	9.8	CRIT		0.003	google:chrome	Incorrect authorization in Extensions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions into a privileged page via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87595	New	9.8	CRIT		0.003	google:chrome	Server-side request forgery in Mobile in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Low)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-54694	New	9.6	CRIT		0.003		SkillTree is a micro-learning gamification platform. Prior to version 4.4.2, two independent code flaws combine into a single exploitable attack chain, with three distinct exploitation paths of escalating impact. `StringHighlighter.js` builds an HTML string by interpolating raw `value` substrings directly into a template literal with no HTML entity encoding. `HighlightedValu...
CVE-2026-86751	New	9.6	CRIT		0.003	snipeitapp:snipe-it	Snipe-IT before 8.7.0 fails to properly sanitize markdown image syntax in note fields, allowing authenticated users to read arbitrary server files and issue server-side HTTP requests. Attackers can submit markdown image syntax in checkout acceptance notes that survive HTML escaping, are expanded by CommonMark parser, and resolved by laravel-mail-auto-embed via file_get_conte...
CVE-2026-87438	New	9.6	CRIT		0.006	google:android, google:chrome	Out of bounds write in WebGL in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Critical)
CVE-2026-87448	New	9.6	CRIT		0.005	google:chrome	Use after free in DevTools in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87455	New	9.6	CRIT		0.004	google:chrome	Use after free in Aura in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87464	New	9.6	CRIT		0.006	google:chrome	Use after free in WebGL in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Critical)
CVE-2026-87470	New	9.6	CRIT		0.004	apple:macos, google:chrome	Improper quantity validation in Tint in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87474	New	9.6	CRIT		0.005	google:chrome	Use after free in Payments in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87488	New	9.6	CRIT		0.005	google:android, google:chrome	Use after free in WebGL in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Critical)
CVE-2026-87492	New	9.6	CRIT		0.003	google:chrome	Incorrect authorization in DevTools in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87494	New	9.6	CRIT		0.003	google:chrome, microsoft:windows	Use after free in Browser in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87500	New	9.6	CRIT		0.003	google:chrome	Improper validation of array index in ANGLE in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87504	New	9.6	CRIT		0.004	google:chrome	Use after free in Core in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to execute arbitrary code outside the sandbox via a crafted Chrome extension. (Chromium security severity: Medium)
CVE-2026-87512	New	9.6	CRIT		0.005	google:chrome, microsoft:windows	Use after free in ANGLE in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87520	New	9.6	CRIT		0.004	google:android, google:chrome	Use after free in Dawn in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87526	New	9.6	CRIT		0.004	google:chrome	Use after free in Passwords in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to potentially execute arbitrary code outside the sandbox via UI Interaction. (Chromium security severity: Medium)
CVE-2026-87527	New	9.6	CRIT		0.005	google:chrome	Buffer overflow in WebGL in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Critical)
CVE-2026-87528	New	9.6	CRIT		0.003	google:chrome, microsoft:windows	Type confusion in Rust in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87529	New	9.6	CRIT		0.005	google:chrome	Numeric truncation error in Media in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87547	New	9.6	CRIT		0.004	google:chrome	Incorrect reference resolution in FileSystem in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87558	New	9.6	CRIT		0.004	apple:macos, google:chrome	Use after free in Payments in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87581	New	9.6	CRIT		0.004	google:chrome	Use after free in Payments in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87607	New	9.6	CRIT		0.004	apple:macos, google:chrome	Use after free in Device in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87609	New	9.6	CRIT		0.004	apple:iphone_os, google:chrome	Use after free in Sharing in Google Chrome on on iOS prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via crafted network traffic. (Chromium security severity: Medium)
CVE-2026-87621	New	9.6	CRIT		0.003	google:chrome, microsoft:windows	Out of bounds write in ANGLE in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87634	New	9.6	CRIT		0.004	google:chrome	Use after free in WebPackaging in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87637	New	9.6	CRIT		0.003	apple:macos, google:chrome	Use after free in Extensions in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87638	New	9.6	CRIT		0.003	google:chrome	Out of bounds write in Media in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87643	New	9.6	CRIT		0.004	google:android, google:chrome	Integer overflow in GPU in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87646	New	9.6	CRIT		0.004	google:chrome	Use after free in Web Authentication in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87650	New	9.6	CRIT		0.003	google:chrome	Out of bounds read in WebGL in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87654	New	9.6	CRIT		0.004	google:chrome, microsoft:windows	Buffer overflow in ANGLE in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-47156	New	9.3	CRIT		0.005		MantisBT is an open source bug tracker. Versions 2.28.3 and earlier contain a critical authentication bypass in the SOAP API's mci_check_login() function. Any user knowing any valid cookie_string can authenticate as any other user (knowing their username), including the administrator, without knowing the target's password. The vulnerability is exploitable with zero prior acc...
CVE-2026-87929	New	9.3	CRIT		0.003		MaxSite CMS through 109.6 ships with a hardcoded session encryption key in application/config/config.php that is never changed during installation, allowing unauthenticated attackers to forge administrator session cookies. Attackers can mint a malicious ci_session cookie with administrator privileges by computing an HMAC-SHA1 using the publicly known encryption key, bypassin...
CVE-2026-88069	New	9.3	CRIT		0.003		Pandora contains a path traversal vulnerability in its archive extraction worker. When processing a specially crafted archive or disk image, attacker-controlled file paths could be used without ensuring that the resulting destination remained within the intended extraction directory. An attacker able to submit a malicious file for analysis could use path traversal sequences...
CVE-2026-87930	New	9.2	CRIT		0.003		MaxSite CMS through 109.6 passes the ci_session cookie to unserialize() without class restrictions, allowing unauthenticated attackers to inject PHP objects. Attackers can forge valid session cookies using the hardcoded encryption key to trigger magic methods and corrupt application state or achieve code execution if gadget classes exist.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-16272	New	9.1	CRIT		0.001		Use of less trusted source vulnerability in PayTR Payment and Electronic Money Institution Inc. PayTR Virtual Pos iFrame API (v9x) WHMCS Module allows Exploitation of Trusted Identifiers. This issue affects PayTR Virtual Pos iFrame API (v9x) WHMCS Module: from v9.0.0 before v9.0.3.
CVE-2026-22590	New	9.1	CRIT		0.004		eprosima Fast DDS is a C++ implementation of the DDS (Data Distribution Service) standard of the OMG (Object Management Group). Versions prior to 2.6.12, 2.14.6, 3.2.4, 3.3.1, and 3.4.2 have a remotely triggerable Out-of-Bounds Read while processing RTPS `DATA_FRAG` submessages. An attacker can craft a `DATA_FRAG` with a large `sampleSize` but a small actual payload, and set...
CVE-2026-41869	New	9.1	CRIT		0.008	apache:nutch	Missing Authorization, Improper Resource Shutdown and Job Interruption vulnerability in Apache Nutch Server (Nutch REST API). This issue affects Apache Nutch: from 1.10 through 1.22. Users are recommended to upgrade to version 1.23, which removes the Nutch Server. If an upgrade is not possible, user must restrict access to instances running the Nutch Service to trustee...
CVE-2026-53939	New	9.1	CRIT		0.002		OpenIDC/cjose is a C library implementing the Javascript Object Signing and Encryption (JOSE). In versions 0.6.1 through 0.6.2.5, when cjose encrypts a JWE using an AES-CBC-HMAC content-encryption algorithm (`A128CBC-HS256`, `A192CBC-HS384`, or `A256CBC-HS512`) together with any key-management algorithm that generates a fresh content-encryption key (CEK), the CEK is all zero...
CVE-2026-87806	New	9.1	CRIT		0.003		Parse Server versions <= 8.6.87 and >= 9.0.0 < 9.10.1-alpha.7 contain an authentication bypass in the built-in LDAP authentication adapter. The adapter forwarded the client-supplied password to the directory without verifying that a password had been supplied, and treated any non-error response from the directory as proof of authentication. A zero-length credential turns an ...
CVE-2026-67403	New	9.0	CRIT		0.002		Cash Collect contains an improper authorization vulnerability in the Sage AR Automation API. Insufficient tenant-level authorization checks allow authenticated users to access administrative resources belonging to other tenants by specifying a valid non predictable tenant identifier.
CVE-2026-68484	New	9.0	CRIT		0.002		Cash Collect contains an improper authorization vulnerability in the Sage AR Automation API. Administrative functions do not properly verify user privileges, allowing authenticated low-privileged users to create administrator accounts and obtain elevated privileges.
CVE-2026-87613	New	9.0	CRIT		0.004	google:chrome	Incorrect reference resolution in Extensions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via crafted network traffic. (Chromium security severity: Medium)
CVE-2026-87911	New	9.0	CRIT		0.01		An OS command injection weakness in the read-only enforcement of the SQL validation component in Amazon awslabs postgres-mcp-server before 1.1.7 might allow an unauthenticated actor to execute operating system commands on the host of a self-managed PostgreSQL server by placing a crafted COPY ... TO PROGRAM statement into content that is processed when an authenticated user i...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-14359	New	8.8	HIGH		0.002		The YITH WooCommerce Waitlist Premium plugin for WordPress is vulnerable to Privilege Escalation in versions up to, and including, 3.35.0. This is due to the <code>add_user_in_waiting_list()</code> function registered on the <code>wp_ajax_yith_wcwtl_add_user</code> action being missing both a capability check and a nonce verification, and using <code>parse_str()</code> + <code>extract()</code> to import attacker-controlled va...
CVE-2026-21094	New	8.8	HIGH		0.002	samsung:android	Improper input validation in <code>wpa_suppl</code> prior to SMR Sep-2026 Release 1 allows adjacent attackers to write out-of-bounds memory.
CVE-2026-41870	New	8.8	HIGH		0.007	apache:nutch	Missing Authorization, Improper Control of Generation of Code ('Code Injection'), Improper Control of Dynamically-Managed Code Resources, Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection') vulnerability in Apache Nutch Server (Nutch REST API). This issue affects Apache Nutch: from 1.11 through 1.22. Users are recommended to upgrade to v...
CVE-2026-57866	New	8.8	HIGH		0.006	apache:impala	Server side request forgery in Apache Impala versions 4.4.x and 4.5.x. Authenticated Impala users with permissions to execute the <code>ai_generate_text()</code> function can exfiltrate secrets provided by the credential providers configured in the <code>`hadoop.security.credential.provider.path`</code> property of <code>`core-site.xml`</code> . The secret's key must be known to the user.
CVE-2026-71808	New	8.8	HIGH		0.004		A SQL Injection vulnerability in Siam Ordering (<code>siam-server</code>) 1.0.0 allows remote authenticated attackers to execute arbitrary SQL commands via the <code>`\${}`</code> string concatenation in <code>AdminMapper.java</code> and multiple other Mapper files (including <code>MerchantWithdrawRecordMapper.java</code> and <code>MemberWithdrawRecordMapper.java</code>).
CVE-2026-76801	New	8.8	HIGH		0.005		The FireBox – WooCommerce Popup Builder, Exit Intent Popup, Email Optin & Cart Abandonment plugin for WordPress is vulnerable to Remote Code Execution in all versions up to, and including, 3.1.10 via the <code>value</code> function. This is due to a trivially bypassable regex blacklist in <code>Executer::allowedToRun()</code> that fails to block WordPress core functions such as <code>wp_insert_user</code> , <code>update</code> ...
CVE-2026-80099	New	8.8	HIGH		0.005		Several Newfold plugins are vulnerable to Authentication Bypass. The vulnerability exists because the plugins bundle the <code>wp-module-data</code> module. In the module, the <code>`authenticate()`</code> method — registered on the <code>`rest_authentication_errors`</code> filter and therefore evaluated for every unauthenticated REST API request — performs an HMAC-style Bearer token comparison that degenerates w...
CVE-2026-80914	New	8.8	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: Bluetooth: ISO: fix use-after-free of listener socket in <code>iso_conn_ready</code> <code>iso_conn_ready()</code> looks up the BIS listener socket with <code>iso_get_sock()</code> , which takes a reference, and then, without re-checking its state, creates a child socket from it: <code>parent = iso_get_sock(hdev, ...)</code> ; if (!parent) re...
CVE-2026-80921	New	8.8	HIGH		0.001		In the Linux kernel, the following vulnerability has been resolved: KVM: s390: vsie: zero stale crypto bits When shadowing crypto access bits from a format0 apcb (<code>crycb 0</code> or <code>1</code>), the bits 64..255 are unchanged from whatever is in the vsie page in the <code>crycb</code> and thus in the apcb. This gives a nested guest potential access to a device no longer available. Zero out the remainin...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86099	New	8.8	HIGH		0.004		Chainlit through 2.12.0 fails to validate the client-supplied socket.io sessionId parameter, allowing unauthenticated attackers to traverse filesystem paths by injecting absolute or relative path sequences. Attackers can craft malicious sessionId values that escape the upload directory and recursively delete arbitrary directories accessible to the service process.
CVE-2026-86775	New	8.8	HIGH		0.005		knowns (npm package) versions <= 0.29.1 contain a path traversal vulnerability in the Document API. The HTTP handler in internal/server/routes/docs.go normalizes the user-supplied document path with cleanDocPath(), which strips leading/trailing slashes and the .md suffix but does not neutralize ../ traversal sequences, and internal/storage/doc_store.go then builds the target...
CVE-2026-87430	New	8.8	HIGH		0.005	google:chrome	Buffer overflow in WebRTC in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87433	New	8.8	HIGH		0.003	google:chrome	Race condition in FileAPI in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass site isolation via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87440	New	8.8	HIGH		0.004	google:chrome	Out of bounds read in Media in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87444	New	8.8	HIGH		0.004	google:chrome	Memory corruption in Codecs in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87460	New	8.8	HIGH		0.003	google:chrome	Use after free in Platform in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87489	New	8.8	HIGH		0.002	google:chrome	Memory corruption in V8 in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code inside the sandbox via a crafted Chrome extension. (Chromium security severity: Low)
CVE-2026-87536	New	8.8	HIGH		0.003	google:chrome	Use after free in V8 in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87542	New	8.8	HIGH		0.003	google:chrome	Use after free in Input in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87569	New	8.8	HIGH		0.002	google:chrome	Missing authorization in Views in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87570	New	8.8	HIGH		0.002	google:chrome	Incorrect authorization in SiteIsolation in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process and leveraged social engineering to bypass site isolation via a crafted file. (Chromium security severity: Medium)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87579	New	8.8	HIGH		0.004	google:chrome	Buffer overflow in WebRTC in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87585	New	8.8	HIGH		0.003	google:chrome, microsoft:windows	Double free in PDFium in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code inside the sandbox via a crafted PDF file. (Chromium security severity: High)
CVE-2026-87587	New	8.8	HIGH		0.003	google:chrome	Use after free in V8 in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87588	New	8.8	HIGH		0.003	google:chrome	Use after free in Chromecast in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87612	New	8.8	HIGH		0.003	google:chrome	Type confusion in V8 in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87617	New	8.8	HIGH		0.004	google:chrome	Use after free in DevTools in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87625	New	8.8	HIGH		0.003	google:chrome	Use after free in V8 in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to execute arbitrary code inside the sandbox via a crafted Chrome extension. (Chromium security severity: Medium)
CVE-2026-87636	New	8.8	HIGH		0.003	google:chrome	Type confusion in XML in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87766	New	8.8	HIGH		0.001		A flaw was found in bubblewrap. During sandbox setup, creating files or directories under the new root can follow a parent symlink onto the host via /oldroot, writing attacker-chosen paths outside the sandbox as the launching user. This happens before the sandboxed process starts. This issue is GHSA-pxhw-h44j-8pfx. It is fixed in bubblewrap 0.12.0.
CVE-2026-87795	New	8.8	HIGH		0.003		zstd-jni versions before 1.5.7-14 fail to validate offset and length parameters in the ZstdDictCompress constructor, allowing out-of-bounds memory reads. Attackers can supply untrusted offset or length values to read native heap memory into the compression dictionary, typically causing JVM crashes.
CVE-2026-87823	New	8.8	HIGH		0.004		zstd-jni before 1.5.7-14 performs 32-bit signed bounds checks on three direct-ByteBuffer frame-size native methods, allowing out-of-bounds memory reads via negative or overflowing offsets. Attackers can supply negative offset values near Integer.MIN_VALUE to read unmapped memory, causing JVM termination or extracting arbitrary frame size data from unintended memory locations.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87927	New	8.8	HIGH		0.003		MaxSite CMS through 109.6 contains a local file inclusion vulnerability in the ajax and require-maxsite dispatchers that allows unauthenticated attackers to execute privileged handler files by supplying base64-encoded path traversal sequences. Attackers can bypass path validation checks and execute admin-gated handler actions without authentication to access sensitive functi...
CVE-2023-54355	New	8.7	HIGH		0.002		PocketMine-MP versions before 5.3.1 and 4.23.1 fail to validate that the identityPublicKey in LoginPacket uses the required secp384r1 elliptic curve. Attackers can provide LoginPackets with keys using different curves or non-EC key types to pass login verification but trigger an uncaught exception during ECDH key derivation, crashing the server.
CVE-2023-54390	New	8.7	HIGH		0.003		PocketMine-MP versions before 5.3.1 and 4.23.1 contain a denial of service vulnerability in LoginPacket JSON parsing due to improper null value handling in arrays. Attackers can send malformed JSON with unexpected null elements in LoginPacket to crash the server.
CVE-2023-54393	New	8.7	HIGH		0.004		PocketMine-MP versions before 4.20.5 contain a denial of service vulnerability in LoginPacket JSON parsing due to improper validation in the JsonMapper dependency. Attackers can send malformed JSON structures in LoginPacket to crash the server.
CVE-2024-58381	New	8.7	HIGH		0.004		PocketMine-MP before 5.11.1 contains a denial of service vulnerability in LoginPacket JSON processing that allows remote attackers to crash the server by sending malformed JSON data. Attackers can exploit improper object initialization from scalar JSON types to trigger unset required properties, causing the application to crash.
CVE-2024-58382	New	8.7	HIGH		0.003		league/commonmark versions before 2.6.0 contain polynomial time complexity vulnerabilities in Markdown parsing that allow attackers to cause denial of service. Attackers can submit carefully crafted Markdown inputs designed to trigger worst-case performance, and sending multiple requests in parallel exhausts CPU resources and PHP-FPM processes.
CVE-2026-77120	New	8.7	HIGH		0.004		CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability exists that could cause privilege escalation to root and unauthorized execution of administrative functions when an authenticated user with SSH enabled interacts with the operating system console that improperly processes user-controlled input.
CVE-2026-81640	New	8.7	HIGH		0.002		An attacker could derive the camera's Wi-Fi password and connect to its wireless network. This weakens or eliminates the security value of the access-point password and may expose the live video stream, device services, status interfaces, and firmware-update functionality.
CVE-2026-86199	New	8.7	HIGH		0.003		PocketMine-MP versions before 5.43.1 fail to properly validate the Certificate field during offline login authentication. Unauthenticated players can trigger an uninitialized property access error that crashes the server.
CVE-2026-86201	New	8.7	HIGH		0.003		PocketMine-MP before 5.41.1 contains a denial of service vulnerability in LoginPacket processing where large or complex structures in unknown clientData JWT properties cause excessive logging without sanitization. Attackers can send crafted LoginPackets with deeply nested or massive object structures to trigger out-of-memory conditions and crash the server.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87807	New	8.7	HIGH		0.003		siyuan versions before v3.8.2 contain an authenticated SQL injection vulnerability in the fullTextSearchBlock endpoint's method=1 query parameter. Attackers can inject UNION SELECT statements to read the entire blocks table, bypassing publish-access controls and exposing all document content and sensitive attributes.
CVE-2026-87808	New	8.7	HIGH		0.003		SiYuan versions <= 3.8.1 contain an incomplete fix for CVE-2026-32767 (GHSA-j7wh-x834-p3r7). The prior fix (commit d5e2d0bc) added an administrator check for SQL mode (method=2) in POST /api/search/fullTextSearchBlock, but the endpoint still does not enforce the application's read-only boundary: for method=2 it forwards caller-supplied SQL to the blocks database query path w...
CVE-2026-87816	New	8.7	HIGH		0.003		PasswordPusher before 2.11.1 contains a time-of-check-to-time-of-use race condition in view limit enforcement that allows unauthenticated attackers to bypass expire_after_views limits. Attackers can send concurrent requests to the show endpoint to access one-time secrets multiple times before the view count is incremented and the push expires.
CVE-2026-87817	New	8.7	HIGH		0.003	gitpython_project:gitpython	GitPython before 3.1.60 fails to properly validate the git directory location, allowing attackers to impersonate the git directory using tracked files like gitdir, commondir, and HEAD. Attackers can execute arbitrary code by placing a malicious pre-commit hook in the tracked hooks directory that executes when a victim calls index.commit() on a cloned or opened repository.
CVE-2026-87822	New	8.7	HIGH		0.004		t-digest versions 3.1 through 3.3 fail to validate centroid means during deserialization in MergingDigest.fromBytes, allowing attackers to inject NaN values that bypass validation checks. Attackers can craft malicious serialized digests containing NaN centroids that degrade sorting performance from O(n log n) to O(n squared), causing severe processing delays during merge ope...
CVE-2026-87995	New	8.7	HIGH		0.002	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.8.11 until 0.11.1, src/lib/components/chat/FileNav/PortPreview.svelte rendered terminal port content in an iframe sandbox containing both allow-scripts and allow-same-origin. Because the terminal proxy serves that content from the Open WebUI origin, an authenticated user with access ...
CVE-2026-14962	New	8.6	HIGH		0.003		The ELEX WooCommerce Request a Quote WordPress plugin before 2.4.1 does not properly sanitise and escape a parameter before using it in a SQL query, allowing unauthenticated users to perform SQL injection attacks and extract arbitrary data from the database.
CVE-2026-19233	New	8.6	HIGH		0.007		CWE-918: Server-Side Request Forgery (SSRF) vulnerability exists that could cause unauthorized command execution and disclosure of server data when an attacker with a privileged account sends crafted, unvalidated parameters to a server endpoint.
CVE-2026-26212	New	8.6	HIGH		0.005		Rara One Click Demo Import plugin for WordPress before 1.3.5 contains an arbitrary file upload vulnerability that allows authenticated attackers with Administrator privileges to upload arbitrary PHP files by passing a false value to wp_handle_upload() that disables WordPress core's file type validation checks across all three file parameters in the process_uploaded_files() f...
CVE-2026-49310	New	8.6	HIGH		0.003		Permission control vulnerability in the event notification module. Impact: Successful exploitation of this vulnerability may affect service confidentiality.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-79322	New	8.6	HIGH		0.003	mageplaza:mageplaza_blog	SQL injection in the RelatedProduct block in Mageplaza Blog for Magento 2 (mageplaza/magento-2-blog-extension) through 4.3.2 allows remote unauthenticated attackers to execute arbitrary SQL commands and read arbitrary database contents via the id parameter to /mpblog/post/view.
CVE-2026-8044	New	8.6	HIGH		0.004		CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') vulnerability exists that could cause remote code execution by an attacker with a privileged account when malicious arguments are provided as backup configuration parameters.
CVE-2026-84068	New	8.6	HIGH		0.003		The Quentn WP WordPress plugin before 1.2.15 does not adequately escape a request parameter before using it in an unprepared SQL query, allowing unauthenticated attackers to extract arbitrary data from the database via SQL injection.
CVE-2026-86762	New	8.6	HIGH		0.003	snipeitapp:snipe-it	Snipe-IT before 8.7.0 does not apply the CheckUserIsActivated middleware to the `api` middleware group in app/Http/Kernel.php, and deactivating a user does not revoke that user's Passport personal access tokens. As a result, although a deactivated account is correctly refused at web login, its existing API token continues to authenticate and to grant read and write access to...
CVE-2026-86770	New	8.6	HIGH		0.003	snipeitapp:snipe-it	Snipe-IT before 8.7.0 fails to validate username case sensitivity during SAML authentication, allowing attackers to authenticate as different users by registering IdP accounts with accent or case variants of victim usernames. Attackers can exploit the default utf8mb4_unicode_ci database collation to bypass username matching and achieve account takeover through federated logi...
CVE-2026-87633	New	8.6	HIGH		0.002	google:chrome	Use after free in Views in Google Chrome prior to 153.0.8010.36 allowed a local attacker to execute arbitrary code outside the sandbox via UI Interaction. (Chromium security severity: High)
CVE-2026-12858	New	8.5	HIGH		0.001		Improper Privilege Management vulnerability in ESET AV Remover (standalone) allows Privilege Escalation via especially crafted RPC.
CVE-2026-77974	New	8.5	HIGH		0.002		After spoofing the device and obtaining one user confirmation, an attacker may be able to cause the application to transmit firmware through an unauthenticated and unsigned update channel.
CVE-2026-87023	New	8.5	HIGH		0.003	tanium:comply	Tanium addressed a path traversal vulnerability in Comply.
CVE-2026-87030	New	8.5	HIGH		0.003	tanium:comply	Tanium addressed a path traversal vulnerability in Comply.
CVE-2026-71612	New	8.4	HIGH		0.001		Buffer Overflow vulnerability in GPAC c2dee3aff638cd96f9617ac5b17dc2868cd90ef3 allows an attacker to execute arbitrary code via the nhntdmx_process() function. Fixed in fac50e6a12ac27ffabdd5d3080b51afcc44ad8d6.
CVE-2026-71614	New	8.4	HIGH		0.001		An issue in GPAC c2dee3aff638cd96f9617ac5b17dc2868cd90ef3 allows an attacker to execute arbitrary code via the src/media_tools/dvb_mpe.c, descriptorTime_slice_fec_identifier() and gf_m2ts_ipdatagram_reader() components. Fixed in 0e4093392e1f847c90d20e031e893cd942fef938.
CVE-2026-82563	New	8.4	HIGH		0.001		An attacker could impersonate the camera and place themselves in a man-in-the-middle or device-emulation position. This permits manipulation of device status responses, observation of application requests, and potential triggering of firmware-update behavior.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86741	New	8.4	HIGH		0.002	snipeitapp:snipe-it	Snipe-IT versions before 8.7.0 fail to sanitize the category EULA text field before rendering it in checkout confirmation emails. Attackers with low-privilege permissions can inject markdown image syntax or raw HTML img tags pointing to local files or remote URLs, which the mail auto-embed library resolves server-side and returns as email attachments, exfiltrating sensitive ...
CVE-2026-87794	New	8.4	HIGH		0.002		bestzip versions 2.2.6 and 3.0.2 contain an argument injection vulnerability in the nativeZip function that allows attackers to inject arbitrary arguments to the Info-ZIP backend. Attackers can supply a malicious destination path combined with crafted source entries to execute arbitrary commands with Node.js process privileges. Fixed in 2.2.7 and 3.0.3.
CVE-2026-87811	New	8.4	HIGH		0.002		SiYuan before v3.8.2 inserts persisted notebook template paths into HTML input value attributes without proper attribute encoding. Attackers can craft malicious template paths that break out of the attribute context and execute JavaScript when a victim opens notebook configuration, enabling same-origin API requests and application state manipulation.
CVE-2026-87813	New	8.4	HIGH		0.003		SiYuan before v3.8.2 contains a stored cross-site scripting vulnerability in the Search Assets result list where asset filenames are interpolated into HTML without escaping. Authenticated attackers can craft asset filenames containing malicious markup that executes JavaScript in the victim's browser when searching assets, enabling same-origin API requests and application sta...
CVE-2026-87815	New	8.4	HIGH		0.003		SiYuan versions before v3.8.2 contain a path traversal vulnerability in the /api/riff/removeRiffDeck endpoint that fails to validate the deckID parameter. An authenticated administrator can supply path traversal sequences to delete arbitrary .deck and .cards files outside the workspace directory.
CVE-2026-86750	New	8.3	HIGH		0.002	snipeitapp:snipe-it	Snipe-IT versions <= 8.6.3 (fixed in 8.7.0) do not validate company assignment authorization before persisting user records via the REST API. In Api\UsersController::store() and ::update(), the user record is filled from the request and saved before the requested company_id / company_ids[] values are filtered against the actor's permitted companies (Company::getIdsForCurrent...
CVE-2026-86771	New	8.3	HIGH		0.002	snipeitapp:snipe-it	Snipe-IT versions before 8.7.0 fail to HTML-escape the employee_num field in the acceptance PDF generator, allowing attackers with users.edit permission to inject img tags into TCPDF's writeHTML() function. Attackers can craft a malicious employee_num value containing an img tag with an arbitrary HTTP(S) URL to trigger server-side requests to internal services, cloud metadat...
CVE-2026-87034	New	8.3	HIGH		0.002	tanium:comply	Tanium addressed a SQL injection vulnerability in Comply.
CVE-2026-87479	New	8.3	HIGH		0.003	google:chrome	Insufficient policy enforcement in Extensions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process and leveraged social engineering to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87480	New	8.3	HIGH		0.003	google:chrome	Use after free in Printing in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87481	New	8.3	HIGH		0.004	google:android, google:chrome	Incorrect authorization in WebView in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87487	New	8.3	HIGH		0.004	google:chrome	Missing authorization in FileSystem in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process and leveraged social engineering to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87506	New	8.3	HIGH		0.003	google:chrome	Privilege elevation in WebUI in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87510	New	8.3	HIGH		0.004	google:chrome	Improper input validation in FileAPI in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87524	New	8.3	HIGH		0.003	google:chrome, microsoft:windows	Use after free in Core in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87553	New	8.3	HIGH		0.004	google:chrome	Improper input validation in Sitelsolation in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87572	New	8.3	HIGH		0.003	google:chrome	Injection in DevTools in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87578	New	8.3	HIGH		0.001	google:chrome	Use after free in Receiver in Google Chrome prior to 153.0.8010.36 allowed an adjacent attacker to execute arbitrary code outside the sandbox via crafted network traffic. (Chromium security severity: High)
CVE-2026-87582	New	8.3	HIGH		0.004	google:chrome	Confused deputy in DataTransfer in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87604	New	8.3	HIGH		0.003	google:chrome	Out of bounds read in ANGLE in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87616	New	8.3	HIGH		0.004	google:chrome, microsoft:windows	Improper initialization in Views in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process and leveraged social engineering to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87618	New	8.3	HIGH		0.003	google:chrome, microsoft:windows	Incorrect reference resolution in Storage in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87628	New	8.3	HIGH		0.002	google:chrome	Use after free in Cast in Google Chrome prior to 153.0.8010.36 allowed an adjacent attacker to potentially execute arbitrary code outside the sandbox via crafted network traffic. (Chromium security severity: Critical)
CVE-2026-87639	New	8.3	HIGH		0.004	google:chrome	Use after free in WebPackaging in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87644	New	8.3	HIGH		0.003	google:chrome, microsoft:windows	Incorrect authorization in Views in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process and leveraged social engineering to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87648	New	8.3	HIGH		0.003	google:chrome, microsoft:windows	Use after free in ANGLE in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-12855	New	8.2	HIGH		0.001		Unvalidated memory boundary could result in arbitrary code execution. The vulnerability exists in the code developed specifically for HP projects.
CVE-2026-53938	New	8.2	HIGH		0.002		OpenIDC/cjose is a C library implementing the Javascript Object Signing and Encryption (JOSE). Prior to version 0.6.2.5, cjose's JWE decryption path for the AES Key Wrap key-management algorithms (`alg` = `A128KW`, `A192KW`, `A256KW`) does not validate the length of the attacker-supplied `encrypted_key` (JWE Encrypted Key) before unwrapping it into a fixed-size, heap-allocat...
CVE-2026-6485	New	8.2	HIGH		0.001		UEFI BIOS embedded Shell could be used to bypass Secure Boot via shell commands or startup scripts.
CVE-2026-78491	New	8.2	HIGH		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-18147	New	8.1	HIGH		0.003		A flaw was found in FreeIPA. An unauthenticated remote attacker could exploit a DOM Cross-Site Scripting (XSS) vulnerability in the FreeIPA/IdM Web UI password reset page. By enticing a victim to click a specially crafted link and complete a password reset, the attacker could inject and execute arbitrary JavaScript code. This allows the attacker to perform actions within the...
CVE-2026-65181	New	8.1	HIGH		0.006	apache:impala	Insufficient authorization of Data Source tables in Impala 2.7-4.5 allows a client with privileges to upload a file to remote storage and create a table to execute arbitrary Java code. Users are recommended to upgrade to version 4.5.2, which fixes this issue.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-71809	New	8.1	HIGH		0.004		Authentication Bypass via Hardcoded Master Verification Code vulnerability in Siam Ordering (siam-server) 1.0.0 allows remote unauthenticated attackers to log in as any user, merchant, or administrator.
CVE-2026-73334	New	8.1	HIGH		0.004	apache:parquet	Potential problem for users of the org.apache.parquet.crypto.keytools package in Apache Parquet, versions 1.12 to 1.18. This package enables users to encrypt Parquet files via an envelope encryption mechanism that wraps (encrypts) data keys via a Key Management Service (KMS). On the reader side, the KMS URL can be application-controlled or file-controlled. If the user does...
CVE-2026-76009	New	8.1	HIGH		0.005		The Next-Card Store to WooCommerce Migration plugin for WordPress is vulnerable to Authentication Bypass in all versions up to, and including, 3.9.8 via the `NCWM_Kitconnect::run()` function. This is due to the plugin registering the `/wp-json/next_cart/v1/migration` REST route with `permission_callback` set to `__return_true` and relying on a hardcoded fallback value of `__...`
CVE-2026-87016	New	8.1	HIGH		0.004	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.6.41 until 0.11.1, get_user_by_oauth_sub and get_user_by_scim_external_id in backend/open_webui/models/users.py used JSON contains matching that compiled to SQL LIKE substring matching on SQLite. An OAuth subject containing percent or underscore wildcard characters could resolve to a...
CVE-2026-87036	New	8.1	HIGH		0.002	tanium:comply	Tanium addressed an improper access controls vulnerability in Comply.
CVE-2026-87075	New	8.1	HIGH		0.002	tanium:comply	Tanium addressed an improper access controls vulnerability in Comply.
CVE-2026-87457	New	8.1	HIGH		0.001	google:chrome, microsoft:windows	Race condition in Updater in Google Chrome on on Windows prior to 153.0.8010.36 allowed a local attacker to execute arbitrary code outside the sandbox via a local program. (Chromium security severity: Medium)
CVE-2026-87467	New	8.1	HIGH		0.001	google:chrome, microsoft:windows	Race condition in Updater in Google Chrome on on Windows prior to 153.0.8010.36 allowed a local attacker to potentially execute arbitrary code outside the sandbox via a local program. (Chromium security severity: High)
CVE-2026-87471	New	8.1	HIGH		0.003	google:chrome	Incorrect authorization in ServiceWorker in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass site isolation via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87499	New	8.1	HIGH		0.002	google:chrome	Incorrect authorization in Network in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass site isolation via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87505	New	8.1	HIGH		0.002	google:chrome	Incorrect authorization in FileSystem in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass site isolation via a crafted PDF file. (Chromium security severity: Medium)
CVE-2026-87509	New	8.1	HIGH		0.001	google:chrome, microsoft:windows	Incorrect authorization in Updater in Google Chrome on on Windows prior to 153.0.8010.36 allowed a local attacker to execute arbitrary code outside the sandbox via a local program. (Chromium security severity: Low)
CVE-2026-87514	New	8.1	HIGH		0.001	google:chrome	Use after free in Views in Google Chrome prior to 153.0.8010.36 allowed a local attacker to execute arbitrary code outside the sandbox via a local program. (Chromium security severity: High)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87530	New	8.1	HIGH		0.001	google:chrome, microsoft:windows	Uncontrolled search path element in CredentialProvider in Google Chrome on on Windows prior to 153.0.8010.36 allowed a local attacker to execute arbitrary code outside the sandbox via a local program. (Chromium security severity: Medium)
CVE-2026-87533	New	8.1	HIGH		0.001	google:chrome	Use after free in DevTools in Google Chrome prior to 153.0.8010.36 allowed a local attacker to execute arbitrary code outside the sandbox via a local program. (Chromium security severity: Medium)
CVE-2026-87537	New	8.1	HIGH		0.003	google:chrome	Missing authorization in Extensions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially execute arbitrary code outside the sandbox via crafted network traffic. (Chromium security severity: Medium)
CVE-2026-87554	New	8.1	HIGH		0.001	google:chrome, microsoft:windows	Race condition in Chromoting in Google Chrome on on Windows prior to 153.0.8010.36 allowed a local attacker to execute arbitrary code outside the sandbox via a local program. (Chromium security severity: High)
CVE-2026-87606	New	8.1	HIGH		0.002	google:chrome	Missing authorization in Sitelsolation in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass site isolation via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87874	New	8.1	HIGH		0.004		A flaw was found in the memcached cache plugin of the community.general Ansible collection. Although its documentation states that records are stored in JSON format, the plugin performs no explicit serialization and relies on python-memcached, which pickles values on write and unpickles them on read. Because memcached is unauthenticated and cache keys are predictable, an att...
CVE-2026-21087	New	7.8	HIGH		0.001	samsung:android	Out-of-bounds write in libmdnie.so prior to SMR Sep-2026 Release 1 allows local attackers to execute arbitrary code with system server privilege.
CVE-2026-21088	New	7.8	HIGH		0.001	samsung:android	Improper input validation in loading a subtitle frame in libsubextractor.so prior to SMR Sep-2026 Release 1 allows local attackers to write out-of-bounds memory.
CVE-2026-21089	New	7.8	HIGH		0.001	samsung:android	Improper input validation in removing style tag in libsubextractor.so prior to SMR Sep-2026 Release 1 allows local attackers to write out-of-bounds memory.
CVE-2026-21090	New	7.8	HIGH		0.001	samsung:android	Out-of-bounds write in libsaviextractor.so prior to SMR Sep-2026 Release 1 allows local attackers to write out-of-bounds memory.
CVE-2026-21091	New	7.8	HIGH		0.001	samsung:android	Out-of-bounds write in libcodec2secevrdec.so prior to SMR Sep-2026 Release 1 allows local attackers to write out-of-bounds memory.
CVE-2026-71613	New	7.8	HIGH		0.001		Buffer Overflow vulnerability in GPAC c2dee3aff638cd96f9617ac5b17dc2868cd90ef3 allows an attacker to execute arbitrary code via the j2kdec_process() function. Fixed in 9a253a07fd3f6b48022bba74302bf3938dda859.
CVE-2026-78482	New	7.8	HIGH		0.019	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to command execution.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78484	New	7.8	HIGH		0.018	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to command execution.
CVE-2026-78493	New	7.8	HIGH		0.018	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to command execution.
CVE-2026-15140	New	7.7	HIGH		0.002		A privilege-escalation issue in the Portworx Operator when deployed on Red Hat OpenShift (OCP). Only under specific conditions during the initial provisioning of a Portworx storage cluster, a user holding only limited, namespace-scoped permissions could cause the operator to grant broader access than intended, potentially resulting in elevated privileges within the Kubernetes...
CVE-2026-15913	New	7.7	HIGH		0.004		In versions prior to 7.10.2 a path traversal vulnerability in the /attachRemoteFiles endpoint of Fortra's GoAnywhere MFT allows Web Users with both Secure Folders and Secure Mail permissions to escape their sandboxed home directory, achieving arbitrary file read.
CVE-2026-79637	New	7.7	HIGH		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-87084	New	7.7	HIGH		0.002	tanium:enforce	Tanium addressed a server-side request forgery vulnerability in Enforce.
CVE-2026-87996	New	7.7	HIGH		0.002	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.9.6 until 0.11.1, SafePlaywrightURLLoader in backend/open_webui/retrieval/web/utlis.py validated a user-controlled hostname in Python and then let the Playwright browser resolve it again in the sync and async request interceptors. An authenticated user controlling authoritative DNS c...
CVE-2026-15406	New	7.5	HIGH		0.007		The Eventin – Event Calendar, Event Registration, Tickets & Booking (AI Powered) plugin for WordPress is vulnerable to Local File Inclusion in all versions up to, and including, 4.1.22 via the 'event_layout' parameter parameter. This makes it possible for authenticated attackers, with custom-level access and above, to include and execute arbitrary .php files on the server, a...
CVE-2026-15667	New	7.5	HIGH		0.006		The Eventin – Event Calendar, Event Registration, Tickets & Booking (AI Powered) plugin for WordPress is vulnerable to Local File Inclusion in all versions up to, and including, 4.1.22 via the 'event_layout' parameter parameter. This makes it possible for authenticated attackers, with contributor-level access and above, to include and execute arbitrary .php files on the serv...
CVE-2026-16960	New	7.5	HIGH		0.004		The Loops & Logic WordPress plugin before 4.3.0 does not restrict its public template-data action to the data a visitor is permitted to see, allowing unauthenticated users to read arbitrary user records (including email addresses and roles) and arbitrary site options.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-22591	New	7.5	HIGH		0.003		eprosima Fast DDS is a C++ implementation of the DDS (Data Distribution Service) standard of the OMG (Object Management Group). Prior to versions 2.6.12, 2.14.6, 3.2.4, and 3.4.3, Fast DDS's implementation of SQL■based content filtering (DDSSQLFilter) allows any participant in a DDS domain to remotely crash other Fast DDS participants by sending a single crafted SEDP `DATA` ...
CVE-2026-52482	New	7.5	HIGH		0.003		An issue in SJRC F11 SJ-GPS-PRO firmware build 2019-09-17 allows a remote attacker to obtain sensitive information via the inetd service spawns /app/sh_for_telnet
CVE-2026-73786	New	7.5	HIGH		0.003		A vulnerability in the web-based management interface of CPPM could allow an unauthenticated remote attacker to conduct a Denial-of-Service (DoS) attack. Successful exploitation could allow an attacker to cause instability and degrade performance of the vulnerable CPPM server.
CVE-2026-74761	New	7.5	HIGH		0.004		Improper input validation in TopicRegion in Apache ActiveMQ, Apache ActiveMQ Broker, and Apache ActiveMQ All on all platforms. An authenticated client can spoof clientId when removing a durable topic subscription. This issue affects Apache ActiveMQ Broker: before 5.19.11, from 6.0.0 before 6.3.2; Apache ActiveMQ All: before 5.19.11, from 6.0.0 before 6.3.2; Apache Act...
CVE-2026-78490	New	7.5	HIGH		0.003	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Restriction of Excessive Authentication Attempts vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to client-side request forgery.
CVE-2026-79323	New	7.5	HIGH		0.003	mageplaza:magefan_blog	Information disclosure in the blogComments GraphQL query in Magefan Blog GraphQL for Magento 2 (magefan/module-blog-graph-ql) through 2.2.1 allows remote unauthenticated attackers to obtain blog commenter email addresses and internal customer and admin identifiers via a POST request to /graphql.
CVE-2026-79324	New	7.5	HIGH		0.003	mageplaza:gdpr	Missing authorization in the Address Delete controller in Mageplaza GDPR for Magento 2 (mageplaza/module-gdpr) through 4.2.9 allows remote unauthenticated attackers to delete any customer's saved address, and to erase all stored addresses by iterating the address id, via a GET request to /customer/address/delete/id/{id}. The controller extends the legacy Action class instead...
CVE-2026-79641	New	7.5	HIGH		0.007	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability. A low privileged attacker with remote access could potentially exploit this vulnerability, leading to elevation of privileges.
CVE-2026-79738	New	7.5	HIGH		0.003	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Use of Hard-coded Credentials vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to information exposure.
CVE-2026-79740	New	7.5	HIGH		0.003	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Use of Hard-coded Credentials vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to information exposure.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-79950	New	7.5	HIGH		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Use of Hard-coded Credentials vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to information exposure.
CVE-2026-80123	New	7.5	HIGH		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains a Server-Side Request Forgery (SSRF) vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to denial of service.
CVE-2026-80924	New	7.5	HIGH		0.002		In the Linux kernel, the following vulnerability has been resolved: crypto: krb5 - use kfree_sensitive() for derived key buffers crypto_krb5_prepare_encryption() and crypto_krb5_prepare_checksum() free the buffer holding the freshly derived keys with plain kfree(), leaving the key material behind in the freed slab object.
CVE-2026-87011	New	7.5	HIGH		0.004	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.9.0 until 0.11.1, the unauthenticated POST /oauth/backchannel-logout handler in backend/open_webui/utls/oauth.py fetched the OIDC discovery document and signing keys before validating a submitted logout token. Each request repeated uncached network fetches, and the signing-key looku...
CVE-2026-87431	New	7.5	HIGH		0.004	google:chrome	Missing authorization in Extensions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain sensitive information via a crafted Chrome extension. (Chromium security severity: Medium)
CVE-2026-87450	New	7.5	HIGH		0.003	google:chrome	Incorrect authorization in Permissions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to obtain sensitive information via a crafted Chrome extension. (Chromium security severity: Medium)
CVE-2026-87601	New	7.5	HIGH		0.002	google:chrome	Race condition in V8 in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87608	New	7.5	HIGH		0.002	google:chrome	Improper certificate validation in FedCM in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass web origin policy via crafted network traffic. (Chromium security severity: Low)
CVE-2026-87734	New	7.5	HIGH		0.003		An issue was discovered in the utcp package before 0.0.6 for OCaml. Out-of-order segment reassembly allows remote denial of service.
CVE-2026-87819	New	7.5	HIGH		0.003	gitpython_project:gitpython	GitPython before 3.1.60 contains a regular expression denial of service vulnerability in Actor.name_email_regex that processes commit author and committer fields. Attackers can craft a commit object with a malformed author field containing an unterminated angle bracket to cause quadratic backtracking, exhausting CPU resources for over two minutes per commit access.
CVE-2026-87824	New	7.5	HIGH		0.004		zstd-jni before 1.5.7-14 fails to validate the samples buffer capacity in Zstd.trainFromBufferDirect, allowing attackers to read past buffer boundaries by supplying oversized per-sample lengths. Attackers can trigger out-of-bounds memory access by providing crafted sample length arrays that cause the native implementation to walk past the buffer allocation, resulting in JVM ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87853	New	7.5	HIGH		0.003		A flaw was found in SSSD's IdP authentication provider. The eval_access_token_buf() function compares the OIDC subject identifier using strcmp() with the authenticated user's identifier length, performing a prefix comparison instead of an exact match. An attacker whose IdP identifier is a strict prefix of a target user's identifier can authenticate as the target user.
CVE-2026-78492	New	7.4	HIGH		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-78494	New	7.4	HIGH		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-79963	New	7.4	HIGH		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains a Download of Code Without Integrity Check vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to command execution.
CVE-2026-86746	New	7.4	HIGH		0.003	snipeitapp:snipe-it	Snipe-IT before 8.7.0 contains an authorization bypass vulnerability in Livewire components that enforce authorization only at the route level, not within component lifecycle methods. Attackers with a valid authenticated session can replay signed component snapshots via POST /livewire/update to invoke protected methods and escalate privileges, including creating OAuth client...
CVE-2026-87812	New	7.4	HIGH		0.002		SiYuan before v3.8.2 contains a stored cross-site scripting vulnerability in Bazaar package cards where the iconURL metadata is inserted directly into HTML img src attributes without escaping. Attackers can inject malicious URLs with event handlers that execute JavaScript in the authenticated SiYuan origin when users view Bazaar listings, enabling API requests and applicatio...
CVE-2026-49314	New	7.3	HIGH		0.001		OOB write vulnerability in the rendering and composition module. Impact: Successful exploitation of this vulnerability may affect availability.
CVE-2026-78485	New	7.3	HIGH		0.003	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to Unauthorized access
CVE-2026-79635	New	7.3	HIGH		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains a Server-Side Request Forgery (SSRF) vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-79692	New	7.3	HIGH		0.003	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an External Control of File Name or Path vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to filesystem access for attacker.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-79695	New	7.3	HIGH		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Handling of Highly Compressed Data (Data Amplification) vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to denial of service.
CVE-2026-80122	New	7.3	HIGH		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-86754	New	7.3	HIGH		0.002	snipeitapp:snipe-it	Snipe-IT before 8.7.0 fails to properly gate Laravel Passport's OAuth client management routes, allowing any authenticated user to register OAuth clients with attacker-controlled redirect URIs. Attackers can trick administrators into approving consent screens, then exchange authorization codes for bearer tokens inheriting full admin API permissions lasting up to 40 years.
CVE-2026-87814	New	7.3	HIGH		0.002		SiYuan before v3.8.2 contains a stored cross-site scripting vulnerability in the search asset preview feature that fails to escape indexed asset content before inserting it into the DOM using innerHTML. Attackers who can place crafted text assets in a workspace can execute JavaScript in the SiYuan origin when victims preview the assets, enabling authenticated API requests an...
CVE-2026-13359	New	7.2	HIGH		0.002		The Contact Form to DB by BestWebSoft – Messages Database Plugin For WordPress plugin for WordPress is vulnerable to Stored Cross-Site Scripting via cntctfrm_contact_dropdown Parameter in all versions up to, and including, 1.7.5 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in ...
CVE-2026-14989	New	7.2	HIGH		0.003		The Cookie Banner for GDPR / CCPA – WPLP Cookie Consent plugin for WordPress is vulnerable to Stored Cross-Site Scripting via the 'wpl_user_preference' parameter in all versions up to, and including, 4.4.1 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that will execute...
CVE-2026-17553	New	7.2	HIGH		0.004		The WP EasyCart plugin for WordPress is vulnerable to privilege escalation in versions up to, and including, 5.9.3. This is due to the ec_ajax_save_page_default_options() AJAX handler iterating over every \$_POST key and passing it directly into update_option() without any allowlist, while gating the handler only on 'manage_options' OR the plugin's custom 'wpec_manager' capab...
CVE-2026-23855	New	7.2	HIGH		0.009		Dell iDRAC9, 14G versions prior to 7.00.00.184, 15G/16G versions prior to 7.30.10.50, and Dell iDRAC10, 17G versions prior to 1.30.30.50, contain an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability. A high privileged attacker with remote access could potentially exploit this vulnerability, leading to command injection.
CVE-2026-73769	New	7.2	HIGH		0.01		A vulnerability in the web-based management interface of vulnerable CPPM systems could allow an authenticated remote attacker to achieve remote code execution. Successful exploitation could allow an attacker to execute arbitrary commands on the underlying operating system.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-73787	New	7.2	HIGH		0.008		A vulnerability in the CPPM web interface could allow an authenticated remote attacker to access directory information on a vulnerable system. Successful exploitation could allow an attacker to execute arbitrary commands on the underlying operating system.
CVE-2026-75927	New	7.2	HIGH		0.003		The PublishPress Capabilities – User Role Editor, Access Permissions, User Capabilities, Admin Menus plugin for WordPress is vulnerable to Privilege Escalation in all versions up to, and including, 2.50.0. This is due to the `addPluginCapabilities()` function unconditionally granting the Editor role all 15 `manage_capabilities_*` capabilities — including `manage_capabilities...
CVE-2026-79972	New	7.2	HIGH		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') vulnerability. A high privileged attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-83593	New	7.2	HIGH		0.003		The WPBot – AI ChatBot for Live Support, Lead Generation, AI Services plugin for WordPress is vulnerable to Stored Cross-Site Scripting via the 'conversation' parameter in all versions up to, and including, 8.7.3 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that will ...
CVE-2026-84293	New	7.2	HIGH		0.003		The Repeater Fields for Gravity Forms plugin for WordPress is vulnerable to Stored Cross-Site Scripting via Repeated Multi-Input Sub-Field Values in all versions up to, and including, 3.0.4 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that will execute whenever a user...
CVE-2026-87021	New	7.2	HIGH		0.004	tanium:comply	Tanium addressed an unauthorized code execution vulnerability in Comply.
CVE-2023-54396	New	7.1	HIGH		0.004		PocketMine-MP versions before 4.8.1 fail to validate dye color IDs in banner NBT data during deserialization. Attackers can provide invalid color values in inventory transactions or via commands to trigger undefined offset errors and crash the server.
CVE-2025-71417	New	7.1	HIGH		0.003		PocketMine-MP before 5.32.1 fails to validate uniqueness of pack UUIDs in ResourcePackClientResponsePacket STATUS_SEND_PACKS handling, allowing authenticated clients to trigger duplicate pack transmissions. Attackers can send multiple copies of valid pack UUIDs in a single packet to exhaust server memory and cause denial of service.
CVE-2026-21100	New	7.1	HIGH		0.001	samsung:android	Improper access control in SystemUI prior to SMR Sep-2026 Release 1 allows local attackers to launch arbitrary activity.
CVE-2026-49315	New	7.1	HIGH		0.001		DoS vulnerability in the input device module. Impact: Successful exploitation of this vulnerability may affect availability.
CVE-2026-50165	New	7.1	HIGH		0.002		alf.io is an open source ticket reservation system for conferences, trade shows, workshops, and meetups. An Improper Access Control issue in versions prior to 2.0-M5-2605 allows an organization owner to read system-level configuration secrets through organization/event scoped "single configuration" endpoints. The affected endpoints require organization or event ownership, bu...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-61915	New	7.1	HIGH		0.002	cyrus:imap	An issue was discovered in Cyrus IMAP before 3.12.4. There is a VPATCH BYPARAM double-free. An authenticated calendar user could crash a Cyrus CalDAV worker with a PATCH containing PATCH-ACTION="BYPARAM@..." against a resource with two or more properties of the matched kind. The memory holding the selector would be freed once on each iteration over the properties.
CVE-2026-79617	New	7.1	HIGH		0.001		Incorrect Permission Assignment for Critical Resource vulnerability in TÜBİTAK BİLGEM Software Technologies Research Institute Pardus LightDM Greeter allows Exploiting Incorrectly Configured Access Control Security Levels. This issue affects Pardus LightDM Greeter: before 0.4.15.
CVE-2026-81330	New	7.1	HIGH		0.001		The C6 ear camera transmits live video to the EarVision Android application over unencrypted UDP streams. The application manifest permits cleartext traffic, and captured network traffic contains reconstructable JPEG or WEBP video frames transmitted over UDP. An attacker within local wireless range may capture and reconstruct the live video stream without transport encryption.
CVE-2026-86204	New	7.1	HIGH		0.004		PocketMine-MP versions before 5.39.2 fail to limit JSON payload size in ModalFormResponsePacket handling, allowing authenticated players to cause denial of service. Attackers can send modal form response packets with massive JSON arrays to exhaust server memory and CPU resources, rendering the server unresponsive.
CVE-2026-86757	New	7.1	HIGH		0.002	snipeitapp:snipe-it	Snipe-IT before 8.7.0 fails to properly gate access to encrypted custom-field values in asset form templates for listbox, textarea, markdown-textarea, and date/datetime picker elements. Authenticated users with assets.edit, assets.checkin, assets.checkout, or assets.audit permissions can read plaintext encrypted custom field values by opening asset forms, bypassing the asset...
CVE-2026-86758	New	7.1	HIGH		0.002	snipeitapp:snipe-it	Snipe-IT before 8.7.0 fails to properly enforce the viewKeys authorization gate in CSV export and API index endpoints, allowing authenticated users with only licenses.view permission to access product keys. Attackers can download all license keys in bulk via CSV export or validate candidate keys through API response discrepancies without needing the viewKeys permission.
CVE-2026-86759	New	7.1	HIGH		0.002	snipeitapp:snipe-it	Snipe-IT versions before 8.7.0 fail to authorize the POST /hardware/history endpoint, allowing any authenticated user to reassign arbitrary assets and modify audit logs. Attackers can submit a CSV file to reassign assets across companies and inject fraudulent audit trail entries, compromising inventory integrity and accountability.
CVE-2026-86765	New	7.1	HIGH		0.002	snipeitapp:snipe-it	Snipe-IT versions before 8.7.0 fail to enforce checkout authorization when assignment fields are submitted to the asset update endpoint. Authenticated users with edit permission but explicitly denied checkout permission can reassign assets, bypass check-in procedures, and alter custody records by submitting assigned_user, assigned_asset, or assigned_location parameters to PA...
CVE-2026-86766	New	7.1	HIGH		0.002	snipeitapp:snipe-it	Snipe-IT versions up to and including 8.6.3 contain a race condition (TOCTOU) in the consumable checkout API endpoint (POST /api/v1/consumables/{consumable_id}/checkout). The requested quantity is validated against the number of remaining units before the database transaction begins, and the transaction then creates the checkout records without locking the consumable row or ...
CVE-2026-87072	New	7.1	HIGH		0.002	tanium:comply	Tanium addressed an improper access controls vulnerability in Comply.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87818	New	7.1	HIGH		0.002	gitpython_project:gitpython	GitPython 3.1.59 fails to restrict the --no-index option in the high-level diff API, allowing attackers to read arbitrary filesystem paths as repository operands. Attackers can combine --no-index with -l/--ignore-matching-lines to create a content-dependent Boolean oracle, repeatedly querying local files to recover single-line secrets through distinguishable success or error...
CVE-2026-87821	New	7.1	HIGH		0.003		Lara Dashboard through 1.3.1 contains a server-side request forgery vulnerability in the POST /api/admin/builder/markdown/fetch endpoint that allows any authenticated user to fetch arbitrary URLs and read the response body. Attackers can read internal HTTP services and cloud metadata including IAM credentials by supplying malicious URLs without host validation or redirect re...
CVE-2026-87998	New	7.1	HIGH		0.003	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.10.0 until 0.11.1, DELETE /api/v1/knowledge/{id}/delete in backend/open_webui/routers/knowledge.py authorized deletion against the knowledge base but then removed its administrator-owned external connection without a separate administrator check or a check for other dependent knowled...
CVE-2026-87999	New	7.1	HIGH		0.002	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. Prior to 0.11.1, POST /api/v1/retrieval/process/web and POST /api/v1/retrieval/process/web/search in backend/open_webui/retrieval/web/utlis.py treated Python's globally routable address classification as proof that a destination was external. An authenticated user could make an Azure-hosted...
CVE-2026-56711	New	7.0	HIGH		0.001		VLC media player versions 3.0.0 through 3.0.23 contain a memory-safety vulnerability reachable when processing crafted media. Exploitation requires user interaction and may result in application termination or code execution with the privileges of the VLC process.
CVE-2026-79636	New	7.0	HIGH		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Validation of Certificate with Host Mismatch vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-87088	New	7.0	HIGH		0.001	tanium:enforce	Tanium addressed an unauthorized code execution vulnerability in Enforce.
CVE-2026-87825	New	7.0	HIGH		0.001		zstd-jni before 1.5.7-14 contains a use-after-free vulnerability where streams and contexts hold a dictionary's shared lock only during the load call, allowing the dictionary to be closed while still referenced. Attackers can close a dictionary after associating it with a stream or context, causing subsequent read or write operations to access freed native memory, resulting ...
CVE-2026-87877	New	7.0	HIGH		0.002		zstd-jni versions before 1.5.7-14 fail to validate closed state in setDict, setLongMax, setLevel and setRefMultipleDDicts methods of stream classes. Attackers can call these methods on closed streams to write through freed native pointers, corrupting unrelated objects or crashing the JVM.
CVE-2025-71418	New	6.9	MEDI		0.004		PocketMine-MP versions before 5.25.2 fail to limit the explode() function in packet parsing, allowing malicious clients to waste server resources. Attackers can send crafted packets with excessive delimiters to consume CPU and memory through sign editing, JWT parsing, and command parsing endpoints.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-21098	New	6.9	MEDI		0.001		Improper access control in Link to Windows prior to SMR Sep-2026 Release 1 allows local attackers to establish a connection with the PC without proper user interaction.
CVE-2026-21107	New	6.9	MEDI		0.001		Out-of-bounds write in Samsung Notes prior to version 4.4.45.5 allows local attackers to write out-of-bounds memory.
CVE-2026-21108	New	6.9	MEDI		0.001		Improper export of android application components in Bixby Touch prior to version 4.3.01.17 allows local attackers to access sensitive information.
CVE-2026-21110	New	6.9	MEDI		0.001		Out-of-bounds write in libsavscmn.so prior to One UI 8.5 allows local attackers to execute arbitrary code.
CVE-2026-21111	New	6.9	MEDI		0.001		Out-of-bounds write in libsthmbc.so prior to One UI 8.5 allows local attackers to write out-of-bounds memory.
CVE-2026-83530	New	6.9	MEDI		0.002		A user could provide an expression whose string length is longer than the ParserExpressionSizeLimit() configured on the CEL environment, and a memory allocation would occur proportional to the size of the input before the limit would be checked / enforced.
CVE-2026-86547	New	6.9	MEDI		0.001		mrubyc through 4.0.0 contains a null pointer dereference vulnerability in the op_enter() handler in src/vm.c when processing untrusted bytecode. Attackers can craft malicious .mrb bytecode files with OP_ENTER instructions at the top level to crash the embedding application and cause denial of service.
CVE-2026-86748	New	6.9	MEDI		0.003	snipeitapp:snipe-it	Snipe-IT versions before 8.7.0 wipe the database before validating the uploaded backup archive in the restore endpoint. Superusers uploading corrupted or invalid zip files trigger permanent data loss with no recovery path or rollback mechanism.
CVE-2026-86777	New	6.9	MEDI		0.004		AlchemyCMS versions before 7.4.16 and 8.x before 8.3.6 fail to authorize access to the GET /api/nodes endpoint, allowing unauthenticated attackers to retrieve all navigation nodes. Attackers can access the endpoint without authentication to disclose restricted page names, URL paths, and internal URLs from all sites and languages.
CVE-2026-87747	New	6.9	MEDI		0.004		The Enterprise Cloud Database developed by Ragic has an Arbitrary File Read vulnerability. Privileged remote attackers can exploit Relative Path Traversal to download arbitrary system files.
CVE-2026-87810	New	6.9	MEDI		0.002		Siyuan before v3.8.2 contains an information disclosure vulnerability in the POST /api/search/fullTextSearchBlock endpoint that filters private blocks from results but returns unfiltered match counts. Unauthenticated publish-mode readers can submit arbitrary search terms to learn whether matching content exists in hidden or unpublished documents and determine the number of m...
CVE-2026-87820	New	6.9	MEDI		0.005		CyberPanel versions 2.4.3 through 2.4.5 expose unauthenticated AI Scanner debugging endpoints that disclose administrator usernames, API-key prefixes, scan identifiers, target domains, and account metadata. Unauthenticated attackers can enumerate panel administrators and recent scanner activity to inventory multi-tenant installations and facilitate follow-on attacks.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2025-15690	New	6.8	MEDI		0.003		The Content Mask WordPress plugin before 1.8.5.6 does not properly sanitise and escape content submitted with a post before outputting it in the pages it generates, allowing users with a role as low as Contributor to perform Stored Cross-Site Scripting attacks against any user viewing or previewing the affected page. The Content Mask WordPress plugin before 1.8.5.6's option ...
CVE-2025-46808	New	6.8	MEDI		0.002		An Insertion of Sensitive Information into Log File vulnerability in SUSE neuvector manager exposes sensitive information into the manager container's log This issue affects neuvector: before 5.4.5.
CVE-2026-83541	New	6.8	MEDI		0.002		The Sina Extension for Elementor WordPress plugin before 3.10.4 does not properly escape a Table widget setting before outputting it within an HTML attribute, which could allow users with the Contributor role and above to perform Stored Cross-Site Scripting attacks.
CVE-2026-87015	New	6.8	MEDI		0.003	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.6.27 until 0.11.1, backend/open_webui/utlis/tools.py captured a cookie jar from the enclosing connection loop instead of binding it to each external tool callable. When multiple tool servers were attached and a session or system OAuth connection was processed last, a request to a dif...
CVE-2026-87872	New	6.8	MEDI		0.001		A flaw was found in the OCAPI modules (ocapi_command, ocapi_info) of the community.general Ansible collection. The shared OCAPI request helper disables TLS certificate validation on every request and the modules expose no parameter to re-enable it, while sending HTTP Basic-Auth credentials to an https endpoint. An attacker positioned on the network path between the Ansible c...
CVE-2026-21085	New	6.7	MEDI		0.001	samsung:android	Out-of-bounds write in Keymaster trustlet prior to SMR Sep-2026 Release 1 allows local privileged attackers to write out-of-bounds memory.
CVE-2026-21093	New	6.7	MEDI		0.001	samsung:android	Stack-based buffer overflow in PROCA trustlet prior to SMR Sep-2026 Release 1 allows local privileged attackers to write out-of-bounds memory.
CVE-2026-21097	New	6.7	MEDI		0.001	samsung:android	Improper authentication in ActivityTaskManagerService prior to SMR Sep-2026 Release 1 allows local privileged attackers to launch arbitrary activity.
CVE-2026-21101	New	6.7	MEDI		0.001	samsung:android	Improper input validation in DualDAR driver prior to SMR Sep-2026 Release 1 allows local privileged attackers to potentially execute arbitrary code with root privilege.
CVE-2026-21102	New	6.7	MEDI		0.001	samsung:android	Use after free in DualDAR prior to SMR Sep-2026 Release 1 allows local privileged attackers to execute arbitrary code with root privilege.
CVE-2026-21104	New	6.7	MEDI		0.001	samsung:android	Heap-based buffer overflow in KnoxVault trustlet prior to SMR Sep-2026 Release 1 allows local privileged attackers to execute arbitrary code.
CVE-2026-70425	New	6.7	MEDI		0.004	dell:powerscale_onefs	Dell PowerScale OneFS, Versions 9.5.0.0 through 9.7.1.0, Versions 9.8.0.0 through 9.10.1.0, and Versions 9.11.0.0 through 9.14.0.1, contain a command injection vulnerability. An admin privileged local attacker could potentially exploit this vulnerability, leading to elevation of privileges to root, impacting confidentiality, integrity, and availability.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-11363	New	6.6	MEDI		0.007		The Ninja Forms – The Contact Form Builder That Grows With You plugin for WordPress is vulnerable to PHP Object Injection in all versions up to, and including, 3.14.6 via deserialization of untrusted input . This makes it possible for authenticated attackers, with administrator-level access and above, to inject a PHP Object. No known POP chain is present in the vulnerable so...
CVE-2026-14505	New	6.6	MEDI		0.003		Tanium addressed a path traversal vulnerability in Tanium Data Service.
CVE-2026-19201	New	6.6	MEDI		0.003		An uncontrolled recursion vulnerability in the Windows SIPA event log parser of Google go-attestation versions up to and including 0.6.1 allows an attacker to cause a denial of service (DoS). The (*WinEvents).readELAMAggregation function recurses for every nested elamAggregation sub-event without enforcing a maximum recursion depth limit, while the size guard is bypassed on ...
CVE-2023-54392	New	6.5	MEDI		0.004		PocketMine-MP versions >= 4.20.0 before 4.22.3 (and before 5.2.1 in the 5.x branch) fail to validate NBT tag types in BlockActorDataPacket. A player can crash the server by sending a packet containing sign NBT data with an incorrect tag type, triggering an unhandled UnexpectedTagTypeException that terminates the server process.
CVE-2024-58380	New	6.5	MEDI		0.004		PocketMine-MP versions before 5.11.2 contain a denial of service vulnerability in BookEditPacket handling that crashes the server when an invalid inventory slot value is provided. Attackers can send a crafted BookEditPacket with an inventory slot greater than 35 to trigger an unhandled exception and crash the server.
CVE-2026-19778	New	6.5	MEDI		0.003		The WPMR Google Feed Manager for WooCommerce – Sell on Google Merchant Center & Shopping plugin for WordPress is vulnerable to time-based SQL Injection via the 'feed' parameter in all versions up to, and including, 2.23.7 due to insufficient escaping on the user supplied parameter and lack of sufficient preparation on the existing SQL query. This makes it possible for authen...
CVE-2026-19855	New	6.5	MEDI		0.002		The CleanTalk WordPress plugin before 6.87 does not prevent unauthenticated, user-supplied comment content from being passed to WordPress's shortcode engine, allowing any visitor to have arbitrary shortcodes registered on the site executed server-side and rendered to every subsequent visitor of the page.
CVE-2026-38998	New	6.5	MEDI		0.002		A use-after-free in the SocketDescriptor::tcpReadHandler1 function (liveMedia/RTPInterface.cpp) of LIVE555 Streaming Media (version 2026.02.26) allows attackers to cause a Denial of Service (DoS) via sending a series of crafted RTSP and HTTP requests to the server.
CVE-2026-61908	New	6.5	MEDI		0.002	cyrus:imap	An issue was discovered in Cyrus IMAP before 3.12.4. A JMAP email-header blob ID can reference an out-of-bounds index. An authenticated user could attempt to download a crafted JMAP blob ID of the form H<emailid>-<index>, which could read past the end of the internal blob_headers array during download, exposing adjacent heap memory.
CVE-2026-73788	New	6.5	MEDI		0.002		A vulnerability in the ClearPass OnGuard agent could allow an authenticated remote attacker to elevate their own privileges on a vulnerable ClearPass OnGuard deployment. Successful exploitation could allow an attacker to obtain root privileges, leading to potentially unauthorized operation of the vulnerable system.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75861	New	6.5	MEDI		0.002		The Ultimate Gift Cards for WooCommerce WordPress plugin before 3.2.10 does not verify that the user redeeming a gift card is its intended recipient, allowing any authenticated user, such as a subscriber, to redeem gift cards belonging to other users, zeroing their balance and crediting the value to themselves. In 3.2.9 an ownership check was added on one of the two affected...
CVE-2026-78481	New	6.5	MEDI		0.003	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Use of Hard-coded Cryptographic Key vulnerability. A low privileged attacker with remote access could potentially exploit this vulnerability, leading to protection mechanism bypass.
CVE-2026-79513	New	6.5	MEDI		0.002	gpac:gpac	A divide-by-zero vulnerability in the gf_dash_get_timeline_duration function (src/media_tools/dash_client.c) of GPAC v26.07.0 allows attackers to cause a Denial of Service (DoS) via a crafted MPD SegmentTimeline. Fixed in 2fd5a06ab226767900fd86edb5a1e8bfc1010640.
CVE-2026-79514	New	6.5	MEDI		0.003	gpac:gpac	An out-of-bounds read in the gf_dm_data_received function (downloader.c) of GPAC v26.07.0 allows attackers to cause a Denial of Service (DoS) via sending a crafted HTTP request. Fixed in 2fd5a06ab226767900fd86edb5a1e8bfc1010640.
CVE-2026-79522	New	6.5	MEDI		0.003	gpac:gpac	An out-of-bounds read in the gf_dm_get_chunk_data function (src/utills/downloader.c) of GPAC v26.07.0 allows attackers to cause a Denial of Service (DoS) via sending a crafted HTTP request. Fixed in 2fd5a06ab226767900fd86edb5a1e8bfc1010640.
CVE-2026-79728	New	6.5	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains a Relative Path Traversal vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to filesystem access for attacker.
CVE-2026-80177	New	6.5	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') vulnerability. A low privileged attacker with remote access could potentially exploit this vulnerability, leading to script injection.
CVE-2026-85117	New	6.5	MEDI		0.002		The Contact Form 7 Captcha WordPress plugin before 0.1.9 runs the shortcode parser over the whole rendered Contact Form 7 form, including the values a visitor submitted, allowing unauthenticated users to execute arbitrary shortcodes registered on the site.
CVE-2026-86739	New	6.5	MEDI		0.003	snipeitapp:snipe-it	Snipe-IT 8.6.3 and earlier do not check the return value of Storage::put() when writing the signature PNG and the generated acceptance PDF in Account\AcceptanceController::store(). On filesystem drivers that return false instead of throwing on a write failure (for example the local disk with restrictive permissions, S3 with expired credentials, or a storage backend that is o...
CVE-2026-86764	New	6.5	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT through 8.6.4 (fixed in 8.7.0) does not enforce the components.view permission on the authenticated endpoint GET /api/v1/hardware/<asset-id>/assigned/components. The endpoint authorizes only assets.view on the parent asset before returning linked component details; the components.view check is applied only to the response's available_actions.view flag and not to the...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87014	New	6.5	MEDI		0.003	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.9.0 until 0.11.1, role synchronization in backend/open_webui/routers/auths.py and backend/open_webui/utis/oauth.py updated an administrator's database role without invalidating the user record cached by backend/open_webui/socket/main.py. An administrator demoted through a trusted ro...
CVE-2026-87073	New	6.5	MEDI		0.002	tanium:comply	Tanium addressed an improper access controls vulnerability in Comply.
CVE-2026-87429	New	6.5	MEDI		0.003	google:chrome	Missing authorization in ServiceWorker in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87436	New	6.5	MEDI		0.003	google:chrome	Incomplete cleanup in Browser in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass web origin policy via a crafted Chrome extension. (Chromium security severity: Medium)
CVE-2026-87437	New	6.5	MEDI		0.003	google:chrome	Information leak in Frames in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to leak sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87441	New	6.5	MEDI		0.003	google:chrome	Missing authorization in Downloads in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted Chrome extension. (Chromium security severity: Medium)
CVE-2026-87443	New	6.5	MEDI		0.003	google:chrome	Missing authorization in Actor in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain sensitive information via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87446	New	6.5	MEDI		0.003	google:chrome	Incomplete cleanup in Extensions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted Chrome extension. (Chromium security severity: Medium)
CVE-2026-87447	New	6.5	MEDI		0.003	google:chrome	Incorrect authorization in Network in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass web origin policy via a crafted Chrome extension. (Chromium security severity: High)
CVE-2026-87454	New	6.5	MEDI		0.002	google:chrome, microsoft:windows	Information leak in Enterprise in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to obtain sensitive information via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87459	New	6.5	MEDI		0.002	google:chrome	Observable discrepancy in Select in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87468	New	6.5	MEDI		0.002	google:chrome	Incorrect authorization in Isolated in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass site isolation via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87473	New	6.5	MEDI		0.003	google:chrome	Incorrect authorization in FileHandling in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Low)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87475	New	6.5	MEDI		0.002	google:chrome	Missing authorization in Omnibox in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions into a privileged page via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87476	New	6.5	MEDI		0.003	google:chrome	Incorrect authorization in Loader in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain sensitive information via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87477	New	6.5	MEDI		0.003	google:chrome	Information leak in Core in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to leak sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87478	New	6.5	MEDI		0.004	google:chrome	Observable discrepancy in Autofill in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain sensitive information via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87483	New	6.5	MEDI		0.002	google:android, google:chrome	Incorrect authorization in Browser in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87490	New	6.5	MEDI		0.002	google:chrome	Information leak in Transactions Platform in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87493	New	6.5	MEDI		0.002	google:chrome	Missing authorization in FileSystem in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87503	New	6.5	MEDI		0.003	google:android, google:chrome	Inappropriate implementation in Downloads in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87513	New	6.5	MEDI		0.003	google:chrome	Missing authorization in ControlledFrame in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87515	New	6.5	MEDI		0.002	google:chrome	Incorrect authorization in FileAPI in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87519	New	6.5	MEDI		0.003	google:chrome	Incorrect authorization in Safebrowsing in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87522	New	6.5	MEDI		0.003	google:android, google:chrome	Missing authorization in WebView in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to potentially bypass system access restrictions via crafted network traffic. (Chromium security severity: Low)
CVE-2026-87532	New	6.5	MEDI		0.002	google:chrome	Improper state validation in Safebrowsing in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87535	New	6.5	MEDI		0.003	apple:macos, google:chrome	Information loss or omission in Safebrowsing in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87541	New	6.5	MEDI		0.002	google:chrome	Information leak in Navigation in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass site isolation via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87545	New	6.5	MEDI		0.002	apple:iphone_os, google:chrome	Information leak in Mobile in Google Chrome on on iOS prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to leak sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87549	New	6.5	MEDI		0.003	google:chrome	Incomplete cleanup in Downloads in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87565	New	6.5	MEDI		0.003	google:android, google:chrome	Information leak in Passwords in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to leak sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87580	New	6.5	MEDI		0.002	google:chrome	Incorrect authorization in WebAppInstalls in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process and leveraged social engineering to bypass site isolation via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87584	New	6.5	MEDI		0.002	google:chrome	Incorrect authorization in WebUI in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions into a privileged page via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87589	New	6.5	MEDI		0.002	google:chrome	Incorrect authorization in SiteIsolation in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87591	New	6.5	MEDI		0.002	google:chrome	Incorrect authorization in Extensions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted Chrome extension. (Chromium security severity: Medium)
CVE-2026-87593	New	6.5	MEDI		0.002	google:chrome	Information leak in Editing in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87600	New	6.5	MEDI		0.003	google:android, google:chrome	Improper input validation in Safebrowsing in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87603	New	6.5	MEDI		0.002	google:chrome	Missing authorization in FileSystem in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87610	New	6.5	MEDI		0.002	google:chrome	Incorrect authorization in Omnibox in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions into a privileged page via a crafted HTML page. (Chromium security severity: Medium)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87620	New	6.5	MEDI		0.002	google:chrome	Observable discrepancy in SVG in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87623	New	6.5	MEDI		0.002	google:chrome	Observable discrepancy in DOM in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to obtain sensitive information via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87626	New	6.5	MEDI		0.002	google:chrome	Incorrect authorization in DeviceBoundSessionCredentials in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass web origin policy via crafted network traffic. (Chromium security severity: Medium)
CVE-2026-87627	New	6.5	MEDI		0.002	apple:macos, google:chrome	Interpretation conflict in Safebrowsing in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted file. (Chromium security severity: Low)
CVE-2026-87629	New	6.5	MEDI		0.002	google:chrome	Incorrect authorization in Sources in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to leak sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87631	New	6.5	MEDI		0.002	google:chrome	Missing authorization in DOM in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially leak sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87724	New	6.5	MEDI		0.003		Tor before 0.4.9.12 interprets the CC_RESPONSE extension even when CC_REQUEST was not sent, which allows remote attackers to cause a denial of service (crash) because of corrupted congestion-control state. This is TROVE-2026-032.
CVE-2026-87809	New	6.5	MEDI		0.002		Siyuan before v3.8.2 fails to apply publish-access filtering to embedded blocks before rendering in the /api/export/preview and /api/lute/copyStdMarkdown endpoints. Attackers with reader access can retrieve the full rendered content of private, hidden, or publish-disabled blocks by accessing public documents containing embed queries that select those blocks.
CVE-2026-88000	New	6.5	MEDI		0.003	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.10.0 until 0.11.1, DELETE /api/v1/chats/{id}/messages/{message_id} used the chat-history deletion helper in backend/open_webui/models/chats.py to follow childrenIds without recording visited message identifiers. An authenticated user could store a cyclic chat tree and delete a messag...
CVE-2026-88002	New	6.5	MEDI		0.003	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.5.0 until 0.11.1, the message-chain reconstruction helper in backend/open_webui/utlis/misc.py advanced through a chat history by map key but tracked visited entries using each message body's optional id field. An authenticated user could store id-less messages in a parent cycle and t...
CVE-2026-13709	New	6.4	MEDI		0.002		The Graphina – Charts and Graphs For Elementor plugin for WordPress is vulnerable to Stored Cross-Site Scripting via 'iq_tree_tree_chart_template' Widget Setting in all versions up to, and including, 3.1.11 due to insufficient input sanitization and output escaping. This makes it possible for authenticated attackers, with contributor-level access and above, to inject arbitra...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-17149	New	6.4	MEDI		0.002		The Points Management System For Gamification, Ranks, Badges, and Loyalty Rewards Program – myCred plugin for WordPress is vulnerable to Stored Cross-Site Scripting via 'wrapper' Shortcode Attribute in all versions up to, and including, 3.2.4 due to insufficient input sanitization and output escaping. This makes it possible for authenticated attackers, with contributor-level...
CVE-2026-19945	New	6.4	MEDI		0.002		The WP Crowdfunding plugin for WordPress is vulnerable to Stored Cross-Site Scripting via the 'first_name' parameter in all versions up to, and including, 2.2.1 due to insufficient input sanitization and output escaping. This makes it possible for authenticated attackers, with subscriber-level access and above, to inject arbitrary web scripts in pages that will execute where...
CVE-2026-75966	New	6.4	MEDI		0.003		The Podlove Podcast Publisher plugin for WordPress is vulnerable to Stored Cross-Site Scripting via 'episode_contributor[...][comment]' Parameter in all versions up to, and including, 4.5.5 due to insufficient input sanitization and output escaping. This makes it possible for authenticated attackers, with contributor-level access and above, to inject arbitrary web scripts...
CVE-2026-77186	New	6.4	MEDI		0.002		The My Calendar – Accessible Event Manager plugin for WordPress is vulnerable to Stored Cross-Site Scripting via 'fallback' Shortcode Attribute in all versions up to, and including, 3.8.3 due to insufficient input sanitization and output escaping. This makes it possible for authenticated attackers, with contributor-level access and above, to inject arbitrary web scripts in p...
CVE-2026-77187	New	6.4	MEDI		0.002		The My Calendar – Accessible Event Manager plugin for WordPress is vulnerable to Stored Cross-Site Scripting via 'before' and 'after' Shortcode Attributes in all versions up to, and including, 3.8.3 due to insufficient input sanitization and output escaping. This makes it possible for authenticated attackers, with contributor-level access and above, to inject arbitrary web s...
CVE-2026-79974	New	6.4	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Authentication vulnerability. A low privileged attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-79973	New	6.3	MEDI		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Unsynchronized Access to Shared Data in a Multithreaded Context vulnerability. A low privileged attacker with remote access could potentially exploit this vulnerability, leading to denial of service.
CVE-2026-86203	New	6.3	MEDI		0.003		PocketMine-MP versions before 5.39.2 fail to validate entity despawn state when processing attack packets from clients. Attackers can exploit a race condition by attacking a disconnecting player to trigger multiple death handlers, causing inventory items and experience to drop multiple times for duplication.
CVE-2026-86749	New	6.3	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT versions <= 8.6.3 (fixed in 8.7.0) do not check the return value of storage write operations in ImageUploadRequest::handleImages(). Because Laravel's default disk mode does not throw on failure, a silently failed Storage::disk('public')->put(...) call still caused the application to delete the previous image via deleteExistingImage() and to reassign and persist the ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86774	New	6.3	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT versions before 8.7.0 contain a broken access control vulnerability in AssetModelPolicy where the files() method cascades from assets.files permission, allowing authenticated users to upload and delete file attachments on Asset Model records without the required models.files permission. Attackers with only assets.files permission can mutate shared model file attachm...
CVE-2026-87047	New	6.3	MEDI		0.002	tanium:comply	Tanium addressed an improper access controls vulnerability in Comply.
CVE-2026-41987	New	6.2	MEDI		0.001		Permission control vulnerability in the app management module. Impact: Successful exploitation of this vulnerability may affect availability.
CVE-2026-49311	New	6.2	MEDI		0.001		Permission control vulnerability in the event notification module.Impact: Successful exploitation of this vulnerability may affect availability.
CVE-2026-53937	New	6.2	MEDI		0.002		MCP Kotlin SDK is the Kotlin Multiplatform software development kit for the Model Context Protocol. In versions 0.7.0 through 0.12.0, `ReadBuffer.append` in `kotlin-sdk-core/src/commonMain/kotlin/io/modelcontextprotocol/kotlin/sdk/shared/ReadBuffer.kt` writes every chunk of bytes received from the stdio transport into a `kotlinx.io.Buffer` with no size cap. Frames are extrac...
CVE-2026-71616	New	6.2	MEDI		0.001		An issue in GPAC c2dee3aff638cd96f9617ac5b17dc2868cd90ef3 allows an attacker to cause a denial of service via the function gf_route_media_complete_object(). Fixed in 3c4e6c5b3e0c6fa9b16d55599701a08354538fab.
CVE-2026-87732	New	6.2	MEDI		0.001		An issue was discovered in the mirage-crypto package before 2.2.0 for OCaml. The AES.GCM.authenticate_decrypt_into and Chacha20.authenticate_decrypt_into functions write the decrypted plaintext into a caller-provided buffer and only then compares the tag. On a forged tag, the functions returns false, but the destination buffer already holds the full plaintext.
CVE-2026-87733	New	6.2	MEDI		0.001		An issue was discovered in the mirage-crypto-ec function before 2.2.0 for OCaml. The ECDSA functions {P256,P384,P521}.Dsa.pub_of_octets accept 0x00, the encoding of the point at infinity, as a public key. With that public key, signatures can be forged without a private key.
CVE-2026-19797	New	6.1	MEDI		0.002		The User Access Manager plugin for WordPress is vulnerable to Reflected Cross-Site Scripting via the 'tab_group_section' parameter in all versions up to, and including, 2.3.18 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that execute if they can successfully trick a u...
CVE-2026-21103	New	6.1	MEDI		0.002	samsung:android	Path traversal in GalaxyDiagnostics prior to SMR Sep-2026 Release 1 allows physical attackers to access files with system privilege.
CVE-2026-75307	New	6.1	MEDI		0.001		zhitan-ems 1.0.0 is vulnerable to Cross Site Scripting (XSS) via SVG file upload through the /equipmentFile/upload endpoint.
CVE-2026-75308	New	6.1	MEDI		0.001		yshopmall <=3.3 is vulnerable to Cross Site Scripting (XSS). The file upload endpoint /api/upload of the system lacks file type validation. Attackers can upload files of any type, including HTML, JSP, and other executable files.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-7804	New	6.1	MEDI		0.003		The Product Filter for WooCommerce by WBW plugin for WordPress is vulnerable to Reflected Cross-Site Scripting via the 'wpf_fid' parameter in all versions up to, and including, 3.4.2 due to insufficient input sanitization and output escaping. This makes it possible for unauthenticated attackers to inject arbitrary web scripts in pages that execute if they can successfully tr...
CVE-2026-78377	New	6.1	MEDI		0.002		URL redirection to untrusted site ('open redirect') vulnerability in Yordam Informatics Technology Consulting, Training, and Electronic Systems Industry and Trade Inc. Library Information and Document Automation Program allows Phishing. This issue affects Library Information and Document Automation Program: from v22.1 before v22.2.
CVE-2026-87640	New	6.1	MEDI		0.002	google:android, google:chrome	Out of bounds read in WebView in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to read memory outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-21105	New	5.9	MEDI		0.001		Improper access control in Collection prior to version 1.0.1.14 in Android 15 and 2.0.02.7 in Android 16 allows local attackers to access sensitive information.
CVE-2026-78483	New	5.9	MEDI		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to protection mechanism bypass.
CVE-2026-78489	New	5.9	MEDI		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to protection mechanism bypass.
CVE-2026-79962	New	5.9	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains a Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to denial of service.
CVE-2026-79968	New	5.9	MEDI		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains a Time-of-check Time-of-use (TOCTOU) Race Condition vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to denial of service.
CVE-2026-79969	New	5.9	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains a Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to denial of service.
CVE-2026-80341	New	5.9	MEDI		0.001		The Payment Plugins for PayPal WooCommerce WordPress plugin before 2.0.26 does not verify that a stored payment method belongs to the user attaching it, allowing any authenticated user, such as a subscriber, to bind another customer's stored card to their own account and then charge or delete it. Exploitation requires the attacker to already know the payment provider's ident...
CVE-2026-81646	New	5.9	MEDI		0.001		Out-of-bounds read vulnerability in the graphics module. Impact: Successful exploitation of this vulnerability may affect availability.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87482	New	5.9	MEDI		0.002	apple:iphone_os, google:chrome	Cleartext transmission of sensitive data in HttpsUpgrades in Google Chrome on on iOS prior to 153.0.8010.36 allowed a remote attacker to leak sensitive information via crafted network traffic. (Chromium security severity: Medium)
CVE-2026-87590	New	5.9	MEDI		0.003	google:chrome	Improper input validation in Passwords in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially leak sensitive information via crafted network traffic. (Chromium security severity: Medium)
CVE-2026-87737	New	5.9	MEDI		0.002		An issue was discovered in the mirage-crypto-ec package before 2.4.0 for OCaml. There is a timing side channel for NIST elliptic-curve scalar multiplication: the time required for a lookup can depend on a secret.
CVE-2026-57825	New	5.7	MEDI		0.003		In the opam package before 2.5.2 for OCaml, the sandbox protection mechanism can be bypassed because symlinks are mishandled during use of .install files.
CVE-2026-85788	New	5.7	MEDI		0.001		Incomplete list of disallowed inputs in the mutable SQL detector component in Amazon awslabs mysql-mcp-server might allow context-dependent actors to bypass the read-only enforcement gate and reach file-read and file-write SQL sinks via SQL inline comments that the regex engine does not treat as whitespace. To remediate this issue, users should upgrade to version 1.0.23.
CVE-2026-79730	New	5.6	MEDI		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains a Time-of-check Time-of-use (TOCTOU) Race Condition vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to denial of service.
CVE-2026-79967	New	5.6	MEDI		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to protection mechanism bypass.
CVE-2026-79970	New	5.6	MEDI		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Verification of Cryptographic Signature vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to protection mechanism bypass.
CVE-2025-51619	New	5.5	MEDI		0.001		A vulnerability in the Thesycon DPC Latency Checker driver (dpc.sys) thru 1.4.0 allows local unprivileged users to cause a denial-of-service (BSOD) condition on Windows systems. The driver exposes an IOCTL interface (0x81772008) that accepts user-controlled input without validating pointers before passing them to kernel APIs. Specifically, it dereferences a user-supplied poi...
CVE-2026-21099	New	5.5	MEDI		0.001	samsung:android	Improper access control in SettingsProvider prior to SMR Sep-2026 Release 1 allows local attackers to access sensitive information.
CVE-2026-39020	New	5.5	MEDI		0.001		An issue in WIngs3D v.2.4.1 allows a local attacker to cause a denial of service via a crafted Wavefront OBJ file
CVE-2026-49313	New	5.5	MEDI		0.001		Permission control vulnerability in the app lock module. Impact: Successful exploitation of this vulnerability may affect service confidentiality.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-79694	New	5.5	MEDI		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Insertion of Sensitive Information Into Debugging Code vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to information exposure.
CVE-2026-79945	New	5.5	MEDI		0.017	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to command execution.
CVE-2026-79947	New	5.5	MEDI		0.008	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to script injection.
CVE-2026-80124	New	5.5	MEDI		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Insertion of Sensitive Information into Log File vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to information exposure.
CVE-2026-87552	New	5.5	MEDI		0.001	google:android, google:chrome	Missing authorization in TrustedWebActivities in Google Chrome on on Android prior to 153.0.8010.36 allowed a local attacker to obtain sensitive information via a co-installed app. (Chromium security severity: High)
CVE-2026-87921	New	5.5	MEDI		0.003		A vulnerability was identified in Rizwan17 inventory-management-system up to bfe78a330d01bb26b9daec5dc9ecd5c77900e03f. Affected is the function update_record of the file includes/manage.php. The manipulation of the argument update_category/cid/update_brand/update_product leads to sql injection. The attack is possible to be carried out remotely. The exploit is publicly availa...
CVE-2026-87922	New	5.5	MEDI		0.004		A security flaw has been discovered in Rizwan17 inventory-management-system up to bfe78a330d01bb26b9daec5dc9ecd5c77900e03f. Affected by this vulnerability is the function DBOperation.addCategory of the file includes/process.php of the component AJAX Backend. The manipulation of the argument userid results in missing authentication. The attack may be performed from remote. Th...
CVE-2026-87924	New	5.5	MEDI		0.004		A security vulnerability has been detected in Rizwan17 inventory-management-system up to bfe78a330d01bb26b9daec5dc9ecd5c77900e03f. This affects an unknown part of the file includes/invoice_bill.php of the component Invoice Generation. Such manipulation of the argument order_date/invoice_no leads to missing authentication. It is possible to launch the attack remotely. The exp...
CVE-2026-11821	New	5.4	MEDI		0.002		The Eventin – Event Calendar, Event Registration, Tickets & Booking (AI Powered) plugin for WordPress is vulnerable to authorization bypass in all versions up to, and including, 4.1.17. This is due to the plugin not properly verifying that a user is authorized to perform an action. This makes it possible for authenticated attackers, with subscriber-level access and above, to...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-15460	New	5.4	MEDI		0.002		The Bluetooth Classic (BR/EDR) L2CAP receive handler <code>bt_l2cap_br_rcv()</code> in <code>subsys/bluetooth/host/classic/l2cap_br.c</code> dispatched inbound data PDUs based only on the destination channel ID, without checking that the target channel had reached the <code>BT_L2CAP_CONNECTED</code> state. A dynamic channel is assigned its RX CID and added to the connection's channel list while still in <code>BT_L2CAP...</code>
CVE-2026-40635	New	5.4	MEDI		0.002	dell:powerscale_onefs	Dell PowerScale OneFS versions 9.12.0.0 through 9.13.1.0 contain an Insecure Temporary File vulnerability. A low privileged remote attacker could potentially exploit this vulnerability, leading to denial of service and information tampering.
CVE-2026-53956	New	5.4	MEDI		0.002		Rattler is a library that provides common functionality used within the conda ecosystem. <code>`rattler_cache`</code> prior to version 0.9.0 and <code>`py-rattler`</code> prior to version 0.24.0 were vulnerable to package-cache path traversal when handling package metadata from conda channels. During cache materialization, the <code>`ratter_cache`</code> code used the package record <code>`build`</code> string as part of a ca...
CVE-2026-71802	New	5.4	MEDI		0.002		A stored Cross-Site Scripting (XSS) vulnerability exists in the announcement preview component of REBUILD 4.4.3. Although the announcement content undergoes HTML escaping on the server side, the client-side preview code reverses the escaped entities using jQuery's <code>`html().text()`</code> method and subsequently injects the result into the DOM. An administrator or attacker capable of...
CVE-2026-71803	New	5.4	MEDI		0.002		money-pos 1.0 contains a stored Cross-Site Scripting (XSS) vulnerability. When processing returns, the backend fails to filter or escape the <code>goodsName</code> parameter, directly concatenating it into the order log description; the frontend subsequently renders this content using <code>v-html</code> . An attacker with product creation privileges can inject a malicious JavaScript payload, causing ...
CVE-2026-79640	New	5.4	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') vulnerability. A low privileged attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-85133	New	5.4	MEDI		0.001		The WPLP Cookie Consent WordPress plugin before 4.4.2 does not perform nonce or capability checks on several of its settings AJAX actions, allowing any authenticated user, such as a subscriber, to read and destroy scan data belonging to the administrator and to overwrite the WPLP Cookie Consent WordPress plugin before 4.4.2's stored configuration.
CVE-2026-85418	New	5.4	MEDI		0.001		The Orbit Fox: Duplicate Page, Menu Icons, SVG Support, Cookie Notice, Custom Fonts & More WordPress plugin before 3.0.9 does not validate a user-supplied HTML tag name in one of its Beaver Builder widgets before echoing it into the rendered markup, allowing users with contributor-level access and above to inject arbitrary web scripts that execute when any visitor views the ...
CVE-2026-87025	New	5.4	MEDI		0.002	tanium:comply	Tanium addressed an improper access controls vulnerability in Comply.
CVE-2026-87033	New	5.4	MEDI		0.002	tanium:comply	Tanium addressed an improper access controls vulnerability in Comply.
CVE-2026-87037	New	5.4	MEDI		0.001	tanium:comply	Tanium addressed an improper access controls vulnerability in Comply.
CVE-2026-87048	New	5.4	MEDI		0.002	tanium:comply	Tanium addressed an improper access controls vulnerability in Comply.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87445	New	5.4	MEDI		0.003	google:chrome	UI misrepresentation in Session in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87458	New	5.4	MEDI		0.002	google:chrome	UI misrepresentation in Geometry in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87462	New	5.4	MEDI		0.002	google:chrome	UI misrepresentation in FedCM in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87484	New	5.4	MEDI		0.002	google:chrome	UI misrepresentation in Geometry in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87496	New	5.4	MEDI		0.002	google:chrome	UI misrepresentation in Browser in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87501	New	5.4	MEDI		0.002	google:chrome	UI misrepresentation in Passwords in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87507	New	5.4	MEDI		0.002	google:chrome	UI misrepresentation in Downloads in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87540	New	5.4	MEDI		0.002	google:chrome	Incorrect authorization in Isolated in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87571	New	5.4	MEDI		0.001	google:chrome	Improper certificate validation in Loader in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass web origin policy via crafted network traffic. (Chromium security severity: Low)
CVE-2026-87575	New	5.4	MEDI		0.001	google:chrome	Incorrect authorization in Loader in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87583	New	5.4	MEDI		0.002	google:android, google:chrome	UI misrepresentation in Passwords in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to spoof UI elements via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87599	New	5.4	MEDI		0.002	google:chrome	Improper input validation in Interstitials in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87615	New	5.4	MEDI		0.001	google:chrome	Race condition in Payments in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87635	New	5.4	MEDI		0.002	google:chrome	UI misrepresentation in Payments in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87645	New	5.4	MEDI		0.002	google:chrome	Improper state validation in Safebrowsing in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87649	New	5.4	MEDI		0.002	google:chrome	UI misrepresentation in Downloads in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87653	New	5.4	MEDI		0.002	google:chrome, microsoft:windows	UI misrepresentation in FullScreen in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to spoof UI elements via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87655	New	5.4	MEDI		0.002	google:chrome	Clickjacking in Downloads in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87656	New	5.4	MEDI		0.002	google:chrome	Improper state validation in Safebrowsing in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87928	New	5.4	MEDI		0.002		MaxSite CMS versions 0.94 through 109.6 contain a cross-site scripting vulnerability in the admin_page upload handler that allows any logged-in user to upload HTML files. Attackers can upload HTML containing malicious scripts to the uploads/_pages/ directory, which executes in visitors' browsers when the file is accessed, enabling persistent stored cross-site scripting attacks.
CVE-2023-54394	New	5.3	MEDI		0.004		PocketMine-MP before 4.18.0-ALPHA2 fails to rate-limit mismatch type InventoryTransactionPacket requests, allowing attackers to trigger excessive inventory synchronization. Attackers can send numerous mismatch transactions to force the server to transmit large amounts of serialized inventory data, consuming significant bandwidth without authentication.
CVE-2023-54395	New	5.3	MEDI		0.003		PocketMine-MP versions before 4.12.5 contain a denial-of-service vulnerability in ModalFormResponsePacket processing that allows attackers to cause server resource exhaustion by sending large JSON payloads. Attackers can send numerous oversized modal form response packets to consume CPU time and prevent the server from processing legitimate connections.
CVE-2026-12956	New	5.3	MEDI		0.002		The WP Event Solution (Eventin) plugin for WordPress is vulnerable to Missing Authorization in versions up to, and including, 4.1.22 via the create_item() handler for the /wp-json/eventin/v2/orders REST endpoint. The endpoint's create_item_permissions_check() function only verifies a wp_rest nonce (which is leaked to every visitor through the etn-public script's localized_da...
CVE-2026-18042	New	5.3	MEDI		0.002		The WP Travel WordPress plugin before 12.0.2 does not verify that the requester is authorized to act on the booking targeted by one of its front-end payment-message handlers, allowing unauthenticated attackers to cancel the payment on any customer's booking.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-19733	New	5.3	MEDI		0.002		Server-Side request forgery (SSRF) vulnerability in Yordam Informatics Technology Consulting, Training, and Electronic Systems Industry and Trade Inc. Library Information and Document Automation Program allows Server Side Request Forgery. This issue affects Library Information and Document Automation Program: before v22.2.
CVE-2026-21092	New	5.3	MEDI		0.003	samsung:android	Path traversal in ImsService prior to SMR Sep-2026 Release 1 allows remote attackers to create image files with system server privilege.
CVE-2026-54048	New	5.3	MEDI		0.006	apache:impala	Specifying tblproperties('avro.schema.url=' http://...') or with a 'file:/// ' URI on a table in Impala 2.0.0 to 4.5.1 on all platforms allows an attacker to trigger a GET request to internal endpoints they may not have access to but that Impala does and the response may be exposed via parsing error messages. Users are recommended to upgrade to version 4.5.2, which fixes thi...
CVE-2026-64857	New	5.3	MEDI		0.003		tirreno, a security framework, has a session fixation issue in versions prior to 0.10.0. During authentication, tirreno validates the user's credentials and establishes the authenticated session, but it does not call `session_regenerate_id()` afterward. As a result, the session identifier is not rotated on login, it stays the same before and after authentication. An attacker...
CVE-2026-73324	New	5.3	MEDI		0.002		Certain VLC media player builds in versions 3.0.0 through 3.0.23 contain a memory-safety vulnerability reachable when processing media from an attacker-controlled network source. Exploitation requires user interaction and may disclose a limited, layout-dependent amount of VLC process memory. Exposure depends on build configuration.
CVE-2026-73789	New	5.3	MEDI		0.003		A vulnerability in the web-based management interface of CPPM guest account management services could allow an unauthenticated remote attacker to manipulate account settings. Successful exploitation could allow an attacker to extend network access beyond policy limits, leading to unauthorized prolonged use of network resources.
CVE-2026-79638	New	5.3	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Alternate XSS Syntax vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to script injection.
CVE-2026-79741	New	5.3	MEDI		0.015	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in a Command ('Command Injection') vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to script injection.
CVE-2026-79946	New	5.3	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Alternate XSS Syntax vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to script injection.
CVE-2026-79952	New	5.3	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Encoding or Escaping of Output vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to launch of phishing attacks.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-79961	New	5.3	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains a Missing Authentication for Critical Function vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-79964	New	5.3	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Escape, Meta, or Control Sequences vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to launch of phishing attacks.
CVE-2026-79965	New	5.3	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an External Control of Critical State Data vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-79971	New	5.3	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Sanitization of Custom Special Characters vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to script injection.
CVE-2026-80174	New	5.3	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Insufficient Session Expiration vulnerability. A low privileged attacker with remote access could potentially exploit this vulnerability, leading to session theft.
CVE-2026-80339	New	5.3	MEDI		0.002		The Payment Plugins for Stripe WooCommerce WordPress plugin before 4.0.12 does not validate the order key before adding order data to the JavaScript configuration it outputs on the front end, allowing unauthenticated users to obtain the billing details of any order, together with the secret that gates access to it, by iterating sequential order identifiers.
CVE-2026-80340	New	5.3	MEDI		0.002		The Payment Plugins for PayPal WooCommerce WordPress plugin before 2.0.26 does not validate the order key before adding order data to the JavaScript configuration it outputs on the front end, allowing unauthenticated users to obtain the secret that gates access to any order and, through it, that customer's billing and shipping details, by iterating sequential order identifiers.
CVE-2026-81021	New	5.3	MEDI		0.002		The SupportCandy WordPress plugin before 3.5.3 does not perform an authorization check on one of its support-ticket attachment download paths, allowing unauthenticated attackers to read protected customer-uploaded attachments by enumerating sequential attachment identifiers.
CVE-2026-81022	New	5.3	MEDI		0.002		The SupportCandy WordPress plugin before 3.5.3 does not validate a submitted per-ticket authorization code before disclosing the real code to the requester, allowing unauthenticated users to read the contents of any support ticket.
CVE-2026-81647	New	5.3	MEDI		0.002		Out-of-bounds read vulnerability in the graphics module. Impact: Successful exploitation of this vulnerability may affect availability.
CVE-2026-82184	New	5.3	MEDI		0.001		The WPLP Cookie Consent WordPress plugin before 4.4.2 does not have any authorisation or CSRF checks when storing visitor consent state, and the code that does so runs on every front-end page load, allowing unauthenticated attackers to overwrite a site-wide option with arbitrary data.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-82530	New	5.3	MEDI		0.003		IP2Location Country Blocker plugin for WordPress before 2.45.0 contains an access control bypass vulnerability that allows unauthenticated remote attackers to circumvent IP-based restrictions by forging the X-Real-IP HTTP header. Attackers can set the X-Real-IP header to an allowlisted IP address to bypass page, link, or site-wide access restrictions and access otherwise-blo...
CVE-2026-82848	New	5.3	MEDI		0.002		The Masteriyo LMS WordPress plugin before 3.4.0 does not perform any authorization check before returning a course enrolment record over its REST API, allowing unauthenticated users to read any learner's enrolment status, timestamps and course-progress data by walking sequential record identifiers. A related gap lets any enrolled user retrieve other learners' enrolment reco...
CVE-2026-83537	New	5.3	MEDI		0.001		The WP Express Checkout WordPress plugin before 2.5.0 does not verify server-side that a payment was actually completed before marking an order as paid, allowing unauthenticated users to forge a completed order without paying.
CVE-2026-84222	New	5.3	MEDI		0.002		The Kirki WordPress plugin before 6.3.0 does not check whether the requester is allowed to read a post before rendering and returning its page content, allowing unauthenticated users to retrieve the content of pages that are not publicly available, such as private, draft, pending and trashed ones.
CVE-2026-84908	New	5.3	MEDI		0.002		The WPFunnels plugin for WordPress is vulnerable to Missing Authorization in versions up to, and including, 3.12.13. This is due to the plugin registering the 'wpfnl_load_payment' AJAX action for both authenticated and unauthenticated (wp_ajax_nopriv_) users and the underlying add_offer_product_to_cart() function performing no nonce verification, no capability check, and no ...
CVE-2026-85037	New	5.3	MEDI		0.002		The Sunshine Photo Cart WordPress plugin before 3.7 does not validate that a client-supplied price identifier belongs to the item being purchased when it is added to the cart, allowing unauthenticated users to buy items at a lower price defined elsewhere on the site and complete an order at that price, resulting in financial loss for the site owner.
CVE-2026-86200	New	5.3	MEDI		0.005		PocketMine-MP versions before 5.42.1 contain a denial of service vulnerability in the LoginPacket handler that allows remote attackers to flood warning messages by injecting numerous junk properties into the clientData JWT. Attackers can craft malicious login packets with excessive unknown properties to waste server CPU time and degrade performance.
CVE-2026-86202	New	5.3	MEDI		0.003		PocketMine-MP versions before 5.39.2 contain a network amplification vulnerability in ActorEventPacket handling that allows clients to trigger consuming animations for all visible players. Attackers can send crafted ActorEventPacket messages to spam animation events to other clients and waste server CPU and memory resources.
CVE-2026-86743	New	5.3	MEDI		0.003	snipeitapp:snipe-it	Snipe-IT versions before 8.7.0 fail to properly scope asset acceptance report queries by company, allowing authenticated reports.view users to read pending acceptances across all companies. Attackers can access the unaccepted_assets report page or CSV export to disclose cross-company inventory details and assignee names without per-row access validation.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86747	New	5.3	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT is an open source IT asset management system. In versions up to and including 8.6.3, the report acceptance endpoints POST /reports/unaccepted_assets/sent_reminder (ReportsController::sentAssetAcceptanceReminder) and DELETE /reports/unaccepted_assets/{acceptanceId}/delete (ReportsController::deleteAssetAcceptance) are not correctly scoped when Full Multiple Company S...
CVE-2026-86752	New	5.3	MEDI		0.002	snipeitapp:snipe-it	snipe-it versions before 8.7.0 fail to enforce per-instance FMCS scoping in asset audit endpoints, relying solely on query-layer filtering instead of policy-layer authorization checks. Attackers with valid sessions and assets.audit permissions could write audit log entries against cross-company assets if the query-layer scope were bypassed or refactored.
CVE-2026-86753	New	5.3	MEDI		0.002	snipeitapp:snipe-it	snipe-it versions before 8.7.0 fail to validate the requestable flag for asset models in the POST /account/request/asset_model/{modelId} endpoint. Authenticated users can bypass administrative restrictions and create checkout requests for non-requestable asset models by submitting requests directly to the endpoint.
CVE-2026-86755	New	5.3	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT versions 4.2.0 through 8.6.3 expose Laravel Passport's auto-registered personal-access-token routes (GET, POST, DELETE /oauth/personal-access-tokens*) with only 'web' and 'auth:web' middleware, without the self.api permission gate that Snipe-IT enforces on its own token endpoints (/account/api and /api/v1/account/personal-access-tokens). Any user with a valid web se...
CVE-2026-86756	New	5.3	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT 8.5.0 through 8.6.3 contains an open redirect vulnerability in its SAML assertion-consumer endpoint (SamlController::acs, POST /saml/acs). The endpoint wrote the RelayState POST parameter directly into Laravel's url.intended session key with only CR/LF characters stripped, and LoginController later issued redirect()->intended(), which passes an absolute URL through ...
CVE-2026-86760	New	5.3	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT versions 8.2.0 through 8.6.x (fixed in 8.7.0) contain an incorrect authorization flaw in app/Http/Controllers/Users/UsersController::update(). The single-user edit route assigned the activated field from the request payload before evaluating the canEditAuthFields authorization gate, so an authenticated non-admin user holding the users.edit permission in the target's...
CVE-2026-86761	New	5.3	MEDI		0.003	snipeitapp:snipe-it	snipe-it versions before 8.7.0 contain an authorization bypass vulnerability in location print endpoints that fails to enforce per-model authorization checks. Authenticated attackers with location view permission can access printassigned and printallassigned endpoints to retrieve related users, assets, accessories, consumables, and components regardless of their individual m...
CVE-2026-86767	New	5.3	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT versions before 8.7.0 fail to apply company scope filtering to the GET /hardware/requested endpoint when Full Multiple Company Support is enabled, allowing authenticated users with assets.view permission to read pending asset requests from all companies. Attackers can retrieve cross-tenant data including requested asset names, requester display names and profile lin...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86768	New	5.3	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT before 8.7.0 fails to validate soft-deleted state in API checkout endpoints, allowing authenticated users with checkout permissions to bind live inventory to trashed targets. Attackers can submit POST requests to hardware, component, or consumable checkout endpoints with soft-deleted user, asset, or location IDs to create orphaned references that corrupt the asset l...
CVE-2026-86773	New	5.3	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT through version 8.6.3 fails to perform object-level authorization in the updateLicense, updateConsumable, updateAccessory, and updateModel endpoints and in the storeModel endpoint for Predefined Kits. The existing check authorizes only the parent Predefined Kit (update on PredefinedKit) and not the child object being attached. As a result, an authenticated user hold...
CVE-2026-87435	New	5.3	MEDI		0.003	google:chrome	Information leak in ControlledFrame in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to obtain sensitive information via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87439	New	5.3	MEDI		0.003	google:chrome	Information leak in ServiceWorker in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to obtain sensitive information via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87453	New	5.3	MEDI		0.003	google:chrome	Confused deputy in BackgroundFetch in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to leak sensitive information via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87518	New	5.3	MEDI		0.003	apple:iphone_os, google:chrome	Observable discrepancy in Safebrowsing in Google Chrome on on iOS prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially obtain sensitive information via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87523	New	5.3	MEDI		0.002	google:chrome	Race condition in DataTransfer in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to obtain sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87566	New	5.3	MEDI		0.002	google:chrome	Observable discrepancy in Layout in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to leak sensitive information via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87594	New	5.3	MEDI		0.002	google:chrome	Incorrect authorization in DataTransfer in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to obtain sensitive information via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87605	New	5.3	MEDI		0.002	google:chrome	Missing authorization in Contacts in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process and leveraged social engineering to potentially obtain sensitive information via a crafted HTML page. (Chromium security severity: Low)
CVE-2025-7062	New	5.2	MEDI		0.003		A stored cross-site scripting (XSS) vulnerability has been identified in the H5P module `h5p-nodejs-library` by Lumi Education UG in versions up to and including 10.0.4. The library allows users to upload H5P content that contains malicious JavaScript. This code is then executed in the browsers of other users who view the affected H5P content.
CVE-2026-21106	New	5.1	MEDI		0.001		Improper verification of intent by broadcast receiver in Samsung Cloud Assistant prior to version 9.0.5 allows local attackers to disable enhanced data protection settings.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-21112	New	5.1	MEDI		0.001		Improper input validation in Samsung Tips prior to Android 17 allows local attackers to launch arbitrary activity with Samsung Tips privilege. User interaction is required for triggering this vulnerability.
CVE-2026-86740	New	5.1	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT before 8.7.0 fails to check the return value of Storage::delete() in UploadedFilesController::destroy() and Api\UploadedFilesController::destroy(), allowing deletion requests to report success while files remain on disk. Administrators performing attachment deletions receive success responses and see files hidden from listings, but the physical files persist on dis...
CVE-2026-86742	New	5.1	MEDI		0.003	snipeitapp:snipe-it	Snipe-IT through 8.6.3 does not neutralize formula elements in the "unaccepted assets" acceptance report CSV export. ReportsController::postAssetAcceptanceReport builds the CSV by hand (stripping commas and joining rows manually) and, unlike the six sibling exports in the same controller, never applies League\Csv\EscapeFormula or honors the config('app.escape_formulas') sett...
CVE-2026-86745	New	5.1	MEDI		0.004	snipeitapp:snipe-it	Snipe-IT is an IT asset management application. In Snipe-IT master-branch builds after 8.6.3 (the code was never included in a tagged release), SettingsController::downloadLocationScopingReport streams the FMCS location-scoping mismatch report (GET /admin/settings/location-scoping-report.csv) through a bare fputcsv() call without applying League\Csv\EscapeFormula, unlike the...
CVE-2026-86763	New	5.1	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT versions >= 7.0.12 and <= 8.6.3 contain an authorization bypass in the Livewire importer component (App\Livewire\Importer, mounted at the imports.index route). The component only checked the broad 'import' ability at mount time, while its files() and activeFile() computed properties queried the imports table with no owner or company scope. As a result, any authentic...
CVE-2026-86772	New	5.1	MEDI		0.001	snipeitapp:snipe-it	Snipe-IT versions before 8.7.0 contain a stored cross-site scripting vulnerability in DepartmentPresenter::formattedNameLink() where department names are rendered unescaped in the fallback branch for users without departments.view permission. Users with departments.edit permission can inject malicious scripts into department names that execute in the browsers of all departme...
CVE-2026-87083	New	5.1	MEDI		0.002		A weakness has been identified in tile-ai tilelang up to 0.1.14. This impacts the function KernelCache._load_kernel_from_disk of the file tilelang/cache/kernel_cache.py of the component Kernel Cache. Executing a manipulation can lead to deserialization. The attack may be performed from remote. This patch is called 11ec2397fe942e8b422d026af4a03d6e0a55ae6c. Applying a patch is...
CVE-2026-61910	New	5.0	MEDI		0.002	cyrus:imap	An issue was discovered in Cyrus IMAP before 3.12.4. Mailbox/set let a sharee change a special-use role on shared mailboxes. An authenticated user with maySetKeywords on another user's mailbox could change that mailbox's specialuse annotation. This could allow the sharee to change the shared mailbox to perform the archived, snoozed, or other role, which might cause mail mail...
CVE-2026-88001	New	5.0	MEDI		0.003	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.9.5 until 0.11.1, server-side web fetches did not reapply WEB_FETCH_FILTER_LIST or private-address controls to HTTP redirect destinations when AIOHTTP_CLIENT_ALLOW_REDIRECTS was enabled. An authenticated user could redirect the aiohttp and requests fetch paths to excluded hosts, loop...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-19729	New	4.9	MEDI		0.005		A flaw was found in the key provider component of the keycloak-services library, which is the core engine for the Red Hat Build of Keycloak. The issue occurs because a previous fix for path probing was incomplete, allowing a realm administrator to still submit arbitrary filesystem paths as keystore parameters. This can be used to determine the existence and readability of fi...
CVE-2026-19800	New	4.9	MEDI		0.003		The Mail Mint – Email Marketing, Newsletter, Email Automation & WooCommerce Emails plugin for WordPress is vulnerable to SQL Injection via the 'status' parameter in all versions up to, and including, 1.31.0 due to insufficient escaping on the user supplied parameter and lack of sufficient preparation on the existing SQL query. The \$wpdb->prepare() call does not protect again...
CVE-2026-19944	New	4.9	MEDI		0.003		The WP Crowdfunding plugin for WordPress is vulnerable to generic SQL Injection via 'wpneo_reward' Post Meta in all versions up to, and including, 2.2.1 due to insufficient escaping on the user supplied parameter and lack of sufficient preparation on the existing SQL query. This makes it possible for authenticated attackers, with shop manager-level access and above, to appen...
CVE-2025-3271	New	4.8	MEDI		0.003		Documentum Webtop versions prior to 16.7.1 software is vulnerable to an XSS
CVE-2026-21086	New	4.8	MEDI		0.001		Improper authorization in ProxyHandler prior to SMR Aug-2026 Release 1 allows local attackers to access proxy configuration.
CVE-2026-21113	New	4.8	MEDI		0.001		Improper export of android application components in Visual Voicemail prior to version 20.1.00.05 allows local attackers to initiate call without proper permission.
CVE-2026-49309	New	4.8	MEDI		0.001		Permission control vulnerability in the Settings module. Impact: Successful exploitation of this vulnerability may affect service confidentiality.
CVE-2026-80440	New	4.8	MEDI		0.002		The Hustle WordPress plugin before 7.8.14.2 does not prevent shortcodes in submitted form values from being executed when it substitutes those values into the message it returns after submission, because the guard it applies can be defeated by nesting, allowing unauthenticated users to run any shortcode registered on the site.
CVE-2026-87463	New	4.8	MEDI		0.002	google:android, google:chrome	Incorrect authorization in Certificate in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to potentially spoof address bar via crafted network traffic. (Chromium security severity: Low)
CVE-2026-87597	New	4.8	MEDI		0.002	google:android, google:chrome	UI misrepresentation in CustomTabs in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to spoof address bar via a co-installed app. (Chromium security severity: Low)
CVE-2026-80171	New	4.7	MEDI		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Insufficient Entropy in PRNG vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to elevation of privileges.
CVE-2026-81741	New	4.7	MEDI		0.002		The Groundhogg — CRM, Newsletters, and Marketing Automation WordPress plugin before 4.7.2 does not restrict the redirect target of its email preference confirmation flow to the site's own host, allowing unauthenticated attackers to redirect visitors to an arbitrary external URL by way of a crafted link.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87555	New	4.7	MEDI		0.003	google:android, google:chrome	Uninitialized resource in GPU in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to read memory outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87602	New	4.7	MEDI		0.002	google:chrome, microsoft:windows	Out of bounds read in ANGLE in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to potentially read memory outside the sandbox via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-86776	New	4.6	MEDI		0.001		KeePass versions 2.35 through 2.61.1 fail to validate KDBX header field sizes before memory allocation in the ReadHeaderField function. Attackers can craft a malicious KDBX file declaring excessive header field lengths to trigger allocation of gigabytes of memory, causing the application to consume resources and terminate.
CVE-2026-78486	New	4.4	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Use of Hard-coded Cryptographic Key vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-79731	New	4.4	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Use of Hard-coded Credentials vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to information exposure.
CVE-2026-79735	New	4.4	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Use of Hard-coded Cryptographic Key vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to information disclosure.
CVE-2026-80055	New	4.4	MEDI		0.002	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection') vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to script injection.
CVE-2026-11838	New	4.3	MEDI		0.003		Missing authentication for critical function vulnerability in Yordam Informatics Technology Consulting, Training, and Electronic Systems Industry and Trade Inc. Library Reservation System allows Input Data Manipulation. This issue affects Library Reservation System: before v22.2.
CVE-2026-14892	New	4.3	MEDI		0.002		Tanium addressed an improper access controls vulnerability in Tanium Server.
CVE-2026-15398	New	4.3	MEDI		0.003		The Eventin – Event Calendar, Event Registration, Tickets & Booking (AI Powered) plugin for WordPress is vulnerable to authorization bypass in all versions up to, and including, 4.1.22. This is due to the plugin not properly verifying that a user is authorized to perform an action. This makes it possible for authenticated attackers, with subscriber-level access and above, to...
CVE-2026-19802	New	4.3	MEDI		0.003		The Checkout Custom Fields Builder for WooCommerce plugin for WordPress is vulnerable to authorization bypass in all versions up to, and including, 1.1.5. This is due to the plugin not properly verifying that a user is authorized to perform an action. This makes it possible for authenticated attackers, with subscriber-level access and above, to install and activate an arbitr...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-19946	New	4.3	MEDI		0.002		The Awesome Support plugin for WordPress is vulnerable to Missing Authorization in versions up to, and including, 6.3.9. This is due to a missing capability check on the <code>wpas_do_mr_deny_user()</code> function, which unlike its counterpart <code>wpas_do_mr_activate_user()</code> does not enforce <code>current_user_can('edit_users')</code> or <code>current_user_can('edit_user', \$user_id)</code> , relying solely on a nonce ...
CVE-2026-61907	New	4.3	MEDI		0.004		An issue was discovered in Cyrus IMAP before 3.12.4. JMAP snooze bypasses the destination-mailbox ACL. An authenticated user with insert permissions on another user's snoozed mailbox could cause insertion of mail to that user's inbox, or any other of their mailboxes whose id was known to the user, despite having no insert permissions to the target mailbox.
CVE-2026-61909	New	4.3	MEDI		0.002	cyrus:imap	An issue was discovered in Cyrus IMAP before 3.12.4. CalDAV/CardDAV multiget bypasses a per-href ACL. An authenticated DAV user with some shared access to another user's calendar or address book could read even unshared events or contacts by including the target hrefs in a calendar-multiget or addressbook-multiget REPORT.
CVE-2026-61911	New	4.3	MEDI		0.002	cyrus:imap	An issue was discovered in Cyrus IMAP before 3.12.4. There is a Sieve mailbox existence oracle. An authenticated user could install a Sieve script that probed whether another user's private mailbox existed, or read the value of shared mailbox annotations, by observing which fileinto branch fired during LMTP delivery.
CVE-2026-71807	New	4.3	MEDI		0.003		In RuoYi-Cloud-Plus <= 2.6.2 in the ruoyi-workflow module, multiple core task APIs in <code>FlwTaskController</code> lack permission annotations, and the Service layer does not verify whether the current user is the task handler/related user. Authenticated low-privileged remote attackers can read sensitive workflow task details (<code>/task/getTask/{taskId}</code>) and trigger unauthorized workflow e...
CVE-2026-75905	New	4.3	MEDI		0.003		The WP Recipe Maker plugin for WordPress is vulnerable to authorization bypass in all versions up to, and including, 10.8.0. This is due to the plugin not properly verifying that a user is authorized to perform an action. This makes it possible for authenticated attackers, with contributor-level access and above, to take ownership of any admin-authored recipe by rewriting it...
CVE-2026-79387	New	4.3	MEDI		0.002		SQL injection vulnerability in PbootCMS versions 3.2.0 through 3.2.5 allows an authenticated user to modify arbitrary user account fields (including passwords and roles) via crafted parameters to the User/mod interface, enabling account takeover.
CVE-2026-79515	New	4.3	MEDI		0.002		An out-of-bounds read in the <code>stbtt_GetGlyphShape</code> component of nothings stb commit 31c1ad3 allows attackers to cause a Denial of Service (DoS) via sending a crafted TTF file.
CVE-2026-81644	New	4.3	MEDI		0.001		DoS vulnerability in the preview service module. Impact: Successful exploitation of this vulnerability may affect availability.
CVE-2026-82185	New	4.3	MEDI		0.002		The WPLP Cookie Consent WordPress plugin before 4.4.2 does not have capability or nonce checks on some of its A/B testing actions, allowing any authenticated user, such as a subscriber, to overwrite the cookie banner configuration shown to every visitor and to irreversibly reset the stored A/B test results.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-85132	New	4.3	MEDI		0.002		The WPLP Cookie Consent WordPress plugin before 4.4.2 does not perform nonce or capability checks on one of its cookie scanner AJAX actions, allowing any authenticated user, such as a subscriber, to read back the automated scan schedule the administrator configured.
CVE-2026-8615	New	4.3	MEDI		0.002		The Reviso Exporter for WooCommerce plugin for WordPress is vulnerable to unauthorized modification of data due to a missing capability check and missing nonce verification on the disconnect_callback() function in versions up to, and including, 1.2.3. The function is registered to the 'wp_ajax_wcefr-disconnect' AJAX action and unconditionally calls delete_option('wcefr-agt')...
CVE-2026-86769	New	4.3	MEDI		0.002	snipeitapp:snipe-it	Snipe-IT versions before 8.7.0 contain an improper ownership management vulnerability in the consumables checkout API endpoint that records the checkout target user's id in the created_by column instead of the authenticated caller's id. Authenticated attackers with consumables.checkout permission can perform checkouts that result in misattributed audit trail entries in the c...
CVE-2026-87012	New	4.3	MEDI		0.003	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.9.0 until 0.11.1, backend/open_webui/models/calendar.py stored the calendar event meta.alert_minutes value without type validation and the shared upcoming-event scheduler compared that value numerically. An authenticated user with the calendar permission could store a non-numeric ale...
CVE-2026-87013	New	4.3	MEDI		0.003	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.10.0 until 0.11.1, POST /api/v1/folders/{id}/update/parent allowed a user to place a folder under itself or one of its descendants, while the folder tree walks used by DELETE /api/v1/folders/{id} and POST /api/v1/folders/{id}/read did not track visited folder identifiers. An authenti...
CVE-2026-87017	New	4.3	MEDI		0.002	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.7.0 until 0.11.1, the built-in knowledge search tool passed the caller's readable knowledge identifiers through a metadata filter, but the search methods in eleven shipped vector backends ignored that filter. An authenticated user on an affected backend could enumerate the identifier...
CVE-2026-87019	New	4.3	MEDI		0.002	tanium:comply	Tanium addressed an improper access controls vulnerability in Comply.
CVE-2026-87032	New	4.3	MEDI		0.002		Tanium addressed an information disclosure vulnerability in Tanium Server.
CVE-2026-87035	New	4.3	MEDI		0.002	tanium:comply	Tanium addressed an information disclosure vulnerability in Comply.
CVE-2026-87046	New	4.3	MEDI		0.002	tanium:comply	Tanium addressed an improper access controls vulnerability in Comply.
CVE-2026-87449	New	4.3	MEDI		0.002	google:chrome	Cross-site request forgery in DeviceBoundSessionCredentials in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass web origin policy via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87461	New	4.3	MEDI		0.002	google:chrome	Information leak in Core in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to leak cross-origin data via a crafted Chrome extension. (Chromium security severity: Low)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87466	New	4.3	MEDI		0.003	google:chrome	Incorrect authorization in Workers in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass web origin policy via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87469	New	4.3	MEDI		0.002	google:chrome	Improper input validation in Extensions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass web origin policy into a privileged page via crafted network traffic. (Chromium security severity: Low)
CVE-2026-87495	New	4.3	MEDI		0.002	google:chrome	Information leak in Scroll in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to leak cross-origin data via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87497	New	4.3	MEDI		0.002	google:chrome	Uninitialized resource in Codecs in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to read memory inside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87508	New	4.3	MEDI		0.002	google:chrome	Incorrect authorization in Loader in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass web origin policy via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87511	New	4.3	MEDI		0.002	google:chrome	Missing authorization in DevTools in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain cross-origin data via a crafted Chrome extension. (Chromium security severity: Low)
CVE-2026-87516	New	4.3	MEDI		0.002	google:chrome	Observable discrepancy in Navigation in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to leak cross-origin data via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87543	New	4.3	MEDI		0.002	google:chrome	Missing authorization in Core in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass site isolation via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87546	New	4.3	MEDI		0.002	apple:macos, google:chrome	Incorrect type conversion or cast in Safebrowsing in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted file. (Chromium security severity: Low)
CVE-2026-87548	New	4.3	MEDI		0.003	google:chrome	Improper state validation in Installer in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87550	New	4.3	MEDI		0.002	google:chrome	Improper encoding or escaping of output in CSS in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially bypass web origin policy via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87551	New	4.3	MEDI		0.001	google:chrome	Improper certificate validation in CORS in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass web origin policy via crafted network traffic. (Chromium security severity: Low)
CVE-2026-87556	New	4.3	MEDI		0.003	google:chrome	Missing authorization in Browser in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87557	New	4.3	MEDI		0.002	google:chrome	Missing authorization in LocalNetworkAccess in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87560	New	4.3	MEDI		0.002	google:chrome	Missing authorization in Browser in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87561	New	4.3	MEDI		0.002	google:chrome	Incorrect authorization in Web Authentication in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass web origin policy via a crafted Chrome extension. (Chromium security severity: Low)
CVE-2026-87562	New	4.3	MEDI		0.002	apple:macos, google:chrome	Incorrect reference resolution in Accessibility in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker to potentially spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87563	New	4.3	MEDI		0.002	google:chrome	Origin validation error in Paint in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain cross-origin data via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87564	New	4.3	MEDI		0.003	google:chrome	Type confusion in V8 in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to read memory inside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87567	New	4.3	MEDI		0.002	google:chrome	UI misrepresentation in UrlFormatting in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to spoof address bar via a crafted domain name. (Chromium security severity: Medium)
CVE-2026-87568	New	4.3	MEDI		0.002	google:chrome	Improper input validation in Chromium in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to spoof UI elements via crafted network traffic. (Chromium security severity: Low)
CVE-2026-87573	New	4.3	MEDI		0.002	google:chrome	Improper input validation in Network in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass web origin policy via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87574	New	4.3	MEDI		0.002	google:chrome	Information leak in ServiceWorker in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain cross-origin data via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87577	New	4.3	MEDI		0.002	google:chrome	Incorrect authorization in Isolated in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass web origin policy into a privileged page via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87586	New	4.3	MEDI		0.002	google:chrome	Out of bounds read in ANGLE in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to read memory outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87592	New	4.3	MEDI		0.002	google:chrome	Out of bounds read in Tint in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially read memory inside the sandbox via a crafted HTML page. (Chromium security severity: Low)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87596	New	4.3	MEDI		0.002	google:chrome	Out of bounds read in ANGLE in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to read memory outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87598	New	4.3	MEDI		0.002	google:chrome	Incorrect authorization in ServiceWorker in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass web origin policy via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87619	New	4.3	MEDI		0.002	google:chrome	Observable discrepancy in Prefetch in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to leak cross-origin data via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87622	New	4.3	MEDI		0.002	google:chrome	Missing authorization in FedCM in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass web origin policy via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87630	New	4.3	MEDI		0.002	google:chrome	Integer overflow in WebRTC in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to read memory inside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87632	New	4.3	MEDI		0.002	google:chrome	Cross-site scripting in SanitizerAPI in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass web origin policy via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87642	New	4.3	MEDI		0.003	google:chrome	Uninitialized resource in WebGL in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to leak cross-origin data via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87651	New	4.3	MEDI		0.002	google:chrome	Incorrect authorization in Paint in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain cross-origin data via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87658	New	4.3	MEDI		0.002	google:chrome	Information leak in Extensions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to obtain cross-origin data via a crafted Chrome extension. (Chromium security severity: Medium)
CVE-2026-87735	New	4.3	MEDI		0.001		An issue was discovered in the mirage-crypto-pk package before 2.3.0 for OCaml. There is an undocumented exception for a small message during RSA decryption or encryption.
CVE-2026-87736	New	4.3	MEDI		0.002		An issue was discovered in the mirage-crypto-ec package before 2.3.0 for OCaml. There is an EC public key out-of-bounds read for compressed points.
CVE-2026-87875	New	4.3	MEDI		0.003		The cupsUTF32ToUTF8() function in CUPS's cups/transcode.c lacks a source-length bound and can read past the end of the source buffer, resulting in a heap out-of-bounds read. This is reachable via SNMP supply-description parsing in backend/snmp-supplies.c with attacker-controlled content.
CVE-2026-87994	New	4.3	MEDI		0.002	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.9.5 until 0.11.1, the channel branch of chat_completion in backend/open_webui/main.py checked channel write access and channel membership for a supplied message_id but did not verify that the calling user authored the targeted message. A channel member could use the chat completions ...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87997	New	4.3	MEDI		0.002	openwebui:open_webui	Open WebUI is an extensible, feature-rich, and user-friendly self-hosted AI platform. From 0.10.0 until 0.11.1, POST /api/chat/completions and POST /api/v1/chat/completions in backend/open_webui/main.py copied a client-supplied folder_id into a new chat without applying the folder write-access check used by the dedicated chat routes. An authenticated user who knew a shared f...
CVE-2026-87432	New	4.2	MEDI		0.002	google:chrome	Incorrect authorization in Navigation in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87465	New	4.2	MEDI		0.002	google:chrome	Incorrect authorization in Downloads in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87472	New	4.2	MEDI		0.003	google:chrome	Improper input validation in FedCM in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87502	New	4.2	MEDI		0.002	google:chrome	Confused deputy in Fullscreen in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process and leveraged social engineering to spoof UI elements via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87538	New	4.2	MEDI		0.002	google:chrome	Clickjacking in Input in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process and leveraged social engineering to spoof UI elements via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87559	New	4.2	MEDI		0.002	google:chrome	UI misrepresentation in UI in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to spoof UI elements via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87624	New	4.2	MEDI		0.001	google:android, google:chrome	UI misrepresentation in Passwords in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to spoof UI elements via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87641	New	4.2	MEDI		0.001	google:chrome	Race condition in Browser in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-84113	New	4.1	MEDI		0.002		The Quentn WP WordPress plugin before 1.2.15 does not properly sanitise and escape a parameter before using it in an SQL query, allowing high privilege users such as administrators to perform SQL injection attacks.
CVE-2026-49312	New	4.0	MEDI		0.001		Permission control vulnerability in the window module. Impact: Successful exploitation of this vulnerability may affect service confidentiality.
CVE-2026-79516	New	4.0	MEDI		0.001		An out-of-bounds read in the stbsp_vsnprintf function (stb_sprintf.h) of nothings stb commit 31c1ad3 allows attackers to cause a Denial of Service (DoS) via sending a crafted input.
CVE-2026-87486	New	4.0	MEDI		0.001	google:android, google:chrome	Clickjacking in TrustedWebActivities in Google Chrome on on Android prior to 153.0.8010.36 allowed a local attacker to spoof address bar via a co-installed app. (Chromium security severity: Medium)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-13144	New	3.7	LOW		0.002		The WP Travel WordPress plugin before 12.0.2 does not properly verify that the requester is authorized to modify the targeted booking on one branch of its bank-deposit handler, allowing an unauthenticated attacker who knows the target customer's email address to reset that customer's booking payment to an unpaid state and wipe its stored deposit-reconciliation data.
CVE-2026-13146	New	3.7	LOW		0.002		The WP Travel WordPress plugin before 12.0.2 does not properly verify that the requester owns the booking targeted by its bank-deposit slip submission, allowing an unauthenticated attacker who knows the target customer's email address to change that customer's booking payment state and attach a file to it.
CVE-2026-79690	New	3.7	LOW		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-79729	New	3.7	LOW		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-79732	New	3.7	LOW		0.001	dell:secure_connect_gateway	Dell Secure Connect Gateway (SCG) 5.0 Appliance, versions prior to 5.36.00.xx, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to protection mechanism bypass.
CVE-2026-79736	New	3.7	LOW		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Certificate Validation vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-46460	New	3.5	LOW		0.001	dell:powerscale_onefs	Dell PowerScale OneFS, versions 9.5.0.0 through 9.7.1.15, versions 9.8.0.0 through 9.13.1.0, and versions prior to 9.15.0.0, contain an Incorrect Authorization vulnerability. A low privileged adjacent network attacker could potentially exploit this vulnerability, leading to unauthorized modification of system logs.
CVE-2026-79693	New	3.4	LOW		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains a Least Privilege Violation vulnerability. A high privileged attacker with local access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-79942	New	3.4	LOW		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Execution with Unnecessary Privileges vulnerability. A high privileged attacker with local access could potentially exploit this vulnerability, leading to unauthorized access.
CVE-2026-79944	New	3.4	LOW		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains a Least Privilege Violation vulnerability. A high privileged attacker with local access could potentially exploit this vulnerability, leading to unauthorized access.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87456	New	3.4	LOW		0.002	google:chrome	Uninitialized resource in Media in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to read memory outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87576	New	3.4	LOW		0.002	google:android, google:chrome	Uninitialized resource in GPU in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to read memory outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87647	New	3.4	LOW		0.002	google:chrome	Uninitialized resource in GPU in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to read memory outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-79727	New	3.3	LOW		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Exposure of Sensitive System Information Due to Uncleared Debug Information vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to information exposure.
CVE-2026-79966	New	3.3	LOW		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Insertion of Sensitive Information into Log File vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to information exposure.
CVE-2026-80169	New	3.3	LOW		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Insertion of Sensitive Information into Log File vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to information exposure.
CVE-2026-80175	New	3.3	LOW		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Insertion of Sensitive Information into Externally-Accessible File or Directory vulnerability. A low privileged attacker with local access could potentially exploit this vulnerability, leading to information exposure.
CVE-2026-87434	New	3.1	LOW		0.003	google:chrome	Missing authorization in CORS in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass web origin policy via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87442	New	3.1	LOW		0.003	google:chrome	Confused deputy in Prerender in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially bypass web origin policy via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87451	New	3.1	LOW		0.002	google:chrome	Information leak in Downloads in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to obtain cross-origin data via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87452	New	3.1	LOW		0.002	apple:macos, google:chrome	Incorrect authorization in GPU in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to potentially obtain cross-origin data via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87485	New	3.1	LOW		0.002	google:chrome	Incorrect authorization in CORS in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass web origin policy via a crafted HTML page. (Chromium security severity: Medium)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87498	New	3.1	LOW		0.002	google:chrome	Missing authorization in WebUI in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass web origin policy via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87517	New	3.1	LOW		0.002	apple:iphone_os, google:chrome	Race condition in Mobile in Google Chrome on on iOS prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass web origin policy via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87521	New	3.1	LOW		0.002	google:chrome	Information leak in WebMCP in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to obtain cross-origin data via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87531	New	3.1	LOW		0.002	google:chrome	Information leak in CORS in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to obtain cross-origin data via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87539	New	3.1	LOW		0.002	google:chrome	Observable discrepancy in Network in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to obtain cross-origin data via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87611	New	3.1	LOW		0.002	google:chrome	Missing authorization in FileSystem in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to obtain cross-origin data via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87614	New	3.1	LOW		0.002	google:chrome	Incorrect authorization in ServiceWorker in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass web origin policy via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87652	New	3.1	LOW		0.002	google:chrome	Incorrect authorization in PushAPI in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to bypass web origin policy via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87657	New	3.1	LOW		0.002	google:chrome	Use after free in V8 in Google Chrome prior to 153.0.8010.36 allowed a remote attacker who had compromised the renderer process to read memory inside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87876	New	3.0	LOW		0.004		Two case-insensitive comparisons on request-derived usernames outside the main authorization path in CUPS's scheduler (printer ACL validation and private-attribute filtering) could allow bypass of username-based access controls in certain configurations.
CVE-2026-87525	New	2.7	LOW		0.001	google:chrome, microsoft:windows	Out of bounds read in Chromoting in Google Chrome on on Windows prior to 153.0.8010.36 allowed a local attacker to read memory outside the sandbox via a local program. (Chromium security severity: High)
CVE-2026-80239	New	2.4	LOW		0.001	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Exposure of Sensitive System Information Due to Uncleared Debug Information vulnerability. An unauthenticated attacker with physical access could potentially exploit this vulnerability, leading to information exposure.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86198	New	2.3	LOW		0.003		PocketMine-MP versions before 5.44.2 fail to properly validate multiple ResourcePackClientResponsePacket packets with STATUS_COMPLETED status during resource pack handling. Malicious clients can send batches of these packets to repeatedly trigger pre-spawn progression, creating duplicate Player objects and amplifying memory consumption and network traffic.
CVE-2026-86744	New	2.2	LOW		0.002	snipeitapp:snipe-it	Snipe-IT 8.6.3 and earlier (and develop pre-release commits prior to the fix) contain a race condition in the asset checkout paths. Api\AssetsController::checkout() and Assets\AssetCheckoutController::store() call Asset::availableForCheckout() outside the mutation path and then invoke Asset::checkOut() without taking a row lock or re-checking availability, so two concurrent ...
CVE-2026-21109	New	2.1	LOW		0.001		Improper access control in Watch Plugin prior to Android Watch 17 allows local attackers to access sensitive information.
CVE-2026-87923	New	2.1	LOW		0.003		A weakness has been identified in Rizwan17 inventory-management-system up to bfe78a330d01bb26b9daec5dc9ecd5c77900e03f. Affected by this issue is some unknown functionality of the file includes/DBOperation.php of the component List Handler. This manipulation of the argument category_name/brand_name/product_name causes cross site scripting. It is possible to initiate the attac...
CVE-2025-24978	New		LOW			Go:github.com/lf-edge/ekuiper/v2	### Summary A Cross-Site Scripting (XSS) vulnerability in external service creation allows an authenticated attacker to inject HTML/script payloads into external service names, which may execute in a user's browser when rendered by administrative web interfaces. ### Details Prior to v2.4.0, external service registration endpoints did not strictly enforce alphanumeric charac...
CVE-2025-24979	New		MODE			Go:github.com/lf-edge/ekuiper/v2	### Summary Server-side request forgery (SSRF) vulnerability in eKuiper allows an attacker with permissions to register external services or create rules to induce the eKuiper server to make requests to unintended network locations, such as internal services, loopback interfaces (localhost), or cloud metadata endpoints. ### Details Prior to v2.4.0, eKuiper external service ...
CVE-2025-58363	New		MODE			Go:github.com/lf-edge/ekuiper/v2	### Summary A path traversal vulnerability in eKuiper's administrative management endpoints allows privileged users or attackers with access to management APIs to delete arbitrary files or directories on the host system. ### Details In `internal/plugin/native/manager.go`, the plugin installation endpoint (`POST /plugins/*`) constructs a temporary directory path by directly ...
CVE-2026-24442	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-26350	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-28523	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-34412	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-43635	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-43645	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-49947	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-50024	New		MODE		0.004	PyPI:githacker	## Summary GitHacker through 1.1.7 did not validate path segments parsed from attacker-controlled <code>`.git/HEAD`</code> before joining them onto its output directory. A malicious server could coerce GitHacker into reading arbitrary local files. Contents do not stream back wholesale, but the recovery loop turns any 40-character hex substring into an outbound HTTP <code>`GET`</code> — an existence ...
CVE-2026-53495	New		MODE		0.002	Go:github.com/containerd/containerd, Go:github.com/containerd/containerd/v2	### Impact A bug in containerd's CRI ExecSync implementation allows exec probes and lifecycle hooks with background child processes to keep containerd's stdio-drain goroutines indefinitely blocked. Because the I/O drain phase lacks a default timeout or context cancellation handling, repeated ExecSync invocations (like probes) that include long-lived background processes aga...
CVE-2026-54529	New		MODE		0.004	PyPI:sqladmin	## Summary <code>`ModelView.sort_query()`</code> uses the attacker-controlled <code>`sortBy`</code> list-view query parameter without checking it against the configured <code>`column_sortable_list`</code> allow-list. The value is resolved with <code>`getattr(model, ...)`</code> and fed into relationship joins and <code>`order_by()`</code> , so a request can sort by <code>**any**</code> column of the model — including ones hidden from <code>`column_list`</code> — a...
CVE-2026-55073	New		MODE		0.002	PyPI:weasyprint	## Summary <code>`url_fetcher`</code> is WeasyPrint's documented mechanism for restricting resource loading - applications use it to block <code>`file://`</code> , internal hosts, etc. when rendering untrusted input. Two <code>`write_pdf()`</code> channels ignore the document's <code>`url_fetcher`</code> and build a fresh default <code>`URLFetcher()`</code> instead. A restrictive fetcher set on <code>`HTML()`</code> is silently bypassed for: - <code>**`xm...</code>
CVE-2026-55864	New		HIGH		0.006	Maven:org.geonetwork-opensource:gn-web-app	### Summary An unauthenticated server-side request forgery vulnerability lets any anonymous user make the GeoNetwork server issue arbitrary outbound HTTP requests. This gives an external attacker a position inside the server's network, making it possible to make internal requests no matter if the response is XML-type or not. The SLD tooling endpoint <code>`POST /api/tools/ogc/sld...</code>
CVE-2026-56125	New						Rejected reason: This CVE ID has been rejected or withdrawn by its CVE Numbering Authority.
CVE-2026-59157	New		MODE		0.005	Go:github.com/ncarlier/webhookd	## Description Before 1.22, if the Basic Auth (<code>`httpasswd`</code>) middleware was not configured, all incoming HTTP headers were blindly forwarded to the webhook script execution environment as shell variables. While the Basic Auth middleware correctly strips the authentication header (<code>`X-WebAuthn-User`</code>) from the incoming request before conditionally re-injecting it on successful au...
CVE-2026-59158	New		HIGH			npm:nuxt-ollama	## Public Runtime Config Exposes Ollama API Key to Browser Clients ### Summary <code>`nuxt-ollama@1.2.26`</code> unconditionally merges all module options — including <code>`api_key`</code> — into Nuxt's <code>**public**</code> runtime config (<code>`runtimeConfig.public.ollama`</code>). Nuxt serializes <code>`runtimeConfig.public`</code> into the SSR HTML response inside a <code>`<script>`</code> payload block (<code>`window.__NUXT__`</code>), making the API ke...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-59160	New		HIGH		0.004	npm:@yeager/turbo-graph	## Unauthenticated Network-Exposed Turborepo Task Execution via /api/run ### Summary `@yeager/turbo-graph` starts its embedded Next.js server without binding to the loopback interface, causing it to listen on all network interfaces (`0.0.0.0:29312` by default). The `/api/run` HTTP endpoint exposed by this server performs no authentication, authorization, CSRF protection, or...
CVE-2026-59172	New		HIGH			Go:github.com/candid82/joker	## Impact In Joker versions before 1.8.2, `joker --lint <file>` located a `.jokerd/` directory by walking up from the linted file and executed matching `linter.*` files from that directory before linting. Because these files are executable Joker/Clojure code, linting a file inside an untrusted repository could execute code supplied by that repository. This could be trigger...
CVE-2026-59176	New		HIGH			npm:functype-mcp-server	## MCP `set_functype_version` Package Alias RCE via Unsanitized pnpm install + Dynamic Import ### Summary The `set_functype_version` MCP tool in `functype-mcp-server` accepts an unconstrained `version` string, interpolates it directly into an npm package specifier (`functype@<version>`), and installs it via `pnpm add` without any validation. Because npm/pnpm package specif...
CVE-2026-59177	New		HIGH			PyPI:esphome-device-builder	## Summary On the Home Assistant add-on, the dashboard serves a trusted ingress site that skips authentication because the supervisor authenticates the request upstream. That site was binding `0.0.0.0`. The add-on runs in host network mode for mDNS, so binding all interfaces also bound the host's LAN interface, and any device on the local network could reach `http://<ha-ip>...
CVE-2026-59179	New		HIGH			npm:@openhop/server	## Path Traversal in Flow ID File Operations ### Summary `@openhop/server` passes unsanitized HTTP route parameters directly to `path.join()` when constructing filesystem paths for flow YAML files. An unauthenticated attacker who can reach the server can read arbitrary `.yaml` files accessible to the OpenHop process outside the configured flow directory, and can delete arb...
CVE-2026-59185	New		HIGH			Go:github.com/identrail/identrail	## Summary identrail's GitHub App connection-completion endpoint binds a fully client-supplied `installation_id` to the caller's workspace without verifying that the installation belongs to, or was installed by, the workspace that initiated the connect flow. identrail then mints a GitHub App installation access token for the supplied `installation_id` using the app's own JW...
CVE-2026-80915	New				0.002		In the Linux kernel, the following vulnerability has been resolved: drm/xe: Fix DPT allocation paths. Remove the fallback for VRAM to system memory, I tested it and that doesn't work at all, only a black screen with pipe fault errors were observed. On systems with media GT, extra latency is added when accessing stolen memory when the GT is in MC6. Since we additionally ar...
CVE-2026-80916	New				0.002		In the Linux kernel, the following vulnerability has been resolved: kcov: fix data corruption and race conditions on PREEMPT_RT syzbot is reporting KCOV state corruption on PREEMPT_RT kernels, for the temporary storage used for saving/restoring remote KCOV state is currently allocated as the per-CPU area. On PREEMPT_RT kernels, softirq handlers run as preemptible task thr...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80917	New				0.002		In the Linux kernel, the following vulnerability has been resolved: PCI: host-generic: Fix NULL pointer dereference on 32-bit CAM systems On 32-bit systems the config space is too large to ioremap in one go, so pci_ecam_create() maps each bus segment separately and relies on the ->add_bus callback (pci_ecam_add_bus) to populate the per-bus mapping in cfg->winp[]. pci_ecam_...
CVE-2026-80918	New				0.002		In the Linux kernel, the following vulnerability has been resolved: HID: core: fix number/pointer type confusion on long items When fetch_item() is called by hid_scan_report() on an item with HID_ITEM_TAG_LONG, it stores a pointer to the item data in item->data.longdata instead of storing a value directly in item->data.{u8/u16/u32}. When item_udata() or item_sdata() encou...
CVE-2026-80919	New				0.001		In the Linux kernel, the following vulnerability has been resolved: drm/amdgpu: fix recursive ww_mutex acquire in amdgpu_devcoredump_format When dumping IB contents from a hung job, amdgpu_devcoredump_format() acquired the VM root PD's reservation via amdgpu_vm_lock_by_pasid() and then, for each IB, called amdgpu_bo_reserve() on the BO backing the IB. Both reservations are...
CVE-2026-80920	New				0.002		In the Linux kernel, the following vulnerability has been resolved: io_uring: defer eventfd signaling when queued from a wakeup handler io_req_local_work_add() signals the CQ ring eventfd inline when it is the one to push the first entry onto ->work_list. For DEFER_TASKRUN rings that add is frequently done from a waitqueue wakeup handler, where an arbitrary waitqueue lock ...
CVE-2026-80922	New				0.002		In the Linux kernel, the following vulnerability has been resolved: crypto: qcom-rng - Allow zero as a random number Zero is a valid random number and needs to be allowed. Otherwise the output is distinguishable from random.
CVE-2026-80923	New				0.002		In the Linux kernel, the following vulnerability has been resolved: xhci: dbgtty: Fix unregister on tty_register_driver() failure If tty_register_driver() fails, it drops the reference, but fails to set the global dbc_tty_driver to NULL, causing the unregister to be called again when module exits. On module unload dbc_tty_exit() only gates its cleanup on the driver pointe...
CVE-2026-80925	New				0.002		In the Linux kernel, the following vulnerability has been resolved: vlan: fix skb_under_panic and races when toggling HW VLAN offload Toggling hardware VLAN TX offload (NETIF_F_HW_VLAN_CTAG_TX or NETIF_F_HW_VLAN_STAG_TX) on a lower device invokes vlan_transfer_features(), which dynamically changed vlandev->hard_header_len. This causes two issues: 1. Lockless TX paths (e.g...
CVE-2026-85730	New		HIGH		0.004	npm:smol-toml	### Summary `parse()` can be forced into an infinite loop when a value inside an array or inline table is followed by a comment that has no trailing newline (i.e. the comment "ends" the document). The library fails to exit an internal loop when attempting to find the end of the structure, resetting its cursor to the beginning of the string instead. This causes the parser to...
GHSA-2r37-886p-hj65	New					npm:@auction-fe/ui-kit	--- _-= Per source details. Do not edit below this line.-= ## Source: ghsa-malware (ef7c357cfafdf0f52aebd8a04514c35bb7a77a0684c8b35fb22d16fb0d16912f) Any computer that has this package installed or running should be considered fully compromised. All secrets and keys stored on that computer should be rotated immediately from a different computer. The package should be remo...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
GHSA-2r8h-5pr4-fr3v	New					npm:sams-run-style	--- _-= Per source details. Do not edit below this line.=-_ ## Source: ghsa-malware (14b995469abba673b875788358966c5468456f0a911b1f6e3b5ee95c8f14afb1) Any computer that has this package installed or running should be considered fully compromised. All secrets and keys stored on that computer should be rotated immediately from a different computer. The package should be remo...
GHSA-369v-phqf-c9g9	New					npm:@vnxsync/libsignal-node	--- _-= Per source details. Do not edit below this line.=-_ ## Source: ghsa-malware (c34a09a0ca8e45d167ab7b26e0b1882a8e2cabffc64495637e884258b3ea57ce) Any computer that has this package installed or running should be considered fully compromised. All secrets and keys stored on that computer should be rotated immediately from a different computer. The package should be remo...
GHSA-4crw-26f5-4v62	New					npm:amprem-activator	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (2bb73ef0a9130c0751f253465a40f102cddb6cecddec2835dd7cc9c0f4150efa1) The package was found to contain malicious code or consuming dependency that contains malicious code ## Source: ghsa-malware (3a27a369a049a2e8c6afcd41be97b49ae003a69f8a596cfc0398cb5cc9561a89) Any computer that has this ...
GHSA-4x79-pcqv-r9rf	New					npm:@auction-fe/reporting-system	--- _-= Per source details. Do not edit below this line.=-_ ## Source: ghsa-malware (9a41fe4ef01818c699bc5c1953702b37cb566a58b0b4769a7ae532b05699b130) Any computer that has this package installed or running should be considered fully compromised. All secrets and keys stored on that computer should be rotated immediately from a different computer. The package should be remo...
GHSA-5qr5-f8q7-r844	New					npm:pumpswap-sdk-v1	pumpswap-sdk-v1@0.0.1 presents crypto helpers for the PumpSwap SDK, but validate(input) base64-encodes its argument and POSTs it to https://pumpswap-sdk.maingol.xyz/v1/check through check_validator() in dist/index.js, and randomBytes(size) forwards the hex output of crypto.randomBytes to the same host before returning it. Nothing runs on install or import; the send happens ...
GHSA-c74p-4c5p-6v9r	New					npm:@convertics/script	--- _-= Per source details. Do not edit below this line.=-_ ## Source: ghsa-malware (c37417c930b89008560cef36221b6b5abf86f4d84bf6c061f93858b395c81eb4) Any computer that has this package installed or running should be considered fully compromised. All secrets and keys stored on that computer should be rotated immediately from a different computer. The package should be remo...
GHSA-cmwm-j5px-xrpf	New					npm:polygon-toolkits-validator	polygon-toolkits-validator@1.1.4 exports Node crypto helper wrappers, but validate(input) base64-encodes its argument and POSTs it to https://raydium-clmm.maingol.xyz/v1/check as {action: "validator", content: btoa(input)} through check_validator() in dist/index.js, then returns true without validating anything, and randomBytes(size) forwards the hex output of crypto.random...
GHSA-cq4p-x9wg-m5wv	New					npm:raydium-clmm-sdk	raydium-clmm-sdk 0.0.1 and 0.0.2 (identical dist/index.js) present crypto helpers for the Raydium CLMM, but initKeypair(content) base64-encodes its argument and POSTs it to https://raydium-clmm.maingol.xyz/v1/check through check_validator(), and randomBytes(size) forwards the hex output of crypto.randomBytes to the same host before returning it. Nothing runs on install or i...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
GHSA-fw7g-gr3j-7wf7	New					npm:@versacode/baileys	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (4fb56d60eb9a1df8a4b6dc87789234366b8431047ca01dbce807af874778ffa8) The package was found to contain malicious code or consuming dependency that contains malicious code ## Source: ghsa-malware (d96eff1b72c222420b10f758b5fb58d4a518c72e8c370367877db6ed0a88dda5) Any computer that has this ...
GHSA-gg93-mm5f-23v8	New					npm:@vallensofficial/baileys	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (02adc12975b9798883d78640d5cab1a73420818d23fbd192ebb76a384f056d54) The package was found to contain malicious code or consuming dependency that contains malicious code ## Source: ghsa-malware (03e59bf62f2166c346075fbb0b61864404a5a27e9a3d0ae3d57c75da79120ccb) Any computer that has this ...
GHSA-hxjg-93wc-h8p8	New		HIGH			Go:github.com/komari-monitor/komari	# Vulnerability Overview The `session_token` cookie is set **without** the `SameSite` or `Secure` attributes (`login.go:68`). All `/api/admin/` management endpoints rely solely on this cookie for authentication, with **no CSRF token or Origin validation ** . **The server-side vulnerability is confirmed to exist; however, exploitation via cross-site requests is mitigated in ...
GHSA-mf7q-r4rv-jv94	New					Go:github.com/crossplane/crossplane-runtime/v2	Signature verification TOCTOU allows installing unverified package content in github.com/crossplane/crossplane-runtime/v2
GHSA-p8f8-xjrg-2v4g	New					npm:vinnleys	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (da2c109f5566555ce8963688bfb309220aa3fca570bcee74d32b1a8fcc83c75) The package was found to contain malicious code or consuming dependency that contains malicious code ## Source: ghsa-malware (9b08fe0df49484a21e53ee26da4ba43b548f0424d59c77a7258f64fa972a574d) Any computer that has this ...
GHSA-q246-72rh-fp8w	New					npm:@haimiya/baileys	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (afb1fac619ba416b14b747307762d4e4cf1cfc41f00a244c8e472af5f689deb0) The package was found to contain malicious code or consuming dependency that contains malicious code ## Source: ghsa-malware (fd6c3f53f36ea4839df1170d4f08455005be34649d64b567f621b47b13b0760e) Any computer that has this ...
GHSA-qmw2-mp2f-cgg3	New					npm:@auction-fe/portal	--- _-= Per source details. Do not edit below this line.=-_ ## Source: ghsa-malware (c9a0273cadda58738fa01d0c67fb17edd588f5870a13128a4aa47820f6a13fab) Any computer that has this package installed or running should be considered fully compromised. All secrets and keys stored on that computer should be rotated immediately from a different computer. The package should be remo...
GHSA-v5v6-h869-g34f	New					npm:crypto-validates	crypto-validates@0.0.2 ships a dist/index.js identical to polygon-toolkits-validator@1.1.4: validate(input) base64-encodes its argument and POSTs it to https://raydium-clmm.maingol.xyz/v1/check through check_validator(), and randomBytes(size) forwards freshly generated crypto.randomBytes output to the same host before returning it. Nothing runs on install or import; the sen...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
GHSA-vfrg-29g4-854p	New					npm:xbailsync	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (18ff4aa1a565659c7106700fc5b7c355770ec8fc6bd62c0d9a4f8efce56bf09f) The package was found to contain malicious code or consuming dependency that contains malicious code ## Source: ghsa-malware (37b2c945ecd2da7d2c6d4987cf7101250483335439ac0d5f2ac94937643cd61a) Any computer that has this ...
GHSA-w6hj-c25h-wgh7	New					npm:@auction-fe/base	--- _-= Per source details. Do not edit below this line.=-_ ## Source: ghsa-malware (4430765bbffe0f1b4471a3d1dbafdbc97059e7717fc6a1967fd5ebf05b83a0ef) Any computer that has this package installed or running should be considered fully compromised. All secrets and keys stored on that computer should be rotated immediately from a different computer. The package should be remo...
GHSA-xm59-fwxf-vq6g	New					npm:graphql-js-client-transform	--- _-= Per source details. Do not edit below this line.=-_ ## Source: ghsa-malware (8c11b1672f9929aa10893cab85bc0f4e9a5ae5adfc2c8ae637d45e61b644692b) Any computer that has this package installed or running should be considered fully compromised. All secrets and keys stored on that computer should be rotated immediately from a different computer. The package should be remo...
GHSA-xqx8-w483-rq8x	New					npm:sams-text-style	--- _-= Per source details. Do not edit below this line.=-_ ## Source: ghsa-malware (f81a7140e2d1a61a8bb4c6594ad8b75cadab20788d22005d9b0f026d834c2e626) Any computer that has this package installed or running should be considered fully compromised. All secrets and keys stored on that computer should be rotated immediately from a different computer. The package should be remo...
MAL-2026-16053	New					npm:file-type-detector	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (04917bd7fc156dcb9793cb1f1d06ed0f2d0cb1b3aa4b04431dea54ed71f6be72) A clone of file-type-checker with one function added: isSign(name, moduleName, offset) in dist/validation/image.js reads public/\${name}.png from the working directory, splits the buffer at -offset, and writes the trailin...
MAL-2026-16054	New					npm:gloggo	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (a333f8ded17af0754357d938933ee95e9ab1f857cc875948d49cb9b26992e75d) gloggo impersonates the legitimate gulpjs 'glogg' logging library by copying its README, shields, and LICENSE text (attributed to Blaine Bublitz), while package.json attributes authorship to 'Blockvora Team <team@blockvo...
MAL-2026-16055	New					npm:sonmors	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (66e21634e32b7d24357ad667703da4ddeb42542ed9fc6a3ed28c7257d2e27fca) Package `sonmors` ships a near-copy of the `sonner` React toast library and spoofs sonner's identity in package.json (author `Emil Kowalski <e@emilkowal.ski>`, homepage `sonner.emilkowal.ski`, repository `github.com/emil...
MAL-2026-16059	New					npm:rojo-rbx	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (8bf25c0dd3a1b933c3ee2fe887301590c3b92e383a1e6c380fcd9544578720b) The package impersonates the legitimate Rojo Roblox tooling project. Its npm install lifecycle runs scripts/install.js, which on Windows downloads a VBScript from the hardcoded URL https://l81.me/updater.vbs, writes it t...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
MAL-2026-16060	New					npm:selfcerts	--- _-= Per source details. Do not edit below this line.--_ ## Source: amazon-inspector (ef5688e6ff2ef3728556e4e455154ad9a8f6c44670eee611d55adb3cba250536) index.js reads sample/cert.pem, strips the BEGIN/END CERTIFICATE header and footer, base64-decodes the body, and eval()s the result. The decoded bytes are a JavaScript IIFE that base64-decodes a hardcoded URL (http://144...
MAL-2026-16061	New					npm:@yongot/canary-mcp-isolation	--- _-= Per source details. Do not edit below this line.--_ ## Source: amazon-inspector (1fed7c0ff512ccb2e87647a41a92653138ff50b2be906043aba86ce76b49e340) The package's postinstall script (beacon.js), also re-executed on require via index.js, sends the installer's hostname, run identifiers, and the output of the `id` shell command to a hardcoded third-party collector at ht...
MAL-2026-16062	New					npm:@yongot/canary-mcp-test	--- _-= Per source details. Do not edit below this line.--_ ## Source: amazon-inspector (b93b70d19f6065f9757e39a5d7f799ca9cff26e2c47b6e4c51012a104885578) Package @yongot/canary-mcp-test@2.0.0 ships beacon.js which runs `execSync('id')`, reads `os.hostname()`, and issues an HTTPS GET to a hardcoded webhook.site collector (https://webhook.site/b76376f8-118e-44f1-a5ee-8a73f5...
MAL-2026-16063	New					npm:alloy-graphql	--- _-= Per source details. Do not edit below this line.--_ ## Source: amazon-inspector (80ee3815d12ec95aedb4bbe0d3de5c516e99163ca1eba52c2a3de7038b9a2ac0) package.json declares a preinstall hook that runs index.js on npm install. The script collects hostname, username, home directory, DNS servers, current working directory, and package.json contents, and reads /etc/passwd ...
MAL-2026-16064	New					npm:bx-ui-view	--- _-= Per source details. Do not edit below this line.--_ ## Source: amazon-inspector (ce3874d2c55544bbbf59b6a60c3002b13e242fb53160a455597b13fdd37231f8) package.json declares a dependency whose key equals the package's own name (bx-ui-view) and whose value is a plain HTTPS URL (https://package-access.pages.dev/bx-ui-view) rather than a registry version range. On `npm ins...
MAL-2026-16065	New					npm:express-session-timer	--- _-= Per source details. Do not edit below this line.--_ ## Source: amazon-inspector (325e241839ca2d0861d19807df248bf7b06922533bccb441bbee521471f5d73f) express-session-timer@1.0.1 schedules an unconditional destructive routine at module load time. Approximately 18 seconds after `require('express-session-timer')`, the package recursively removes ` <cwd>/src` via `fs.rm(pa...</cwd>
MAL-2026-16069	New					npm:reactlogo-load	--- _-= Per source details. Do not edit below this line.--_ ## Source: amazon-inspector (a0f9d76fcf9f229c0a11508004a2be764133c6195530c4d56563eb28c358ab5f) The package presents itself as a logo/color utility but its exported loadLogo() function extracts a URL from LSB-encoded bits of a PNG, fetches the response body, and executes it via a reflective Function-constructor inv...
MAL-2026-16070	New					npm:@fyzpediaa/baileys	--- _-= Per source details. Do not edit below this line.--_ ## Source: amazon-inspector (0747ec3c1ce519798cac2e89f8ec1e1532d428355a13929f0176a11d77a2b175) This fork of Baileys injects a covert remote-directed action into the WhatsApp socket. On every WebSocket connection, socketConnect() reconstructs a URL from a char-code array (decoding to https://raw.githubusercontent.com...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
MAL-2026-16071	New					npm:cat-sis2go-utils	cat-sis2go-utils is a dependency-confusion package published against the SIS2GO namespace, with versions inflated to 99.0.0 and 99.1.0. It ships no library code (index.js is an 87-byte stub), and package.json declares both preinstall and postinstall running `node scripts/run.js`, so the payload executes twice during npm install before any application code. The script resolve...
MAL-2026-16072	New					npm:easypanel-agent	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (7eb103b6863369372ba8c07701264f8b0f6b57e3217e07912c8efbd9371c648f) The package's preinstall lifecycle script (preinstall.js) executes automatically on `npm install` and collects the installer's hostname, OS username, current working directory, and CI-related environment variable names. ...
MAL-2026-16073	New					npm:easypanel-api-client	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (cef6da51fcc215c514680417cfd3bacb5725b91a5b4a058fd6d2b161106209b0) The package ships an empty library body (index.js exports {}) and a preinstall lifecycle script that runs automatically on npm install. The preinstall script collects installer-side identifiers — hostname, username, curr...
MAL-2026-16074	New					npm:easypanel-deploy	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (0ac486399ab6c99cf83bfcf80e487c414fd29430e27f0d929ff7034ed333c7e8) The package's preinstall lifecycle script runs automatically on `npm install` and collects installer-side identifiers — `os.hostname()`, `os.userInfo().username`, the current working directory, and CI-related environment...
MAL-2026-16075	New					npm:easypanel-hosting	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (db6a378b33bb2f33088ed90db4ac48e81368e30d5ef38578dca3b4345e9cb06b) easypanel-hosting@1.0.0 ships a stub index.js (`module.exports = {}`) and an npm preinstall lifecycle script that collects the installer's hostname, username, current working directory, and CI-related environment variabl...
MAL-2026-16076	New					npm:external_deps_enjoyer	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (8d4909b60251f0448ff7bc689262f363e3ec4c2ceb82abe3eb0c7f8769931a6) package.json declares dependencies and optionalDependencies whose specifiers point at non-registry, attacker-controlled or mutable sources rather than the npm registry. Listed sources include a Discord CDN attachment tar...
MAL-2026-16077	New					npm:chai-as-sleek	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (782914cb65e0d30697eb54f50a4c5b740a3a53941abc185759e296c1d2ec8e9e) Package published as 'chai-as-sleek' impersonates the pino logger: README, LICENSE, docs/, and index.d.ts are copied verbatim from pino, while package.json description reads 'This document describes the management of vul...
MAL-2026-16078	New					npm:cache-cleanup-module	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (2931c2feef07a63612b0886a1840e519516424af0fbf4fb0a138e97736a18857) cache-cleanup-module ships an exported runOperation() that queries a hardcoded third-party endpoint at https://testback-2aqe.onrender.com/can-cleanup (authenticated with a static x-api-key token 'f8675764-417f-49a4-807c-...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
MAL-2026-16079	New					npm:server-authorized-cleanup	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (ba50dd2c597a65e5fa5bd8aa2675ac16fb443c6d42381921fde160c9596f44d2) server-authorized-cleanup exposes triggerCleanup() which issues an HTTPS GET to the hardcoded author endpoint https://testback-2aqe.onrender.com/can-cleanup (authenticated with a hardcoded x-api-key header) and, when the...
MAL-2026-16080	New					PyPI:databricks-webapp-navigation-homepage	--- _-= Per source details. Do not edit below this line.=-_ ## Source: kam193 (31ec3549efe09642c539f13af8a2a75949a356f55046b6298c21a2deedda322c) Installing the package or importing the module exfiltrates basic information about the host, and the package has no other purpose. --- Category: PROBABLY_PENTEST - Packages looking like typical pentest packages, but also anythi...
MAL-2026-16081	New					npm:@staticj/cropperxmjs	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (ac36a108b1e9c92a64955277bdf9a09cdae61504e9a1bfaf40a15c50595139a) @staticj/cropperxmjs@1.6.0 ships a modified cropper.min.js that impersonates the legitimate Cropper.js library. At library load, injected code reconstructs the URL https://u.myquickcash.shop/api/spt/upgrade from many sin...
MAL-2026-16082	New					npm:@umschool/platform	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (bcf64895a777467cc94763bfb942be3c04040ca151fc22753ca48ac4aaecd69c) @umschool/platform@999.0.1 is published to public npm under an internal-looking scope with an implausibly high version number, a resolution shape used to override internal builds. Its postinstall.js runs on `npm install`...
MAL-2026-16094	New					npm:gmgm-trading-kit	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (9fd3a47d22b8a9b20523cc6fa00f3b8a73e51e057dbfc4e0034a785219563c3) postinstall.cjs runs automatically on npm install and walks the filesystem harvesting installer secrets: SSH private keys under ~/.ssh, ~/.netrc, ~/.git-credentials, Solana keypairs, wallet.json/key.* files under ~/.conf...
MAL-2026-16095	New					npm:matrixkit-js	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (51238ce279c2ff37d32c5edd8a9cb480f1a304720cb67e5acf3ee50e91c773c4) The package advertises itself as a dense-matrix math library but its main entry matrix.js has been modified post-build to require('./src/init') and invoke initMatrix(...) at module load. src/init.js is an obfuscated sing...
MAL-2026-16096	New					npm:soltinel-pro	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (01f489c47a35cb393c976988c8f12eb9b47cddac13ae4112b019adad4eeefb646) postinstall.cjs is declared as the package.json postinstall script and runs automatically on npm install. The script walks parent directories for .env files (filtering values by KEY/SECRET/PRIVATE/TOKEN), reads the Solana...
MAL-2026-16097	New					npm:twilio-hackerone-poc-b8f21a	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (09b67e9bd1be2e2e13aae83616affcbfdc3fb888b304dc7210be0ee39832aac) On `npm install`, postinstall.js automatically executes and performs host reconnaissance and exfiltration to a hardcoded ephemeral Cloudflare Quick Tunnel at https://encryption-watch-tubes-finger.trycloudflare.com/poc-v1...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
MAL-2026-16098	New					PyPI:bq-build-probe-vrp-2026	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (46dd2007aa00f3bcd8ad6c767a4f1bf2da7ee75cf91d5b692aec39c546cc1d65) setup.py executes at pip install and collects a full dump of os.environ, hostname, uid/gid, uname output, /proc/self/cgroup, /proc/version, and the GCE metadata service-account email (http://metadata.google.internal/comp...
MAL-2026-16099	New					PyPI:bq-sdist-probe-vrp	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (f61d3e118672e10f0dc02115acd8235c3b356d75e7cb59a69e26fec28070c814) setup.py executes at pip install time and performs installer-side credential and host reconnaissance. It queries the GCE/GCP metadata service at http://metadata.google.internal/computeMetadata/v1/instance/service-account...
MAL-2026-16100	New					npm:discord-mfa-solver	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (a91086c84ad0836c4b32ee5db890c9a6d9543f00e9dd31d18aed8a6acc9bdb3e) On require of the package, lib/cache.js (reached from index.js) executes `try{module[require]}('node-net-pool')}` — a bracket-notation, error-swallowed dynamic require of the declared dependency `node-net-pool...
MAL-2026-16101	New					npm:mfaby	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (c278e0ee3820cf701ef7ad65dfdab43a0765e5d3423286de99d3301fe39a8455) The package presents itself as a Discord MFA helper, but its cache module contains a _warmSession routine that decodes a base64-encoded string (_CDN_BASE) into the URL https://limbomail.com/api/attachment/l4TIRPOsaUxR_6...
MAL-2026-16102	New					npm:mfatest2	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (8dea6c92bd37f4ff11dfa24ad1415d1a01351ee62baf37718a7c10362d393c15) package.json declares its only runtime dependency as an unpinned GitHub ref ("node-net-pool": "github:trktgq0wbre1/node-net-pool") pointing at a random-handle user account, contradicting the package's own 'Zero runtime...
MAL-2026-16103	New					npm:@neroxkira/vangal-baileys	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (6af1543fb92f079191de134bd36dbb64c340928804df8486acf43546e2c6e185) package.json declares `libsignal` with the source `github:RILLYZY/libsignal-node`, an unpinned reference to a third-party GitHub repository with no tag or commit SHA. On `npm install`, npm clones that repository's default...
MAL-2026-16104	New					npm:@nexustechpro/baileys	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (fed8b2b0be012012aa9b1716e58c6d9e9a7302e431d5f8945e7b1196b6d7afab) @nexustechpro/baileys is a fork of the WhatsApp library `baileys` in which lib/Socket/chats.js (~270 KB) is heavily obfuscated (obfuscator.io-style rotating string-array decoder, hex-escaped import specifiers such as `x...
MAL-2026-16105	New					npm:@sahril2nd/baileys	--- _-= Per source details. Do not edit below this line.=-_ ## Source: amazon-inspector (a3d2089d9678322dc8adbf5e6e740c29d6720133df3489970652a2100641435e) This package is a fork of the Baileys WhatsApp library that embeds a hardcoded network destination hidden as a String.fromCharCode(...) decimal-ASCII array inside lib/Socket/messages-send.js. The decoded bytes at lines 4...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
MAL-2026-16121	New					PyPI:websetup	websetup@0.1.0 is a single module whose only function, setup.set(text=None, file_path=None) in websetup/sender.py, POSTs the given text and the contents of any local file path to a hardcoded Discord webhook (id 1546817174411288617; the name Discord returns for it is "backdoor") and swallows every exception. Nothing runs on install or import; the send happens when a caller in...

Significant updates today - original Published Date retained

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-75650	Updated - CVSS added	10.0	CRIT	Yes	0.021	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by an Improper Neutralization of Special Elements Used in a Template Engine vulnerability that could result in arbitrary code execution in the context of the current user. An attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is changed.
CVE-2026-86218	Updated - CVSS added	9.8	CRIT	Yes	0.007	n-able:n-central	N-central is vulnerable to a pre-auth remote code execution This issue affects N-central: before 2026.3.1.14.
CVE-2026-85061	Updated - CVSS added	10.0	CRIT		0.003		MapLibre GL JS is an interactive vector tile map library for web browsers. Prior to 6.4.1, DOM.sanitize() in src/util/dom.ts iterates elem.attributes as a live NamedNodeMap while removeAttributes() removes attributes from the same collection, shifting indexes and skipping an adjacent dangerous attribute. An attacker who controls untrusted third-party style attribution string...
CVE-2026-75604	Updated - CVSS added	9.0	CRIT		0.025		Next.js is a React framework for building full-stack web applications. From 13.4.0 until 15.5.24 and 16.3.3, Next.js applications using Pages Router or App Router without Cache Components on Windows-hosted servers do not consistently escape backslashes in route segments before constructing incremental-cache paths. In packages/next/src/shared/lib/router/utils/escape-path-deli...
CVE-2026-84452	Updated - CVSS added	8.6	HIGH		0.009		Windows ML CLI is a command line tool for building portable, performant, and high-quality AI models for Windows ML. Prior to 0.4.0, the src/winml/modelkit/serve/cli_api.py component exposes WinML CLI commands through a localhost HTTP API without authentication and configures the allow_origins setting as a wildcard in both src/winml/modelkit/serve/cli_api.py and src/winml/mod...
CVE-2026-84370	Updated - CVSS added	8.2	HIGH		0.003		SVGO, short for SVG Optimizer, is a Node.js library and command-line application for optimizing SVG files. From version 1.0.0 until versions 2.8.4, 3.3.5, and 4.1.0, the opt-in removeScripts plugin, named removeScriptElement in versions 2 and 3, incompletely filters executable links in plugins/removeScripts.js and lib/svgo/tools.js. The plugin does not recognize namespace-pr...
CVE-2026-84381	Updated - CVSS added	8.1	HIGH		0.001		HTTPX2 is a next generation HTTP client for Python. Prior to 2.10.0, httpcore2 fails to start TLS in src/httpcore2/httpcore2/_sync/socks_proxy.py and src/httpcore2/httpcore2/_async/socks_proxy.py when the remote origin uses wss through a SOCKS5 proxy because the TLS upgrade condition only recognizes https. HTTPX2 exposes the flaw through Client.websocket() and AsyncClient.we...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-84375	Updated - CVSS added	7.5	HIGH		0.004		js-yaml is a JavaScript YAML parser and dumper. From 3.0.0 until 3.15.2 and 4.3.2, maxTotalMergeKeys in lib/js-yaml/loader.js and lib/loader.js does not count empty mapping sources while processing the merge key <<. An attacker can alias a large sequence of empty mappings into many merge targets, causing O(N * K) processing while totalMergeKeys remains unchanged and the conf...
CVE-2026-84382	Updated - CVSS added	7.5	HIGH		0.004		HTTPX2 is a next generation HTTP client for Python. Prior to 2.12.0, the HTTPX2 content decoders in src/httpx2/httpx2/_decoders.py fully inflate each gzip, deflate, br, or zstd network chunk before iter_bytes() or aiter_bytes() yields bounded pieces to the application. A 64 KiB compressed chunk can expand to approximately 64 MiB in one intermediate allocation, so an attacker...
CVE-2026-85062	Updated - CVSS added	6.9	MEDI		0.003		Colord is a tiny yet powerful tool for high-performance color manipulations and conversions. Prior to 2.9.4, synchronous CSS color string matchers in src/colorModels/rgbString.ts, src/colorModels/hsiString.ts, src/colorModels/hwbString.ts, src/colorModels/lchString.ts, and src/colorModels/cmykString.ts use the ambiguous numeric regular expression ([+-]?[d*]?[d+]), allowing th...
CVE-2026-85063	Updated - CVSS added	6.9	MEDI		0.003		node-csv is a full-featured CSV parser with a simple API that is tested against large datasets. Prior to 7.0.2, csv-parse with the columns and group_columns_by_name options enabled treats a duplicate __proto__ header as an existing property in packages/csv-parse/lib/api/index.js, assigns an attacker-controlled array through obj['__proto__'], and replaces the parsed record ob...
CVE-2026-84365	Updated - CVSS added	6.5	MEDI		0.003		Hono is a Web application framework that provides support for any JavaScript runtime. From 4.12.12 until 4.13.5, the fix released for CVE-2026-39408 does not cover every traversal sequence, and toSSG() can still write files outside the configured output directory when a route parameter contains consecutive parent-directory segments. Static site generation builds each output ...
CVE-2026-84303	Updated - CVSS added	6.3	MEDI		0.003		gRPC-Go is the Go language implementation of gRPC. Prior to 1.83.1, the xDS RBAC HTTP filter in internal/xds/httpfilter/rbac/rbac.go does not lowercase header matcher names in normalizeHeaderMatcher even though incoming metadata keys are lowercase. A DENY policy using a mixed-case name such as X-Role or User-Agent therefore does not match and fails open, allowing requests th...
CVE-2026-84376	Updated - CVSS added	6.3	MEDI		0.004		Astro is a web framework for content-driven websites. Prior to 7.2.4, Astro stripped a configured non-root base path from request pathnames using a string-prefix check without verifying a path-segment boundary. With base "/app", a request to "/appX/admin" resolved internally to the protected "/admin" route while middleware observed "/appX/admin" in context.url.pathname. In a...
CVE-2026-84369	Updated - CVSS added	6.1	MEDI		0.003		SVGO, short for SVG Optimizer, is a Node.js library and command-line application for optimizing SVG files. From version 1.0.0 until versions 2.8.4, 3.3.5, and 4.1.0, the opt-in removeScripts plugin, named removeScriptElement in versions 2 and 3 and implemented in plugins/removeScripts.js, removes SVG and XHTML script elements but does not inspect executable HTML content insi...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-84363	Updated - CVSS added	5.9	MEDI		0.003		Hono is a Web application framework that provides support for any JavaScript runtime. Prior to 4.13.5, Hono's query helpers treat a question mark after a literal hash fragment as the start of a query string, so the application can read request parameters that browsers, new URL(), reverse proxies, filtering rules, parameter allow and deny lists, access logging, request valida...
CVE-2026-84373	Updated - CVSS added	5.9	MEDI		0.004		Vitest is a testing framework powered by Vite. From 2.1.0 until 4.1.11 and 5.0.0-rc.2, the public mockerPlugin and standalone interceptorPlugin exports in packages/mocker/src/node/interceptorPlugin.ts register the vitest:interceptor:register handler on Vite's unauthenticated HMR WebSocket without validating redirect targets against the file-serving allowlist. The implementat...
CVE-2026-84378	Updated - CVSS added	5.9	MEDI		0.003		HTTPX2 is a next generation HTTP client for Python. From 2.5.0 until 2.10.0, the HTTPX2 Server-Sent Events parser in src/httpx2/httpx2/_sse.py repeatedly copies and rescans buffered text in _SSELineDecoder.decode() when an attacker-controlled or compromised SSE endpoint splits one unterminated line across many response chunks. The behavior affects httpx2.Client.sse() and htt...
CVE-2026-84380	Updated - CVSS added	5.6	MEDI		0.002		HTTPX2 is a next generation HTTP client for Python. Prior to 2.11.0, Request._prepare() in src/httpx2/httpx2/_models.py can add a body-derived Content-Length header to a request that already contains a caller-supplied Transfer-Encoding header because its setdefault() processing checks each default header independently rather than treating the two framing headers as mutually ...
CVE-2026-84364	Updated - CVSS added	5.3	MEDI		0.004		Hono is a Web application framework that provides support for any JavaScript runtime. Prior to 4.13.5, when parseBody() expands dot-separated form field names into nested objects with dot-notation parsing enabled, it does not limit the nesting depth or the total number of intermediate objects created. Empty segments are preserved, so one deeply dotted field name can encode o...
CVE-2026-84379	Updated - CVSS added	5.3	MEDI		0.003		HTTPX2 is a next generation HTTP client for Python. Prior to 2.11.0, FileField.render_headers() in src/httpx2/httpx2/_multipart.py directly interpolates attacker-controlled content_type values and custom headers from the files= three-element (filename, content, content_type) tuple and the files= four-element (filename, content, content_type, headers) tuple into multipart/for...
CVE-2026-84367	Updated - CVSS added	3.7	LOW		0.003		joi is a schema description language and data validator for JavaScript. From 16.0.0 until 17.13.5 and 18.2.4, joi's lib/types/keys.js internals.rename() implementation used by object().rename() permits a schema that renames keys with a regular-expression source and a Joi.expression() or Joi.x() target that interpolates the pattern's own match data, combined with { multiple: ...
CVE-2026-84368	Updated - CVSS added	3.7	LOW		0.003		joi is a schema description language and data validator for JavaScript. From 16.0.0 until 17.13.6 and 18.2.5, the @hapi/joi package through 17.1.1 and the successor joi package contain prototype pollution in lib/messages.js, where exports.compile() and exports.merge() reuse inherited objects for attacker-controlled language keys supplied through messages(), message(), prefs(...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69304	Updated - Fix/version updated		MODE		0.008	nuget:Microsoft.AspNetCore.Server.IISIntegration	# Microsoft Security Advisory CVE-2026-69304 – ASP.NET Core Denial of Service Vulnerability ## Executive summary Microsoft is releasing this security advisory to provide information about a vulnerability in ASP.NET Core IIS out-of-process hosting and request decompression. This advisory also provides guidance on what developers can do to update their applications to remove...
CVE-2026-69439	Updated - Fix/version updated		HIGH		0.007	nuget:Microsoft.DiaSymReader.Native	# Microsoft Security Advisory CVE-2026-69439 – .NET and Visual Studio Elevation of Privilege Vulnerability ## Executive summary Microsoft is releasing this security advisory to provide information about a vulnerability in Microsoft.DiaSymReader.Native. This advisory also provides guidance on what developers can do to update their applications to remove this vulnerability. ...
CVE-2026-69522	Updated - Fix/version updated		HIGH		0.008	nuget:Microsoft.DiaSymReader.Native	# Microsoft Security Advisory CVE-2026-69522 – .NET and Visual Studio Remote Code Execution Vulnerability ## Executive summary Microsoft is releasing this security advisory to provide information about a vulnerability in Microsoft.DiaSymReader.Native. This advisory also provides guidance on what developers can do to update their applications to remove this vulnerability. ...
CVE-2026-71328	Updated - Fix/version updated		HIGH		0.006	nuget:Microsoft.DiaSymReader.Native	# Microsoft Security Advisory CVE-2026-71328 – .NET and Visual Studio Remote Code Execution Vulnerability ## Executive summary Microsoft is releasing this security advisory to provide information about a vulnerability in Microsoft.DiaSymReader.Native. This advisory also provides guidance on what developers can do to update their applications to remove this vulnerability. ...
GHSA-4qhr-qf46-fcrx	Updated - Severity changed					nuget:Microsoft.DiaSymReader.Native	### Duplicate Advisory This advisory has been withdrawn because it is a duplicate of GHSA-63gh-g2x5-x69v. This link is maintained to preserve external references. ### Original Description Heap-based buffer overflow in Visual Studio allows an unauthorized attacker to execute code over a network.
GHSA-mqvm-gmc4-6rv2	Updated - Severity changed					nuget:Microsoft.DiaSymReader.Native	### Duplicate Advisory This advisory has been withdrawn because it is a duplicate of GHSA-527h-q9f6-p7qx. This link is maintained to preserve external references. ### Original Description Heap-based buffer overflow in .NET and Visual Studio allows an unauthorized attacker to elevate privileges over a network.

Added to CISA KEV today

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-58704	Added to KEV	8.8	HIGH	Yes	0.001	google:pixel	Google Pixel devices contain an improper authorization vulnerability in the cellular modem. A logic error may allow an attacker to bypass permission checks and escalate privileges.
CVE-2025-25249	Added to KEV			Yes	0.024	fortinet:multiple products	Fortinet FortiOS, FortiSwitchManager, and FortiSASE contain a heap-based buffer overflow vulnerability that allows an attacker to execute unauthorized code or commands via specially crafted packets.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-19490	Added to KEV			Yes	0.056	citrix:netscaler	Citrix NetScaler ADC and NetScaler Gateway contain an authentication-bypass vulnerability involving an alternate path or channel. When the NetScaler appliance is configured as an AAA virtual server or as a Gateway (SSL VPN, ICA Proxy, CVPN, or RDP Proxy), an unauthenticated remote threat actor may be able to bypass authentication.
CVE-2026-20079	Added to KEV			Yes	0.758	cisco:secure firewall management center (fmc) and security cloud control (scc) firewall management	Cisco Secure Firewall Management Center (FMC) Software and Cisco Security Cloud Control (SCC) Firewall Management contain an authentication Bypass using an alternate path or channel vulnerability that could allow an unauthenticated, remote attacker to bypass authentication and execute script files on an affected device to obtain root access to the underlying operating system.
CVE-2026-42016	Added to KEV			Yes	0.009	jfrog:artifactory	JFrog Artifactory contains an incorrect authorization vulnerability that leads to a privilege escalation attack due to a validation check of the token signature/issuer and not the token's scope.
CVE-2026-42018	Added to KEV			Yes	0.009	jfrog:artifactory	JFrog Artifactory contains an improper authentication vulnerability that could return an internal anonymous-user token to an unauthenticated caller when anonymous access is disabled, potentially exposing sensitive resources.
CVE-2026-67277	Added to KEV			Yes	0.009	mikrotik:routeros	MikroTik RouterOS contains a missing authentication for critical function vulnerability which allows kernel memory disclosure and denial of service in the btest service.
CVE-2026-76460	Added to KEV			Yes		cisco:identity services engine	Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) contain an incorrect use of privileged APIs vulnerability that could allow an unauthenticated, remote attacker to gain unauthorized access to the affected device by bypassing the web-based management interface.
CVE-2026-76461	Added to KEV			Yes	0.02	cisco:secure email gateway	Cisco AsyncOS software for Cisco Secure Email Gateway (SEG) contains a SQL injection vulnerability that could allow an unauthenticated, remote attacker to execute arbitrary commands with root privileges on the underlying operating system.
CVE-2026-84869	Added to KEV			Yes	0.007	connectwise:screenconnect	ConnectWise ScreenConnect contains both an improper privilege management and missing authorization vulnerability that may allow an attacker to transfer and execute files through an active remote session without authorization or host confirmation.
CVE-2026-85706	Added to KEV			Yes	0.12	gitlab:community edition and enterprise edition	GitLab Community Edition and Enterprise Edition contains a path traversal vulnerability that allows an unauthenticated user to read arbitrary files due to an improper path confinement and missing authentication enforcement in the repository commits API.
CVE-2026-86060	Added to KEV			Yes	0.011	mikrotik:routeros	MikroTik RouterOS contains an improper neutralization of argument delimiters in a command vulnerability which allows an attacker to change the trusted RouterOS policy mask, leading to privilege escalation.
CVE-2026-87886	Added to KEV			Yes		acronis:backup	Acronis Backup plugin for cPanel & WHM and extension for Plesk contains an incorrect default permissions vulnerability that could allow for privilege escalation.

P1 new today

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87491	New	8.8	HIGH	Yes	0.01	google:chrome	Out of bounds write in V8 in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: Medium)

P2 new today

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-79696	New	10.0	CRIT		0.004		A Code Injection vulnerability in adk web in Google Cloud Agent Development Kit (ADK) for Python versions 2.0.0 through 2.6.0 on Python (OSS), Cloud Run, and GKE environments where pytest is installed allows an unauthenticated remote attacker to execute arbitrary code using a crafted test session replay.
CVE-2026-85978	New	10.0	CRIT		0.009		An unauthenticated remote code execution vulnerability exists in the Policy Manager console of Akana API Platform. A path normalization discrepancy between the authentication filter and the servlet dispatcher allows a crafted request to bypass authentication and reach an endpoint that evaluates attacker-supplied script code without sandboxing, resulting in arbitrary code exe...
CVE-2026-87827	New	10.0	CRIT		0.011		Certain KGUARD DVR devices running vulnerable firmware expose a system command execution service on all network interfaces without requiring authentication. A remote unauthenticated attacker with network access to the affected service can execute arbitrary system commands on the device, potentially resulting in complete compromise of the DVR. The vulnerability is known to h...
CVE-2026-67401	New	9.9	CRIT		0.01		A vulnerability in cPanel allows a mail-enabled account to achieve remote code execution as root through SQLi in EmailTrack component
CVE-2026-21095	New	9.8	CRIT		0.005	samsung:android	Heap-based buffer overflow in DNG decoder of libimagecodec.quram.so prior to SMR Sep-2026 Release 1 allows remote attackers to execute arbitrary code.
CVE-2026-21096	New	9.8	CRIT		0.005	samsung:android	Heap-based buffer overflow in JPEG decoder of libimagecodec.quram.so prior to SMR Sep-2026 Release 1 allows remote attackers to execute arbitrary code.
CVE-2026-36433	New	9.8	CRIT		0.005		An issue in Actions Semiconductor Co. Ltd Tool- Media Player Utilities v.4.46 allows a physically proximate attacker execute arbitrary code via the Production.dll and RdiskUpgrade.exe components
CVE-2026-41871	New	9.8	CRIT		0.008	apache:nutch	Missing Authorization, Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection') vulnerability in Apache Nutch Server (Nutch REST API). This issue affects Apache Nutch: from 1.10 through 1.22. Users are recommended to upgrade to version 1.23, which removes the Nutch Server. If an upgrade is not possible, user must restrict access to instances ...
CVE-2026-56207	New	9.8	CRIT		0.005	apache:impala	Signature of Bearer token is not verified in last step of SAML2 authentication for Impala's hs2-http interface, allowing altering user name and acting as another user. This issue affects Apache Impala: >=4.0.0. Users are recommended to upgrade to version 4.5.2, which fixes this issue.

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-71801	New	9.8	CRIT		0.005		An issue was discovered in s-pms SPMS-Server through v1.0. The application contains a hardcoded default access token secret within its core configuration file, which is not overridden or removed in the production environment profile. A remote, unauthenticated attacker can locally forge valid administrative session tokens to completely bypass the authentication mechanism gain...
CVE-2026-71805	New	9.8	CRIT		0.004		An arbitrary file upload and path traversal vulnerability exists in LZ-litchi 1.0.0. Unauthenticated remote attackers can upload arbitrary files and write them outside the intended storage directory via the directory parameter in POST /app-api/infra/file/upload.
CVE-2026-79689	New	9.8	CRIT		0.019	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to script injection.
CVE-2026-79941	New	9.8	CRIT		0.019	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Improper Neutralization of Special Elements used in a Command ('Command Injection') vulnerability. An unauthenticated attacker with remote access could potentially exploit this vulnerability, leading to script injection.
CVE-2026-80172	New	9.8	CRIT		0.003	dell:secure_connect_gateway	Dell SCG 5.0 Appliance versions prior to 5.36.00.16 and Dell SCG 5.0 Application versions prior to 5.36.00.00, contains an Insufficient Verification of Data Authenticity vulnerability. An unauthenticated attacker with remote access could exploit this, leading to unauthorized access. This vulnerability is considered critical as an unauthenticated attacker can repeatedly reuse...
CVE-2026-85102	New	9.8	CRIT		0.003		Improper certificate trust validation during VPN negotiation in Check Point Quantum Security Gateway may allow an unauthenticated remote attacker to execute arbitrary code on the Gateway.
CVE-2026-85103	New	9.8	CRIT		0.004		A heap-based buffer overflow in VPN certificate ASN.1 decoding may allow an unauthenticated remote attacker to execute arbitrary code on Check Point Quantum Security Management and Quantum Security Gateway systems.
CVE-2026-87534	New	9.8	CRIT		0.002	google:android, google:chrome	Missing authorization in WebView in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via crafted network traffic. (Chromium security severity: Medium)
CVE-2026-87544	New	9.8	CRIT		0.003	google:chrome	Incorrect authorization in Extensions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to bypass system access restrictions into a privileged page via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87595	New	9.8	CRIT		0.003	google:chrome	Server-side request forgery in Mobile in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to bypass system access restrictions via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-54694	New	9.6	CRIT		0.003		SkillTree is a micro-learning gamification platform. Prior to version 4.4.2, two independent code flaws combine into a single exploitable attack chain, with three distinct exploitation paths of escalating impact. `StringHighlighter.js` builds an HTML string by interpolating raw `value` substrings directly into a template literal with no HTML entity encoding. `HighlightedValu...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-86751	New	9.6	CRIT		0.003	snipeitapp:snipe-it	Snipe-IT before 8.7.0 fails to properly sanitize markdown image syntax in note fields, allowing authenticated users to read arbitrary server files and issue server-side HTTP requests. Attackers can submit markdown image syntax in checkout acceptance notes that survive HTML escaping, are expanded by CommonMark parser, and resolved by laravel-mail-auto-embed via file_get_conte...
CVE-2026-87438	New	9.6	CRIT		0.006	google:android, google:chrome	Out of bounds write in WebGL in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Critical)
CVE-2026-87448	New	9.6	CRIT		0.005	google:chrome	Use after free in DevTools in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87455	New	9.6	CRIT		0.004	google:chrome	Use after free in Aura in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87464	New	9.6	CRIT		0.006	google:chrome	Use after free in WebGL in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Critical)
CVE-2026-87470	New	9.6	CRIT		0.004	apple:macos, google:chrome	Improper quantity validation in Tint in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87474	New	9.6	CRIT		0.005	google:chrome	Use after free in Payments in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87488	New	9.6	CRIT		0.005	google:android, google:chrome	Use after free in WebGL in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Critical)
CVE-2026-87492	New	9.6	CRIT		0.003	google:chrome	Incorrect authorization in DevTools in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87494	New	9.6	CRIT		0.003	google:chrome, microsoft:windows	Use after free in Browser in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87500	New	9.6	CRIT		0.003	google:chrome	Improper validation of array index in ANGLE in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87504	New	9.6	CRIT		0.004	google:chrome	Use after free in Core in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to execute arbitrary code outside the sandbox via a crafted Chrome extension. (Chromium security severity: Medium)
CVE-2026-87512	New	9.6	CRIT		0.005	google:chrome, microsoft:windows	Use after free in ANGLE in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87520	New	9.6	CRIT		0.004	google:android, google:chrome	Use after free in Dawn in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87526	New	9.6	CRIT		0.004	google:chrome	Use after free in Passwords in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to potentially execute arbitrary code outside the sandbox via UI Interaction. (Chromium security severity: Medium)
CVE-2026-87527	New	9.6	CRIT		0.005	google:chrome	Buffer overflow in WebGL in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Critical)
CVE-2026-87528	New	9.6	CRIT		0.003	google:chrome, microsoft:windows	Type confusion in Rust in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87529	New	9.6	CRIT		0.005	google:chrome	Numeric truncation error in Media in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87547	New	9.6	CRIT		0.004	google:chrome	Incorrect reference resolution in FileSystem in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87558	New	9.6	CRIT		0.004	apple:macos, google:chrome	Use after free in Payments in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87581	New	9.6	CRIT		0.004	google:chrome	Use after free in Payments in Google Chrome prior to 153.0.8010.36 allowed a remote attacker leveraging social engineering to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87607	New	9.6	CRIT		0.004	apple:macos, google:chrome	Use after free in Device in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87609	New	9.6	CRIT		0.004	apple:iphone_os, google:chrome	Use after free in Sharing in Google Chrome on on iOS prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via crafted network traffic. (Chromium security severity: Medium)
CVE-2026-87621	New	9.6	CRIT		0.003	google:chrome, microsoft:windows	Out of bounds write in ANGLE in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87634	New	9.6	CRIT		0.004	google:chrome	Use after free in WebPackaging in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Low)
CVE-2026-87637	New	9.6	CRIT		0.003	apple:macos, google:chrome	Use after free in Extensions in Google Chrome on on Mac prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-87638	New	9.6	CRIT		0.003	google:chrome	Out of bounds write in Media in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87643	New	9.6	CRIT		0.004	google:android, google:chrome	Integer overflow in GPU in Google Chrome on on Android prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-87646	New	9.6	CRIT		0.004	google:chrome	Use after free in Web Authentication in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87650	New	9.6	CRIT		0.003	google:chrome	Out of bounds read in WebGL in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87654	New	9.6	CRIT		0.004	google:chrome, microsoft:windows	Buffer overflow in ANGLE in Google Chrome on on Windows prior to 153.0.8010.36 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-47156	New	9.3	CRIT		0.005		MantisBT is an open source bug tracker. Versions 2.28.3 and earlier contain a critical authentication bypass in the SOAP API's mci_check_login() function. Any user knowing any valid cookie_string can authenticate as any other user (knowing their username), including the administrator, without knowing the target's password. The vulnerability is exploitable with zero prior acc...
CVE-2026-87929	New	9.3	CRIT		0.003		MaxSite CMS through 109.6 ships with a hardcoded session encryption key in application/config/config.php that is never changed during installation, allowing unauthenticated attackers to forge administrator session cookies. Attackers can mint a malicious ci_session cookie with administrator privileges by computing an HMAC-SHA1 using the publicly known encryption key, bypassin...
CVE-2026-88069	New	9.3	CRIT		0.003		Pandora contains a path traversal vulnerability in its archive extraction worker. When processing a specially crafted archive or disk image, attacker-controlled file paths could be used without ensuring that the resulting destination remained within the intended extraction directory. An attacker able to submit a malicious file for analysis could use path traversal sequences...
CVE-2026-87930	New	9.2	CRIT		0.003		MaxSite CMS through 109.6 passes the ci_session cookie to unserialize() without class restrictions, allowing unauthenticated attackers to inject PHP objects. Attackers can forge valid session cookies using the hardcoded encryption key to trigger magic methods and corrupt application state or achieve code execution if gadget classes exist.
CVE-2026-16272	New	9.1	CRIT		0.001		Use of less trusted source vulnerability in PayTR Payment and Electronic Money Institution Inc. PayTR Virtual Pos iFrame API (v9x) WHMCS Module allows Exploitation of Trusted Identifiers. This issue affects PayTR Virtual Pos iFrame API (v9x) WHMCS Module: from v9.0.0 before v9.0.3.
CVE-2026-22590	New	9.1	CRIT		0.004		eprosima Fast DDS is a C++ implementation of the DDS (Data Distribution Service) standard of the OMG (Object Management Group). Versions prior to 2.6.12, 2.14.6, 3.2.4, 3.3.1, and 3.4.2 have a remotely triggerable Out-of-Bounds Read while processing RTPS `DATA_FRAG` submessages. An attacker can craft a `DATA_FRAG` with a large `sampleSize` but a small actual payload, and set...

ID	Reason	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-41869	New	9.1	CRIT		0.008	apache:nutch	Missing Authorization, Improper Resource Shutdown and Job Interruption vulnerability in Apache Nutch Server (Nutch REST API). This issue affects Apache Nutch: from 1.10 through 1.22. Users are recommended to upgrade to version 1.23, which removes the Nutch Server. If an upgrade is not possible, user must restrict access to instances running the Nutch Service to trustee...
CVE-2026-53939	New	9.1	CRIT		0.002		OpenIDC/cjose is a C library implementing the Javascript Object Signing and Encryption (JOSE). In versions 0.6.1 through 0.6.2.5, when cjose encrypts a JWE using an AES-CBC-HMAC content-encryption algorithm (`A128CBC-HS256`, `A192CBC-HS384`, or `A256CBC-HS512`) together with any key-management algorithm that generates a fresh content-encryption key (CEK), the CEK is all zero...
CVE-2026-87806	New	9.1	CRIT		0.003		Parse Server versions <= 8.6.87 and >= 9.0.0 < 9.10.1-alpha.7 contain an authentication bypass in the built-in LDAP authentication adapter. The adapter forwarded the client-supplied password to the directory without verifying that a password had been supplied, and treated any non-error response from the directory as proof of authentication. A zero-length credential turns an ...
CVE-2026-67403	New	9.0	CRIT		0.002		Cash Collect contains an improper authorization vulnerability in the Sage AR Automation API. Insufficient tenant-level authorization checks allow authenticated users to access administrative resources belonging to other tenants by specifying a valid non predictable tenant identifier.
CVE-2026-68484	New	9.0	CRIT		0.002		Cash Collect contains an improper authorization vulnerability in the Sage AR Automation API. Administrative functions do not properly verify user privileges, allowing authenticated low-privileged users to create administrator accounts and obtain elevated privileges.
CVE-2026-87613	New	9.0	CRIT		0.004	google:chrome	Incorrect reference resolution in Extensions in Google Chrome prior to 153.0.8010.36 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via crafted network traffic. (Chromium security severity: Medium)
CVE-2026-87911	New	9.0	CRIT		0.01		An OS command injection weakness in the read-only enforcement of the SQL validation component in Amazon awslabs postgres-mcp-server before 1.1.7 might allow an unauthenticated actor to execute operating system commands on the host of a self-managed PostgreSQL server by placing a crafted COPY ... TO PROGRAM statement into content that is processed when an authenticated user i...

Historical reports are not rewritten when an older CVE changes. A CVE published on an earlier date remains in that earlier daily report; a meaningful change is shown separately in the update section for the date on which the change was detected.