

Daily Vulnerability Report - 2026-09-08

Window (UTC): 2026-09-08T00:00 to 2026-09-09T00:00 | Sources: NVD, CISA KEV, EPSS, Vulnrichment, GHSA, OSV | Generated 2026-09-17 09:49:10 UTC

Total	New	Updated	KEV	Critical	High	Medium	Unscored	Watchlist	Packages
2446	1585	861	19	207	1280	801	109	488	150

P1 - Act now (KEV / high EPSS)

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-84869 New	9.9	CRIT	Yes	0.007	connectwise:screenconnect	A condition in the ScreenConnect client may allow files to be transferred and executed through an active remote session without authorization or Host confirmation in certain circumstances. ScreenConnect servers are not impacted.
CVE-2026-58704 Added to KEV	8.8	HIGH	Yes	0.001	google:pixel	Google Pixel devices contain an improper authorization vulnerability in the cellular modem. A logic error may allow an attacker to bypass permission checks and escalate privileges.
CVE-2026-85046 Newly scored	8.8	HIGH	Yes	0.015	google:chrome, google:v8	Type confusion in V8 in Google Chrome prior to 152.0.7977.82 allowed a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-87491 Added to KEV	8.8	HIGH	Yes	0.01	google:chromium v8	Google Chromium V8 contains an out of bounds write vulnerability that allows a remote attacker to execute arbitrary code inside the sandbox via a crafted HTML page. This vulnerability could affect multiple web browsers that utilize Chromium, including, but not limited to, Google Chrome, Microsoft Edge, and Opera.
CVE-2026-81963 New	7.8	HIGH	Yes	0.006	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Improper link resolution before file access ('link following') in Windows Update Stack allows an authorized attacker to elevate privileges locally.
CVE-2026-85880 New	7.8	HIGH	Yes	0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows ALPC allows an authorized attacker to elevate privileges locally.
CVE-2025-25249 Added to KEV			Yes	0.024	fortinet:multiple products	Fortinet FortiOS, FortiSwitchManager, and FortiSASE contain a heap-based buffer overflow vulnerability that allows an attacker to execute unauthorized code or commands via specially crafted packets.
CVE-2026-19490 Added to KEV			Yes	0.056	citrix:netscaler	Citrix NetScaler ADC and NetScaler Gateway contain an authentication-bypass vulnerability involving an alternate path or channel. When the NetScaler appliance is configured as an AAA virtual server or as a Gateway (SSL VPN, ICA Proxy, CVPN, or RDP Proxy), an unauthenticated remote threat actor may be able to bypass authentication.
CVE-2026-20079 Added to KEV			Yes	0.758	cisco:secure firewall management center (fmc) and security cloud control (scc) firewall management	Cisco Secure Firewall Management Center (FMC) Software and Cisco Security Cloud Control (SCC) Firewall Management contain an authentication Bypass using an alternate path or channel vulnerability that could allow an unauthenticated, remote attacker to bypass authentication and execute script files on an affected device to obtain root access to the underlying operating system.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-42016 Added to KEV			Yes	0.009	jfrog:artifactory	JFrog Artifactory contains an incorrect authorization vulnerability that leads to a privilege escalation attack due to a validation check of the token signature/issuer and not the token's scope.
CVE-2026-42018 Added to KEV			Yes	0.009	jfrog:artifactory	JFrog Artifactory contains an improper authentication vulnerability that could return an internal anonymous-user token to an unauthenticated caller when anonymous access is disabled, potentially exposing sensitive resources.
CVE-2026-67277 Added to KEV			Yes	0.009	mikrotik:routeros	MikroTik RouterOS contains a missing authentication for critical function vulnerability which allows kernel memory disclosure and denial of service in the btest service.
CVE-2026-75650 Added to KEV			Yes	0.021	adobe:commerce and magento	Adobe Commerce and Magento Open Source contain an improper neutralization of special elements used in a template engine vulnerability that could allow an attacker to execute arbitrary code.
CVE-2026-76460 Added to KEV			Yes		cisco:identity services engine	Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) contain an incorrect use of privileged APIs vulnerability that could allow an unauthenticated, remote attacker to gain unauthorized access to the affected device by bypassing the web-based management interface.
CVE-2026-76461 Added to KEV			Yes	0.02	cisco:secure email gateway	Cisco AsyncOS software for Cisco Secure Email Gateway (SEG) contains a SQL injection vulnerability that could allow an unauthenticated, remote attacker to execute arbitrary commands with root privileges on the underlying operating system.
CVE-2026-85706 Added to KEV			Yes	0.12	gitlab:community edition and enterprise edition	GitLab Community Edition and Enterprise Edition contains a path traversal vulnerability that allows an unauthenticated user to read arbitrary files due to an improper path confinement and missing authentication enforcement in the repository commits API.
CVE-2026-86060 Added to KEV			Yes	0.011	mikrotik:routeros	MikroTik RouterOS contains an improper neutralization of argument delimiters in a command vulnerability which allows an attacker to change the trusted RouterOS policy mask, leading to privilege escalation.
CVE-2026-86218 Added to KEV			Yes	0.007	n-able:n-central	N-able N-central contains a static code injection vulnerability that could allow for pre-authentication remote code execution.
CVE-2026-87886 Added to KEV			Yes		acronis:backup	Acronis Backup plugin for cPanel & WHM and extension for Plesk contains an incorrect default permissions vulnerability that could allow for privilege escalation.
CVE-2026-60004 Updated		CRIT		0.868	go:gitea.dev fixed: 1.27.1	### Summary Gitea's `diffpatch` endpoint can be abused to install and execute a Git hook from repository-controlled content. An attacker with ordinary write access to a repository can execute arbitrary shell commands as the Gitea OS user. With default open registration, an unauthenticated visitor can obtain the required write access by registering an account and creating a repository. ### Details `services/rep...

P2 - High (CVSS >= 9.0 or 7.0+ with EPSS >= 0.10)

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-44756 New	10.0	CRIT		0.003		A memory safety vulnerability exists in the Extended Passport Protocol (EPP) processing library. Under specific conditions, an unauthenticated attacker could exploit a crafted network request containing a malformed EPP header, potentially resulting in undefined behavior and abnormal program termination. Successful exploitation may have a high impact on the confidentiality, integrity, and availability of the applic...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-62815 Updated	10.0	CRIT		0.012	nuget:Microsoft.Native.Quic.MsQuic .OpenSSL, nuget:Microsoft.Native.Quic.MsQuic.Schannel fixed: 2.4.19, 2.5.10	# Summary Use after free in Microsoft QUIC allows an unauthorized attacker to execute code over a network. # Details New network path creations and removals triggered by incoming packets can lead to a pointer invalidation. ## Patches - Guard path promotion [e0f55b5](https://github.com/microsoft/msquic/commit/e0f55b5fdc9fff0b4465976d066ebd22fb7e2b3b) # Impact An unauthenticated attacker could exploit this vul...
CVE-2026-70352 Newly scored	10.0	CRIT		0.006		Missing authentication for critical function in Azure AI Language allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-77995 Newly scored	10.0	CRIT		0.003		Joomla Extension - miniorange.com - Arbitrary account takeover in miniOrange OAuth Client < 3.2.0, OAuth Single Sign-On – OIDC SSO < 1.2.2, Login with Keycloak OAuth Single Sign-On (SSO) < 1.2.2, Single Sign-On for Educational Institutes < 1.2.2 - The manipulation of a cookie value allows actors to login as arbitrary accounts, including admins.
CVE-2026-77998 Newly scored	10.0	CRIT		0.003		Joomla Extension - miniorange.com - Unauthenticated Authentication Bypass via SAMLResponse Parameter in miniOrange SAML SSO < 11.0.2, SAML SP Single Sign On – Login with ADFS < 6.4, SAML SP Single Sign On – SAML SSO login with Google Apps < 6.4 - This is due to the mo_saml_validate_signature() function performing a loose boolean check on the raw tri-state integer returned by PHP's openssl_verify(), causing an err...
CVE-2026-80098 Newly scored	10.0	CRIT		0.003	microsoft:copilot_studio	Improper verification of cryptographic signature in Copilot Studio allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-82004 New	10.0	CRIT		0.014	adobe:campaign	Adobe Campaign Classic (ACC) is affected by an Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability that could result in arbitrary code execution in the context of the current user. An attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is changed.
CVE-2026-83711 Newly scored	10.0	CRIT		0.006		Authorization bypass through user-controlled key in Microsoft Azure Active Directory B2C allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-12645 New	9.9	CRIT		0.012		A Missing Authorization vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-12646 New	9.9	CRIT		0.012		A Missing Authorization vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-12647 New	9.9	CRIT		0.012		A Missing Authorization vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-12650 New	9.9	CRIT		0.015		A Deserialization of Untrusted Data vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote authenticated attacker to execute arbitrary code on the server.
CVE-2026-19232 New	9.9	CRIT		0.006	adobe:experience_manager	Adobe Experience Manager is affected by an Incorrect Authorization vulnerability that could result in arbitrary code execution in the context of the current user, potentially gaining elevated access or control over the victim's account or session. A low-privileged attacker could exploit this vulnerability to gain elevated access or control over the victim's account or session. Exploitation of this issue does not r...
CVE-2026-26084 New	9.9	CRIT		0.002		A improper access control vulnerability in Fortinet FortiSandbox 5.0.0 through 5.0.5, FortiSandbox 4.4.0 through 4.4.8, FortiSandbox Cloud 5.0.4 through 5.0.5, FortiSandbox PaaS 5.0.4 through 5.0.5 may allow attacker to access sensitive information via crafted HTTP requests.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-48273 New	9.9	CRIT		0.019	adobe:coldfusion	ColdFusion is affected by an Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') vulnerability that could result in arbitrary code execution in the context of the current user. A low-privileged attacker could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is changed.
CVE-2026-55565 Newly scored	9.9	CRIT		0.005		Yamcs is a mission control framework. Prior to 5.12.8 and 5.13.2, Yamcs LikeExpression.fillCode_getValueReturn in yamcs-core/src/main/java/org/yamcs/yarch/streamsql/LikeExpression.java inserts an unescaped LIKE pattern into Java source compiled by Expression.getCompiledExpression through SimpleCompiler.cook instead of applying ValueExpression.escapeJavaString. The pattern can originate from POST /api/archive/{inst...
CVE-2026-65818 Newly scored	9.9	CRIT		0.003	microsoft:power_platform	Server-side request forgery (ssrf) in Power Automate allows an authorized attacker to elevate privileges over a network.
CVE-2026-78234 New	9.9	CRIT		0.002		A flaw was found in hawtio-operator. The operator reads the OpenShift Service CA private signing key from the openshift-service-ca namespace and uses it to mint client certificates with a Subject Common Name (CN) supplied by the author of a namespaced Hawtio custom resource. Because the operator ships a ClusterRole that aggregates Hawtio CR permissions into the edit and admin roles, any user with edit access in an...
CVE-2026-79748 Newly scored	9.9	CRIT		0.003		MCPHub is a unified hub for centrally managing and dynamically orchestrating multiple MCP servers/APIs into separate endpoints with flexible routing strategies. Prior to version 0.12.15, the POST /api/servers and PUT /api/servers/:name endpoints in MCPHub create/update MCP server configurations and then immediately spawn the configured stdio process via child_process.spawn. Authentication is required, but there is...
CVE-2026-86464 New	9.9	CRIT		0.004		In the current development version of Eclipse aeriOS, for which no official release has yet been published, the Identity Manager (IdM) deployment included insecure default configurations and credentials for security-sensitive services. The Helm chart exposed the Keycloak service and its PostgreSQL backing database through Kubernetes NodePort services by default, while the Docker Compose deployment similarly ex...
CVE-2023-42179 Newly scored	9.8	CRIT		0.003		Bird Home Automation GmbH D1101V-F 000140 is vulnerable to Incorrect Access Control via the Key derivation process, password validation process.
CVE-2024-11080 Newly scored	9.8	CRIT		0.004		The Post Grid and Gutenberg Blocks – ComboBlocks plugin for WordPress is vulnerable to Unauthenticated Hook Injection in versions 2.2.32 to 2.3.1 via several functions in the ~/includes/blocks/form-wrap/function.php file. This makes it possible for unauthenticated attackers to execute actions with hooks in WordPress, granted no other security controls are present in the function.
CVE-2026-10196 Newly scored	9.8	CRIT		0.006		The Mail Mint – Email Marketing, Newsletter, Email Automation & WooCommerce Emails plugin for WordPress is vulnerable to PHP Object Injection in all versions up to, and including, 1.31.0 via deserialization of untrusted input in the 'handle_form_submission' function. This makes it possible for unauthenticated attackers to inject a PHP Object. The additional presence of a POP chain allows attackers to execute code ...
CVE-2026-12744 New	9.8	CRIT		0.022		A Deserialization of Untrusted Data vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote unauthenticated attacker to execute arbitrary code on the server.
CVE-2026-12745 New	9.8	CRIT		0.021		A Deserialization of Untrusted Data vulnerability in Ivanti Neurons for ITSM before 2026.2 allows a remote unauthenticated attacker to execute arbitrary code on the server.
CVE-2026-13447 Newly scored	9.8	CRIT		0.004		The Mstore Api plugin for WordPress is vulnerable to Authentication Bypass via JWT Forgery in versions up to, and including, 4.20.0 This is due to missing cryptographic signature verification in the FirebasePhoneAuthHelper::verify_id_token() function, which decodes and validates Firebase ID token claims (alg, kid, aud, iss) but never calls openssl_verify() or any equivalent to validate the JWT signature against Go...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-16310 Newly scored	9.8	CRIT		0.003		The MemberDash plugin for WordPress is vulnerable to Insecure Direct Object Reference in all versions up to, and including, 1.8.5 via the 'id' parameter due to missing validation on a user controlled key. This makes it possible for unauthenticated attackers to change the password of any WordPress user, including administrators, by supplying an arbitrary user ID during registration, and take over their account with...
CVE-2026-18221 Newly scored	9.8	CRIT		0.003	ibm:i	IBM i 7.6, 7.5, 7.4, and 7.3 could allow a remote attacker to gain unauthorized access due to improper validation of client-supplied authentication parameters.
CVE-2026-28606 New	9.8	CRIT		0.003	google:android	In handleBondStateChanged of AdapterService.java, there is a possible way to skip pairing due to a logic error in the code. This could lead to remote escalation of privilege without user consent with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-31020 Newly scored	9.8	CRIT		0.006		In DocsGPT 0.15.0 and below, the application provides a custom prompt feature that allows users to define prompt content used during chatbot interactions. This functionality renders user-supplied prompt data using Jinja templates without input sanitization or sandboxing. An unauthenticated attacker can inject malicious template expressions, leading to a server-side template injection (SSTI) vulnerability that can ...
CVE-2026-35868 Newly scored	9.8	CRIT		0.014		A Command Injection vulnerability exists in the bs_SetLimitCli_info function within the libshare.so library of LB-link Router AC2100_AZ3 V1.0.4. This flaw occurs due to insufficient validation and sanitization of user-supplied input before it is passed to a system-level command execution context. An attacker can exploit this vulnerability by injecting specially crafted shell metacharacters or payloads into the vul...
CVE-2026-35869 Newly scored	9.8	CRIT		0.013		A Command Injection vulnerability exists in the bs_SetLimitCli_info function within the libshare.so library of LB-link Router AC450M V4.0.0. This flaw occurs due to insufficient validation and sanitization of user-supplied input before it is passed to a system-level command execution context. An attacker can exploit this vulnerability by injecting specially crafted shell metacharacters or payloads into the vulnera...
CVE-2026-37003 Newly scored	9.8	CRIT		0.016		Agno up to and including 2.5.8 is vulnerable to Remote Code Execution (RCE) via prompt injection. The PythonTools and ShellTools components pass unsanitized, LLM-generated arguments directly to execution sinks including exec(), runpy.run_path(), and subprocess.run(). An unauthenticated attacker can exploit this by embedding malicious instructions in content processed by the agent (such as web pages or documents), ...
CVE-2026-37236 Newly scored	9.8	CRIT		0.004		grpc-gateway v2.28.0 is vulnerable to Incorrect Access Control. The application processes the X-HTTP-Method-Override header in ServeMux.ServeHTTP without restricting allowed methods. When a POST request with Content-Type application/x-www-form-urlencoded includes this header, the request method is rewritten to an arbitrary attacker-supplied value before routing. This allows bypassing method-based access controls e...
CVE-2026-49921 New	9.8	CRIT		0.003		In multiple locations, there is a possible memory safety issue due to a heap buffer overflow. This could lead to remote code execution with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-52111 Newly scored	9.8	CRIT		0.003		An issue in fast-note-sync-service <=2.13.7 allows a remote attacker to escalate privileges via the admin configuration endpoint exposes authTokenKey
CVE-2026-55559 Newly scored	9.8	CRIT		0.006		Yamcs is a mission control framework. Prior to 5.12.8 and 5.13.2, Yamcs inserts templateArgs from POST /api/instances and PATCH /api/instances/{instance} into YAML through VarStatement.append in yamcs-core/src/main/java/org/yamcs/templating/VarStatement.java without YAML-context escaping. The rendered configuration is parsed by YamcsServer.createInstance and loaded by YamcsServerInstance, allowing an attacker to i...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-58240 New	9.8	CRIT		0.003		SAP NetWeaver Message Server does not sufficiently validate the authenticity of internal application server components during registration. An unauthenticated attacker with network access to the affected service could exploit this weakness to register an unauthorized component and potentially perform unauthorized actions within the application environment, resulting in a high impact on the confidentiality, integri...
CVE-2026-58822 New	9.8	CRIT		0.003		In multiple functions of ftsmooth.c, there is a possible memory safety issue due to improper casting. This could lead to remote code execution with no additional execution privileges needed. User interaction is not needed for exploitation.
CVE-2026-61516 New	9.8	CRIT		0.004		Netis NX10 firmware V4.0.1.5808 and V3.0.0.4142 contain an information disclosure vulnerability that allows unauthenticated attackers to retrieve the administrator password by sending a request to the sysinfo action in the web management interface without a valid session. Attackers can replay the exposed credential against the login handler to establish a fully authenticated administrator session on the device.
CVE-2026-62916 Newly scored	9.8	CRIT		0.006	microsoft:entra_id	Authentication bypass using an alternate path or channel in Microsoft Entra ID allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-66302 New	9.8	CRIT		0.005	microsoft:skype_for_business_server, microsoft:skype_for_business_server_subscription_edition	External control of file name or path in Skype for Business allows an unauthorized attacker to execute code over a network.
CVE-2026-68839 New	9.8	CRIT		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Mass Storage Class Driver allows an unauthorized attacker to execute code over a network.
CVE-2026-69276 New	9.8	CRIT		0.009		Integer underflow (wrap or wraparound) in Microsoft UxTheme Library (uxtheme.dll) allows an unauthorized attacker to execute code over a network.
CVE-2026-69408 New	9.8	CRIT		0.01		Integer overflow or wraparound in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.
CVE-2026-69431 New	9.8	CRIT		0.009		Heap-based buffer overflow in Telnet Client allows an unauthorized attacker to execute code over a network.
CVE-2026-69463 New	9.8	CRIT		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code over a network.
CVE-2026-69491 New	9.8	CRIT		0.009		Heap-based buffer overflow in Windows Microsoft DirectMusic allows an unauthorized attacker to execute code over a network.
CVE-2026-69493 New	9.8	CRIT		0.01		Out-of-bounds read in Windows Event Logging Service allows an unauthorized attacker to execute code over a network.
CVE-2026-69496 New	9.8	CRIT		0.01		Heap-based buffer overflow in Windows Compressed Folder allows an unauthorized attacker to execute code over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69525 New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Desktop Services allows an unauthorized attacker to execute code over a network.
CVE-2026-69579 New	9.8	CRIT		0.01		Use after free in Windows Message Queuing allows an unauthorized attacker to execute code over a network.
CVE-2026-69586 New	9.8	CRIT		0.01		Integer overflow or wraparound in Microsoft Windows PDF allows an unauthorized attacker to execute code over a network.
CVE-2026-69590 New	9.8	CRIT		0.01		Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine
CVE-2026-69595 New	9.8	CRIT		0.011		Use after free in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to execute code over a network.
CVE-2026-69715 New	9.8	CRIT		0.01		Out-of-bounds read in Windows Direct Show allows an unauthorized attacker to execute code over a network.
CVE-2026-69730 New	9.8	CRIT		0.011		Use after free in Windows DNS allows an unauthorized attacker to execute code over a network.
CVE-2026-69768 New	9.8	CRIT		0.009		Heap-based buffer overflow in Windows RNDIS allows an unauthorized attacker to execute code over a network.
CVE-2026-69769 New	9.8	CRIT		0.009		Heap-based buffer overflow in Windows HTTP Print Provider allows an unauthorized attacker to execute code over a network.
CVE-2026-69819 New	9.8	CRIT		0.009		Out-of-bounds write in RPC Runtime allows an unauthorized attacker to execute code over a network.
CVE-2026-69824 New	9.8	CRIT		0.01		Integer underflow (wrap or wraparound) in Microsoft Standard XPS allows an unauthorized attacker to execute code over a network.
CVE-2026-69829 New	9.8	CRIT		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Shell allows an unauthorized attacker to execute code over a network.
CVE-2026-69845 New	9.8	CRIT		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Heap-based buffer overflow in Windows DHCP Server allows an unauthorized attacker to execute code over a network.
CVE-2026-69910 New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Windows Hyper-V allows an unauthorized attacker to execute code over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-70296 New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds write in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-71374 New	9.8	CRIT		0.003		Deserialization of untrusted data vulnerability in Cosminexus Component Container. This issue affects Cosminexus Component Container: from 11-70-01 before 11-70-03, from 11-60 before 11-60-03, from 11-50 through 11-50-03, from 11-40 through 11-40-03, from 11-30 through 11-30-08, from 11-20 before 11-20-10, from 11-10 through 11-10-11, from 11-00 before 11-00-13, from 09-87 before 09-87-10, from 09-80 before 09-80-...
CVE-2026-71376 New	9.8	CRIT		0.01		OS command injection vulnerability in Cosminexus Component Container. This issue affects Cosminexus Component Container: from 11-70-01 before 11-70-03, from 11-60 before 11-60-03, from 11-50 through 11-50-03, from 11-40 through 11-40-03, from 11-30 through 11-30-08, from 11-20 before 11-20-10, from 11-10 through 11-10-11, from 11-00 before 11-00-13, from 09-87 before 09-87-10, from 09-80 before 09-80-05, from 09-...
CVE-2026-71377 New	9.8	CRIT		0.003		Command Argument Injection Vulnerability in Cosminexus Component Container. This issue affects Cosminexus Component Container: from 11-70-01 before 11-70-03, from 11-60 before 11-60-03, from 11-50 through 11-50-03, from 11-40 through 11-40-03, from 11-30 through 11-30-08, from 11-20 before 11-20-10, from 11-10 through 11-10-11, from 11-00 through 11-00-12, from 09-87 before 09-87-10, from 09-80 through 09-80-04, ...
CVE-2026-72979 New	9.8	CRIT		0.01		Use after free in Windows DHCP Server allows an unauthorized attacker to execute code over a network.
CVE-2026-72982 New	9.8	CRIT		0.009		Stack-based buffer overflow in Windows Netlogon allows an unauthorized attacker to execute code over a network.
CVE-2026-72983 New	9.8	CRIT		0.009		Use after free in Windows Internet Connection Sharing (ICS) allows an unauthorized attacker to execute code over a network.
CVE-2026-73009 New	9.8	CRIT		0.009		Use after free in Windows Secure Socket Tunneling Protocol (SSTP) allows an unauthorized attacker to execute code over a network.
CVE-2026-73010 New	9.8	CRIT		0.009		Use after free in Windows Failover Cluster allows an unauthorized attacker to execute code over a network.
CVE-2026-73025 New	9.8	CRIT		0.009		Weak authentication in Windows iSCSI allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-75430 Newly scored	9.8	CRIT		0.009		PowerJob Worker version 5.1.2 (and likely earlier versions) exposes the /worker/deployContainer HTTP endpoint without authentication on the default transport port. This allows a remote attacker to execute arbitrary code.
CVE-2026-75816 Newly scored	9.8	CRIT		0.005		The Frontend Admin by DynamiApps plugin for WordPress is vulnerable to Authentication Bypass to Account Takeover in all versions up to, and including, 3.29.12. This is due to the pre_update_value function lacking any capability or ownership check, and ActionPost::conditions_logic() short-circuiting its current_user_can('edit_post') authorization gate whenever the post ID is non-numeric — such as the string user_1 ...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-77089 New	9.8	CRIT		0.003	commvault:commvault	Command Center API contained an authentication bypass issue affecting privilege management. Software customers upgrade to resolved maintenance release. Update Command Center.
CVE-2026-77092 New	9.8	CRIT		0.002	commvault:commvault	Content Extractor contained a deserialization of untrusted data issue affecting privilege management. Software customers upgrade to resolved maintenance release. Update Content Extractor.
CVE-2026-77098 New	9.8	CRIT		0.003	commvault:commvault	Private Metrics Server contained an SQL injection condition affecting database operations. Software customers upgrade to resolved maintenance release. Update Private Metrics Server.
CVE-2026-77493 New	9.8	CRIT		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Double free in Microsoft Graphics Component allows an unauthorized attacker to execute code over a network.
CVE-2026-77647 Newly scored	9.8	CRIT		0.026		SPIP before 4.4.20 allows unauthenticated remote attackers to execute arbitrary code, as exploited in the wild in August 2026. This is related to incorrect identification of <?php blocks, and var_export's mishandling of certain cases such as presence of a '<' character.
CVE-2026-77806 Newly scored	9.8	CRIT		0.042		SPIP before 4.4.21 allows unauthenticated remote attackers to execute arbitrary code, as exploited in the wild in August 2026. This is related to code injection via an X-Spif-Filtre HTTP request header that is mishandled by analyse_resultat_skel.
CVE-2026-78362 Newly scored	9.8	CRIT		0.003		The SEO Flow by LupsOnline WordPress plugin before 3.0.3 does not correctly validate the credential supplied with its API requests, allowing unauthenticated users to be served as the administrator who configured the SEO Flow by LupsOnline WordPress plugin before 3.0.3 and take over the site. Exploitation requires the SEO Flow by LupsOnline WordPress plugin before 3.0.3 to have been configured, which is its normal ...
CVE-2026-78445 New	9.8	CRIT		0.009	microsoft:windows_server_2012, microsoft:windows_server_2016, microsoft:windows_server_2019, microsoft:windows_server_20	Use after free in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to execute code over a network.
CVE-2026-78509 New	9.8	CRIT		0.01	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2019, microsoft:office_2021, microsoft:office_2024, micros	Heap-based buffer overflow in Microsoft Office Outlook allows an unauthorized attacker to execute code over a network.
CVE-2026-78510 New	9.8	CRIT		0.01	microsoft:365_apps, microsoft:microsoft_365, microsoft:office_2016, microsoft:office_2019, microsoft:office_2021, micros	Heap-based buffer overflow in Microsoft Office Word allows an unauthorized attacker to execute code over a network.
CVE-2026-79569 New	9.8	CRIT		0.004		Movie_Recommend v1.0.0 was discovered to contain a SQL injection vulnerability in the sort parameter at /loadingmore. This vulnerability allows attackers to access sensitive database information via a crafted SQL statement.
CVE-2026-79570 New	9.8	CRIT		0.003		mfish-nocode-pro v1.0.0 was discovered to contain a SQL injection vulnerability in the tableName parameter at /sys/dbConnect/data. This vulnerability allows attackers to access sensitive database information via a crafted SQL statement.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-79574 New	9.8	CRIT		0.005		An issue in the gateway server of mpush v0.8.1 allows attackers to execute arbitrary code via sending a crafted broadcast message.
CVE-2026-79576 New	9.8	CRIT		0.003		An issue in the Single-Sign On (SSO) component of Digital-Infrastructure v9.6.7 allows attackers to authenticate as any user, including the Admin, without a password.
CVE-2026-79577 New	9.8	CRIT		0.003		An issue in the /cas/login component of sso-master v1.0.0 allows attackers to authenticate into the application without a password via sending a crafted POST request.
CVE-2026-82923 Newly scored	9.8	CRIT		0.006		The AI Website Builder WordPress plugin (GitHub build) 1.0.0 does not perform any authorisation or nonce check on its REST API routes, allowing unauthenticated attackers to install and activate plugins and themes, import content from a URL under their control, write a file of their choosing into the uploads directory, and delete site content and media. On a host that serves PHP from the uploads directory, that fil...
CVE-2026-83627 Newly scored	9.8	CRIT		0.008		The Hummingbird – Speed Optimization, Caching, Minify, Compress & CDN plugin for WordPress is vulnerable to Remote Code Execution in all versions up to, and including, 3.21.0 via the log_msg() function in core/modules/class-page-cache.php. The page-cache debug log is written to wp-content/wphb-logs/page-caching-log.php, a directly web-accessible PHP file that is supposed to be protected by a leading '<?php die(); ...
CVE-2026-85504 Newly scored	9.8	CRIT		0.004		FreeIPMI before 1.6.19 has a stack-based buffer overflow in _ipmi_sel_oem_fujitsu_get_sel_entry_long_text in libfreeipmi/sel/ipmi-sel-string-fujitsu-irmc-common.c via malformed Fujitsu SEL long-text responses.
CVE-2026-85508 Newly scored	9.8	CRIT		0.004		ipmi-oem in FreeIPMI before 1.6.19 has a stack-based buffer overflow in _output_dell_system_info_cmc_ipv6_info in ipmi-oem/ipmi-oem-dell.c (cmc-ipv6-info subcommand to dell get-system-info).
CVE-2026-85509 Newly scored	9.8	CRIT		0.004		FreeIPMI before 1.6.19 has a stack-based buffer overflow in _read_fru_data in libfreeipmi/fru/ipmi-fru.c when a BMC returns more bytes than requested.
CVE-2026-86184 Newly scored	9.8	CRIT		0.006		Lara Dashboard before 1.3.0 contains an authentication bypass vulnerability in the screenshot-login route that allows unauthenticated attackers to authenticate as any user by email when APP_ENV is not production. Attackers can request the GET /screenshot-login/{email} endpoint with a registered email address to receive a fully authenticated session, enabling access to user administration, settings, database conten...
CVE-2026-86189 Newly scored	9.8	CRIT		0.004		WWBN AVideo contains a path traversal vulnerability in notify.ffmpeg.json.php that allows unauthenticated attackers to write files to arbitrary locations by supplying a caller-chosen path in the avideoRelativePath parameter. Attackers can replay any previously issued ciphertext as a notifyCode token, which is decrypted but never validated, to bypass authentication and write files to the application root and subdir...
CVE-2026-86219 Newly scored	9.8	CRIT		0.005		Authen::SASL::Perl::DIGEST_MD5 versions before 2.2100 for Perl accept replayed authentication responses via unverified nonce in server_step. server_start generates a fresh nonce and sends it in the challenge, and nothing later compares that value against the nonce the client returns. server_step derives the expected digest from the client's own parameters, so a response verifies whenever its digest matches the no...
CVE-2026-86304 Newly scored	9.8	CRIT		0.002		MojoX::Authentication versions before 0.006 for Perl allow SAML authentication bypass because parse_assertion builds Net::SAML2::Binding::POST without a trust anchor. parse_assertion in MojoX::Authentication::Model::SAML2 calls Net::SAML2::Binding::POST->new with no cacert, cert_text or anchors argument, then passes the returned XML to Net::SAML2::Protocol::Assertion->new_from_xml with the IdP signing certificate...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-19274 Newly scored	9.6	CRIT		0.002		IBM Observability with Instana (Agent) Build 1.0.303 through 1.0.323 IBM Instana Agent Operator could allow an authenticated Kubernetes tenant to hijack or permanently destroy another tenant's cluster-level RBAC permissions, caused by cluster-scoped RBAC objects being keyed solely by the bare CR name with no namespace disambiguation, allowing a same-named `InstanaAgent` CR in an attacker-controlled namespace to si...
CVE-2026-53552 Newly scored	9.6	CRIT		0.002		Goploy is an open-source automation deployment system. In versions 1.17.5 and prior, Project.AddFile, Project.EditFile, Project.RemoveFile, and Project.Edit in cmd/server/api/project/handler.go accept a project or project-file row id from the JSON body and act on it without checking that the project belongs to the caller's namespace. The corresponding model.ProjectFile.GetData and model.Project.GetData queries fil...
CVE-2026-65669 New	9.6	CRIT		0.007		Improper neutralization of special elements in output used by a downstream component ('injection') in SQL Server allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-81376 New	9.6	CRIT		0.006	microsoft:visual_studio_code	Incomplete comparison with missing factors in Visual Studio Code allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-84333 Newly scored	9.6	CRIT		0.003	google:android, google:chrome	Use after free in Dawn in Google Chrome on on Android prior to 152.0.7977.75 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-84352 Newly scored	9.6	CRIT		0.003	google:android, google:chrome	Use after free in WebGL in Google Chrome on on Android prior to 152.0.7977.75 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Critical)
CVE-2026-84353 Newly scored	9.6	CRIT		0.003	google:android, google:chrome	Use after free in Shared Tab Groups in Google Chrome on on Android prior to 152.0.7977.75 allowed a remote attacker leveraging social engineering to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Critical)
CVE-2026-85042 Newly scored	9.6	CRIT		0.003	google:chrome	Use after free in DevTools in Google Chrome prior to 152.0.7977.82 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-85047 Newly scored	9.6	CRIT		0.003	apple:iphone_os, google:chrome	Improper input validation in Transactions Platform in Google Chrome on on iOS prior to 152.0.7977.82 allowed a remote attacker to potentially execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: Medium)
CVE-2026-85050 Newly scored	9.6	CRIT		0.003	google:android, google:chrome	Out of bounds write in WebGL in Google Chrome on on Android prior to 152.0.7977.82 allowed a remote attacker to execute arbitrary code outside the sandbox via a crafted HTML page. (Chromium security severity: High)
CVE-2026-85085 Newly scored	9.6	CRIT		0.002		The Canva Android App before 2.376.0 allowed an external origin to be loaded in a privileged WebView. A threat actor who controls the page loaded by the user is able to communicate with Canva using the user's session.
GHSA-2xp9-vwfh-vxw4 Updated	9.5	CRIT			npm:next fixed: 15.5.24, 16.3.3	A vulnerability in the underlying `libheif` library used by `sharp` which Next.js uses for image optimization can lead to remote code execution when AVIF files are optimized. Until a fix has propagated, optimization of AVIF files is disabled.
CVE-2026-52777 Newly scored	9.4	CRIT		0.002		YesWiki is a wiki system written in PHP. Prior to version 4.6.6, there is an authenticated PHP object injection vulnerability in BazarImportAction via unserialize. This issue has been patched in version 4.6.6.
CVE-2026-75925 Newly scored	9.4	CRIT		0.007		Improper neutralization of CRLF sequences in IXON VPN Client before version 1.4.7 allows an attacker to execute commands as root or SYSTEM. Configuration values accepted by the local service are written to a file later consumed by a privileged subprocess, without line-ending sequences being neutralized, which allows additional directives to be introduced into that file. The configuration interface accepts changes ...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-76969 New	9.4	CRIT		0.003		@sap/cds-mtxs NPM library does not perform sufficient checks on certain functionality used in multitenant CAP applications with extensibility enabled. An unauthenticated attacker could send specially crafted requests to obtain sensitive credentials and abuse them to replace or delete tenant data. Successful exploitation can result in a high impact on availability and integrity of the application. There may also be...
CVE-2026-78683 Updated	9.4	CRIT		0.003	pip:nlTK fixed: 3.10.0	## Summary The NLTK library's `TransitionParser.parse()` method deserializes model files using `pickle_load()` with the default `restricted=False` parameter, allowing arbitrary Python code execution when loading a malicious model file. The library provides a `RestrictedUnpickler` class for safe deserialization, but it is never used by production code paths, leaving the vulnerability unpatched. ## Root Cause **F...
CVE-2026-82533 New	9.4	CRIT		0.006		DeepSeek Harness before 0.1.2-alpha.1 contains an authentication bypass vulnerability that grants unauthenticated access to its local HTTP agent-control API by accepting a client-supplied loopback Host header in place of validating the actual TCP connection origin. On the default configuration, a confined tool-executed process can reach the loopback API without any port exposure and use it to escape its own OS san...
CVE-2026-86123 Newly scored	9.4	CRIT		0.003		SQL Chat contains four unauthenticated API endpoints that accept client-supplied database connection parameters and execute arbitrary SQL queries against attacker-specified hosts. Attackers can connect to internal databases, execute SQL commands, enumerate schemas, and pivot into the server's network without authentication.
CVE-2026-86148 Newly scored	9.4	CRIT		0.025		A security flaw has been discovered in Tenda CP3 27.5.57.101. This vulnerability affects the function SystemAsh of the file Apis/system.c of the component Kylin. The manipulation of the argument AlarmVoiceURL results in os command injection. It is possible to launch the attack remotely.
CVE-2026-86149 Newly scored	9.4	CRIT		0.02		A weakness has been identified in Tenda CP3 27.5.57.101. This issue affects some unknown processing of the file Net/NetCheckPing.cpp. This manipulation of the argument interface_name/host causes os command injection. The attack can be initiated remotely.
CVE-2026-86153 Newly scored	9.4	CRIT		0.004		A vulnerability has been found in Tenda CP3 27.5.57.101. This affects the function CRedirServer::SetRedirectEnable of the file Functions/Redirect.cpp. The manipulation leads to improper privilege management. Remote exploitation of the attack is possible.
CVE-2023-54391 Newly scored	9.3	CRIT		0.017		Proxmox Virtual Environment (VE) 7.0 through 8.0 contains an authentication bypass vulnerability in libpve-access-control before 8.0.4 that allows unauthenticated attackers to authenticate as any existing enabled user without a configured second factor by supplying an arbitrary tfa-challenge value in the API login endpoint. Attackers can send a POST request to the access ticket API endpoint with any value in the t...
CVE-2024-58376 Newly scored	9.3	CRIT		0.017		Renovate versions 37.158.0 before 37.199.0 contain a command injection vulnerability in the helmv3 manager's registryAliases handling that allows attackers with commit access to execute arbitrary commands. Attackers can manipulate registryAliases keys with unquoted shell metacharacters to inject commands executed during helm repo add operations, gaining full access to Renovate's execution environment.
CVE-2026-16279 Newly scored	9.3	CRIT		0.003		An Improper Authorization vulnerability affecting 3DPassport in 3DSwymer from Release 3DEXPERIENCE R2023x through Release 3DEXPERIENCE R2026x could allow an attacker to gain access to some user accounts.
CVE-2026-55068 Newly scored	9.3	CRIT		0.004		free5GC is an open-source implementation of the 5G core network. In 4.2.2 and earlier, the NRF RegisterNFInstance handler at PUT /nnrf-nfm/v1/nf-instances/{nfInstanceId} accepts NF Profiles without enforcing UUID format, nfStatus enum values, heartBeatTimer ranges, mandatory profile fields, or nfServices.ipEndPoints address constraints. The invalid profiles are persisted in the MongoDB NfProfile collection and ret...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-56705 Newly scored	9.3	CRIT		0.005		Adminer before 5.4.3 fails to sanitize the server field before constructing a PDO DSN string, allowing unauthenticated attackers to inject ODBC parameters via semicolons. Attackers can inject TraceFile and TraceOn parameters to write PHP code to the web root, achieving remote code execution when the trace file is accessed.
CVE-2026-62645 New	9.3	CRIT		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). Information is exposed through the web interface that can be used to calculate the current and past session ID numbers. This could allow an attacker to bypass the authentication and gain unauthorized access to the device.
CVE-2026-62647 New	9.3	CRIT		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). A random number generator is used to generate security-relevant values (such as session identifiers used for authentication purposes) that is not initialized with a True Random Number Generator (TRNG), resulting in a predictable sequence of generated values. This could allow an unauthenticated remote attacker to more easily predict the ge...
CVE-2026-62928 Newly scored	9.3	CRIT		0.012		XING CPTrans-ME-X contains an OS Command Injection (CWE-78). Unauthenticated OS command may be injected.
CVE-2026-66794 Newly scored	9.3	CRIT		0.004		A flaw was found in the `cluster-proxy-addon` component of Multicluster Engine for Kubernetes. This vulnerability allows an unauthenticated attacker, who can access the user-facing route, to bypass authentication and authorization checks. By manipulating URL path segments, the attacker can proxy requests to arbitrary services across any managed cluster. This enables unauthorized access to internal services that wo...
CVE-2026-69356 New	9.3	CRIT		0.007		Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Exchange Server allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-69657 Newly scored	9.3	CRIT		0.003		XING CPTrans-ME-X contains a Use of Default Password (CWE-1393). Anyone with the knowledge of the credential may log in to the affected device.
CVE-2026-70403 Newly scored	9.3	CRIT		0.003		XING CPTrans-ME-X contains a Use of Hard-coded Password (CWE-259). Anyone with the knowledge of the credential may log in to the affected device.
CVE-2026-76200 New	9.3	CRIT		0.005	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by an attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field, potentially gaining elevated access or control over the victim's account or session. Scope is changed.
CVE-2026-76201 New	9.3	CRIT		0.005	adobe:commerce, adobe:commerce_b2b, adobe:magento	Adobe Commerce is affected by a stored Cross-Site Scripting (XSS) vulnerability that could be abused by an attacker to inject malicious scripts into vulnerable form fields. Malicious JavaScript may be executed in a victim's browser when they browse to the page containing the vulnerable field, potentially gaining elevated access or control over the victim's account or session. Scope is changed.
CVE-2026-77642 Newly scored	9.3	CRIT		0.002	torproject:tor	tor before 0.4.9.9 was prone to an out-of-bounds write when parsing a consensus or detached signature with unexpected signature digest type. Impact is minor for most Tor roles, but potentially major for directory authorities. This is TROVE-2026-019.
CVE-2026-78012 Newly scored	9.3	CRIT		0.005		An issue in the NetStax EtherNet/IP Stack prior to v5.6.1 could allow a large Class 3 explicit-message request to exceed the application-side receive buffer without generating an error or warning. The result could be memory corruption, a device crash, or a potential remote attack vector without the originating device receiving a CIP error indicating that the request could not be processed.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78676 Updated	9.3	CRIT		0.004	pip:GitPython fixed: 3.1.59	- CWE: CWE-88 (Argument Injection) / CWE-94 (Code Injection) — via a read-then-corrupt-on-rewrite config round trip, not a direct setter argument - Affected component: `git/config.py` — `GitConfigParser._read()` (multi-line value decoding, lines 444-541, esp. `string_decode()` at line 460 and its call sites at 519/541) and `GitConfigParser._write()`/`write_section()` (serialization, lines ~694-712, esp. li...
CVE-2026-78997 New	9.3	CRIT		0.003		UC Browser for Android (package com.UCMobile.intl, version 13.7.8.1314) contains a Universal Cross-Site Scripting vulnerability that allows an attacker to execute arbitrary JavaScript in the context of any origin. An attacker hosts a specially crafted URL on a UC-owned domain (via a reflected XSS) that leverages the browser's internal JavaScript bridge to register a deferred callback, navigate the tab to a victim ...
CVE-2026-79657 Updated	9.3	CRIT		0.012	pip:nlTK fixed: 3.10.3	### Summary The current source tree still allows arbitrary code execution during supposedly safer allowlisted pickle loading. The allowlist trusts whole module namespaces instead of exact safe globals, so crafted pickles can invoke dangerous in-namespace callables through pickle REDUCE. ### Details - Vulnerability type: Remote code execution via unsafe deserialization - Affected component: `nlTK.pickles...
CVE-2026-82526 Newly scored	9.3	CRIT		0.004		R2R through 3.6.6 contains a stacked SQL injection vulnerability that allows unauthenticated attackers to execute arbitrary SQL statements by manipulating the index name parameter in the vector index creation endpoint. The index name is interpolated directly into a CREATE INDEX statement via string formatting without identifier quoting or allowlist validation, enabling arbitrary DDL and DML execution through semic...
CVE-2026-84479 Newly scored	9.3	CRIT		0.003		WWBN AVideo (current e01e41ecc and earlier) makes three login-time security controls depend solely on the client-supplied User-Agent header. The isAVideoEncoder()/isAVideoMobileApp() checks match HTTP_USER_AGENT against a hardcoded literal ("AVideoEncoder"/"AVideoMobileApp") with no IP check or shared secret. An attacker who submits valid credentials and sets User-Agent: AVideoEncoder bypasses two-factor authentic...
CVE-2026-84480 Newly scored	9.3	CRIT		0.003		WWBN AVideo fails to validate password recovery token expiration in userRecoverPassSave.json.php, allowing attackers to use expired tokens to reset account passwords indefinitely. Attackers who obtain a recovery token can use it at any time to change the target account's password and gain full account access.
CVE-2026-84695 Newly scored	9.3	CRIT		0.003		BookStack before 26.05.4 contains a stored cross-site scripting vulnerability in the drawing upload endpoint that accepts unvalidated base64 content and stores it without content inspection. Attackers with editor permissions can upload SVG files containing scripts that execute in administrator browsers when accessed through the image gallery API without content-type validation or CSP headers.
CVE-2026-85146 Newly scored	9.3	CRIT		0.004		SmartIT Desktop Manager developed by Lightstar has a Use of Hard-coded Credentials vulnerability. Unauthenticated remote attackers can obtain the SSH service account credentials and passwords for the SmartIT Agent directly from the application source code.
CVE-2026-85148 Newly scored	9.3	CRIT		0.004		SmartIT Desktop Manager developed by Lightstar has a Use of Hard-coded Credentials vulnerability. Unauthenticated remote attackers can exploit a fixed password to remotely access user hosts.
CVE-2026-85154 Newly scored	9.3	CRIT		0.003		WWBN AVideo contains an authentication failure vulnerability where the video_id_hash credential is a non-expiring, non-revocable bearer token that grants full administrator session access to the video owner's account. Attackers who obtain a video_id_hash can replay it indefinitely to authenticate as the video owner with full privileges, and the credential remains valid even after the owner changes their password.
CVE-2026-85424 Newly scored	9.3	CRIT		0.005		MOOS core-moos through 10.4.0 lacks authentication in the wire protocol, allowing unauthenticated clients to connect with full publish, subscribe, and database clear privileges. Attackers can bypass the compile-time protocol string check and connect with arbitrary client names to execute privileged operations including DB_CLEAR which resets all variables and clears client mail queues.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-85425 Newly scored	9.3	CRIT		0.01		MOOS-IvP iSay through 24.8.1 contains a remote code execution vulnerability in the SAY_MOOS variable handler that passes unsanitized text to a shell command. Attackers can publish SAY_MOOS messages containing backticks or command substitution syntax to execute arbitrary commands as the iSay process user.
CVE-2026-85426 Newly scored	9.3	CRIT		0.006		MOOS-IvP uMemWatch through 24.8.1 constructs shell commands from attacker-chosen MOOS client names without sanitization. Attackers can inject shell metacharacters into client names to execute arbitrary commands as the uMemWatch process user through unquoted redirection targets in system calls.
CVE-2026-85434 Newly scored	9.3	CRIT		0.002		MOOS-IvP uFldShoreBroker through 24.8.1 fails to verify node ping authenticity before creating outbound bridge routes. Attackers can publish NODE_BROKER_PING messages with crafted HostRecord data to redirect bridged variables to attacker-controlled addresses.
CVE-2026-85435 Newly scored	9.3	CRIT		0.002		MOOS-IvP uFldNodeBroker through 24.8.1 fails to validate the source of TRY_SHORE_HOST messages on the vehicle bus, allowing any publisher to enroll attacker-controlled shore routes. Attackers can publish malicious shore route messages to receive bridged vehicle traffic including sensor data and control information.
CVE-2026-85437 Newly scored	9.3	CRIT		0.007		MOOS-IvP through 24.8.1 contains multiple buffer overflow vulnerabilities in IvP function string decoders that trust attacker-controlled length fields without validation. Attackers can craft malicious encoded strings with mismatched declared and actual field lengths to overflow heap and stack buffers, potentially achieving remote code execution through MOOS variables or alog files.
CVE-2026-85440 Newly scored	9.3	CRIT		0.006		MOOS core-moos through 10.4.0 contains a pre-authentication heap overflow vulnerability in MOOSCommPkt packet handling that allows remote attackers to write arbitrary data by declaring a negative packet length. Attackers can exploit the signed integer check in InflateTo() and negative size conversion in recv() to overflow a four-byte heap buffer during the HandShake phase before authentication.
CVE-2026-85602 Newly scored	9.3	CRIT		0.003		The Grav Form plugin (getgrav/grav-plugin-form) versions 8.0.6 through 9.1.19 select the reCAPTCHA version to validate based solely on which response field key is present in the submitted payload. On a site configured for reCAPTCHA v3, an anonymous attacker can place their v3 token under the v2 field name (g-recaptcha-response instead of token), causing validation to use the v2 branch, which never applies the scor...
CVE-2026-85672 Newly scored	9.3	CRIT		0.015		zerox 1.1.20 contains an OS command injection vulnerability in the file download mechanism where the temporary file extension derived from document URLs is interpolated unsanitized into shell commands executed by poppler utilities. Attackers can craft document URLs with malicious file extensions containing command substitution syntax to execute arbitrary OS commands before document processing occurs.
CVE-2026-86121 Newly scored	9.3	CRIT		0.006		Cua computer-server versions before 0.3.42 skip authentication when the CONTAINER_NAME environment variable is unset and bind to all interfaces by default, allowing unauthenticated attackers to execute arbitrary commands. Attackers can reach TCP port 8000 to run shell commands via the run_command endpoint, read and write arbitrary files through file operation endpoints, and access interactive PTY shells without au...
CVE-2026-86190 Newly scored	9.3	CRIT		0.003		WWBN AVideo contains a broken access control vulnerability in videoViewsInfo endpoints that returns complete user records including password hashes, recovery tokens, and live session identifiers to unauthenticated callers when a hash parameter is provided. Attackers can use the disclosed session identifier to hijack viewer sessions, including administrator accounts, and obtain sensitive personal data for all video...
GHSA-9557-234j-7rv9 Updated	9.3	CRIT			pip:GitPython	## Duplicate Advisory This advisory has been withdrawn because it is a duplicate of GHSA-284h-m62q-gf8w. This link is maintained to preserve external references. ## Original Description GitPython before 3.1.59 fails to safely re-serialize multi-line git-config values during write operations, corrupting dormant quoted values into injected directives like core.hooksPath. Attackers can craft config files with embed...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
GHSA-cw2r-r7mw-j3hc Updated	9.3	CRIT			pip:gitpython	## Duplicate Advisory This advisory has been withdrawn because it is a duplicate of GHSA-v396-v7q4-x2qj. This link is maintained to preserve external references. ## Original Description GitPython 3.1.50 fails to recognize joined short-option forms such as -u<value> (the short form of --upload-pack=<value>) when enforcing its default unsafe-option gate. When an application passes attacker-influenced clone option...
CVE-2026-66047 Newly scored	9.2	CRIT		0.005		ProfilePress (wp-user-avatar) WordPress plugin before 4.17.2 contains an unauthenticated remote code execution vulnerability that allows unauthenticated attackers to install and activate arbitrary plugins by brute-forcing a weak 32-bit connect token via the ppress_connect_process AJAX handler. Attackers can supply a caller-controlled URL through the file request parameter to trigger silent plugin installation and ...
CVE-2026-67367 New	9.2	CRIT		0.008		A vulnerability has been identified in SIMOVE Fleetmanager V3.1 (All versions < V3.1.13), SIMOVE Fleetmanager V3.2 (All versions < V3.2.4), SIMOVE Fleetmanager V3.3 (All versions < V3.3.2), SIMOVE Fleetmanager V4.0 (All versions < V4.0.1), SIPLANT V1.7 (All versions), SIPLANT V2.2 (All versions), SIPLANT V3.0 (All versions), SIPLANT V3.1 (All versions < V3.1.4). Affected devices do not properly validate and neutra...
CVE-2026-77635 Updated	9.2	CRIT		0.003	composer:cakephp/cakephp, composer:cakephp/database fixed: 5.1.10, 5.2.15, 5.3.7	#### Impact The `FunctionsBuilder::jsonValue(\$field, \$jsonPath)` methods with the Postgres driver is vulnerable to SQL injection if user controlled data is supplied to the `\$jsonPath` parameter. ### Patches 5.1.10, 5.2.15, 5.3.7 ### Workarounds Don't provide user controlled data to these functions/parameters.
CVE-2026-82067 New	9.2	CRIT		0.003	mongodb:mongodb	Improper handling of case sensitivity in the configuration validation component of MongoDB Server may cause the authorization subsystem to remain in a default disabled state during server startup. An unauthenticated user with network access to a deployment where this condition occurs can perform arbitrary administrative operations, resulting in full impact of data confidentiality, integrity, and availability.
CVE-2026-84189 Newly scored	9.2	CRIT		0.003		LibreNMS through 26.4.0 renders JSON fields (name, ip, model, author, commit message) returned by the admin-configurable Oxidized integration URL (oxidized.url) into the device showconfig page without applying htmlspecialchars(). An administrator who points the Oxidized URL at an attacker-controlled server (SSRF) can cause it to return malicious JSON, resulting in stored/persistent cross-site scripting affecting a...
CVE-2026-84197 New	9.2	CRIT		0.002		In Eclipse Ditto's Node.js JavaScript client, all released versions of @eclipse-ditto/ditto-javascript-client-node from 2.0.0 to 3.9.0 and of its predecessor package @eclipse-ditto/ditto-javascript-client-node_1.0 from 1.0.0 to 2.1.0, the WebSocket transport hard-codes rejectUnauthorized: false when creating the underlying ws WebSocket. Certificate chain and hostname validation are therefore disabled for every wss...
CVE-2026-85427 Newly scored	9.2	CRIT		0.004		MOOS essential-moos pAntler through 10.0.1 contains a remote code execution vulnerability that allows unauthenticated attackers to execute arbitrary programs by publishing a crafted MISSION_FILE message to the MOOSDB. Attackers can publish a mission file containing malicious Run entries that pAntler parses and executes via execvp() without authentication validation.
CVE-2026-85614 Newly scored	9.2	CRIT		0.002		OpenPanel before 2.3.0 contains an unauthenticated server-side request forgery vulnerability in the GET /tools/site-checker endpoint that accepts a fully client-controlled URL parameter with no private IP filtering or DNS-rebinding protection. Attackers can make the OpenPanel server issue requests to internal services, localhost, and cloud metadata endpoints, reading internal HTTP response titles, headers, status ...
CVE-2026-9317 Newly scored	9.2	CRIT		0.007		Nango before 0.71.6 contains a missing authentication vulnerability in the runner tRPC server that allows unauthenticated attackers to execute arbitrary JavaScript code by invoking the exposed start procedure without credentials. Attackers with network access to the runner port can send requests to the unauthenticated start procedure, bypassing the unenforced RUNNER_SECRET_KEY environment variable, to achieve remo...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
GHSA-g64v-qpgg-v37h Updated	9.2	CRIT			go:github.com/siyuan-note/siyuan/kernel	## Duplicate Advisory This advisory has been withdrawn because it is a duplicate of GHSA-7j72-f6wg-cxw6. This link is maintained to preserve external references. ## Original Description SiYuan versions before v3.7.3 contain an authentication bypass vulnerability in publish mode where content-returning endpoints getHeadingChildrenDOM, getHeading*Transaction, and getBacklinkDoc perform no password check despite pr...
GHSA-xx34-6cjj-rh8 Updated	9.2	CRIT			go:github.com/siyuan-note/siyuan/kernel	## Duplicate Advisory This advisory has been withdrawn because it is a duplicate of GHSA-v684-q882-jgmq. This link is maintained to preserve external references. ## Original Description SiYuan before v3.7.4 fails to properly validate publish access for encrypted notebooks, treating them as publicly accessible by default. Anonymous readers can enumerate and retrieve fully decrypted document content from unlocked ...
CVE-2026-17057 Newly scored	9.1	CRIT		0.004	ibm:i	IBM i 7.6, 7.5, 7.4, and 7.3 could allow a remote attacker to cause a denial of service and affect data integrity due to missing authentication for critical functions.
CVE-2026-17207 Newly scored	9.1	CRIT		0.003	ibm:i	IBM i 7.6, 7.5, 7.4, and 7.3 could allow a remote attacker to cause a denial of service and compromise integrity due to a buffer overflow.
CVE-2026-18664 Newly scored	9.1	CRIT		0.003	nlnetlabs:nsd	When ranges are used for access control (i.e. of the form 1.2.3.4-1.2.3.25), because NSD wrongly compares the IP address with the range on little endian systems, IPs that were meant to be allowed may be denied, and, IPs that were meant to be denied access could be allowed. An IPv4 address is compared with IPv4 ranges as unsigned 32 bit numbers directly with the endianness of the host, but the values to compare are...
CVE-2026-19874 Newly scored	9.1	CRIT		0.007		A heap-based buffer overflow vulnerability exists in Konami's Metal Gear Online 3, originating from improper validation of lobby data fields related to kicked players. The affected function processes a list of kicked player identifiers using the lobby data key "kick_num" to determine the number of entries, and individual kicked player IDs supplied via keys in the format "kicked_id_%i". The function does not valida...
CVE-2026-50152 Newly scored	9.1	CRIT		0.002		Ceph is an open-source distributed storage platform providing object, block, and file storage. In versions prior to 20.2.4 and 19.2.6, the Monitor subscription handler fails to properly authorize access to the configuration-key store, allowing any CephX user with only `mon allow r` capabilities to read the entire store by sending a single crafted MMonSubscribe message. The config-key store holds sensitive secrets...
CVE-2026-55511 Newly scored	9.1	CRIT		0.007		Yamcs is a mission control framework. Prior to 5.12.8 and 5.13.2, Yamcs allows a user with SystemPrivilege.ControlArchiving to create a double-quoted StreamSQL column name that is interpolated into generated Java source by Expression.fillCode_InputDefVars and Expression.sanitizeName. A sum aggregate reaches yamcs-core/src/main/java/org/yamcs/yarch/streamsql/CompilableAggregateExpression.java and yamcs-core/src/mai...
CVE-2026-62646 New	9.1	CRIT		0.003		A vulnerability has been identified in Reyrolle 7SR5 (All versions < V2.70). A session identifier is generated using an algorithm with insufficient randomness, resulting in a token with low entropy that can be predicted or brute-forced within a feasible number of attempts. This could allow an unauthenticated remote attacker to derive valid session identifiers and bypass authentication.
CVE-2026-69641 New	9.1	CRIT		0.008		Missing authorization in Microsoft Exchange Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-73309 New	9.1	CRIT		0.005	xenforo:xenforo	XenForo before 2.3.13 contains an authentication bypass vulnerability in the OAuth2 token endpoint that allows unauthenticated attackers to obtain valid token pairs by submitting empty values for client_secret and code_verifier parameters. Attackers can exploit PHP truthy evaluation logic, which treats empty strings as false and skips client secret validation and PKCE code verifier validation, to exchange a valid ...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-73311 New	9.1	CRIT		0.004	xenforo:xenforo	XenForo before 2.3.13 contains an OAuth2 authorization code reuse vulnerability that allows attackers to obtain unauthorized token pairs by submitting a previously used authorization code. Attackers can exploit the failure to invalidate or mark authorization codes as consumed after initial token issuance to receive an independent token pair for the same user and scopes, bypassing the single-use guarantee of the OA...
CVE-2026-73312 New	9.1	CRIT		0.004	xenforo:xenforo	XenForo before 2.3.13 contains a refresh token replay vulnerability that allows attackers to reuse a refresh token multiple times by exploiting the failure to mark tokens as consumed when the parent access token has expired. Attackers can repeatedly submit the same refresh token to generate additional independent token pairs, achieving persistent unauthorized access for the token's full lifetime.
CVE-2026-73475 Newly scored	9.1	CRIT		0.002	centarro:commerce_paypal	Incorrect Authorization vulnerability in Drupal Commerce PayPal allows Forceful Browsing. This issue affects Commerce PayPal versions: from 0.0.0 to 1.12.0, from 2.0.0 to 2.1.3.
CVE-2026-75156 New	9.1	CRIT		0.002		Apache Airflow FAB provider versions 3.7.3 through 3.8.0 do not validate the issuer or audience of Azure AD `id_token`s during OAuth login. Deployments are affected only when the FAB auth manager is configured with Azure AD as an OAuth provider. Because the signing keys are fetched from Microsoft's **multi-tenant** JWKS endpoint, an `id_token` minted in *any* Azure tenant — including one the attacker creates — pas...
CVE-2026-75160 Newly scored	9.1	CRIT		0.004		An issue in X-Serie Gateway Firmware V6_00_05 allows a remote attacker to escalate privileges via the endpoints /cgi-bin/wwwugw.cgi and /cgi-bin/ugwdownload.cgi.
CVE-2026-75431 Newly scored	9.1	CRIT		0.008		PowerJob Server version 5.1.2 (and likely earlier) uses a predictable JWT signing key for HS256-based authentication. This allows a remote attacker to execute arbitrary code.
CVE-2026-75595 Updated	9.1	CRIT		0.003	maven:io.netty:netty-handler fixed: 4.1.137.Final, 4.2.17.Final	#### Summary A fragmented TLS ClientHello whose handshake header spans multiple records makes Netty silently fall back to the default SslContext; where per-SNI selection is the sole mTLS gate, an unauthenticated attacker can bypass the route's mTLS requirement. #### Details In `io.netty.handler.ssl.SslClientHelloHandler#decode` the guard that should wait for the 4-byte handshake header checks the wrong offset - it ...
CVE-2026-75746 New	9.1	CRIT		0.011		ColdFusion is affected by an Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') vulnerability that could result in arbitrary code execution in the context of the current user. An attacker with high privileges could exploit this vulnerability to execute arbitrary code. Exploitation of this issue does not require user interaction. Scope is changed.
CVE-2026-78327 Newly scored	9.1	CRIT		0.016		An Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') vulnerability in the SonicWall Network Security Manager (NSM) On-Prem Management interface allows an authenticated attacker with SuperAdmin privileges to inject arbitrary commands that are executed on the underlying host, resulting in remote code execution.
CVE-2026-78328 Newly scored	9.1	CRIT		0.005		A missing authorization vulnerability in the SonicWall Network Security Manager (NSM) On-Prem Management interface allows a lower-privileged Admin user to escalate privileges to SuperAdmin.
CVE-2026-79571 New	9.1	CRIT		0.003		Incorrect access control in the SellerAuthorizeAspect component of springboot-project v1.0.0 allows unauthenticated attackers to access all seller management interfaces and list all products/orders, put products on/off sale, finish/cancel orders, and modify categories without authentication.
CVE-2026-80181 Newly scored	9.1	CRIT		0.004		Apache Allura's webhooks are vulnerable to Server-Side Request Forgery (SSRF). This issue affects Apache Allura: through 1.20.0. Users are recommended to upgrade to version 1.21.0, which fixes the issue.
CVE-2026-81939 Newly scored	9.1	CRIT		0.007		A Zip Slip vulnerability in the SonicWall Network Security Manager (NSM) On-Prem file upload and archive processing functionality allows an attacker to extract files outside the intended destination directory using a specially crafted archive.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-85043 Newly scored	9.1	CRIT		0.003	google:chrome	Incomplete cleanup in Network in Google Chrome prior to 152.0.7977.82 allowed a remote attacker to bypass system access restrictions via crafted network traffic. (Chromium security severity: High)
CVE-2026-86729 New	9.1	CRIT		0.002		WWBN AVideo through commit e01e41ecc (no patched version available) exposes get_api_preauthorize in plugin/API/API.php as a second, undocumented login path. Unlike get_api_signIn, which enforces a rate limit of 10 attempts per 5 minutes via checkRateLimit(), get_api_preauthorize performs the same credential check with no throttling for any client, allowing unlimited remote password guessing against arbitrary accou...
CVE-2026-86840 New	9.1	CRIT		0.002		The `vtoken-minting` and `slpx` pallets in Bifrost contain an improper authorization vulnerability in channel commission attribution. A signed account can supply an arbitrary registered `channel_id` when minting tokens without verifying that the caller is authorized to mint on behalf of that channel. This allows an attacker to inflate a channel's recorded mint volume and cause protocol commission payments to be di...
CVE-2026-53581 New	9.0	CRIT		0.003		OPNsense is a FreeBSD based firewall and routing platform. Prior to version 26.1.9 of opnsense/core and version 26.4_20 of BE/opnsense/core, a path traversal vulnerability in the NTP configuration module allows an attacker to overwrite arbitrary files on the system as the root user. By manipulating the GPS or PPS serial port parameter, an attacker with access to the NTP configuration can escape the intended direct...
CVE-2026-66768 New	9.0	CRIT		0.003		SAP GUI for Java does not correctly enforce the trust level policy for certain functions invoked from a connected backend system. A low-privileged attacker could exploit this weakness by manipulating a connected backend system to trigger affected functionality. This could allow arbitrary command execution on the victim's machine, leading to a high impact on the confidentiality, integrity, and availability of the a...
CVE-2026-69854 New	9.0	CRIT		0.006		Improper authentication in Spring Cloud Azure allows an unauthorized attacker to elevate privileges over a network.
CVE-2026-82021 Newly scored	9.0	CRIT		0.002		Hermes Agent 0.18.2 prior to 0.19.0 contains a supply chain vulnerability in its bundled MCP catalog that allows a remote attacker to execute arbitrary code by compromising a third-party upstream repository referenced via a mutable branch rather than a pinned commit SHA. An attacker who compromises the upstream repository can propagate malicious code to every host that installs the affected catalog entry, with no ...
CVE-2026-85982 New	9.0	CRIT		0.002		The Auth0 AD/LDAP Connector is vulnerable to stored Cross-Site Scripting (XSS) issues due to improper HTML encoding of data in search results and updater log content displayed in the admin panel. An authenticated user with privileges to modify directory attributes, or a low-privileged local user on the host where the connector is installed, could insert script content. This script content could then execute in an ...

Watchlist matches (other priorities)

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-55521 Newly scored	8.8	HIGH		0.004		Yamcs is a mission control framework. Prior to 5.12.8 and 5.13.2, Yamcs omits authorization checks in IndexesApi.listPacketIndex, IndexesApi.listEventIndex, Cop1Api.disable, Cop1Api.resume, Cop1Api.initialize, Cop1Api.updateConfig, and TimeApi.setTime. An authenticated low-privilege user can read packet and event index metadata without ObjectPrivilegeType.ReadPacket, alter COP-1 link state without SystemPrivilege....
CVE-2026-62706 New	8.8	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Microsoft Windows Media Foundation allows an unauthorized attacker to execute code over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-66814 New	8.8	HIGH		0.004	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Insufficient granularity of access control in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-66818 New	8.8	HIGH		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper privilege management in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-66819 New	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper neutralization of special elements used in an sql command ('sql injection') in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-66820 New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper neutralization of special elements used in an sql command ('sql injection') in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-67368 New	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper link resolution before file access ('link following') in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-67370 New	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper neutralization of special elements used in an sql command ('sql injection') in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-67373 New	8.8	HIGH		0.006	microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67380 New	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67381 New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-67384 New	8.8	HIGH		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Integer overflow or wraparound in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67385 New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use after free in SQL Server allows an authorized attacker to execute code over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-67388 New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67631 New	8.8	HIGH		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67638 New	8.8	HIGH		0.007	microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67639 New	8.8	HIGH		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67642 New	8.8	HIGH		0.005	microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67643 New	8.8	HIGH		0.008	microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-68775 New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-68786 New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-69266 New	8.8	HIGH		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Integer overflow or wraparound in Windows DHCP Server allows an unauthorized attacker to execute code over a network.
CVE-2026-69268 New	8.8	HIGH		0.007	microsoft:sharepoint_server	Improper access control in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.
CVE-2026-69273 New	8.8	HIGH		0.005	microsoft:sharepoint_server	Improper access control in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.
CVE-2026-69282 New	8.8	HIGH		0.005	microsoft:sharepoint_server	Improper access control in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69461 New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code over a network.
CVE-2026-69464 New	8.8	HIGH		0.009	microsoft:sharepoint_server	Execution with unnecessary privileges in Microsoft Office SharePoint allows an authorized attacker to elevate privileges over a network.
CVE-2026-69465 New	8.8	HIGH		0.008	microsoft:sharepoint_server	Missing authorization in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.
CVE-2026-69518 New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Remote Desktop allows an unauthorized attacker to execute code over a network.
CVE-2026-69669 New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Kernel allows an unauthorized attacker to execute code over a network.
CVE-2026-69716 New	8.8	HIGH		0.009	microsoft:sharepoint_server	Improper neutralization of special elements used in an sql command ('sql injection') in Microsoft Office SharePoint allows an authorized attacker to elevate privileges over a network.
CVE-2026-69724 New	8.8	HIGH		0.008	microsoft:sharepoint_server	Missing authorization in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.
CVE-2026-69860 New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-70203 New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Media Player allows an unauthorized attacker to execute code over a network.
CVE-2026-71336 New	8.8	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Integer overflow or wraparound in Windows Work Folder Service allows an authorized attacker to execute code over a network.
CVE-2026-73006 New	8.8	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Microsoft Graphics Component allows an unauthorized attacker to execute code over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-73016 New	8.8	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Microsoft Graphics Component allows an unauthorized attacker to execute code over a network.
CVE-2026-73028 New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper access control in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-77480 New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Insufficient granularity of access control in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-77481 New	8.8	HIGH		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-77482 New	8.8	HIGH		0.008	microsoft:sql_server_2017, microsoft:sql_server_2019	Heap-based buffer overflow in SQL Server allows an unauthorized attacker to execute code over a network.
CVE-2026-77483 New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Weak authentication in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-77484 New	8.8	HIGH		0.011	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Deserialization of untrusted data in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-77486 New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019	Integer overflow or wraparound in SQL Server allows an unauthorized attacker to execute code over a network.
CVE-2026-77487 New	8.8	HIGH		0.005	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Improper access control in SQL Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-77495 New	8.8	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-78456 New	8.8	HIGH		0.009	microsoft:sql_server_2022	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80083 New	8.8	HIGH		0.002	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Untrusted pointer dereference in Windows Hyper-V allows an authorized attacker to execute code locally.
CVE-2026-80096 New	8.8	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Remote Desktop Services allows an authorized attacker to elevate privileges over a network.
CVE-2026-83992 New	8.8	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Imaging Component allows an unauthorized attacker to execute code over a network.
CVE-2026-83996 New	8.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Error Reporting allows an authorized attacker to elevate privileges locally.
CVE-2026-55250 New	8.7	HIGH		0.006		Marvel, a PHP framework oriented towards dependency injection, prior to version 10.74.0 has a high-severity Token Replay Vulnerability arising from a structural lifecycle mismatch between stateless token validation engines and high-performance relational caching layers. Any application with low cache memory that causes premature eviction to free up memory and applications running macropay-solutions/maravel-framew...
CVE-2026-75133 Newly scored	8.7	HIGH		0.003		Keep Backup Daily plugin for WordPress before 2.1.4 contains a sensitive information exposure vulnerability that allows unauthenticated attackers to trigger a full MySQL database dump by accessing the publicly exposed `kbd_cron_process` parameter without authentication. Attackers can predict the partially predictable dump filename based on the database name, a limited random range, and the current Unix timestamp t...
CVE-2026-82064 New	8.7	HIGH		0.003	mongodb:mongodb	A security issue in MongoDB Server allows an unauthenticated network user to cause a denial of service on a specific type of replica set member. The server contains an assertion in its read concern processing logic that can be reached without authentication, and the assertion's assumptions about internal state do not hold for all member configurations, causing the server process to terminate.
CVE-2026-82075 New	8.7	HIGH		0.003	mongodb:mongodb	An uncontrolled resource consumption weakness exists in the request-handling path of the MongoDB sharded-cluster router process. A client that has network access to a router port and has not authenticated can supply connection-monitoring parameters that cause the server to expend CPU resources without any rate limiting, degrading or denying service to legitimate clients. No authentication, elevated privileges, or ...
CVE-2026-81525 Updated	8.6	HIGH		0.003	composer:mongodb/mongodb fixed: 1.21.4, 2.4.1	#### Impact Passing untrusted input as part of a database or collection name may result in targeting a different database or collection than specified. #### Patches Fixed in PHP library 1.21.4 and 2.4.1. #### Workarounds Validate database and collection names prior to passing into APIs.
CVE-2026-85388 Newly scored	8.6	HIGH		0.003		Worklenz through 3.0.0 fails to properly validate the sort-field query parameter in pagination helper functions, allowing authenticated users to inject arbitrary PostgreSQL expressions into ORDER BY clauses. Attackers can use time-based and boolean-based blind SQL injection techniques to extract sensitive database content including password hashes from other tenants. This is an incomplete fix for CVE-2026-25947.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-45221 Newly scored	8.5	HIGH		0.001		Konga before 2.1.0 contains a privilege escalation vulnerability that allows low-privileged local attackers to execute arbitrary code by planting attacker-controlled OpenSSL configuration or library files in a hardcoded filesystem path absent from default installations. On Windows, the missing directory resides in a location writable by any authenticated local user, enabling attackers to create the directory and p...
CVE-2026-67378 New	8.5	HIGH		0.005	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Untrusted pointer dereference in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67379 New	8.5	HIGH		0.006	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Stack-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-67636 New	8.5	HIGH		0.005	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to execute code over a network.
CVE-2026-76958 New	8.5	HIGH		0.002		SAP Integration Suite does not sufficiently validate XML documents accepted from untrusted sources in certain internal components. An attacker with low privileges could submit specially crafted XML payloads containing malicious external entity declarations. Successful exploitation could allow the attacker to read sensitive file contents from the server and expose them through monitoring or logging output, resultin...
CVE-2026-85656 Newly scored	8.5	HIGH		0.011		An OS command injection issue in the log4j-cve-2021-44228-hotpatch package in Amazon Linux before 1.3-9 might allow a local user to execute arbitrary commands with root privileges via a Java process whose executable path contains embedded newline characters.
CVE-2026-69479 New	8.4	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code locally.
CVE-2026-69638 New	8.4	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code locally.
CVE-2026-52767 Newly scored	8.2	HIGH		0.002		YesWiki is a wiki system written in PHP. From version 4.6.2 to before version 4.6.6, HttpSignatureService::verifySignature() checks the result of PHP's openssl_verify() with a loose boolean negation - if (!openssl_verify(...)) { throw ... }. PHP's openssl_verify has four possible return values: 1, 0, -1, and "false". The -1 row is the bypass: PHP's truthiness rules make -1 a truthy value, so !(-1) === false, the t...
CVE-2026-69846 New	8.2	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Secure Kernel Mode allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69906 New	8.2	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Secure Kernel Mode allows an authorized attacker to elevate privileges locally.
CVE-2026-75594 Newly scored	8.2	HIGH		0.005		Kirby is an open-source content management system. Prior to 4.9.5 and 5.5.2, depending on the release line, Kirby's media handler in src/Cms/Media.php allowed Kirby\Cms\Media::thumb() to append a path-bearing filename to a validated parent media directory. On nginx, PHP's built-in server, or Apache with AllowEncodedSlashes enabled, a remote attacker could submit encoded slash characters such as %2f in the filename...
CVE-2026-81354 New	8.2	HIGH		0.002	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Heap-based buffer overflow in Windows Hello allows an authorized attacker to elevate privileges locally.
CVE-2026-69510 New	8.1	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Stack-based buffer overflow in Windows DHCP Server allows an unauthorized attacker to execute code over a network.
CVE-2026-69620 New	8.1	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Stack-based buffer overflow in Windows DHCP Server allows an unauthorized attacker to execute code over a network.
CVE-2026-69813 New	8.1	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in Windows DNS allows an unauthorized attacker to execute code over a network.
CVE-2026-69858 New	8.1	HIGH		0.007	microsoft:windows_server_2022, microsoft:windows_server_2025	Use after free in Windows DNS allows an unauthorized attacker to execute code over a network.
CVE-2026-69989 New	8.1	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in DNS Server allows an unauthorized attacker to execute code over a network.
CVE-2026-70342 New	8.1	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Ancillary Function Driver for WinSock allows an unauthorized attacker to elevate privileges over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-70563 New	8.1	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper link resolution before file access ('link following') in Windows Shell allows an unauthorized attacker to perform spoofing over a network.
CVE-2026-78444 New	8.1	HIGH		0.005	microsoft:windows_10_1809, microsoft:windows_server_2019, microsoft:windows_server_2022, microsoft:windows_server_2025	Untrusted pointer dereference in Windows Failover Cluster allows an unauthorized attacker to execute code over a network.
CVE-2026-78450 New	8.1	HIGH		0.005	microsoft:windows_10_1809, microsoft:windows_server_2019, microsoft:windows_server_2022, microsoft:windows_server_2025	Use after free in Reliable Multicast Transport Driver (RMCAT) allows an unauthorized attacker to execute code over a network.
CVE-2026-78583 Newly scored	8.1	HIGH		0.002	elastic:kibana	Incorrect Authorization (CWE-863) in Kibana can lead to privilege escalation via Input Data Manipulation (CAPEC-153). Elasticsearch cluster privilege declarations originating from integration packages were not validated before being used to mint credentials for enrolled Elastic Agents. A user holding Fleet management privileges could therefore cause every Elastic Agent on a targeted policy to receive a credential ...
CVE-2026-78626 New	8.1	HIGH		0.002		The Okta Access Gateway improperly handles input sanitization and regular expression evaluation within its Protected Rule authorization check, resulting in an authorization bypass when an administrator has explicitly configured a Protected Rule policy on one or more application resources.
CVE-2026-82066 New	8.1	HIGH		0.002	mongodb:mongodb	A heap out-of-bounds read security issue exists in the query planning component of MongoDB Server. An authenticated user with database read and write privileges can trigger the security issue through crafted query operations, causing the server to read memory beyond allocated buffer boundaries. The revealed memory contents may be partially observable through diagnostic query statistics output.
CVE-2026-83997 New	8.1	HIGH		0.005	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Use after free in Windows Message Queuing allows an unauthorized attacker to execute code over a network.
CVE-2026-84393 New	8.1	HIGH		0.002		A improper validation of certificate with host mismatch vulnerability in Fortinet FortiOS 7.6.1 through 7.6.6, FortiProxy 7.6.2 through 7.6.6 may allow attacker to information disclosure via <insert attack vector here>
CVE-2026-68834 New	8.0	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges over a network.
CVE-2026-68838 New	8.0	HIGH		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Stack-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69332 New	8.0	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69412 New	8.0	HIGH		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Stack-based buffer overflow in Windows DHCP Server allows an authorized attacker to execute code over an adjacent network.
CVE-2026-69423 New	8.0	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Video Driver allows an authorized attacker to elevate privileges over a network.
CVE-2026-69503 New	8.0	HIGH		0.008	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Stack-based buffer overflow in Windows USB Driver allows an authorized attacker to elevate privileges over a network.
CVE-2026-69505 New	8.0	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69727 New	8.0	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges over a network.
CVE-2026-69773 New	8.0	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges over a network.
CVE-2026-69826 New	8.0	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69847 New	8.0	HIGH		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows DHCP Server allows an authorized attacker to execute code over an adjacent network.
CVE-2026-69875 New	8.0	HIGH		0.008	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69876 New	8.0	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in Windows DHCP Server allows an authorized attacker to execute code over an adjacent network.
CVE-2026-68787 New	7.8	HIGH		0.002	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code locally.
CVE-2026-68832 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-68841 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-68875 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Buffer over-read in Windows NTFS allows an authorized attacker to execute code locally.
CVE-2026-69265 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-69270 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69293 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69295 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69298 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69307 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69312 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-69323 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69352 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69421 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer underflow (wrap or wraparound) in Windows Kernel Mode Driver allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69475 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Untrusted pointer dereference in Windows Remote Desktop Services allows an authorized attacker to elevate privileges locally.
CVE-2026-69476 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69489 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69532 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-69571 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69580 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69583 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69584 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows USB Video Driver allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69589 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69593 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69687 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer underflow (wrap or wraparound) in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69707 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69709 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an authorized attacker to execute code locally.
CVE-2026-69738 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69787 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69822 New	7.8	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Numeric truncation error in Windows Kerberos allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69841 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Encrypting File System (EFS) allows an authorized attacker to elevate privileges locally.
CVE-2026-69844 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69900 New	7.8	HIGH		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Untrusted pointer dereference in Kernel Streaming WOW Thunk Service Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69907 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper handling of insufficient permissions or privileges in Windows Enterprise App Management allows an authorized attacker to elevate privileges locally.
CVE-2026-69921 New	7.8	HIGH		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Heap-based buffer overflow in Windows Print Spooler Components allows an authorized attacker to elevate privileges locally.
CVE-2026-70289 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Win32 Kernel Subsystem allows an authorized attacker to elevate privileges locally.
CVE-2026-70564 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Print Spooler Components allows an authorized attacker to elevate privileges locally.
CVE-2026-70569 New	7.8	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Out-of-bounds read in Windows Spaceport.sys allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-70572 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-70581 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-71334 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NFS Portmapper allows an authorized attacker to elevate privileges locally.
CVE-2026-71337 New	7.8	HIGH		0.003	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Stack-based buffer overflow in Windows Storage Management Provider allows an authorized attacker to elevate privileges locally.
CVE-2026-71343 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Remote Access Connection Manager allows an authorized attacker to execute code locally.
CVE-2026-72941 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72988 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72990 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-72991 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72992 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72993 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72994 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72995 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72996 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-72997 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73000 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-73001 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73002 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer overflow or wraparound in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73007 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73011 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73015 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73020 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73021 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-73026 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-76967 New	7.8	HIGH		0.002		SAP NetWeaver Business Client does not perform sufficient validation when processing certain locally stored data during application startup. An attacker with low privileges on the local system could replace this data with specially crafted content. When the application is next launched, the crafted content is processed and could lead to arbitrary code execution in the context of the user. This results in a high im...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-77489 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Null pointer dereference in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-77500 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Release of invalid pointer or reference in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-77503 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an unauthorized attacker to elevate privileges locally.
CVE-2026-77904 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Volume Manager Extension Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-78447 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-78448 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83498 New	7.8	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Untrusted pointer dereference in Windows Virtualization-Based Security (VBS) Enclave allows an authorized attacker to elevate privileges locally.
CVE-2026-83942 New	7.8	HIGH		0.002	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Missing authorization in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-83952 New	7.8	HIGH		0.002	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Heap-based buffer overflow in Windows Resilient File System (ReFS) allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83954 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83955 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83967 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83968 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83969 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83970 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83971 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83972 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83973 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83974 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83975 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83976 New	7.8	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83977 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83978 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83979 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83980 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83981 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83982 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83983 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83985 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83986 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83987 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83988 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83990 New	7.8	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Stack-based buffer overflow in Microsoft Graphics Component allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83995 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-84000 New	7.8	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Microsoft Graphics Component allows an authorized attacker to execute code locally.
CVE-2026-66767 New	7.7	HIGH		0.003		SAP NetWeaver Application Server for ABAP and ABAP Platform allows an unauthenticated user to send a specially crafted packet that triggers reprocessing of a previously buffered user request, potentially hijacking another user's session under narrow timing conditions. Successful exploitation could result in high impact on confidentiality and integrity, with low impact on availability of the application.
CVE-2026-69683 New	7.7	HIGH		0.008	microsoft:sharepoint_server	Server-side request forgery (ssrf) in Microsoft Office SharePoint allows an authorized attacker to disclose information over a network.
CVE-2026-78623 New	7.7	HIGH		0.002		The Okta Access Gateway does not sanitize SAML assertion values before interpolating them into database queries in the advanced mode datastore configuration. The unsanitized values are substituted directly into the query string prior to preparation, resulting in unintended SQL execution against the configured backend database.
CVE-2026-82053 New	7.6	HIGH		0.002	mongodb:mongodb	A security issue exists in MongoDB's LDAP authorization integration where pooled LDAP connections can retain stale authentication identities after user authentication under certain configurations. Subsequent authorization queries may execute under an unintended LDAP identity rather than the expected one. This can result in incorrect role assignments based on the LDAP directory's access control configuration, poten...
CVE-2026-55215 Newly scored	7.5	HIGH		0.004		MariaDB Connector/Node.js is used to connect applications developed on Node.js to MariaDB and MySQL databases. Prior to versions 3.3.3, 3.4.6, and 3.5.3, when ssl is enabled without a pinned CA or server certificate, MariaDB Connector/Node.js sends credentials before completing certificate fingerprint validation. In lib/cmd/handshake/auth/handshake.js, a server that selects mysql_clear_password as the initial auth...
CVE-2026-67376 New	7.5	HIGH		0.008	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Integer overflow or wraparound in SQL Server allows an unauthorized attacker to deny service over a network.
CVE-2026-69342 New	7.5	HIGH		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-69397 New	7.5	HIGH		0.006		Use after free in OpenSSH for Windows allows an unauthorized attacker to execute code over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69514 New	7.5	HIGH		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Remote Desktop Services allows an authorized attacker to execute code over a network.
CVE-2026-69539 New	7.5	HIGH		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Desktop Services allows an authorized attacker to execute code over a network.
CVE-2026-69599 New	7.5	HIGH		0.007	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Use after free in Windows Remote Desktop Services allows an authorized attacker to execute code over a network.
CVE-2026-69803 New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to disclose information over a network.
CVE-2026-69804 New	7.5	HIGH		0.005	microsoft:sharepoint_server	Time-of-check time-of-use (toctou) race condition in Microsoft Office SharePoint allows an authorized attacker to execute code over a network.
CVE-2026-69852 New	7.5	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Remote Code Execution in Windows Routing and Remote Access Service (RRAS) allows attacker to gain an unauthorized access to victim's machine
CVE-2026-69881 New	7.5	HIGH		0.012	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Null pointer dereference in Windows IKE Extension allows an unauthorized attacker to deny service over a network.
CVE-2026-69890 New	7.5	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Virtual Trusted Platform Module allows an authorized attacker to elevate privileges locally.
CVE-2026-69929 New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to disclose information over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69930 New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to disclose information over a network.
CVE-2026-70065 New	7.5	HIGH		0.012	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Missing release of memory after effective lifetime in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-70124 New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to disclose information over a network.
CVE-2026-70587 New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper null termination in Windows Remote Desktop Protocol allows an unauthorized attacker to disclose information over a network.
CVE-2026-71330 New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of sensitive system information to an unauthorized control sphere in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to disclose information over a network.
CVE-2026-72928 New	7.5	HIGH		0.006	microsoft:windows_server_2025	Use after free in Windows DNS allows an authorized attacker to execute code over a network.
CVE-2026-73017 New	7.5	HIGH		0.002	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Heap-based buffer overflow in Windows Graphics Kernel allows an authorized attacker to execute code locally.
CVE-2026-77494 New	7.5	HIGH		0.012	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77498 New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-77499 New	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77501 New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77502 New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77886 New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77888 New	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77889 New	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77890 New	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Access of resource using incompatible type ('type confusion') in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-77893 New	7.5	HIGH		0.008	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-77895 New	7.5	HIGH		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an unauthorized attacker to deny service over a network.
CVE-2026-78523 New	7.5	HIGH		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in Windows DNS allows an unauthorized attacker to deny service over a network.
CVE-2026-78574 New	7.5	HIGH		0.001		The Okta Hyperdrive Integration plugin resolves a required assembly using a registry path within the current user's hive without integrity verification. The referenced path is loaded via Assembly.LoadFrom without signature validation, resulting in an unverified assembly executing within the context of the host process or elevated installer.
CVE-2026-83989 New	7.5	HIGH		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Services for NFS ONCRPC XDR Driver allows an unauthorized attacker to deny service over a network.
CVE-2026-84001 New	7.5	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Key Distribution Center allows an unauthorized attacker to deny service over a network.
CVE-2026-78627 New	7.3	HIGH		0.001		The Okta Hyperdrive Integration installer does not mask the OAuth client secret when passed as an MSI property. The credential is recorded in plaintext in the installer log, the Application Event Log, and the process command line, all of which are readable by an authenticated local user on the workstation.
CVE-2026-82061 New	7.2	HIGH		0.003	mongodb:mongodb	A use-after-free security issue exists in the server's query execution memory tracking subsystem. An authenticated user with read privileges can trigger a write to freed heap memory through a sequence of standard database commands, leading to server process crash or potential memory corruption. No user interaction is required.
CVE-2026-82071 New	7.2	HIGH		0.003	mongodb:mongodb	Insufficient validation of storage engine configuration options in MongoDB Server allows an authenticated user with write privileges to supply crafted parameters during collection creation that override internal storage metadata. This results in an out-of-bounds memory write in the server process, causing a denial of service via server crash, with potential for further impact including arbitrary code execution.
CVE-2026-84387 New	7.2	HIGH		0.009		A improper neutralization of special elements used in a command ('command injection') vulnerability in Fortinet FortiSandbox 5.2.0, FortiSandbox 5.0.0 through 5.0.6, FortiSandbox 4.4.0 through 4.4.9 may allow attacker to execute unauthorized code or commands via <insert attack vector here>
CVE-2026-20293 New	7.1	HIGH		0.001		A vulnerability in the Unified Extensible Firmware Interface (UEFI) Shell implementation of Cisco UCS Servers and UCS-based appliances could allow an authenticated attacker with valid credentials for a user account with the role of user or admin or an unauthenticated attacker with physical access to an affected device to bypass UEFI Secure Boot validation checks and execute unauthorized software. This vuln...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-68846 New	7.1	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Kernel allows an authorized attacker to elevate privileges over a network.
CVE-2026-68893 New	7.1	HIGH		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Use after free in Windows Remote Desktop Licensing Service allows an authorized attacker to elevate privileges over a network.
CVE-2026-69340 New	7.1	HIGH		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an authorized attacker to elevate privileges over a network.
CVE-2026-69366 New	7.1	HIGH		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Kernel allows an authorized attacker to elevate privileges over a network.
CVE-2026-69536 New	7.1	HIGH		0.004	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Use after free in Windows Remote Desktop Services allows an authorized attacker to execute code over a network.
CVE-2026-82052 New	7.1	HIGH		0.004	mongodb:mongodb	The \$regexFindAll expression can be used by an authenticated user who can run aggregation pipeline stages to crash a MongoDB server (mongod). Under certain specific conditions the regex match can start in the middle of a multi-code-unit character, triggering an assertion during query execution.
CVE-2026-82054 New	7.1	HIGH		0.003	mongodb:mongodb	A security issue exists in MongoDB server's JSON Pointer parser used during \$jsonSchema query filter processing. When a find command includes a specially crafted \$jsonSchema filter field, the parser processes the input without enforcing adequate limits on iteration count or total allocation size, resulting in significant memory amplification. Under concurrent request load, the cumulative memory consumption can exh...
CVE-2026-82055 New	7.1	HIGH		0.003	mongodb:mongodb	A security issue exists in MongoDB's 2dsphere index key generation that can cause a server crash due to a null pointer dereference. When a specially crafted GeoJSON document is inserted into a collection with a 2dsphere index, an inconsistency in geometry parsing can leave an internal object in an invalid, partially initialized state. During subsequent index key generation, access to this improperly initialized ob...
CVE-2026-82057 New	7.1	HIGH		0.003	mongodb:mongodb	A security issue was discovered in MongoDB where an authenticated user with readWrite privileges could crash the mongod server process. By specifying a custom WiredTiger storage configuration option with an incompatible value during collection creation, a user could cause a type confusion in the storage engine layer. When documents were subsequently read from the misconfigured collection, the resulting mismatch in...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-82058 New	7.1	HIGH		0.003	mongodb:mongodb	A flaw in MongoDB's JSON Schema validation error generation code allows an authenticated user with readWrite privileges to crash the mongod server. When a BSON document containing an array with a malformed numeric field name fails a \$jsonSchema items type constraint, the error generation path performs unsafe numeric conversion on the user-controlled field name without proper exception handling, resulting in an unc...
CVE-2026-82065 New	7.1	HIGH		0.003	mongodb:mongodb	A security issue in the MongoDB Server's storage engine integration layer allows an authenticated user with collection creation privileges to cause a persistent denial of service. Insufficient validation of user-supplied storage configuration options permits values that, once persisted to durable metadata, trigger a fatal assertion failure when the metadata is subsequently read by diagnostic operations. The corrup...
CVE-2026-82068 New	7.1	HIGH		0.003	mongodb:mongodb	A security issue in MongoDB Server allows an authenticated user with write privileges to trigger a persistent fatal assertion crash by sending specially crafted retryable write commands. The crash state is durably persisted, causing the server process to repeatedly crash on restart and potentially propagating to additional nodes in a sharded cluster. Manual intervention is required to restore service availability.
CVE-2026-82070 New	7.1	HIGH		0.002	mongodb:mongodb	A security issue in MongoDB Server's diagnostic reporting interface allows an authenticated user with monitoring privileges to access insufficiently protected credentials from concurrent administrative operations. The same credentials are properly redacted in server log output, but the diagnostic interface omits equivalent redaction. Successful exploitation requires a valid authenticated session with monitoring-le...
CVE-2026-82073 New	7.1	HIGH		0.003	mongodb:mongodb	A security issue in the MongoDB Server aggregation framework allows an authenticated user with limited read privileges to bypass view-level authorization checks and access data from unauthorized collections when Atlas Search features are in use. The issue stems from insufficient validation of an internal command parameter that can be set by external clients, causing a security check to be improperly skipped.
CVE-2026-82074 New	7.1	HIGH		0.002	mongodb:mongodb	MongoDB Server contains an incorrect authorization vulnerability in the aggregation framework. An authenticated user with minimal privileges can craft a specially formatted aggregation request that causes the server's authorization subsystem to evaluate a different operation than what is actually executed, resulting in unauthorized read access to collection data within the target database.
CVE-2026-82076 New	7.1	HIGH		0.003	mongodb:mongodb	An integer overflow in the query planning component of MongoDB Server can allow an authenticated user with ordinary database-level read/write privileges to bypass an internal resource limit. Submitting a specially crafted query causes the server to consume memory without bound during query planning, and the resulting exhaustion terminates the server process. This may result in a denial of service affecting all dat...
CVE-2026-85689 Newly scored	7.1	HIGH		0.003		Ilmware 0.4.6 contains an SQL injection vulnerability in the collection-database layer (Ilmware/resources.py) where filter and lookup values are directly string-interpolated into SQL WHERE clauses without parameterization or escaping, in both the SQLite and PostgreSQL backends. The filter validator only checks keys against an allow-list and never sanitizes values. Attacker-controlled filter values reaching the pub...
CVE-2026-62727 Newly scored	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Telephony Service allows an authorized attacker to elevate privileges locally.
CVE-2026-68840 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows USB Driver allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-68884 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-69287 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Desktop Services allows an authorized attacker to elevate privileges locally.
CVE-2026-69319 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows USB Video Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69379 New	7.0	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Improper link resolution before file access ('link following') in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-69413 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.
CVE-2026-69422 New	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Use after free in Windows USB Video Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69466 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Time-of-check time-of-use (toctou) race condition in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-69473 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-69501 New	7.0	HIGH		0.002	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Untrusted pointer dereference in Windows Secure Kernel Mode allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69567 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows NTFS allows an authorized attacker to elevate privileges locally.
CVE-2026-69578 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Numeric truncation error in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-69814 New	7.0	HIGH		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Use after free in Windows Credential Providers allows an authorized attacker to elevate privileges locally.
CVE-2026-69816 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Accounts Control allows an authorized attacker to elevate privileges locally.
CVE-2026-69817 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Bluetooth Port Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-69818 New	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Use after free in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-69834 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows ALPC allows an authorized attacker to elevate privileges locally.
CVE-2026-69838 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Print Spooler Components allows an authorized attacker to elevate privileges locally.
CVE-2026-69859 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Time-of-check time-of-use (toctou) race condition in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69866 New	7.0	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69889 New	7.0	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Bluetooth Service allows an authorized attacker to elevate privileges locally.
CVE-2026-69891 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Media allows an authorized attacker to elevate privileges locally.
CVE-2026-69896 New	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Use after free in Windows Error Reporting allows an authorized attacker to elevate privileges locally.
CVE-2026-69911 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Microsoft Windows Search Component allows an authorized attacker to elevate privileges locally.
CVE-2026-70283 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Incorrect authorization in Windows Win32K allows an authorized attacker to elevate privileges locally.
CVE-2026-70562 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Double free in Windows Audio Service allows an authorized attacker to elevate privileges locally.
CVE-2026-70565 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows AF_UNIX Socket Provider allows an authorized attacker to elevate privileges locally.
CVE-2026-70567 New	7.0	HIGH		0.003	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Double free in Windows Display Enhancement Service allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-70568 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Defender Firewall Service allows an authorized attacker to elevate privileges locally.
CVE-2026-70573 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Biometric Service allows an authorized attacker to elevate privileges locally.
CVE-2026-71332 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Secure Socket Tunneling Protocol (SSTP) allows an authorized attacker to elevate privileges locally.
CVE-2026-71333 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Access Connection Manager allows an authorized attacker to elevate privileges locally.
CVE-2026-71340 New	7.0	HIGH		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows File History Service allows an authorized attacker to elevate privileges locally.
CVE-2026-71342 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Remote Access Connection Manager allows an authorized attacker to elevate privileges locally.
CVE-2026-73022 New	7.0	HIGH		0.002	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Modern Device Management (MDM) allows an authorized attacker to elevate privileges locally.
CVE-2026-77485 New	7.0	HIGH		0.002	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use after free in SQL Server allows an authorized attacker to elevate privileges locally.
CVE-2026-77894 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows Installer allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-77899 New	7.0	HIGH		0.002	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2012	Use after free in Windows Security Center allows an authorized attacker to elevate privileges locally.
CVE-2026-77905 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Management Instrumentation allows an authorized attacker to elevate privileges locally.
CVE-2026-78457 New	7.0	HIGH		0.002	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2022, microsof	Use after free in Windows Security Health Service allows an authorized attacker to elevate privileges locally.
CVE-2026-80093 New	7.0	HIGH		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Use after free in Windows Cloud Files Mini Filter Driver allows an authorized attacker to elevate privileges locally.
CVE-2026-82062 New	7.0	HIGH		0.004	mongodb:mongodb	A security issue in MongoDB Server allows an authenticated user with elevated internal privileges to bypass a disabled feature gate in the applyOps command by specifying an internal replication mode value that was not intended to be client-selectable. This bypass enables execution of container operations that are disabled by default in production configurations, allowing direct storage-engine writes to arbitrary i...
CVE-2026-83940 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Device Association Service allows an authorized attacker to elevate privileges locally.
CVE-2026-83999 New	7.0	HIGH		0.002	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Improper link resolution before file access ("link following") in Windows Resilient File System (ReFS) Deduplication Service allows an authorized attacker to elevate privileges locally.
CVE-2026-85360 New	7.0	HIGH		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Kernel allows an authorized attacker to elevate privileges locally.
CVE-2026-68833 New	6.8	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code with a physical attack.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69415 New	6.8	MEDI		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Missing authentication for critical function in Windows DHCP Server allows an authorized attacker to elevate privileges over a network.
CVE-2026-69490 New	6.8	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Mass Storage Class Driver allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-69566 New	6.8	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code with a physical attack.
CVE-2026-71329 New	6.8	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows NTFS allows an unauthorized attacker to execute code with a physical attack.
CVE-2026-71348 New	6.8	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Spaceport.sys allows an unauthorized attacker to execute code with a physical attack.
CVE-2026-76227 Newly scored	6.8	MEDI		0.001		Renovate versions from 42.68.1 before 42.96.3 (and from 42.68.1 before 43.4.4), including corresponding Docker images (renovate/renovate, mend/renovate-ce, renovate-ee-server, renovate-ee-worker >=13.3.0 <13.6.0), fail to restrict environment variables to an allowlist when spawning child processes. As a result, child processes (e.g. npm install, postUpgradeTasks, postUpdateOptions) gain full access to all environm...
CVE-2026-77892 New	6.8	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	No cwe for this issue in Windows Boot Manager allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-78451 New	6.8	MEDI		0.004	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Untrusted pointer dereference in Microsoft Windows SCSI Class System File allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-78579 New	6.8	MEDI		0.002		The Okta Access Gateway does not sanitize SAML assertion attribute values before interpolating them into LDAP search filters in the LDAP datastore configuration. The raw values are substituted directly into the filter string and passed to the LDAP search operation, resulting in modification of the intended query logic.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-71339 New	6.7	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows Installer allows an authorized attacker to elevate privileges locally.
CVE-2026-78625 New	6.7	MEDI		0.002		The Okta Access Gateway does not sanitize dashboard label values before writing them into generated PHP configuration files. The generated file is automatically included during authentication requests, resulting in execution with the privileges of the web server process.
CVE-2026-78630 New	6.7	MEDI		0.002		The Okta Access Gateway does not neutralize shell metacharacters in SNMP configuration values before a privileged script uses them to construct OS commands. An authenticated local user with access to the management interface can supply crafted values, resulting in the execution of arbitrary OS commands with root privileges.
CVE-2026-69469 New	6.6	MEDI		0.004	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Integer overflow or wraparound in Windows USB Audio Class driver (usbaudio.sys) allows an unauthorized attacker to elevate privileges with a physical attack.
CVE-2026-78545 New	6.6	MEDI		0.004		The Okta Access Gateway does not sanitize the application label field before including it in the generated nginx configuration file. The unsanitized value is interpolated into an nginx server block directive, resulting in execution of injected directives.
CVE-2026-78550 New	6.6	MEDI		0.004		The Okta Access Gateway management console passes user-supplied input to eval() without sanitization during an authenticated administrator SSH session. As a result, the unsanitized input is executed directly, leading to code execution with the privileges of the management console.
CVE-2026-44766 New	6.5	MEDI		0.002		SAP S/4HANA (Intercompany Matching and Reconciliation) allows a low-privileged authenticated user to inject malicious input into certain functions, which may be processed by the database without proper validation. This could allow the user to access sensitive information, resulting in high impact on confidentiality, with no impact on integrity and availability of the application.
CVE-2026-55545 Newly scored	6.5	MEDI		0.003		Yamcs is a mission control framework. Prior to 5.12.8 and 5.13.2, Yamcs WebSocket subscription handlers fail to enforce the privileges required by equivalent REST endpoints. PacketsApi.subscribePackets exposes the packets WebSocket topic without ObjectPrivilegeType.ReadPacket, ProcessingApi.subscribeAlgorithmStatus exposes the algorithm-status WebSocket topic without ObjectPrivilegeType.ReadAlgorithm, and MdbOverr...
CVE-2026-55855 Newly scored	6.5	MEDI		0.003		MariaDB Connector/Node.js is used to connect applications developed on Node.js to MariaDB and MySQL databases. Prior to 3.2.4, 3.3.3, 3.4.6, and 3.5.3, MariaDB Connector/Node.js permits SQL injection when attacker-controlled Buffer parameters are escaped client-side under the big5, gbk, sjis, cp932, or gb18030 client character sets. PacketOutputStream.writeBufferEscape in lib/io/packet-output-stream.js escaped byt...
CVE-2026-62801 New	6.5	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper limitation of a pathname to a restricted directory ('path traversal') in Windows PowerShell allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-66816 New	6.5	MEDI		0.007	microsoft:sql_server_2022, microsoft:sql_server_2025	Insufficient logging in SQL Server allows an authorized attacker to bypass a security feature over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-67369 New	6.5	MEDI		0.007	microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67383 New	6.5	MEDI		0.01	microsoft:sql_server_2025	Generation of error message containing sensitive information in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67386 New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use of uninitialized resource in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67389 New	6.5	MEDI		0.007	microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67390 New	6.5	MEDI		0.01	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Buffer over-read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67393 New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Buffer over-read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67633 New	6.5	MEDI		0.008	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to deny service over a network.
CVE-2026-67641 New	6.5	MEDI		0.006	microsoft:sql_server_2022, microsoft:sql_server_2025	Integer overflow or wraparound in SQL Server allows an authorized attacker to deny service over a network.
CVE-2026-67645 New	6.5	MEDI		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-67648 New	6.5	MEDI		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use of uninitialized resource in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68776 New	6.5	MEDI		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Use of uninitialized resource in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68777 New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-68778 New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68779 New	6.5	MEDI		0.006	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68780 New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68781 New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-68784 New	6.5	MEDI		0.007	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Out-of-bounds read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-69297 New	6.5	MEDI		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Storing passwords in a recoverable format in Windows DHCP Server allows an authorized attacker to disclose information over a network.
CVE-2026-69409 New	6.5	MEDI		0.01	microsoft:sharepoint_server	Execution with unnecessary privileges in Microsoft Office SharePoint allows an authorized attacker to disclose information over a network.
CVE-2026-69497 New	6.5	MEDI		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Missing release of memory after effective lifetime in Windows DHCP Server allows an authorized attacker to deny service over a network.
CVE-2026-69636 New	6.5	MEDI		0.01	microsoft:sharepoint_server	Improper neutralization of special elements used in an sql command ('sql injection') in Microsoft Office SharePoint allows an authorized attacker to disclose information over a network.
CVE-2026-69781 New	6.5	MEDI		0.005	microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:windows_server_2025	Missing release of memory after effective lifetime in Windows DHCP Client allows an unauthorized attacker to deny service over an adjacent network.
CVE-2026-69839 New	6.5	MEDI		0.011	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Uncaught exception in Windows iSCSI Target Service allows an authorized attacker to deny service over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-70019 New	6.5	MEDI		0.011	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Windows hard link in Windows Compressed Folder allows an unauthorized attacker to disclose information over a network.
CVE-2026-73029 New	6.5	MEDI		0.007	microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Buffer over-read in SQL Server allows an authorized attacker to disclose information over a network.
CVE-2026-75132 Newly scored	6.5	MEDI		0.003		WAPT Server versions 2.6.1.17834 and earlier contains a SQL injection vulnerability in the `columns` parameter of the GET `/api/v3/hosts` endpoint. A remote authenticated user with read-only privileges can inject arbitrary PostgreSQL expressions into the SQL query constructed by WAPT. By exploiting the injection point, an attacker can inject additional PostgreSQL statements, bypass the host scope restrictions appl...
CVE-2026-76968 New	6.5	MEDI		0.002		SAP Web Dispatcher, Internet Communication Manager and SAP Content Server allows an authenticated low-privileged attacker to access certain administrative functionality or interface and obtain sensitive information about the system state, resulting in information disclosure. This disclosed information could potentially be used to facilitate further attacks. This vulnerability has a high impact on the confidentiality...
CVE-2026-76971 New	6.5	MEDI		0.001		Due to a Server-Side Request Forgery (SSRF) vulnerability in SAP Manufacturing Integration and Intelligence, an attacker could cause the server to initiate arbitrary outbound requests. If processed by the application, this behavior could be combined with XML/XSL processing to enable execution of scripts. Successful exploitation could result in a low impact on the confidentiality, integrity, and availability of the...
CVE-2026-78453 New	6.5	MEDI		0.009	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Integer underflow (wrap or wraparound) in Microsoft Windows SCSI Class System File allows an unauthorized attacker to disclose information over a network.
CVE-2026-82059 New	6.5	MEDI		0.003	mongodb:mongodb	An internal aggregation expression in MongoDB Server was incorrectly registered as accessible to any authenticated user rather than being restricted to internal cluster operations. By crafting a malformed index specification within this expression, an authenticated user with read-only privileges could trigger an assertion failure in the index key generation code path. In certain build configurations, this assertio...
CVE-2026-82069 New	6.5	MEDI		0.003	mongodb:mongodb	A security issue in MongoDB Server's query statistics serialization on the router allows users with monitoring privileges to access unredacted search query text from other users' operations. An improper conditional check in the serialization logic causes the data redaction mechanism to be bypassed when processing search queries through the sharded cluster router. This results in sensitive query literals being stor...
CVE-2026-84391 New	6.5	MEDI		0.002		A use of uninitialized variable vulnerability in Fortinet FortiAnalyzer 7.6.3 through 7.6.6 may allow attacker to denial of service via <insert attack vector here>
CVE-2026-69874 New	6.4	MEDI		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Untrusted pointer dereference in Windows ALPC allows an authorized attacker to elevate privileges locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69878 New	6.4	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Heap-based buffer overflow in Windows DHCP Server allows an authorized attacker to execute code locally.
CVE-2026-71338 New	6.4	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Double free in Windows Failover Cluster allows an authorized attacker to elevate privileges locally.
CVE-2026-77887 New	6.4	MEDI		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an authorized attacker to execute code locally.
CVE-2026-77891 New	6.4	MEDI		0.002	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an authorized attacker to execute code locally.
CVE-2026-86590 New	6.3	MEDI		0.004		In Eclipse Che versions 7.79.0 through 7.121.0, the dashboard backend's POST /dashboard/api/data/resolver endpoint passes a caller-supplied URL directly to an outbound HTTP GET request with no host filtering. An authenticated user can exploit this server-side request forgery (SSRF) to read responses from internal network addresses, including the cloud instance metadata service (169.254.169.254), loopback interface...
CVE-2026-52773 Newly scored	6.1	MEDI		0.005		YesWiki is a wiki system written in PHP. From version 4.1.0 to before version 4.6.6, YesWiki's archived-revision view reflects the time GET parameter into a hidden HTML input in handlers/page/show.php without escaping. Because MySQL coerces malformed DATETIME strings, an attacker can append HTML or JavaScript to a valid archived revision timestamp, still load that archived revision, and execute arbitrary JavaScrip...
CVE-2026-78552 New	6.0	MEDI		0.003		The Okta Access Gateway does not apply its Lua directive restriction to the application-level custom configuration field. The field is interpolated directly into the nginx server block without inspection, resulting in execution of injected directives.
CVE-2026-78622 New	6.0	MEDI		0.001		The Okta Verify for Windows uninstaller does not verify whether the user data directory is a filesystem junction before deleting its contents with elevated privileges. The delete operation follows the junction target, resulting in recursive deletion of unintended directory contents.
CVE-2026-82056 New	6.0	MEDI		0.002	mongodb:mongodb	A race condition in MongoDB server's text index query parsing can cause a heap use-after-free read when handling upsert retry paths. Under certain concurrent index lifecycle operations, a raw pointer to internal text index metadata may be dereferenced after the underlying structures have been freed, leading to a server crash. An authenticated user with readWrite privileges can trigger this condition through specif...
CVE-2026-82063 New	6.0	MEDI		0.003	mongodb:mongodb	A use-after-free security issue in the cursor management component of MongoDB Server allows an authenticated user to cause a denial of service. Under specific timing conditions during cursor operations, a stale pointer to a freed resource may be retained and subsequently dereferenced during cursor cleanup, leading to a server process crash.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-55854 Newly scored	5.9	MEDI		0.003		MariaDB Connector/Node.js is used to connect applications developed on Node.js to MariaDB and MySQL databases. Prior to 3.2.4, 3.3.3, 3.4.6, and 3.5.3, MariaDB Connector/Node.js can disclose an account password when PAM dialog authentication is negotiated over an insecure transport. In lib/cmd/handshake/auth/pam-password-auth.js and lib/cmd/handshake/authentication.js, the SendPamAuthPacketFactory behavior for the...
CVE-2026-55856 Newly scored	5.9	MEDI		0.002		MariaDB Connector/J is used to connect applications developed in Java to MariaDB and MySQL databases. Prior to 2.7.14, 3.3.5, 3.4.3, and 3.5.9, when a Java application connects with sslMode=verify-full or sslMode=verify-ca, supplies a password, and does not configure serverSslCert or trustStore, Connector/J can accept an untrusted self-signed certificate through the fallbackToSystemTrustStore=true ephemeral trust ...
CVE-2026-55857 Newly scored	5.9	MEDI		0.002		MariaDB Connector/J is used to connect applications developed in Java to MariaDB and MySQL databases. Prior to 2.7.14, 3.3.5, 3.4.3, and 3.5.9, PAM dialog authentication can be coerced into transmitting the account password over an insecure connection. The mysql_clear_password plugin is gated behind a secure transport, but the sibling PAM handler SendPamAuthPacketFactory, named dialog by the server, does not decla...
CVE-2026-55858 Newly scored	5.9	MEDI		0.003		MariaDB Connector/J is used to connect applications developed in Java to MariaDB and MySQL databases. Prior to 2.7.14, 3.3.5, 3.4.3, and 3.5.9, the connector encodes and decodes protocol text and performs client-side escaping under the assumption that the connection character set is UTF-8. The server can report a mid-session change to character_set_client through OK-packet session-state tracking, including a chang...
CVE-2026-55859 Newly scored	5.9	MEDI		0.003		MariaDB Connector/R2DBC is a non-blocking MariaDB and MySQL client implemented in Java. Prior to 1.4.1, org.mariadb:r2dbc-mariadb encodes and decodes all character data under the assumption that the connection character set is UTF-8. A server can announce a mid-session change to character_set_client through the OK-packet session-state-tracking mechanism, including through SET NAMES executed by a stored routine or ...
CVE-2026-55860 Newly scored	5.9	MEDI		0.002		MariaDB Connector/R2DBC is a non-blocking MariaDB and MySQL client implemented in Java. Prior to 1.4.1, org.mariadb:r2dbc-mariadb does not gate clear-text password authentication plugins on transport encryption because the AuthenticationPlugin interface has no capability for a plugin to require a secure connection. A hostile or man-in-the-middle MariaDB server can send an AuthSwitchRequest naming mysql_clear_passw...
CVE-2026-70091 New	5.9	MEDI		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Concurrent execution using shared resource with improper synchronization ('race condition') in Windows DNS allows an unauthorized attacker to deny service over a network.
CVE-2026-78620 New	5.9	MEDI		0.003		The Okta Access Gateway Kerberos configuration handler does not validate file paths specified in event payloads before writing file contents. The path from the event payload is used directly as the write destination, resulting in files being written to unintended locations on the appliance filesystem.
CVE-2026-69405 New	5.7	MEDI		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Missing release of memory after effective lifetime in Windows DHCP Server allows an authorized attacker to deny service over an adjacent network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69591 New	5.7	MEDI		0.009	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to disclose information over a network.
CVE-2026-69637 New	5.7	MEDI		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an authorized attacker to deny service over an adjacent network.
CVE-2026-69679 New	5.7	MEDI		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_server_2012, microsoft:windows_server_2016, micr	Out-of-bounds read in Windows DHCP Server allows an authorized attacker to deny service over an adjacent network.
CVE-2026-69723 New	5.7	MEDI		0.01	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of sensitive system information to an unauthorized control sphere in Windows Kernel allows an authorized attacker to disclose information over a network.
CVE-2026-78629 New	5.6	MEDI		0.001		The Okta Hyperdrive agent plugin returns a success response without a signed SAML assertion when the organization's policy requires no MFA for a given user. The response contains only a bare boolean validation indicator with no cryptographic artifact, resulting in an unverifiable authentication verdict being delivered to the relying application.
CVE-2026-83557 Newly scored	5.6	MEDI		0.006		DefaultBaseTypeLimitingValidator is the PolymorphicTypeValidator applied automatically whenever @JsonTypeInfo is used without an explicitly configured custom validator. It denies polymorphic resolution only for a fixed set of "unsafe base types", and its isSafeSubType method returns true unconditionally for every base type outside that set. java.lang.Comparable was absent from the list despite being implemented by...
CVE-2026-68830 New	5.5	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper link resolution before file access ('link following') in Windows Universal Plug and Play (UPnP) Device Host allows an authorized attacker to disclose information locally.
CVE-2026-68831 New	5.5	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Files or directories accessible to external parties in Windows Defender Firewall Service allows an authorized attacker to disclose information locally.
CVE-2026-68851 New	5.5	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Buffer over-read in Windows NTFS allows an authorized attacker to disclose information locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69286 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Audio Class driver (usbaudio.sys) allows an authorized attacker to disclose information locally.
CVE-2026-69343 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Overlay Filter allows an authorized attacker to disclose information locally.
CVE-2026-69406 New	5.5	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of sensitive system information to an unauthorized control sphere in Windows Kernel allows an authorized attacker to disclose information locally.
CVE-2026-69457 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Driver allows an authorized attacker to disclose information locally.
CVE-2026-69504 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows NTFS allows an authorized attacker to disclose information locally.
CVE-2026-69527 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows USB Mass Storage Class Driver allows an authorized attacker to disclose information locally.
CVE-2026-69616 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Remote Desktop Services allows an authorized attacker to disclose information locally.
CVE-2026-69627 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Remote Desktop Licensing Service allows an authorized attacker to disclose information locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-69808 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Win32K allows an authorized attacker to disclose information locally.
CVE-2026-69862 New	5.5	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Wireless Wide Area Network Service allows an authorized attacker to disclose information locally.
CVE-2026-70145 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Microsoft Windows Search Component allows an authorized attacker to disclose information locally.
CVE-2026-70290 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use of uninitialized resource in Windows Win32 Kernel Subsystem allows an authorized attacker to disclose information locally.
CVE-2026-71341 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Partition Management Driver allows an authorized attacker to disclose information locally.
CVE-2026-73008 New	5.5	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of private personal information to an unauthorized actor in Windows Biometric Service allows an authorized attacker to disclose information locally.
CVE-2026-77488 New	5.5	MEDI		0.003	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Integer underflow (wrap or wraparound) in SQL Server allows an authorized attacker to disclose information locally.
CVE-2026-77491 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows GDI allows an unauthorized attacker to disclose information locally.
CVE-2026-78454 New	5.5	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows CD-ROM Driver allows an authorized attacker to disclose information locally.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-83501 New	5.5	MEDI		0.003	microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:windows_11_25h2, microsoft:windows_11_26h1, microsoft:wi	Out-of-bounds read in Windows Virtualization-Based Security (VBS) Enclave allows an authorized attacker to disclose information locally.
CVE-2026-83991 New	5.5	MEDI		0.003	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Missing authentication for critical function in Windows Cloud Files Mini Filter Driver allows an authorized attacker to perform tampering locally.
CVE-2026-86220 Newly scored	5.5	MEDI		0.003		A vulnerability was detected in SourceCodester Class and Exam Timetabling System 1.0. The affected element is the function mysqli_query of the file /admin/modal_add_course.php. The manipulation of the argument course results in sql injection. The attack can be launched remotely. The exploit is now public and may be used.
CVE-2026-86221 Newly scored	5.5	MEDI		0.003		A flaw has been found in SourceCodester Class and Exam Timetabling System 1.0. The impacted element is the function mysqli_query of the file /admin/modal_add_course1.php. This manipulation of the argument course causes sql injection. The attack may be initiated remotely. The exploit has been published and may be used.
CVE-2026-86223 Newly scored	5.5	MEDI		0.003		A vulnerability was found in SourceCodester Class and Exam Timetabling System 1.0. This impacts the function mysqli_query of the file /admin/modal_add_coursea.php. Performing a manipulation of the argument course results in sql injection. Remote exploitation of the attack is possible. The exploit has been made public and could be used.
CVE-2026-86225 Newly scored	5.5	MEDI		0.003		A vulnerability was identified in SourceCodester Class and Exam Timetabling System 1.0. Affected by this vulnerability is the function mysqli_query of the file /admin/modal_add_room.php. The manipulation of the argument room_name leads to sql injection. The attack is possible to be carried out remotely. The exploit is publicly available and might be used.
CVE-2026-86673 New	5.5	MEDI		0.003		A vulnerability was determined in ningzichun Student Management System up to 98760f5711cf6dc8b4adca53a9e207ca49b02ebf. Affected by this issue is the function mysqli_connect of the file config/database.php of the component Database Connection. This manipulation causes hard-coded credentials. The attack may be initiated remotely. The exploit has been publicly disclosed and may be utilized. This product uses a rollin...
CVE-2026-69402 New	5.4	MEDI		0.004	microsoft:sharepoint_server	Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Office SharePoint allows an authorized attacker to perform spoofing over a network.
CVE-2026-69417 New	5.4	MEDI		0.004	microsoft:sharepoint_server	Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Office SharePoint allows an authorized attacker to perform spoofing over a network.
CVE-2026-69690 New	5.4	MEDI		0.004	microsoft:sharepoint_server	Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Office SharePoint allows an authorized attacker to perform spoofing over a network.
CVE-2026-84385 New	5.4	MEDI		0.001		A improper access control vulnerability in Fortinet FortiSOAR PaaS 7.6.0 through 7.6.6, FortiSOAR PaaS 7.5.0 through 7.5.3, FortiSOAR PaaS 7.4 all versions, FortiSOAR PaaS 7.3 all versions, FortiSOAR on-premise 7.6.0 through 7.6.6, FortiSOAR on-premise 7.5.0 through 7.5.3, FortiSOAR on-premise 7.4 all versions, FortiSOAR on-premise 7.3 all versions may allow attacker to escalation of privilege via <insert attack v...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-19032 Newly scored	5.3	MEDI		0.005		jackson-databind's deserializer for java.nio.file.Path resolves an attacker-supplied URI without restricting the URI scheme. In JDKFromStringDeserializer.NioPathHelper.deserialize, a string bound from untrusted JSON is passed to new URI(value) and then to Path.of(uri). When that throws FileSystemNotFoundException, the code enumerates ServiceLoader<FileSystemProvider> and calls provider.getPath(uri) on the first pr...
CVE-2026-47680 New	5.3	MEDI		0.003		The source-controller is a Kubernetes operator, specialised in artifacts acquisition from external sources such as Git, OCI, Helm repositories and S3-compatible buckets. In versions 0.0.17 through 1.8.4, an actor with the ability to influence the contents of a bucket referenced by a `Bucket` resource can cause source-controller to write fetched object data to paths outside the per-reconciliation working directory....
CVE-2026-56704 Newly scored	5.3	MEDI		0.002		Adminer before 5.4.3 inserts unsanitized database server version strings into script tags with valid CSP nonces without proper validation. Attackers controlling a rogue MySQL server can return crafted version strings that break out of the JavaScript context and execute arbitrary code, bypassing Content Security Policy protections.
CVE-2026-78446 New	5.3	MEDI		0.006	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use after free in Windows Distributed File System (DFS) allows an authorized attacker to deny service over a network.
CVE-2026-78602 Newly scored	5.3	MEDI		0.004	elastic:maps_server	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (CWE-22) in Elastic Maps Server can lead to information disclosure via Path Traversal (CAPEC-126). An unauthenticated attacker able to reach the service over the network could cause it to return the contents of files outside its intended content directory that are readable by the server process.
CVE-2026-78631 New	5.3	MEDI		0.001		The Okta Hyperdrive Agent writes the decoded SAML bearer assertion to a local application log file at the default log level on every successful MFA completion. This insertion of sensitive information into the log file makes a live authentication credential readable by any local user with access to the log file.
CVE-2026-84386 New	5.1	MEDI		0.001		A unverified ownership vulnerability in Fortinet FortiClientWindows 7.4.0 through 7.4.7, FortiClientWindows 7.2 all versions may allow attacker to improper access control via <insert attack vector here>
CVE-2026-85781 Newly scored	5.1	MEDI		0.003		Unverified ownership of a storage access point in the volume deletion component of the Amazon EFS CSI Driver before v3.4.1 might allow an authenticated Kubernetes user with PersistentVolume creation privileges to cause recursive deletion of directories on an EFS filesystem they are not authorized to access, via a crafted PersistentVolume volumeHandle that pairs an access point from one filesystem with a different ...
CVE-2026-78635 New	5.0	MEDI		0.002		The Okta Privileged Access client URL handler does not insert an option terminator before appending the target value to the command-line arguments. When a scaleft:// protocol handler link contains a value beginning with a hyphen, the underlying CLI framework interprets it as a command-line flag, causing unintended modification of the SSH client's behavior.
CVE-2026-22575 New	4.9	MEDI		0.002		An improper access control vulnerability in Fortinet FortiManager 7.6.0 through 7.6.4, FortiManager 7.4.0 through 7.4.10, FortiManager 7.2 all versions, FortiManager Cloud 7.6.2 through 7.6.4, FortiManager Cloud 7.4.1 through 7.4.10, FortiManager Cloud 7.2 all versions may allow an administrator to bypass the approval process for workflow sessions via crafted HTTP or HTTPs requests.
CVE-2026-68785 New	4.9	MEDI		0.008	microsoft:sql_server_2017, microsoft:sql_server_2019, microsoft:sql_server_2022, microsoft:sql_server_2025	Heap-based buffer overflow in SQL Server allows an authorized attacker to execute code over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78624 New	4.9	MEDI		0.004		The Okta Access Gateway backup restore function does not validate the filename embedded in an encrypted backup payload. This results in writing file contents to unintended locations on the appliance filesystem.
CVE-2026-69615 New	4.8	MEDI		0.004	microsoft:sharepoint_server	Improper neutralization of input during web page generation ('cross-site scripting') in Microsoft Office SharePoint allows an authorized attacker to perform spoofing over a network.
CVE-2026-78560 New	4.8	MEDI		0.002		The Okta Access Gateway includes an optional pass-through authentication source that accepts user identity from a client-supplied HTTP header without cryptographic validation. In architectures where this optional source is enabled without an upstream reverse proxy or firewall configured to sanitize and enforce client headers, an unauthenticated user can supply an arbitrary identity value to initiate a session.
CVE-2026-18567 Newly scored	4.7	MEDI		0.001	ibm:db2_mirror_for_i	IBM Db2 Mirror for i 7.4, 7.5, and 7.6 could allow a local attacker to obtain information due to a race condition involving a predictable Unix domain socket path in a world-writable directory.
CVE-2026-68849 New	4.7	MEDI		0.002	microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:windows_11_24h2, microsoft:wi	Out-of-bounds read in Windows Bluetooth Port Driver allows an authorized attacker to disclose information locally.
CVE-2026-69832 New	4.7	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Exposure of sensitive system information to an unauthorized control sphere in Windows Win32K allows an authorized attacker to disclose information locally.
CVE-2026-69853 New	4.7	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Use of uninitialized resource in Windows Win32K allows an authorized attacker to disclose information locally.
CVE-2026-69895 New	4.7	MEDI		0.003	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows Spaceport.sys allows an authorized attacker to disclose information locally.
CVE-2026-69548 New	4.6	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Heap-based buffer overflow in Windows RNDIS allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-76959 New	4.6	MEDI		0.001		SAP S/4HANA Finance (Advanced Payment Management) does not perform sufficient Cross-Site Request Forgery protection on certain requests due to this an attacker with low privileges could craft a malicious link or page. If an authenticated victim interacts with it, unintended actions could be triggered on the web server on their behalf. This results in a low impact on confidentiality and integrity. There is no impac...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-78452 New	4.6	MEDI		0.005	microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:windows_11_23h2, microsoft:wi	Out-of-bounds read in Microsoft Windows SCSI Class System File allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-78508 New	4.6	MEDI		0.004	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Windows CD-ROM Driver allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-73019 New	4.3	MEDI		0.007	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Improper resolution of path equivalence in Windows URL Moniker allows an unauthorized attacker to bypass a security feature over a network.
CVE-2026-76962 New	4.3	MEDI		0.002		SAP S/4HANA (Manage Bank Chains app) does not perform sufficient authorization checks within certain affected functionality. An attacker with low privileges could send specially crafted requests to delete specific entries that should not be accessible to them. This results in a low impact on availability. There is no impact on confidentiality and integrity.
CVE-2026-76963 New	4.3	MEDI		0.002		Due to a missing authorization check in Application Server ABAP of SAP NetWeaver and ABAP Platform, an authenticated attacker could gain unauthorized access to sensitive system configuration information. Successful exploitation could result in exposure of security relevant settings and internal system details, resulting in low impact on confidentiality while integrity and availability remain unaffected.
CVE-2026-76977 New	4.3	MEDI		0.002		SAP UI5 does not sufficiently validate the parent frame's origin against the configured allowlist. An unauthenticated attacker could host a malicious page to bypass framing restrictions. If an authenticated victim visits the attacker's page and interacts with it, the attacker could trick the victim into performing unintended actions, resulting in a low impact on integrity. There is no impact on confidentiality and...
CVE-2026-78455 New	4.3	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Out-of-bounds read in Xbox allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-78516 New	4.3	MEDI		0.005	microsoft:windows_10_1607, microsoft:windows_10_1809, microsoft:windows_10_21h2, microsoft:windows_10_22h2, microsoft:wi	Buffer over-read in Windows Storage allows an unauthorized attacker to disclose information with a physical attack.
CVE-2026-78593 Newly scored	4.3	MEDI		0.002		An insufficiently validated configuration field in Kibana's Cribl integration allows an authenticated user holding Kibana Fleet management privileges to inject attacker-controlled expressions into a server-side script template, resulting in an Elasticsearch ingest pipeline being written beyond the caller's authorized Elasticsearch permissions.
CVE-2026-69904 New	3.5	LOW		0.006	microsoft:sharepoint_server	Server-side request forgery (ssrf) in Microsoft Office SharePoint allows an authorized attacker to disclose information over a network.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-76960 New	3.5	LOW		0.001		SAP S/4HANA Finance (Advanced Payment Management) does not perform sufficient Cross-Site Request Forgery protection on certain requests, due to this an attacker with low privileges could craft a malicious link or page. If an authenticated victim interacts with it, unintended actions could be triggered on the web server on their behalf. This results in a low impact on confidentiality and integrity. There is no impa...
CVE-2026-76961 New	3.5	LOW		0.001		SAP S/4HANA Finance (Advanced Payment Management) does not perform sufficient Cross-Site Request Forgery protection on certain requests, due to this an attacker with low privileges could craft a malicious link or page. If an authenticated victim interacts with it, unintended actions could be triggered on the web server on their behalf. This results in a low impact on confidentiality and integrity. There is no impa...
CVE-2026-84389 New	3.1	LOW		0.001		A url redirection to untrusted site ('open redirect') vulnerability in Fortinet FortiSIEM 7.5.0 through 7.5.1, FortiSIEM 7.4.1 through 7.4.2 may allow attacker to execute unauthorized code or commands via <insert attack vector here>
CVE-2026-84392 New	2.7	LOW		0.003		A NULL Pointer Dereference vulnerability [CWE-476] vulnerability in Fortinet FortiOS 7.4 all versions, FortiOS 7.2 all versions, FortiPAM 1.9.0, FortiPAM 1.8 all versions, FortiPAM 1.7 all versions, FortiPAM 1.6 all versions, FortiPAM 1.5 all versions, FortiPAM 1.4 all versions, FortiPAM 1.3 all versions, FortiPAM 1.2 all versions, FortiPAM 1.1 all versions, FortiPAM 1.0 all versions, FortiProxy 7.6.0 through 7.6....
CVE-2026-82060 New	2.3	LOW		0.002	mongodb:mongodb	In MongoDB, insufficient validation of shard key values during document insertion allowed authenticated users to store documents with specially crafted, operator-shaped objects as shard key values in sharded collections. When change stream events for such documents were processed with the updateLookup full document mode, the crafted values were embedded into internal post-image lookup queries without proper sanit...
CVE-2026-58234 New	2.2	LOW		0.002		SAP Process Integration (SOAP Adapter) allows a privileged user to send specially crafted requests containing deeply nested entity definitions, which under certain conditions could temporarily increase processor load and degrade system responsiveness. Successful exploitation results in low impact on availability with no impact on confidentiality and integrity.
CVE-2026-86517 New	2.1	LOW		0.002		A flaw has been found in itsourcecode Sales and Inventory System 1.0. The impacted element is the function mysqli_query of the file /pages/us_searchfrm.php. Executing a manipulation of the argument ID can lead to sql injection. It is possible to launch the attack remotely. The exploit has been published and may be used.
CVE-2026-85643 Newly scored	2.0	LOW		0.002		A flaw has been found in code-projects Online Shopping System 1.0. Impacted is the function mysqli_query of the file admin/adduser.php. Executing a manipulation of the argument mobile can lead to sql injection. The attack may be performed from remote. The exploit has been published and may be used.
CVE-2026-41855 Updated				0.003	maven:org.springframework:spring-jms fixed: 6.2.19, 7.0.8	In an untrusted JMS environment, org.springframework.jms.support.converter.MappingJackson2MessageConverter and org.springframework.jms.support.converter.JacksonJsonMessageConverter allow arbitrary class instantiation, which can lead to unauthorized actions via gadget class deserialization. Affected versions: Spring Framework 7.0.0 through 7.0.7; 6.2.0 through 6.2.18; 6.1.0 through 6.1.27; 5.3.0 through 5.3.48.
CVE-2026-84372 Updated				0.004	composer:predis/predis fixed: 3.3.0	### Summary An improper CRLF neutralization flaw in Predis' pipeline handling on aggregate connections lets an unauthenticated attacker who can influence any pipelined argument — a value **or** a key, e.g. a URL slug used as a cache key — smuggle arbitrary Redis commands into the connection. - On **cluster** connections (`cluster` option, incl. client-side sharding) this is remote command injection: shard-wide...
GHSA-2q33-cf8w-7q23 Updated					nuget:Microsoft.Native.Quic.MsQuic.OpenSSL	## Duplicate Advisory This advisory has been withdrawn because it is a duplicate of GHSA-92f5-vc22-8j33. This link is maintained to preserve external references. ## Original Description Use after free in Microsoft QUIC allows an unauthorized attacker to execute code over a network.