

Daily Vulnerability Report - 2026-09-13

Window (UTC): 2026-09-13T00:00 to 2026-09-14T00:00 | Sources: NVD, CISA KEV, EPSS, Vulnrichment, GHSA, OSV | Generated 2026-09-17 09:57:07 UTC

Total	New	Updated	KEV	Critical	High	Medium	Unscored	Watchlist	Packages
280	137	143	4	39	134	53	10	10	0

P1 - Act now (KEV / high EPSS)

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-58704 Added to KEV	8.8	HIGH	Yes	0.001	google:pixel	Google Pixel devices contain an improper authorization vulnerability in the cellular modem. A logic error may allow an attacker to bypass permission checks and escalate privileges.
CVE-2026-76460 Added to KEV			Yes		cisco:identity services engine	Cisco Identity Services Engine (ISE) and Cisco ISE Passive Identity Connector (ISE-PIC) contain an incorrect use of privileged APIs vulnerability that could allow an unauthenticated, remote attacker to gain unauthorized access to the affected device by bypassing the web-based management interface.
CVE-2026-76461 Added to KEV			Yes	0.02	cisco:secure email gateway	Cisco AsyncOS software for Cisco Secure Email Gateway (SEG) contains a SQL injection vulnerability that could allow an unauthenticated, remote attacker to execute arbitrary commands with root privileges on the underlying operating system.
CVE-2026-87886 Added to KEV			Yes		acronis:backup	Acronis Backup plugin for cPanel & WHM and extension for Plesk contains an incorrect default permissions vulnerability that could allow for privilege escalation.

P2 - High (CVSS >= 9.0 or 7.0+ with EPSS >= 0.10)

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-81648 New	10.0	CRIT		0.003		The CryptoPayment Gateway WordPress plugin from 1.2.1 to 1.2.2 does not apply an authorization check on one of its AJAX endpoints, allowing unauthenticated users to invoke administrative operations, including deleting arbitrary files on the server, overwriting the payment gateway configuration and recovering stored wallet credentials in cleartext.
CVE-2026-80926 Newly scored	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ksmbd: fix use-after-free in oplock break notification smb2_oplock_break_noti() reads opinfo->conn without any lock and dereferences it after two allocations which may sleep. When the durable handle owning the oplock is disconnected, session_fd_check() clears opinfo->conn and drops its conn reference under ci->m_lock, and the last ksmbd_conn_pu...
CVE-2026-80980 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: stop killed, freed and out_of_sync sharing a byte The three connection state flags are single-bit bitfields, so they occupy one byte of struct smc_connection and every store to one is a read-modify-write of the other two: u8 killed : 1; u8 freed : 1; u8 out_of_sync : 1; They are not written under a common lock. smc_cdc...
CVE-2026-80981 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: fix use-after-free of the LLC qentry in smc_llc_srv_add_link() smc_llc_srv_add_link() keeps add_llc pointing into the queue entry: add_llc = &qentry->msg.add_link; smc_llc.c:1482 ... smc_llc_save_add_link_info(link_new, add_llc); smc_llc.c:1494 smc_llc_flow_qentry_del(&lgr->llc_flow_lcl); smc_llc.c:1495 ... u8 *llc_msg =...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-80986 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: net/smc: bound the peer rkey counts in SMC-Rv2 LLC messages On a link whose device has max_rcv_sge == 1 there is no shared v2 receive buffer, and smc_llc_save_add_link_rkeys() takes the v2 extension from 44 bytes past the start of the queue entry's inline message: ext = (struct smc_llc_msg_add_link_v2_ext *)(&llc_msg + SMC_WR_TX_SIZE); The e...
CVE-2026-89492 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ocfs2: validate directory-index entry counts when reading metadata ocfs2_validate_dx_leaf() and ocfs2_validate_dx_root() check the ECC and signature of an indexed-directory block before it reaches higher-level callers, but neither validator bounds the ocfs2_dx_entry_list counts against the capacity of the block that holds them. ocfs2_dx_dir_sea...
CVE-2026-89526 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Validate Read chunk positions before reconstruction The RPC/RDMA Read chunk position field is supplied by the remote client and stored verbatim in the parsed chunk list. xdr_count_read_segments() checks only 4-byte alignment; it never compares the position against the received inline body length. In the single-chunk path, svc_rdma_read...
CVE-2026-89530 Newly scored	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: svcrdma: Reject inline replies that overflow the pull-up buffer An RPC-over-RDMA client can request a reply, such as an NFS READ payload, without providing a Write list or a Reply chunk to carry it. When such a reply needs more scatter/gather entries than the device's Send Queue supports, svc_rdma_pull_up_needed() selects pull-up and svc_rdma_pu...
CVE-2026-89546 Newly scored	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: close backchannel before destroying callback service A backchannel receive can complete a request while the NFS callback service is being torn down. xprt_complete_bc_request() removes the request from bc_pa_list, drops bc_alloc_count, marks the request in use, and then asks xprt_enqueue_bc_request() to hand it to the callback service. ...
CVE-2026-89558 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: md/raid10: fix still_degraded being inverted in raid10_sync_request() Commit fe6a19d40ceb ("md/md-bitmap: merge md_bitmap_start_sync() into bitmap_operations") converted still_degraded from int to bool, but inverted the assignment in the loop that checks whether the array will still be degraded after the current device is recovered: "still_degra...
CVE-2026-89610 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: verify run length exceeding volume boundary The mapping pairs decoder validates that the starting LCN is within the volume but does not check if the run extends beyond the volume boundary. A malformed NTFS image with a crafted mapping pairs array could cause the kernel to access memory beyond the volume boundary, potentially leading to me...
CVE-2026-89611 Newly scored	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ntfs: validate non-resident attribute offsets ntfs_attr_update_meta() shifts the attribute name when converting between non-sparse and sparse attributes. Converting to sparse also adds the compressed_size field before the name and mapping pairs, requiring eight additional bytes in the attribute record. However, the validator does not check that...
CVE-2026-89612 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: reject invalid MFT LCNs from boot sector The NTFS boot sector stores the MFT and MFTMirr locations as unsigned 64-bit LCNs, but parse_ntfs_boot_sector() decoded them into an s64. A crafted high-bit value could therefore become negative and pass the existing upper-bound check. The invalid value then propagated into the MFT zone allocator a...
CVE-2026-89613 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ntfs: reject invalid empty mapping pairs Reject an attribute with empty mapping pairs if it has inconsistent highest VCN and size.
CVE-2026-89614 Newly scored	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ntfs: bound the free-cluster bitmap scan to the volume vol->lc_n_empty_bits_per_page is sized from vol->nr_clusters at mount, but ntfs_cluster_alloc() bounds its scan of that array by the size of \$Bitmap. Those are independent on-disk quantities and the mount-time check only rejects a \$Bitmap that is too small, so an image whose \$Bitmap covers mo...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89633 Newly scored	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix OOB read/write from unvalidated DataOffset in coalesce_t2() coalesce_t2() computes data pointers directly from server-supplied DataOffset fields with no validation against buffer bounds: data_area_of_tgt = (char *)&pSMBt->hdr.Protocol + get_unaligned_le16(&pSMBt->t2_rsp.DataOffset); data_area_of_src = (...
CVE-2026-89635 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ksmbd: only rebind the reopened file's own oplock on durable reconnect ksmbd_reopen_durable_fd() walks the inode's m_op_list and rebinds every detached oplock to the reconnecting session: list_for_each_entry_rcu(op, &ci->m_op_list, op_entry, lockdep_is_held(&ci->m_lock)) { if (op->conn) continue; op->conn = ksmbd_conn_get(fp->conn);...
CVE-2026-89637 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: smb: client: fix UAF and buffer leak in cifs_check_trans2() for malformed secondary T2 When a valid primary TRANSACT2 response has been received (mid->resp_buf set, mid->multiRsp true) and a subsequent secondary response causes cifs_check_trans2() to return false -- either because the SMB header is invalid (malformed != 0) or because check2ndT2(...
CVE-2026-89651 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: ceph: bound MDSCapAuth path and fs_name decode in handle_session() handle_session() decodes the MDSCapAuth records carried by a CEPH_SESSION_OPEN message (msg_version >= 6). For each record the match.path and match.fs_name byte strings are read by first decoding a 32-bit length and then copying that many bytes with the bare ceph_decode_copy(). U...
CVE-2026-89654 Newly scored	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: ceph: fix UAF in check_new_map() on session freed during unlock check_new_map() iterates mdsc->sessions[] and for each active session drops mdsc->mutex to perform per-session operations. The forced-close path (rank removed from map) correctly takes a reference on s via ceph_get_mds_session() before releasing mdsc->mutex, but three other paths d...
CVE-2026-89658 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during NFSv4.0 revoked-state cleanup nfs40_clean_admin_revoked() takes a stateid reference under clp->cl_lock, drops nn->client_lock, and calls nfsd4_drop_revoked_stid(), which dereferences the stateid's client through s->sc_client->cl_lock. The stateid reference does not pin the client, so a teardown racing ...
CVE-2026-89659 Newly scored	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during delegation revoke A delegation stateid holds only a bare pointer to its owning nfs4_client and does not keep it alive. The client survives its stateids only because __destroy_client() drains cl_delegations and cl_revoked before free_client() runs. nfs4_laundromat() breaks that invariant: it unhashes a...
CVE-2026-89660 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: Prevent client use-after-free during admin state revocation A stateid holds only a bare pointer to its nfs4_client; a stateid reference does not pin it. The client survives only because __destroy_client() drains its stateids before free_client() runs. nfsd4_revoke_states() drops nn->client_lock across revoke_one_stid(), which dereference...
CVE-2026-89675 Newly scored	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix UAF in async copy cancel and shutdown An async copy could be freed or used after free while a teardown caller (OFFLOAD_CANCEL, nfsd4_shutdown_copy, nfsd4_cancel_copy_by_sb) raced the copy kthread: - find_async_copy() bumped copy->refcount but left the copy on clp->async_copies, so the reaper's cleanup_async_copy() could run ...
CVE-2026-89676 Newly scored	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix stale s2s_cp_stateids IDR entry for async COPY For an async COPY, nfsd4_copy() called nfs4_init_copy_state() before dup_copy_fields(), so the s2s_cp_stateids IDR was pointed at &u->copy->cp_stateid -- memory in the per-rqstp COMPOUND buffer that is reused by the next request. dup_copy_fields() copies only the value into async_copy, so ...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89677 Newly scored	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix possible fh_compose of wrong dentry in nfsd4_create_file() dentry_create() can hypothetically provide a different dentry than the one passed in. This could happen, for example, if the exported filesystem is NFS, and the server returned to OPEN a filehandle which matched a directory that was already in the dcache. Clearly this would n...
CVE-2026-89681 Newly scored	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix layout fence worker double-reference race The workqueue core clears WORK_STRUCT_PENDING before the callback is invoked, so delayed_work_pending() in lm_breaker_timedout() can return false while the fence worker is already running. This lets the breaker take a duplicate sc_count reference and schedule a new worker that coalesces with th...
CVE-2026-89686 Newly scored	9.8	CRIT		0.007		In the Linux kernel, the following vulnerability has been resolved: nfsd: fix BUG_ON in nfsd4_alloc_layout_stateid on racing delegation revoke nfsd4_alloc_layout_stateid reads fp->fi_deleg_file without holding fi_lock when the parent stateid is a delegation. A concurrent delegation revoke via the laundromat can clear fi_deleg_file under fi_lock, causing nfsd_file_get() to return NULL and triggering the BUG_ON. ...
CVE-2026-89688 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: drop the stateid, not the stateowner, on seqid_op replay retry In nfs4_preprocess_seqid_op() the stateid is obtained from nfsd4_lookup_stateid(), which holds a reference on the nfs4_stid (sc_count) but takes no reference on the stateowner. openlockstateid() merely casts that stid and likewise takes no reference. When nfsd4_cstate_assign_r...
CVE-2026-89689 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: don't free session slots that are still in use nfsd4_sequence() can free the very slot it is currently processing. When the session shrinker has reduced se_target_maxslots below se_fchannel.maxreqs, the shrink path checks three conditions before calling free_session_slots(): 1. se_target_maxslots < maxreqs (shrink was advertised) 2. ...
CVE-2026-89702 Newly scored	9.8	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: nfsd: size fh_verify server sockaddr slot by xpt_locallen The nfsd_fh_verify and nfsd_fh_verify_err tracepoints declare the server sockaddr slot sized by xpt_remotelen but fill it from xpt_local using xpt_locallen: TP_STRUCT__entry(... __sockaddr(server, rqstp->rq_xprt->xpt_remotelen) ...) TP_fa...
CVE-2026-89703 Newly scored	9.8	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: nfsd: set SC_STATUS_FREED in nfsd4_drop_revoked_stid for delegations nfsd4_drop_revoked_stid() handles FREE_STATEID for admin-revoked delegations but does not set SC_STATUS_FREED before releasing cl_lock. revoke_delegation() uses this flag to detect whether FREE_STATEID has already processed the delegation -- without it, the freed delegation is ...
CVE-2026-89708 Newly scored	9.8	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: nfsd: RCU-protect cl_cb_session to fix use-after-free on session teardown After a DESTROY_SESSION the per-session teardown path can free a session while rpciod still holds an inflight callback rpc_task that dereferences clp->cl_cb_session. nfsd4_probe_callback_sync() flushes cl_callback_wq, but once nfsd4_run_cb_work() has called rpc_call_async...
CVE-2026-90562 New	9.2	CRIT		0.004		LangBot before 4.10.11 generates password recovery keys with only 24 bits of entropy and applies no rate limiting to the unauthenticated reset-password endpoint. Remote attackers knowing the administrator email can exhaust the keyspace through concurrent requests to reset the admin password and gain account access.
CVE-2026-80945 Newly scored	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: crypto: iaa - unmap dst before software fallback on decompress On a hardware analytics error, decompress retries through the software fallback, which writes req->dst with the CPU while it is still mapped DMA_FROM_DEVICE. With SWIOTLB active the later dma_unmap_sg() copies the stale bounce buffer over req->dst, corrupting the result. Unmap befor...

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-89537 Newly scored	9.1	CRIT		0.005		In the Linux kernel, the following vulnerability has been resolved: SUNRPC: Reject short RFC 4121 MIC tokens in gss_krb5_verify_mic_v2 gss_krb5_verify_mic_v2() reads the token ID at ptr[0..1], the flags byte at ptr[2], and padding at ptr[3..7], then passes ptr + GSS_KRB5_TOK_HDR_LEN and cksum_len to gss_krb5_mic_build_sg(). None of these accesses check read_token->len first. The minimum safe token size is GSS_K...
CVE-2026-89630 Newly scored	9.1	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: smb: client: restore the data_offset bound in is_valid_oplock_break() Commit 83bfbd0bb902 ("cifs: Remove the RFC1002 header from smb_hdr") changed the quantity this bound is measured against. It used to be srv->total_read minus the 4-byte RFC1002 preamble that total_read then included, so it was the SMB message length. The same commit stopped ...
CVE-2026-89631 Newly scored	9.1	CRIT		0.004		In the Linux kernel, the following vulnerability has been resolved: smb: client: reject a tree connect response whose byte count is too small CIFSTCon() bounds its strlen() over the byte area with the server's ByteCount minus two, which for ByteCount 0 or 1 goes negative as an int and converts to a huge size_t. The later subtraction wraps the __u16 bytes_left, and that is what bounds cifs_strndup_from_utf16():...
CVE-2026-89713 Newly scored	9.1	CRIT		0.006		In the Linux kernel, the following vulnerability has been resolved: NFSD: check truncate permission under inode lock nfsd_setattr() checks whether a size update needs NFSD_MAY_TRUNC before it takes inode_lock(). The comparison uses the file size sampled by that unlocked read, but the actual ATTR_SIZE update is applied later under inode_lock() by notify_change(). This leaves a TOCTOU window for append-only files...

Watchlist matches (other priorities)

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-90772 New	8.3	HIGH		0.002		Amundsen frontend through 4.3.0 renders table, dashboard, and feature descriptions with dangerouslySetInnerHTML without HTML sanitization in ResourceListItem components. Attackers can inject malicious markup like img elements with onerror handlers into descriptions via the metadata service or Elasticsearch, executing JavaScript in every user's browser that views search results.
CVE-2026-90651 New	8.1	HIGH		0.002		Socket Firewall (socketdev/socket-registry-firewall) in registry mode before 2.0.0 does not verify upstream TLS certificates by default. When the api_ssl_verify and upstream_ssl_verify configuration keys are omitted from socket.yml, the generated configuration sets SOCKET_API_SSL_VERIFY='false' and UPSTREAM_SSL_VERIFY='false', and the OpenResty/Lua HTTP client used for outbound requests accepts any certificate, in...
CVE-2026-90775 New	6.5	MEDI		0.003		PostGIS address_standardizer through 3.7.0 fails to validate the Weight parameter from caller-supplied rules tables before using it as an array index. Attackers can craft malicious rule rows with out-of-range Weight values to trigger out-of-bounds reads in the load_value array, causing the PostgreSQL backend process to crash and terminate all cluster sessions.
CVE-2026-90563 New	5.1	MEDI		0.002		A vulnerability was determined in maliangnansheng bbs-springboot 3.0.0. This affects the function utils.toToc of the file ArticleController.java. This manipulation causes cross site scripting. The attack is possible to be carried out remotely.
CVE-2026-90581 New	2.1	LOW		0.002		A vulnerability was determined in cym1102 nginxWebUI up to 4.4.2. This issue affects the function MainController.autoUpdate of the file /adminPage/main/autoUpdate. This manipulation of the argument url causes code injection. Remote exploitation of the attack is possible. The exploit has been publicly disclosed and may be utilized. The pull request to fix this issue awaits acceptance.

ID	CVSS	Sev	KEV	EPSS	Vendor / Product / Package	Description
CVE-2026-90594 New	2.1	LOW		0.002		A vulnerability was identified in wxiaoqi Spring-Cloud-Platform 3.0.1/3.1.0. This vulnerability affects the function <code>PermissionService.checkUserPermission</code> of the file <code>/rpc/service/PermissionService.java</code> of the component Permission Service. The manipulation leads to missing authorization. Remote exploitation of the attack is possible. The exploit is publicly available and might be used. The project was informed of ...
CVE-2026-90595 New	2.1	LOW		0.002		A security flaw has been discovered in wxiaoqi Spring-Cloud-Platform 1.0/2.2/3.0. This issue affects the function <code>OnlineController.getOnlineInfo</code> of the file <code>aceModules/ace-admin/auth/controller/OnlineController.java</code> . The manipulation results in missing authorization. The attack can be executed remotely. The exploit has been released to the public and may be used for attacks. The project was informed of the problem...
CVE-2026-90598 New	2.1	LOW		0.002		A vulnerability was detected in jaygajera17 E-commerce-project-springBoot up to 5e74a46b4b70623d0e4a0c9c4aee3bd1777185d2. The impacted element is the function <code>UserController.updateUser</code> of the file <code>UserController.java</code> . Performing a manipulation of the argument <code>userid</code> results in authorization bypass. It is possible to initiate the attack remotely. The exploit is now public and may be used. This product is using a ro...

P3/P4 items (237) are in the Excel report. Unscored CVEs are newly published and awaiting NVD analysis; re-check tomorrow's report.