

MODULE 4

BAYESIAN LEARNING

Bayesian reasoning provides a probabilistic approach to inference. It is based on the assumption that the quantities of interest are governed by probability distribution and that optimal decisions can be made by reasoning about these probabilities together with observed data.

Introduction

Bayesian learning methods are relevant to study of machine learning for two different reasons.

- 1] First, Bayesian learning algorithms that calculate explicit probabilities for hypotheses, such as the naive Bayes classifier are among the most practical approaches to certain types of learning problems.
- 2] The second reason is that they provide a useful perspective for understanding many learning algorithms that do not explicitly manipulate probabilities.

Features of Bayesian Learning Methods.

- * Each observed training example can incrementally decrease or increase the estimated probability that a hypothesis is correct. This provides a more flexible approach to learning than algorithms that completely eliminate a hypothesis if it is found to be inconsistent with any single example.
- * Prior knowledge can be combined with observed data to determine the final probability of a hypothesis. In Bayesian learning, prior knowledge is provided by asserting (1) a prior probability for each candidate hypothesis, and (2) a probability distribution over observed data for each possible hypothesis.

- * Bayesian methods can accommodate hypotheses that make probabilistic predictions.
- * New instances can be classified by combining the predictions of multiple hypotheses, weighted by their probabilities.
- * Even in cases where Bayesian methods prove computationally intractable, they can provide a standard of optimal decision making against which other practical methods can be measured.

Practical difficulty in applying Bayesian methods

- 1] One practical difficulty in applying Bayesian methods is that they typically require initial knowledge of many probabilities. When these probabilities are not known in advance they are often.
- 2] A second practical difficulty is the significant computational cost required to determine the Bayes optimal hypothesis in the general case. In certain specialized situations, this computational cost can be significantly reduced.

BAYES THEOREM

Bayes theorem provides a way to calculate the probability of a hypothesis based on its prior probability, the probability of observing various data given the hypothesis, and the observed data itself.

Notations

- * $P(h)$ prior probability of h , reflects any background knowledge about the chance that h is wrong.
- * $P(D)$ prior probability of D , probability that D will be observed
- * $P(D|h)$ probability of observing D given a world in which h holds.
- * $P(h|D)$ posterior probability of h , reflects confidence that h holds after D has been observed.

Bayes theorem is the cornerstone of Bayesian learning methods because it provides a way to calculate the posterior probability $P(h|D)$, from the prior probability $P(h)$ together with $P(D)$ and $P(D|h)$.

Bayes Theorem:

$$P(h|D) = \frac{P(D|h) P(h)}{P(D)}$$

- * $P(h|D)$ increases with $P(h)$ and with $P(D|h)$ according to Bayes theorem.
- * $P(h|D)$ decreases as $P(D)$ increases, because the more probable it is that D will be observed independent of h , the less evidence D provides in support of h .

Maximum a Posteriori (MAP) Hypothesis

- * In many learning scenarios, the learner considers some set of candidate hypotheses H and is interested in finding the most probable hypothesis $h \in H$ given the observed data D . Any such maximally probable hypothesis is called a maximum a posteriori (MAP) hypothesis.
- * Bayes theorem to calculate the posterior probability of each candidate hypothesis is h_{MAP} is a MAP hypothesis provided.

$$\begin{aligned} h_{MAP} &= \operatorname{argmax}_{h \in H} P(h|D) \\ &= \operatorname{argmax}_{h \in H} \frac{P(D|h) P(h)}{P(D)} \\ &= \operatorname{argmax}_{h \in H} P(D|h) P(h). \end{aligned}$$

- * $P(D)$ can be dropped, because it is a constant independent of h .

Maximum likelihood (ML) Hypothesis

- * In some cases, it is assumed that every hypothesis in H is equally probable a priori ($P(h_i) = P(h_j)$ for all h_i and h_j in H)
- * In this case the below equation can be simplified and need only consider the term $P(D|h)$ to find the most probable hypothesis.

$$h_{MAP} = \operatorname{argmax}_{h \in H} P(D|h) P(h)$$

The equation can be simplified.

$$h_{ML} = \operatorname{argmax}_{h \in H} P(D|h)$$

$P(D|h)$ is often called the likelihood of the data D given h , and any hypothesis that maximizes $P(D|h)$ is called a maximum likelihood (ML) hypothesis.

Example

- * Consider a medical diagnosis problem in which there are two alternative hypotheses:
 - (1) that the patient has particular form of cancer.
 - (2) that the patient does not. The available data is from a particular laboratory test with two possible outcomes: + (positive) and - (negative).
- * We have prior knowledge that over the entire population of people only .008 have this disease. Furthermore, the lab test is only an imperfect indicator of the disease.
- * The test returns a correct positive result in only 98% of the cases in which the disease is actually present and a correct negative result in only 97% of the cases in which the disease is not present. In other cases, the test returns the opposite result.
- * The above situation can be summarized by the following.

Probabilities:

$$P(\text{cancer}) = .008 \quad P(-\text{cancer}) = 0.992.$$

$$P(\oplus | \text{cancer}) = .98 \quad P(\ominus | \text{cancer}) = .02.$$

$$P(\oplus | -\text{cancer}) = .03 \quad P(\ominus | -\text{cancer}) = .97.$$

Suppose a new patient is observed for whom the lab test returns a positive (+) result. Should we diagnose the patient as having cancer or not?

$$P(\oplus | \text{cancer}) P(\text{cancer}) = (.98) \cdot .008 = .0078$$

$$P(\oplus | -\text{cancer}) P(-\text{cancer}) = (.03) \cdot 0.992 = .0298$$

$$\Rightarrow h_{MAP} = -\text{cancer}.$$

The exact posterior probabilities can also be determined by normalizing the above quantities so that they sum to 1.

$$P(\text{cancer} | \oplus) = \frac{0.0078}{0.0078 + 0.0298} = 0.21.$$

$$P(-\text{cancer} | \oplus) = \frac{0.0298}{0.0078 + 0.0298} = 0.79.$$

Basic formulas for calculating probabilities are summarized in Table.

* Product rule: probability $P(A \wedge B)$ of a conjunction of two events A and B.

$$P(A \wedge B) = P(A | B) P(B) = P(B | A) P(A).$$

* Sum rule: probability of a disjunction of two events A and B

$$P(A \vee B) = P(A) + P(B) - P(A \wedge B).$$

* Bayes theorem: the posterior probability $P(h | D)$ of h given D.

$$P(h | D) = \frac{P(D | h) P(h)}{P(D)}.$$

* Theorem of total probability: if events A_1, \dots, A_n are mutually exclusive with $\sum_{i=1}^n P(A_i) = 1$, then

$$P(B) = \sum_{i=1}^n P(B|A_i) P(A_i).$$

Bayes Theorem and Concept Learning

What is the relationship between Bayes theorem and the problem of concept learning?

Since Bayes theorem provides a principled way to calculate the posterior probability of each hypothesis given the training data, and can use it as the basis for a straight forward learning algorithm that calculates the probability for each possible hypothesis, then outputs the most probable.

Bouite - Force Bayes Concept Learning.

Consider the concept learning problem.

* Assume the learner considers some finite hypothesis space H defined over the instance space X , in which the task is to learn some target concept $c: X \rightarrow \{0, 1\}$.

* Learner is given some sequence of training examples $((x_1, d_1), \dots, (x_m, d_m))$ where x_i is some instance from X and where d_i is the target value of x_i (i.e., $d_i = c(x_i)$).

* The sequence of target values are written as $D = (d_1, \dots, d_m)$

We can design a straightforward concept learning algorithm to output the maximum a posteriori hypothesis, based on Bayes theorem, as follows:

Bouite - Force Map Learning algorithm:

I For each hypothesis h in H , calculate the posterior probability

$$P(h|D) = \frac{P(D|h) P(h)}{P(D)}$$

2] Output the hypothesis h_{MAP} with the highest posterior probability.

$$h_{MAP} = \underset{h \in H}{\operatorname{argmax}} P(h/D)$$

In order to specify a learning problem for the BRUTE FORCE MAP LEARNING algorithm we must specify what values are to be used for $P(h)$ and for $P(D/h)$?

Let's choose $P(h)$ and for $P(D/h)$ to be consistent with the following assumptions:

- * The training data D is noise free (i.e., $d_i = c(x_i)$)
- * The target concept c is contained in the hypothesis space H
- * Do not have a priori reason to believe that any hypothesis is more probable than any other.

What values should we specify for $P(h)$?

- * Given no prior knowledge that one hypothesis is more likely than another, it is reasonable to assign the same prior probability to every hypothesis h in H .
- * Assume the target concept is contained in H and require that these prior probabilities sum to 1.

$$P(h) = \frac{1}{|H|} \text{ for all } h \in H$$

What choice shall we make for $P(D/h)$?

- * $P(D/h)$ is the probability of observing the target values $D = (d_1, \dots, d_m)$ for the fixed set of instances (x_1, \dots, x_m) , given a world hypothesis h holds.
- * Since we assume noise-free training data, the probability of observing classification d_i given h is just 1 if $d_i = h(x_i)$ and 0 if $d_i \neq h(x_i)$. Therefore,

$$P(D/h) = \begin{cases} 1 & \text{if } d_i = h(x_i) \text{ for all } d_i \in D \\ 0 & \text{otherwise.} \end{cases}$$

Given three choices for $P(h)$ and for $P(D|h)$ we now have a fully-defined problem for the above BRUTE-FORCE MAP LEARNING algorithm.

Recalling, Bayes theorem, we have:

$$P(h|D) = \frac{P(D|h) P(h)}{P(D)}$$

Consider the case where h is inconsistent with the training data D .

$$P(h|D) = \frac{0 \cdot P(h)}{P(D)} = 0$$

The posterior probability of a hypothesis inconsistent with D is zero.

Consider the case where h is consistent with D .

$$P(h|D) = \frac{\frac{1}{|H|} \cdot \frac{1}{|H|}}{P(D)} = \frac{\frac{1}{|H|}}{\frac{|VS_{H,D}|}{|H|}} = \frac{1}{|VS_{H,D}|}$$

where, $VS_{H,D}$ is the subset of hypotheses from H that are consistent with D .


To summarize, Bayes theorem implies that the posterior probability $P(h|D)$ under our assumed $P(h)$ and $P(D|h)$ is

$$P(D|h) = \begin{cases} \frac{1}{|VS_{H,D}|} & \text{if } h \text{ is consistent with } D \\ 0 & \text{otherwise.} \end{cases}$$

The Evolution of Probabilities Associated with Hypotheses

- * Figure (a) all hypotheses have the same probability.
- * Figure (b) and (c), As training data accumulates, the posterior probability for inconsistent hypotheses becomes zero while the total probability summing to 1 is shared equally among

the remaining consistent hypotheses.



MAP Hypotheses and Consistent Learners

- * A learning algorithm is a consistent learner if it outputs a hypothesis that commits zero errors over the training examples.
- * Every consistent learner outputs a MAP hypothesis, if we assume a uniform prior probability distribution over H ($P(h_i) = P(h_j)$ for all i, j), and deterministic, noise free training data ($P(D|h) = 1$ if D and h are consistent, and 0 otherwise).

Example :

- * FIND-S outputs a consistent hypothesis, it will output a MAP hypothesis under the probability distributions $P(h)$ and $P(D|h)$ defined above.
- * Are there other probability distributions for $P(h)$ and $P(D|h)$ under which FIND-S outputs MAP hypotheses? Yes.
- * Because FIND-S outputs a maximally specific hypothesis from the version space, its output hypothesis will be a MAP hypothesis relative to any prior probability distribution that favours more specific hypotheses.

Note

- * Bayesian framework is a way to characterize the behaviour of learning algorithms.
- * By identifying probability distributions $P(h)$ and $P(D|h)$ under which the output is a optimal hypothesis, implicit assumption of the algorithm can be characterized (Inductive Bias).
- * Inductive inference is modelled by an equivalent probabilistic reasoning system based on Bayes theorem.

Maximum Likelihood And Least-Squared Error Hypothesis

Consider the problem of learning a continuous-valued target function such as neural network learning, linear regression, and polynomial curve fitting.

A straightforward Bayesian analysis will show that under certain assumptions any learning algorithm that minimizes the squared error between the output hypothesis predictions and the training data will output a maximum likelihood [ML] hypothesis.

- * Learner L consider an instance space X and a hypothesis space H consisting of some class of real-valued functions defined over X , i.e., $(\forall h \in H)[h: X \rightarrow \mathbb{R}]$ and training examples of the form $\langle x_i, d_i \rangle$
- * The problem faced by L is to learn an unknown target function $f: X \rightarrow \mathbb{R}$
- * A set of m training examples is provided, where the target value of each example is corrupted by random noise drawn according to a Normal probability distribution with zero mean ($d_i = f(x_i) + e_i$)
- * Each training example is a pair of the form (x_i, d_i) where $d_i = f(x_i) + e_i$.

⇒ Here $f(x_i)$ is the noise-free value of the target function and e_i is a random variable representing the noise.
 ⇒ It is assumed that the values of the e_i are drawn independently and that they are distributed according to a Normal distribution with zero mean.

* The task of the learner is to output a maximum likelihood hypothesis or a MAP hypothesis assuming all hypotheses are equally probable a priori

Using the definition of h_{ML} we have:

$$h_{ML} = \operatorname{argmax}_{h \in H} p(D|h)$$

Assuming training examples are mutually independent given h , we can write $P(D|h)$ as the product of the various $p(d_i|h)$

$$h_{ML} = \operatorname{argmax}_{h \in H} \prod_{i=1}^m p(d_i|h)$$

Given the noise e_i obeys a Normal distribution with zero mean and unknown variance σ^2 , each d_i must also obey a Normal distribution around the true target value $f(x_i)$. Because we are writing the expression for $P(D|h)$, we assume h is the correct description of f .

$$\text{Hence, } h = f(x_i) = h(x_i)$$

$$h_{ML} = \operatorname{argmax}_{h \in H} \prod_{i=1}^m \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{1}{2\sigma^2}(d_i - h)^2}$$

$$h_{ML} = \operatorname{argmax}_{h \in H} \prod_{i=1}^m \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{1}{2\sigma^2}(d_i - h(x_i))^2}$$

Maximize the less complicated logarithm, which is justified because of the monotonicity of function p .

$$h_{ML} = \underset{h \in H}{\operatorname{argmax}} \sum_{i=1}^m \ln \frac{1}{\sqrt{2\pi\sigma^2}} - \frac{1}{2\sigma^2} (d_i - h(x_i))^2$$

The first term in this expression is a constant independent of h , and can therefore be discarded, yielding.

$$h_{ML} = \underset{h \in H}{\operatorname{argmax}} \sum_{i=1}^m - \frac{1}{2\sigma^2} (d_i - h(x_i))^2$$

Maximizing this negative quantity is equivalent to minimizing the corresponding positive quantity

$$h_{ML} = \underset{h \in H}{\operatorname{argmin}} \sum_{i=1}^m \frac{1}{2\sigma^2} (d_i - h(x_i))^2$$

Finally, discard constants that are independent of h .

$$h_{ML} = \underset{h \in H}{\operatorname{argmin}} \sum_{i=1}^m (d_i - h(x_i))^2$$

Thus, above equation shows that the maximum likelihood hypothesis h_{ML} is the one that minimizes the sum of the squared errors between the observed training values d_i and the hypothesis predictions $h(x_i)$

Note :

Why is it reasonable to choose the Normal distribution to characterize noise?

- * Good approximation of many types of noise in physical systems
- * Central Limit Theorem shows that the sum of a sufficiently large number of independent, identically distributed random variables itself obeys a Normal distribution. Only noise in the target value is considered, not in the attributes describing the instances themselves.

Maximum Likelihood Hypotheses For Predicting Probabilities

- * Consider the setting in which we wish to learn a nondeterministic (probabilistic) function $f: X \rightarrow \{0, 1\}$, which has two discrete output values.
- * We want a function approximator whose output is the probability that $f(x) = 1$. In other words, learn the target function $f': X \rightarrow [0, 1]$ such that $f'(x) = P(f(x) = 1)$.

How can we learn f' using a neural network?

- * One of brute force way would be to first collect the observed frequencies of 1's and 0's for each possible value x and to train the neural network to output the target frequency for each x .

What criterion should we optimize in order to find a maximum likelihood hypothesis for f' in this setting?

- * First obtain an expression for $P(D|h)$.
- * Assume the training data D is of the form $D = \{(x_1, d_1), \dots, (x_m, d_m)\}$, where d_i is the observed 0 or 1. value for $f(x_i)$
- * Both x_i and d_i as random variables, and assuming that each training example is drawn independently, we can write $P(D|h)$ as.

$$P(D|h) = \prod_{i=1}^m P(x_i, d_i|h) \quad \dots \text{equ(1)}$$

Applying the product rule.

$$P(D|h) = \prod_{i=1}^m P(d_i|h, x_i) P(x_i) \quad \dots \text{equ(2)}$$

The probability $P(d_i|h, x_i)$.

$$P(d_i | h, x_i) = \begin{cases} h(x_i) & \text{if } d_i = 1 \\ (1 - h(x_i)) & \text{if } d_i = 0 \end{cases} \quad \dots \text{equ(3)}$$

Re-express it in a more mathematically manipulable form, as:

$$P(d_i | h, x_i) = h(x_i)^{d_i} (1 - h(x_i))^{1-d_i} \quad \dots \text{equ(4)}$$

Equation (4) to substitute for $P(d_i | h, x_i)$ in equ(5) to obtain

$$P(D|h) = \prod_{i=1}^m h(x_i)^{d_i} (1 - h(x_i))^{1-d_i} P(x_i) \quad \dots \text{equ(5)}$$

We write an expression for the maximum likelihood hypothesis

$$h_{ML} = \operatorname{argmax}_{h \in H} \prod_{i=1}^m h(x_i)^{d_i} (1 - h(x_i))^{1-d_i} P(x_i).$$

The last term is a constant independent of h , so it can be dropped.

$$h_{ML} = \operatorname{argmax}_{h \in H} \prod_{i=1}^m h(x_i)^{d_i} (1 - h(x_i))^{1-d_i} \quad \dots \text{equ(6)}$$

It easier to work with the log of the likelihood, yielding

$$h_{ML} = \operatorname{argmax}_{h \in H} \sum_{i=1}^m d_i \ln h(x_i) + (1 - d_i) \ln (1 - h(x_i)). \quad \dots \text{equ(7)}$$

Equation (7) describes the quantity that must be maximized in order to obtain the maximum likelihood hypothesis in our current problem setting.

Gradient Search to Maximize Likelihood in a Neural Net

- * Derive a weight-adjusting rule for neural network learning that seeks to maximize $G(h, D)$ using gradient ascent.
- * The gradient of $G(h, D)$ is given by the vector of partial derivatives of $G(h, D)$ with respect to the various network weights that define the hypothesis h represented by the learned network.
- * In this case, the partial derivative of $G(h, D)$ with respect to weight w_{jk} from input k to unit j is

$$\begin{aligned}\frac{\partial G(h, D)}{\partial w_{jk}} &= \sum_{i=1}^m \frac{\partial G(h, D)}{\partial h(x_i)} \frac{\partial h(x_i)}{\partial w_{jk}} \\ &= \sum_{i=1}^m \frac{\partial (d_i \ln h(x_i) + (1-d_i) \ln(1-h(x_i)))}{\partial h(x_i)} \frac{\partial h(x_i)}{\partial w_{jk}} \\ &= \sum_{i=1}^m \frac{d_i - h(x_i)}{h(x_i)(1-h(x_i))} \frac{\partial h(x_i)}{\partial w_{jk}} \quad \text{equation (1)}.\end{aligned}$$

- * Suppose our neural network is constructed from a single layer of sigmoid units. Then,

$$\frac{\partial h(x_i)}{\partial w_{jk}} = \sigma'(x_i) x_{ijk} = h(x_i)(1-h(x_i)) x_{ijk},$$

where x_{ijk} is the k^{th} input to unit j for the i^{th} training example, and $\sigma(x)$ is the derivative of the sigmoid squashing function.

- * Finally, substituting this expression into equation (1), we obtain a simple expression for the derivatives that constitute the gradient.

$$\frac{\partial G(h, D)}{\partial w_{jk}} = \sum_{i=1}^m (d_i - h(x_i)) x_{ijk}$$

Because we seek to maximize rather than minimize $P(D|h)$, we perform gradient ascent rather than gradient descent search. On each iteration of the search the weight vector is adjusted in the direction of the gradient, using the weight update rule.

$$w_{jk} \leftarrow w_{jk} + \Delta w_{jk}$$

where,

$$\Delta w_{jk} = \eta \sum_{i=1}^m (d_i - h(x_i)) x_{ijk} \quad \text{equ(2)}$$

where, η is a small positive constant that determines the step size of the gradient ascent search.

Minimum Description Length Principle.

- * A Bayesian Perspective on Occam's razor.
- * Motivated by interpreting the definition of h_{MAP} in the light of basic concepts from information theory.

$$h_{MAP} = \underset{h \in H}{\operatorname{argmax}} P(D|h) P(h).$$

which can be equivalently expressed in terms of maximizing the logs.

$$h_{MAP} = \underset{h \in H}{\operatorname{argmax}} \log_2 P(D|h) + \log_2 P(h).$$

or alternatively, minimizing the negative of this quantity.

$$h_{MAP} = \underset{h \in H}{\operatorname{argmin}} -\log_2 P(D|h) - \log_2 P(h) \quad \text{equ(1)}$$

This equation (1) can be interpreted as a statement that short hypotheses are preferred, assuming a particular representation scheme for encoding hypothesis and data.

* $-\log_2 P(h)$: the description length of h under the optimal encoding for the hypothesis space H , $L_H(h) = -\log_2 P(h)$, where C_H is the optimal code for hypothesis space H .

* $-\log_2 P(D|h)$: the description length of the training data D given hypothesis h , under the optimal encoding from the hypothesis space H : $L_{C_D}(D|h) = -\log_2 P(D|h)$, where $C_D|h$ is the optimal code for describing data D assuming that both the sender and receiver know the hypothesis h .

* Rewrite Equation (1) to show that h_{MAP} is the hypothesis h that minimizes the sum given by the description length of the hypothesis plus the description length of the data given the hypothesis.

$$h_{MAP} = \underset{h \in H}{\operatorname{argmin}} L_{C_H}(h) + L_{C_D|h}(D|h).$$

where C_H and $C_D|h$ are the optimal encoding for H and for D given h .

The Minimum Description Length (MDL) principle recommends choosing the hypothesis that minimizes the sum of these two description length of eqn.

$$h_{MDL} = \underset{h \in H}{\operatorname{argmin}} L_{C_1}(h) + L_{C_2}(D|h).$$

Minimum Description length principle:

$$h_{MDL} = \underset{h \in H}{\operatorname{argmin}} L_{C_1}(h) + L_{C_2}(D|h)$$

where, codes C_1 and C_2 to represent the hypothesis and the data given the hypothesis.

The above analysis shows that if we choose C_1 to be the optimal encoding the hypotheses C_H and if we choose C_2 to be the optimal encoding $C_D|h$, then $h_{MDL} = h_{MAP}$.

Application to Decision Tree learning.

Apply the MDL principle to the problem of learning decision trees from some training data.

What should we choose for the representations C_1 and C_2 of hypotheses and data?

- * For C_1 : C_1 might be some obvious encoding, in which the description length grows with the number of nodes and with the number of edges.
- * For C_2 : Suppose that the sequence of instances (x_1, \dots, x_m) is already known to both the transmitter and receiver, so that we need only transmit the classifications $(f(x_1), \dots, f(x_m))$.
- * Now if the training classifications $(f(x_1), \dots, f(x_m))$ are identical to the predictions of the hypothesis, then there is no need to transmit any information about these examples. The description length of the classifications given the hypothesis ZERO.
- * If examples are misclassified by h , then for each misclassification we need to transmit a message that identifies which example is misclassified as well as its correct classification.
- * The hypothesis h_{MDL} under the encoding C_1 and C_2 is just the one that minimizes the sum of these description lengths.

NAIVE BAYES CLASSIFIER

- * The Naive Bayes classifier applies to learning tasks where each instance x is described by a conjunction of attributes values and where the target function $f(x)$ can take on any value from some finite set V .
- * A set of training examples of the target function is provided, and a new instance is presented, described by the tuple of attribute values (a_1, a_2, \dots, a_n) .
- * The learner is asked to predict the target value, or classification, for this new instance.

The Bayesian approach to classifying the new instance is to assign the most probable target value, v_{MAP} , given the attribute values (a_1, a_2, \dots, a_n) that describe the instance

$$v_{MAP} = \underset{v_j \in V}{\operatorname{argmax}} P(v_j | a_1, a_2, \dots, a_n)$$

Use Bayes theorem to rewrite this expression as.

$$v_{MAP} = \underset{v_j \in V}{\operatorname{argmax}} \frac{P(a_1, a_2, \dots, a_n | v_j) P(v_j)}{P(a_1, a_2, \dots, a_n)}$$

$$= \underset{v_j \in V}{\operatorname{argmax}} P(a_1, a_2, \dots, a_n | v_j) P(v_j) \quad \text{(equ.)}$$

- * The naive Bayes classifier is based on the assumption that the attribute values are conditionally independent given the target value. Means, the assumption is that given the target value of the instance, the probability of observing the conjunction (a_1, a_2, \dots, a_n) .

$$P(a_1, a_2, \dots, a_n | v_j) = \prod_i P(a_i | v_j)$$

Substituting this into equation (1).

Naive Bayes classifier:

$$V_{NB} = \operatorname{argmax}_{v_j \in V} P(v_j) \prod_i P(a_i | v_j) \quad \text{equ(2).}$$

where, V_{NB} denotes the target value output by the naive Bayes classifier.

An Illustrative Example.

- * Let us apply the naive Bayes classifier to a concept learning problem i.e., classifying days according to whether someone will play tennis.
- * The below table provides a set of 14 training examples of the target concept Play Tennis, where each day is described by the attributes outlook, Temperature, Humidity and Wind.

Day	Outlook	Temperature	Humidity	Wind	Play Tennis
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rain	Mild	High	Weak	Yes
D5	Rain	Cool	Normal	Weak	Yes
D6	Rain	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rain	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rain	Mild	High	Strong	No

* Use the naive Bayes classifier and the training data from this table to classify the following novel instance:
 <outlook = sunny, Temperature = cool, Humidity = high, Wind = strong>

* Our task is to predict the target value (yes/no) of the target concept Play Tennis for this new instance.

$$V_{NB} = \operatorname{argmax}_{v_j \in \{\text{yes}, \text{no}\}} P(v_j) \prod_i P(a_i | v_j).$$

$$V_{NB} = \operatorname{argmax}_{v_j \in \{\text{yes}, \text{no}\}} P(v_j) \cdot P(\text{outlook} = \text{sunny} | v_j) P(\text{Temperature} = \text{cool} | v_j) \\ P(\text{Humidity} = \text{high} | v_j) P(\text{Wind} = \text{strong} | v_j).$$

The probabilities of the different target values can easily be estimated based on their frequencies over the 14 training examples.

$$* P(\text{Play Tennis} = \text{yes}) = 9/14 = 0.64.$$

$$* P(\text{Play Tennis} = \text{no}) = 5/14 = 0.36.$$

Similarly, estimate the conditional probabilities. For example, those for Wind = strong.

$$* P(\text{Wind} = \text{strong} | \text{Play Tennis} = \text{yes}) = 3/9 = 0.33.$$

$$* P(\text{Wind} = \text{strong} | \text{Play Tennis} = \text{no}) = 3/5 = 0.60.$$

Calculate V_{NB} according to Equation (1).

$$P(\text{yes}) P(\text{sunny} | \text{yes}) P(\text{cool} | \text{yes}) P(\text{high} | \text{yes}) P(\text{strong} | \text{yes}) = .0053$$

$$P(\text{no}) P(\text{sunny} | \text{no}) P(\text{cool} | \text{no}) P(\text{high} | \text{no}) P(\text{strong} | \text{no}) = .0206.$$

Thus, the naive Bayes classifier assigns the target value Play Tennis = no to this new instance, based on the probability estimates learned from the training data.

By normalizing the above equation to sum to one, calculate the conditional probability that the target value is no, given the observed attribute values.

$$\frac{.0206}{(.0206 + .0053)} = .795.$$

Estimating Probabilities

- * We have estimated probabilities by the fraction of times the event is observed to occur over the total number of opportunities.
- * For example, in the above case we estimated $P(\text{Wind} = \text{Strong} \mid \text{Play Tennis} = \text{no})$ by the fraction n_c/n where, $n=5$ is the total number of training examples for which play Tennis = no, and $n_c=3$ is the number of these for which Wind = strong.
- * When $n_c=0$, then n_c/n will be zero and this probability term will dominate the quantity calculated in Equation (2) requires multiplying all the other probability terms by this zero value.
- * To avoid this difficulty we can adopt a Bayesian approach to estimating the probability, using the m-estimate defined as follows.

m-estimate of probability:

$$\frac{n_c + mp}{n + m}$$

- * p is our prior estimate of the probability we wish to determine, and m is a constant called the equivalent sample size, which determines how heavily to weight p relative to the observed data.
- * Method for choosing p in the absence of other information is to assume uniform priors; that is, if an attribute has k possible values we set $p = 1/k$.

Bayesian Belief Networks.

- * The naive Bayes classifier makes significant use of the assumption that the values of the attributes a_1, \dots, a_n are conditionally independent given the target value v .
- * This assumption dramatically reduces the complexity of learning the target function.

A Bayesian belief network describes the probability distribution governing a set of variables by specifying a set of conditional independence assumptions along with a set of conditional probabilities.

Bayesian belief networks allow stating conditional independence assumptions that apply to subsets of the variables.

Notation

- * consider an arbitrary set of random variables Y_1, \dots, Y_n , where each variable Y_i can take on the set of possible value $V(Y_i)$.
- * The joint space of the set of variables Y to be the cross product $V(Y_1) \times V(Y_2) \times \dots \times V(Y_n)$.
- * In other words, each item in the joint space corresponds to one of the possible assignments of values to the tuple of variables (Y_1, \dots, Y_n) . The probability distribution over this joint space is called joint probability distribution.
- * The joint probability distribution specifies the probability for each of the possible variable bindings for the tuple (Y_1, \dots, Y_n) .
- * A Bayesian belief network describes the joint probability distribution for a set of variables.

Conditional Independence

Let X, Y and Z be three discrete-valued random variables. X is conditionally independent of Y given Z if the probability distribution governing X is independent of the value of Y given a value for Z , that is, if

$$(\forall x_i, y_j, z_k) P(X=x_i | Y=y_j, Z=z_k) = P(X=x_i | Z=z_k)$$

where,

$$x_i \in V(X), y_j \in V(Y), \text{ and } z_k \in V(Z).$$

The above expression is written in abbreviated form as

$$P(X|Y, Z) = P(X|Z).$$

Conditional independence can be extended to sets of variables. The set of variables X_1, \dots, X_d is conditionally independent of the set of variables Y_1, \dots, Y_m given the set of variables Z_1, \dots, Z_n if

$$P(X_1, \dots, X_d | Y_1, \dots, Y_m, Z_1, \dots, Z_n) = P(X_1, \dots, X_d | Z_1, \dots, Z_n)$$


The naive Bayes classifier assumes that the instance attribute A_1 is conditionally independent of instance attribute A_2 given the target value V . This allows the naive Bayes classifier to calculate $P(A_1, A_2 | V)$ as follows.

$$\begin{aligned} P(A_1, A_2 | V) &= P(A_1 | A_2, V) P(A_2 | V) \\ &= P(A_1 | V) P(A_2 | V) \end{aligned}$$


Representation

A Bayesian belief network represents the joint probability distribution for a set of variables.

Bayesian networks (BN) are represented by directed acyclic graphs.



	$S.B$	$S.\neg B$	$\neg S.B$	$\neg S.\neg B$
C	0.4	0.1	0.8	0.2
$\neg C$	0.6	0.9	0.2	0.8



The Bayesian network in above figure represents the joint probability distribution over the boolean variables Storm, Lightning, Thunder, Forestfire, Campfire and BusTourGroup.

A Bayesian network (BN) represents the joint probability distribution by specifying a set of conditional independence assumptions.

- * BN represented by a directed acyclic graph, together with sets of local conditional probabilities.
- * Each variable in the joint space is represented by a node in the Bayesian network.
- * The network arcs represent the assertion that the variable is conditionally independent of its non-descendants in the network given its immediate predecessors in the network.
- * A conditional probability table (CPT) is given for each variable, describing the probability distribution for that variable given the values of its immediate predecessors.


The joint probability for any desired assignment of values (y_1, \dots, y_n) to the tuple of network variables (Y_1, \dots, Y_m) can be computed by the formula.

$$P(y_1, \dots, y_n) = \prod_{i=1}^n P(y_i | \text{Parents}(Y_i)).$$

where, Parents (Y_i) denotes the set of immediate predecessors of Y_i in the network.

Example :

Consider the node Campfire. The network nodes and arcs represent the assertion that Campfire is conditionally independent of its non-descendants Lightning and Thunder, given its immediate parents Storm and BusTourGroup.



This means that once we know the value of the variables Storm and BusTourGroup, the variables Lightning and Thunder provide no additional information about Campfire. The conditional probability table associated with the variable Campfire. The assertion is

$$P(\text{Campfire} = \text{True} | \text{Storm} = \text{True}, \text{BusTourGroup} = \text{True}) = 0.4.$$

Inference

- * Use a Bayesian network to infer the value of some target variable (e.g., ForestFire) given the observed values of the other variables.
- * Inference can be straightforward if values for all of the other variables in the network are known exactly.

- * A Bayesian network can be used to compute the probability distribution for any subset of network variables given the values or distributions for any subset of the remaining variables.
- * An arbitrary Bayesian network is known to be NP-hard.

Learning Bayesian Belief Networks

Affective algorithms can be considered for learning Bayesian belief networks from training data by considering several different settings for learning problem.

- ⇒ First, the network structure might be given in advance, or it might have to be inferred from the training data.
- ⇒ Second, all the network variables might be directly observable in each training example, or some might be unobservable.
- * In the case where the network structure is given in advance and the variables are fully observable in the training examples, learning the conditional probability tables is straightforward and estimate the conditional probability table entries.
- * In the case where the network structure is given but only some of the variable values are observable in the training data, the learning problem is more difficult. The learning problem can be compared to learning weights for an ANN.

Gradient Ascent Training of Bayesian Network

The gradient ascent rule which maximizes $P(D|h)$ by following the gradient of $\ln P(D|h)$ with respect to the parameters that define the conditional probability tables of the Bayesian Network.

Let w_{ijk} denote a single entry in one of the conditional probability tables. In particular w_{ijk} denote the conditional probability that the network variable Y_i will take on the value y_i , given that its immediate parents U_i take on the values given by u_{ik} .

The gradient of $\ln P(D|h)$ is given by the derivatives $\frac{\partial \ln P(D|h)}{\partial w_{ijk}}$ for each of the w_{ijk} .

As shown below, each of these derivatives can be calculated as

$$\frac{\partial \ln P(D|h)}{\partial w_{ij}} = \sum_{d \in D} \frac{P(Y_i = y_{ij}, U_i = u_{ik} | d)}{w_{ijk}} \quad \dots \text{equ(1)}$$

Derive the gradient defined by the set of derivatives $\frac{\partial \ln P_h(d)}{\partial w_{ijk}}$ for all i, j , and k . Assuming the training example d in the data set D are drawn independently, we write this derivative as.

$$\frac{\partial \ln P_h(D)}{\partial w_{ijk}} = \frac{\partial}{\partial w_{ijk}} \ln \prod_{d \in D} P_h(d).$$

$$= \sum_{d \in D} \frac{\partial \ln P_h(d)}{\partial w_{ijk}}$$

$$= \sum_{d \in D} \frac{1}{P_h(d)} \frac{\partial P_h(d)}{\partial w_{ijk}}$$

$$= \sum_{d \in D} \frac{P_h(y_{ij}, u_{ik}|d) P_h(u_{ik})}{P_h(y_{ij}, u_{ik})}$$

$$= \sum_{d \in D} \frac{P_h(y_{ij}, u_{ik}|d)}{P_h(y_{ij}|u_{ik})}$$

$$= \sum_{d \in D} \frac{P_h(y_{ij}, u_{ik}|d)}{w_{ijk}} \quad \dots \text{eqn(2)}$$

Thus, we have derived the gradient given in equation(1). There is one more item that must be considered before we can state the gradient ascent training procedure. In particular, we require that as the weights w_{ijk} are updated they must remain valid probabilities in the interval $[0,1]$. We also require that the sum $\sum_j w_{ijk}$ remains 1 for all i, k . These constraints can be satisfied by updating weights in a two-step process. First we update each w_{ijk} by gradient ascent.

$$w_{ijk} \leftarrow w_{ijk} + \eta \sum_{d \in D} \frac{P_h(y_{ij}, u_{ik}|d)}{w_{ijk}}$$

where η is a small constant called the learning rate. Second, we renormalize the weights w_{ijk} to assure that the above constraints are satisfied.

This process will converge to a locally maximum likelihood hypothesis for the conditional probabilities in the Bayesian network.

We write the abbreviation $P_h(\theta)$ to represent $P(D|h)$.

This last step makes use of a general equality.

$$\frac{\partial \ln f(x)}{\partial x} = \frac{1}{f(x)} \frac{\partial f(x)}{\partial x}. \text{ We can now introduce the values of}$$

the variables y_i and $u_i = \text{Parents}(y_i)$, by summing over their possible values y_{ij} and u_{ik} .

$$\begin{aligned} \frac{\partial \ln P_h(\theta)}{\partial w_{ijk}} &= \sum_{d \in D} \frac{1}{P_h(d)} \frac{\partial}{\partial w_{ijk}} \sum_{j' \neq k'} P_h(d|y_{ij'}, u_{ik'}) P_h(y_{ij'}, u_{ik'}) \\ &= \sum_{d \in D} \frac{1}{P_h(d)} \frac{\partial}{\partial w_{ijk}} \sum_{j', k'} P_h(d|y_{ij'}, u_{ik'}) P_h(y_{ij'}, u_{ik'}) P_h(u_{ik'}) \end{aligned}$$

This last step follows from the product rule of probability. Now consider the rightmost sum in the final expression above. Given that $w_{ijk} \equiv P_h(y_{ij}|u_{ik})$, the only term in this sum for which $\frac{\partial}{\partial w_{ijk}}$ is nonzero is the term for which $j' = j$ and $i' = i$. Therefore,

$$\begin{aligned} \frac{\partial \ln P_h(\theta)}{\partial w_{ijk}} &= \sum_{d \in D} \frac{1}{P_h(d)} \frac{\partial}{\partial w_{ijk}} P_h(d|y_{ij}, u_{ik}) P_h(y_{ij}|u_{ik}) P_h(u_{ik}) \\ &= \sum_{d \in D} \frac{1}{P_h(d)} \frac{\partial}{\partial w_{ijk}} P_h(d|y_{ij}, u_{ik}) w_{ijk} P_h(u_{ik}). \\ &= \sum_{d \in D} \frac{1}{P_h(d)} P_h(d|y_{ij}, u_{ik}) P_h(u_{ik}). \end{aligned}$$

Applying Bayes Theorem to rewrite $P_h(d|y_{ij}, u_{ik})$, we have.


$$\frac{\partial \ln P_h(\theta)}{\partial w_{ijk}} = \sum_{d \in D} \frac{1}{P_h(d)} \frac{P_h(y_{ij}, u_{ik}|d) P_h(d) P_h(u_{ik})}{P_h(y_{ij}, u_{ik})}$$

THE EM Algorithm

The EM Algorithm can be used even for variables whose value is never directly observed, provided the general form of the probability distribution governing these variables is known.

Estimating Means of k Gaussians

- * Consider a problem in which the Data D is a set of instances generated by a probability distribution that is mixture of k distinct Normal distributions



- * This problem setting is illustrated in figure for the case where $k=2$ and where the instances are the points shown along the x axis.
- * Each instance is generated using a two-step process:
 - * first, one of the k Normal

- * To simplify, consider the special case.
 - * The selection of the single Normal distribution at each step is based on choosing each with uniform probability
 - * Each of the k Normal distributions has the same variance σ^2 , known value.
- * The learning task is to output a hypothesis $h = (\mu_1, \dots, \mu_k)$ that describes the means of each of the k distributions
- * We would like to find a maximum likelihood hypothesis for these means; that is, a hypothesis \underline{h} that maximizes $p(D|h)$.

$$\mu_{ML} = \underset{\mu}{\operatorname{argmin}} \sum_{i=1}^m (x_i - \mu)^2 \quad \dots \dots \dots (1)$$

In this case, the sum of squared errors is minimized by the sample mean.

$$\mu_{ML} = \frac{1}{m} \sum_{i=1}^m x_i \quad \dots \dots \dots (2)$$

- * Our problem here, however, involves a mixture of k different Normal distributions, and we cannot observe which instances were generated by which distribution
- * Consider full description of each instance as the triple (x_i, z_{i1}, z_{i2})
 - * where x_i is the observed value of the instance and
 - * where z_{i1} and z_{i2} indicate which of the two normal distributions was used to generate the value x_i .
- * In particular, z_{ij} has the value 1 if x_i was created by the j^{th} normal distribution and 0 otherwise.
- * Here x_i is the observed variable in the description of the instance, and z_{i1} and z_{i2} are hidden variables.

- * If the values of z_{ij} and z_{ik} were observed, we could use following equation to solve for the means μ_1 and μ_2 .
- * Because they are not, we will instead use the EM algorithm.

EM Algorithm.

Step 1: calculate the expected value $E[z_{ij}]$ of each hidden variable z_{ij} , assuming the current hypothesis $h = \langle \mu_1, \mu_2 \rangle$ holds.

Step 2: calculate a new maximum likelihood hypothesis $h' = \langle \mu'_1, \mu'_2 \rangle$, assuming the value taken on by each hidden variable z_{ij} is its expected value $E[z_{ij}]$ calculated in Step 1. Then replace the hypothesis $h = \langle \mu_1, \mu_2 \rangle$ by the new hypothesis $h' = \langle \mu'_1, \mu'_2 \rangle$ and iterate.

Let us examine how both of these steps can be implemented in practice.

Step 1 must calculate the expected value of each z_{ij} . This $E[z_{ij}]$ is just the probability that instance x_i was generated by the j th Normal distribution

$$\begin{aligned} E[z_{ij}] &= \frac{P(x = x_i | \mathcal{H} = \mu_j)}{\sum_{n=1}^2 P(x = x_i | \mathcal{H} = \mu_n)} \\ &= \frac{e^{-\frac{1}{2\sigma^2}(x_i - \mu_j)^2}}{\sum_{n=1}^2 e^{-\frac{1}{2\sigma^2}(x_i - \mu_n)^2}}. \end{aligned}$$

Thus the first step is implemented by substituting the current values $\langle \mu_1, \mu_2 \rangle$ and the observed x_i into the above expression.

In the second step we use the $E[\hat{z}_{ij}]$ calculated during Step 1 to derive a new maximum likelihood hypothesis $h' = \langle \mu'_1, \mu'_2 \rangle$.

maximum likelihood hypothesis in this case is given by.

$$\mu'_j \leftarrow \frac{\sum_{i=1}^m E[\hat{z}_{ij}] x_i}{\sum_{i=1}^m E[\hat{z}_{ij}]}$$