SOP-MDL-004: ML Model and Model Serving Endpoint Access

Owner: MLOps Platform Team | Version 1.0 | Sample SOP for prototype

1. Purpose and Scope

- This SOP covers access to machine learning models registered in Unity Catalog and to Databricks Model Serving endpoints, including foundation model endpoints.

2. When to use this SOP

- A user, group or service principal needs EXECUTE on a registered model to load it for inference.
- A consumer needs CAN_QUERY on a model serving endpoint, or CAN_MANAGE to update the endpoint.
- A team needs access to an LLM or foundation model endpoint.

3. Not covered by this SOP

- Access to tables, schemas or SQL functions: use SOP-UC-001.

4. Required information in the ticket

- Model full name (catalog.schema.model) or serving endpoint name.
- Principal and permission (EXECUTE, CAN_QUERY, CAN_MANAGE).
- Environment and expected request volume for serving endpoints.

5. Validation rules

- Model or endpoint must exist and be in READY state.
- CAN_MANAGE is granted only to the owning ML team.
- Foundation model endpoints require an approved use-case ID.

6. Approval

- Model owner / Data Product Owner (DPO) approves.

7. Implementation

- Repository: quanta-provisioning.
- Branch: feature/-model-access created from dev.
- File: data_products//models/.yaml. Add the principal under the model or endpoint permissions block.

8. Deployment

- Jenkins job: quanta-provisioning-deploy- after merge.

9. Post-deployment verification

- Query the endpoint permissions API or run SHOW GRANTS ON MODEL and comment on the ASPEN ticket.