


## Integrating Azure OpenAI, with ASP.NET Core + Blazor (Server or WASM)

### 1 Setting up an Azure OpenAI Service



### What is Azure OpenAI?

**Azure OpenAI Service** provides enterprise access to OpenAI models (GPT-4.x, GPT-4o, embeddings, etc.) with:

- Azure AD & API key security
- Regional compliance
- Private networking
- SLA & enterprise governance

### Step-by-Step Setup

#### 1. Create the Azure OpenAI resource

- Azure Portal → **Create Resource**

- Search **Azure OpenAI**
- Select region (important for latency + compliance)
- Pricing tier: *Standard S0*

## 2. Deploy a model

Azure OpenAI **requires model deployment names**.

Example:

Model	Deployment Name
GPT-4o-mini	gpt-chat
text-embedding-3-large	embeddings

 **You never call the model name directly—only the deployment name**

---

### Required Configuration

// appsettings.json

```
{  
  "AzureOpenAI": {  
    "Endpoint": "https://your-openai-resource.openai.azure.com/",  
    "ApiKey": "YOUR_API_KEY",  
    "ChatDeployment": "gpt-chat",  
    "EmbeddingDeployment": "embeddings"  
  }  
}
```

---

## Implementing Smart Pasting (AI-assisted paste)

### What is Smart Pasting?

When a user pastes **raw or messy content**, AI:

- Cleans formatting
- Summarizes
- Converts to structured text (Markdown / JSON / bullets)
- Removes sensitive data

## Architecture

Clipboard → Blazor UI

→ API → Azure OpenAI

→ Cleaned Output → UI

## Blazor Demo – Smart Paste

### Razor Component

```
<textarea @onpaste="HandlePaste" class="form-control" rows="6"></textarea>
```

```
<p><b>AI Enhanced:</b></p>
```

```
<textarea class="form-control" rows="6">@enhancedText</textarea>
```

### Code-Behind

```
private string enhancedText;
```

```
private async Task HandlePaste(ClipboardEventArgs e)
```

```
{
```

```
    var pastedText = await JS.InvokeAsync<string>(
        "navigator.clipboard.readText");
```

```
    enhancedText = await _aiService.SmartPasteAsync(pastedText);
```

```
}
```

### AI Prompt Logic

```

public async Task<string> SmartPasteAsync(string input)
{
    var prompt = $"
Clean and structure the following text.

Remove noise, fix grammar, and return concise bullet points.


Text:
{input}
";

    return await SendToOpenAI(prompt);
}

```

---

### 3 Implementing a Smart Text Area (Context-Aware AI Writing)



## What Makes a Text Area “Smart”?

- Suggests next sentence
  - Improves tone
  - Auto-completes based on **context**
  - Grammar + clarity optimization
- 

### Smart Text Area Example

```
<textarea @bind="userText" class="form-control"></textarea>
```

```
<button @onclick="ImproveText">Improve</button>
```

```
<p><b>Suggestion:</b> @aiSuggestion</p>
```

```
private async Task ImproveText()
```

```
{
```

```
    aiSuggestion = await _aiService.EnhanceTextAsync(userText);
```

```
}
```

```
public async Task<string> EnhanceTextAsync(string text)
```

```
{
```

```
    var prompt = $""
```

```
    Improve clarity and professionalism.
```

```
    Do not change meaning.
```

```
    Text:
```

```
    {text}
```

```
    """,
```


```
    return await SendToOpenAI(prompt);
```

}

### 📌 Use cases

- Email drafting
- Code comments
- Requirement descriptions
- User stories (Jira 👍 )

### 4 Adding a ChatBot (Conversational AI)



### Core Concepts

- **System Prompt** → defines bot personality
- **Conversation Memory**
- **User Messages**
- **Assistant Responses**

### ChatBot UI (Blazor)

```
<input @bind="userMessage" />
```

```
<button @onclick="Send">Send</button>
```

```
@foreach (var msg in chatHistory)
```

```
{
```

```
    <p><b>@msg.Role:</b> @msg.Content</p>
```

```
}
```

```
private async Task Send()
```

```
{
```

```
    var reply = await _aiService.ChatAsync(chatHistory, userMessage);
```

```
    chatHistory.Add(("User", userMessage));
```

```
    chatHistory.Add(("AI", reply));
```

```
}
```

---

### Chat Service Logic

```
public async Task<string> ChatAsync(
```

```
    List<(string Role, string Content)> history,
```

```
    string userInput)
```

```
{
```

```
    var messages = history.Select(h =>
```

```
        $"{h.Role}: {h.Content}");
```

```
    var prompt = string.Join("\n", messages)
```

```
        + $\nUser: {userInput}\nAI:";
```



```
    return await SendToOpenAI(prompt);
```

```
}
```

💡 **Production tip**

- Persist history in Redis / SQL
- Trim context to avoid token explosion

**5** Connecting Azure OpenAI to an Existing Data Index (RAG)



**Why RAG?**

LLMs:

- ❌ Do not know your private data
- ❌ Hallucinate



**Retrieval-Augmented Generation (RAG)** solves this.

---

### High-Level Flow

User Question



Generate Embedding



Search Vector Index (Azure AI Search)



Inject Retrieved Data into Prompt



Azure OpenAI Answer

---

### Embedding Generation

```
public async Task<float[]> CreateEmbedding(string text)
{
    // Call embedding deployment
}
```

---

### Querying Existing Data

```
var results = await _searchClient.SearchAsync<SearchDocument>(
    vector: embedding,
    top: 5
);
```

---

### Final Prompt (RAG)

Answer using ONLY the context below.

If not found, say "Data not available".

Context:

- Product A price is 100
- Product B discontinued

Question:

What is the price of Product A?

---

### Security & Best Practices

- ✓ Use **server-side calls only** (never expose API key)
  - ✓ Rate limit AI endpoints
  - ✓ Log prompts & responses (for audits)
  - ✓ Validate user input (prompt injection defense)
  - ✓ Cache responses where possible
- 

### Summary

Feature	What AI Adds
Smart Pasting	Clean & structured input
Smart Text Area	Context-aware writing
ChatBot	Conversational UX
Data Index (RAG)	Enterprise-safe AI answers

---