

4_RObjects

sanudelhi1199

5/11/2021

introducing R objects

vectors

hold values of same class and declared using vector () and c()

```
v1 <- c(1,2,3,4,5,6,7,8,9,10)
```

```
v1
```

```
## [1] 1 2 3 4 5 6 7 8 9 10
```

```
class(v1)
```

```
## [1] "numeric"
```

```
v2 <- c("hitesh","gajuji","solanki")
```

```
v2
```

```
## [1] "hitesh" "gajuji" "solanki"
```

```
class(v2)
```

```
## [1] "character"
```

```
v3 <- c(T,F)
```

```
v3
```

```
## [1] TRUE FALSE
```

```
class(v3)
```

```
## [1] "logical"
```

```
### how to create vector using vector ()
```

```
v4 <- vector("numeric", length = 20)
```

```
v4
```

```
## [1] 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
```

```
class(v4)
```

```
## [1] "numeric"
```

```
length(v4)
```

```
## [1] 20
```

```
### concatenating vector meaning mixing two vector of different class and auto assigning mutual class
```

```
v5 <- c("hitesh" , "gajuji")
```

```
v6 <- c(1,2)
```

```
v7 <- c(v5,v6)
```

```
v7
```

```
## [1] "hitesh" "gajuji" "1" "2"
```

```
class(v7)
```

```
## [1] "character"
```

```
v8 <- c(T,F)
```

```
class(v8)
```

```
## [1] "logical"
```

```
v9 <- c("True", "False")
```

```
class(v9)
```

```
## [1] "character"
```

```
v10 <- c(v8,v9)
```

```
v10
```

```
## [1] "TRUE" "FALSE" "True" "False"
```

```

class(v10)

## [1] "character"

### how to print ABCD

v11 <- letters[1:26]

v11

## [1] "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s"
## [20] "t" "u" "v" "w" "x" "y" "z"

### how to do external coercion using as.xxx() function

v12 <- 1:10

v12

## [1] 1 2 3 4 5 6 7 8 9 10

class(v12)

## [1] "integer"

v13 <- as.numeric(v12)

class(v13)

## [1] "numeric"

v14 <- as.character(v12)

class(v14)

## [1] "character"

v15 <- as.logical(v12)

v15

## [1] TRUE TRUE TRUE TRUE TRUE TRUE TRUE TRUE TRUE TRUE

class(v15)

## [1] "logical"

```

```
v16 <- "hitesh"
```

```
v17 <- as.numeric(v16)
```

```
## Warning: NAs introduced by coercion
```

```
class(v17)
```

```
## [1] "numeric"
```

```
v17
```

```
## [1] NA
```

```
### how to get attributes
```

```
v18 <- "my name is hitesh"
```

```
attributes(v18)
```

```
## NULL
```

list ()

can hold value of multiple class

```
### while creating list each item is seperate vector
```

```
l1 <- list("hitesh", 5 , T)
```

```
l1
```

```
## [[1]]
```

```
## [1] "hitesh"
```

```
##
```

```
## [[2]]
```

```
## [1] 5
```

```
##
```

```
## [[3]]
```

```
## [1] TRUE
```

```
class(l1)
```

```
## [1] "list"
```

```
attributes(l1)
```

```
## NULL
```

```
### how to assign names to list objects
```

```
l2 <- list("names" = c("hitesh","gajuji"), "Age" = c(22,50), "alive"= c(T,T))
```

```
l2
```

```
## $names  
## [1] "hitesh" "gajuji"  
##  
## $Age  
## [1] 22 50  
##  
## $alive  
## [1] TRUE TRUE
```

```
class(l2)
```

```
## [1] "list"
```

```
attributes(l2)
```

```
## $names  
## [1] "names" "Age"   "alive"
```

```
### hoe to check if it is list
```

```
class(l2)
```

```
## [1] "list"
```

```
is.list(l2)
```

```
## [1] TRUE
```

```
### how to give name to list after creating list
```

```
l3 <- list(c("hitesh","gajuji"),c(22,50), c(T,T))
```

```
l3
```

```
## [[1]]  
## [1] "hitesh" "gajuji"  
##  
## [[2]]  
## [1] 22 50  
##  
## [[3]]  
## [1] TRUE TRUE
```

```
names(l3) <- c("name","age","alive")
```

```
l3
```

```
## $name
## [1] "hitesh" "gajuji"
##
## $age
## [1] 22 50
##
## $alive
## [1] TRUE TRUE
```

```
### how to get value from list
```

```
l3
```

```
## $name
## [1] "hitesh" "gajuji"
##
## $age
## [1] 22 50
##
## $alive
## [1] TRUE TRUE
```

```
l3[[1]]
```

```
## [1] "hitesh" "gajuji"
```

```
l3[[2]]
```

```
## [1] 22 50
```

```
l3[[3]]
```

```
## [1] TRUE TRUE
```

```
l3
```

```
## $name
## [1] "hitesh" "gajuji"
##
## $age
## [1] 22 50
##
## $alive
## [1] TRUE TRUE
```

```
### how to get well output using str
```

```
l4 <-str(l3)
```

```
## List of 3  
## $ name : chr [1:2] "hitesh" "gajuji"  
## $ age : num [1:2] 22 50  
## $ alive: logi [1:2] TRUE TRUE
```

```
l4
```

```
## NULL
```

```
### how to get specific output from list
```

```
l3[[1]]
```

```
## [1] "hitesh" "gajuji"
```

```
l3$name[[1]]
```

```
## [1] "hitesh"
```

```
l3$name[[2]]
```

```
## [1] "gajuji"
```

```
# using similar function
```

```
l4 <- list("name" = "rashmika", "age" = 30, "alive" = T)
```

```
l2 <- list("names" = c("hitesh","gajuji"), "Age" = c(22,50), "alive"= c(T,T), similar = l4)
```

```
l2
```

```
## $names  
## [1] "hitesh" "gajuji"  
##  
## $Age  
## [1] 22 50  
##  
## $alive  
## [1] TRUE TRUE  
##  
## $similar  
## $similar$name  
## [1] "rashmika"  
##  
## $similar$age
```

```
## [1] 30
##
## $similar$alive
## [1] TRUE
```

```
# getting perticulat object from list
```

```
l2[[1]]
```

```
## [1] "hitesh" "gajuji"
```

```
l2$names[[1]]
```

```
## [1] "hitesh"
```

```
l2$similar[[1]]
```

```
## [1] "rashmika"
```

```
l2$similar$name[[1]]
```

```
## [1] "rashmika"
```

```
### accessing a list item from name
```

```
l2$names
```

```
## [1] "hitesh" "gajuji"
```

```
l2[["names"]]
```

```
## [1] "hitesh" "gajuji"
```

```
l2[["Age"]]
```

```
## [1] 22 50
```

```
### how to use logics to get list
```

```
l2
```

```
## $names
## [1] "hitesh" "gajuji"
##
## $Age
## [1] 22 50
##
## $alive
```



```
## [1] TRUE TRUE
##
## $similar
## $similar$name
## [1] "rashmika"
##
## $similar$age
## [1] 30
##
## $similar$alive
## [1] TRUE
```

```
l2[c(T,F,T,F,T,F)]
```

```
## $names
## [1] "hitesh" "gajuji"
##
## $alive
## [1] TRUE TRUE
##
## $<NA>
## NULL
```

```
### how to add vector in list
```

```
l2
```

```
## $names
## [1] "hitesh" "gajuji"
##
## $Age
## [1] 22 50
##
## $alive
## [1] TRUE TRUE
##
## $similar
## $similar$name
## [1] "rashmika"
##
## $similar$age
## [1] 30
##
## $similar$alive
## [1] TRUE
```

```
vect <- "kamkhya"
```

```
vect2 <- 3
```

```
vect3 <- T
```

```
l2 <- list("names" = c("hitesh","gajuji", vect), "Age" = c(22,50, vect2), "alive"= c(T,T,vect3), simila
```

```
l2
```

```
## $names
## [1] "hitesh" "gajuji" "kamkhya"
##
## $Age
## [1] 22 50 3
##
## $alive
## [1] TRUE TRUE TRUE
##
## $similar
## $similar$name
## [1] "rashmika"
##
## $similar$age
## [1] 30
##
## $similar$alive
## [1] TRUE
```