Real-Time Ads Data Processing Into Cassandra

- This project was about processing real-time advertisement data using Spark Streaming to gain business insights and store the aggregated data into Cassandra.
- I set up confluent kafka in local system and created topic named as ads_data.
 Wrote a python script to generate ads data in json format using 'random_mock_data_generator.py' file

random_mock_data_genrator.py:

```
# Create a list of random data
data = []
for i in range(1500):
    # Create an ISO string
    iso_string = "2023-08-23T12:01:05Z"

# Convert the ISO string to a datetime object
datetime_object = datetime.datetime.fromisoformat(iso_string)
#print(datetime_object)

# Create a timedelta object representing few seconds
timedelta_object = datetime.timedelta(seconds=i)

# Add the timedelta object to the datetime object
datetime_object += timedelta_object

# Convert the datetime object back to an ISO string
new_iso_string = datetime_object.isoformat().replace('+00:00', 'Z')

# Print the new ISO string
#print(datetime_object)
print(new_iso_string)

ad_ids = [12345, 54321, 13245, 54231, 14235, 53241, 15234, 43251, 67891, 19876, 68791, 19786, 69781, 18796]

data.append({
    "ad_id": str(random.choice(ad_ids)),
    "timestamp": new_iso_string,
    "clicks": random.randint(2, 52),
    "views": random.randint(15, 167),
    "cost": round(random.uniform(50.75, 112.66), 2)
})

# Write the data to a ISON file
with open("mock_ads_data.json", "w") as f:
    json.dump(data, f)
```

mock ads data.json:

```
{
    "ad_id": "19786",
        "timestamp": "2023-08-23T12:01:05Z",
        "clicks": 38,
        "views": 78,
        "cost": 75.37
},
{
    "ad_id": "54321",
        "timestamp": "2023-08-23T12:01:06Z",
        "clicks": 8,
        "views": 145,
        "cost": 63.6
},
{
    "ad_id": "68791",
        "timestamp": "2023-08-23T12:01:07Z",
        "clicks": 48,
        "views": 119,
        "cost": 71.79
},

    "ad_id": "18796",
        "timestamp": "2023-08-23T12:01:08Z",
        "clicks": 8,
        "views": 166,
        "cost": 64.56
},
```

3. Created a producer script which was publishing those json ads data into kafka topic.

```
from confluent_kafka import Producer
import json
import time
def delivery_report(err, msg):
    if err is not None:
        print(f"Message delivery failed: {err}")
    else:
        print(f"Message delivered to {msg.topic()}")
with open('mock_ads_data.json') as f:
    data = json.load(f)
p = Producer({'bootstrap.servers': 'localhost:9092'})
for record in data:
    p.pol1(0)
    record_str = json.dumps(record)
   p.produce('ads_data', record_str, callback=delivery_report)
    print("Message Published -> ",record_str)
    time.sleep(0.5) # wait for half second before sending the next record
p.flush()
```

4. Next I set up a spark streaming application where I used the kafka connector to read data from ads_data topic. Then parsed the json data into proper structure using my defined schema.

```
spark = SparkSession.builder \
     .appName("Ads Stream") \
     .master("local[3]") \
     .config("spark.sql.shuffle.partitions", "2") \
     .config("spark.streaming.stopGracefullyOnShutdown", "true") \
     .config("spark.jars.packages", "org.apache.spark:spark-sql-kafka-0-10_2.12:3.3.0") \
.config("spark.cassandra.connection.host", "localhost") \
.config("spark.cassandra.connection.port", "9042") \
     .getOrCreate()
spark.sparkContext.setLogLevel("ERROR")
load_dotenv()
schema = StructType([
     StructField("ad_id", StringType()),
     StructField("timestamp", TimestampType()),
StructField("clicks", IntegerType()),
StructField("views", IntegerType()),
     StructField("cost", FloatType()),
# Read the stream from Kafka
df = spark.readStream.format("kafka")\
    .option("kafka.bootstrap.servers", "localhost:9092")\
.option("subscribe", "ads_data")\
.option("startingOffsets", "earliest")\
     .load()
# Parse the JSON data and select the fields
df = df.select(from_json(col("value").cast("string"), schema).alias("data")).select("data.*")
```

5. Further transformed data by performed windowed based aggregation and included cassandra connection script into spark stream app so that I can write aggregated data into cassandra table.

6. But writing data with the logic was like if entry already existed with 'ad_id' then updated that record or else inserting new entry in table.

```
#### create table ######
create table query = f"""
CREATE TABLE IF NOT EXISTS ads_data.agg_ads_data (
   ad_id TEXT,
   total_clicks INT,
   total_views INT,
    total_cost FLOAT,
    avg_cost_per_view FLOAT,
    PRIMARY KEY (ad id)
session.execute(create_table_query)
# Convert Spark DataFrame to Pandas DataFrame
write_query = df.writeStream \
.outputMode("update") \
.format("org.apache.spark.sql.cassandra") \
.option("keyspace", "ads_data") \
.option("table", "agg_ads_data") \
.option("truncate", "false") \
.trigger(processingTime="3 second") \
.start() \
.awaitTermination()
```