



HTML Styles - CSS

[< Previous](#)[Next >](#)

CSS = Styles and
Colors

M a n i p u l a t e T e x t
C o l o r s , B o x e s

Styling HTML with CSS

CSS stands for **C**ascading **S**tyle **S**heets.

CSS describes **how HTML elements are to be displayed on screen, paper, or in other media.**

CSS **saves a lot of work.** It can control the layout of multiple web pages all at once.

CSS can be added to HTML elements in 3 ways:

- **Inline** - by using the style attribute in HTML elements
- **Internal** - by using a `<style>` element in the `<head>` section
- **External** - by using an external CSS file

The most common way to add CSS, is to keep the styles in separate CSS files. However, here we will use inline and internal styling, because this is easier to demonstrate, and easier for you to try it yourself.

Tip: You can learn much more about CSS in our [CSS Tutorial](#).

Inline CSS

An inline CSS is used to apply a unique style to a single HTML element.

An inline CSS uses the style attribute of an HTML element.

This example sets the text color of the `<h1>` element to blue:

Example

```
<h1 style="color:blue;">This is a Blue Heading</h1>
```

Try it Yourself »

Internal CSS

An internal CSS is used to define a style for a single HTML page.

An internal CSS is defined in the `<head>` section of an HTML page, within a `<style>` element:

Example

```
<!DOCTYPE html>  
<html>  
<head>  
<style>
```

```
body {background-color: powderblue;}
h1   {color: blue;}
p    {color: red;}
</style>
</head>
<body>

<h1>This is a heading</h1>
<p>This is a paragraph.</p>

</body>
</html>
```

Try it Yourself »

External CSS

An external style sheet is used to define the style for many HTML pages.

With an external style sheet, you can change the look of an entire web site, by changing one file!

To use an external style sheet, add a link to it in the `<head>` section of the HTML page:

Example

```
<!DOCTYPE html>
<html>
<head>
  <link rel="stylesheet" href="styles.css">
</head>
<body>

<h1>This is a heading</h1>
<p>This is a paragraph.</p>

</body>
</html>
```

Try it Yourself »

An external style sheet can be written in any text editor. The file must not contain any HTML code, and must be saved with a .css extension.

Here is how the "styles.css" looks:

```
body {  
    background-color: powderblue;  
}  
h1 {  
    color: blue;  
}  
p {  
    color: red;  
}
```

CSS Fonts

The CSS `color` property defines the text color to be used.

The CSS `font-family` property defines the font to be used.

The CSS `font-size` property defines the text size to be used.

Example

```
<!DOCTYPE html>  
<html>  
<head>  
<style>  
h1 {  
    color: blue;  
    font-family: verdana;  
    font-size: 300%;  
}  
p {  
    color: red;  
    font-family: courier;  
    font-size: 160%;  
}  
</style>  
</head>
```

```
<body>

<h1>This is a heading</h1>
<p>This is a paragraph.</p>

</body>
</html>
```

Try it Yourself »

CSS Border

The CSS **border** property defines a border around an HTML element:

Example

```
p {
  border: 1px solid powderblue;
}
```

Try it Yourself »

CSS Padding

The CSS **padding** property defines a padding (space) between the text and the border:

Example

```
p {
  border: 1px solid powderblue;
  padding: 30px;
}
```

Try it Yourself »

CSS Margin

The CSS **margin** property defines a margin (space) outside the border:

Example

```
p {  
    border: 1px solid powderblue;  
    margin: 50px;  
}
```

Try it Yourself »

The id Attribute

To define a specific style for one special element, add an **id** attribute to the element:

```
<p id="p01">I am different</p>
```

then define a style for the element with the specific id:

Example

```
#p01 {  
    color: blue;  
}
```

Try it Yourself »

Note: The id of an element should be unique within a page, so the id selector is used to select one unique element!

The class Attribute

To define a style for a special type of elements, add a **class** attribute to the element:

```
<p class="error">I am different</p>
```

then define a style for the elements with the specific class:

Example

```
p.error {  
  color: red;  
}
```

[Try it Yourself »](#)

External References

External style sheets can be referenced with a full URL or with a path relative to the current web page.

This example uses a full URL to link to a style sheet:

Example

```
<link rel="stylesheet"  
href="https://www.w3schools.com/html/styles.css">
```

[Try it Yourself »](#)

This example links to a style sheet located in the html folder on the current web site:

Example

```
<link rel="stylesheet" href="/html/styles.css">
```

[Try it Yourself »](#)

This example links to a style sheet located in the same folder as the current page:

Example

```
<link rel="stylesheet" href="styles.css">
```

Try it Yourself »

You can read more about file paths in the chapter [HTML File Paths](#).

Chapter Summary

- Use the HTML **style** attribute for inline styling
- Use the HTML **<style>** element to define internal CSS
- Use the HTML **<link>** element to refer to an external CSS file
- Use the HTML **<head>** element to store **<style>** and **<link>** elements
- Use the CSS **color** property for text colors
- Use the CSS **font-family** property for text fonts
- Use the CSS **font-size** property for text sizes
- Use the CSS **border** property for borders
- Use the CSS **padding** property for space inside the border
- Use the CSS **margin** property for space outside the border

Test Yourself with Exercises!

Exercise 1 »

Exercise 2 »

Exercise 3 »

Exercise 4 »

Exercise 5 »


Exercise 6 »

HTML Style Tags

Tag	Description
<u><style></u>	Defines style information for an HTML document
<u><link></u>	Defines a link between a document and an external resource

[< Previous](#)[Next >](#)

COLOR PICKER



HOW TO

Tabs

Dropdowns

Accordions

Convert Weights

Animated Buttons

Side Navigation

Top Navigation

Modal Boxes

Progress Bars

Parallax

Login Form

HTML Includes

Google Maps

Range Sliders

Tooltips

Slideshow

Filter List

Sort List

SHARE



CERTIFICATES

HTML, CSS, JavaScript, PHP, jQuery, Bootstrap and XML.

[Read More »](#)

REPORT ERROR

[PRINT PAGE](#)[FORUM](#)[ABOUT](#)

Top 10 Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[SQL Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Angular Tutorial](#)
[How To Tutorial](#)

Top 10 References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[SQL Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)
[AngularJS Reference](#)

Top 10 Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[HTML DOM Examples](#)
[PHP Examples](#)
[jQuery Examples](#)
[Angular Examples](#)
[XML Examples](#)

Web Certificates

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[jQuery Certificate](#)
[PHP Certificate](#)
[Bootstrap Certificate](#)
[XML Certificate](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot

warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2018 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

