

[HTML](#)[CSS](#)[MORE ▾](#)

SQL Aliases

[< Previous](#)[Next >](#)

SQL Aliases

SQL aliases are used to give a table, or a column in a table, a temporary name.

Aliases are often used to make column names more readable.

An alias only exists for the duration of the query.

Alias Column Syntax

```
SELECT column_name AS alias_name  
FROM table_name;
```

Alias Table Syntax

```
SELECT column_name(s)  
FROM table_name AS alias_name;
```

Demo Database

In this tutorial we will use the well-known Northwind sample database.

Below is a selection from the "Customers" table:

CustomerID	CustomerName	ContactName	Address	City	PostalCode
2	Ana Trujillo Emparedados y helados	Ana Trujillo	Avda. de la Constitución 2222	México D.F.	05021
3	Antonio Moreno Taquería	Antonio Moreno	Mataderos 2312	México D.F.	05023
4	Around the Horn	Thomas Hardy	120 Hanover Sq.	London	WA1 1DP



And a selection from the "Orders" table:

OrderID	CustomerID	EmployeeID	OrderDate	ShipperID
10354	58	8	1996-11-14	3
10355	4	6	1996-11-15	1
10356	86	6	1996-11-18	2



Alias for Columns Examples

The following SQL statement creates two aliases, one for the CustomerID column and one for the CustomerName column:

Example

```
SELECT CustomerID as ID, CustomerName AS Customer  
FROM Customers;
```

Try it Yourself »

The following SQL statement creates two aliases, one for the CustomerName column and one for the ContactName column. **Note:** It requires double quotation marks or square brackets if the alias name contains spaces:

Example

```
SELECT CustomerName AS Customer, ContactName AS [Contact Person]
FROM Customers;
```

Try it Yourself »

The following SQL statement creates an alias named "Address" that combine four columns (Address, PostalCode, City and Country):

Example

```
SELECT CustomerName, Address + ', ' + PostalCode + ', ' + City + ', ' +
Country AS Address
FROM Customers;
```

Try it Yourself »

Note: To get the SQL statement above to work in MySQL use the following:

```
SELECT CustomerName, CONCAT(Address, ', ',PostalCode, ', ',City, ',
',Country) AS Address
FROM Customers;
```

Alias for Tables Example

The following SQL statement selects all the orders from the customer with CustomerID=4 (Around the Horn). We use the "Customers" and "Orders" tables, and give them the table aliases of "c" and "o" respectively (Here we use aliases to make the SQL shorter):

Example

```
SELECT o.OrderID, o.OrderDate, c.CustomerName
FROM Customers AS c, Orders AS o
WHERE c.CustomerName="Around the Horn" AND c.CustomerID=o.CustomerID;
```

[Try it Yourself »](#)

The following SQL statement is the same as above, but without aliases:

Example

```
SELECT Orders.OrderID, Orders.OrderDate, Customers.CustomerName
FROM Customers, Orders
WHERE Customers.CustomerName="Around the Horn" AND
Customers.CustomerID=Orders.CustomerID;
```

[Try it Yourself »](#)

Aliases can be useful when:

- There are more than one table involved in a query
- Functions are used in the query
- Column names are big or not very readable
- Two or more columns are combined together

[◀ Previous](#)

[Next ▶](#)

COLOR PICKER



HOW TO

Tabs
Dropdowns
Accordions
Convert Weights
Animated Buttons
Side Navigation
Top Navigation
Modal Boxes
Progress Bars

Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List


SHARE



CERTIFICATES

HTML, CSS, JavaScript, PHP, jQuery, Bootstrap and XML.

[Read More »](#)



REPORT ERROR

[PRINT PAGE](#)[FORUM](#)[ABOUT](#)

Top 10 Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[SQL Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Angular Tutorial](#)
[How To Tutorial](#)

Top 10 References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[SQL Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)
[AngularJS Reference](#)

Top 10 Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[HTML DOM Examples](#)
[PHP Examples](#)
[jQuery Examples](#)
[Angular Examples](#)
[XML Examples](#)

Web Certificates

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[jQuery Certificate](#)
[PHP Certificate](#)
[Bootstrap Certificate](#)
[XML Certificate](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot

warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2018 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

