PHP Program To Create Login And Logout Using Sessions

// Form.php

```
<!DOCTYPE html>
<html>
<body>

form method="post" action="login.php">
User Id: <input type="text" name="userid"><br>
Password: <input type="password" name="password"><br>
<input type="submit" value="Login">
</form>
</body>
</html>
```

// Login.PHP

```
<!DOCTYPE html>
<html>
<body>
<?php
$uid = $_POST['userid'];
$pw = $_POST['password'];

if($uid == 'ben' and $pw == 'ben23')
{
    session_start();
    $_SESSION['sid']=session_id();
    echo "Logged in successfully";
}
?>
</body>
</html>
```

// Logout.PHP

```
<!DOCTYPE html>
<html>
<body>
<?php

    echo "Logged out successfully";

    session_start();
    session_destroy();

?>
</body>
</html>
```

How to Create Login and Logout Page with Session and Cookies in PHP

- 1. Open phpMyAdmin.
- 2. Click databases, create a database and name it as "cookie".
- After creating a database, click the SQL and paste the below code. See image below for detailed instruction.

```
CREATE TABLE `user` (
  `userid` INT(11) NOT NULL AUTO_INCREMENT,
  `username` VARCHAR(30) NOT NULL,
  `password` VARCHAR(30) NOT NULL,
  `fullname` VARCHAR(60) NOT NULL,
  PRIMARY KEY (`userid`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

Inserting Data into our Database

Next, we insert users into our database. This will be our reference when we log in.

- 1. Click the database we created earlier.
- 2. Click SQL and paste the code below.

```
INSERT INTO `user` (`username`, `password`, `fullname`) VALUES
('neovic', 'devierte', 'neovic devierte'),
('lee', 'ann', 'lee ann');
```

Creating our Connection

conn.php

```
1. <?php
2. $conn = mysqli_connect("localhost", "root", "", "cookie");
3.
4. // Check connection
5. if (mysqli_connect_errno())
6. {
7. echo "Failed to connect to MySQL: " . mysqli_connect_error();
8. }
9. ?>
```

Creating our Login Form

index.php

```
1. <?php
2. session start();
3. include('conn.php');
4. ?>
5. <!DOCTYPE html>
6. <html>
7. <head>
8. <title>Login Using Cookie with Logout</title>
9. </head>
10. <body>
11.
      <h2>Login Form</h2>
12.
      <form method="POST" action="login.php">
    <label>Username:</label> <input type="text" value="<?php if</pre>
  (isset($ COOKIE["user"])) {echo $ COOKIE["user"];} ?>" name="username">
14. <label>Password:input type="password" value="<?php if</pre>
  (isset($ COOKIE["pass"])) {echo $ COOKIE["pass"];}?>"
  name="password"><br><br>
        <input type="checkbox" name="remember" <?php if</pre>
  (isset($ COOKIE["user"]) && isset($ COOKIE["pass"])) { echo "checked";}?>>
  Remember me <br><br>>
16. <input type="submit" value="Login" name="login">
17.
       </form>
18.
      <span>
19.
      <?php
20.
21.
      if (isset($ SESSION['message'])){
22.
      echo $ SESSION['message'];
23.
24.
      unset($_SESSION['message']);
25.
       ?>
      </span>
      </body>
27.
    </html>
28.
```

Creating our Login Success Page

success.php

```
1. <?php
2. session_start();
3.
4. if (!isset($_SESSION['id']) ||(trim ($_SESSION['id']) == '')) {
5. header('index.php');
6. exit();
7. }
8. include('conn.php');</pre>
```

```
9. $query=mysqli query($conn,"select * from user where
  userid='".$_SESSION['id']."'");
10.
        $row=mysqli fetch assoc($query);
11.
12.
       <!DOCTYPE html>
       <html>
13.
13.
14.
       <head>
15.
       <title>Setting Up Cookie on User Login</title>
16.
       </head>
       <body>
<h2>Login Success</h2>
17.
18.
19.
       <?php echo $row['fullname']; ?>
       <br>
20.
       <a href="logout.php">Logout</a>
21.
21. <a href:
22. </body>
23. </html>
```

Creating our Logout Script

logout.php

```
1. <?php
2. session_start();
3. session_destroy();
4.
5. if (isset($_COOKIE["user"]) AND isset($_COOKIE["pass"])){
6. setcookie("user", '', time() - (3600));
7. setcookie("pass", '', time() - (3600));
8. }
9.
10. header('location:index.php');
11.
12. ?>
```

PHP Login logout example with session

login_user.sql

```
CREATE TABLE `login_user` (
  `id` int(11) NOT NULL,
  `name` varchar(60) NOT NULL,
  `user_name` varchar(20) NOT NULL,
  `password` varchar(20) NOT NULL
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

login.php

```
<?php
    session start();
    $message="";
    if(count($ POST)>0) {
        con =
mysqli connect('127.0.0.1:3306','root','','admin') or
die('Unable To connect');
        $result = mysqli query($con, "SELECT * FROM login user
WHERE user name='" . $ POST["user name"] . "' and password = '".
$ POST["password"]."'");
        $row = mysqli fetch array($result);
        if(is array($row)) {
        $SESSION["id"] = $row['id'];
        $ SESSION["name"] = $row['name'];
        } else {
         $message = "Invalid Username or Password!";
    if(isset($ SESSION["id"])) {
   header("Location:index.php");
?>
<html>
<head>
<title>User Login</title>
</head>
<body>
<form name="frmUser" method="post" action="" align="center">
```

index.php

```
<?php
session start();
?>
<html>
<head>
<title>User Login</title>
</head>
<body>
<?php
if($ SESSION["name"]) {
Welcome <?php echo $ SESSION["name"]; ?>. Click here to <a
href="logout.php" tite="Logout">Logout.
<?php
}else echo "<h1>Please login first .</h1>";
?>
</body>
</html>
```

logout.php

```
<?php
session_start();
unset($_SESSION["id"]);
unset($_SESSION["name"]);
header("Location:login.php");
?>
```

PHP CRUD Example

index.php

```
<?php
include 'backend/database.php';
<!DOCTYPE html>
<html lang="en">
<head>
      <meta charset="utf-8">
      <meta http-equiv="X-UA-Compatible" content="IE=edge">
      <meta name="viewport" content="width=device-width,</pre>
initial-scale=1">
      <title>User Data</title>
      <link rel="stylesheet"</pre>
href="https://fonts.googleapis.com/css?family=Roboto|Varela+Roun
      <link rel="stylesheet"</pre>
href="https://fonts.googleapis.com/icon?family=Material+Icons">
      <link rel="stylesheet"</pre>
href="https://maxcdn.bootstrapcdn.com/font-
awesome/4.7.0/css/font-awesome.min.css">
      <link rel="stylesheet"</pre>
href="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/css/bootst
rap.min.css">
      <link rel="stylesheet" href="css/style.css">
      <script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.12.4/jquery.
min.js"></script>
      <script
src="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/js/bootstra
p.min.js"></script>
      <script src="ajax/ajax.js"></script>
</head>
<body>
    <div class="container">
      <div class="table-wrapper">
            <div class="table-title">
                <div class="row">
                    <div class="col-sm-6">
                                       <h2>Manage
<b>Users</b></h2>
                                </div>
                                <div class="col-sm-6">
```

```
<a
```

```
href="#addEmployeeModal" class="btn btn-success" data-
toggle="modal"><i class="material-icons">\(\sigma\) </i> <span>Add New
User</span></a>
                                <a
href="JavaScript:void(0);" class="btn btn-danger"
id="delete multiple"><i class="material-icons">□</i>
<span>Delete</span></a>
                           </div>
             </div>
          </div>
          <thead>
                 <span class="custom-</pre>
checkbox">
                                           <input
type="checkbox" id="selectAll">
                                           <label
for="selectAll"></label>
                                      </span>
                                SL NO
                    NAME
                    EMAIL
                                PHONE
                    CITY
                    ACTION
                 </thead>
                     <?php
                      $result = mysqli query($conn, "SELECT *
FROM crud");
                           $i=1;
                           while($row =
mysqli fetch array($result)) {
                      ">
                      <span class="custom-</pre>
checkbox">
                                            <input
type="checkbox" class="user checkbox" data-user-id="<?php echo</pre>
$row["id"]; ?>">
```

```
<label</pre>
for="checkbox2"></label>
                                           </span>
                                     </t.d>
                               <?php echo $i; ?>
                               <?php echo $row["name"];
?>
                               <?php echo $row["email"];
?>
                               <?php echo $row["phone"];
?>
                               <?php echo $row["city"];
?>
                               href="#editEmployeeModal" class="edit" data-toggle="modal">
                                           <i class="material-</pre>
icons update" data-toggle="tooltip"
                                           data-id="<?php echo
$row["id"]; ?>"
                                           data-name="<?php
echo $row["name"]; ?>"
                                           data-email="<?php
echo $row["email"]; ?>"
                                           data-phone="<?php
echo $row["phone"]; ?>"
                                           data-city="<?php
echo $row["city"]; ?>"
                                           title="Edit">\(\text{i} \> \)
                                     </a>
                                     <a
href="#deleteEmployeeModal" class="delete" data-id="<?php echo</pre>
$row["id"]; ?>" data-toggle="modal"><i class="material-icons"</pre>
data-toggle="tooltip"
                                      title="Delete"> </i></a>
                   <?php
                        $i++;
                         }
                        ?>
                        </div>
   </div>
      <!-- Add Modal HTML -->
```

```
<div id="addEmployeeModal" class="modal fade">
             <div class="modal-dialog">
                    <div class="modal-content">
                           <form id="user form">
                                  <div class="modal-header">
                                         <h4 class="modal-
title">Add User</h4>
                                         <button type="button"</pre>
class="close" data-dismiss="modal" aria-hidden="true">x</button>
                                  </div>
                                  <div class="modal-body">
                                         <div class="form-group">
                                               <label>NAME</label>
                                               <input type="text"</pre>
id="name" name="name" class="form-control" required>
                                         <div class="form-group">
                                               <label>EMAIL</label>
                                               <input type="email"</pre>
id="email" name="email" class="form-control" required>
                                         </div>
                                         <div class="form-group">
                                               <label>PHONE</label>
                                               <input type="phone"</pre>
id="phone" name="phone" class="form-control" required>
                                         </div>
                                         <div class="form-group">
                                               <label>CITY</label>
                                               <input type="city"</pre>
id="city" name="city" class="form-control" required>
                                        </div>
                                  </div>
                                  <div class="modal-footer">
                                      <input type="hidden"</pre>
value="1" name="type">
                                         <input type="button"</pre>
class="btn btn-default" data-dismiss="modal" value="Cancel">
                                        <button type="button"</pre>
class="btn btn-success" id="btn-add">Add</button>
                                  </div>
                           </form>
                    </div>
             </div>
       </div>
       <!-- Edit Modal HTML -->
       <div id="editEmployeeModal" class="modal fade">
             <div class="modal-dialog">
```

```
<div class="modal-content">
                           <form id="update form">
                                  <div class="modal-header">
                                         <h4 class="modal-
title">Edit User</h4>
                                         <button type="button"</pre>
class="close" data-dismiss="modal" aria-hidden="true">x</button>
                                  </div>
                                  <div class="modal-body">
                                         <input type="hidden"</pre>
id="id u" name="id" class="form-control" required>
                                         <div class="form-group">
                                                <label>Name</label>
                                                <input type="text"</pre>
id="name u" name="name" class="form-control" required>
                                         <div class="form-group">
                                               <label>Email</label>
                                               <input type="email"</pre>
id="email u" name="email" class="form-control" required>
                                         </div>
                                         <div class="form-group">
                                               <label>PHONE</label>
                                               <input type="phone"</pre>
id="phone u" name="phone" class="form-control" required>
                                         </div>
                                         <div class="form-group">
                                               <label>City</label>
                                               <input type="city"</pre>
id="city u" name="city" class="form-control" required>
                                         </div>
                                  </div>
                                  <div class="modal-footer">
                                  <input type="hidden" value="2"</pre>
name="type">
                                         <input type="button"</pre>
class="btn btn-default" data-dismiss="modal" value="Cancel">
                                         <button type="button"</pre>
class="btn btn-info" id="update">Update</button>
                                  </div>
                           </form>
                    </div>
             </div>
       </div>
       <!-- Delete Modal HTML -->
       <div id="deleteEmployeeModal" class="modal fade">
             <div class="modal-dialog">
```

```
<div class="modal-content">
                         <form>
                                <div class="modal-header">
                                      <h4 class="modal-
title">Delete User</h4>
                                      <button type="button"</pre>
class="close" data-dismiss="modal" aria-hidden="true">x</button>
                                </div>
                                <div class="modal-body">
                                      <input type="hidden"</pre>
id="id d" name="id" class="form-control">
                                      Are you sure you want
to delete these Records?
                                      warning"><small>This action cannot be undone.</small>
                                </div>
                                <div class="modal-footer">
                                      <input type="button"</pre>
class="btn btn-default" data-dismiss="modal" value="Cancel">
                                      <button type="button"</pre>
class="btn btn-danger" id="delete">Delete</button>
                                </div>
                          </form>
                   </div>
            </div>
      </div>
</body>
</html>
```

backend/database.php

```
<?php
$servername = "localhost";
$username = "root";
$password = "";
$dbname = "user";
$conn = mysqli_connect($servername, $username, $password, $dbname);
if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}
?>
```

backend/save.php

```
<?php
include 'database.php';
if(count($ POST)>0){
      if($ POST['type']==1){
             $name=$ POST['name'];
             $email=$ POST['email'];
             $phone=$ POST['phone'];
             $city=$ POST['city'];
             $sql = "INSERT INTO `crud`( `name`,
`email`,`phone`,`city`)
             VALUES ('$name','$email','$phone','$city')";
             if (mysqli query($conn, $sql)) {
                   echo json encode(array("statusCode"=>200));
             }
             else {
                   echo "Error: " . $sql . " <br>" .
mysqli error($conn);
            mysqli close($conn);
      }
if(count($ POST)>0){
      if($ POST['type']==2){
             $id=$ POST['id'];
             $name=$ POST['name'];
             $email=$ POST['email'];
             $phone=$ POST['phone'];
             $city=$ POST['city'];
             $sql = "UPDATE `crud` SET
`name`='$name', `email`='$email', `phone`='$phone', `city`='$city'
WHERE id=$id";
             if (mysqli query($conn, $sql)) {
                   echo json encode(array("statusCode"=>200));
             }
             else {
                   echo "Error: " . $sql . "<br>" .
mysqli error($conn);
            mysqli close($conn);
      }
if(count($ POST)>0){
      if($ POST['type']==3){
             $id=$ POST['id'];
             $sql = "DELETE FROM `crud` WHERE id=$id ";
```

```
if (mysqli_query($conn, $sql)) {
                    echo $id;
             }
             else {
                    echo "Error: " . $sql . " <br>" .
mysqli error($conn);
             mysqli close($conn);
}
if (count ($ POST) > 0) {
      if($ POST['type']==4){
             $id=$ POST['id'];
             $sql = "DELETE FROM crud WHERE id in ($id)";
             if (mysqli query($conn, $sql)) {
                    echo $id;
             }
             else {
                    echo "Error: " . $sql . "<br>" .
mysqli error($conn);
             mysqli_close($conn);
      }
}
?>
```