

# AWS Config

## Step 1 Setting up the Configuration Recorder

### Introduction

To begin using AWS Config, you must first set up the configuration recorder. You tell the configuration recorder what resource configurations to record and where to record configuration items (CIs) in AWS Simple Storage Service (S3) and through AWS Simple Notification Service (SNS). This lab won't focus on S3 or SNS, but it is a requirement to set up an S3 bucket to use AWS Config. AWS Config also uses an Identity and Access Management (IAM) role to enable the service to record configurations.

### Instructions

1. In the AWS Management Console, navigate to AWS Config by clicking on **Config** under **Management Tools** in the Service drop down menu:



#### Management Tools

CloudWatch

CloudFormation

CloudTrail

Config

OpsWorks

Service Catalog

Trusted Advisor

Managed Services

2. Click on **Get Started** when presented with the AWS Config welcome page:



# AWS Config

AWS Config provides an inventory of your AWS resources and a history of configuration changes to these resources. You can use AWS Config to define rules that evaluate these configurations for compliance.

[Get started](#)

This will directly take to you to the configuration recorder setup form.

3. Enter the following commands into the **Settings** form:

- **Resource types to record**
  - **Record all resources supported in this region:** *Unchecked*
  - **Specific Types:** *EC2: SecurityGroup* (select SecurityGroup from the drop-down menu)
- **Amazon S3 bucket**
  - **Create a bucket:** *Selected*
  - **Bucket name:** Leave the default value (it will be something like config-bucket-123456789012, changing this will mean you won't have access to the created bucket)
- **Amazon SNS**
  - **Stream configuration changes and notifications to an Amazon SNS topic:** *Unchecked*
- **AWS Config role**
  - **Choose a role from your account:** *Selected*
  - **Role name:** *config-role-us-west-2*
  - **Use the role as is:** *Checked*

## Set up AWS Config

### | Step 1: Settings

Step 2: Rules

Step 3: Review

## Resource types to

Select the types of AWS resources you want to monitor. You can also choose to record configuration changes for the selected resource types.

### All resources

### Specific types

## Amazon S3 buckets

Your bucket receives configuration changes for the following resource types:

- ☒ Create a bucket
- ☐ Choose a bucket
- ☐ Choose a bucket

**Bucket name\***

Choose a bucket name

4. Once you have verified the values are correct, click **Next**.

5. In the **Rules** step, click **Skip** at the bottom right of the page.

You will go through the AWS managed rules in a future Lab Step. There are more managed rules available after you initialize the configuration recorder than there are available now, before it is initialized.

6. In the **Review** step, verify there are 0 **Config rules** and only the **AWS::EC2::SecurityGroup Resource type** appears.

## AWS Config rules (0)

---

### Settings

---

**Resource types**

AWS::EC2::SecurityGroup

**Amazon S3 bucket**

config-bucket-123456789012

**AWS Config role**

config-role-us-west-2

7. Click **Confirm** to start the configuration recorder.

## Summary

In this Lab Step, you configured the configuration recorder to record EC2 security group configurations. You created an S3 bucket to store AWS Config history files and snapshots.

## Step 2 Working with AWS Config Managed Rules


### Introduction

Now that the configuration recorder has started, you can start to enable Config Rules. In this Lab Step, you will use an AWS managed rule to quickly start checking compliance. There are many managed rules provided by AWS. You should be familiar with the managed rules that are available to you since they cover many common use cases. They also don't require custom development and maintenance on your part, which can't be said for custom rules. You will work with a managed rule that checks for specific tags being set on resources.

### Instructions

1. Select **Rules** in the AWS Config navigation panel on the left.

2. Click **Add rule**:



You will be presented with a list of AWS managed rules. Take a moment to see the types of rules available in the list.

3. In the **Filter by rule name, label or description** box highlighted in the image below, enter *required-tags*

## Add rule

Add rules to define the desired configuration settings of your AWS resources. Customize any of the following rules to suit your needs, or add a custom rule. To add a custom rule, you must create an AWS Lambda function for the rule.

+ Add custom rule

Filter by rule name, label or description

« < Viewing 1 - 9 of 32 AWS managed rules > »

### acm-certificate-expiration-check

Checks whether ACM Certificates in your account are marked for expiration within the specified number of days. Certificates provided by ACM are automatically renewed.

ACM

### approved-amis-by-id

Checks whether running instances are using specified AMIs. Specify a list of approved AMI IDs. Running instances with AMIs that are not on this list are noncompliant.

EC2

### approved-amis-by-tag

Checks whether running instances are using specified AMIs. Specify the tags that identify the AMIs. Running instances with AMIs that don't have at least one of the specified tags

EC2

### cloudtrail-enabled

Checks whether AWS CloudTrail is enabled in your AWS account. Optionally, you can specify which S3 bucket, SNS topic, and Amazon CloudWatch Logs ARN to use.

CloudTrail . Periodic

### db-instance-backup-enabled

Checks whether RDS DB instances have backups enabled. Optionally, the rule checks the backup retention period and the backup window.

RDS

### desired-instance-tenancy

Checks instances for specified tenancy. Specify AMI IDs to check instances that are launched from those AMIs or specify Host IDs to check whether instances are launched on

EC2

### desired-instance-type

Checks whether your EC2 instances are of the specified instance types.

EC2

### dynamodb-throughput-limit-check

Checks whether provisioned DynamoDB throughput is approaching the maximum limit for your account. By default, the rule checks if provisioned throughput exceeds a threshold of

DynamoDb . Periodic

### ebs-optimized-instance

Checks whether EBS optimization is enabled for your EC2 instances that can be EBS-optimized.

EC2

5. Click on the **required-tags** rule card:

### required-tags

Checks whether your resources have the tags that you specify. For example, you can check whether your EC2 instances have the 'CostCenter' tag. Separate multiple values

AWS

The **required-tags** rule can check that resources have specific tags that you require. For this lab, imagine you are building out a blue-green deployment environment. Blue-green deployments

maintain two copies of the deployment environment, a blue environment and a green environment. As part of governing your environments, you require all resources to have a Deployment tag that identifies if it is part of the blue environment or the green environment.

6. In the **Add AWS managed rule** form, keep the default values for **Name**, **Description**, **Scope of changes** and the **Triggers** section:

# Add AWS managed rule

AWS Config evaluates your AWS resources against this rule when it is triggered.

Name\*

required-tags

A unique name for the rule. 64 characters max. No special characters or spaces.

Description

Checks whether your resources have the tags that you specify. For example, you can check whether your EC2 instances have the 'CostCenter' tag. Separate multiple

Managed rule name

REQUIRED\_TAGS



## Trigger

AWS Config evaluates resources when the trigger occurs.

Trigger type\*



Configuration changes



Periodic



Scope of changes\*



Resources



Tags



All changes



Resources\*

EC2: CustomerGateway ×

EC2: Instance ×

EC2: InternetGateway ×

EC2: NetworkAcl ×

EC2: NetworkInterface ×

EC2: RouteTable ×

EC2: SecurityGroup ×

EC2: Subnet ×

EC2: Volume ×

EC2: VPC ×

EC2: VPNConnection ×

EC2: VPNGateway ×

ACM: Certificate ×

RDS: DBInstance ×

RDS: DBSecurityGroup ×

RDS: DBSnapshot ×

RDS: DBSubnetGroup ×

RDS: EventSubscription ×

S3: Bucket ×





Notice that the **Trigger type** is set to **Configuration changes**. This means the rule will evaluate any time the configuration recorder records a new configuration. The **Resources** list contains all the types supported. You can leave all the resources in the list. It won't hurt to have all of them even though the configuration recorder is only recording security group configuration changes.

7. In the **Rule parameters** section at the bottom of the form, enter:

- **tag1Key:** *Deployment*
- **tag1Value:** *Blue, Green*

### Rule parameters

Rule parameters define attributes for which your resources are evaluated; for example, a required tag or S3 bucket.

Key		Value
<input type="text" value="tag1Key"/>		<input type="text" value="Deployment"/>
<input type="text" value="tag1Value"/>		<input type="text" value="Blue, Green"/>

The key is required, while the value(s) is optional. When the value is specified, the tag must have one of the specified values. Multiple values are separated by commas. If no value is specified, the rule only checks if the tag is set with no specific criteria for the tag value.

8. Click **Save** to create the rule and have AWS Config automatically start evaluating the rule on the Resources.

It can take a minute for the evaluation to complete.

## Summary

In this Lab Step, you set up an AWS Config managed rule. The rule checks resource compliance when using a specific tag and allowable values. This type of rule can be useful for many scenarios including the deployment governance scenario utilized in this lab.

## Step 3 Analyzing and Remediating a Noncompliant Resource

### Introduction

Recall that the configuration recorder is recording only security group configurations. The security group is not compliant with the managed rule you previously set up. In this Lab Step, you will learn to analyze noncompliant resources using AWS Config and use its integration with CloudTrail to review associated API calls. After analyzing, you will adjust the security group configuration and verify it is compliant.

## Instructions

1. On the AWS Config **Rules** page, observe that it found **1 noncompliant resource** after rule evaluation:

Rules			Status ?
Rules represent your desired configuration settings. AWS Config evaluates whether your resource configurations comply with relevant rules and summarizes the results in the following table.			
<a href="#">Add rule</a>			
Rule name	Compliance	Edit rule	
<a href="#">required-tags</a>	1 noncompliant resource(s)		

*Note:* You can click the refresh button on the right hand side until you see the noncompliant resource. The managed rule can take about a minute to finish evaluating.

2. Click on **required-tags** in the **Rule name** column.

This will open the rule details view for the **required-tags** rule. In the top section, you will see all of the settings you configured when adding the rule.


3. Scroll down to the **Resources evaluated** section:

Resources evaluated					
Click on the  icon to view configuration details for the resource when it was last evaluated with this rule.					
Resource type	Config timeline	Compliance	Last successful invocation	Last successful evaluation	Manage resource
EC2 SecurityGroup	sg-82753cf9	Noncompliant	May 23, 2017 12:58:15 PM	May 23, 2017 12:58:15 PM	

Here you will find a summary of all the resources evaluated against your rules. You will see it evaluated an **EC2 Security Group** and it is **Noncompliant** with your rules.

4. Click on the **Noncompliant** security group name under the **Config timeline** to open the Config timeline.

5. Click on the timeline box that shows some Events below the date:



The screenshot displays the AWS Config console interface for an EC2 SecurityGroup. At the top, the resource is identified as "EC2 SecurityGroup sg-872fd6e1" with a timestamp "on May 26, 2017 2:18:25 PM Pacific Standard Time (UTC-08:00)". A "Manage resource" button is visible. Below this is a timeline visualization with several gray boxes representing events. The selected event is highlighted in blue, showing the date "26<sup>th</sup> May 2017" and time "2:18:25 PM". To the right of the timeline are "Now" and "Calendar" buttons. Below the timeline, the "Configuration Details" section is expanded, showing a table of resource attributes.

Configuration Details	
Amazon Resource Name	arn:aws:ec2:us-west-2:649853194954:security-group/sg-872fd6e1
Resource type	AWS::EC2::SecurityGroup
Resource ID	sg-872fd6e1
Availability zone	Not Applicable
Created on	null
Tags (0)	
Group name	default
Group description	default VPC security group

*Note:* You can periodically click on the **Now** button to refresh the timeline in case you don't see any **Events** under the configuration item in the timeline.

The Config timeline presents configuration changes over time. The **Configuration Details** section summarizes the configuration. You will see important configuration details for the resource configuration at the time selected in the timeline. Notice the Tags don't include a Deployment tag. The missing Deployment tag is currently causing the noncompliance.

6. Click on **View Details** on the far right of **Configuration Details**.


This will open the full configuration. There are many details here that are not in the summary. For example, scroll down and see that the **ipPermissions** that specify the security group ingress and egress permissions are visible.

7. Click **Close** to return the the Config timeline page.

8. Scroll down and expand the **Relationships** section by clicking on the triangle to the left of it:

▼ Relationships 1




**EC2 VPC**

vpc-144d7373 

Here you will find all of the resources related to the security group that AWS Config found. In the case of your security group, the resource is a VPC. This summary is very useful for getting a quick overview of how a resource fits into your cloud environment.

9. Expand the **CloudTrail Events** section at the bottom:

▼ CloudTrail Events 3

Event time	User name	Event name	View event
May 26, 2017 at 2:15:39 PM	cloudacademylab-FixSecurityGroup-WE2U4A5UO2KN	AuthorizeSecurityGroupIngress	 CloudTrail
May 26, 2017 at 2:15:39 PM	cloudacademylab-FixSecurityGroup-WE2U4A5UO2KN	AuthorizeSecurityGroupIngress	 CloudTrail
May 26, 2017 at 2:15:39 PM	cloudacademylab-FixSecurityGroup-WE2U4A5UO2KN	AuthorizeSecurityGroupIngress	 CloudTrail



The lab environment enabled CloudTrail as part of the lab startup routine so you can view the CloudTrail events related to resource configurations within AWS Config. You can see when events happened, what user performed them, and what the name of the event is. There is also a link to view the event in CloudTrail. This can be useful for seeing the event in relation to events impacting other resources.

10. As an example, click on the **CloudTrail** link next to an **AuthorizeSecurityGroupIngress** event:

## API activity history

The following list includes the last 7 days of API activity for [supported services](#). The list only includes API activity for **create**, **modify**, and **delete** API calls. For read-only API activity, go to your Amazon S3 bucket or CloudWatch Logs.


You can filter the list using the available attributes, and you can choose an event to see more detail about the event. [Learn more](#).



Filter: **Event ID**

27827550-82dd-469f-804a-cefd...

Time range:



Event time	User name	Event name	Resource type	Resource name
2017-05-26, 02:15:39 PM	cloudacademylab-FixSecuri...	AuthorizeSecurityGroupIng...	EC2 SecurityGroup	sg-872fd6e1

**AWS access key** ASIAIABCD0000MYKEYQ

**AWS region** us-west-2

**Error code**

**Event ID** 27827550-82dd-469f-804a-cefd4ac4ed9e

**Event name** AuthorizeSecurityGroupIngress

**Event source** ec2.amazonaws.com


**Event time** 2017-05-26, 02:15:39 PM

**Request ID** de6562cb-0266-47ad-a1eb-bfbe50c3a315

**Source IP address** 123.123.123.123

**User name** cloudacademylab-FixSecurityGroup-WE2U4A5UO2KN

Resources Referenced (1)

Resource type	Resource name	Config timeline
EC2 SecurityGroup	<a href="#">sg-872fd6e1</a>	

[View event](#)

From this view inside CloudTrail, you can see more detailed information about the event. For example, the **Source IP address** of the API request. Even more details about the identity of the user are available if you click the **View event** button in the bottom right corner.

You could also filter the **API Activity history** to show events that happened before this event as a technique for analyzing the sequence of events. Since CloudTrail records all API activity, you can gain more perspective around the event in Cloudtrail. This is in contrast to the timeline view in AWS Config which only shows the events related to one resource. Lastly, note that when AWS Config is enabled, CloudTrail provides a link back to Config under the Config timeline column. This shows that AWS Config also integrates nicely into CloudTrail.

11. Return to the AWS Config browser tab, scroll to the top and click **Manage resource**.

This is a quick way to go to the Management Console page for configuring the resource.

12. On the **Tags** tab, click the **Add/Edit Tags** button.

13. In the Add/Edit Tags dialog, click **Create Tag** and enter the following values:

- **Key:** *Deployment*

- **Value:** *Green*

## Add/Edit Tags ✕

Apply tags to your resources to help organize and identify them.

A tag consists of a case-sensitive key-value pair. For example, you could define a tag with key = Name and value = Webserver. [Learn more](#) about tagging your Amazon EC2 resources.

Key	Value	
Deployment	Green	✕

Create Tag
Cancel
Save

This tag makes the security group compliant with the managed rule you enabled.

14. Click **Save** and return to the AWS Config timeline browser tab.

15. Click on the **Now** until you see a new configuration item in the timeline:



*Note:* It can take up to 10 minutes for the configuration change to be recorded. You may want to read ahead in the lab and return to this step after several minutes

Notice the new item has a **Change** and an **Event**. The **Configuration Details** also include the **Deployment:Green** tag now.

16. Expand the **Changes** and **CloudTrail Events**:

▼ Changes **1**

Configuration Changes **1**

Field	From	To
Configuration.Tags.0		Object key: "Deployment" value: "Green"

Relationship Changes **0**

▼ CloudTrail Events **1**

Event time	User name	Event name	View event
May 23, 2017 at 10:20:46 PM	student	CreateTags	<a href="#">CloudTrail</a>

In the **Changes** section, AWS Config tells you what changed from the most previously recorded configuration. In this case, it tells you the Deployment: Green tag was added in the **Configuration Changes**. There were no **Relationship Changes** this time, but AWS Config also records those changes.

In the **CloudTrail Events**, the **CreateTags** event is logged by the **student** user.

17. Return to the **Rules** page by navigating to **Services > Management Tools > Config > Rules**:

AWS Config

Rules

Resources

Settings

Rules

Status ⓘ

Rules represent your desired configuration settings. AWS Config evaluates whether your resource configurations comply with relevant rules and summarizes the results in the following table.

Add rule

Rule name	Compliance	Edit rule
required-tags	Compliant	

The **Compliance** column value reads **Compliant**, verifying the rule is in compliance after the security group configuration change.

## Summary

In this Lab Step, you enabled an AWS Config managed rule. In analyzing a noncompliant resource, you saw how AWS Config integrates with CloudTrail to combine the benefits of both services. For practical experience, you also resolved a noncompliant configuration and observed how AWS Config reports changes in the timeline.

## Step 4 Working with AWS Config Custom Rules

### Introduction

AWS Config custom rules can be used for a wide variety of scenarios when AWS managed rules don't fit your use case. Custom rules rely on an AWS Lambda function to evaluate resource configuration. You will be exposed to how to create a custom rule using pre-written code for a Lambda function. For demonstration purposes, the code simply evaluates whether an RDP tcp port is open to incoming traffic. You will check and correct noncompliance using the custom rule in this Lab Step.

*Note:* There is a managed rule that can achieve a similar result. The rule's name is *restricted-common-ports*. You should use that managed rule if you need to block the RDP port. The custom rule in the Lab Step is for demonstration purposes only, allowing you to get familiar with the process of working with custom rules.

### Instructions

1. From the AWS Config **Rules** page, click **Add rule**.
2. Click **Add custom rule** below the **Add rule** heading:



AWS Config

**Rules**

Resources

Settings

Rules > Add rule

## Add rule

Add rules to define the desired state of your AWS resources. To create a custom rule, you must create a Lambda function.

**+ Add custom rule**

3. Click **Create AWS Lambda function**:

## Add custom rule

AWS Config evaluates your AWS resources against this rule when it is triggered.

**Name\***

A unique name for the rule. 64 characters max. No special characters or spaces.

**Description**

**AWS Lambda function ARN\***

[Create AWS Lambda function](#)

AWS Config will gain permission to invoke the function by updating the function's access policy.

This takes you directly to the AWS Lambda new function wizard to create the function that will evaluate your custom rule.

4. In the **Basic Information** section, enter the following:

- **Name:** *evaluate-port-ingress* (Important to enter exactly as written or the Lambda function will fail to create)
- **Role:** *Choose an existing role*
- **Existing role:** *config-lambda-role*

The config-lambda-role was created for you during the lab startup. It authorizes Lambda to describe security groups (`ec2.describeSecurityGroups`) and put evaluations into AWS Config (`config.putEvaluations`).

Click **Create Function**

5. In the **Lambda function code** section, leave the **Code entry type** as **Edit code inline** and paste in the following JavaScript code block that targets Node.js:

```
//  
// Ensure a security group does not allow tcp ingress on a specified port  
//  
  
var aws = require('aws-sdk');  
var config = new aws.ConfigService();  
  
// Helper function used to validate input  
function checkDefined(reference, referenceName) {  
  if (!reference) {  
    console.log("Error: " + referenceName + " is not defined");  
    throw referenceName;  
  }  
  return reference;  
}  
  
// Check whether the resource has been deleted. If it has, then the  
// evaluation is unnecessary.  
function isApplicable(configurationItem, event) {  
  checkDefined(configurationItem, "configurationItem");  
  checkDefined(event, "event");  
  var status = configurationItem.configurationItemStatus;  
  var eventLeftScope = event.eventLeftScope;  
  return ('OK' === status || 'ResourceDiscovered' === status) && false ===  
  eventLeftScope;  
}  
  
function createPutEvaluationsRequest(event, configurationItem, compliance) {  
  var putEvaluationsRequest = {};  
  
  // Put together the request that reports the evaluation status  
  putEvaluationsRequest.Evaluations = [
```

```

        {
            ComplianceResourceType: configurationItem.resourceType,
            ComplianceResourceId: configurationItem.resourceId,
            ComplianceType: compliance,
            OrderingTimestamp: configurationItem.configurationItemCaptureTime
        }
    ];
    putEvaluationsRequest.ResultToken = event.resultToken;
    putEvaluationsRequest.TestMode = false;

    return putEvaluationsRequest;
}

function putEvaluations(callback, putEvaluationsRequest) {
    // Invoke the Config API to report the result of the evaluation
    config.putEvaluations(putEvaluationsRequest, function (err, data) {
        if (err) {
            callback(err);
        } else {
            callback(null, "success");
        }
    });
}

// This is the handler that's invoked by Lambda
exports.handler = function (event, context, callback) {
    event = checkDefined(event, "event");
    var invokingEvent = JSON.parse(event.invokingEvent);
    var ruleParameters = JSON.parse(event.ruleParameters);
    var configurationItem = checkDefined(invokingEvent.configurationItem,
"invokingEvent.configurationItem");
    var compliance = 'NOT_APPLICABLE';
    var putEvaluationsRequest = {};

    if (isApplicable(configurationItem, event)) {
        checkDefined(configurationItem, "configurationItem");
        checkDefined(configurationItem.configuration,
"configurationItem.configuration");
        checkDefined(ruleParameters, "ruleParameters");

        // This is where it is determined whether the resource is compliant or
        not.
        // In this example, we look at the IP permissions of the EC2 security
        group and determine
        // if it allows ingress traffic on a specified TCP port. If the port is
        open, the
        // security group is marked non-compliant. Otherwise, it is marked
        compliant.
        if ('AWS::EC2::SecurityGroup' !== configurationItem.resourceType) {
            putEvaluationsRequest = createPutEvaluationsRequest(event,
configurationItem, compliance);
            putEvaluations(callback, putEvaluationsRequest);
        } else {
            groupId = configurationItem.configuration.groupId;

            var ec2 = new aws.EC2({ apiVersion: '2016-11-15' });
            var params = {

```

```

        DryRun: false,
        GroupIds: [
            groupId
        ]
    };
    ec2.describeSecurityGroups(params, function (err, data) {
        var compliance = 'COMPLIANT';
        if (err) {
            compliance = 'NON_COMPLIANT';
        } else {
            var ipPermissions = data.SecurityGroups[0].IpPermissions;
            for (var i = 0; i < ipPermissions.length; i++) {
                var ipPermission = ipPermissions[i];
                // The actual test condition (allows default allow all rule
                (IpProtocol === '-1') to be compliant for demonstration purposes)
                if (ipPermission.IpProtocol === 'tcp'
                    && ipPermission.FromPort >= ruleParameters.port
                    && ipPermission.ToPort <= ruleParameters.port) {
                    compliance = 'NON_COMPLIANT';
                    break;
                }
            }
        }
        putEvaluationsRequest = createPutEvaluationsRequest(event,
            configurationItem, compliance);
        putEvaluations(callback, putEvaluationsRequest);
    });
}
} else {
    putEvaluationsRequest = createPutEvaluationsRequest(event,
        configurationItem, compliance);
    putEvaluations(callback, putEvaluationsRequest);
}
};

```


*Note:* It is not important to understand the code. All you need to know is that the code checks whether a security group allows inbound traffic on a specified TCP port. It makes use of the AWS SDK to access AWS Config and EC2. It is possible to modify the Lambda function so that it automatically enforces compliance by modifying the security group. This is left as an exercise to the student.

6. In the **Basic Settings** frame, set the following values:

- **Memory (MB):** 128 (default value)
- **Timeout:** 0 min 30 sec
- Default values for the rest

This allows the Lambda function 30 seconds and 128MB of peak memory to complete evaluation. This is more than enough for the simple check performed by the code.

7. Copy the Lambda function's **ARN** in the upper right corner:



The screenshot shows a section of the AWS Lambda console. At the top, the ARN is displayed: **ARN - arn:aws:lambda:us-west-2:753004491394:function:evalute-port-ingress**. Below this, there are four buttons: **Actions** with a dropdown arrow, **Select a test event..** with a dropdown arrow, **Test**, and **Save**.

8. Return to the AWS Config **Add custom rule** browser tab and enter the following (paste the **AWS Lambda function ARN** first while it's in your clipboard):

- **Name:** *disallow-rdp-ingress*
- **Description:** *Check security groups for allowing incoming RDP TCP traffic. Disallow the traffic to become compliant.*
- **AWS Lambda function ARN:** Paste the ARN copied from the AWS Lambda function page
- **Trigger**
  - **Trigger type:** *Configuration changes*
  - **Scope of changes:** *Resources*
  - **Resources:** *EC2: SecurityGroup*
- **Rule parameters**
  - **Key:** *port* (lower-case)
  - **Value:** *3389*

RDP traffic is over tcp port 3389 by default. There are ways to get RDP traffic around this rule, but it is only for demonstration purposes. **Rule parameters** are a way to make your custom rules generalizable. The same rule could be used to block any desired port using different settings of the **Rule parameters**. If you are curious about the code, the values set for **Rule parameters** correspond to `ruleParameters` in the code above.

9. Click **Save**.

Your custom rule will automatically begin evaluating.

10. After a minute, click the refresh button on the right side of the **Rules** section:

## Rules

Status ?

Rules represent your desired configuration settings. AWS Config evaluates whether your resource configurations comply with relevant rules and summarizes the results in the following table.

<a href="#">+ Add rule</a>			
Rule name	Compliance	Edit rule	
<a href="#">disallow-rdp-ingress</a>	1 noncompliant resource(s)		
<a href="#">required-tags</a>	Compliant		

You will see the rule reports that there is **1 noncompliant resource**. You will now investigate and enforce compliance.

11. Click on **disallow-rdp-ingress** in the **Rules** table.

12. Open the **Manage resource** link for the for the **Noncompliant** security group.

13. Select the **Inbound** tab.

Notice the security group is allowing incoming RDP traffic. That is causing the noncompliance.

14. Click the **Edit** button:

sg-872fd6e1

default

vpc-aa52d2ce

default VPC security group

Security Group: sg-872fd6e1

Description

Inbound

Outbound

Tags

Edit

Type ⓘ	Protocol ⓘ	Port Range ⓘ	Source ⓘ
HTTP	TCP	80	0.0.0.0/0
RDP	TCP	3389	0.0.0.0/0
HTTPS	TCP	443	0.0.0.0/0

15. Click on the **x** on the right side of the **RDP** row:

**Edit inbound rules** ✕

Type ⓘ	Protocol ⓘ	Port Range ⓘ	Source ⓘ	
HTTP ▾	TCP	80	Custom ▾ 0.0.0.0/0	✕
<b>RDP</b> ▾	TCP	3389	Custom ▾ 0.0.0.0/0	<b>✕</b>
HTTPS ▾	TCP	443	Custom ▾ 0.0.0.0/0	✕

Add Rule

NOTE: Any edits made on existing rules will result in the edited rule being deleted and a new rule created with the new details. This will cause traffic that depends on that rule to be dropped for a very brief period of time until the new rule can be created.


Cancel Save



16. Click **Save**.

17. Navigate back to **Service > Management Tools > Config > Rules** and click on **disallow-rdp-ingress**.

The rule is configured to evaluate on configuration changes. After a few minutes the configuration change will be recorded and by refreshing the page, you will see the security group has changed to the **Compliant** state:

#### Resources evaluated

Click on the  icon to view configuration details for the resource when it was last evaluated with this rule.

Resource type ▾	Config timeline  ▾	Compliance ▾	Last successful invocation ▾	Last successful evaluation ▾	Manage resource
EC2 SecurityGroup	<a href="#">sg-82753cf9</a>	Compliant	May 25, 2017 1:58:21 PM	May 25, 2017 1:58:21 PM	

*Note:* You can click on the **Re-evaluate** button further down the page to check the rule immediately. This will allow the **Compliance** state to be updated, but it won't speed up the time it takes for configuration items to be recorded in the next instruction. This is because the code above directly queries the security group instead of depending on a configuration item.

18. Click on the security group name under the **Config timeline**:

▼ Changes **1**

Configuration Changes **1**

Field	From	To
Configuration.IpPermissions.0	<pre>Object ipProtocol: "tcp" fromPort: 3389 toPort: 3389 userIdGroupPairs: Array [0] [] ipv6Ranges: Array [0] [] prefixListIds: Array [0] [] ipv4Ranges: Array [1]   0: Object     cidrIp: "0.0.0.0/0"   ipRanges: Array [1]     0: "0.0.0.0/0"</pre>	

Relationship Changes **0**

▼ CloudTrail Events **1**

Event time	User name	Event name	View event
May 25, 2017 at 1:18:57 PM	student	RevokeSecurityGroupIngress	<a href="#">CloudTrail</a>

You can see the **Configuration Changes** section recorded the removal of the RDP IpPermission (ingress rule). Further down under **CloudTrail Events**, the **RevokeSecurityGroupIngress** event that triggered the change has been recorded in CloudTrail and linked to by Config.

## Summary

In this Lab Step, you created a custom rule for AWS Config. The rule used a lambda function that detects if a security group is allowing incoming tcp traffic over the default RDP port. You also got more practice investigating noncompliant resources and modifying configurations to bring about compliance.