

# Constraints Movie-Ratings Exercises

You will enhance the movie-ratings database that was also used for the SQL Movie-Ratings Query Exercises. In this set of exercises you will declare integrity constraints on the data, and you will verify that they are being enforced by the underlying database management system. You will experiment with several types of constraints: *key constraints*, *non-null constraints*, *attribute-based* and *tuple-based check constraints*, and *referential integrity*. A SQL file to set up the original schema and data for the movie-ratings database is downloadable from the Dropbox link. You will be using the same data, but modifying the schema to add constraints.

## Schema:

Movie ( mID, title, year, director )

English: There is a movie with ID number *mID*, a *title*, a release *year*, and a *director*.

Reviewer ( rID, name )

English: The reviewer with ID number *rID* has a certain *name*.

Rating ( rID, mID, stars, ratingDate )

English: The reviewer *rID* gave the movie *mID* a number of *stars* rating (1-5) on a certain *ratingDate*.

Unlike most of our other exercises, which are a set of queries to be written individually, this exercise set involves bigger chunks of work followed by a series of tests. If the constraints are implemented correctly, the tests will generate or not generate errors as specified. To verify that the referential integrity policies are implemented correctly, there is a check of the final database state.

## Task 1: Constraint Declarations

Modify the three CREATE TABLE statements in the [movie-rating database](#) to add the following ten constraints. (Note: You may want to examine the date format in the data file so you can specify date-related constraints as string comparisons.)

### Key Constraints

1. mID is a key for Movie
2. (title,year) is a key for Movie
3. rID is a key for Reviewer
4. (rID,mID,ratingDate) is a key for Rating but with null values allowed

### Non-Null Constraints

5. Reviewer.name may not be NULL

6. Rating.stars may not be NULL

### **Attribute-Based Check Constraints**

7. Movie.year must be after 1900
8. Rating.stars must be in {1,2,3,4,5}
9. Rating.ratingDate must be after 2000

### **Tuple-Based Check Constraints**

10. "Steven Spielberg" movies must be before 1990 and "James Cameron" movies must be after 1990

### **Task 2: Load the Database**

After creating the three tables using your modified CREATE TABLE statements, you should be able to load the original data (i.e., execute all of the INSERT statements in the data file) without any errors.

### **Task 3: Constraint Enforcement**

*Each of the following commands should generate an error.*

11. update Movie set mID = mID + 1;
12. insert into Movie values (109, 'Titanic', 1997, 'JC');
13. insert into Reviewer values (201, 'Ted Codd');
14. update Rating set rID = 205, mID = 104;
15. insert into Reviewer values (209, null);
16. update Rating set stars = null where rID = 208;
17. update Movie set year = year - 40;
18. update Rating set stars = stars + 1;
19. insert into Rating values (201, 101, 1, '1999-01-01');
20. insert into Movie values (109, 'Jurassic Park', 1993, 'Steven Spielberg');
21. update Movie set year = year-10 where title = 'Titanic';

*None of the following commands should generate errors.*

22. insert into Movie values (109, 'Titanic', 2001, null);
23. update Rating set mID = 109;
24. update Movie set year = 1901 where director <> 'James Cameron';
25. update Rating set stars = stars - 1;

#### **Task 4: Referential Integrity Declarations**

Further modify one or more of your CREATE TABLE statements to include the following referential integrity constraints and policies.

26. Referential integrity from Rating.rID to Reviewer.rID  
Reviewers updated: cascade  
Reviewers deleted: set null  
All others: error
26. Referential integrity from Rating.mID to Movie.mID  
Movies deleted: cascade  
All others: error

#### **Task 5: Reload the Database**

Recreate the three tables using your modified CREATE TABLE statements. You should be able to load the original data (i.e., execute all of the INSERT statements in the data file) without any errors.

#### **Task 6: Referential Integrity Enforcement**

*Each of the following commands should generate an error.*

**Important Note: If using SQLite, make sure to turn on referential integrity checking with the command "pragma foreign\_keys = on;"**

27. insert into Rating values (209, 109, 3, '2001-01-01');
28. update Rating set rID = 209 where rID = 208;
29. update Rating set mID = mID + 1;

30. update Movie set mID = 109 where mID = 108;

*None of the following commands should generate errors, but they will make additional database modifications according to the referential-integrity policies.*

31. update Movie set mID = 109 where mID = 102;

32. update Reviewer set rID = rID + 10;

33. delete from Reviewer where rID > 215;

34. delete from Movie where mID < 105;