

```
<!DOCTYPE html>
<html lang="id">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Navbar dengan Tailwind CSS</title>
    <!-- Link ke CDN Tailwind CSS untuk menggunakan kelasnya -->
    <script src="https://cdn.tailwindcss.com"></script>
    <script>
        // Konfigurasi Tailwind untuk menambahkan warna kustom dan font
        tailwind.config = {
            theme: {
                extend: {
                    fontFamily: {
                        'inter': ['Inter', 'sans-serif'],
                    },
                    colors: {
                        // Warna-warna kustom yang digunakan dalam CSS asli
                        'custom-white': '#ffffff',
                        'custom-gray': '#e0e0e0',
                        'custom-dark-gray': '#333',
                        'custom-light-gray': '#ddd',
                        'custom-red': '#e63946',
                        'custom-light-gray-2': '#eee',
                        'custom-dark-gray-2': '#444',
                        'custom-green': 'green'
                    },
                }
            }
        }
    </script>
    <style>
        /* Menggunakan font Inter dari Google Fonts */
        @import url('https://fonts.googleapis.com/css2?family=Inter:wght@400;500;700;900&display=swap');

        /* Animasi sederhana untuk transisi menu */
        .nav-items-open {
            max-height: 500px;
            opacity: 1;
            visibility: visible;
        }
    </style>
</head>
<body class="font-inter bg-gray-50">

    <!-- ===== Navbar Container ===== -->
    <!--
        - flex: display:flex
        - items-center: align-items: center
        - justify-between: justify-content: space-between
        - py-1.5 px-2: padding: 6px 8px (menggunakan unit rem, 1 rem = 16px)
        - bg-white: background: #ffffff
        - border-b-2 border-gray-200: border-bottom: 2px solid #e0e0e0
        - sticky: position: sticky
        - top-0: menempel di bagian atas layar
        - z-10: z-index: 10
    -->
    <nav class="flex items-center justify-between py-1.5 px-2 bg-white border-b-2 border-custom-gray sticky top-0 z-10">
```

```

<!-- ===== Logo ===== -->
<!--
- text-2xl: font-size: 23px
- font-bold: font-weight: 700
- text-custom-dark-gray: color: #333
-->
<a href="#" class="text-2xl font-bold text-custom-dark-gray">Brand</a>

<!-- ===== Search ===== -->
<!--
- flex-1: flex: 1
- mx-1.5: margin: 0 5px
- max-md:hidden: display: none pada layar < 768px
-->
<div id="search-container" class="flex-1 mx-1.5 hidden md:block">
<!--
- w-full: width: 100%
- py-1 px-3: padding: 5px 12px
- border-2 border-custom-light-gray: border: 2px solid #ddd
- rounded-xl: border-radius: 12px
- text-sm: font-size: 14px
- outline-none: outline: none
-->
<input type="text" placeholder="Cari..." class="w-full py-1 px-3 border-2 border-custom-light-gray rounded-xl text-sm outline-none">
</div>

<!-- ===== Nav Items (Mobile) ===== -->
<!--
- flex-col: flex-direction: column
- absolute: position: absolute
- top-[55px]: top: 55px (tinggi navbar)
- right-0: right: 0
- w-1/2: width: 45% (diubah ke 50% atau w-1/2 untuk kemudahan, bisa diatur lagi)
- bg-white: background: #fff
- border-t-2 border-custom-light-gray-2: border-top: 1px solid #eee
- overflow-hidden: overflow: hidden
- opacity-0: opacity: 0
- invisible: visibility: hidden
- transition-all duration-300 ease-in-out: transisi lembut
- md:flex md:items-center md:static md:w-auto md:bg-transparent md:border-none md:visible md:opacity-100
md:ml-6 md:flex-row md:gap-0: kembali ke tampilan desktop
-->
<div id="nav-items" class="flex flex-col absolute top-[55px] right-0 w-1/2 bg-white border-t border-custom-light-gray-2 overflow-hidden opacity-0 invisible transition-all duration-300 ease-in-out md:flex md:items-center md:static md:w-auto md:bg-transparent md:border-none md:visible md:opacity-100 md:ml-6 md:flex-row md:gap-0">
    <a href="#" class="block text-custom-dark-gray font-medium py-3 px-12 border-b-2 border-custom-light-gray-2
    hover:text-custom-red hover:border-l-4 hover:border-custom-red hover:px-10 md:py-1.5 md:px-2 md:border-b-2
    md:hover:border-b-2 md:hover:border-custom-red md:border-none md:hover:border-l-0
    md:hover:text-custom-red">Beranda</a>
    <a href="#" class="block text-custom-dark-gray font-medium py-3 px-12 border-b-2 border-custom-light-gray-2
    hover:text-custom-red hover:border-l-4 hover:border-custom-red hover:px-10 md:py-1.5 md:px-2 md:border-b-2
    md:hover:border-b-2 md:hover:border-custom-red md:border-none md:hover:border-l-0
    md:hover:text-custom-red">Produk</a>
    <a href="#" class="block text-custom-dark-gray font-medium py-3 px-12 border-b-2 border-custom-light-gray-2
    hover:text-custom-red hover:border-l-4 hover:border-custom-red hover:px-10 md:py-1.5 md:px-2 md:border-b-2
    md:hover:border-b-2 md:hover:border-custom-red md:border-none md:hover:border-l-0
    md:hover:text-custom-red">Tentang</a>
</div>

```

```

<!-- ===== Actions ===== -->
<!--
- flex: display: flex
- items-center: align-items: center
- ml-5: margin-left: 20px
-->
<div class="flex items-center ml-5">
<!--
- text-3xl: font-size: 28px
- cursor-pointer: cursor: pointer
- text-custom-dark-gray-2: color: #444
- bg-transparent: background: none
- border-none: border: none
- mx-1.5: margin: 0 5px
-->
<button class="text-3xl cursor-pointer text-custom-dark-gray-2 bg-transparent border-none mx-1.5">≡ </button>
<button class="text-3xl cursor-pointer text-custom-dark-gray-2 bg-transparent border-none mx-1.5">👤 </button>

<!-- Hamburger Menu (Mobile) -->
<!--
- block: display: block
- md:hidden: display: none pada layar >= 768px
- pt-1.5: padding-top: 5px
-->
<button id="menu-toggle" class="block md:hidden pt-1.5 ml-1">
  <svg xmlns="http://www.w3.org/2000/svg" class="h-6 w-6 text-custom-dark-gray-2" fill="none" viewBox="0 0 24 24" stroke="currentColor">
    <path stroke-linecap="round" stroke-linejoin="round" stroke-width="2" d="M4 6h16M4 12h16m-7 6h7" />
  </svg>
</button>
</div>
</nav>

<!-- JavaScript untuk mengontrol menu toggle -->
<script>
  const menuToggle = document.getElementById('menu-toggle');
  const navItems = document.getElementById('nav-items');

  menuToggle.addEventListener('click', () => {
    // Toggle class untuk menampilkan/menyembunyikan menu
    navItems.classList.toggle('nav-items-open');
  });
</script>

</body>
</html>

```